

Document Version: V2026.1
Date of first issue: 2021.01.21
Date viewed: 2026.06.18

MULTIline FORCE uv

Product name	Lateral Repairs MULTIline FORCE UV
Product code	FORCEUV

Material composition

Polyester needle-punched fleece liner with filament reinforcement and a thermoplastic polyurethane (TPU) coating.

Supply data

Pipe diameter	100 mm - 600 mm / 4 inch - 24 inch Other dimensions available on request
Liner undersized	10 %
Liner lengths	50 m; 100 m / 164 feet; 328 feet Other lengths available on request

General data

Type of fibers	Polyester
Coating	TPU
Basic color	White
Color coating	Transparent
Type of basic material	Needle-punched fleece with filament
Used seam (stitched) and seam sealing	Stitched seam with PES-thread Seam sealed with TPU seam tape

Physical properties

Weight		g/m ²	500
Weight of coating	[Tracking force 20cN/cm ² bearing area 25 cm ²]	g/m ²	150
Thickness	± 3 %	mm inch	3,30 0,13
Water penetration resistance	ISO 811	mbar	≥ 500

Handling parameter

Heat resistance	Max. 80 °C / 176 °F
Negotiating bends up to	Max. 45°
Pinch roller gap (impregnation)	2 x Wall thickness + 2 mm
Additional lengths	2 %

The final quality depends on the resin system used, the inversion pressure and the curing pressure. We advise against the use of other resin systems or higher inversion and/or curing pressures and accept no liability.