

Document Version: V2026.1  
 Date of first issue: 2021.01.21  
 Date viewed: 2026.05.01

## MULTIline FLEX

|                     |                                      |
|---------------------|--------------------------------------|
| <b>Product name</b> | Lateral Repairs MULTIline FLEX 3.0mm |
| <b>Product code</b> | FLEX                                 |

|                             |                                                            |
|-----------------------------|------------------------------------------------------------|
| <b>Material composition</b> |                                                            |
|                             | PES-Plush (knitted) and brushed with one sided PU-Coating. |

|                    |                                                                                                        |
|--------------------|--------------------------------------------------------------------------------------------------------|
| <b>Supply data</b> |                                                                                                        |
| Pipe diameter      | 30, 40, 50, 60, 65, 70, 75, 80, 100, 125, 150, 200, 225, 250.<br>Other dimensions available on request |
| Liner undersized   | 5 %, 9 %, 18 %                                                                                         |
| Liner lengths      | 50 m; 100 m / 164 feet; 328 feet<br>Other lengths available on request                                 |

|                                       |                                                           |
|---------------------------------------|-----------------------------------------------------------|
| <b>General data</b>                   |                                                           |
| Type of fibers                        | Polyester                                                 |
| Coating                               | One side PU                                               |
| Basic color                           | White                                                     |
| Color coating                         | Transparent                                               |
| Type of basic material                | PES-Plush (knitted)                                       |
| Used seam (stitched) and seam sealing | Stitched seam with PES-Yarn<br>Seam sealed with a PU-Tape |

|                                                 |                                 |                  |                 |
|-------------------------------------------------|---------------------------------|------------------|-----------------|
| <b>Physical properties</b>                      |                                 |                  |                 |
| Weight                                          | DIN EN 12127                    | g/m <sup>2</sup> | 450*            |
| Weight of coating                               |                                 | g/m <sup>2</sup> | 250*            |
| Thickness                                       | (Simulating 0.5 bar / 7.25 psi) | mm<br>inch       | 3,00*<br>0,12*  |
| Water penetration resistance<br>(20 °C / 68 °F) | ISO 811                         | Mbar<br>psi      | ≤ 500<br>≤ 7,25 |

Document Version: V2026.1  
Date of first issue: 2021.01.21  
Date viewed: 2026.05.01

# MULTIline FLEX

| Handling parameter              |                           |
|---------------------------------|---------------------------|
| Heat resistance                 | Max. 50 °C / 122 °F       |
| Negotiating bends up to         | 90°                       |
| Pinch roller gap (impregnation) | 2 x Wall thickness + 2 mm |
| Additional lengths              | 5 %                       |

The final quality depends on the resin system used, the inversion pressure and the curing pressure. We advise against the use of other resin systems or higher inversion and/or curing pressures and accept no liability.

\* = Modal value (typical value)

Additional Information – please see “methods of application”.

\* STEAM CURING IS ONLY POSSIBLE WITH A CALIBRATION HOSE.