The Feature Lab: Keep, Fix, or Toss?

A city's police department wants to predict how long it will take an officer to arrive after a 911 call is dispatched. Each row in the dataset is one call. Using the data dictionary below, decide whether to **keep**, **fix**, or **toss** each feature, and explain why.

Column	Type	Description	Example
call_id	Text	Unique ID assigned to each 911 call	CAD-2026-0048213
dispatch_timestamp	Text	Date and time an officer was dispatched	2026-03-14 02:47:13
officer_arrival_time	Text	Date and time the first officer arrived on scene	2026-03-14 02:55:40
call_address	Text	Street address where the call came from. About 45,000 unique addresses.	1820 Linden Ave
distance_from_station_feet	Numeric	Straight-line distance from the call location to the nearest police station, in feet (0 to 50,000)	18,450
officers_on_duty	Numeric	Number of officers on patrol citywide at the time of dispatch (5 to 40)	22
weather_condition	Categorical	Weather at the time of the call: clear, rain, snow, or fog. Blank for about 30% of calls.	rain
call_priority	Ordinal	Urgency assigned by the dispatcher, from 1 (life-threatening emergency) to 5 (routine)	2
case_closed_flag	Binary	1 if the incident report has been finalized and the case closed, 0 otherwise	1
response_time_min	Numeric	**Target.** Minutes from dispatch to first officer arrival	8.45

For each feature, decide whether to keep, fix, or toss it. Assume the model is a linear regression.

1. call_id

2. dispatch_timestamp

3. officer_arrival_time

4. call_address

5. distance_from_station_feet and officers_on_duty

6. weather_condition

7. call_priority

8. case_closed_flag