


Deep Neural Networks for Image Classification: Architectures, Approaches, and Advice

Kyle Kastner
University of Texas - San Antonio


Previously, on FOX...

- Datasets
 - CIFAR-10
 - Asirra subset
- Partial success
 - CIFAR10 was good
 - Did not generalize
- Better preprocessing
- New advances
- Now... a recap



Techniques

- Zero phase components (ZCA) preprocessing
- Global Contrast Normalization (GCN)
- Flip randomly during training
- Trained by SGD
- Convolutional units
- Maxout units
- Dropout
- Softmax classification



<http://kastnerkyle.github.io>


Preprocessing

- ZCA mimics the processing of the human visual system
- Similar concept to Principle Component Analysis (PCA)
- Typically used only for images
- **Bell A.J. and Sejnowski T.J. 1996.** *The 'Independent Components' of natural scenes are edge filters*

$$W = (XX^T)^{\frac{1}{2}} = ED^{\frac{1}{2}}E^T$$
$$X_w = XW$$


Convolutional Units

- Inspired by research on cat visual cortex
- Used to exploit correlation in input
- Designed for vision tasks



Dropout

- Randomly drop ~50% of input
- Typically keep 80% in first layer
- Equivalent to training many nets
- Very strong regularizer
- Limit weight adaptation
- Typically ReLU or Maxout units



Maxout

- Uses localized “max” units
- Shown to be an approximator for many functions
- Designed to be used in conjunction with dropout






Fig. 1. Maxout architectures in this paper: (a) maxout layer with the group size of 3; (b) maxout autoencoder; (c) sparse feature extractor.

First Experiment

- CIFAR10 dataset
- Standard benchmark for vision
- Replicate performance
- Planned to extend for Asirra
- Results: **88.9%** accuracy
- Similar:
 - CIFAR100
 - ImageNet, STL-10





Results from CIFAR10 Training


Failed Extension

- Image bas
- Developed by
- Kaggle Dogs vs. Cats
- SOTA: **96%**
- Best accu
- This is **BAD!**



Successful Approach

- Transfer learning
- Trained for ImageNet
 - 1000 classes!
- Cut off softmax layer
- Forward propagate new data
- Use output as new features




DeCAF

- Used for preprocessing
- Details here:
 - <http://decaf.no-ip.org/>
- Newer, better version
 - Caffe
 - <http://daggerfs.com/caffe/>
- ImageNet
 - 120 GB labeled images
 - 1.2 TB total images
 - <http://www.image-net.org>




Results

- Tried several classifiers
 - Logistic Regression: **94.6%**
 - Linear SVM: **94.3%**
 - Polynomial SVM, degree 3: **96.1%**
 - Deep classifier, softmax: **96.67%**
 - Deep classifier, SVM cost: **??%**
- Deep Classifier
 - **5000-5000-5000-5000-2**
 - Learning rate **.001**
 - Rectified Linear units
 - Softmax cost
 - SVM cost *should* improve ~1%



Graphic from unrelated dataset
<http://kastnerkyle.github.io>



Results from deep classifier training

Discussion

- Reduced computation
 - Network training needs GPU
 - SVM is possible on embedded
- Minimal increases WRT comp
 - Indicates **GOOD** features
 - At least for this task
- SOTA was ~80%
 - Currently **97.04%**
 - *And climbing!*



Advice

- Many hyperparameters don't matter!
 - *Random Search for Hyper-Parameter Optimization*
 - Bergstra, Bengio 2012
 - Sizes and number of layers - ***not very important***
 - Learning rate - ***very important***
 - Type of activation functions - ***very important***
 - Regularization - ***dropout***
- Train and tune network until strongly overfit
 - Then add dropout
- Advanced hyperparameter search packages
 - Hyperopt, Spearmint

More Advice

- Preprocessing is vital!
 - Global Contrast Normalization (GCN)
 - ZCA
 - Flip upside-down randomly ($p = .5$) during training
- Rectified Linear, Maxout are very good with dropout
- For more, read this paper:
 - <http://arxiv.org/abs/1206.5533>
- GPU is critical for big networks
 - Use pretrained nets to simplify
 - Transfer learning has great potential



Final Thoughts

- Links
 - <https://github.com/lisa-lab/pylearn2>
 - <https://github.com/UCB-ICSI-Vision-Group/decaf-release>
 - <https://github.com/kastnerkyle/kaggle-dogs-vs-cats>
 - <https://github.com/kastnerkyle/kaggle-cifar10>
 - <http://arxiv.org/abs/1206.5533>

Thank you!