

# International Research Symposium - 2024 (IRS 2024-UoVT)

# Vocational Technology Education for a Sustainable Greener Economy



University of Vocational Technology Sri Lanka

### **ABSTRACT PROCEEDINGS**

### International Research Symposium - 2024

### IRS 2024 - UoVT

#### DISCLAIMER

The papers published in these proceedings reflect the opinion of the respective authors. Information contained in these proceedings has been obtained by the editors from sources believed to be reliable. Authors of specific papers are responsible for the accuracy of the text and technical data. Neither the publisher nor the editors guarantee the accuracy or completeness of any information published herein, and neither the publisher nor the editors shall be responsible for any errors, omissions, or damages arising out of use of this information. Trademarks are used with no warranty of free usability.

All rights reserved. No part of this publication, including the cover design, may be reproduced, stored or transmitted in any form or by any means, whether electrical, chemical, mechanical, optical, recording or photocopying, without prior permission of the publisher.

### TABLE OF CONTENTS

TABLE OF CONTENTS
PROCEEDINGS OF IRS 2024 - PREAMBLES XV
List of Reviewers
Editorial Committee
Symposium Organizing Committee
Message from the Vice Chancellor
Message from the Keynote Speaker
Message from the Guest of Honour
Message from the Dean, Faculty of Education
Message from the Dean, Faculty of Engineering Technology
Message from the Dean, Faculty of Industrial Technology XXVI
Message from the Dean, Faculty of Information Technology XXVII
Message from the Symposium Chair
TECHNICAL SESSION 1 - EDUCATIONAL STRATEGIES FOR SUSTAINABLE TVET  1
Effectiveness of the Mind Mapping Technique in Essay Writing: A Case Study of Grade 11 ESL Learners by Dinithi S Senavirathne and Dimuthusiri Suraweera

An Analysis of Pronunciation Teaching Inclusion Into Sri Lankan English Textbooks From Grade Three to G. C. E. (AL)  by Rafeela Mohamed Azver	3
Needs Analysis of English for Academic Purposes for ELT Undergraduates by Darsha Kulathilaka and Buddhima Karunarathna	4
A Case Study of Academic, Social and Family History and Behavioural Situation of Below Average Level Student Readers with Spelling and Word Recognition Challenges  by Sandanayani S Silva	5
An Exploratory Case Study on ESL Teachers' Perceptions and Practices in Fostering Learner Autonomy to Enhance the English Language Competency of ESL Learners.  by Chathurangi U Karunasena	6
The Role of Oral Acknowledgement in Enhancing Learners' Intrinsic Interest: Utilising Oral Acknowledgement for Minimum Effort in English Language Learning by Harshani S Chandrasekara	7
Indices to Consider for Further Development of Degree Programs: Case Study-University of Vocational Technology, Sri Lanka by Uruthiran Sivachelvy	8
Challenges Faced by Students in Learning English as a Second Language for G.C.E. O/L Examination in Puttlam South Education Division by Dinithi Lakshani Wijesinghe and Pramodi C. Somarathna	9
The Impact of University Lecturers' Attitudes on Undergraduate's Learning: A Comparative Analysis Across Europe, Asia, and Sri Lanka by Malkanthi Thenabadu and D V D Sajeewani	10
Effectiveness of Using PowerPoint Presentations in Online Education at University of Vocational Technology  by Sanjaya U Dharmadasa	11

Investigating The Factors Affecting to The Selection of Courses in University Colleges, Sri Lanka with Special Reference to University College of Kuliyapitiya Sri Lanka	
by Maduni Hansika	12
ESL Teacher Competence in Integrating Technology with ESL Instruction: A Comparative Study Between Government and Private Sector In-Service ESL Student-Teachers by Vindya Madushani	13
Perceptions of Instructors on the Use of EGP and ESP in Teaching English: A Study Carried out in Technical and Vocational Education and Training Institution	
by Shashini Dileka Thennakoon	14
Sustainable TVET: The Descriptive Study On the Barriers to Developing the English Language Among TVET Skill Learners by Niluka S Gunathunga	15
Usage of ICT Tools in the Teaching-Learning Process in the Technical and Vocational Sector: Technology Acceptance Model (TAM) Approach by Mahalingam Ramanan	16
Exploring Gender Differences in the Adoption of Digital Platforms for Entrepreneurship: A Study Among Higher National Diploma Students in Colombo, Sri Lanka	
by Helawikum A Seneviratne	17
Enhancement of Career Guidance for Vocational Training Recipients of Vocational Training Authority of Sri Lanka by Yamuna Manathunge	18
by famuna Manadudige	10
Gamification as an Innovative Teaching Methodology to Engage and Motivate Learners for Sustainable Technical and Vocational Education and Training by Janaka Jayalath	19
Perceptions of Lecturers in Using Mobile Assisted Language Learning in ESL Classroom	
by Kapu Gamage Ishara Madumalika and Pramodi C. Somarathna	20

TECHNICAL SESSION 2 - ENGINEERING TECHNOLOGY FOR GREEN ECONOMY	
A Cost- Benefit Analysis to Assess the Profitability of Installing Solar Panels at the Irrigation Department Head Office in Colombo by Uruthiran Sivachelvy	22
Factors Influencing Intention to Purchase Residential Solar Panel Systems in Sri Lanka by G Thilak Kumar	23
Development of an Automate Solar Panel Cleaning System by S.P.A.R.S Jayathilaka	24
Green Energy and Social Equity: Addressing Disparities in Access and Benefits  by Tashni P Herath	25
Electro-Magnetic Interference Filter For Ultrasound Scanner by Jayaweera K Kanthi	26
Design and Implementation of a Power Monitoring System for Industrial Applications  by Ashan Nimsara Yapa and Sudeepa M Herath	27
Assessing the Feasibility and Potential of Vertical Axis Wind Turbines (VAWTs) as a Sustainable Energy Source for Remote University Settings by Dinithi M Warakagoda	28
Advancements and Impacts of Combine Harvesters in Paddy Cultivation in Northern Sri Lanka: A Comprehensive Review by Murugaiyah Priyatharsini	29
A Review on Existing Tricycle Suspension Systems by Nilushika Sudarshani Menike	30
Automating and Improving Oil-Water Separators to Reduce Environmental Effects in Associated Industries  by Indika IPK Pushpakumara and Sasiri V.R. Gamage	31

Utilisation of Sugarcane Bagasse Ash as a Substitute for Fine Aggregate in Cement Products	
by Kamala Gayanthi Alahapperuma and T. M. S. Madhushika	32
A Review on Chassis Systems of Tricycles by Tharindu Deshan Delpachithra	33
Investigation of Burned Timber Ash as a Partial Substitute of Cement in Soilcement Mix as a Backfilling Material in Small-scale Building Construction by Shankani Gunarathna	34
An Investigation Into How Drone Technology Is Employed in Construction Management by Kayukaran Vaitheki	35
Investigating the Potential of 4D Printing for Sustainable Solutions in Civil Engineering: A Systematic Review by Kamalaseelan Kajeenthan and Pirabakaran Kavippriyan	36
A New Wall Tile Design with Clay From the Abandoned Tile Factory Yatiyana, Matara, Sri Lanka by Tharinda Dasun Denagama and Deepadhi Abeygunawardena	37
A Comprehensive Analysis of the Role of Digital Twin Technology in the Construction Industry by Kayukaran Vaitheki	38
Case Studies of Soft Active Materials for Engineering Applications by Mapa Mudhiyanselage Lahiru Pemachandra	39
Failures in Project Completion by Hashan Tharindu Fonseka	40
Minimizing Variation Orders in the Construction of Married Quarters for Special Task Force, Sri Lanka: A Case Study by Edirisinghe Sanduni Nimasha Nadeeshani	41

Pavement in Sri Lanka by Imalka Subhashini Jayasundara	42
Delay in Progress Due to Late Payment; the Case of Historic Rajawasala Restoration Project in Kandy by Vindya H Epanage (S.E.V.H Epanage)	43
Evaluation of Bonding Strength and Cost Effectiveness of a Substitute Internal Plastering Mix by Anjana Jayasuriya	<b>4</b> 4
Experimental Investigation to Find out Solution for Pepper Joint Waterproofing at ITC Project by Thanuka R Gunathilake and Kasun Nandapala	45
Causes and Impacts of Variation Orders in the Grand Tower Residencies Apartment Project: a Case Study in Colombo, Sri Lanka by Mohamed Rikas and Mohamed Rikas	46
Use of Coconut Coir as a Reinforcing Material in Clay Bricks by Kamala Gayanthi Alahapperuma and Thilini Madhushani Gamage	47
Cost Effective Wireless Guestroom Control System by Madhavi Perera	48
Impact of Building Services on Customer Satisfaction in Sri Lankan Hotels by Naleen S Karunasinghe	49
Air Quality of Air-Conditioned and Non-air-conditioned Buses by Pathiranage pubudu	50
Low Cost Solar Powered Daylight Tube for Residential Buildings in Sri Lanka by Madhavi Perera	51
Evaluating the Thermal Insulation Properties of Mushroom Production Waste in Building Applications by Harshani R.M.M. Upamalika, Sanjaya Kumara, Thiruvakaran Luckshanth and Kasun Nandapala	52

Construction. A Case Study Analysis for Hotel Building Project in Sri Lanka by Madushani Kaushalya	53
Identification of Best Plant Combinations in Increasing the Thermal Conductivity of Vertical Green Systems Under Tropical Climatic Conditions by Samantha Manawadu	54
Analysis of Frequent Electrical Breakdowns in Mawanella: Causes, Impacts, and Mitigation Strategies  by Prasad Dissanayake	55
Development of a Non-Lethal Wildlife Deterrent System: Addressing Human-Wildlife Conflict with Asian Palm Civets in Agricultural and Residential Areas	
by Mohammad Hadhil	56
Image-Based Quality Inspection in Metal Roofing Sheets Products Using Image Processing	57
by Sondarangallage D.A Sanjeewa	57
Automation of Traditional Agriculture: Robot Harvesting with Challenges by Duminda S.B. Ratnayake	58
Advanced Wheel Chair Control System Rasberry Pi-3-based Joystick Analog and Voice Control by Dilshan T Ganegoda	59
Design and Implementation of Smart Shock Absorber Integrated with GPS-Based Road Condition Analysis by Barathy M Aklakurajah	60
Design a Full-Body Covered Safety Airbag System for Motorcyclists by Barathy M Aklakurajah	61
Error Detection of The Tower Parts in Tower Fabrication Industry by Image Processing	
by Sondarangallage D.A Sanjeewa	62

TECHNICAL SESSION 3 - DIGITAL TECHNOLOGIES AND CREATIVE IN- DUSTRIES	
An Enhancing Public Transportation in Sri Lanka Through Real Time Tracking and Booking System  by Uruthiran Uruthiran	64
Analysis The Influence Factors of The Indoor Path Loss Calculation by Suranga Sampath Dissanayake, Maheshika Dissanayake and Asanka Pathirana	65
Low Cost IoT-Based Home Remote Monitoring and Controlling System by Rukshanth Marudhapulle	66
Developing a Specialized Job Board for NVQ Certificate Holders in Sri Lanka by Jayasuriya Kuda Baduge Erandika Sandaruwani	67
Next-Generation School Bus Tracking: A Mobile-Centric Approach for Real- Time Monitoring by Asanka Indrajith Pathirana	68
Development of an Etymological Analysis Tool for Sinhala Language by Lasika Kodagoda and Chamika Hulangamuwa	69
Virtual Fitting Room System (Fit-Me) by Achini Apeksha Nanayakkara	70
Development and Evaluation of an Automated Student Attendance Tracking System Using Facial Recognition Technology  by Thejani Perera	71
Strategies Used in Film Marketing, Based on Case Studies in Major Film Industries by Nipuni N.S Dompage and Nalin G.A. Sampath (G.A.N. Sampath)	72
TECHNICAL SESSION 4 - INNOVATION AND ENTREPRENEURSHIP FOR ECONOMIC RESILIENCE	73

Employees' Perceptions	74
by Uruthiran Sivachelvy	/4
Optimizing Inventory Through ABC-FSN Analysis by Gayan D. Wickramasinghe	75
Purchase Intention of Cloud Products: A Study of SME Customers in Leading Telecommunication Provider in Sri Lanka by Rumesh C. Kumaradasa	76
Optimization of a Single Supplier Raw Materials Inventory System in a Fabric Manufacturing Plant by Kasun Lankapura and Jayalal Wettasinghe	77
An Effect of MAS Holdings in the Sri Lankan Garment Industry by Uruthiran Sivachelvy	78
Manufacturers' Perception of Establishing Refilling Stations in the Cleaning Products Manufacturing Industry as a Sustainable Solution for Single-use Plastics	
by K.G.S.S. Bandara and T.R. Vidanapathirane	79
Improving the Efficiency of the MTU Workshop at the Sri Lanka Naval Dock-yard, Trincomalee	80
by Nimesh Lakshitha Senerath	80
Customer Churn of Fibre Retail Customers in Leading Telecommunication Provider in Sri Lanka	
by Sulakshi Himesha Hettiarachchi	81
University Employee Students' Time Management and Its Effect on Academic Success	
by Sagarika Maduwanthi Chandrarathna	82
The Factors Influencing Tourists' Satisfaction and Their Impacts on Destination Loyalty in Domestic Tourism in Sri Lanka	
by Shanmuganathan Kalimuththu	83

Review on Skin Depigmenting Activity of Common Medicinal Plants Used in Sri Lankan Traditional Beauty Remedies by Ayesha Gunarathna	84
Assessing the Entrepreneurial Intentions of Cosmetology Students in Sri Lankan University Colleges	0.5
by Thembamala E. Nirmalan, Imalsha De Silva and Kiruthiga R	85
Review of Toxic Chemicals in Cosmetics by Imalsha J.H.I.G De Silva, Dinelka Bandara and Sugath Prasanna	86
Visitor Interpretative Infrastructure Development as a Tourist Educational Tool for Sustainable Nature Tourism; A Case Study in Horton Plains National Park by Dhanusha Premarathna	87
Exploring the Factors Affecting on Tourist Satisfaction with Ride-sharing Services in Sri Lanka (With Special Reference to Colombo District) by Hasini P. Kottage and Niluka Fonseka	88
Challenge and Opportunities on Adopting Tourist Information Kiosks in Cultural Triangle Sri Lanka: Tourism Stakeholders' Perspective by Madhumali Sudeshanee H.P. Sudeshanee	89
Identify the Psychological Aspects of Digital Nomads for Tourism Destination Marketing in Sri Lanka by Thashila Yohani, Amaya Ranaweera and Gangani Marasinghe	90
A Preliminary Study on The Bragadi Thailaya of Thalpathe Piliyam for Darunaka by Chamila Ekanayake	91
ECHNICAL SESSION 5 - SUSTAINABLE PRACTICES FOR MULTIFUNCTIONAL REEN ECONOMY	92
A Review of Developed Lean Construction Frameworks in the Sri Lankan Context by P.L. Perera, S. Kajewski, V. Coffey	93

Towards the Development of a Specific Procurement Guideline for the Water Supply Sector in Sri Lanka	
by Nipuna Sisilakhsa and Muditha P Seneviratne	94
Major Determinants of Site Level Labors Retention: The Case of Direct Skilled Labors of Sri Lanka by Muditha P Seneviratne and Ayanthika Subodhani S Gunathilaka	95
Construction Projects Performance Attributes on Domestic Contractor's Cost Controlling Action of Sri Lankan Construction Industry by Damith Balasooriya, Muditha P Seneviratne and Thamara BMTD Jayasekara .	96
Approaches to Face the Current Sri Lankan Crises as a Successful Local Quantity Surveyor by Vijayaragunathan Srivishagan and Rasanthi Thalpage	97
Mitigate the Impacts of Project Delays on the Contractor's Cash Flow: Case Study Approach by Didula Chamikara Wedikkara, Chandana Jayalath and Muditha P Seneviratne.	98
Enhancing the Formality of Informal Construction Sector in Sri Lanka by Overcoming the Existing Challenges by Rasanthi Thalpage and Vijayaragunathan Srivishagan	99
Measures to Overcome Project Complexity Occurred over Series of Project Revisions and Overlapped Variations Transpired out of Contractual Scope: A Case Study Approach by Madhawa M Wijesirinarayana	100
Aptness of the CIDA Formula Method to Mitigate Construction Cost Uncertainties: Sri Lankan Case Study During Economic Recession by Hiroshani Yakupitiya Ruwanmali	101
Suggestions to Mitigating Impacts of Skilled Labor Shortage in Sri Lanka by Wathsala G.R Prasadini, Chandana Jayalath and Muditha P Seneviratne	102

Mitigate the Consequences on Contractor's Profit by Variations at Rural Domestic Residential Construction: Case Study: SME Construction Company of	
Sri Lanka by Bulathgamage Madushika Hansini Jayathilaka, Chandana Jayalath and Muditha	
P Seneviratne	103
Determination of Nutritional and Functional Properties of Sri Lankan Traditional Fermented Rice	
by Malan Madhushanka D.M. Premarathna, Malkanthi Thenabadu and Chathuni Jayathilake	104
Detection of Adulteration in Non-Labeled Chili and Turmeric Powders Available in the Retail Market in the Matara City Area	
by Chathurika M Jayasekara, Nipuni Kaushalya and Varunitha p; Sudeepa Dissanayaka	105
Development of Spreadable Creamed Coconut (Coconut Spread) by Yogaprathish V and Amila U.P.A.L Dasanayaka	106
Consumer Acceptability of Ceylon Date Palm Fruit Incorporated Alcoholic Beverage	
by Pasindu P.D. Samanthilaka, W.A.C. Hasini Wijayathilaka and M.L P.Thathsarani	107
Development of a Monitoring System for Tracking and Analyzing Pre-packaged Fast Food Consumption	
by Rajitha Wasana Wedage	108
Development and Characterization of a Coriander Leaf and Green Chili-Based Culinary Sauce	
by Pushparaj P Anusha, Selvaraj Danushan and Piranavan Karthiha	109
Development and Evaluation of a Ready-to-Eat Ketogenic Bar: Formulation, Nutritional Composition, Sensory Properties	
by Kithulampitiya Wickramasinghage Yasintha, Abeykon Jayalath Rathnayake Pulathisi Pasan Edirisinghe Mudiyanselage Savini Hansi Savini Kumari	110

Development of a Systematic Approach to Culinary Ingredient Shelf-Life Management and Safety: A Case Study of Cinnamon Hotels and Resorts	
by Ayesha I Nikalansooriya, Janitha Chandimal, Malsha Samarasekara, Chanaka	
Bandara and Geeshani Somaratne	111
Development of Chocolate Alternative Using Avocado Seed (Persea Americana)	
by Maheshi Dissanayake and Sagara Kamal Edirisinghe	112
Evaluation of the Efficacy of Natural Spices as Preserva-tives in Chicken Sausages: Nutritional, Microbial, and Sensory Implications of Garlic, Clove, and Cardamom	
	113
Factors Influencing Fast Food Consumption and Nutritional Status Among University Students: A Case Study of a Vocational University, Colombo, Sri Lanka	
by Malkanthi Thenabadu, D.V.D. Sajeewani and P.A.H. Madushani	114
Pilot Study: Quantitative Assessment of Household Coping Strategies in Response to Food Insecurity in Urban Coastal Villages of Sri Lanka by Malkanthi Thenabadu	115
by Markanun Thenabadu	113
Development and Sensory Quality Evaluation of Innovative Marmalade Product Using Jackfruit Seed Outer Bark (Jack Arlis) as Zero-Waste Solution	
by Dilini J.K.P.D. Lakshani	116
Development of Cassava Flour Cake Layered with Carro Jam by Priyanka T Dilrukshi (Priyanka Dilrukshi) and Usha Nandhani	117
Development of a Kiri Ala Flour Incorporated Healthy Biscuit as An Innovative Product to Biscuit Manufacture	
by Edirisinghe Mudiyanselage Savini Hansi Savini Kumari, Gayani Silva, Pasan Rathnayake and Ashani Sewwandi	118

### PROCEEDINGS OF IRS 2024

### **PREAMBLES**

### LIST OF REVIEWERS

Dr. K A Lalithadheera Director-General, Tertiary and Vocational Education

Commission (Chairman)

Dr. L.W.S. Kularatne Dean, Faculty of Education

Ms. T.K. Malwatta
Dean, Faculty of Information Technology
Dr. U.A.S.K. Edirisinghe
Dean, Faculty of Industrial Technology
Dr. Jayalal Wettasinghe
Dean, Faculty of Engineering Technology

Mr. M.G. Dharmasiri Director General (Covering), University of Vocational

Technonlogy

Dr. Kasun Nandapala Director - Admission, Accreditation & Quality Assur-

ance

Mr. S.C. Jagath Director-General, Department of Technical Education &

Training

#### **EDITORIAL COMMITTEE**

Dr. Kasun Nandapala Director - Admission, Accreditation &

Quality Assurance

Mr. T.D. Denagama Head, Department of Construction

Technology

Ms. W.A.I.M. Gunasekara Head, Department of Industrial Management

Ms. L.H.D.L. Ranasuriya Head, Department of Language Studies
Ms. Y. S. Manathunga Head, Department of Education & Training
Mr. P.H.S.S. Wijayarathna Head, Department of Network Technology
Dr. (Ms.) J.A.E.C. Jayawardena Acting Head, Department of Agriculture &

Food Technology

Mr. P Uruthiran Acting Head, Department of Software

Technology

Prof. Chandana Jayalath Professor, Department of Quantity Surveying

Dr. D.D.D. Suraweera Senior Lecturer, Department of

Electro-Mechanical Technology

Dr. J.A.D. Jayalath Senior Lecturer, Multimedia & Web

Technology

Dr. (Ms.) T. Somaratne Senior Lecturer, Department of Agriculture &

Food Technology

Ms. A.A. Gunawardana Senior Lecturer, Department of Language

Studies

Ms. J.A.M.B. Karunarathna Senior Lecturer, Department of Language

Studies

Ms. W.C.C. Sumathiratna Senior Lecturer, Department of Building

Services Technology

Ms. K.G. Alahapperuma Senior Lecturer, Department of

Electro-Mechanical Technology

Ms. J.K. Kanthi Senior Lecturer, Department of

Electro-Mechanical Technology

Ms. M. Thenabadu	Senior Lecturer, Department of Agriculture &
	Food Technology
Ms. U. Sivachelvy	Senior Lecturer, Department of Industrial
	Management
Ms. B.M.T.D. Jayasekara	Senior Lecturer, Department of Industrial
	Management
Ms. K .T. P. C. Somarathna	Lecturer (Probationary), Department of
	Language Studies
Ms. A.A.S.U. Gunarathna	Lecturer (Probationary), Department of
	Construction Technology
Mr. P.D.S. Ashan	Lecturer (Probationary), Department of
	Building Services Technology
Mr. H.A. Gayan Madushanka	Lecturer (Probationary), Department of Film
	& Television Production Technology
Mr. H.N.W. Gunasekara	Lecturer (Probationary), Department of
	Electro-Mechanical Technology
Mr. A.H.M.S. Siriwardana	Lecturer (Probationary), Department of
	Construction Technology
Mr. G.A.N. Sampath	Lecturer (Probationary), Department of Film
	& Television Production Technology
Mr. S.V.R. Gamage	Lecturer (Probationary), Department of
	Electro-Mechanical Technology
Mr. L.P.S.S. Dissanayake	Lecturer (Probationary), Department of
	software Technology
Dr. S.A.N Danushka	Teaching Assistant, Department of Education
	& Training
Ms. T.R. Vidanapathirane	Teaching Assistant, Department of Industrial
	Management

#### SYMPOSIUM ORGANIZING COMMITTEE

#### **Advisory Committee**

Professor C. Mahesh Edirisinghe Vice Chancellor

Dr. D.D.D. Suraweera Former Chair – IRS 2017
Prof. Chandana Jayalath Former Chair – IRS 2021
Dr. L.W.S. Kularatne Former Chair – IRS 2022
Mr. H.A. Seneviratne Former Chair – IRS 2023

#### **Programme Committee**

Ms. P.M Perera Symposium Chair

Ms. Samantha Manawadu Symposium Co-Secretary
Mr. R.R.M.D.P Rathnayake Symposium Co-Secretary
Dr. L.W.S Kularatne Dean, Faculty of Education

Ms. T.K Malwatte Dean, Faculty of Information Technology
Dr. J. Wettasinghe Dean, Faculty of Engineering Technology
Dr. U.A.S. Kamal Edirisinghe Dean, Faculty of Industrial Technology
Dr. Kasun Nandapala Director, Admission, Accreditation and

Quality Assurance

Mr. S.P.A.R.S. Jayathilaka Director, Human Resource Development

Centre

Mr. A.M.C.K Gunathilaka

Director, Media & Information Services

Ms. Dilini Ranasuriya

Head, Department of Education & Training

Ms. Indrachapa Gunasekeara

Head, Department of Management Studies

Head, Department of Quantity Surveying

Mr. D.T. Ganegoda

Head, Department of Electro Mechanical

Technology

Mr. T.D. Denagama Head, Department of Construction

Technology

Dr. E. C. Jayawardena Acting Head, Department of Agriculture &

Food Technology

Mr. R.M.C.A.B Rathnayake Acting Head, Department of Network

Technology

Mr. P Uruthiran Acting Head, Department of Software

Technology

Ms. S.G Nambuwasam Acting Head, Department of Multimedia &

Web Technology

Professor R.L.W Koggalage Associate Professor, Department of Electro

Mechanical Technology

Dr. S.D.A Sanjeewa Senior Lecturer, Department of Electro

Mechanical Technology

Dr. S.A.N Danushka Teaching Assistant, Department of Education

& Training

Dr. Thikshani Somarathna Senior Lecturer, Department of Agriculture &

Food Technology

Dr. Janaka Jayalath Senior Lecturer, Multimedia & Web

Technology

Mr. M.G Dharmasiri Director General (Covering) / Senior

Assistant Registrar (Establishments and

Administration)

Mr. R.D.P.I. Priyadarshana System Administrator

Mr. T.C Jayamuthuge Producer

#### MESSAGE FROM THE VICE CHANCELLOR



Dear Participants,

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium

2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

#### MESSAGE FROM THE KEYNOTE SPEAKER



Dear Participants,

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward

to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

#### MESSAGE FROM THE GUEST OF HONOUR



Dr. Nadeesha Chandrasena posing with her two award

Dear Participants,

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward

to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

### MESSAGE FROM THE DEAN, FACULTY OF EDUCATION



Dear Participants,

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium

2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

### MESSAGE FROM THE DEAN, FACULTY OF ENGINEERING TECHNOLOGY



Dear Participants,

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium

2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

### MESSAGE FROM THE DEAN, FACULTY OF INDUSTRIAL TECHNOLOGY



Dear Participants,

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium

2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Sincerely, Chairman's Name

XXVI

### MESSAGE FROM THE DEAN, FACULTY OF INFORMATION TECHNOLOGY



Dear Participants,

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium

2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

#### MESSAGE FROM THE SYMPOSIUM CHAIR



Dear Participants,

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium

2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event. Welcome to the International Research Symposium 2023. We are delighted to have you here and look forward to an engaging and productive event.

### **TECHNICAL SESSION 1**

# EDUCATIONAL STRATEGIES FOR SUSTAINABLE TVET



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials

### **TECHNICAL SESSION 2**

# ENGINEERING TECHNOLOGY FOR GREEN ECONOMY



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



### USE OF COCONUT COIR TO IMPROVE STRENGTH PROPERTIES OF DRIED CLAY BRICKS

### K. G. Alahapperuma, E. R. Madhushanka, G. T. Madhushani and R. G. P. C. Rajamanthri

Department of Electromechanical Technology, University of Vocational Technology, Sri Lanka kgalahapperuma@uovt.ac.lk

Abstract: In Sri Lanka, most of the traditional domestic buildings, which include residential houses are based on clay bricks. Production of the traditional clay bricks involves a burning step using firewood, which contributes to deforestation, air pollution, and also emission of carbon dioxide gas. This step contributes to high energy consumption and associated costs as well. This study was mainly aimed at improving the strength characteristics of the unburnt clay cricks by incorporating coconut coir as a reinforcing phase to the same. Since burning of bricks hasn't taken place, all associated disadvantages aren't issues of the study. Visual appearance, density, water absorption, compressive strength, and thermal conductivity were the tested properties. Coir percentage was varied by 0%, 10%, 20%, 30%, 40% and 50% by volume. As outcomes, 10% coconut coir-added bricks were selected as the composition with the highest quality. These bricks show a better compressive strength of 1.761 Nm<sup>-2</sup> compared to 1.654 Nm<sup>-2</sup> of the clay bricks with no coir addition. However, none of the brick composition showed a favourable level of water absorption. Bricks with selected composition can be recommended to be applied in non-load-bearing applications where water attack is unlikely.

Keywords: Compressive Strength, Clay Bricks, Coconut Coir, Reinforcing Material, Water Absorption.



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials

## **TECHNICAL SESSION 3**

# DIGITAL TECHNOLOGIES AND CREATIVE INDUSTRIES



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials

## **TECHNICAL SESSION 4**

# INNOVATION AND ENTREPRENEURSHIP FOR ECONOMIC RESILIENCE



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



# EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials

### **TECHNICAL SESSION 5**

# SUSTAINABLE PRACTICES FOR MULTIFUNCTIONAL GREEN ECONOMY

### 08th International Symposium of University of Vocational Technology 2024

### Rathmalana, Sri Lanka | 12th. December 2024

### A REVIEW OF DEVELOPED LEAN CONSTRUCTION FRAMEWORKS IN THE SRI LANKAN CONTEXT

#### P.L. Perera, S. Kajewski, V. Coffey

School of Architecture and Built Environment, Queensland University of Technology (QUT),
Brisbane, Australia
panapitikankanamalage.perera@hdr.qut.edu.au

Abstract: There is a growing necessity to thoroughly review the developed lean construction frameworks within a Sri Lankan context because most of the developed frameworks in this country were introduced at a conceptual level and in a scattered diffused manner across various construction domains. Several scholars have underscored the lack of comprehensive frameworks encompassing the entire construction lifecycle and the absence of industry-validated processes in Sri Lanka from 2012 to 2018. After 2018, a few frameworks emerged, but they exhibit significant limitations, such as insufficient transparency, biases, and reliance on limited mono or bi-evidence case studies on lean tool implementation. This study aims to review existing lean construction frameworks developed from 2012 to 2024, identifying their benefits, shortcomings, issues, and limitations through a comprehensive literature review-based approach. As one of the pioneering review studies in this area, the summarized tabular framework demonstrates the drawbacks and loopholes while providing suggestions to overcome them. The outcomes provide new thinking perspectives for novel framework development that apply in Sri Lanka and other developing countries that share the same level of lean construction maturity and characteristics. This paper will be a foundation for determining future probable areas such as: cost overrun, time delays, quality issues, risk predictability, and stakeholder management to consider in lean construction framework development in the Sri Lankan context.

Keywords: Frameworks Review, Lean Construction, Sri Lanka.



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



### EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



### EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



### EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



### EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



## EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials



### EVALUATING THE THERMAL INSULATION PROPETIES OF MUSHROOM PRODUCTION WASTE IN BUILDING APPLICATION

R.M.M.H.U. Chandrasiri<sup>1\*</sup>, R.S. Kumara<sup>1</sup>, T. Luckshanth<sup>1</sup>, Kasun Nandapala <sup>1</sup>

<sup>1\*</sup> Department of Construction Technology, University of Vocational Technology, 100, Kandawala, Rathmalana, Srilanka.

\*E-mail-ctrm18b131@uovt.ac.lk

**Abstract**: The Building Construction Sector is notably resource intensive, with a significant dependence on raw materials. This study investigates the potential of mushroom cultivation waste as a sustainable insulation material to mitigate environmental impact and conserve natural resources. A slab model was developed, incorporating a void filled with mushroom waste and encased in concrete, alongside a conventional concrete slab serving as the control. Following a 12-hour heat simulation, the mushroom waste slab exhibited a thermal conductivity of 0.191 W/m./k, Specific heat capacity of 320 J/ kg.K, Density of 450kg/m³, and thermal Resistance of 0.1571m2K/W. The results indicate that the mushroom waste slab outperforms the control slab in thermal performance, highlighting its viability as an effective building insulation materials