

Rockchip	Rockchip Electronics Co., Ltd
Project:	GR3568bv1
File:	<Page name>

Date:	Wednesday, July 20, 2022	Rev:	V1.0
Designed by: Zhangdz	Reviewed by: Default	Sheet:	1 of 10



GPIO4_A6 ⟷ GMAC1_TXEN_M1
GPIO4_A2 ⟷ GMAC1_RXD3_M1
GPIO4_B0 ⟷ GMAC1_RXD1_M1
GPIO4_A0 ⟷ GMAC1_TXCLK_M1
GPIO4_A4 ⟷ GMAC1_TXD0_M1
GPIO4_A1 ⟷ GMAC1_RXD2_M1
GPIO4_A5 ⟷ GMAC1_TXD1_M1
GPIO4_B1 ⟷ GMAC1_RXDV_CRS_M1
GPIO3_D7 ⟷ GMAC1_TXD3_M1
GPIO4_A7 ⟷ GMAC1_RXD0_M1
GPIO3_D6 ⟷ GMAC1_TXD2_M1
GPIO4_B6 ⟷ GMAC1_MDC_M1
GPIO4_B7 ⟷ GMAC1_MDIO_M1
GPIO4_A3 ⟷ GMAC1_RXCLK_M1
GPIO3_C3 ⟷ PCIE_PWREN_H_GPIO3_C3

GPIO3_D3 ⟷ SDMMC2_CLK_M0
GPIO3_D0 ⟷ SDMMC2_D2_M0
GPIO3_C7 ⟷ SDMMC2_D1_M0
GPIO3_D1 ⟷ SDMMC2_D3_M0
GPIO3_C6 ⟷ SDMMC2_D0_M0
GPIO3_D2 ⟷ SDMMC2_CMD_M0
GPIO3_D4 ⟷ WIFI_WAKE_HOST_H_GPIO3_D4
GPIO4_C0 ⟷ CIF_CLKOUT
GPIO4_C5 ⟷ UART9_TX_M1
GPIO4_C6 ⟷ UART9_RX_M1
GPIO3_D5 ⟷ WIFI_REG_ON_H_GPIO3_D5
GPIO4_B3 ⟷ I2C4_SCL_M0
GPIO4_B2 ⟷ I2C4_SDA_M0
GPIO4_C1 ⟷ GMAC1_MCLKINOUT_M1

	Rockchip Electronics Co., Ltd				
Project:	**GR3568bv1**				
File:	**<Page name>**				
Date:	Wednesday, July 20, 2022			Rev:	V1.0
Designed by:	Zhangdz	Reviewed by:	Default	Sheet	2 of 10



Rockchip Electronics Co., Ltd

Project:	GR3568bv1		
File:	<Page name>		
Date:	Wednesday, July 20, 2022	Rev:	V1.0
Designed by: Zhangdz	Reviewed by: Default	Sheet:	3 of 10



这三个脚可换成1.8V的脚

MIPI/LVDS复用，通过程序配置

MIPI/EDP复用，通过核心板电阻配置

HDMI TX DDC

HDMI TX CEC

HDMI TX HPD

Rockchip Electronics Co., Ltd

Project:	GR3568bv1
File:	<Page name>
Date:	Wednesday, July 20, 2022
Rev:	V1.0
Designed by:	Zhangdz
Reviewed by:	Default
Sheet	4 of 10



Note:
Adjusted the load capacitance according to the crystal specification.

Please choose IO voltage values according to the real mounted module and modify the corresponding software configuration.

SDIO voltage select:
0: 3.3V 1:1.8V

Rockchip Electronics Co., Ltd

Project:	GR3568bv1
File:	<Page name>

Date: Wednesday, July 20, 2022 Rev: V1.0
Designed by: Zhangdz Reviewed by: Default Sheet: 5 of 10



VCCIO_PHY0=3.3V	DNP	22R	
VCCIO_PHY0=1.8V	120R	100R	Default

RGMII Power Source	CFG_EXT	CFG_LDO[1:0]	
External 3.3V	1'b1	2'b00	
External 1.8V (default)	1'b1	2'b10	
Internal 1.8V	1'b0	2'b10	

PHY Address	PHYAD[2:0]
1 (default)	3'b001

Rockchip Confidential

Rockchip Electronics Co., Ltd

Project:	GR3568bv1				
File:	<Page name>				
Date:	Wednesday, July 20, 2022			Rev:	V1.0
Designed by:	Zhangdz	Reviewed by:	Default	Sheet:	6 of 10



VCCIO_PHY1=3.3V	DNP	22R	
VCCIO_PHY1=1.8V	120R	100R	Default

RGMII Power Source	CFG_EXT	CFG_LDO[1:0]
External 3.3V	1'b1	2'b00
External 1.8V (default)	1'b1	2'b10
Internal 1.8V	1'b0	2'b10

PHY Address	PHYAD[2:0]
1 (default)	3'b001

Rockchip Electronics Co., Ltd

Project:	GR3568bv1				
File:	<Page name>				
Date:	Wednesday, July 20, 2022			Rev:	V1.0
Designed by:	Zhangdz	Reviewed by:	Default	Sheet:	7 of 10

SPK

Note:8ohm/1.3W
Speaker Output



MIC











Gyroscope+G-sensor



IR
Receiver



Rockchip Electronics Co., Ltd			
Project:	**GR3568bv1**		
File:	**<Page name>**		
Date:	Wednesday, July 20, 2022	Rev:	V1.0
Designed by: Zhangdz	Reviewed by: Default	Sheet:	8 of 10

PCIe3.0 x 2Lanes (X 4Slot)



If board target trace impedance is 50ohm
then R = 475ohm providing an IREF of 2.32 mA .
The output current (IOH) is 6 * IREF .
6x2.32X50=696mV

Rockchip Electronics Co., Ltd

Project:	GR3568bv1				
File:	<Page name>				
Date:	Wednesday, July 20, 2022			Rev:	V1.0
Designed by:	Zhangdz	Reviewed by:	Default	Sheet:	9 of 10



SATA3.0 Port2



NOTES:The SATA differential trace impedance is 100 OHM.
The SATA trace length is less than 5 inch.



NOTES:Close to DC Port

CAN1_M1

CAN transceiver IC



TCAN332G:PIN3=3.3V,PIN5,8=NC

TCAN1044V-Q1:PIN3=5V,PIN5=VIO,PIN8=S

Rockchip 瑞芯微电子	Rockchip Electronics Co., Ltd		
Project:	GR3568bv1		
File:	<Page name>		
Date:	Wednesday, July 20, 2022	Rev:	V1.0
Designed by: Zhangdz	Reviewed by: Default	Sheet:	10 of 10