

## ✓ Implement Alpha-Beta Search Tree using Game Strategy

### Part-01: List of Tasks to Perform

1. Install the Python Libraries for Game Strategy
2. Implement a Game Class Constructor with - actions, is\_terminal, result, utility
3. Implement a Player Game using game class function

```
from collections import namedtuple, Counter, defaultdict
import random
import math
import functools
cache = functools.lru_cache(10**6)

class Game:
    """A game is similar to a problem, but it has a terminal test instead of
    a goal test, and a utility for each terminal state. To create a game,
    subclass this class and implement `actions`, `result`, `is_terminal`,
    and `utility`. You will also need to set the .initial attribute to the
    initial state; this can be done in the constructor."""

    def actions(self, state):
        """Return a collection of the allowable moves from this state."""
        raise NotImplementedError

    def result(self, state, move):
        """Return the state that results from making a move from a state."""
        raise NotImplementedError

    def is_terminal(self, state):
        """Return True if this is a final state for the game."""
        return not self.actions(state)

    def utility(self, state, player):
        """Return the value of this final state to player."""
        raise NotImplementedError

def play_game(game, strategies: dict, verbose=False):
    """Play a turn-taking game. `strategies` is a {player_name: function} dict,
    where function(state, game) is used to get the player's move."""
    state = game.initial
    while not game.is_terminal(state):
        player = state.to_move
        move = strategies[player](game, state)
        state = game.result(state, move)
        if verbose:
            print('Player', player, 'move:', move)
            print(state)
    return state
```

## ✓ Part-02: Implementation of Game Strategy Algorithm

1. MiniMax Tree
2. Alpha-Beta Search Algorithm

```
def minimax_search(game, state):
    """Search game tree to determine best move; return (value, move) pair."""
```

```
    player = state.to_move
```

```
    def max_value(state):
        if game.is_terminal(state):
            return game.utility(state, player), None
        v, move = -infinity, None
        for a in game.actions(state):
            v2, _ = min_value(game.result(state, a))
            if v2 > v:
                v, move = v2, a
        return v, move
```

```
    def min_value(state):
        if game.is_terminal(state):
            return game.utility(state, player), None
        v, move = +infinity, None
        for a in game.actions(state):
            v2, _ = max_value(game.result(state, a))
            if v2 < v:
                v, move = v2, a
        return v, move
```

```
    return max_value(state)
```

```
infinity = math.inf
```

```
def alphabeta_search(game, state):
    """Search game to determine best action; use alpha-beta pruning.
    """Search all the way to the leaves."""
```

```
    player = state.to_move
```

```
    def max_value(state, alpha, beta):
        if game.is_terminal(state):
            return game.utility(state, player), None
        v, move = -infinity, None
        for a in game.actions(state):
            v2, _ = min_value(game.result(state, a), alpha, beta)
            if v2 > v:
                v, move = v2, a
                alpha = max(alpha, v)
            if v >= beta:
                return v, move
        return v, move
```

```
    def min_value(state, alpha, beta):
        if game.is_terminal(state):
            return game.utility(state, player), None
        v, move = +infinity, None
        for a in game.actions(state):
            v2, _ = max_value(game.result(state, a), alpha, beta)
            if v2 < v:
                v, move = v2, a
                beta = min(beta, v)
            if v <= alpha:
                return v, move
        return v, move
```

```
    return max_value(state, -infinity, +infinity)
```

## ✓ Part-03: Implement the Game Strategy using TicTacToe

```
class TicTacToe(Game):
    """Play TicTacToe on an `height` by `width` board, needing `k` in a row to win.
    'X' plays first against 'O'."""
```

```
    def __init__(self, height=3, width=3, k=3):
        self.k = k # k in a row
        self.squares = {(x, y) for x in range(width) for y in range(height)}
        self.initial = Board(height=height, width=width, to_move='X', utility=0)
```

```
    def actions(self, board):
        """Legal moves are any square not yet taken."""
        return self.squares - set(board)
```

```
    def result(self, board, square):
        """Return the board after the move on `square` is made.
        """
```

```

"""Place a marker for current player on square."""
player = board.to_move
board = board.new({square: player}, to_move=('O' if player == 'X' else 'X'))
win = k_in_row(board, player, square, self.k)
board.utility = (0 if not win else +1 if player == 'X' else -1)
return board

def utility(self, board, player):
    """Return the value to player; 1 for win, -1 for loss, 0 otherwise."""
    return board.utility if player == 'X' else -board.utility

def is_terminal(self, board):
    """A board is a terminal state if it is won or there are no empty squares."""
    return board.utility != 0 or len(self.squares) == len(board)

def display(self, board): print(board)

def k_in_row(board, player, square, k):
    """True if player has k pieces in a line through square."""
    def in_row(x, y, dx, dy): return 0 if board[x, y] != player else 1 + in_row(x + dx, y + dy, dx, dy)
    return any(in_row(*square, dx, dy) + in_row(*square, -dx, -dy) - 1 >= k
               for (dx, dy) in ((0, 1), (1, 0), (1, 1), (1, -1)))

class Board(defaultdict):
    """A board has the player to move, a cached utility value,
    and a dict of {(x, y): player} entries, where player is 'X' or 'O'."""
    empty = '.'
    off = '#'

    def __init__(self, width=8, height=8, to_move=None, **kwargs):
        self.__dict__.update(width=width, height=height, to_move=to_move, **kwargs)

    def new(self, changes: dict, **kwargs) -> 'Board':
        """Given a dict of {(x, y): contents} changes, return a new Board with the changes."""
        board = Board(width=self.width, height=self.height, **kwargs)
        board.update(self)
        board.update(changes)
        return board

    def __missing__(self, loc):
        x, y = loc
        if 0 <= x < self.width and 0 <= y < self.height:
            return self.empty
        else:
            return self.off

    def __hash__(self):
        return hash(tuple(sorted(self.items()))) + hash(self.to_move)

    def __repr__(self):
        def row(y): return ' '.join(self[x, y] for x in range(self.width))
        return '\n'.join(map(row, range(self.height))) + '\n'

def random_player(game, state): return random.choice(list(game.actions(state)))

def player(search_algorithm):
    """A game player who uses the specified search algorithm"""
    return lambda game, state: search_algorithm(game, state)[1]

```

## ✓ Evaluate the Game Strategy using TicTokToe

```
play_game(TicTacToe(), dict(X=random_player, O=player(alphabeta_search)), verbose=True).utility
```

```

Player X move: (2, 0)
. . X
. . .
. . .

Player O move: (1, 1)
. . X
. O .
. . .

Player X move: (0, 0)
X . X
. O .
. . .

```

```

Player 0 move: (1, 0)
X O X
. O .
. . .

```

```

Player X move: (2, 1)
X O X
. O X
. . .

```

```

Player 0 move: (1, 2)
X O X
. O X
. O .

```

```

-1

```

```

play_game(TicTacToe(), dict(X=player(alphabeta_search), O=player(minimax_search)), verbose=True).utility

```

```

Player X move: (0, 1)
. . .
X . .
. . .

```

```

Player 0 move: (2, 1)
. . .
X . 0
. . .

```

```

Player X move: (1, 2)
. . .
X . 0
. X .

```

```

Player 0 move: (0, 0)
0 . .
X . 0
. X .

```

```

Player X move: (1, 1)
0 . .
X X 0
. X .

```

```

Player 0 move: (1, 0)
0 0 .
X X 0
. X .

```

```

Player X move: (2, 0)
0 0 X
X X 0
. X .

```

```

Player 0 move: (0, 2)
0 0 X
X X 0
0 X .

```

```

Player X move: (2, 2)
0 0 X
X X 0
0 X X

```

```

0

```