

Machine Handoff

Two machines, two Claude Code sessions. This is the split — what runs on the dev laptop, what runs on clubuntu, so neither session duplicates or waits on the other.

companion to docs 1-6 2026-08-16

– The repo is the only thing that crosses



Everything the dev laptop produces reaches clubuntu only through this path. Once the runner is registered (the one clubuntu-side task below), no further manual step on clubuntu is needed for any future release.

01 On the dev laptop — where the code lives

#	ACTION	COVERED IN
1	Create the empty private GitHub repo (browser)	Doc 1
2	<code>git init</code> , <code>commit</code> , <code>git remote add origin</code> , <code>git push -u origin main</code>	Doc 1
3	Edit <code>docker-compose.yml</code> — add <code>image:</code> alongside every <code>build:</code>	Doc 2
4	Create <code>docker-compose.deploy.yml</code> (image-only)	Doc 2
5	Create <code>.github/workflows/build.yml</code> and <code>deploy.yml</code>	Docs 3-4
6	Commit + push everything above	—

#	ACTION	COVERED IN
7	<i>Ongoing:</i> <code>git push origin main</code> to build, <code>git tag vX.Y.Z && git push origin vX.Y.Z</code> to deploy	Doc 6
8	<i>Ongoing:</i> edit <code>coder_commands.xlsx</code> , <code>scp</code> it to clubuntu when it changes	Doc 2 §05

02 On clubuntu — the other session

#	ACTION	COVERED IN
1	Confirm the real path of the existing deploy directory (has a working <code>.env</code>) — the one open placeholder in <code>deploy.yml</code>	Doc 4, plan §07
2	Confirm the registry is really unauthenticated, as assumed	plan §07
3	Create a dedicated, non-login user; add it to the <code>docker</code> group only	Doc 5
4	Get a runner registration token from GitHub (Settings → Actions → Runners)	Doc 5
5	Download the runner, run <code>config.sh</code> with that token, install as a systemd service	Doc 5
6	Confirm <code>coder_commands.xlsx</code> exists at the deploy path	Doc 2 §05
7	<i>Ongoing:</i> nothing — the runner picks up jobs on its own	—

– In one sentence

clubuntu's job is to register a self-hosted runner as a systemd service under a `docker`-group user and confirm one directory path — nothing else. All pipeline logic lives in files authored on the dev laptop and arrives via git; nothing is typed on clubuntu by hand once the runner exists.