

CSCB63 WINTER 2021

WEEK 2 - BALANCED TREES

Anna Bretscher

January 18, 2021

WHY BALANCED TREES?

- ▶ What is the worst case complexity of `insert`, `delete`, `search` in a binary search tree?

WHY BALANCED TREES?

- ▶ What is the worst case complexity of `insert`, `delete`, `search` in a binary search tree?
- ▶ $O(n)$

WHY BALANCED TREES?

- ▶ What is the worst case complexity of `insert`, `delete`, `search` in a binary search tree?
- ▶ $O(n)$
- ▶ We need to do something better...

WHY BALANCED TREES?

- ▶ What is the worst case complexity of `insert`, `delete`, `search` in a binary search tree?
- ▶ $O(n)$
- ▶ We need to do something better...
 - ▶ AVL trees

WHY BALANCED TREES?

- ▶ What is the worst case complexity of `insert`, `delete`, `search` in a binary search tree?
- ▶ $O(n)$
- ▶ We need to do something better...
 - ▶ AVL trees
 - ▶ B-trees

WHY BALANCED TREES?

- ▶ What is the worst case complexity of `insert`, `delete`, `search` in a binary search tree?
- ▶ $O(n)$
- ▶ We need to do something better...
 - ▶ AVL trees
 - ▶ B-trees
 - ▶ Splay trees

AVL TREES

AVL Trees were invented by *Adelson-Velskii* and *Landis* in 1962.

An *AVL tree* is similar to a *BST* in that it

- ▶ stores values in the *internal nodes* and

AVL TREES

AVL Trees were invented by *Adelson-Velskii* and *Landis* in 1962.

An *AVL tree* is similar to a *BST* in that it

- ▶ stores values in the *internal nodes* and
- ▶ has a property *relating* the values stored in a *subtree* to the values in the *parent node*.

AVL TREES

AVL Trees were invented by *Adelson-Velskii* and *Landis* in 1962.

An *AVL tree* is similar to a *BST* in that it

- ▶ stores values in the *internal nodes* and
- ▶ has a property *relating* the values stored in a *subtree* to the values in the *parent node*.

but different from a *BST* because

AVL TREES

AVL Trees were invented by *Adelson-Velskii* and *Landis* in 1962.

An *AVL tree* is similar to a *BST* in that it

- ▶ stores values in the *internal nodes* and
- ▶ has a property *relating* the values stored in a *subtree* to the values in the *parent node*.

but different from a *BST* because

- ▶ The height of an *AVL tree* is $O(\log n)$.

AVL TREES

AVL Trees were invented by *Adelson-Velskii* and *Landis* in 1962.

An *AVL tree* is similar to a *BST* in that it

- ▶ stores values in the *internal nodes* and
- ▶ has a property *relating* the values stored in a *subtree* to the values in the *parent node*.

but different from a *BST* because

- ▶ The height of an *AVL* tree is $O(\log n)$.
- ▶ Each *internal node* has a *balance property* equal to -1, 0, 1.

AVL TREES

AVL Trees were invented by *Adelson-Velskii* and *Landis* in 1962.


An *AVL tree* is similar to a *BST* in that it

- ▶ stores values in the *internal nodes* and
- ▶ has a property *relating* the values stored in a *subtree* to the values in the *parent node*.

but different from a *BST* because


- ▶ The height of an *AVL* tree is $O(\log n)$.
- ▶ Each *internal node* has a *balance property* equal to -1, 0, 1.
- ▶ Balance value = *height* of the *left* subtree - *height* of the *right* subtree.

AVL TREES



Q. What is the purpose of the *balance* property?


AVL TREES



Q. What is the purpose of the *balance* property?


A. Ensures that the *height* is always a function of $\log n$.

AVL TREES




- Q.** What is the purpose of the *balance* property?
- A.** Ensures that the *height* is always a function of $\log n$.
- Q.** What information will we need to store in order to update the *balance factors* easily?

AVL TREES




- Q. What is the purpose of the *balance* property?
- A. Ensures that the *height* is always a function of $\log n$.
- Q. What information will we need to store in order to update the *balance factors* easily?
- A. The *height* of the tree rooted at each node.

AVL OPERATIONS




Searching in an AVL tree is the *same* as a BST.

AVL OPERATIONS



Searching in an AVL tree is the *same* as a BST.
Consider *inserting* 6 into the tree above.

AVL OPERATIONS




Searching in an AVL tree is the *same* as a BST.

Consider *inserting* 6 into the tree above.

Q: What are the new *balance factors* in the tree after inserting 6?

A:

AVL OPERATIONS



Searching in an AVL tree is the *same* as a BST.


Consider *inserting* 6 into the tree above.

Q: What are the new *balance factors* in the tree after inserting 6?

A: 17 has value 0


AVL INSERTION

Q. Let's insert 35. What are the *balance factors* now?




AVL INSERTION

Q. Let's insert 35. What are the *balance factors* now?



AVL INSERTION


Q. Let's insert 35. What are the *balance factors* now?



A. 32 has -1, 17 has -2. 44 has 0.

AVL INSERTION

Q. Let's insert 35. What are the *balance factors* now?




A. 32 has -1, 17 has -2. 44 has 0.

Q. How do we solve this problem?

AVL INSERTION

Q. Let's insert 35. What are the *balance factors* now?




A. 32 has -1, 17 has -2. 44 has 0.

Q. How do we solve this problem?

- ▶ We resolve the problem by doing a **single rotation**. How should we *rotate*?

AVL INSERTION

Q. Let's insert 35. What are the *balance factors* now?




A. 32 has -1, 17 has -2. 44 has 0.

Q. How do we solve this problem?

- ▶ We resolve the problem by doing a **single rotation**. How should we *rotate*?
- ▶ Counter clock-wise. 17 comes down, 32 moves up.


AVL INSERTION

- We rotate counter clock-wise. 17 comes down, 32 moves up.



AVL INSERTION


- We rotate counter clock-wise. 17 comes down, 32 moves up.



Q. How do we update the *balance factors*?

AVL INSERTION

- We rotate counter clock-wise. 17 comes down, 32 moves up.




Q. How do we update the *balance factors*?

A. Update the heights first and then update balance factors.

AVL INSERTION


Now let's insert 45.



- Notice the *balance factors* now. How should we resolve the problem?

AVL INSERTION


Now let's insert **45**.



- ▶ Notice the *balance factors* now. How should we resolve the problem?
- A. Do a *single rotation* clock-wise about the **78**. 50 goes *up*, 78 *down*.

AVL INSERTION


Now let's insert **45**.



- Notice the *balance factors* now. How should we resolve the problem?
- A.** Do a *single rotation* clock-wise about the **78**. 50 goes *up*, 78 *down*.
- Q.** What happens to the subtree rooted at 62?


AVL INSERTION

Now let's insert **45**.




- Notice the *balance factors* now. How should we resolve the problem?
- A. Do a *single rotation* clock-wise about the **78**. 50 goes *up*, 78 *down*.
- Q. What happens to the subtree rooted at 62?
- A. It becomes the left subtree of 78.

AVL INSERTION




- Notice the updated *balance factors*.

AVL INSERTION




- Notice the updated *balance factors*.
- Let's insert 46 this time.

AVL INSERTION



Q. Can we do a rotation about 48?


AVL INSERTION




Q. Can we do a rotation about 48?

A. NO. Need a **double rotation**.

DOUBLE ROTATION




DOUBLE ROTATION



Q. How do we know that we need a *double rotation*?

DOUBLE ROTATION



Q. How do we know that we need a *double rotation*?

A. Have change in sign of the balance factors (+2, -1 or -2, +1).

DELETE

- ▶ If the key is a leaf node, delete and rebalance

DELETE

- ▶ If the key is a leaf node, delete and rebalance
- ▶ If the key is an internal node, replace with predecessor/successor and rebalance.

- ▶ Since the tree is balanced the height of an *AVL* tree is $O(\log n)$ (we will prove this shortly).

- ▶ Since the tree is balanced the height of an *AVL* tree is $O(\log n)$ (we will prove this shortly).
- ▶ This means *insert*, *delete* and *search* are all $O(\log n)$.

- ▶ Since the tree is balanced the height of an *AVL* tree is $O(\log n)$ (we will prove this shortly).
- ▶ This means *insert*, *delete* and *search* are all $O(\log n)$.
- ▶ Searching for the location to *insert* or *delete*, takes $O(\log n)$.

- ▶ Since the tree is balanced the height of an *AVL* tree is $O(\log n)$ (we will prove this shortly).
- ▶ This means *insert*, *delete* and *search* are all $O(\log n)$.
- ▶ Searching for the location to *insert* or *delete*, takes $O(\log n)$.
- ▶ *Rebalancing* takes at most $O(\log n)$.

AVL TREE HEIGHT

If there are n nodes, what is the *maximum* possible *height* h ?

Q. What is *another* way to say this in terms of the number of nodes n ?

A.

AVL TREE HEIGHT

If there are n nodes, what is the *maximum* possible *height* h ?

Q. What is *another* way to say this in terms of the number of nodes n ?

A. If the *height* is h , what is the *minimum* possible number of *nodes*?

AVL TREE HEIGHT

If there are n nodes, what is the *maximum* possible *height* h ?

Q. What is *another* way to say this in terms of the number of nodes n ?

A. If the *height* is h , what is the *minimum* possible number of *nodes*?

Let *minsize*(h) be the minimum number of nodes for an AVL tree of height h .

AVL TREE HEIGHT

Let *minsize*(*h*) be the minimum number of nodes for an AVL tree of height *h*.

Then, we can say:

$$\textit{minsize}(0) = 0$$

$$\textit{minsize}(1) = 1$$

$$\textit{minsize}(h+2) = 1 + \textit{minsize}(h+1) + \textit{minsize}(h)$$

Q. Does this *remind* you of anything?

A. Fibonacci...

AVL TREE HEIGHT

Let *minsize*(*h*) be the minimum number of nodes for an AVL tree of height *h*.

Then, we can say:

$$\text{minsize}(0) = 0$$

$$\text{minsize}(1) = 1$$

$$\text{minsize}(h+2) = 1 + \text{minsize}(h+1) + \text{minsize}(h)$$

Q. Does this *remind* you of anything?

A.

AVL TREE HEIGHT

Let *minsize*(*h*) be the minimum number of nodes for an AVL tree of height *h*.

Then, we can say:

$$\textit{minsize}(0) = 0$$

$$\textit{minsize}(1) = 1$$

$$\textit{minsize}(h+2) = 1 + \textit{minsize}(h+1) + \textit{minsize}(h)$$

Q. Does this *remind* you of anything?

A. Fibonacci...

AVL TREE HEIGHT

$$\text{minsize}(h+2) = 1 + \text{minsize}(h+1) + \text{minsize}(h)$$

and *Fibonacci*:

Can prove by *induction*:

$$\text{minsize}(h) = \text{fib}(h+2) - 1$$

and given the *golden ratio* $\phi = (\sqrt{5} + 1)/2 = 1.618\dots$ that

AVL TREE HEIGHT

$$\text{minsize}(h+2) = 1 + \text{minsize}(h+1) + \text{minsize}(h)$$

and *Fibonacci*:

Can prove by *induction*:

$$\text{minsize}(h) = \text{fib}(h+2) - 1$$

and given the *golden ratio* $\phi = (\sqrt{5} + 1)/2 = 1.618\dots$ that

$$\text{minsize}(h) = \frac{\phi^{h+2} - (1 - \phi)^{h+2}}{\sqrt{5}} - 1$$

AVL TREE HEIGHT

$$\begin{aligned} \text{minsize}(h) &= \frac{\phi^{h+2}}{\sqrt{5}} - \frac{(1-\phi)^{h+2}}{\sqrt{5}} - 1 \\ &> \frac{\phi^{h+2}}{\sqrt{5}} - 1 - 1 \end{aligned}$$

$$n \geq \text{minsize}(h) > \frac{\phi^{h+2}}{\sqrt{5}} - 1 - 1$$

Solving for h :

$$\frac{\phi^{h+2}}{\sqrt{5}} - 2 < n$$

$$\begin{aligned} h &< \frac{\lg(n+2)}{\lg \phi} + \frac{\sqrt{5}}{\lg \phi} + 2 \\ &= 1.44 \lg(n+2) + \text{constant} \\ &\in O(\lg n) \end{aligned}$$