FIB UPC UNIVERSITAT POLITÈCNICA DE CATALUNYA BARCELONATECH Facultat d'Informàtica de Barcelona

Timers
CCP Module

Dpt. Enginyeria de Sistemes, Automàtica i Informàtica Industrial

Introduction

- **Time** is represented by the count in a timer.

- There are many applications that cannot be implemented without a timer:

1. Event arrival time recording and comparison
2. Periodic interrupt generation
3. Pulse width and period measurement
4. Frequency and duty cycle measurement
5. Generation of waveforms with certain frequency and duty cycle
6. Time references
7. Event counting
8. Others

Generic Timers



Clock source (IN)

Pause (IN)

Rollover/Overflow (OUT)
Count limit reached

e.g. Configurable counter:

One count:
0, 1, 2, … , N-1, N, N, N, N

Cyclic count:
0, 1, 2, … , N-1, N, 0, 1, 2, … , N-1, N

The PIC18 Timer System

- A PIC18F45K22 microcontroller has up to 7 timers: Timer 0…Timer 6.

- Timer 0, Timer 1, Timer 3 and Timer 5 are 16-bit timers whereas Timer 2, Timer 4 and Timer 6 are 8-bit.

- When a timer rolls over, an interrupt may be generated if it is enabled.

- Timer 2, Timer 4 and Timer 6 use instruction cycle clock as the clock source whereas the other timers may also use external clock input as the clock source.

- Timer 0 is designed to act as a time base (core interrupt) while the other timers are in the peripheral group (alternate time base and CCP operation).

The PIC18 Timer0

- Can be configured as 8-bit or 16-bit

- Is a timer/counter depending upon the clock source.

- An interrupt may be requested when Timer0 rolls over from 0xFFFF to 0x0000.

- Operation is controlled by the T0CON register.

The PIC18 Timer0



Figure 8.1b Timer0 block diagram in 16-bit mode (redraw with permission of Microchip)

T0CON Register

values after Reset →

R/W-1	R/W-1	R/W-1	R/W-1	R/W-1	R/W-1	R/W-1	R/W-1
TMR0ON	T08BIT	T0CS	T0SE	PSA	TOPS<2:0>		
bit 7							bit 0

bit 7 **TMR0ON:** Timer0 On/Off Control bit
1 = Enables Timer0
0 = Stops Timer0

bit 6 **T08BIT**: Timer0 8-bit/16-bit Control bit
1 = Timer0 is configured as an 8-bit timer/counter
0 = Timer0 is configured as a 16-bit timer/counter

bit 5 **T0CS**: Timer0 Clock Source Select bit
1 = Transition on T0CKI pin
0 = Internal instruction cycle clock (CLKOUT)

bit 4 **T0SE**: Timer0 Source Edge Select bit
1 = Increment on high-to-low transition on T0CKI pin
0 = Increment on low-to-high transition on T0CKI pin

bit 3 **PSA**: Timer0 Prescaler Assignment bit
1 = TImer0 prescaler is NOT assigned. Timer0 clock input bypasses prescaler.
0 = Timer0 prescaler is assigned. Timer0 clock input comes from prescaler output.

bit 2-0 **T0PS<2:0>**: Timer0 Prescaler Select bits
111 = 1:256 prescale value
110 = 1:128 prescale value
101 = 1:64 prescale value
100 = 1:32 prescale value
011 = 1:16 prescale value
010 = 1:8 prescale value
001 = 1:4 prescale value
000 = 1:2 prescale value

The PIC18 Timer1/3/5

- Is a 16-bit timer/counter depending upon the clock source.

- An interrupt may be requested when TimerX rolls over from 0xFFFF to 0x0000.

- TimerX operation is controlled by the TxCON and TxGCON register.

- These timers have a number of frequency input sources and a complex gate enable circuitry (if TMRxGE=1)

- These timers can be used to create time delays and measure the frequency of an unknown signal (using the CCP modules).

The PIC18 Timer1/3/5



The PIC18 Timer1/3/5



TxCON Register (x=1/3/5)

R/W-0/u	R/W-0/u	R/W-0/u	R/W-0/u	R/W-0/u	R/W-0/u	R/W-0/0	R/W-0/u
TMRxCS<1:0>		TxCKPS<1:0>		TxSOSCEN	$\overline{\text{TxSYNC}}$	TxRD16	TMRxON
bit 7							bit 0

bit 7-6 **TMRxCS<1:0>:** Timer1/3/5 Clock Source Select bits
11 = Reserved. Do not use.
10 = Timer1/3/5 clock source is pin or oscillator:
If TxSOSCEN = 0:
External clock from TxCKI pin (on the rising edge)
If TxSOSCEN = 1:
Crystal oscillator on SOSCI/SOSCO pins
01 = Timer1/3/5 clock source is system clock (FOSC)
00 = Timer1/3/5 clock source is instruction clock (FOSC/4)

bit 5-4 **TxCKPS<1:0>:** Timer1/3/5 Input Clock Prescale Select bits
11 = 1:8 Prescale value
10 = 1:4 Prescale value
01 = 1:2 Prescale value
00 = 1:1 Prescale value

bit 3 **TxSOSCEN:** Secondary Oscillator Enable Control bit
1 = Dedicated Secondary oscillator circuit enabled
0 = Dedicated Secondary oscillator circuit disabled

bit 2 **$\overline{\text{TxSYNC}}$:** Timer1/3/5 External Clock Input Synchronization Control bit
TMRxCS<1:0> = 1X
1 = Do not synchronize external clock input
0 = Synchronize external clock input with system clock (FOSC)

TMRxCS<1:0> = 0X
This bit is ignored. Timer1/3/5 uses the internal clock when TMRxCS<1:0> = 1X.

bit 1 **TxRD16:** 16-Bit Read/Write Mode Enable bit
1 = Enables register read/write of Timer1/3/5 in one 16-bit operation
0 = Enables register read/write of Timer1/3/5 in two 8-bit operation

bit 0 **TMRxON:** Timer1/3/5 On bit
1 = Enables Timer1/3/5
0 = Stops Timer1/3/5
Clears Timer1/3/5 Gate flip-flop

TxGCON Register (x=1/3/5)

REGISTER 12-2: TXGCON: TIMER1/3/5 GATE CONTROL REGISTER

R/W-0/u	R/W-0/u	R/W-0/u	R/W-0/u	R/W/HC-0/u	R-x/x	R/W-0/u	R/W-0/u
TMRxGE	TxGPOL	TxGTM	TxGSPM	TxGGO/$\overline{\text{DONE}}$	TxGVAL	TxGSS<1:0>	
bit 7							bit 0

Legend:		
R = Readable bit	W = Writable bit	U = Unimplemented bit, read as '0'
u = Bit is unchanged	x = Bit is unknown	-n/n = Value at POR and BOR/Value at all other Resets
'1' = Bit is set	'0' = Bit is cleared	HC = Bit is cleared by hardware

bit 7 **TMRxGE:** Timer1/3/5 Gate Enable bit
If TMRxON = 0:
This bit is ignored
If TMRxON = 1:
1 = Timer1/3/5 counting is controlled by the Timer1/3/5 gate function
0 = Timer1/3/5 counts regardless of Timer1/3/5 gate function

TMRxGE=0 !!!

bit 6 **TxGPOL:** Timer1/3/5 Gate Polarity bit
1 = Timer1/3/5 gate is active-high (Timer1/3/5 counts when gate is high)
0 = Timer1/3/5 gate is active-low (Timer1/3/5 counts when gate is low)

bit 5 **TxGTM:** Timer1/3/5 Gate Toggle Mode bit
1 = Timer1/3/5 Gate Toggle mode is enabled
0 = Timer1/3/5 Gate Toggle mode is disabled and toggle flip-flop is cleared
Timer1/3/5 gate flip-flop toggles on every rising edge.

bit 4 **TxGSPM:** Timer1/3/5 Gate Single-Pulse Mode bit
1 = Timer1/3/5 gate Single-Pulse mode is enabled and is controlling Timer1/3/5 gate
0 = Timer1/3/5 gate Single-Pulse mode is disabled

bit 3 **TxGGO/$\overline{\text{DONE}}$:** Timer1/3/5 Gate Single-Pulse Acquisition Status bit
1 = Timer1/3/5 gate single-pulse acquisition is ready, waiting for an edge
0 = Timer1/3/5 gate single-pulse acquisition has completed or has not been started
This bit is automatically cleared when TxGSPM is cleared.

bit 2 **TxGVAL:** Timer1/3/5 Gate Current State bit
Indicates the current state of the Timer1/3/5 gate that could be provided to TMRxH:TMRxL.
Unaffected by Timer1/3/5 Gate Enable (TMRxGE).

bit 1-0 **TxGSS<1:0>:** Timer1/3/5 Gate Source Select bits
00 = Timer1/3/5 Gate pin
01 = Timer2/4/6 Match PR2/4/6 output (See Table 12-5 for proper timer match selection)
10 = Comparator 1 optionally synchronized output (sync_C1OUT)
11 = Comparator 2 optionally synchronized output (sync_C2OUT)

The PIC18 Timer2/4/6

- There are three 8-bit timers with instruction clock source Fcy (Fosc/4) and prescaler and postscaler block logic.
- Controlled by TxCON and related to PRx registers.
- An interrupt may be requested when Timer value matches PRx
- They can be a source for PWM signals (CCP modules).

FIGURE 13-1: TIMER2/4/6 BLOCK DIAGRAM



TxCON Register (x=2/4/6)

REGISTER 13-1: TxCON: TIMER2/TIMER4/TIMER6 CONTROL REGISTER

U-0	R/W-0	R/W-0	R/W-0	R/W-0	R/W-0	R/W-0	R/W-0
—	TxOUTPS<3:0>				TMRxON	TxCKPS<1:0>	
bit 7							bit 0

bit 7 **Unimplemented:** Read as '0'

bit 6-3 **TxOUTPS<3:0>:** TimerX Output Postscaler Select bits

0000 = 1:1 Postscaler
0001 = 1:2 Postscaler
0010 = 1:3 Postscaler
0011 = 1:4 Postscaler
0100 = 1:5 Postscaler
0101 = 1:6 Postscaler
0110 = 1:7 Postscaler
0111 = 1:8 Postscaler
1000 = 1:9 Postscaler
1001 = 1:10 Postscaler
1010 = 1:11 Postscaler
1011 = 1:12 Postscaler
1100 = 1:13 Postscaler
1101 = 1:14 Postscaler
1110 = 1:15 Postscaler
1111 = 1:16 Postscaler

bit 2 **TMRxON:** TimerX On bit

1 = TimerX is on
0 = TimerX is off

bit 1-0 **TxCKPS<1:0>:** Timer2-type Clock Prescale Select bits

00 = Prescaler is 1
01 = Prescaler is 4
1x = Prescaler is 16

The PIC18 CCP units

- A PIC18 device may have one, two, or **five (K22)** CCP modules.
- CCP stands for **Capture**, **Compare**, and **Pulse Width Modulation**.
- Each CCP module can be configured to perform capture, compare, or PWM function.
- In **capture** operation, the CCP module copy the contents of a 16 bit timer into a capture register on a signal edge.
- In **compare** operation, the CCP module compares the contents of a CCPR register with that of a Timer (1, 3 or 5) in every clock cycle. When these two registers are equal, the associated pin may be pulled to high, or low, or toggled.
- In **PWM** mode, the CCP module can be configured to generate a waveform with certain frequency and duty cycle. Timers 2/4/6 are related with the PWM hardware.

Capture/Compare/PWM (CCP) Modules

- PIC18F45K22 has 5 CCP Modules.
- Each CCP module requires the use of timer resource.
- In capture or compare mode, the CCP module may use either Timer1, Timer3 or Timer5 to operate.
- In PWM mode, either Timer2, Timer4 or Timer6 may be used.
- The operation of a CCP module is controlled by the CCPxCON register (to select the mode), the CCPTMRS0 and CCPTMRS1 registers (to select the operating timer) and the 16-bits data register CCPRx (CCPRxH and CCPRxL).
- A device pin (CCPx pin) can be associated to CCP module operation (with appropriate TRIS configuration).

CCPxCON Register

14.5 Register Definitions: ECCP Control

REGISTER 14-1: CCPxCON: STANDARD CCPx CONTROL REGISTER

U-0	U-0	R/W-0	R/W-0	R/W-0	R/W-0	R/W-0	R/W-0
—	—	DCxB<1:0>		CCPxM<3:0>			
bit 7							bit 0

Legend:		
R = Readable bit	W = Writable bit	U = Unimplemented bit, read as '0'
u = Bit is unchanged	x = Bit is unknown	-n/n = Value at POR and BOR/Value at all other Reset
'1' = Bit is set	'0' = Bit is cleared	

bit 7-6 **Unused**

bit 5-4 **DCxB<1:0>:** PWM Duty Cycle Least Significant bits

Capture mode:
Unused

Compare mode:
Unused

PWM mode:
These bits are the two LSbs of the PWM duty cycle. The eight MSbs are found in CCPRxL.

bit 3-0 **CCPxM<3:0>:** ECCPx Mode Select bits

0000 = Capture/Compare/PWM off (resets the module)
0001 = Reserved
0010 = Compare mode: toggle output on match
0011 = Reserved

0100 = Capture mode: every falling edge
0101 = Capture mode: every rising edge
0110 = Capture mode: every 4th rising edge
0111 = Capture mode: every 16th rising edge

1000 = Compare mode: set output on compare match (CCPx pin is set, CCPxIF is set)
1001 = Compare mode: clear output on compare match (CCPx pin is cleared, CCPxIF is set)
1010 = Compare mode: generate software interrupt on compare match (CCPx pin is unaffected, CCPxIF is set)
1011 = Compare mode: Special Event Trigger (CCPx pin is unaffected, CCPxIF is set)
TimerX (selected by CxTSEL bits) is reset
ADON is set, starting A/D conversion if A/D module is enabled(1)
11xx =: PWM mode

Note 1: This feature is available on CCP5 only.

CCPTMRS0/1 (Timer select) Register

REGISTER 14-3: CCPTMRS0: PWM TIMER SELECTION CONTROL REGISTER 0

R/W-0	R/W-0	U-0	R/W-0	R/W-0	U-0	R/W-0	R/W-0
C3TSEL<1:0>		—	C2TSEL<1:0>		—	C1TSEL<1:0>	
bit 7							bit 0

bit 7-6 **C3TSEL<1:0>:** CCP3 Timer Selection bits
00 = CCP3 – Capture/Compare modes use Timer1, PWM modes use Timer2
01 = CCP3 – Capture/Compare modes use Timer3, PWM modes use Timer4
10 = CCP3 – Capture/Compare modes use Timer5, PWM modes use Timer6
11 = Reserved

bit 5 **Unused**

bit 4-3 **C2TSEL<1:0>:** CCP2 Timer Selection bits
00 = CCP2 – Capture/Compare modes use Timer1, PWM modes use Timer2
01 = CCP2 – Capture/Compare modes use Timer3, PWM modes use Timer4
10 = CCP2 – Capture/Compare modes use Timer5, PWM modes use Timer6
11 = Reserved

bit 2 **Unused**

bit 1-0 **C1TSEL<1:0>:** CCP1 Timer Selection bits
00 = CCP1 – Capture/Compare modes use Timer1, PWM modes use Timer2
01 = CCP1 – Capture/Compare modes use Timer3, PWM modes use Timer4
10 = CCP1 – Capture/Compare modes use Timer5, PWM modes use Timer6
11 = Reserved

REGISTER 14-4: CCPTMRS1: PWM TIMER SELECTION CONTROL REGISTER 1

U-0	U-0	U-0	U-0	R/W-0	R/W-0	R/W-0	R/W-0
—	—	—	—	C5TSEL<1:0>		C4TSEL<1:0>	
bit 7							bit 0

Legend:		
R = Readable bit	W = Writable bit	U = Unimplemented bit, read as '0'
u = Bit is unchanged	x = Bit is unknown	-n/n = Value at POR and BOR/Value at all other Resets
'1' = Bit is set	'0' = Bit is cleared	

bit 7-4 **Unimplemented:** Read as '0'

bit 3-2 **C5TSEL<1:0>:** CCP5 Timer Selection bits
00 = CCP5 – Capture/Compare modes use Timer1, PWM modes use Timer2
01 = CCP5 – Capture/Compare modes use Timer3, PWM modes use Timer4
10 = CCP5 – Capture/Compare modes use Timer5, PWM modes use Timer6
11 = Reserved

bit 1-0 **C4TSEL<1:0>:** CCP4 Timer Selection bits
00 = CCP4 – Capture/Compare modes use Timer1, PWM modes use Timer2
01 = CCP4 – Capture/Compare modes use Timer3, PWM modes use Timer4
10 = CCP4 – Capture/Compare modes use Timer5, PWM modes use Timer6
11 = Reserved

Capture Function



Gives a reference on the instant in which the event takes place
(Application: measure the period of a given signal)

Capture Mode

- Main use of CCP is to capture **event** arrival time

- An event is represented by a signal edge.

The PIC18 event can be one of the following:

1. every falling edge
2. every rising edge
3. every 4th rising edge
4. every 16th rising edge

Capture Unit

FIGURE 14-1: CAPTURE MODE OPERATION BLOCK DIAGRAM



CCPx Pin must be configured as an Input

TimerX must be active and configured (prescaler, CLK source) properly.

The five capture units operate independently

Compare Function

Compare Function



Generates equally spaced time intervals
(Application: Delays, Pulse Trains)

Compare Mode

- 16-bit CCPRx register is compared against one of the Timers(1/3/5).
- When they match, one of the following actions may occur on the associated CCPx pin:

1. driven high
2. driven low
3. toggle output
4. remains unchanged

Software Interrupt Mode

When Generate Software Interrupt mode is chosen (1010), the CCPx module does not assert control of the CCPx pin.

Special Event Trigger

The CCPx modules can also generate this event (mode 1011) to reset TMR1/3/5 depending on which timer is the base timer. When this mode is selected CCP5 will start an ADC conversion, if the ADC is enabled.

Compare Unit

FIGURE 14-2: COMPARE MODE OPERATION BLOCK DIAGRAM



CCPx Pin must be configured as an Output

TimerX must be active and configured (prescaler, CLK source) properly.

Example: use CCP Compare to Generate Sound



Figure 8.22 Circuit connection for siren generation

Pitch table

	Frequency (Hz)							
Note	Octave 0	Octave 1	Octave 2	Octave 3	**Octave 4**	Octave 5	Octave 6	Octave 7
C	16.351	32.703	65.406	130.813	**261.626**	523.251	1046.502	2093.005
C#,Db	17.324	34.646	69.296	138.591	**277.183**	554.365	1100.731	2217.461
D	18.354	36.708	73.416	146.832	**293.665**	587.330	1174.659	2349.318
D#,Eb	19.445	38.891	77.782	155.563	**311.127**	622.254	1244.508	2489.016
E	20.061	41.203	82.407	164.814	**329.626**	659.255	1318.510	2367.021
F	21.827	43.654	87.307	174.614	**349.228**	698.456	1396.913	2637.021
F#,Gb	23.124	46.249	92.449	184.997	**369.994**	739.989	1474.978	2959.955
G	24.499	48.999	97.999	195.998	**391.995**	783.991	1567.982	3135.964
G#,Ab	25.956	51.913	103.826	207.652	**415.305**	830.609	1661.219	3322.438
A	**27.500**	**55.000**	**110.000**	**220.000**	**440.000**	**880.000**	**1760.000**	**3520.000**
A#,Bb	29.135	58.270	116.541	233.082	**466.164**	932.326	1664.655	3729.310
B	30.868	61.735	123.471	246.942	**493.883**	987.767	1975.533	3951.066

Example code:

For the circuit in Figure 8.22, write a program to generate a simple song assuming that f_{OSC} = 4MHz.

Solution:
Two tables are used by the program. 1) Table of numbers to be added to CCPR1 register to generate the waveform with the desired frequency. 2) Table of numbers that select the duration of each note. CCP1 module is used to generate te signal -compare mode toggle CCP1 pin on match-. TIMER0 is used for note duration.

Example XC8

```
#include   <xc.h>
#define    base      3125  // counter count to create 0.1 s delay
#define    NOTES     38    // total notes in the song to be played
#define    C4        0x777 // semioperiod
#define    F4        0x598 // for each
#define    G4        0x4FC // note freq
#define    A4        0x470
#define    B4        0x3F4
#define    C5        0x3BC
#define    D5        0x353
#define    F5        0x2CC

unsigned int half_cycle;

const unsigned int per_arr[38]={ C4,A4,G4,A4,F4,C4,C4,C5,
                                 B4,C5,A4,A4,F4,D5,D5,D5,
                                 C5,A4,C5,C5,B4,A4,B4,C5,
                                 A4,F4,D5,F5,D5,C5,A4,C5,
                                 C5,B4,A4,B4,C5,A4};

const unsigned char wait[38] = { 3,5,3,3,5,3,3,5,
                                 3,3,5,3,3,5,3,3,
                                 5,3,3,3,2,2,3,3,
                                 6,3,5,3,3,5,3,3,
                                 3,2,2,3,3,6};
```

```
void  delay (unsigned char xc);

void interrupt high_ISR(void)
{
      if (PIE1bits.CCP1IE && PIR1bits.CCP1IF) {
            PIR1bits.CCP1IF = 0;
            CCPR1 += half_cycle;
      }
}


void interrupt low_priority low_ISR (void)
{
}
```

```
void main (void)
{    int i, j;

     TRISCbits.TRISC2 = 0;   /* configure CCP1 pin for output */
     T3CON = 0x81;   /* enables Timer3 in 16-bit mode, Timer1  for CCP1 time base */
     T1CON = 0x81;   /* enable Timer1 in 16-bit mode */
     CCP1CON = 0x02;   /* CCP1 compare mode, pin toggle on match */
     IPR1bits.CCP1IP = 1;   /* set CCP1 interrupt to high priority */
     PIR1bits.CCP1IF = 0;   /* clear CCP1IF flag */
     PIE1bits.CCP1IE = 1;   /* enable CCP1 interrupt */
     INTCON |= 0xC0;       /* enable high priority interrupt */

     for (j = 0; j < 3; j++) {     /* Play song several times */
          i = 0;
          half_cycle = per_arr[0];
          CCPR1 = TMR1 + half_cycle;
          while (i < NOTES) {
               half_cycle = per_arr[i];   /* get the cycle count for half period of the note */
               delay (wait[i]);            /* stay for the duration of the note */
               i++;
          }
          INTCON &= 0x3F;   /* disable interrupt */
          delay (11);               /* Pause before replay song */
          INTCON |= 0xC0;    /* re-enable interrupt */
     }
}
```

```
/* The following function runs on a PIC18 demo board running with a 4 MHz crystal  */
/* oscillator. The parameter xc specifies the amount of delay to be created        */
/* ------------------------------------------------------------------------------------------------*/
void delay (unsigned char xc)
{
     switch (xc){
          case 1:        /* create 0.1 second delay (sixteenth note) */
               T0CON = 0x84; /* enable TMR0 with prescaler set to 32 */
               TMR0 = 0xFFFF - base; /* set TMR0 to this value so it overflows in 0.1 second */
               INTCONbits.TMR0IF = 0;
               while (!INTCONbits.TMR0IF);
               break;
          case 2:        /* create 0.2 second delay (eighth note) */
               T0CON = 0x84; /* set prescaler to Timer0 to 32 */
               TMR0 = 0xFFFF - 2*base; /* set TMR0 to this value so it overflows in 0.2 second */
               INTCONbits.TMR0IF = 0;
               while (!INTCONbits.TMR0IF);
               break;
          case 3:        /* create 0.4 seconds delay (quarter note) */
               T0CON = 0x84; /* set prescaler to Timer0 to 32 */
               TMR0 = 0xFFFF - 4*base; /* set TMR0 to this value so it overflows in 0.4 second */
               INTCONbits.TMR0IF = 0;
               while (!INTCONbits.TMR0IF);
               break;
```

```
            case 4:         /* create 0.6 s delay (3 eighths note) */
                    T0CON = 0x84; /* set prescaler to Timer0 to 32 */
                    TMR0 = 0xFFFF - 6*base; /* set TMR0 to this value so it overflows in 0.6 second */
                    INTCONbits.TMR0IF = 0;
                    while (!INTCONbits.TMR0IF);
                    break;
            case 5:         /* create 1.2 second delay (3 quarter note) */
                    T0CON = 0x84; /* set prescaler to Timer0 to 32 */
                    TMR0 = 0xFFFF - 12*base; /* set TMR0 to this value so it overflows in 1.2 second */
                    INTCONbits.TMR0IF = 0;
                    while (!INTCONbits.TMR0IF);
                    break;
            case 6:         /* create 1.6 second delay (full note) */
                    T0CON = 0x84; /* set prescaler to Timer0 to 32 */
                    TMR0 = 0xFFFF - 16*base; /* set TMR0 to this value so it overflows in 1.6 second */
                    INTCONbits.TMR0IF = 0;
                    while (!INTCONbits.TMR0IF);
                    break;

            default:
            break;
        }
}
```

PWM function

Pulse Width Modulation (PWM) Function

Generates (automatically) a PWM signal



Period = T_{PWM}

Frecuency, $F_{PWM} = 1/ T_{PWM}$

Duty Cycle = $(T_{ON} / T_{PWM}) \times 100$

PWM Mode

FIGURE 14-4: SIMPLIFIED PWM BLOCK DIAGRAM





Note 1: The 8-bit timer TMRx register is concatenated with the 2-bit internal system clock (Fosc), or 2 bits of the prescaler, to create the 10-bit time base.

2: In PWM mode, CCPRxH is a read-only register.

Period & Duty cycle

Pwm formulas:

EQUATION 14-1: PWM PERIOD

$$PWM\ Period = [(PRx) + 1] \bullet 4 \bullet Tosc \bullet (TMRx\ Prescale\ Value)$$

Note 1: Tosc = 1/Fosc

EQUATION 14-2: PULSE WIDTH

$$Pulse\ Width = (CCPRxL:CCPxCON<5:4>) \bullet Tosc \bullet (TMRx\ Prescale\ Value)$$

EQUATION 14-4: PWM RESOLUTION

$$Resolution = \frac{\log[4(PRx + 1)]}{\log(2)}\ bits$$

EQUATION 14-3: DUTY CYCLE RATIO

$$Duty\ Cycle\ Ratio = \frac{(CCPRxL:CCPxCON<5:4>)}{4(PRx + 1)}$$

TABLE 14-7: EXAMPLE PWM FREQUENCIES AND RESOLUTIONS (Fosc = 32 MHz)

PWM Frequency	1.95 kHz	7.81 kHz	31.25 kHz	125 kHz	250 kHz	333.3 kHz
Timer Prescale (1, 4, 16)	16	4	1	1	1	1
PRx Value	0xFF	0xFF	0xFF	0x3F	0x1F	0x17
Maximum Resolution (bits)	10	10	10	8	7	6.6

TABLE 14-8: EXAMPLE PWM FREQUENCIES AND RESOLUTIONS (Fosc = 20 MHz)

PWM Frequency	1.22 kHz	4.88 kHz	19.53 kHz	78.12 kHz	156.3 kHz	208.3 kHz
Timer Prescale (1, 4, 16)	16	4	1	1	1	1
PRx Value	0xFF	0xFF	0xFF	0x3F	0x1F	0x17
Maximum Resolution (bits)	10	10	10	8	7	6.6

TABLE 14-9: EXAMPLE PWM FREQUENCIES AND RESOLUTIONS (Fosc = 8 MHz)

PWM Frequency	1.22 kHz	4.90 kHz	19.61 kHz	76.92 kHz	153.85 kHz	200.0 kHz
Timer Prescale (1, 4, 16)	16	4	1	1	1	1
PRx Value	0x65	0x65	0x65	0x19	0x0C	0x09
Maximum Resolution (bits)	8	8	8	6	5	5

Programming recipe.

1. Disable the CCPx pin output driver by setting the associated TRIS bit.
2. Select the 8-bit TimerX resource, (Timer2, Timer4 or Timer6) to be used for PWM generation by setting the CxTSEL<1:0> bits in the CCPTMRSx register.(1)
3. Load the PRx register for the selected TimerX with the PWM period value.
4. Configure the CCP module for the PWM mode by loading the CCPxCON register with appropriate values.
5. Load the CCPRxL register and the DCxB<1:0> bits of the CCPxCON register, with the PWM duty cycle value.
6. Configure and start the 8-bit TimerX resource:
   - Clear the TMRxIF interrupt flag bit of the PIR2 or PIR4 register.
   - Configure the TxCKPS bits of the TxCON register with the Timer prescale value.
   - Enable the Timer by setting the TMRxON bit of the TxCON register.
7. Enable PWM output pin:
   - Wait until the Timer overflows and the TMRxIF bit of the PIR2 or PIR4 register is set.
   - Enable the CCPx pin output driver by clearing the associated TRIS bit.

Light dimmer



Figure 8.25 Using PWM to control the brightness of a light bulb

DC Motor Control

- DC motor speed is regulated by controlling its average driving voltage. The higher the voltage, the faster the motor rotates.
- Changing motor direction can be achieved by reversing the driving voltage.
- Motor braking can be performed by reversing the driving voltage for certain length of time.
- Most PIC18 devices have PWM functions that can be used to drive DC motors.
- Many DC motors operate with 5 V supply.
- DC motors require large amount of current to operate. Special driver circuits are needed for this purpose.
- A simplified DC motor control circuit is shown in Figure 8.26.



Figure 8.26A simplified circuit for DC motor control

DC Motor Driver



(a) Pin Assignment (b) Motor connection

Figure 8.27 Motor driver L293 pin assignment and motor connection

Speed sensor



Figure 8.28 The output waveform of the Hall-effect transistor

Motor control system



Figure 8.29 Schematic of a PIC18-based motor-control system

Clockwise or counterclockwise Rotation



Figure 8.30 The L293 motor driver

Servomotors