

Schletter, Inc.		30° Tilt w/ Seismic Design
HCV	Standard FS Racking System	
	Representative Calculations - ASCE 7-10	

1. INTRODUCTION

1.1 Project Description

The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. FS ground mount system.

1.2 Construction

Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to galvanized steel posts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

	Maximum		Minimum
Height =	2000 mm	Height =	1900 mm
Width =	1050 mm	Width =	970 mm
Dead Load =	3.00 psf	Dead Load =	1.75 psf

Modules Per Row =	2
Module Tilt =	30°
Maximum Height Above Grade =	3 ft



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

1.3 Technical Codes

- ASCE 7-10 - Chapter 26-31, Wind Loads
- ASCE 7-10 - Chapter 7, Snow Loads
- ASCE 7-10 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2012, 2015
- Aluminum Design Manual, Eighth Edition, 2005

2. LOAD ACTIONS

2.1 Permanent Loads

g_{MAX} =	3.00 psf	*Self-weight of the PV modules.*
g_{MIN} =	1.75 psf	

2.2 Snow Loads

Ground Snow Load, P_g =	30.00 psf	
Sloped Roof Snow Load, P_s =	16.49 psf	*(ASCE 7-10, Eq. 7.4-1)*
I_s =	1.00	
C_s =	0.73	
C_e =	0.90	
C_t =	1.20	

2.3 Wind Loads

Design Wind Speed, V =	140 mph		Exposure Category = C
Height <	15 ft		Importance Category = II
Peak Velocity Pressure, q_z =	30.77 psf	*Including the gust factor, G=0.85. (ASCE 7-10, Eq. 27.3-1)*	

Pressure Coefficients

$Cf+_{TOP}$ =	1.15	*(Pressure)*	*Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0510-e. Negative forces are applied away from the surface.*
$Cf+_{BOTTOM}$ =	1.85		
$Cf-_{TOP}$ =	-2.3	*(Suction)*	
$Cf-_{BOTTOM}$ =	-1.1		

2.4 Seismic Loads

S_S =	2.50	R =	1.25	*ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.*
S_{DS} =	1.67	C_S =	0.8	
S_1 =	1.00	ρ =	1.3	
S_{D1} =	1.00	Ω =	1.25	
T_a =	0.08	C_d =	1.25	

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.5W
1.2D + 1.0W + 0.5S
0.9D + 1.0W [M]
1.54D + 1.3E + 0.2S [R]
0.56D + 1.3E [R]
1.54D + 1.25E + 0.2S [O]
0.56D + 1.25E [O]

(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S
1.0D + 0.6W
1.0D + 0.75L + 0.45W + 0.75S
0.6D + 0.6W [M]
1.238D + 0.875E [O]
1.1785D + 0.65625E + 0.75S [O]
0.362D + 0.875E [O]

(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)

[M] *Uses the minimum allowable module dead load.*
[R] *Include redundancy factor of 1.3.*
[O] *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location
M10	Top
M11	Mid-Top
M12	Mid-Bottom
M13	Bottom

Posts	Location
M2	Outer
M5	Inner
M8	Outer

Girders	Location
M1	Outer
M4	Inner
M7	Outer

Reactions	Location
N9	Outer
N19	Inner
N29	Outer

Struts	Location
M3	Outer
M6	Inner
M9	Outer

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type =	**S1.5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	90	in
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	25.07	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	23.08	ksi
S_y =	1.33	in^3
S_x =	0.6	in^3
E =	10100	ksi
I_y =	2.16	in^4
I_x =	1.07	in^4
A =	1.25	in^2
g =	1.50	lbs/ft
M_y =	1.431	k-ft
M_z =	0.081	k-ft
$M_{y\ allowable}$ =	2.779	k-ft
$M_{z\ allowable}$ =	1.154	k-ft
Utilization =	59%	



DETAIL VIEW

4.2 Girder Design

Loads from purlins are transferred to the posts using an inclined girder, which is connected to the steel post. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type =	**T5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	81.77	in
$\Phi F_{ty\ AXIAL}$ =	30.80	ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	30.06	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	31.56	ksi
S_y =	1.98	in^3
S_x =	1.32	in^3
E =	10100	ksi
I_y =	4.74	in^4
I_x =	1.83	in^4
A =	1.93	in^2
g =	2.32	lbs/ft
M_y =	4.112	k-ft
M_z =	0.000	k-ft
P_n =	1.491	k
$M_{y\ allowable}$ =	4.960	k-ft
$M_{z\ allowable}$ =	3.472	k-ft
$P_{n\ allowable}$ =	59.439	k
Utilization =	85%	



DETAIL VIEW

4.3 Strut Design

The aluminum strut connects a portion of the girder to the galvanized steel post. Girder forces are then transferred down through the strut into the post. The strut is attached with single M10 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	74.80	in
$\Phi F_{ty\ AXIAL}$ =	9.61	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.007	k-ft
M_z =	0.000	k-ft
P_n =	4.713	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	9.441	k
Utilization =	50%	



4.4 Post Design

Galvanized steel posts are a roll formed steel section, that are either ram driven into the ground or placed in a concrete foundation at a defined depth. Embedment depths will be provided on the structural drawings or through a geotechnical testing report. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Post Type =	**FG8**	
Steel Type =	J2340	
F_{ty} =	60	ksi
L_b =	89.60	in
Φ =	0.90	
ΦF_{ty} =	54.00	ksi
S_y =	3.46	in^3
S_x =	1.55	in^3
E =	29000	ksi
I_y =	10.94	in^4
I_x =	4.31	in^4
A =	2.23	in^2
g =	7.59	lbs/ft
M_y =	12.043	k-ft
M_z =	0.000	k-ft
P_r =	-5.095	k
$M_{y\ allowable}$ =	19.207	k-ft
$M_{z\ allowable}$ =	14.389	k-ft
P_c =	25.874	k
Utilization =	78%	



5. FOUNDATION DESIGN CALCULATIONS

5.1 Rammed Post Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete footing design.

Maximum Tensile Load =	6.59	k
Maximum Lateral Load =	3.96	k

5.2 Design of Drilled Shaft Foundations

The galvanized steel post is to be embedded into a cylindrical drilled shaft foundation. For the purpose of design, the post is considered to be fixed to the ground. The applicable lateral force, uplift, and compression resistance checks are seen below.

5.3 Lateral Force Resistance

The equivalent lateral force is applied at the top of the post to determine the required embedment depth. A lateral soil bearing capacity for clay is assumed. Footing is unrestrained at ground level. (IBC, Eq. 18-1)

Lateral Force @ Top of Pole, P =	0.79	k
Height of Pole Above Grade, H =	6.47	ft
Diameter of Pole Footing, B =	2.00	ft
Lateral Soil Bearing Capacity, S =	0.10	ksf/ft
Isolated Pole Factor, F =	2	
First Trial Depth, D =	3.25	ft

Lateral Bearing @ Bottom =	S_3
Lateral Bearing @ D/3 =	S_1
Required Depth =	D

$$S_3 = Min\ (D, 12')$$

$$S_1 = Min\left(\frac{D}{3}, 12'\right)$$

$$A = 2.34\ P/S_1 B$$

$$D = \left\{0.5A\left(1+\sqrt{1+\left(\frac{4.36\ H}{A}\right)}\right)\right\}$$



Non-Constrained

Lateral Force @ Top of Pole, P =	0.79	k
Height of Pole Above Grade, H =	6.47	ft
Diameter of Pole Footing, B =	2.00	ft
Lateral Soil Bearing Capacity, S =	0.20	ksf/ft

1st Trial @ D_1 =	3.25	ft
Lateral Soil Bearing @ D/3, S_1 =	0.22	ksf
Lateral Soil Bearing @ D, S_3 =	0.65	ksf
Constant 2.34P/(S_1B), A =	4.27	
Required Footing Depth, D =	8.02	ft

2nd Trial @ D_2 =	5.64	ft
Lateral Soil Bearing @ D/3, S_1 =	0.38	ksf
Lateral Soil Bearing @ D, S_3 =	1.13	ksf
Constant 2.34P/(S_1B), A =	2.46	
Required Footing Depth, D =	5.58	ft

3rd Trial @ D_3 =	5.61	ft
Lateral Soil Bearing @ D/3, S_1 =	0.37	ksf
Lateral Soil Bearing @ D, S_3 =	1.12	ksf
Constant 2.34P/(S_1B), A =	2.48	
Required Footing Depth, D =	5.60	ft

4th Trial @ D_4 =	5.60	ft
Lateral Soil Bearing @ D/3, S_1 =	0.37	ksf
Lateral Soil Bearing @ D, S_3 =	1.12	ksf
Constant 2.34P/(S_1B), A =	2.48	
Required Footing Depth, D =	5.60	ft

5th Trial @ D_5 =	5.60	ft
Lateral Soil Bearing @ D/3, S_1 =	0.37	ksf
Lateral Soil Bearing @ D, S_3 =	1.12	ksf
Constant 2.34P/(S_1B), A =	2.48	
Required Footing Depth, D =	5.75	ft

A 2ft diameter x 5.75ft deep footing unrestrained at ground level is required for the racking structure.

5.4 Uplifting Force Resistance

Uplifting forces of the racking system are checked against the uplift resistance of the soil. Clay soils are assumed.

Weight of Concrete, g_{con} =	145	pcf
Uplifting Force, N =	3.02	k
Footing Diameter, B =	2.00	ft
Factor of Safety =	2.50	
Cohesion =	208.85	psf
γ_s =	120.43	pcf
α =	0.45	
Required Concrete Weight, g =	1.98	k
Required Concrete Volume, V =	13.69	ft^3
Required Footing Depth, D =	4.50	ft

Iteration	z	dz	Qs	Side
1	0.2	0.2	118.10	6.53
2	0.4	0.2	118.10	6.43
3	0.6	0.2	118.10	6.33
4	0.8	0.2	118.10	6.22
5	1	0.2	118.10	6.12
6	1.2	0.2	118.10	6.02
7	1.4	0.2	118.10	5.91
8	1.6	0.2	118.10	5.81
9	1.8	0.2	118.10	5.71
10	2	0.2	118.10	5.60
11	2.2	0.2	118.10	5.50
12	2.4	0.2	118.10	5.39
13	2.6	0.2	118.10	5.29
14	2.8	0.2	118.10	5.19
15	3	0.2	118.10	5.08
16	3.2	0.2	118.10	4.98
17	3.4	0.2	118.10	4.88
18	3.6	0.2	118.10	4.77
19	3.8	0.2	118.10	4.67
20	4	0.2	118.10	4.56
21	4.2	0.2	118.10	4.46
22	4.4	0.2	118.10	4.36
23	0	0.0	0.00	4.36
24	0	0.0	0.00	4.36
25	0	0.0	0.00	4.36
26	0	0.0	0.00	4.36
27	0	0.0	0.00	4.36
28	0	0.0	0.00	4.36
29	0	0.0	0.00	4.36
30	0	0.0	0.00	4.36
31	0	0.0	0.00	4.36
32	0	0.0	0.00	4.36
33	0	0.0	0.00	4.36
34	0	0.0	0.00	4.36
Max	4.4	Sum	1.04	

A 2ft diameter x 4.5ft deep footing unrestrained at ground level is required for the racking structure.



5.5 Compressive Force Resistance

Skin friction of the soil is checked against the compression force from the racking and the weight of the drilled shaft foundation. Skin friction starts at 3ft below grade. Clay soils are again assumed.

Depth Below Grade, D =	5.75	ft
Footing Diameter, B =	2.00	ft
Compressive Force, P =	3.71	k
Footing Area =	3.14	ft^2
Circumference =	6.28	ft
Skin Friction Area =	17.28	ft^2
Concrete Weight =	0.145	kcf

Bearing Pressure

Bearing Area =	3.14	ft^2
Bearing Capacity =	1.5	ksf
Resistance =	4.71	k

Weight of Concrete

Footing Volume	18.06	ft^3
Weight	2.62	k

Skin Friction Resistance

Skin Friction =	0.15	ksf
Resistance =	2.59	k
1/3 Increase for Wind =	1.33	
Total Resistance =	9.74	k
Applied Force =	6.33	k
Utilization =	65%	

A 2ft diameter footing passes at a depth of 5.75ft.



6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of 40mm mounting clamps. The reliability of calculations is uncertain due to limited standards, therefore the strength of the clamp fasteners has been evaluated by load testing.

Fastening of Modules to Purlins

Maximum Uplifting Force	=	0.782 k
Allowable Uplift	=	1.214 k
Utilization	=	64%



Fastening of Purlins to Girders

Maximum Uplifting Force	=	2.093 k
Allowable Uplift	=	2.180 k
Utilization	=	96%



6.2 Strut Connections

The aluminum struts connect the front end of girder to a center section of the steel post. Single M10 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Maximum Axial Load	=	4.713 k
M10 Bolt Shear Capacity	=	8.894 k
Utilization	=	53%

Bolt capacity is accounting for double shear. (ASCE 8-02, Eq. 5.3.4-1)



A strut under compression is shown to demonstrate the load transfer from the girder. Single M10 bolts are located at each end of the strut and are subjected to double shear.

6.3 Girder to Post Connection

In order to connect the girder to the post, custom extruded sections are assembled to create a post head piece. The reliability of calculations is uncertain due to limited standards, therefore the strength of the head piece has been evaluated by load testing.

Maximum Tensile Load	=	4.301 k
Allowable Load	=	5.649 k
Utilization	=	76%



FRONT VIEW



SIDE VIEW



7. SEISMIC DESIGN

7.1 Seismic Drift

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx}	=	79.13 in
Allowable Story Drift for All Other Structures, Δ	= {	$0.020h_{sx}$
		1.583 in
Max Drift, Δ_{MAX}	=	0.877 in

0.877 ≤ 1.583, OK.

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **S1.5**

Strong Axis:		Weak Axis:	
3.4.14		**3.4.14**	
L_b =	90 in	L_b =	90
J =	0.432	J =	0.432
	248.982		158.338
$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$		$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$	
S1 =	0.51461	S1 =	0.51461
$S2 = \left(\frac{C_c}{1.6}\right)^2$		$S2 = \left(\frac{C_c}{1.6}\right)^2$	
S2 =	1701.56	S2 =	1701.56
φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]	φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L=	28.2 ksi	φF_L=	29.3
3.4.16		**3.4.16**	
b/t =	32.195	b/t =	37.0588
$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$		$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$	
S1 =	12.2	S1 =	12.2
$S2 = \frac{k_1 Bp}{1.6Dp}$		$S2 = \frac{k_1 Bp}{1.6Dp}$	
S2 =	46.7	S2 =	46.7
φF_L=	φb[Bp-1.6Dp*b/t]	φF_L=	φb[Bp-1.6Dp*b/t]
φF_L=	25.1 ksi	φF_L=	23.1 ksi
3.4.16.1	Not Used	**3.4.16.1**	
Rb/t =		N/A for Weak Direction	
$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$			
S1 =	1.1		
$S2 = C_t$			
S2 =	141.0		
φF_L=	1.17φyFcy		
φF_L=	38.9 ksi		
3.4.18		**3.4.18**	
h/t =	37.0588	h/t =	32.195
$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$		$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$	
S1 =	36.9	S1 =	36.9
m =	0.65	m =	0.65
C_0 =	40.985	C_0 =	45.5
Cc =	41.015	Cc =	45.5
$S2 = \frac{k_1 Bbr}{mDbr}$		$S2 = \frac{k_1 Bbr}{mDbr}$	
S2 =	77.2	S2 =	77.3
φF_L=	φb[Bbr-mDbr*h/t]	φF_L=	1.3φyFcy
φF_L=	43.2 ksi	φF_L=	43.2 ksi
φF_LSt=	25.1 ksi	φF_LWk=	23.1 ksi
Ix =	897074 mm^4	Iy =	446476 mm^4
	2.155 in^4		1.073 in^4
y =	41.015 mm	x =	45.5 mm
Sx =	1.335 in^3	Sy =	0.599 in^3
M_{max}St =	2.788 k-ft	M_{max}Wk =	1.152 k-ft

Compression

3.4.9

b/t = 32.195
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 25.1 ksi

b/t = 37.0588
S1 = 12.21
S2 = 32.70
φF_L = (φck2*√(BpE))/(1.6b/t)
φF_L = 21.9 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 21.94 ksi
A = 1215.13 mm^2
1.88 in^2
P_{max} = 41.32 kips

A.2 Design of Aluminum Girders - Aluminum Design Manual, 2005 Edition

Girder = **T5**

Strong Axis:

3.4.14

L_b = 81.7717 in
J = 1.98
105.231

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.1 ksi

3.4.16

b/t = 4.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φyFcy
φF_L = 33.3 ksi

Weak Axis:

3.4.14

L_b = 81.7717
J = 1.98
114.202

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.9

3.4.16

b/t = 16.3333

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 31.6 ksi

3.4.16.1 Used

Rb/t = 20.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= φb[Bt-Dt*√(Rb/t)]

φF_L= 30.8 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 16.3333

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 37.9

m = 0.63

C_0 = 61.046

Cc = 58.954

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 79.4

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 30.1 ksi

Ix = 1970917 mm^4

4.735 in^4

y = 61.046 mm

Sx = 1.970 in^3

$M_{max}St$ = 4.935 k-ft

3.4.18

h/t = 4.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 35

Cc = 35

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 31.6 ksi

Iy = 763048 mm^4

1.833 in^4

x = 35 mm

Sy = 1.330 in^3

$M_{max}Wk$ = 3.499 k-ft

Compression

3.4.9

b/t = 4.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φyFcy

φF_L= 33.3 ksi

b/t = 16.3333

S1 = 12.21

S2 = 32.70

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 31.6 ksi

3.4.10

Rb/t = 20.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L= φc[Bt-Dt*√(Rb/t)]

φF_L= 30.80 ksi

φF_L= 30.80 ksi

A = 1215.13 mm^2

1.88 in^2

P_{max} = 58.01 kips

A.3 Design of Aluminum Struts - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 74.8031 in

J = 0.942

116.737

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 29.9 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

Weak Axis:

3.4.14

L_b = 74.8031

J = 0.942

116.737

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 29.9

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 1.73045

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.82226

$\varphi F_L = (\varphi ccFcy)/(\lambda^2)$

φF_L = 9.61085 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 9.61 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 9.89 kips

A.4 Design of Galvanized Steel Posts

Post Type = **FG8**

Unbraced Length =	89.60	in	
Pr =	-5.09	k	(LRFD Factored Load)
Mr (Strong) =	12.04	k-ft	(LRFD Factored Load)
Mr (Weak) =	0.00	k-ft	(LRFD Factored Load)

Flexural Buckling:

kL/r =	128.92			
4.71√(E/Fy) =	103.55	=>	kL/r	> 4.71√(E/Fy)
Fcr =	15.10	ksi		
Fe =	17.22	ksi		
Pn =	33.677	k		

Torsional/Flexural Torsional Buckling:

Fcr =	11.6026	ksi
Fey =	43.9243	ksi
Fez =	14.9387	ksi
Pn =	25.8738	k

Bending (Strong Axis):

Yielding:

Mn =	21.95	k-ft

Flange Local Buckling:

Mn =	19.207	k-ft

Pr/Pc =	0.1513	<	0.2	
Utilization =	0.78	<	1.0	OK

Bending (Weak Axis):

Yielding:

Mn =	14.65	k-ft

Flange Local Buckling:

Mn =	14.39	k-ft

Pr/Pc =	0.151	<	0.2	
Utilization =	0.00	<	1.0	OK

Combined Forces

Utilization = 78%

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				4		
2	Dead Load, Min	DL		-1				4		
3	Snow Load	SL						4		
4	Wind Load - Pressure	WL						4		
5	Wind Load - Suction	WL						4		
6	Seismic - Lateral	EL			.8			8		

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-9.843	-9.843	0	0
2	M11	Y	-9.843	-9.843	0	0
3	M12	Y	-9.843	-9.843	0	0
4	M13	Y	-9.843	-9.843	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-5.454	-5.454	0	0
2	M11	Y	-5.454	-5.454	0	0
3	M12	Y	-5.454	-5.454	0	0
4	M13	Y	-5.454	-5.454	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-46.866	-46.866	0	0
2	M11	Y	-46.866	-46.866	0	0
3	M12	Y	-46.866	-46.866	0	0
4	M13	Y	-46.866	-46.866	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	y	-116.109	-116.109	0	0
2	M11	y	-116.109	-116.109	0	0
3	M12	y	-186.784	-186.784	0	0
4	M13	y	-186.784	-186.784	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	y	232.218	232.218	0	0
2	M11	y	232.218	232.218	0	0
3	M12	y	111.061	111.061	0	0
4	M13	y	111.061	111.061	0	0

Member Distributed Loads (BLC 6 : Seismic - Lateral)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Z	7.874	7.874	0	0
2	M11	Z	7.874	7.874	0	0
3	M12	Z	7.874	7.874	0	0
4	M13	Z	7.874	7.874	0	0
5	M10	Z	0	0	0	0
6	M11	Z	0	0	0	0
7	M12	Z	0	0	0	0
8	M13	Z	0	0	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.5W	Yes	Y		1	1.2	3	1.6	4	.5														
2	LRFD 1.2D + 1.0W + 0.5S	Yes	Y		1	1.2	3	.5	4	1														
3	LRFD 0.9D + 1.0W	Yes	Y		2	.9					5	1												
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3												
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3												
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25												
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25												
8																								
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																
10	ASD 1.0D + 0.6W	Yes	Y		1	1			4	.6														
11	ASD 1.0D + 0.75L + 0.45W + 0....	Yes	Y		1	1	3	.75	4	.45														
12	ASD 0.6D + 0.6W	Yes	Y		2	.6					5	.6												
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875												
14	LATERAL - ASD 1.1785D + 0.65...	Yes	Y		1	1.1...	3	.75			6	.656												
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875												

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N9	max	755.236	2	2226.306	2	110.785	2	.167	1	.018	5	5.861	1
2		min	-1106.281	3	-1628.946	3	-315.751	5	-1.526	5	-.01	2	.838	15
3	N19	max	3032.923	2	5943.782	2	0	3	0	2	.019	4	8.498	1
4		min	-2936.622	3	-5056.975	3	-332.613	5	-1.585	4	0	1	.338	15
5	N29	max	755.236	2	2226.306	2	136.441	3	.213	3	.019	4	5.861	1
6		min	-1106.281	3	-1628.946	3	-336.423	4	-1.581	4	-.004	3	-.505	5
7	Totals:	max	4543.395	2	10396.394	2	0	10						
8		min	-5149.185	3	-8314.867	3	-971.522	4						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M1	1	max	0	1	.003	2	0	4	0	1	0	1	0	1
2			min	0	1	0	3	0	1	0	1	0	1	0	1
3		2	max	-16.228	12	308.305	3	-10.949	12	.037	3	.242	1	.259	2
4			min	-192.745	1	-701.559	2	-111.173	1	-.178	2	.033	12	-.111	3
5		3	max	-16.685	12	307.116	3	-10.949	12	.037	3	.169	1	.72	2
6			min	-193.66	1	-703.144	2	-111.173	1	-.178	2	.026	12	-.313	3
7		4	max	-17.143	12	305.928	3	-10.949	12	.037	3	.097	4	1.182	2
8			min	-194.575	1	-704.728	2	-111.173	1	-.178	2	.019	12	-.514	3
9		5	max	399.4	3	645.963	2	-2.908	12	.008	2	.113	1	1.397	2
10			min	-1125.311	2	-268.72	3	-139.185	1	-.038	3	-.022	3	-.609	3
11		6	max	398.714	3	644.379	2	-2.908	12	.008	2	.035	2	.973	2
12			min	-1126.226	2	-269.908	3	-139.185	1	-.038	3	-.038	5	-.433	3
13		7	max	398.028	3	642.794	2	-2.908	12	.008	2	-.014	10	.551	2
14			min	-1127.14	2	-271.097	3	-139.185	1	-.038	3	-.086	4	-.255	3
15		8	max	397.342	3	641.21	2	-2.908	12	.008	2	-.019	12	.13	2
16			min	-1128.055	2	-272.285	3	-139.185	1	-.038	3	-.161	1	-.077	3
17		9	max	370.369	3	13.692	3	4.1	3	.018	5	.091	1	.009	3
18			min	-1237.484	2	-11.081	2	-182.766	1	-.118	2	.017	10	-.067	2
19		10	max	369.683	3	12.504	3	4.1	3	.018	5	.04	3	0	3
20			min	-1238.398	2	-12.666	2	-182.766	1	-.118	2	-.033	2	-.06	2
21		11	max	368.997	3	11.316	3	4.1	3	.018	5	.043	3	-.001	15
22			min	-1239.313	2	-14.25	2	-182.766	1	-.118	2	-.149	1	-.051	2
23		12	max	336.635	3	704.124	3	20.498	2	.182	3	.12	1	.103	2
24			min	-1422.227	1	-440.82	2	-187.619	4	-.154	2	.023	10	-.236	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
25		13	max	335.949	3	702.936	3	20.498	2	.182	3	.103	1	.392	2
26			min	-1423.142	1	-442.405	2	-189.205	4	-.154	2	-.045	5	-.698	3
27		14	max	335.263	3	701.748	3	20.498	2	.182	3	.09	2	.683	2
28			min	-1424.057	1	-443.989	2	-190.79	4	-.154	2	-.162	5	-1.159	3
29		15	max	334.577	3	700.559	3	20.498	2	.182	3	.103	2	.975	2
30			min	-1424.972	1	-445.574	2	-192.376	4	-.154	2	-.281	5	-1.619	3
31		16	max	194.924	1	447.135	2	62.304	5	.131	2	.017	3	.743	2
32			min	12.001	15	-734.953	3	-95.445	1	-.322	3	-.157	4	-1.236	3
33		17	max	194.009	1	445.551	2	60.718	5	.131	2	-.007	12	.45	2
34			min	11.725	15	-736.141	3	-95.445	1	-.322	3	-.191	1	-.753	3
35		18	max	193.094	1	443.967	2	59.133	5	.131	2	-.023	12	.158	2
36			min	11.449	15	-737.33	3	-95.445	1	-.322	3	-.253	1	-.27	3
37		19	max	0	1	0	2	0	1	0	1	0	1	0	1
38			min	0	1	-.002	3	0	4	0	1	0	1	0	1
39	M4	1	max	0	1	.007	2	0	4	0	1	0	1	0	1
40			min	0	1	-.001	3	0	1	0	1	0	1	0	1
41		2	max	1.679	3	964.327	3	0	1	.045	4	.233	4	.58	2
42			min	-281.77	1	-1879.55	2	-87.997	5	0	1	0	1	-.306	3
43		3	max	.993	3	963.139	3	0	1	.045	4	.175	4	1.814	2
44			min	-282.685	1	-1881.134	2	-89.583	5	0	1	0	1	-.939	3
45		4	max	.307	3	961.951	3	0	1	.045	4	.116	4	3.049	2
46			min	-283.599	1	-1882.719	2	-91.169	5	0	1	0	1	-1.57	3
47		5	max	1475.942	3	1885.955	2	0	1	0	1	.006	4	3.592	2
48			min	-2945.685	2	-1006.88	3	-81.852	4	-.028	4	0	1	-1.84	3
49		6	max	1475.256	3	1884.37	2	0	1	0	1	0	1	2.355	2
50			min	-2946.599	2	-1008.069	3	-83.437	4	-.028	4	-.049	5	-1.179	3
51		7	max	1474.57	3	1882.786	2	0	1	0	1	0	1	1.119	2
52			min	-2947.514	2	-1009.257	3	-85.023	4	-.028	4	-.104	4	-.517	3
53		8	max	1473.884	3	1881.202	2	0	1	0	1	0	1	.146	3
54			min	-2948.429	2	-1010.445	3	-86.608	4	-.028	4	-.16	4	-.119	1
55		9	max	1478.802	3	-1.562	12	0	1	.013	4	.125	4	.461	3
56			min	-3010.188	2	-105.939	2	-196.99	4	0	1	0	1	-.686	2
57		10	max	1478.116	3	-2.129	15	0	1	.013	4	0	1	.463	3
58			min	-3011.102	2	-107.523	2	-198.575	4	0	1	-.004	4	-.616	2
59		11	max	1477.43	3	-2.607	15	0	1	.013	4	0	1	.465	3
60			min	-3012.017	2	-109.108	2	-200.161	4	0	1	-.135	4	-.544	2
61		12	max	1493.126	3	2004.243	3	0	1	.139	4	.111	5	.019	9
62			min	-3083.507	2	-1485.201	2	-200.612	5	0	1	0	1	-.17	3
63		13	max	1492.44	3	2003.055	3	0	1	.139	4	0	1	.924	2
64			min	-3084.422	2	-1486.785	2	-202.198	5	0	1	-.022	4	-1.485	3
65		14	max	1491.754	3	2001.867	3	0	1	.139	4	0	1	1.9	2
66			min	-3085.337	2	-1488.37	2	-203.783	5	0	1	-.155	4	-2.799	3
67		15	max	1491.068	3	2000.679	3	0	1	.139	4	0	1	2.877	2
68			min	-3086.251	2	-1489.954	2	-205.369	5	0	1	-.29	4	-4.112	3
69		16	max	282.902	1	1343.282	2	53.988	5	0	1	0	1	2.19	2
70			min	3.108	3	-1921.986	3	0	1	-.131	4	-.118	5	-3.121	3
71		17	max	281.987	1	1341.697	2	52.403	5	0	1	0	1	1.309	2
72			min	2.422	3	-1923.175	3	0	1	-.131	4	-.083	5	-1.86	3
73		18	max	281.072	1	1340.113	2	50.817	5	0	1	0	1	.429	2
74			min	1.736	3	-1924.363	3	0	1	-.131	4	-.049	4	-.598	3
75		19	max	0	1	.002	2	0	1	0	1	0	1	0	1
76			min	0	1	-.005	3	0	4	0	1	0	1	0	1
77	M7	1	max	0	1	.003	2	.001	4	0	1	0	1	0	1
78			min	0	1	0	3	0	12	0	1	0	1	0	1
79		2	max	23.851	5	308.305	3	111.173	1	.178	2	.118	5	.259	2
80			min	-192.745	1	-701.559	2	-40.175	5	-.037	3	-.242	1	-.111	3
81		3	max	23.424	5	307.116	3	111.173	1	.178	2	.091	5	.72	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
82			min	-193.66	1	-703.144	2	-41.761	5	-.037	3	-.169	1	-.313	3
83		4	max	22.997	5	305.928	3	111.173	1	.178	2	.063	5	1.182	2
84			min	-194.575	1	-704.728	2	-43.347	5	-.037	3	-.096	1	-.514	3
85		5	max	399.4	3	645.963	2	139.185	1	.038	3	.022	3	1.397	2
86			min	-1125.311	2	-268.72	3	-32.314	5	-.025	4	-.113	1	-.609	3
87		6	max	398.714	3	644.379	2	139.185	1	.038	3	.025	3	.973	2
88			min	-1126.226	2	-269.908	3	-33.9	5	-.025	4	-.039	4	-.433	3
89		7	max	398.028	3	642.794	2	139.185	1	.038	3	.07	1	.551	2
90			min	-1127.14	2	-271.097	3	-35.485	5	-.025	4	-.061	5	-.255	3
91		8	max	397.342	3	641.21	2	139.185	1	.038	3	.161	1	.13	2
92			min	-1128.055	2	-272.285	3	-37.071	5	-.025	4	-.085	5	-.077	3
93		9	max	370.369	3	13.692	3	182.766	1	.118	2	.052	5	.009	3
94			min	-1237.484	2	-11.081	2	-68.991	5	.015	15	-.091	1	-.067	2
95		10	max	369.683	3	12.504	3	182.766	1	.118	2	.033	2	0	3
96			min	-1238.398	2	-12.666	2	-70.577	5	.015	15	-.04	3	-.06	2
97		11	max	368.997	3	11.316	3	182.766	1	.118	2	.149	1	-.004	15
98			min	-1239.313	2	-14.25	2	-72.162	5	.015	15	-.043	3	-.051	2
99		12	max	336.635	3	704.124	3	163.782	3	.154	2	.055	5	.103	2
100			min	-1422.227	1	-440.82	2	-170.383	5	-.182	3	-.12	1	-.236	3
101		13	max	335.949	3	702.936	3	163.782	3	.154	2	.023	3	.392	2
102			min	-1423.142	1	-442.405	2	-171.968	5	-.182	3	-.103	1	-.698	3
103		14	max	335.263	3	701.748	3	163.782	3	.154	2	.13	3	.683	2
104			min	-1424.057	1	-443.989	2	-173.554	5	-.182	3	-.183	4	-1.159	3
105		15	max	334.577	3	700.559	3	163.782	3	.154	2	.238	3	.975	2
106			min	-1424.972	1	-445.574	2	-175.14	5	-.182	3	-.291	4	-1.619	3
107		16	max	194.924	1	447.135	2	95.445	1	.322	3	.128	1	.743	2
108			min	6.389	15	-734.953	3	22.611	10	-.131	2	-.118	5	-1.236	3
109		17	max	194.009	1	445.551	2	95.445	1	.322	3	.191	1	.45	2
110			min	6.113	15	-736.141	3	22.611	10	-.131	2	-.069	5	-.753	3
111		18	max	193.094	1	443.967	2	95.445	1	.322	3	.253	1	.158	2
112			min	5.837	15	-737.33	3	22.611	10	-.131	2	-.022	5	-.27	3
113		19	max	0	1	0	2	0	15	0	1	0	1	0	1
114			min	0	1	-.002	3	0	1	0	1	0	1	0	1
115	M10	1	max	95.486	1	442.371	2	-5.57	15	.01	2	.285	1	.131	2
116			min	22.61	10	-738.396	3	-192.436	1	-.023	3	.001	15	-.322	3
117		2	max	95.486	1	318.875	2	-3.858	15	.01	2	.14	1	.215	3
118			min	22.61	10	-549.401	3	-155.518	1	-.023	3	-.004	5	-.186	2
119		3	max	95.486	1	195.38	2	-2.147	15	.01	2	.045	2	.594	3
120			min	22.61	10	-360.406	3	-118.601	1	-.023	3	-.008	5	-.401	2
121		4	max	95.486	1	71.884	2	-.435	15	.01	2	.005	10	.815	3
122			min	22.61	10	-171.41	3	-81.683	1	-.023	3	-.057	1	-.512	2
123		5	max	95.486	1	20.592	5	1.797	5	.01	2	-.006	15	.879	3
124			min	20.518	15	-51.612	2	-44.766	1	-.023	3	-.11	1	-.52	2
125		6	max	95.486	1	206.58	3	5.415	4	.01	2	-.004	15	.786	3
126			min	13.899	15	-175.108	2	-21.376	2	-.023	3	-.132	1	-.426	2
127		7	max	95.486	1	395.576	3	29.069	1	.01	2	-.001	15	.535	3
128			min	7.28	15	-298.603	2	-8.222	10	-.023	3	-.123	1	-.228	2
129		8	max	95.486	1	584.571	3	65.987	1	.01	2	.005	5	.127	3
130			min	.661	15	-422.099	2	-4.737	3	-.023	3	-.083	1	-.023	5
131		9	max	95.486	1	773.566	3	102.905	1	.01	2	.02	4	.475	2
132			min	-8.501	5	-545.595	2	-2.128	3	-.023	3	-.062	2	-.439	3
133		10	max	95.486	1	962.562	3	.879	12	.023	3	.089	9	.981	2
134			min	20.624	15	31.701	15	-139.822	1	-.003	14	-.036	10	-1.163	3
135		11	max	95.486	1	545.595	2	2.128	3	.023	3	.016	9	.475	2
136			min	14.005	15	-773.566	3	-102.905	1	-.01	2	-.062	2	-.439	3
137		12	max	95.486	1	422.099	2	4.737	3	.023	3	-.009	15	.127	3
138			min	7.386	15	-584.571	3	-65.987	1	-.01	2	-.083	1	.021	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
139		13	max	95.486	1	298.603	2	8.222	10	.023	3	-.009	15	.535	3
140			min	.767	15	-395.576	3	-29.069	1	-.01	2	-.123	1	-.228	2
141		14	max	95.486	1	175.108	2	21.376	2	.023	3	-.007	15	.786	3
142			min	-8.404	5	-206.58	3	-2.621	9	-.01	2	-.132	1	-.426	2
143		15	max	95.486	1	51.612	2	44.766	1	.023	3	-.004	15	.879	3
144			min	-18.238	5	-17.585	3	4.331	15	-.01	2	-.11	1	-.52	2
145		16	max	95.486	1	171.41	3	81.683	1	.023	3	.005	10	.815	3
146			min	-28.071	5	-71.884	2	6.042	15	-.01	2	-.057	1	-.512	2
147		17	max	95.486	1	360.406	3	118.601	1	.023	3	.045	2	.594	3
148			min	-37.905	5	-195.38	2	7.754	15	-.01	2	.003	9	-.401	2
149		18	max	95.486	1	549.401	3	155.518	1	.023	3	.14	1	.215	3
150			min	-47.739	5	-318.875	2	9.465	15	-.01	2	.013	15	-.186	2
151		19	max	95.486	1	738.396	3	192.436	1	.023	3	.285	1	.131	2
152			min	-57.573	5	-442.371	2	11.177	15	-.01	2	.022	15	-.322	3
153	M11	1	max	156.102	1	424.409	2	37.436	5	0	3	.339	1	.11	4
154			min	-167.742	3	-694.503	3	-203.316	1	-.008	1	-.175	5	-.271	3
155		2	max	156.102	1	300.913	2	40.083	5	0	3	.185	1	.229	3
156			min	-167.742	3	-505.508	3	-166.398	1	-.008	1	-.142	5	-.266	2
157		3	max	156.102	1	177.417	2	42.731	5	0	3	.062	2	.572	3
158			min	-167.742	3	-316.513	3	-129.48	1	-.008	1	-.108	5	-.466	2
159		4	max	156.102	1	53.922	2	45.379	5	0	3	.024	3	.757	3
160			min	-167.742	3	-127.517	3	-92.563	1	-.008	1	-.082	4	-.562	2
161		5	max	156.102	1	61.478	3	48.026	5	0	3	.005	3	.784	3
162			min	-167.742	3	-69.574	2	-55.645	1	-.008	1	-.092	1	-.555	2
163		6	max	156.102	1	250.473	3	50.674	5	0	3	.009	5	.654	3
164			min	-167.742	3	-193.07	2	-26.811	2	-.008	1	-.123	1	-.446	2
165		7	max	156.102	1	439.469	3	60.636	4	0	3	.052	5	.367	3
166			min	-167.742	3	-316.566	2	-15.844	3	-.008	1	-.123	1	-.234	2
167		8	max	156.102	1	628.464	3	71.823	4	0	3	.098	5	.082	2
168			min	-167.742	3	-440.061	2	-13.234	3	-.008	1	-.093	1	-.078	3
169		9	max	156.102	1	817.459	3	92.025	1	0	3	.148	4	.5	2
170			min	-167.742	3	-563.557	2	-10.625	3	-.008	1	-.072	2	-.681	3
171		10	max	156.102	1	204.36	14	128.943	1	.008	1	.222	4	1.021	2
172			min	-167.742	3	-1006.454	3	-51.498	14	-.004	14	-.056	3	-1.441	3
173		11	max	156.102	1	563.557	2	43.581	5	.008	1	.004	9	.5	2
174			min	-167.742	3	-817.459	3	-92.025	1	0	5	-.145	5	-.681	3
175		12	max	156.102	1	440.061	2	46.229	5	.008	1	-.023	12	.082	2
176			min	-167.742	3	-628.464	3	-55.107	1	0	5	-.122	4	-.078	3
177		13	max	156.102	1	316.566	2	48.877	5	.008	1	-.016	12	.367	3
178			min	-167.742	3	-439.469	3	-20.142	9	0	5	-.123	1	-.234	2
179		14	max	156.102	1	193.07	2	53.141	4	.008	1	-.008	12	.654	3
180			min	-167.742	3	-250.473	3	4.113	9	0	5	-.123	1	-.446	2
181		15	max	156.102	1	69.574	2	64.327	4	.008	1	.018	5	.784	3
182			min	-167.742	3	-61.478	3	12.99	12	0	5	-.092	1	-.555	2
183		16	max	156.102	1	127.517	3	92.563	1	.008	1	.065	5	.757	3
184			min	-167.742	3	-53.922	2	14.73	12	0	5	-.031	1	-.562	2
185		17	max	156.102	1	316.513	3	129.48	1	.008	1	.122	4	.572	3
186			min	-167.742	3	-177.417	2	16.469	12	0	5	.025	9	-.466	2
187		18	max	156.102	1	505.508	3	166.398	1	.008	1	.199	4	.229	3
188			min	-167.742	3	-300.913	2	18.209	12	0	5	.042	12	-.266	2
189		19	max	156.102	1	694.503	3	203.316	1	.008	1	.339	1	.048	1
190			min	-167.742	3	-424.409	2	19.949	12	0	5	.057	12	-.271	3
191	M12	1	max	30.173	5	649.73	2	37.172	5	-.001	15	.358	1	.126	2
192			min	-42.943	1	-287.385	3	-207.212	1	-.004	1	-.172	5	.021	9
193		2	max	20.34	5	467.339	2	39.819	5	-.001	15	.201	1	.254	3
194			min	-42.943	1	-199.354	3	-170.294	1	-.004	1	-.14	5	-.339	2
195		3	max	10.506	5	284.947	2	42.467	5	-.001	15	.077	2	.383	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
196			min	-42.943	1	-111.323	3	-133.376	1	-.004	1	-.106	5	-.652	2
197		4	max	7.825	3	102.556	2	45.115	5	-.001	15	.019	2	.439	3
198			min	-42.943	1	-23.292	3	-96.459	1	-.004	1	-.079	4	-.814	2
199		5	max	7.825	3	64.739	3	47.762	5	-.001	15	-.002	12	.422	3
200			min	-42.943	1	-79.836	2	-59.541	1	-.004	1	-.086	1	-.823	2
201		6	max	7.825	3	152.77	3	50.41	5	-.001	15	.01	5	.331	3
202			min	-42.943	1	-262.227	2	-31.302	2	-.004	1	-.12	1	-.681	2
203		7	max	7.825	3	240.801	3	60.001	4	-.001	15	.054	5	.168	3
204			min	-42.943	1	-444.619	2	-15.865	2	-.004	1	-.124	1	-.386	2
205		8	max	7.825	3	328.833	3	71.188	4	-.001	15	.099	5	.06	2
206			min	-49.718	4	-627.01	2	-8.029	3	-.004	1	-.097	1	-.07	3
207		9	max	7.825	3	416.864	3	88.129	1	-.001	15	.148	4	.659	2
208			min	-59.552	4	-809.402	2	-5.42	3	-.004	1	-.08	2	-.381	3
209		10	max	7.825	3	-10.301	15	125.047	1	.004	1	.221	4	1.409	2
210			min	-69.386	4	-991.794	2	1.177	12	-.003	14	-.061	2	-.765	3
211		11	max	40.763	5	809.402	2	43.638	5	.004	1	.002	9	.659	2
212			min	-42.943	1	-416.864	3	-88.129	1	-.001	5	-.146	4	-.381	3
213		12	max	30.93	5	627.01	2	46.285	5	.004	1	-.021	12	.06	2
214			min	-42.943	1	-328.833	3	-51.211	1	-.001	5	-.124	4	-.07	3
215		13	max	21.096	5	444.619	2	48.933	5	.004	1	-.016	12	.168	3
216			min	-42.943	1	-240.801	3	-18.768	9	-.001	5	-.124	1	-.386	2
217		14	max	11.262	5	262.227	2	53.795	4	.004	1	-.01	12	.331	3
218			min	-42.943	1	-152.77	3	5.487	9	-.001	5	-.12	1	-.681	2
219		15	max	7.825	3	79.836	2	64.981	4	.004	1	.017	5	.422	3
220			min	-42.943	1	-64.739	3	9.876	12	-.001	5	-.086	1	-.823	2
221		16	max	7.825	3	23.292	3	96.459	1	.004	1	.064	5	.439	3
222			min	-42.943	1	-102.556	2	11.615	12	-.001	5	-.026	9	-.814	2
223		17	max	7.825	3	111.323	3	133.376	1	.004	1	.123	4	.383	3
224			min	-42.943	1	-284.947	2	13.355	12	-.001	5	.017	12	-.652	2
225		18	max	7.825	3	199.354	3	170.294	1	.004	1	.201	1	.254	3
226			min	-42.943	1	-467.339	2	15.094	12	-.001	5	.029	12	-.339	2
227		19	max	7.825	3	287.385	3	207.212	1	.004	1	.358	1	.126	2
228			min	-48.982	4	-649.73	2	16.834	12	-.001	5	.042	12	-.042	5
229	M13	1	max	38.487	5	700.898	2	24.283	5	.008	3	.279	1	.178	2
230			min	-111.043	1	-309.514	3	-191.524	1	-.025	2	-.131	5	-.037	3
231		2	max	28.653	5	518.507	2	26.93	5	.008	3	.135	1	.184	3
232			min	-111.043	1	-221.483	3	-154.607	1	-.025	2	-.11	5	-.33	2
233		3	max	18.819	5	336.115	2	29.578	5	.008	3	.04	2	.332	3
234			min	-111.043	1	-133.452	3	-117.689	1	-.025	2	-.086	4	-.686	2
235		4	max	8.986	5	153.723	2	32.226	5	.008	3	.007	3	.406	3
236			min	-111.043	1	-45.421	3	-80.772	1	-.025	2	-.077	4	-.89	2
237		5	max	-.353	15	42.61	3	34.873	5	.008	3	-.004	12	.408	3
238			min	-111.043	1	-28.668	2	-43.854	1	-.025	2	-.113	1	-.942	2
239		6	max	-6.972	15	130.641	3	38.736	4	.008	3	-.001	15	.335	3
240			min	-111.043	1	-211.06	2	-20.46	2	-.025	2	-.134	1	-.842	2
241		7	max	-10.948	12	218.672	3	49.923	4	.008	3	.03	5	.19	3
242			min	-111.043	1	-393.451	2	-8.994	3	-.025	2	-.124	1	-.59	2
243		8	max	-10.948	12	306.703	3	66.899	1	.008	3	.065	5	-.01	15
244			min	-111.043	1	-575.843	2	-6.384	3	-.025	2	-.084	1	-.186	2
245		9	max	-10.948	12	394.735	3	103.816	1	.008	3	.107	4	.369	2
246			min	-111.043	1	-758.234	2	-3.775	3	-.025	2	-.062	2	-.321	3
247		10	max	-10.948	12	-9.014	15	140.734	1	.025	2	.172	4	1.077	2
248			min	-111.043	1	-940.626	2	.107	12	-.006	14	-.038	3	-.687	3
249		11	max	26.656	5	758.234	2	28.908	5	.025	2	.016	9	.369	2
250			min	-111.043	1	-394.735	3	-103.816	1	-.008	3	-.098	5	-.321	3
251		12	max	16.823	5	575.843	2	31.556	5	.025	2	-.02	12	0	15
252			min	-111.043	1	-306.703	3	-66.899	1	-.008	3	-.086	4	-.186	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
253		13	max	6.989	5	393.451	2	34.203	5	.025	2	-.016	12	.19	3
254			min	-111.043	1	-218.672	3	-29.981	1	-.008	3	-.124	1	-.59	2
255		14	max	-1.685	15	211.06	2	36.851	5	.025	2	-.01	15	.335	3
256			min	-111.043	1	-130.641	3	-3.001	9	-.008	3	-.134	1	-.842	2
257		15	max	-8.304	15	28.668	2	47.093	4	.025	2	.016	5	.408	3
258			min	-111.043	1	-42.61	3	8.805	12	-.008	3	-.113	1	-.942	2
259		16	max	-10.948	12	45.421	3	80.772	1	.025	2	.05	5	.406	3
260			min	-111.043	1	-153.723	2	10.545	12	-.008	3	-.061	1	-.89	2
261		17	max	-10.948	12	133.452	3	117.689	1	.025	2	.087	4	.332	3
262			min	-111.043	1	-336.115	2	12.285	12	-.008	3	0	9	-.686	2
263		18	max	-10.948	12	221.483	3	154.607	1	.025	2	.15	4	.184	3
264			min	-111.043	1	-518.507	2	14.024	12	-.008	3	.025	12	-.33	2
265		19	max	-10.948	12	309.514	3	191.524	1	.025	2	.279	1	.178	2
266			min	-111.043	1	-700.898	2	15.764	12	-.008	3	.037	12	-.037	3
267	M2	1	max	2226.306	2	1105.615	3	110.893	2	.018	5	1.526	5	5.861	1
268			min	-1628.946	3	-754.087	2	-315.819	5	-.01	2	-.167	1	.838	15
269		2	max	2223.035	2	1105.615	3	110.893	2	.018	5	1.413	5	5.945	1
270			min	-1631.399	3	-754.087	2	-312.984	5	-.01	2	-.132	1	.798	15
271		3	max	1566.78	1	1007.73	1	76.324	2	.001	2	1.297	5	5.793	1
272			min	-1358.396	3	131.164	15	-291.563	5	0	5	-.117	1	.754	15
273		4	max	1563.508	1	1007.73	1	76.324	2	.001	2	1.192	5	5.431	1
274			min	-1360.849	3	131.164	15	-288.727	5	0	5	-.092	1	.707	15
275		5	max	1560.237	1	1007.73	1	76.324	2	.001	2	1.09	4	5.069	1
276			min	-1363.303	3	131.164	15	-285.892	5	0	5	-.067	1	.66	15
277		6	max	1556.965	1	1007.73	1	76.324	2	.001	2	.99	4	4.707	1
278			min	-1365.756	3	131.164	15	-283.057	5	0	5	-.043	1	.613	15
279		7	max	1553.694	1	1007.73	1	76.324	2	.001	2	.891	4	4.345	1
280			min	-1368.21	3	131.164	15	-280.222	5	0	5	-.051	3	.565	15
281		8	max	1550.423	1	1007.73	1	76.324	2	.001	2	.793	4	3.983	1
282			min	-1370.664	3	131.164	15	-277.386	5	0	5	-.095	3	.518	15
283		9	max	1547.151	1	1007.73	1	76.324	2	.001	2	.696	4	3.62	1
284			min	-1373.117	3	131.164	15	-274.551	5	0	5	-.139	3	.471	15
285		10	max	1543.88	1	1007.73	1	76.324	2	.001	2	.6	4	3.258	1
286			min	-1375.571	3	131.164	15	-271.716	5	0	5	-.183	3	.424	15
287		11	max	1540.608	1	1007.73	1	76.324	2	.001	2	.505	4	2.896	1
288			min	-1378.024	3	131.164	15	-268.881	5	0	5	-.228	3	.377	15
289		12	max	1537.337	1	1007.73	1	76.324	2	.001	2	.411	4	2.534	1
290			min	-1380.478	3	131.164	15	-266.045	5	0	5	-.272	3	.33	15
291		13	max	1534.065	1	1007.73	1	76.324	2	.001	2	.318	4	2.172	1
292			min	-1382.931	3	131.164	15	-263.21	5	0	5	-.316	3	.283	15
293		14	max	1530.794	1	1007.73	1	76.324	2	.001	2	.227	4	1.81	1
294			min	-1385.385	3	131.164	15	-260.375	5	0	5	-.361	3	.236	15
295		15	max	1527.522	1	1007.73	1	76.324	2	.001	2	.219	2	1.448	1
296			min	-1387.839	3	131.164	15	-257.54	5	0	5	-.405	3	.188	15
297		16	max	1524.251	1	1007.73	1	76.324	2	.001	2	.246	2	1.086	1
298			min	-1390.292	3	131.164	15	-254.704	5	0	5	-.449	3	.141	15
299		17	max	1520.979	1	1007.73	1	76.324	2	.001	2	.274	2	.724	1
300			min	-1392.746	3	131.164	15	-251.869	5	0	5	-.493	3	.094	15
301		18	max	1517.708	1	1007.73	1	76.324	2	.001	2	.301	2	.362	1
302			min	-1395.199	3	131.164	15	-249.034	5	0	5	-.538	3	.047	15
303		19	max	1514.437	1	1007.73	1	76.324	2	.001	2	.329	2	0	1
304			min	-1397.653	3	131.164	15	-246.199	5	0	5	-.582	3	0	1
305	M5	1	max	5943.782	2	2933.03	3	0	1	.019	4	1.585	4	8.498	1
306			min	-5056.975	3	-3028.686	2	-332.735	5	0	1	0	1	.338	15
307		2	max	5940.511	2	2933.03	3	0	1	.019	4	1.466	4	9.144	1
308			min	-5059.429	3	-3028.686	2	-329.9	5	0	1	0	1	.344	15
309		3	max	4116.756	2	1591.051	1	0	1	0	1	1.346	4	9.146	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
310			min	-4107.862	3	58.38	15	-310.908	4	0	4	0	1	.336	15
311		4	max	4113.485	2	1591.051	1	0	1	0	1	1.234	4	8.574	1
312			min	-4110.315	3	58.38	15	-308.073	4	0	4	0	1	.315	15
313		5	max	4110.213	2	1591.051	1	0	1	0	1	1.124	4	8.003	1
314			min	-4112.769	3	58.38	15	-305.238	4	0	4	0	1	.294	15
315		6	max	4106.942	2	1591.051	1	0	1	0	1	1.015	4	7.431	1
316			min	-4115.222	3	58.38	15	-302.402	4	0	4	0	1	.273	15
317		7	max	4103.67	2	1591.051	1	0	1	0	1	.907	4	6.859	1
318			min	-4117.676	3	58.38	15	-299.567	4	0	4	0	1	.252	15
319		8	max	4100.399	2	1591.051	1	0	1	0	1	.8	4	6.288	1
320			min	-4120.13	3	58.38	15	-296.732	4	0	4	0	1	.231	15
321		9	max	4097.127	2	1591.051	1	0	1	0	1	.694	4	5.716	1
322			min	-4122.583	3	58.38	15	-293.897	4	0	4	0	1	.21	15
323		10	max	4093.856	2	1591.051	1	0	1	0	1	.589	4	5.145	1
324			min	-4125.037	3	58.38	15	-291.061	4	0	4	0	1	.189	15
325		11	max	4090.585	2	1591.051	1	0	1	0	1	.485	4	4.573	1
326			min	-4127.49	3	58.38	15	-288.226	4	0	4	0	1	.168	15
327		12	max	4087.313	2	1591.051	1	0	1	0	1	.382	4	4.001	1
328			min	-4129.944	3	58.38	15	-285.391	4	0	4	0	1	.147	15
329		13	max	4084.042	2	1591.051	1	0	1	0	1	.28	4	3.43	1
330			min	-4132.398	3	58.38	15	-282.556	4	0	4	0	1	.126	15
331		14	max	4080.77	2	1591.051	1	0	1	0	1	.179	4	2.858	1
332			min	-4134.851	3	58.38	15	-279.72	4	0	4	0	1	.105	15
333		15	max	4077.499	2	1591.051	1	0	1	0	1	.079	4	2.286	1
334			min	-4137.305	3	58.38	15	-276.885	4	0	4	0	1	.084	15
335		16	max	4074.227	2	1591.051	1	0	1	0	1	0	1	1.715	1
336			min	-4139.758	3	58.38	15	-274.05	4	0	4	-.021	5	.063	15
337		17	max	4070.956	2	1591.051	1	0	1	0	1	0	1	1.143	1
338			min	-4142.212	3	58.38	15	-271.215	4	0	4	-.118	4	.042	15
339		18	max	4067.684	2	1591.051	1	0	1	0	1	0	1	.572	1
340			min	-4144.666	3	58.38	15	-268.379	4	0	4	-.215	4	.021	15
341		19	max	4064.413	2	1591.051	1	0	1	0	1	0	1	0	1
342			min	-4147.119	3	58.38	15	-265.544	4	0	4	-.311	4	0	1
343	M8	1	max	2226.306	2	1105.615	3	136.338	3	.019	4	1.581	4	5.861	1
344			min	-1628.946	3	-754.087	2	-336.645	4	-.004	3	-.213	3	-.505	5
345		2	max	2223.035	2	1105.615	3	136.338	3	.019	4	1.461	4	5.945	1
346			min	-1631.399	3	-754.087	2	-333.809	4	-.004	3	-.164	3	-.454	5
347		3	max	1566.78	1	1007.73	1	123.181	3	0	3	1.34	4	5.793	1
348			min	-1358.396	3	-72.372	5	-309.115	4	-.001	2	-.126	3	-.416	5
349		4	max	1563.508	1	1007.73	1	123.181	3	0	3	1.23	4	5.431	1
350			min	-1360.849	3	-72.372	5	-306.28	4	-.001	2	-.082	3	-.39	5
351		5	max	1560.237	1	1007.73	1	123.181	3	0	3	1.12	4	5.069	1
352			min	-1363.303	3	-72.372	5	-303.445	4	-.001	2	-.038	3	-.364	5
353		6	max	1556.965	1	1007.73	1	123.181	3	0	3	1.012	4	4.707	1
354			min	-1365.756	3	-72.372	5	-300.61	4	-.001	2	.004	12	-.338	5
355		7	max	1553.694	1	1007.73	1	123.181	3	0	3	.904	4	4.345	1
356			min	-1368.21	3	-72.372	5	-297.774	4	-.001	2	-.003	10	-.312	5
357		8	max	1550.423	1	1007.73	1	123.181	3	0	3	.798	4	3.983	1
358			min	-1370.664	3	-72.372	5	-294.939	4	-.001	2	-.027	2	-.286	5
359		9	max	1547.151	1	1007.73	1	123.181	3	0	3	.692	4	3.62	1
360			min	-1373.117	3	-72.372	5	-292.104	4	-.001	2	-.054	2	-.26	5
361		10	max	1543.88	1	1007.73	1	123.181	3	0	3	.588	4	3.258	1
362			min	-1375.571	3	-72.372	5	-289.268	4	-.001	2	-.082	2	-.234	5
363		11	max	1540.608	1	1007.73	1	123.181	3	0	3	.486	5	2.896	1
364			min	-1378.024	3	-72.372	5	-286.433	4	-.001	2	-.109	2	-.208	5
365		12	max	1537.337	1	1007.73	1	123.181	3	0	3	.388	5	2.534	1
366			min	-1380.478	3	-72.372	5	-283.598	4	-.001	2	-.137	2	-.182	5

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
367		13	max	1534.065	1	1007.73	1	123.181	3	0	3	.316	3	2.172	1
368			min	-1382.931	3	-72.372	5	-280.763	4	-.001	2	-.164	2	-.156	5
369		14	max	1530.794	1	1007.73	1	123.181	3	0	3	.361	3	1.81	1
370			min	-1385.385	3	-72.372	5	-277.927	4	-.001	2	-.192	2	-.13	5
371		15	max	1527.522	1	1007.73	1	123.181	3	0	3	.405	3	1.448	1
372			min	-1387.839	3	-72.372	5	-275.092	4	-.001	2	-.219	2	-.104	5
373		16	max	1524.251	1	1007.73	1	123.181	3	0	3	.449	3	1.086	1
374			min	-1390.292	3	-72.372	5	-272.257	4	-.001	2	-.246	2	-.078	5
375		17	max	1520.979	1	1007.73	1	123.181	3	0	3	.493	3	.724	1
376			min	-1392.746	3	-72.372	5	-269.422	4	-.001	2	-.274	2	-.052	5
377		18	max	1517.708	1	1007.73	1	123.181	3	0	3	.538	3	.362	1
378			min	-1395.199	3	-72.372	5	-266.586	4	-.001	2	-.301	2	-.026	5
379		19	max	1514.437	1	1007.73	1	123.181	3	0	3	.582	3	0	1
380			min	-1397.653	3	-72.372	5	-263.751	4	-.001	2	-.329	2	0	1
381	M3	1	max	1694.737	2	5.617	4	34.176	2	.01	3	.02	5	0	1
382			min	-711.466	3	1.32	15	-19.205	5	-.021	2	-.002	2	0	1
383		2	max	1694.528	2	4.993	4	34.176	2	.01	3	.014	4	0	15
384			min	-711.623	3	1.174	15	-18.746	5	-.021	2	-.004	3	-.002	4
385		3	max	1694.319	2	4.369	4	34.176	2	.01	3	.022	2	0	15
386			min	-711.779	3	1.027	15	-18.288	5	-.021	2	-.009	3	-.004	4
387		4	max	1694.111	2	3.745	4	34.176	2	.01	3	.034	2	-.001	15
388			min	-711.936	3	.88	15	-17.829	5	-.021	2	-.014	3	-.005	4
389		5	max	1693.902	2	3.121	4	34.176	2	.01	3	.046	2	-.001	15
390			min	-712.092	3	.734	15	-17.37	5	-.021	2	-.019	3	-.006	4
391		6	max	1693.694	2	2.497	4	34.176	2	.01	3	.059	2	-.002	15
392			min	-712.249	3	.587	15	-16.912	5	-.021	2	-.023	3	-.007	4
393		7	max	1693.485	2	1.872	4	34.176	2	.01	3	.071	2	-.002	15
394			min	-712.405	3	.44	15	-16.453	5	-.021	2	-.028	3	-.008	4
395		8	max	1693.276	2	1.248	4	34.176	2	.01	3	.083	2	-.002	15
396			min	-712.562	3	.293	15	-15.994	5	-.021	2	-.033	3	-.009	4
397		9	max	1693.068	2	.624	4	34.176	2	.01	3	.095	2	-.002	15
398			min	-712.718	3	.147	15	-15.536	5	-.021	2	-.038	3	-.009	4
399		10	max	1692.859	2	0	1	34.176	2	.01	3	.107	2	-.002	15
400			min	-712.875	3	0	1	-15.077	5	-.021	2	-.043	3	-.009	4
401		11	max	1692.651	2	-.147	15	34.176	2	.01	3	.119	2	-.002	15
402			min	-713.031	3	-.624	6	-14.618	5	-.021	2	-.048	3	-.009	4
403		12	max	1692.442	2	-.293	15	34.176	2	.01	3	.132	2	-.002	15
404			min	-713.187	3	-1.248	6	-14.16	5	-.021	2	-.052	3	-.009	4
405		13	max	1692.233	2	-.44	15	34.176	2	.01	3	.144	2	-.002	15
406			min	-713.344	3	-1.872	6	-13.701	5	-.021	2	-.057	3	-.008	4
407		14	max	1692.025	2	-.587	15	34.176	2	.01	3	.156	2	-.002	15
408			min	-713.5	3	-2.497	6	-13.546	3	-.021	2	-.062	3	-.007	4
409		15	max	1691.816	2	-.734	15	34.176	2	.01	3	.168	2	-.001	15
410			min	-713.657	3	-3.121	6	-13.546	3	-.021	2	-.067	3	-.006	4
411		16	max	1691.608	2	-.88	15	34.176	2	.01	3	.18	2	-.001	15
412			min	-713.813	3	-3.745	6	-13.546	3	-.021	2	-.072	3	-.005	4
413		17	max	1691.399	2	-1.027	15	34.176	2	.01	3	.193	2	0	15
414			min	-713.97	3	-4.369	6	-13.546	3	-.021	2	-.077	3	-.004	4
415		18	max	1691.19	2	-1.174	15	34.176	2	.01	3	.205	2	0	15
416			min	-714.126	3	-4.993	6	-13.546	3	-.021	2	-.081	3	-.002	4
417		19	max	1690.982	2	-1.32	15	34.176	2	.01	3	.217	2	0	1
418			min	-714.283	3	-5.617	6	-13.546	3	-.021	2	-.086	3	0	1
419	M6	1	max	4713.378	2	5.617	6	0	1	.002	5	.02	4	0	1
420			min	-2452.738	3	1.32	15	-21.212	4	0	1	0	1	0	1
421		2	max	4713.169	2	4.993	6	0	1	.002	5	.013	4	0	15
422			min	-2452.894	3	1.174	15	-20.753	4	0	1	0	1	-.002	6
423		3	max	4712.96	2	4.369	6	0	1	.002	5	.006	4	0	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
424			min	-2453.051	3	1.027	15	-20.294	4	0	1	0	1	-.004	6
425		4	max	4712.752	2	3.745	6	0	1	.002	5	0	1	-.001	15
426			min	-2453.207	3	.88	15	-19.836	4	0	1	-.002	5	-.005	6
427		5	max	4712.543	2	3.121	6	0	1	.002	5	0	1	-.001	15
428			min	-2453.364	3	.734	15	-19.377	4	0	1	-.009	4	-.006	6
429		6	max	4712.335	2	2.497	6	0	1	.002	5	0	1	-.002	15
430			min	-2453.52	3	.587	15	-18.918	4	0	1	-.015	4	-.007	6
431		7	max	4712.126	2	1.872	6	0	1	.002	5	0	1	-.002	15
432			min	-2453.677	3	.44	15	-18.46	4	0	1	-.022	4	-.008	6
433		8	max	4711.917	2	1.248	6	0	1	.002	5	0	1	-.002	15
434			min	-2453.833	3	.293	15	-18.001	4	0	1	-.029	4	-.009	6
435		9	max	4711.709	2	.624	6	0	1	.002	5	0	1	-.002	15
436			min	-2453.989	3	.147	15	-17.542	4	0	1	-.035	4	-.009	6
437		10	max	4711.5	2	0	1	0	1	.002	5	0	1	-.002	15
438			min	-2454.146	3	0	1	-17.084	4	0	1	-.041	4	-.009	6
439		11	max	4711.292	2	-.147	15	0	1	.002	5	0	1	-.002	15
440			min	-2454.302	3	-.624	4	-16.625	4	0	1	-.047	4	-.009	6
441		12	max	4711.083	2	-.293	15	0	1	.002	5	0	1	-.002	15
442			min	-2454.459	3	-1.248	4	-16.166	4	0	1	-.053	4	-.009	6
443		13	max	4710.874	2	-.44	15	0	1	.002	5	0	1	-.002	15
444			min	-2454.615	3	-1.872	4	-15.708	4	0	1	-.059	4	-.008	6
445		14	max	4710.666	2	-.587	15	0	1	.002	5	0	1	-.002	15
446			min	-2454.772	3	-2.497	4	-15.249	4	0	1	-.064	4	-.007	6
447		15	max	4710.457	2	-.734	15	0	1	.002	5	0	1	-.001	15
448			min	-2454.928	3	-3.121	4	-14.791	4	0	1	-.07	4	-.006	6
449		16	max	4710.248	2	-.88	15	0	1	.002	5	0	1	-.001	15
450			min	-2455.085	3	-3.745	4	-14.332	4	0	1	-.075	4	-.005	6
451		17	max	4710.04	2	-1.027	15	0	1	.002	5	0	1	0	15
452			min	-2455.241	3	-4.369	4	-13.873	4	0	1	-.08	4	-.004	6
453		18	max	4709.831	2	-1.174	15	0	1	.002	5	0	1	0	15
454			min	-2455.398	3	-4.993	4	-13.415	4	0	1	-.085	4	-.002	6
455		19	max	4709.623	2	-1.32	15	0	1	.002	5	0	1	0	1
456			min	-2455.554	3	-5.617	4	-12.956	4	0	1	-.089	4	0	1
457	M9	1	max	1694.737	2	5.617	4	13.546	3	.021	2	.021	4	0	1
458			min	-711.466	3	1.32	15	-34.176	2	-.01	3	0	3	0	1
459		2	max	1694.528	2	4.993	4	13.546	3	.021	2	.013	5	0	15
460			min	-711.623	3	1.174	15	-34.176	2	-.01	3	-.01	2	-.002	4
461		3	max	1694.319	2	4.369	4	13.546	3	.021	2	.009	3	0	15
462			min	-711.779	3	1.027	15	-34.176	2	-.01	3	-.022	2	-.004	4
463		4	max	1694.111	2	3.745	4	13.546	3	.021	2	.014	3	-.001	15
464			min	-711.936	3	.88	15	-34.176	2	-.01	3	-.034	2	-.005	4
465		5	max	1693.902	2	3.121	4	13.546	3	.021	2	.019	3	-.001	15
466			min	-712.092	3	.734	15	-34.176	2	-.01	3	-.046	2	-.006	4
467		6	max	1693.694	2	2.497	4	13.546	3	.021	2	.023	3	-.002	15
468			min	-712.249	3	.587	15	-34.176	2	-.01	3	-.059	2	-.007	4
469		7	max	1693.485	2	1.872	4	13.546	3	.021	2	.028	3	-.002	15
470			min	-712.405	3	.44	15	-34.176	2	-.01	3	-.071	2	-.008	4
471		8	max	1693.276	2	1.248	4	13.546	3	.021	2	.033	3	-.002	15
472			min	-712.562	3	.293	15	-34.176	2	-.01	3	-.083	2	-.009	4
473		9	max	1693.068	2	.624	4	13.546	3	.021	2	.038	3	-.002	15
474			min	-712.718	3	.147	15	-34.176	2	-.01	3	-.095	2	-.009	4
475		10	max	1692.859	2	0	1	13.546	3	.021	2	.043	3	-.002	15
476			min	-712.875	3	0	1	-34.176	2	-.01	3	-.107	2	-.009	4
477		11	max	1692.651	2	-.147	15	13.546	3	.021	2	.048	3	-.002	15
478			min	-713.031	3	-.624	6	-34.176	2	-.01	3	-.119	2	-.009	4
479		12	max	1692.442	2	-.293	15	13.546	3	.021	2	.052	3	-.002	15
480			min	-713.187	3	-1.248	6	-34.176	2	-.01	3	-.132	2	-.009	4

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
481		13	max	1692.233	2	-.44	15	13.546	3	.021	2	.057	3	-.002	15
482			min	-713.344	3	-1.872	6	-34.176	2	-.01	3	-.144	2	-.008	4
483		14	max	1692.025	2	-.587	15	13.546	3	.021	2	.062	3	-.002	15
484			min	-713.5	3	-2.497	6	-34.176	2	-.01	3	-.156	2	-.007	4
485		15	max	1691.816	2	-.734	15	13.546	3	.021	2	.067	3	-.001	15
486			min	-713.657	3	-3.121	6	-34.176	2	-.01	3	-.168	2	-.006	4
487		16	max	1691.608	2	-.88	15	13.546	3	.021	2	.072	3	-.001	15
488			min	-713.813	3	-3.745	6	-34.176	2	-.01	3	-.18	2	-.005	4
489		17	max	1691.399	2	-1.027	15	13.546	3	.021	2	.077	3	0	15
490			min	-713.97	3	-4.369	6	-34.176	2	-.01	3	-.193	2	-.004	4
491		18	max	1691.19	2	-1.174	15	13.546	3	.021	2	.081	3	0	15
492			min	-714.126	3	-4.993	6	-34.176	2	-.01	3	-.205	2	-.002	4
493		19	max	1690.982	2	-1.32	15	13.546	3	.021	2	.086	3	0	1
494			min	-714.283	3	-5.617	6	-34.176	2	-.01	3	-.217	2	0	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M1	1	max	-.057	15	-.061	12	.01	1	6.596e-3	3	NC	3	NC	1
2			min	-.432	1	-.733	1	-.736	4	-1.975e-2	2	137.45	1	275.796	5
3		2	max	-.057	15	-.062	15	0	12	6.354e-3	3	NC	12	NC	2
4			min	-.432	1	-.616	1	-.713	4	-1.859e-2	2	155.011	1	289.702	4
5		3	max	-.057	15	-.055	15	-.001	12	5.879e-3	3	8898.988	12	NC	3
6			min	-.432	1	-.502	1	-.683	4	-1.632e-2	2	177.06	1	308.796	4
7		4	max	-.056	15	-.047	15	-.001	12	5.404e-3	3	6904.055	12	NC	3
8			min	-.432	1	-.397	1	-.647	4	-1.405e-2	2	203.813	1	335.199	4
9		5	max	-.056	15	-.04	15	0	3	5.196e-3	3	6980.366	12	NC	3
10			min	-.432	1	-.307	1	-.607	4	-1.244e-2	2	234.25	1	370.204	4
11		6	max	-.056	15	-.032	15	.001	3	5.674e-3	3	9827.991	12	NC	2
12			min	-.431	1	-.234	1	-.566	4	-1.255e-2	2	266.47	1	414.376	4
13		7	max	-.056	15	-.025	15	.002	3	6.153e-3	3	NC	3	NC	1
14			min	-.431	1	-.173	1	-.527	4	-1.265e-2	2	301.155	1	468.121	5
15		8	max	-.056	15	-.018	15	0	3	6.632e-3	3	NC	3	NC	1
16			min	-.431	1	-.118	1	-.491	4	-1.275e-2	2	340.591	1	529.512	5
17		9	max	-.056	15	-.011	15	0	10	7.445e-3	3	6905.177	12	NC	1
18			min	-.43	1	-.067	3	-.459	4	-1.203e-2	2	390.302	1	601.622	5
19		10	max	-.056	15	0	10	.001	2	8.574e-3	3	4261.322	12	NC	1
20			min	-.43	1	-.046	3	-.425	4	-1.053e-2	2	458.371	1	701.865	5
21		11	max	-.056	15	.044	1	0	1	9.702e-3	3	3081.426	12	NC	1
22			min	-.429	1	-.026	3	-.391	4	-9.02e-3	2	556.751	1	842.969	5
23		12	max	-.056	15	.099	1	.003	3	9.159e-3	3	3575.426	10	NC	1
24			min	-.429	1	-.005	3	-.359	4	-7.294e-3	2	711.656	1	1045.091	5
25		13	max	-.056	15	.153	1	.01	3	6.84e-3	3	7632.364	10	NC	1
26			min	-.428	1	.012	12	-.324	4	-5.331e-3	2	977.115	1	1397.648	5
27		14	max	-.056	15	.202	1	.015	3	4.521e-3	3	NC	10	NC	1
28			min	-.427	1	.024	15	-.291	4	-5.451e-3	4	950.76	3	2053.668	5
29		15	max	-.056	15	.241	1	.015	3	2.202e-3	3	NC	2	NC	1
30			min	-.427	1	.032	15	-.264	4	-6.701e-3	4	702.43	3	3285.384	5
31		16	max	-.056	15	.267	1	.011	1	5.626e-3	3	NC	11	NC	2
32			min	-.427	1	.039	15	-.246	4	-5.801e-3	4	507.708	3	5451.663	5
33		17	max	-.056	15	.282	1	.012	1	9.724e-3	3	NC	10	NC	2
34			min	-.427	1	.046	15	-.234	4	-4.65e-3	4	377.122	3	7450.325	1
35		18	max	-.056	15	.389	3	.006	1	1.382e-2	3	NC	1	NC	1
36			min	-.427	1	.054	15	-.227	4	-6.025e-3	2	292.747	3	NC	1
37		19	max	-.056	15	.501	3	-.002	12	1.591e-2	3	NC	1	NC	1
38			min	-.427	1	.061	15	-.224	4	-6.875e-3	2	237.664	3	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
39	M4	1	max	-.025	15	-.019	12	0	1	6.888e-4	4	NC	3	NC	1
40			min	-.68	1	-1.301	2	-.736	4	0	1	88.625	1	275.696	4
41		2	max	-.025	15	-.034	15	0	1	3.993e-4	4	4216.536	12	NC	1
42			min	-.68	1	-1.062	1	-.714	4	0	1	102.87	1	287.636	4
43		3	max	-.025	15	-.028	15	0	1	0	1	3251.608	15	NC	1
44			min	-.68	1	-.847	1	-.685	4	-1.684e-4	4	121.892	1	305.896	4
45		4	max	-.025	15	-.023	15	0	1	0	1	3707.69	15	NC	1
46			min	-.68	1	-.653	1	-.648	4	-7.361e-4	4	146.238	1	331.994	4
47		5	max	-.025	15	-.018	15	0	1	0	1	4212.806	15	NC	1
48			min	-.68	1	-.496	1	-.607	4	-1.044e-3	4	174.453	1	367.248	4
49		6	max	-.025	15	-.014	15	0	1	0	1	4729.958	15	NC	1
50			min	-.679	1	-.382	1	-.566	4	-6.855e-4	4	202.897	1	411.811	4
51		7	max	-.025	15	-.011	15	0	1	0	1	5277.459	15	NC	1
52			min	-.678	1	-.296	1	-.526	4	-3.267e-4	4	231.465	1	465.682	4
53		8	max	-.025	15	-.008	15	0	1	3.274e-5	5	5906.844	15	NC	1
54			min	-.677	1	-.223	1	-.49	4	0	1	262.946	1	527.463	4
55		9	max	-.025	15	-.005	15	0	1	1.214e-4	4	9509.442	12	NC	1
56			min	-.676	1	-.147	1	-.459	4	0	1	305.885	1	596.864	4
57		10	max	-.025	15	-.002	15	0	1	0	1	NC	3	NC	1
58			min	-.675	1	-.062	1	-.424	4	-4.332e-5	4	374.422	1	698.267	4
59		11	max	-.025	15	.03	1	0	1	0	1	9775.061	15	NC	1
60			min	-.673	1	0	3	-.39	4	-2.08e-4	4	495.614	1	840.292	4
61		12	max	-.025	15	.13	1	0	1	0	1	NC	15	NC	1
62			min	-.672	1	.005	15	-.359	4	-1.148e-3	4	761.374	1	1026.987	4
63		13	max	-.025	15	.23	1	0	1	0	1	NC	5	NC	1
64			min	-.671	1	.008	15	-.326	4	-2.911e-3	4	1648.813	1	1350.623	4
65		14	max	-.025	15	.317	1	0	1	0	1	NC	1	NC	1
66			min	-.67	1	.011	15	-.294	4	-4.675e-3	4	1461.173	3	1947.908	4
67		15	max	-.025	15	.376	1	0	1	0	1	NC	4	NC	1
68			min	-.669	1	.014	15	-.268	4	-6.438e-3	4	780.835	3	3027.186	4
69		16	max	-.025	15	.395	1	0	1	0	1	NC	4	NC	1
70			min	-.669	1	.015	15	-.251	4	-5.127e-3	4	431.258	3	4815.44	4
71		17	max	-.025	15	.503	3	0	1	0	1	NC	4	NC	1
72			min	-.669	1	.016	15	-.238	4	-3.455e-3	4	270.223	3	8433.182	4
73		18	max	-.025	15	.728	3	0	1	0	1	NC	4	NC	1
74			min	-.669	1	.016	15	-.229	4	-1.783e-3	4	189.196	3	NC	1
75		19	max	-.025	15	.961	3	0	1	0	1	NC	1	NC	1
76			min	-.669	1	.016	15	-.221	4	-9.304e-4	4	144.263	3	NC	1
77	M7	1	max	.031	5	.027	5	-.001	12	1.975e-2	2	NC	3	NC	1
78			min	-.432	1	-.733	1	-.742	4	-6.596e-3	3	137.45	1	271.348	4
79		2	max	.031	5	.026	5	.007	1	1.859e-2	2	NC	5	NC	2
80			min	-.432	1	-.616	1	-.709	4	-6.354e-3	3	155.011	1	289.129	4
81		3	max	.031	5	.025	5	.016	1	1.632e-2	2	NC	5	NC	3
82			min	-.432	1	-.502	1	-.675	4	-5.879e-3	3	177.06	1	311.059	4
83		4	max	.031	5	.024	5	.018	1	1.405e-2	2	NC	5	NC	3
84			min	-.432	1	-.397	1	-.638	4	-5.404e-3	3	203.813	1	338.427	4
85		5	max	.031	5	.022	5	.015	1	1.244e-2	2	NC	5	NC	3
86			min	-.432	1	-.307	1	-.6	4	-5.196e-3	3	234.25	1	372.658	4
87		6	max	.031	5	.019	5	.01	1	1.255e-2	2	NC	5	NC	2
88			min	-.431	1	-.234	1	-.562	4	-5.674e-3	3	266.47	1	413.795	4
89		7	max	.031	5	.015	5	.004	2	1.265e-2	2	NC	3	NC	1
90			min	-.431	1	-.173	1	-.525	4	-6.153e-3	3	301.155	1	462.73	4
91		8	max	.031	5	.011	5	0	10	1.275e-2	2	NC	3	NC	1
92			min	-.431	1	-.118	1	-.491	4	-6.632e-3	3	340.591	1	521.179	4
93		9	max	.031	5	.007	5	0	3	1.203e-2	2	NC	13	NC	1
94			min	-.43	1	-.067	3	-.458	4	-7.445e-3	3	390.302	1	592.417	4
95		10	max	.031	5	.003	5	.001	3	1.053e-2	2	NC	13	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
96			min	-.43	1	-.046	3	-.425	4	-8.574e-3	3	458.371	1	688.936	4
97		11	max	.031	5	.044	1	0	3	9.02e-3	2	NC	4	NC	1
98			min	-.429	1	-.026	3	-.391	4	-9.702e-3	3	556.751	1	824.877	4
99		12	max	.031	5	.099	1	.003	1	7.294e-3	2	NC	4	NC	1
100			min	-.429	1	-.005	3	-.357	4	-9.159e-3	3	711.656	1	1027.236	4
101		13	max	.031	5	.153	1	.006	2	5.331e-3	2	NC	4	NC	1
102			min	-.428	1	-.008	5	-.323	4	-6.84e-3	3	977.115	1	1369.163	4
103		14	max	.031	5	.202	1	.005	2	3.369e-3	2	NC	4	NC	1
104			min	-.427	1	-.012	5	-.291	4	-4.805e-3	5	950.76	3	1965.004	4
105		15	max	.031	5	.241	1	.001	10	1.406e-3	2	NC	2	NC	1
106			min	-.427	1	-.018	5	-.267	4	-6.374e-3	5	702.43	3	2946.626	4
107		16	max	.031	5	.267	1	-.002	10	2.692e-3	2	NC	4	NC	2
108			min	-.427	1	-.024	5	-.252	4	-5.626e-3	3	507.708	3	4329.325	4
109		17	max	.031	5	.282	1	-.003	10	4.358e-3	2	NC	4	NC	2
110			min	-.427	1	-.032	5	-.24	4	-9.724e-3	3	377.122	3	6677.283	4
111		18	max	.031	5	.389	3	-.001	12	6.025e-3	2	NC	1	NC	1
112			min	-.427	1	-.04	5	-.23	4	-1.382e-2	3	292.747	3	NC	1
113		19	max	.031	5	.501	3	.009	1	6.875e-3	2	NC	1	NC	1
114			min	-.427	1	-.048	5	-.219	4	-1.591e-2	3	237.664	3	NC	1
115	M10	1	max	0	1	.446	3	.427	1	1.423e-2	3	NC	1	NC	1
116			min	-.225	4	-.044	5	-.031	5	-1.135e-3	2	NC	1	NC	1
117		2	max	0	1	.609	3	.461	1	1.593e-2	3	NC	4	NC	3
118			min	-.225	4	-.029	5	-.021	5	-1.832e-3	2	1107.917	3	5309.878	1
119		3	max	0	1	.76	3	.511	1	1.763e-2	3	NC	4	NC	5
120			min	-.225	4	-.019	5	-.011	5	-2.53e-3	2	573.559	3	2152.386	1
121		4	max	0	1	.879	3	.564	1	1.933e-2	3	NC	4	NC	5
122			min	-.225	4	-.012	5	-.003	15	-3.227e-3	2	415.514	3	1318.294	1
123		5	max	0	1	.955	3	.61	1	2.103e-2	3	NC	4	NC	5
124			min	-.225	4	-.012	10	.003	15	-3.925e-3	2	354.08	3	981.491	1
125		6	max	0	1	.982	3	.645	1	2.273e-2	3	NC	4	NC	5
126			min	-.225	4	-.003	10	.007	15	-4.622e-3	2	335.956	3	824.337	1
127		7	max	0	1	.967	3	.666	1	2.444e-2	3	NC	4	NC	5
128			min	-.225	4	.002	15	.011	15	-5.32e-3	2	345.743	3	753.135	1
129		8	max	0	1	.923	3	.673	1	2.614e-2	3	NC	4	NC	5
130			min	-.225	4	.005	15	.015	15	-6.017e-3	2	377.607	3	730.801	1
131		9	max	0	1	.873	3	.672	1	2.784e-2	3	NC	2	NC	5
132			min	-.225	4	.01	15	.019	15	-6.715e-3	2	422.044	3	735.731	1
133		10	max	0	1	.847	3	.669	1	2.954e-2	3	NC	2	NC	5
134			min	-.225	4	.016	15	.025	15	-7.412e-3	2	448.618	3	744.287	1
135		11	max	0	10	.873	3	.672	1	2.784e-2	3	NC	2	NC	5
136			min	-.225	4	.02	15	.031	15	-6.715e-3	2	422.044	3	735.731	1
137		12	max	0	10	.923	3	.673	1	2.614e-2	3	NC	4	NC	5
138			min	-.225	4	.022	15	.036	15	-6.017e-3	2	377.607	3	730.801	1
139		13	max	0	10	.967	3	.666	1	2.444e-2	3	NC	4	NC	5
140			min	-.225	4	.018	10	.04	15	-5.32e-3	2	345.743	3	753.135	1
141		14	max	0	10	.982	3	.645	1	2.273e-2	3	NC	5	NC	5
142			min	-.225	4	-.003	10	.043	15	-4.622e-3	2	335.956	3	824.337	1
143		15	max	0	10	.955	3	.61	1	2.103e-2	3	NC	7	NC	5
144			min	-.225	4	-.012	10	.045	15	-3.925e-3	2	354.08	3	981.491	1
145		16	max	0	10	.879	3	.564	1	1.933e-2	3	NC	15	NC	5
146			min	-.225	4	-.006	10	.047	15	-3.227e-3	2	415.514	3	1318.294	1
147		17	max	0	10	.76	3	.511	1	1.763e-2	3	NC	7	NC	5
148			min	-.225	4	.016	10	.049	15	-2.53e-3	2	573.559	3	2152.386	1
149		18	max	0	10	.609	3	.461	1	1.593e-2	3	NC	5	NC	3
150			min	-.225	4	.045	15	.052	15	-1.832e-3	2	1107.917	3	5309.878	1
151		19	max	0	10	.446	3	.427	1	1.423e-2	3	NC	1	NC	1
152			min	-.225	4	.058	15	.056	15	-1.135e-3	2	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
153	M11	1	max	.001	1	.072	1	.429	1	7.024e-3	1	NC	1	NC	1
154			min	-.374	4	-.015	3	-.031	5	-4.662e-4	5	NC	1	NC	1
155		2	max	0	1	.09	3	.452	1	7.646e-3	1	NC	4	NC	2
156			min	-.374	4	-.016	2	0	15	-3.368e-4	5	1714.041	3	6051.714	4
157		3	max	0	1	.183	3	.497	1	8.269e-3	1	NC	4	NC	3
158			min	-.374	4	-.082	2	.01	15	-2.074e-4	5	908.517	3	2644.958	1
159		4	max	0	1	.246	3	.548	1	8.891e-3	1	NC	4	NC	12
160			min	-.374	4	-.123	2	.013	15	-7.802e-5	5	691.098	3	1504.621	1
161		5	max	0	1	.267	3	.597	1	9.513e-3	1	NC	4	NC	15
162			min	-.374	4	-.133	2	.01	15	1.997e-5	15	638.728	3	1070.699	1
163		6	max	0	1	.246	3	.635	1	1.014e-2	1	NC	4	NC	5
164			min	-.374	4	-.113	2	.005	15	1.063e-4	15	690.52	3	870.974	1
165		7	max	0	1	.189	3	.661	1	1.076e-2	1	NC	4	NC	5
166			min	-.374	4	-.069	2	0	15	1.925e-4	15	881.458	3	776.357	1
167		8	max	0	1	.113	3	.672	1	1.138e-2	1	NC	4	NC	5
168			min	-.374	4	-.013	2	0	15	2.788e-4	15	1403.459	3	738.763	1
169		9	max	0	1	.059	1	.674	1	1.2e-2	1	NC	1	NC	5
170			min	-.374	4	.001	15	.007	15	3.651e-4	15	3139.369	3	733.369	1
171		10	max	0	1	.081	1	.673	1	1.263e-2	1	NC	1	NC	5
172			min	-.374	4	.003	15	.025	15	4.514e-4	15	7301.262	3	737.657	1
173		11	max	0	3	.059	1	.674	1	1.2e-2	1	NC	1	8409.571	15
174			min	-.374	4	.003	15	.043	15	5.011e-4	15	3139.369	3	733.369	1
175		12	max	0	3	.113	3	.672	1	1.138e-2	1	NC	4	7359.921	15
176			min	-.374	4	-.013	2	.05	15	5.508e-4	15	1403.459	3	738.763	1
177		13	max	0	3	.189	3	.661	1	1.076e-2	1	NC	5	9204.098	15
178			min	-.374	4	-.069	2	.05	15	6.005e-4	15	881.458	3	776.357	1
179		14	max	0	3	.246	3	.635	1	1.014e-2	1	NC	5	NC	5
180			min	-.374	4	-.113	2	.044	15	6.502e-4	15	690.52	3	870.974	1
181		15	max	0	3	.267	3	.597	1	9.513e-3	1	NC	7	NC	5
182			min	-.374	4	-.133	2	.037	15	6.999e-4	15	638.728	3	1070.699	1
183		16	max	0	3	.246	3	.548	1	8.891e-3	1	NC	15	NC	4
184			min	-.374	4	-.123	2	.031	15	7.497e-4	15	691.098	3	1504.621	1
185		17	max	0	3	.183	3	.497	1	8.269e-3	1	NC	5	NC	3
186			min	-.374	4	-.082	2	.03	15	7.994e-4	15	908.517	3	2644.958	1
187		18	max	.001	3	.09	3	.452	1	7.646e-3	1	NC	5	NC	2
188			min	-.374	4	-.016	2	.037	15	8.491e-4	15	1714.041	3	7618.547	1
189		19	max	.001	3	.072	1	.429	1	7.024e-3	1	NC	1	NC	1
190			min	-.374	4	-.015	3	.056	15	8.988e-4	15	NC	1	NC	1
191	M12	1	max	0	3	.009	5	.43	1	6.752e-3	1	NC	1	NC	1
192			min	-.475	4	-.093	1	-.031	5	-4.984e-4	5	NC	1	NC	1
193		2	max	0	3	.008	5	.45	1	7.073e-3	1	NC	4	NC	2
194			min	-.475	4	-.195	1	-.001	15	-3.786e-4	5	1422.378	2	6307.08	4
195		3	max	0	3	.039	3	.493	1	7.395e-3	1	NC	5	NC	3
196			min	-.475	4	-.302	2	.009	15	-2.588e-4	5	765.595	2	2861.349	1
197		4	max	0	3	.069	3	.544	1	7.717e-3	1	NC	5	9437.363	12
198			min	-.475	4	-.375	2	.012	15	-1.39e-4	5	583.63	2	1576.433	1
199		5	max	0	3	.076	3	.594	1	8.038e-3	1	NC	5	NC	15
200			min	-.475	4	-.404	2	.009	15	-2.583e-5	15	533.237	2	1101.618	1
201		6	max	0	3	.06	3	.634	1	8.36e-3	1	NC	5	NC	5
202			min	-.475	4	-.389	2	.004	15	5.426e-5	15	558.958	2	885.162	1
203		7	max	0	3	.026	3	.661	1	8.682e-3	1	NC	5	NC	5
204			min	-.475	4	-.337	2	0	15	1.344e-4	15	667.481	2	781.722	1
205		8	max	0	3	-.005	15	.674	1	9.003e-3	1	NC	5	NC	5
206			min	-.475	4	-.265	1	0	15	2.145e-4	15	915.01	2	738.503	1
207		9	max	0	3	-.006	15	.677	1	9.325e-3	1	NC	5	NC	5
208			min	-.475	4	-.212	1	.007	15	2.945e-4	15	1408.678	2	729.333	1
209		10	max	0	1	-.007	15	.676	1	9.647e-3	1	NC	3	NC	5

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
210			min	-.475	4	-.188	1	.025	15	3.746e-4	15	1878.255	2	732.053	1
211		11	max	0	1	-.009	15	.677	1	9.325e-3	1	NC	5	8254.535	15
212			min	-.475	4	-.212	1	.043	15	4.319e-4	15	1408.678	2	729.333	1
213		12	max	0	1	-.012	12	.674	1	9.003e-3	1	NC	5	7165.73	15
214			min	-.475	4	-.265	1	.051	15	4.892e-4	15	915.01	2	738.503	1
215		13	max	0	1	.026	3	.661	1	8.682e-3	1	NC	5	8829.179	15
216			min	-.475	4	-.337	2	.051	15	5.464e-4	15	667.481	2	781.722	1
217		14	max	0	1	.06	3	.634	1	8.36e-3	1	NC	5	NC	5
218			min	-.475	4	-.389	2	.045	15	6.037e-4	15	558.958	2	885.162	1
219		15	max	0	1	.076	3	.594	1	8.038e-3	1	NC	5	NC	5
220			min	-.475	4	-.404	2	.038	15	6.609e-4	15	533.237	2	1101.618	1
221		16	max	0	1	.069	3	.544	1	7.717e-3	1	NC	5	NC	4
222			min	-.475	4	-.375	2	.032	15	7.182e-4	15	583.63	2	1576.433	1
223		17	max	0	1	.039	3	.493	1	7.395e-3	1	NC	5	NC	3
224			min	-.475	4	-.302	2	.03	15	7.754e-4	15	765.595	2	2861.349	1
225		18	max	0	1	-.008	12	.45	1	7.073e-3	1	NC	5	NC	2
226			min	-.475	4	-.195	1	.037	15	8.327e-4	15	1422.378	2	8233.491	5
227		19	max	0	1	-.015	15	.43	1	6.752e-3	1	NC	1	NC	1
228			min	-.475	4	-.093	1	.056	15	8.899e-4	15	NC	1	NC	1
229	M13	1	max	0	12	.026	5	.432	1	1.551e-2	2	NC	1	NC	1
230			min	-.726	4	-.676	1	-.031	5	-1.886e-3	3	NC	1	NC	1
231		2	max	0	12	.017	5	.468	1	1.731e-2	2	NC	5	NC	3
232			min	-.726	4	-.84	1	-.003	5	-2.482e-3	3	913.243	2	4980.021	1
233		3	max	0	12	.017	3	.52	1	1.911e-2	2	NC	5	NC	12
234			min	-.726	4	-1.003	2	.008	15	-3.078e-3	3	477.8	2	2056.218	1
235		4	max	0	12	.054	3	.574	1	2.091e-2	2	NC	5	8865.858	12
236			min	-.726	4	-1.146	2	.013	15	-3.674e-3	3	346.649	2	1270.99	1
237		5	max	0	12	.068	3	.621	1	2.271e-2	2	NC	5	NC	15
238			min	-.726	4	-1.24	2	.013	15	-4.271e-3	3	293.426	2	951.195	1
239		6	max	0	12	.061	3	.657	1	2.452e-2	2	NC	5	NC	5
240			min	-.726	4	-1.283	2	.011	15	-4.867e-3	3	274.218	2	801.315	1
241		7	max	0	12	.036	3	.678	1	2.632e-2	2	NC	15	NC	5
242			min	-.726	4	-1.28	2	.008	15	-5.463e-3	3	275.367	2	733.305	1
243		8	max	0	12	0	3	.685	1	2.812e-2	2	NC	15	NC	5
244			min	-.726	4	-1.246	2	.008	15	-6.059e-3	3	290.744	2	712.03	1
245		9	max	0	12	-.026	12	.683	1	2.992e-2	2	NC	15	NC	5
246			min	-.726	4	-1.201	2	.013	15	-6.656e-3	3	313.067	2	716.835	1
247		10	max	0	1	-.035	12	.68	1	3.172e-2	2	NC	15	NC	5
248			min	-.726	4	-1.178	2	.025	15	-7.252e-3	3	326.164	2	725.056	1
249		11	max	0	1	-.026	12	.683	1	2.992e-2	2	NC	15	NC	15
250			min	-.726	4	-1.201	2	.038	15	-6.656e-3	3	313.067	2	716.835	1
251		12	max	0	1	0	3	.685	1	2.812e-2	2	NC	15	NC	15
252			min	-.726	4	-1.246	2	.043	15	-6.059e-3	3	290.744	2	712.03	1
253		13	max	0	1	.036	3	.678	1	2.632e-2	2	NC	15	NC	15
254			min	-.726	4	-1.28	2	.043	15	-5.463e-3	3	275.367	2	733.305	1
255		14	max	0	1	.061	3	.657	1	2.452e-2	2	NC	15	NC	5
256			min	-.726	4	-1.283	2	.04	15	-4.867e-3	3	274.218	2	801.315	1
257		15	max	0	1	.068	3	.621	1	2.271e-2	2	NC	15	NC	5
258			min	-.726	4	-1.24	2	.036	15	-4.271e-3	3	293.426	2	951.195	1
259		16	max	0	1	.054	3	.574	1	2.091e-2	2	NC	15	NC	4
260			min	-.726	4	-1.146	2	.032	15	-3.674e-3	3	346.649	2	1270.99	1
261		17	max	0	1	.017	3	.52	1	1.911e-2	2	NC	5	NC	4
262			min	-.726	4	-1.003	2	.033	15	-3.078e-3	3	477.8	2	2056.218	1
263		18	max	0	1	-.027	12	.468	1	1.731e-2	2	NC	5	NC	3
264			min	-.726	4	-.84	1	.04	15	-2.482e-3	3	913.243	2	4980.021	1
265		19	max	0	1	-.065	12	.432	1	1.551e-2	2	NC	1	NC	1
266			min	-.726	4	-.676	1	.057	15	-1.886e-3	3	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
267	M2	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
268			min	0	1	0	1	0	1	0	1	NC	1	NC	1
269		2	max	0	3	0	15	.001	5	3.41e-3	2	NC	1	NC	1
270			min	0	2	-.002	1	0	1	-6.399e-3	5	NC	1	NC	1
271		3	max	0	3	-.001	15	.005	5	4.813e-3	2	NC	2	NC	1
272			min	0	2	-.008	1	0	1	-9.288e-3	5	9291.674	1	NC	1
273		4	max	0	3	-.003	15	.011	5	4.429e-3	2	NC	4	NC	1
274			min	0	2	-.019	1	-.001	1	-9.05e-3	5	4118.618	1	6749.951	5
275		5	max	0	3	-.004	15	.02	5	4.045e-3	2	NC	5	NC	1
276			min	0	2	-.033	1	-.002	1	-8.811e-3	5	2341.681	1	3913.077	5
277		6	max	0	3	-.007	15	.03	5	3.66e-3	2	NC	15	NC	1
278			min	0	2	-.051	1	-.003	1	-8.573e-3	5	1521.53	1	2577.215	5
279		7	max	0	3	-.01	15	.042	5	3.276e-3	2	8044.844	15	NC	1
280			min	0	2	-.072	1	-.004	1	-8.335e-3	5	1075.146	1	1840.958	5
281		8	max	0	3	-.013	15	.056	5	2.892e-3	2	6044.845	15	NC	1
282			min	0	2	-.096	1	-.005	1	-8.096e-3	5	805.012	1	1391.439	5
283		9	max	0	3	-.016	15	.071	5	2.508e-3	2	4733.153	15	NC	1
284			min	0	2	-.123	1	-.006	1	-7.858e-3	5	628.701	1	1096.111	5
285		10	max	0	3	-.02	15	.087	5	2.123e-3	2	3826.108	15	NC	1
286			min	0	2	-.153	1	-.007	1	-7.619e-3	5	507.221	1	891.556	5
287		11	max	0	3	-.024	15	.104	5	1.739e-3	2	3171.359	15	NC	1
288			min	-.001	2	-.185	1	-.007	1	-7.381e-3	5	419.774	1	743.719	5
289		12	max	.001	3	-.029	15	.123	4	1.355e-3	2	2683.306	15	NC	1
290			min	-.001	2	-.219	1	-.008	1	-7.143e-3	5	354.735	1	633.347	4
291		13	max	.001	3	-.034	15	.142	4	9.707e-4	2	2309.316	15	NC	1
292			min	-.001	2	-.254	1	-.009	1	-6.929e-3	4	304.986	1	548.407	4
293		14	max	.001	3	-.038	15	.161	4	5.865e-4	2	2016.387	15	NC	1
294			min	-.001	2	-.292	1	-.009	1	-6.729e-3	4	266.078	1	481.856	4
295		15	max	.001	3	-.044	15	.181	4	6.752e-4	3	1782.592	15	NC	1
296			min	-.001	2	-.33	1	-.009	1	-6.529e-3	4	235.064	1	428.748	4
297		16	max	.001	3	-.049	15	.201	4	8.926e-4	3	1593.031	15	NC	1
298			min	-.002	2	-.37	1	-.008	1	-6.329e-3	4	209.945	1	385.719	4
299		17	max	.001	3	-.054	15	.221	4	1.11e-3	3	1437.268	15	NC	1
300			min	-.002	2	-.41	1	-.008	1	-6.129e-3	4	189.323	1	350.409	4
301		18	max	.002	3	-.059	15	.242	4	1.327e-3	3	1307.783	15	NC	1
302			min	-.002	2	-.451	1	-.009	3	-5.929e-3	4	172.195	1	321.124	4
303		19	max	.002	3	-.065	15	.262	4	1.545e-3	3	1199.09	15	NC	1
304			min	-.002	2	-.492	1	-.015	3	-5.729e-3	4	157.828	1	296.619	4
305	M5	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
306			min	0	1	0	1	0	1	0	1	NC	1	NC	1
307		2	max	0	3	0	15	.001	4	0	1	NC	1	NC	1
308			min	0	2	-.003	1	0	1	-6.685e-3	4	NC	1	NC	1
309		3	max	0	3	0	15	.005	4	0	1	NC	3	NC	1
310			min	0	2	-.012	1	0	1	-9.696e-3	4	6344.098	1	NC	1
311		4	max	0	3	-.001	15	.012	4	0	1	NC	4	NC	1
312			min	0	2	-.028	1	0	1	-9.431e-3	4	2732.115	1	6501.22	4
313		5	max	.001	3	-.002	15	.021	4	0	1	NC	5	NC	1
314			min	-.001	2	-.051	1	0	1	-9.167e-3	4	1534.034	1	3770.254	4
315		6	max	.001	3	-.003	15	.031	4	0	1	NC	5	NC	1
316			min	-.002	2	-.078	1	0	1	-8.902e-3	4	989.828	1	2484.381	4
317		7	max	.002	3	-.004	15	.044	4	0	1	NC	5	NC	1
318			min	-.002	2	-.111	1	0	1	-8.638e-3	4	696.346	1	1775.699	4
319		8	max	.002	3	-.006	15	.058	4	0	1	NC	15	NC	1
320			min	-.002	2	-.149	1	0	1	-8.373e-3	4	519.802	1	1343.018	4
321		9	max	.002	3	-.007	15	.073	4	0	1	NC	15	NC	1
322			min	-.002	2	-.192	1	0	1	-8.109e-3	4	405.057	1	1058.758	4
323		10	max	.003	3	-.009	15	.09	4	0	1	8763.159	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
324			min	-.003	2	-.238	1	0	1	-7.844e-3	4	326.242	1	861.874	4
325		11	max	.003	3	-.011	15	.108	4	0	1	7251.808	15	NC	1
326			min	-.003	2	-.288	1	0	1	-7.58e-3	4	269.642	1	719.597	4
327		12	max	.003	3	-.013	15	.127	4	0	1	6127.859	15	NC	1
328			min	-.003	2	-.341	1	0	1	-7.315e-3	4	227.625	1	613.445	4
329		13	max	.003	3	-.015	15	.146	4	0	1	5268.214	15	NC	1
330			min	-.003	2	-.397	1	0	1	-7.051e-3	4	195.536	1	532.078	4
331		14	max	.004	3	-.017	15	.166	4	0	1	4595.95	15	NC	1
332			min	-.004	2	-.455	1	0	1	-6.786e-3	4	170.471	1	468.358	4
333		15	max	.004	3	-.019	15	.186	4	0	1	4060.106	15	NC	1
334			min	-.004	2	-.516	1	0	1	-6.522e-3	4	150.512	1	417.55	4
335		16	max	.004	3	-.021	15	.206	4	0	1	3626.135	15	NC	1
336			min	-.004	2	-.578	1	0	1	-6.257e-3	4	134.362	1	376.43	4
337		17	max	.004	3	-.024	15	.226	4	0	1	3269.887	15	NC	1
338			min	-.005	2	-.641	1	0	1	-5.992e-3	4	121.114	1	342.737	4
339		18	max	.005	3	-.026	15	.246	4	0	1	2973.995	15	NC	1
340			min	-.005	2	-.705	1	0	1	-5.728e-3	4	110.118	1	314.851	4
341		19	max	.005	3	-.028	15	.266	4	0	1	2725.805	15	NC	1
342			min	-.005	2	-.769	1	0	1	-5.463e-3	4	100.9	1	291.579	4
343	M8	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
344			min	0	1	0	1	0	1	0	1	NC	1	NC	1
345		2	max	0	3	0	5	.001	4	1.393e-3	3	NC	1	NC	1
346			min	0	2	-.002	1	0	3	-6.948e-3	4	NC	1	NC	1
347		3	max	0	3	0	5	.005	4	1.934e-3	3	NC	2	NC	1
348			min	0	2	-.008	1	0	3	-1.006e-2	4	9291.674	1	NC	1
349		4	max	0	3	.002	5	.012	4	1.716e-3	3	NC	4	NC	1
350			min	0	2	-.019	1	-.001	3	-9.753e-3	4	4118.618	1	6522.521	4
351		5	max	0	3	.003	5	.021	4	1.499e-3	3	NC	4	NC	1
352			min	0	2	-.033	1	-.002	3	-9.446e-3	4	2341.681	1	3783.296	4
353		6	max	0	3	.004	5	.031	4	1.282e-3	3	NC	4	NC	1
354			min	0	2	-.051	1	-.003	3	-9.14e-3	4	1521.53	1	2493.197	4
355		7	max	0	3	.005	5	.044	4	1.064e-3	3	NC	5	NC	1
356			min	0	2	-.072	1	-.004	3	-8.833e-3	4	1075.146	1	1782.074	4
357		8	max	0	3	.007	5	.058	4	8.467e-4	3	NC	5	NC	1
358			min	0	2	-.096	1	-.005	3	-8.527e-3	4	805.012	1	1347.857	4
359		9	max	0	3	.009	5	.073	4	6.293e-4	3	NC	13	NC	1
360			min	0	2	-.123	1	-.006	3	-8.22e-3	4	628.701	1	1062.565	4
361		10	max	0	3	.011	5	.09	4	4.119e-4	3	NC	13	NC	1
362			min	0	2	-.153	1	-.006	3	-7.913e-3	4	507.221	1	864.955	4
363		11	max	0	3	.014	5	.107	4	1.945e-4	3	9103.278	13	NC	1
364			min	-.001	2	-.185	1	-.006	3	-7.607e-3	4	419.774	1	722.146	4
365		12	max	.001	3	.016	5	.126	4	-1.597e-5	12	7680.422	13	NC	1
366			min	-.001	2	-.219	1	-.006	3	-7.3e-3	4	354.735	1	615.592	4
367		13	max	.001	3	.019	5	.145	4	-7.05e-5	9	6594.632	13	NC	1
368			min	-.001	2	-.254	1	-.005	3	-6.994e-3	4	304.986	1	533.913	4
369		14	max	.001	3	.022	5	.165	4	4.508e-5	9	5747.115	13	NC	1
370			min	-.001	2	-.292	1	-.004	3	-6.687e-3	4	266.078	1	469.945	4
371		15	max	.001	3	.024	5	.185	4	1.607e-4	9	5072.651	13	NC	1
372			min	-.001	2	-.33	1	-.002	3	-6.392e-3	5	235.064	1	418.937	4
373		16	max	.001	3	.027	5	.205	4	4.233e-4	1	4527.15	13	NC	1
374			min	-.002	2	-.37	1	0	12	-6.128e-3	5	209.945	1	377.651	4
375		17	max	.001	3	.03	5	.226	4	7.549e-4	1	4079.87	13	NC	1
376			min	-.002	2	-.41	1	.002	10	-5.865e-3	5	189.323	1	343.82	4
377		18	max	.002	3	.033	5	.246	4	1.086e-3	1	3708.749	13	NC	1
378			min	-.002	2	-.451	1	0	10	-5.601e-3	5	172.195	1	315.817	4
379		19	max	.002	3	.036	5	.265	4	1.418e-3	1	3397.74	13	NC	1
380			min	-.002	2	-.492	1	0	10	-5.337e-3	5	157.828	1	292.442	4

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
381	M3	1	max	.004	1	0	15	.003	5	1.902e-3	2	NC	1	NC	1
382			min	0	15	-.002	1	0	1	-2.904e-3	5	NC	1	NC	1
383		2	max	.003	1	-.005	15	.042	5	2.207e-3	2	NC	1	NC	4
384			min	0	15	-.033	1	-.02	2	-2.903e-3	5	NC	1	3742.487	2
385		3	max	.003	3	-.009	15	.081	5	2.512e-3	2	NC	1	NC	4
386			min	0	15	-.065	1	-.04	2	-2.902e-3	5	NC	1	1885.692	2
387		4	max	.003	3	-.013	15	.121	5	2.817e-3	2	NC	1	9311.411	13
388			min	0	10	-.096	1	-.059	2	-2.901e-3	5	NC	1	1275.193	2
389		5	max	.004	3	-.017	15	.16	5	3.122e-3	2	NC	1	6807.503	13
390			min	0	10	-.127	1	-.076	2	-2.9e-3	5	NC	1	976.816	2
391		6	max	.004	3	-.021	15	.199	5	3.427e-3	2	NC	1	5386.967	13
392			min	0	10	-.158	1	-.093	2	-2.899e-3	5	NC	1	803.989	2
393		7	max	.004	3	-.026	15	.238	5	3.732e-3	2	NC	1	4502.398	13
394			min	-.001	2	-.189	1	-.107	2	-2.899e-3	5	8990.605	4	694.8	2
395		8	max	.005	3	-.03	15	.277	5	4.037e-3	2	NC	1	3923.809	13
396			min	-.002	2	-.22	1	-.119	2	-2.898e-3	5	8301.976	4	623.053	2
397		9	max	.005	3	-.034	15	.314	5	4.342e-3	2	NC	1	3540.114	13
398			min	-.003	2	-.25	1	-.128	2	-2.897e-3	5	7931.316	4	574.942	14
399		10	max	.005	3	-.038	15	.351	5	4.647e-3	2	NC	1	3293.706	13
400			min	-.003	2	-.28	1	-.135	2	-2.896e-3	5	7814.056	4	508.052	14
401		11	max	.005	3	-.041	15	.386	5	4.952e-3	2	NC	1	3155.204	13
402			min	-.004	2	-.31	1	-.138	2	-2.895e-3	5	7931.316	4	454.672	14
403		12	max	.006	3	-.045	15	.421	5	5.257e-3	2	NC	1	3113.425	13
404			min	-.005	2	-.34	1	-.137	2	-2.894e-3	5	8301.976	4	411.097	14
405		13	max	.006	3	-.049	15	.453	5	5.563e-3	2	NC	1	3173.137	13
406			min	-.005	2	-.37	1	-.131	2	-2.893e-3	5	8990.605	4	374.86	14
407		14	max	.006	3	-.053	15	.484	5	5.868e-3	2	NC	1	3359.901	13
408			min	-.006	2	-.399	1	-.121	2	-2.893e-3	5	NC	1	344.25	14
409		15	max	.007	3	-.056	15	.514	5	6.173e-3	2	NC	1	3738.229	13
410			min	-.007	2	-.428	1	-.106	2	-2.892e-3	5	NC	1	318.05	14
411		16	max	.007	3	-.06	15	.541	5	6.478e-3	2	NC	1	4470.328	13
412			min	-.008	2	-.457	1	-.086	2	-2.891e-3	5	NC	1	295.365	14
413		17	max	.007	3	-.063	15	.567	4	6.783e-3	2	NC	1	6054.627	13
414			min	-.008	2	-.486	1	-.059	2	-2.953e-3	3	NC	1	275.524	14
415		18	max	.007	3	-.067	15	.593	4	7.088e-3	2	NC	1	NC	13
416			min	-.009	2	-.515	1	-.027	2	-3.094e-3	3	NC	1	258.017	14
417		19	max	.008	3	-.07	15	.618	4	7.393e-3	2	NC	1	NC	1
418			min	-.01	2	-.544	1	0	12	-3.234e-3	3	NC	1	242.445	14
419	M6	1	max	.006	1	0	15	.003	4	0	1	NC	1	NC	1
420			min	0	15	-.003	1	0	1	-3.039e-3	4	NC	1	NC	1
421		2	max	.005	3	-.002	15	.044	4	0	1	NC	1	NC	1
422			min	0	15	-.052	1	0	1	-3.068e-3	4	NC	1	NC	1
423		3	max	.006	3	-.004	15	.085	4	0	1	NC	1	NC	1
424			min	0	10	-.101	1	0	1	-3.097e-3	4	NC	1	5908.303	4
425		4	max	.007	3	-.007	15	.126	4	0	1	NC	1	NC	1
426			min	-.002	2	-.151	1	0	1	-3.126e-3	4	NC	1	3862.362	4
427		5	max	.008	3	-.009	15	.167	4	0	1	NC	1	NC	1
428			min	-.004	2	-.2	1	0	1	-3.155e-3	4	NC	1	2874.545	4
429		6	max	.009	3	-.011	15	.208	4	0	1	NC	1	NC	1
430			min	-.006	2	-.248	1	0	1	-3.185e-3	4	NC	1	2308.248	4
431		7	max	.01	3	-.013	15	.248	4	0	1	NC	1	NC	1
432			min	-.008	2	-.297	1	0	1	-3.214e-3	4	8990.605	6	1952.818	4
433		8	max	.011	3	-.015	15	.287	4	0	1	NC	1	NC	1
434			min	-.01	2	-.345	1	0	1	-3.243e-3	4	8301.976	6	1719.301	4
435		9	max	.012	3	-.016	15	.326	4	0	1	NC	1	NC	1
436			min	-.012	2	-.394	1	0	1	-3.272e-3	4	7931.316	6	1564.581	4
437		10	max	.013	3	-.018	15	.364	4	0	1	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
438			min	-.014	2	-.442	1	0	1	-3.301e-3	4	7814.056	6	1466.35	4
439		11	max	.014	3	-.02	15	.4	4	0	1	NC	1	NC	1
440			min	-.015	2	-.489	1	0	1	-3.33e-3	4	7931.316	6	1413.458	4
441		12	max	.015	3	-.022	15	.435	4	0	1	NC	1	NC	1
442			min	-.017	2	-.537	1	0	1	-3.359e-3	4	8301.976	6	1402.173	4
443		13	max	.016	3	-.023	15	.467	4	0	1	NC	1	NC	1
444			min	-.019	2	-.584	1	0	1	-3.388e-3	4	8990.605	6	1435.57	4
445		14	max	.017	3	-.025	15	.498	4	0	1	NC	1	NC	1
446			min	-.021	2	-.631	1	0	1	-3.417e-3	4	NC	1	1525.97	4
447		15	max	.018	3	-.026	15	.527	4	0	1	NC	1	NC	1
448			min	-.023	2	-.678	1	0	1	-3.446e-3	4	NC	1	1703.412	4
449		16	max	.019	3	-.028	15	.554	4	0	1	NC	1	NC	1
450			min	-.025	2	-.725	1	0	1	-3.476e-3	4	NC	1	2042.723	4
451		17	max	.021	3	-.029	15	.578	4	0	1	NC	1	NC	1
452			min	-.027	2	-.772	1	0	1	-3.505e-3	4	NC	1	2773.203	4
453		18	max	.022	3	-.03	15	.6	4	0	1	NC	1	NC	1
454			min	-.029	2	-.818	1	0	1	-3.534e-3	4	NC	1	5048.077	4
455		19	max	.023	3	-.032	15	.619	4	0	1	NC	1	NC	1
456			min	-.031	2	-.865	1	0	1	-3.563e-3	4	NC	1	NC	1
457	M9	1	max	.004	1	0	5	.003	4	7.085e-4	3	NC	1	NC	1
458			min	0	5	-.002	1	0	3	-3.194e-3	4	NC	1	NC	1
459		2	max	.003	1	.002	5	.045	4	8.488e-4	3	NC	1	NC	5
460			min	0	5	-.033	1	-.009	3	-3.234e-3	4	NC	1	3742.487	2
461		3	max	.003	3	.003	5	.088	4	9.891e-4	3	NC	1	8827.772	15
462			min	0	5	-.065	1	-.017	3	-3.275e-3	4	NC	1	1885.692	2
463		4	max	.003	3	.005	5	.13	4	1.129e-3	3	NC	1	5768.644	15
464			min	0	5	-.096	1	-.025	3	-3.315e-3	4	NC	1	1275.193	2
465		5	max	.004	3	.006	5	.173	4	1.27e-3	3	NC	1	4291.898	15
466			min	0	5	-.127	1	-.032	3	-3.356e-3	4	NC	1	976.816	2
467		6	max	.004	3	.008	5	.215	4	1.41e-3	3	NC	1	3445.429	15
468			min	0	10	-.158	1	-.039	3	-3.427e-3	2	9817.961	5	803.989	2
469		7	max	.004	3	.01	5	.256	4	1.55e-3	3	NC	1	2932.234	12
470			min	-.001	2	-.189	1	-.045	3	-3.732e-3	2	8011.476	5	694.8	2
471		8	max	.005	3	.012	5	.296	4	1.691e-3	3	NC	1	2630.183	12
472			min	-.002	2	-.22	1	-.05	3	-4.037e-3	2	6710.933	5	623.053	2
473		9	max	.005	3	.014	5	.335	4	1.831e-3	3	NC	1	2432.501	12
474			min	-.003	2	-.25	1	-.054	3	-4.342e-3	2	5730.393	5	576.075	2
475		10	max	.005	3	.016	5	.373	4	1.971e-3	3	NC	1	2312.009	12
476			min	-.003	2	-.28	1	-.057	3	-4.647e-3	2	4966.115	5	547.409	2
477		11	max	.005	3	.018	5	.409	4	2.111e-3	3	NC	1	2255.965	12
478			min	-.004	2	-.31	1	-.058	3	-4.952e-3	2	4355.454	5	534.02	2
479		12	max	.006	3	.02	5	.443	4	2.252e-3	3	NC	1	2261.786	12
480			min	-.005	2	-.34	1	-.058	3	-5.257e-3	2	3858.193	5	535.288	2
481		13	max	.006	3	.023	5	.475	4	2.392e-3	3	NC	1	2337.021	12
482			min	-.005	2	-.37	1	-.056	3	-5.563e-3	2	3447.228	5	552.987	2
483		14	max	.006	3	.025	5	.505	4	2.532e-3	3	NC	1	2503.986	12
484			min	-.006	2	-.399	1	-.052	3	-5.868e-3	2	3103.562	5	592.387	2
485		15	max	.007	3	.028	5	.532	4	2.673e-3	3	NC	1	2814.316	12
486			min	-.007	2	-.428	1	-.047	3	-6.173e-3	2	2813.443	5	665.692	2
487		16	max	.007	3	.03	5	.556	4	2.813e-3	3	NC	1	3394.69	12
488			min	-.008	2	-.457	1	-.039	3	-6.478e-3	2	2566.652	5	802.845	2
489		17	max	.007	3	.033	5	.578	4	2.953e-3	3	NC	1	4631.529	12
490			min	-.008	2	-.486	1	-.029	3	-6.783e-3	2	2355.423	5	1095.195	2
491		18	max	.007	3	.036	5	.596	4	3.094e-3	3	NC	1	8465.897	12
492			min	-.009	2	-.515	1	-.016	3	-7.088e-3	2	2173.754	5	2001.608	2
493		19	max	.008	3	.038	5	.61	4	3.234e-3	3	NC	1	NC	1
494			min	-.01	2	-.544	1	-.016	1	-7.393e-3	2	2016.936	5	NC	1