

Schletter, Inc.		25° Tilt w/ Seismic Design
HCV	Standard FS Racking System	
	Representative Calculations - ASCE 7-10	

1. INTRODUCTION

1.1 Project Description

The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. FS ground mount system.

1.2 Construction

Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to galvanized steel posts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

	Maximum		Minimum
Height =	1700 mm	Height =	1550 mm
Width =	1050 mm	Width =	970 mm
Dead Load =	3.00 psf	Dead Load =	1.75 psf

Modules Per Row =	2
Module Tilt =	25°
Maximum Height Above Grade =	3 ft



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

1.3 Technical Codes

- ASCE 7-10 - Chapter 26-31, Wind Loads
- ASCE 7-10 - Chapter 7, Snow Loads
- ASCE 7-10 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2012, 2015
- Aluminum Design Manual, Eighth Edition, 2005

2. LOAD ACTIONS

2.1 Permanent Loads

g_{MAX} =	3.00	psf	*Self-weight of the PV modules.*
g_{MIN} =	1.75	psf	

2.2 Snow Loads

Ground Snow Load, P_g =	30.00	psf	
Sloped Roof Snow Load, P_s =	18.56	psf	*(ASCE 7-10, Eq. 7.4-1)*
I_s =	1.00		
C_s =	0.82		
C_e =	0.90		
C_t =	1.20		

2.3 Wind Loads

Design Wind Speed, V =	115	mph	Exposure Category = C
Height <	15	ft	Importance Category = II
Peak Velocity Pressure, q_z =	20.76	psf	*Including the gust factor, G=0.85. (ASCE 7-10, Eq. 27.3-1)*

Pressure Coefficients

$Cf+_{TOP}$ =	1.1	*(Pressure)*	*Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0510-e. Negative forces are applied away from the surface.*
$Cf+_{BOTTOM}$ =	1.7		
$Cf-_{TOP}$ =	-2.2	*(Suction)*	
$Cf-_{BOTTOM}$ =	-1		

2.4 Seismic Loads

S_S =	2.50	R =	1.25	*ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.*
S_{DS} =	1.67	C_S =	0.8	
S_1 =	1.00	ρ =	1.3	
S_{D1} =	1.00	Ω =	1.25	
T_a =	0.08	C_d =	1.25	

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.5W
1.2D + 1.0W + 0.5S
0.9D + 1.0W [M]
1.54D + 1.3E + 0.2S [R]
0.56D + 1.3E [R]
1.54D + 1.25E + 0.2S [O]
0.56D + 1.25E [O]

(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S
1.0D + 0.6W
1.0D + 0.75L + 0.45W + 0.75S
0.6D + 0.6W [M]
1.238D + 0.875E [O]
1.1785D + 0.65625E + 0.75S [O]
0.362D + 0.875E [O]

(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)

[M] *Uses the minimum allowable module dead load.*
[R] *Include redundancy factor of 1.3.*
[O] *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location
M10	Top
M11	Mid-Top
M12	Mid-Bottom
M13	Bottom

Posts	Location
M2	Outer
M5	Inner
M8	Outer

Girders	Location
M1	Outer
M4	Inner
M7	Outer

Reactions	Location
N9	Outer
N19	Inner
N29	Outer

Struts	Location
M3	Outer
M6	Inner
M9	Outer

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type =	**S1.5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	138	in
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	25.07	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	23.08	ksi
S_y =	1.33	in^3
S_x =	0.6	in^3
E =	10100	ksi
I_y =	2.16	in^4
I_x =	1.07	in^4
A =	1.25	in^2
g =	1.50	lbs/ft
M_y =	1.967	k-ft
M_z =	0.319	k-ft
$M_{y\ allowable}$ =	2.779	k-ft
$M_{z\ allowable}$ =	1.154	k-ft
Utilization =	98%	



DETAIL VIEW

4.2 Girder Design

Loads from purlins are transferred to the posts using an inclined girder, which is connected to the steel post. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type =	**T5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	63.82	in
$\Phi F_{ty\ AXIAL}$ =	30.80	ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	30.46	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	31.56	ksi
S_y =	1.98	in^3
S_x =	1.32	in^3
E =	10100	ksi
I_y =	4.74	in^4
I_x =	1.83	in^4
A =	1.93	in^2
g =	2.32	lbs/ft
M_y =	3.650	k-ft
M_z =	0.000	k-ft
P_n =	0.027	k
$M_{y\ allowable}$ =	5.026	k-ft
$M_{z\ allowable}$ =	3.472	k-ft
$P_{n\ allowable}$ =	59.439	k
Utilization =	73%	



DETAIL VIEW

4.3 Strut Design

The aluminum strut connects a portion of the girder to the galvanized steel post. Girder forces are then transferred down through the strut into the post. The strut is attached with single M10 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	61.00	in
$\Phi F_{ty\ AXIAL}$ =	13.67	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.000	k-ft
M_z =	0.401	k-ft
P_n =	4.486	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	13.425	k
Utilization =	62%	



4.4 Post Design

Galvanized steel posts are a roll formed steel section, that are either ram driven into the ground or placed in a concrete foundation at a defined depth. Embedment depths will be provided on the structural drawings or through a geotechnical testing report. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Post Type =	**FG8**	
Steel Type =	J2340	
F_{ty} =	60	ksi
L_b =	72.60	in
Φ =	0.90	
ΦF_{ty} =	54.00	ksi
S_y =	3.46	in^3
S_x =	1.55	in^3
E =	29000	ksi
I_y =	10.94	in^4
I_x =	4.31	in^4
A =	2.23	in^2
g =	7.59	lbs/ft
M_y =	11.927	k-ft
M_z =	0.000	k-ft
P_r =	6.662	k
$M_{y\ allowable}$ =	19.207	k-ft
$M_{z\ allowable}$ =	14.389	k-ft
P_c =	38.073	k
Utilization =	79%	



5. FOUNDATION DESIGN CALCULATIONS

5.1 Rammed Post Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete footing design.

Maximum Tensile Load =	5.50	k
Maximum Lateral Load =	2.72	k

5.2 Design of Drilled Shaft Foundations

The galvanized steel post is to be embedded into a cylindrical drilled shaft foundation. For the purpose of design, the post is considered to be fixed to the ground. The applicable lateral force, uplift, and compression resistance checks are seen below.

5.3 Lateral Force Resistance

The equivalent lateral force is applied at the top of the post to determine the required embedment depth. A lateral soil bearing capacity for clay is assumed. Footing is unrestrained at ground level. (IBC, Eq. 18-1)

Lateral Force @ Top of Pole, P =	1.30	k
Height of Pole Above Grade, H =	5.05	ft
Diameter of Pole Footing, B =	2.00	ft
Lateral Soil Bearing Capacity, S =	0.10	ksf/ft
Isolated Pole Factor, F =	2	
First Trial Depth, D =	3.25	ft
Lateral Bearing @ Bottom =	S_3	
Lateral Bearing @ D/3 =	S_1	
Required Depth =	D	

$$S_3 = Min\ (D, 12')$$

$$S_1 = Min\left(\frac{D}{3}, 12'\right)$$

$$A = 2.34\ P/S_1 B$$

$$D = \left\{0.5A\left(1+\sqrt{1+\left(\frac{4.36\ H}{A}\right)}\right)\right\}$$



Non-Constrained

Lateral Force @ Top of Pole, P =	1.30	k
Height of Pole Above Grade, H =	5.05	ft
Diameter of Pole Footing, B =	2.00	ft
Lateral Soil Bearing Capacity, S =	0.20	ksf/ft

1st Trial @ D_1 =	3.25	ft
Lateral Soil Bearing @ D/3, S_1 =	0.22	ksf
Lateral Soil Bearing @ D, S_3 =	0.65	ksf
Constant 2.34P/(S_1B), A =	7.01	
Required Footing Depth, D =	10.64	ft

2nd Trial @ D_2 =	6.94	ft
Lateral Soil Bearing @ D/3, S_1 =	0.46	ksf
Lateral Soil Bearing @ D, S_3 =	1.39	ksf
Constant 2.34P/(S_1B), A =	3.28	
Required Footing Depth, D =	6.20	ft

3rd Trial @ D_3 =	6.57	ft
Lateral Soil Bearing @ D/3, S_1 =	0.44	ksf
Lateral Soil Bearing @ D, S_3 =	1.31	ksf
Constant 2.34P/(S_1B), A =	3.47	
Required Footing Depth, D =	6.43	ft

4th Trial @ D_4 =	6.50	ft
Lateral Soil Bearing @ D/3, S_1 =	0.43	ksf
Lateral Soil Bearing @ D, S_3 =	1.30	ksf
Constant 2.34P/(S_1B), A =	3.50	
Required Footing Depth, D =	6.48	ft

5th Trial @ D_5 =	6.49	ft
Lateral Soil Bearing @ D/3, S_1 =	0.43	ksf
Lateral Soil Bearing @ D, S_3 =	1.30	ksf
Constant 2.34P/(S_1B), A =	3.51	
Required Footing Depth, D =	6.50	ft

A 2ft diameter x 6.5ft deep footing unrestrained at ground level is required for the racking structure.

5.4 Uplifting Force Resistance

Uplifting forces of the racking system are checked against the uplift resistance of the soil. Clay soils are assumed.

Weight of Concrete, g_{con} =	145	pcf
Uplifting Force, N =	2.51	k
Footing Diameter, B =	2.00	ft
Factor of Safety =	2.50	
Cohesion =	208.85	psf
γ_s =	120.43	pcf
α =	0.45	
Required Concrete Weight, g =	1.62	k
Required Concrete Volume, V =	11.14	ft^3
Required Footing Depth, D =	3.75	ft

Iteration	z	dz	Qs	Side
1	0.2	0.2	118.10	5.41
2	0.4	0.2	118.10	5.31
3	0.6	0.2	118.10	5.21
4	0.8	0.2	118.10	5.10
5	1	0.2	118.10	5.00
6	1.2	0.2	118.10	4.89
7	1.4	0.2	118.10	4.79
8	1.6	0.2	118.10	4.69
9	1.8	0.2	118.10	4.58
10	2	0.2	118.10	4.48
11	2.2	0.2	118.10	4.38
12	2.4	0.2	118.10	4.27
13	2.6	0.2	118.10	4.17
14	2.8	0.2	118.10	4.06
15	3	0.2	118.10	3.96
16	3.2	0.2	118.10	3.86
17	3.4	0.2	118.10	3.75
18	3.6	0.2	118.10	3.65
19	3.8	0.2	118.10	3.55
20	0	0.0	0.00	3.55
21	0	0.0	0.00	3.55
22	0	0.0	0.00	3.55
23	0	0.0	0.00	3.55
24	0	0.0	0.00	3.55
25	0	0.0	0.00	3.55
26	0	0.0	0.00	3.55
27	0	0.0	0.00	3.55
28	0	0.0	0.00	3.55
29	0	0.0	0.00	3.55
30	0	0.0	0.00	3.55
31	0	0.0	0.00	3.55
32	0	0.0	0.00	3.55
33	0	0.0	0.00	3.55
34	0	0.0	0.00	3.55
Max	3.8	Sum	0.90	

A 2ft diameter x 3.75ft deep footing unrestrained at ground level is required for the racking structure.



5.5 Compressive Force Resistance

Skin friction of the soil is checked against the compression force from the racking and the weight of the drilled shaft foundation. Skin friction starts at 3ft below grade. Clay soils are again assumed.

Depth Below Grade, D =	6.50	ft
Footing Diameter, B =	2.00	ft
Compressive Force, P =	4.26	k
Footing Area =	3.14	ft^2
Circumference =	6.28	ft
Skin Friction Area =	21.99	ft^2
Concrete Weight =	0.145	kcf

Bearing Pressure

Bearing Area =	3.14	ft^2
Bearing Capacity =	1.5	ksf
Resistance =	4.71	k

Weight of Concrete

Footing Volume	20.42	ft^3
Weight	2.96	k

Skin Friction Resistance

Skin Friction =	0.15	ksf
Resistance =	3.30	k
1/3 Increase for Wind =	1.33	
Total Resistance =	10.68	k
Applied Force =	7.22	k
Utilization =	68%	

A 2ft diameter footing passes at a depth of 6.5ft.



6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of 40mm mounting clamps. The reliability of calculations is uncertain due to limited standards, therefore the strength of the clamp fasteners has been evaluated by load testing.

Fastening of Modules to Purlins

Maximum Uplifting Force	=	0.424 k
Allowable Uplift	=	1.214 k
Utilization	=	35%



Fastening of Purlins to Girders

Maximum Uplifting Force	=	1.717 k
Allowable Uplift	=	2.180 k
Utilization	=	79%



6.2 Strut Connections

The aluminum struts connect the front end of girder to a center section of the steel post. Single M10 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Maximum Axial Load	=	4.486 k
M10 Bolt Shear Capacity	=	8.894 k
Utilization	=	50%

Bolt capacity is accounting for double shear. (ASCE 8-02, Eq. 5.3.4-1)



A strut under compression is shown to demonstrate the load transfer from the girder. Single M10 bolts are located at each end of the strut and are subjected to double shear.

6.3 Girder to Post Connection

In order to connect the girder to the post, custom extruded sections are assembled to create a post head piece. The reliability of calculations is uncertain due to limited standards, therefore the strength of the head piece has been evaluated by load testing.

Maximum Tensile Load	=	3.678 k
Allowable Load	=	5.649 k
Utilization	=	65%



FRONT VIEW



SIDE VIEW



7. SEISMIC DESIGN

7.1 Seismic Drift

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx}	=	58.15 in
Allowable Story Drift for All Other Structures, Δ	= {	$0.020h_{sx}$
		1.163 in
Max Drift, Δ_{MAX}	=	0.641 in

0.641 ≤ 1.163, OK.

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **S1.5**

Strong Axis:		Weak Axis:	
3.4.14		**3.4.14**	
L_b =	138 in	L_b =	138
J =	0.432	J =	0.432
	381.773		242.785
$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$		$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$	
S1 =	0.51461	S1 =	0.51461
$S2 = \left(\frac{C_c}{1.6}\right)^2$		$S2 = \left(\frac{C_c}{1.6}\right)^2$	
S2 =	1701.56	S2 =	1701.56
φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]	φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L=	27.0 ksi	φF_L=	28.3
3.4.16		**3.4.16**	
b/t =	32.195	b/t =	37.0588
$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$		$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$	
S1 =	12.2	S1 =	12.2
$S2 = \frac{k_1 Bp}{1.6Dp}$		$S2 = \frac{k_1 Bp}{1.6Dp}$	
S2 =	46.7	S2 =	46.7
φF_L=	φb[Bp-1.6Dp*b/t]	φF_L=	φb[Bp-1.6Dp*b/t]
φF_L=	25.1 ksi	φF_L=	23.1 ksi
3.4.16.1	Not Used	**3.4.16.1**	
Rb/t =		N/A for Weak Direction	
$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$			
S1 =	1.1		
$S2 = C_t$			
S2 =	141.0		
φF_L=	1.17φyFcy		
φF_L=	38.9 ksi		
3.4.18		**3.4.18**	
h/t =	37.0588	h/t =	32.195
$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$		$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$	
S1 =	36.9	S1 =	36.9
m =	0.65	m =	0.65
C_0 =	40.985	C_0 =	45.5
Cc =	41.015	Cc =	45.5
$S2 = \frac{k_1 Bbr}{mDbr}$		$S2 = \frac{k_1 Bbr}{mDbr}$	
S2 =	77.2	S2 =	77.3
φF_L=	φb[Bbr-mDbr*h/t]	φF_L=	1.3φyFcy
φF_L=	43.2 ksi	φF_L=	43.2 ksi
φF_LSt=	25.1 ksi	φF_LWk=	23.1 ksi
Ix =	897074 mm^4	Iy =	446476 mm^4
	2.155 in^4		1.073 in^4
y =	41.015 mm	x =	45.5 mm
Sx =	1.335 in^3	Sy =	0.599 in^3
M_{max}St =	2.788 k-ft	M_{max}Wk =	1.152 k-ft

Compression

3.4.9

b/t = 32.195
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 25.1 ksi

b/t = 37.0588
S1 = 12.21
S2 = 32.70
φF_L = (φck2*√(BpE))/(1.6b/t)
φF_L = 21.9 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 21.94 ksi
A = 1215.13 mm^2
1.88 in^2
P_{max} = 41.32 kips

A.2 Design of Aluminum Girders - Aluminum Design Manual, 2005 Edition

Girder = **T5**

Strong Axis:

3.4.14

L_b = 63.8189 in
J = 1.98
82.1278

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.5 ksi

3.4.16

b/t = 4.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φyFcy
φF_L = 33.3 ksi

Weak Axis:

3.4.14

L_b = 63.8189
J = 1.98
89.1294

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.3

3.4.16

b/t = 16.3333

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 31.6 ksi

3.4.16.1 Used

Rb/t = 20.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= φb[Bt-Dt*√(Rb/t)]

φF_L= 30.8 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 16.3333

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 37.9

m = 0.63

C_0 = 61.046

Cc = 58.954

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 79.4

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

3.4.18

h/t = 4.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 35

Cc = 35

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 30.5 ksi

Ix = 1970917 mm^4

4.735 in^4

y = 61.046 mm

Sx = 1.970 in^3

$M_{max}St$ = 5.001 k-ft

$\varphi F_L Wk$= 31.6 ksi

Iy = 763048 mm^4

1.833 in^4

x = 35 mm

Sy = 1.330 in^3

$M_{max}Wk$ = 3.499 k-ft

Compression

3.4.9

b/t = 4.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φyFcy

φF_L= 33.3 ksi

b/t = 16.3333

S1 = 12.21

S2 = 32.70

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 31.6 ksi

3.4.10

Rb/t = 20.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L= φc[Bt-Dt*√(Rb/t)]

φF_L= 30.80 ksi

φF_L= 30.80 ksi

A = 1215.13 mm^2

1.88 in^2

P_{max} = 58.01 kips

A.3 Design of Aluminum Struts - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 61 in

J = 0.942

95.1963

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 30.2 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

Weak Axis:

3.4.14

L_b = 61

J = 0.942

95.1963

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 30.2

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 1.41113

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.77756

φF_L = (φccFcy)/(λ²)

φF_L = 13.6667 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 13.67 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 14.07 kips

A.4 Design of Galvanized Steel Posts

Post Type = **FG8**

Unbraced Length =	72.60	in	
Pr =	6.66	k	(LRFD Factored Load)
Mr (Strong) =	11.93	k-ft	(LRFD Factored Load)
Mr (Weak) =	0.00	k-ft	(LRFD Factored Load)

Flexural Buckling:

kL/r =	104.47			
4.71√(E/Fy) =	103.55	=>	kL/r	> 4.71√(E/Fy)
Fcr =	23.00	ksi		
Fe =	26.23	ksi		
Pn =	51.291	k		

Torsional/Flexural Torsional Buckling:

Fcr =	17.0733	ksi
Fey =	66.8981	ksi
Fez =	21.7595	ksi
Pn =	38.0734	k

Bending (Strong Axis):

Yielding:

Mn =	21.95	k-ft

Flange Local Buckling:

Mn =	19.207	k-ft

Pr/Pc =	0.1944	<	0.2	
Utilization =	0.79	<	1.0	OK

Bending (Weak Axis):

Yielding:

Mn =	14.65	k-ft

Flange Local Buckling:

Mn =	14.39	k-ft

Pr/Pc =	0.194	<	0.2	
Utilization =	0.00	<	1.0	OK

Combined Forces

Utilization = 79%

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				4		
2	Dead Load, Min	DL		-1				4		
3	Snow Load	SL						4		
4	Wind Load - Pressure	WL						4		
5	Wind Load - Suction	WL						4		
6	Seismic - Lateral	EL			.8			8		

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-8.366	-8.366	0	0
2	M11	Y	-8.366	-8.366	0	0
3	M12	Y	-8.366	-8.366	0	0
4	M13	Y	-8.366	-8.366	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-4.45	-4.45	0	0
2	M11	Y	-4.45	-4.45	0	0
3	M12	Y	-4.45	-4.45	0	0
4	M13	Y	-4.45	-4.45	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-46.9	-46.9	0	0
2	M11	Y	-46.9	-46.9	0	0
3	M12	Y	-46.9	-46.9	0	0
4	M13	Y	-46.9	-46.9	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	y	-63.697	-63.697	0	0
2	M11	y	-63.697	-63.697	0	0
3	M12	y	-98.441	-98.441	0	0
4	M13	y	-98.441	-98.441	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	y	127.394	127.394	0	0
2	M11	y	127.394	127.394	0	0
3	M12	y	57.906	57.906	0	0
4	M13	y	57.906	57.906	0	0

Member Distributed Loads (BLC 6 : Seismic - Lateral)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Z	6.693	6.693	0	0
2	M11	Z	6.693	6.693	0	0
3	M12	Z	6.693	6.693	0	0
4	M13	Z	6.693	6.693	0	0
5	M10	Z	0	0	0	0
6	M11	Z	0	0	0	0
7	M12	Z	0	0	0	0
8	M13	Z	0	0	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.5W	Yes	Y		1	1.2	3	1.6	4	.5														
2	LRFD 1.2D + 1.0W + 0.5S	Yes	Y		1	1.2	3	.5	4	1														
3	LRFD 0.9D + 1.0W	Yes	Y		2	.9					5	1												
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3												
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3												
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25												
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25												
8																								
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																
10	ASD 1.0D + 0.6W	Yes	Y		1	1			4	.6														
11	ASD 1.0D + 0.75L + 0.45W + 0....	Yes	Y		1	1	3	.75	4	.45														
12	ASD 0.6D + 0.6W	Yes	Y		2	.6					5	.6												
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875												
14	LATERAL - ASD 1.1785D + 0.65...	Yes	Y		1	1.1...	3	.75			6	.656												
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875												

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N9	max	544.044	2	2472.806	1	330.736	1	.418	1	.012	5	5.391	1
2		min	-754.32	3	-1407.924	3	-366.532	5	-1.501	5	-.012	1	.52	15
3	N19	max	2063.945	2	6682.345	1	0	2	0	2	.013	4	11.213	1
4		min	-2093.674	3	-4225.212	3	-403.406	5	-1.582	4	0	1	.394	15
5	N29	max	544.044	2	2472.806	1	287.062	3	.359	3	.015	4	5.391	1
6		min	-754.32	3	-1407.924	3	-446.553	4	-1.622	4	-.005	3	-.133	5
7	Totals:	max	3152.034	2	11627.956	1	0	2						
8		min	-3602.314	3	-7041.059	3	-1165.254	4						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M1	1	max	0	1	.006	1	.002	4	0	1	0	1	0	1
2			min	0	1	0	3	-.001	1	0	1	0	1	0	1
3		2	max	-.221	15	-.473	15	0	12	0	1	0	12	0	6
4			min	-.939	4	-2.011	6	-1.499	5	0	1	0	5	0	15
5		3	max	-10.518	12	236.744	3	-.445	3	.064	3	.332	1	.267	2
6			min	-218.53	1	-613.604	2	-207.84	1	-.256	1	.022	12	-.101	3
7		4	max	-10.883	12	235.568	3	-.445	3	.064	3	.203	1	.648	2
8			min	-219.261	1	-615.172	2	-207.84	1	-.256	1	.021	10	-.248	3
9		5	max	-11.249	12	234.392	3	-.445	3	.064	3	.08	4	1.03	2
10			min	-219.992	1	-616.74	2	-207.84	1	-.256	1	-.007	10	-.393	3
11		6	max	310.978	3	544.228	2	30.015	3	.073	1	.144	1	.987	2
12			min	-1227.129	1	-143.793	3	-281.513	1	-.074	3	-.047	3	-.4	3
13		7	max	310.429	3	542.659	2	30.015	3	.073	1	.014	10	.652	1
14			min	-1227.86	1	-144.969	3	-281.513	1	-.074	3	-.072	4	-.311	3
15		8	max	309.881	3	541.091	2	30.015	3	.073	1	-.007	12	.328	1
16			min	-1228.591	1	-146.145	3	-281.513	1	-.074	3	-.205	1	-.22	3
17		9	max	294.271	3	74.048	3	23.888	3	.018	5	.106	1	.143	1
18			min	-1454.963	1	-67.433	1	-284.25	1	-.216	2	0	10	-.179	3
19		10	max	293.723	3	72.872	3	23.888	3	.018	5	.058	3	.185	1
20			min	-1455.694	1	-69.001	1	-284.25	1	-.216	2	-.071	1	-.224	3
21		11	max	293.174	3	71.696	3	23.888	3	.018	5	.072	3	.229	1
22			min	-1456.426	1	-70.569	1	-284.25	1	-.216	2	-.247	1	-.269	3
23		12	max	274.826	3	666.176	3	157.152	2	.412	3	.189	1	.483	1
24			min	-1678.654	1	-587.393	1	-292.466	3	-.468	1	-.032	5	-.548	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
25		13	max	274.278	3	664.999	3	157.152	2	.412	3	.249	1	.848	1
26			min	-1679.385	1	-588.962	1	-292.466	3	-.468	1	-.172	5	-.961	3
27		14	max	220.759	1	528.231	1	82.342	5	.33	1	.053	3	1.199	1
28			min	11.136	12	-589.713	3	-158.851	1	-.439	3	-.241	4	-1.356	3
29		15	max	220.027	1	526.663	1	80.843	5	.33	1	.031	3	.872	1
30			min	10.77	12	-590.889	3	-158.851	1	-.439	3	-.212	4	-.99	3
31		16	max	219.296	1	525.095	1	79.343	5	.33	1	.009	3	.545	1
32			min	10.404	12	-592.065	3	-158.851	1	-.439	3	-.261	1	-.623	3
33		17	max	218.565	1	523.526	1	77.843	5	.33	1	-.009	12	.22	1
34			min	10.039	12	-593.242	3	-158.851	1	-.439	3	-.359	1	-.255	3
35		18	max	.939	4	2.013	6	1.5	4	0	1	0	12	0	6
36			min	.221	15	.473	15	0	12	0	1	0	4	0	15
37		19	max	0	1	.002	2	.001	1	0	1	0	1	0	1
38			min	0	1	-.004	3	0	5	0	1	0	1	0	1
39	M4	1	max	0	1	.016	1	.002	4	0	1	0	1	0	1
40			min	0	1	-.003	3	0	1	0	1	0	1	0	1
41		2	max	-.221	15	-.473	15	0	1	0	1	0	1	0	6
42			min	-.939	4	-2.009	6	-1.499	5	0	1	0	5	0	15
43		3	max	-15.884	12	739.348	3	0	1	.033	4	.248	4	.683	2
44			min	-411.862	1	-1775.852	2	-119.546	5	0	1	0	1	-.287	3
45		4	max	-16.25	12	738.172	3	0	1	.033	4	.173	4	1.786	2
46			min	-412.593	1	-1777.421	2	-121.046	5	0	1	0	1	-.746	3
47		5	max	-16.615	12	736.995	3	0	1	.033	4	.098	4	2.89	2
48			min	-413.324	1	-1778.989	2	-122.545	5	0	1	0	1	-1.204	3
49		6	max	1101.862	3	1606.958	2	0	1	0	1	0	1	2.751	2
50			min	-3329.002	1	-543.932	3	-112.726	4	-.028	4	-.02	5	-1.191	3
51		7	max	1101.313	3	1605.39	2	0	1	0	1	0	1	1.755	2
52			min	-3329.733	1	-545.109	3	-114.225	4	-.028	4	-.09	4	-.853	3
53		8	max	1100.765	3	1603.822	2	0	1	0	1	0	1	.769	1
54			min	-3330.464	1	-546.285	3	-115.725	4	-.028	4	-.161	4	-.514	3
55		9	max	1078.251	3	225.97	3	0	1	.017	4	.115	4	.2	1
56			min	-3724.448	1	-241.654	1	-239.295	4	0	1	0	1	-.349	3
57		10	max	1077.703	3	224.794	3	0	1	.017	4	0	1	.35	1
58			min	-3725.179	1	-243.222	1	-240.794	4	0	1	-.034	4	-.488	3
59		11	max	1077.154	3	223.618	3	0	1	.017	4	0	1	.502	1
60			min	-3725.91	1	-244.791	1	-242.294	4	0	1	-.184	4	-.628	3
61		12	max	1060.116	3	1842.84	3	0	1	.155	4	0	1	1.249	1
62			min	-4128.181	1	-1776.826	1	-267.171	5	0	1	-.001	4	-1.411	3
63		13	max	1059.568	3	1841.663	3	0	1	.155	4	0	1	2.352	1
64			min	-4128.912	1	-1778.394	1	-268.671	5	0	1	-.168	4	-2.555	3
65		14	max	413.986	1	1513.966	1	73.725	5	0	1	0	1	3.411	1
66			min	17.939	12	-1622.147	3	0	1	-.111	4	-.208	5	-3.65	3
67		15	max	413.254	1	1512.398	1	72.225	5	0	1	0	1	2.472	1
68			min	17.573	12	-1623.323	3	0	1	-.111	4	-.163	5	-2.643	3
69		16	max	412.523	1	1510.83	1	70.725	5	0	1	0	1	1.534	1
70			min	17.207	12	-1624.499	3	0	1	-.111	4	-.118	5	-1.635	3
71		17	max	411.792	1	1509.261	1	69.226	5	0	1	0	1	.597	1
72			min	16.842	12	-1625.675	3	0	1	-.111	4	-.075	4	-.626	3
73		18	max	.939	4	2.014	6	1.5	5	0	1	0	1	0	6
74			min	.221	15	.473	15	0	1	0	1	0	5	0	15
75		19	max	0	1	.005	1	0	1	0	1	0	1	0	1
76			min	0	1	-.01	3	0	4	0	1	0	1	0	1
77	M7	1	max	0	1	.006	1	.003	4	0	1	0	1	0	1
78			min	0	1	0	3	0	12	0	1	0	1	0	1
79		2	max	-.221	15	-.473	15	.001	1	0	1	0	1	0	4
80			min	-.939	4	-2.011	4	-1.499	5	0	1	0	5	0	15
81		3	max	12.53	5	236.744	3	207.84	1	.256	1	.114	5	.267	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
82			min	-218.53	1	-613.604	2	-50.687	5	-.064	3	-.332	1	-.101	3
83		4	max	12.189	5	235.568	3	207.84	1	.256	1	.082	5	.648	2
84			min	-219.261	1	-615.172	2	-52.187	5	-.064	3	-.203	1	-.248	3
85		5	max	11.848	5	234.392	3	207.84	1	.256	1	.049	5	1.03	2
86			min	-219.992	1	-616.74	2	-53.686	5	-.064	3	-.074	1	-.393	3
87		6	max	310.978	3	544.228	2	281.513	1	.074	3	.047	3	.987	2
88			min	-1227.129	1	-143.793	3	-40.532	5	-.073	1	-.144	1	-.4	3
89		7	max	310.429	3	542.659	2	281.513	1	.074	3	.03	1	.652	1
90			min	-1227.86	1	-144.969	3	-42.031	5	-.073	1	-.056	5	-.311	3
91		8	max	309.881	3	541.091	2	281.513	1	.074	3	.205	1	.328	1
92			min	-1228.591	1	-146.145	3	-43.531	5	-.073	1	-.082	5	-.22	3
93		9	max	294.271	3	74.048	3	284.25	1	.216	2	.039	5	.143	1
94			min	-1454.963	1	-67.433	1	-99.895	5	.02	15	-.106	1	-.179	3
95		10	max	293.723	3	72.872	3	284.25	1	.216	2	.071	1	.185	1
96			min	-1455.694	1	-69.001	1	-101.395	5	.02	15	-.058	3	-.224	3
97		11	max	293.174	3	71.696	3	284.25	1	.216	2	.247	1	.229	1
98			min	-1456.426	1	-70.569	1	-102.895	5	.02	15	-.087	5	-.269	3
99		12	max	274.826	3	666.176	3	292.466	3	.468	1	-.011	12	.483	1
100			min	-1678.654	1	-587.393	1	-235.333	4	-.412	3	-.189	1	-.548	3
101		13	max	274.278	3	664.999	3	292.466	3	.468	1	.164	3	.848	1
102			min	-1679.385	1	-588.962	1	-236.832	4	-.412	3	-.249	1	-.961	3
103		14	max	220.759	1	528.231	1	158.851	1	.439	3	.064	1	1.199	1
104			min	7.164	15	-589.713	3	20	10	-.33	1	-.225	5	-1.356	3
105		15	max	220.027	1	526.663	1	158.851	1	.439	3	.162	1	.872	1
106			min	6.943	15	-590.889	3	20	10	-.33	1	-.161	5	-.99	3
107		16	max	219.296	1	525.095	1	158.851	1	.439	3	.261	1	.545	1
108			min	6.723	15	-592.065	3	20	10	-.33	1	-.099	5	-.623	3
109		17	max	218.565	1	523.526	1	158.851	1	.439	3	.359	1	.22	1
110			min	6.502	15	-593.242	3	20	10	-.33	1	-.038	5	-.255	3
111		18	max	.939	4	2.013	4	1.499	5	0	1	0	1	0	4
112			min	.221	15	.473	15	-.001	1	0	1	0	5	0	15
113		19	max	0	1	.002	2	0	12	0	1	0	1	0	1
114			min	0	1	-.004	3	-.001	1	0	1	0	1	0	1
115	M10	1	max	158.837	1	520.086	1	-6.065	15	.007	1	.424	1	.33	1
116			min	19.996	10	-595.555	3	-217.459	1	-.016	3	0	15	-.439	3
117		2	max	158.837	1	378.774	1	-4.135	15	.007	1	.176	1	.222	3
118			min	19.996	10	-438.979	3	-170.54	1	-.016	3	-.008	5	-.244	1
119		3	max	158.837	1	237.461	1	-2.206	15	.007	1	.013	2	.683	3
120			min	19.996	10	-282.404	3	-123.622	1	-.016	3	-.02	4	-.637	1
121		4	max	158.837	1	96.149	1	-.276	15	.007	1	-.006	12	.944	3
122			min	19.996	10	-125.828	3	-76.703	1	-.016	3	-.14	1	-.851	1
123		5	max	158.837	1	30.747	3	2.394	5	.007	1	-.01	12	1.004	3
124			min	19.996	10	-45.164	1	-29.785	1	-.016	3	-.208	1	-.883	1
125		6	max	158.837	1	187.323	3	17.134	1	.007	1	-.007	15	.865	3
126			min	19.46	15	-186.476	1	-1.894	10	-.016	3	-.216	1	-.735	1
127		7	max	158.837	1	343.898	3	64.052	1	.007	1	-.001	15	.526	3
128			min	10.632	15	-327.788	1	2.262	12	-.016	3	-.164	1	-.407	1
129		8	max	158.837	1	500.474	3	110.971	1	.007	1	.01	5	.102	1
130			min	1.803	15	-469.101	1	4.191	12	-.016	3	-.052	1	-.019	5
131		9	max	158.837	1	657.049	3	157.889	1	.007	1	.119	1	.792	1
132			min	-9.977	5	-610.413	1	6.121	12	-.016	3	-.004	10	-.753	3
133		10	max	158.837	1	751.725	1	-5.86	15	.007	1	.351	1	1.662	1
134			min	19.996	10	-813.625	3	-204.808	1	-.016	3	.011	12	-1.693	3
135		11	max	158.837	1	610.413	1	-3.931	15	.016	3	.119	1	.792	1
136			min	19.965	15	-657.049	3	-157.889	1	-.007	1	-.009	5	-.753	3
137		12	max	158.837	1	469.101	1	-2.001	15	.016	3	-.005	12	.102	1
138			min	11.136	15	-500.474	3	-110.971	1	-.007	1	-.052	1	-.014	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
139		13	max	158.837	1	327.788	1	-.072	15	.016	3	-.009	12	.526	3
140			min	2.308	15	-343.898	3	-64.052	1	-.007	1	-.164	1	-.407	1
141		14	max	158.837	1	186.476	1	2.714	5	.016	3	-.01	12	.865	3
142			min	-9.289	5	-187.323	3	-17.134	1	-.007	1	-.216	1	-.735	1
143		15	max	158.837	1	45.164	1	29.785	1	.016	3	-.007	15	1.004	3
144			min	-22.406	5	-30.747	3	1.596	12	-.007	1	-.208	1	-.883	1
145		16	max	158.837	1	125.828	3	76.703	1	.016	3	0	15	.944	3
146			min	-35.523	5	-96.149	1	3.525	12	-.007	1	-.14	1	-.851	1
147		17	max	158.837	1	282.404	3	123.622	1	.016	3	.013	2	.683	3
148			min	-48.639	5	-237.461	1	5.454	12	-.007	1	-.016	9	-.637	1
149		18	max	158.837	1	438.979	3	170.54	1	.016	3	.176	1	.222	3
150			min	-61.756	5	-378.774	1	7.384	12	-.007	1	.008	12	-.244	1
151		19	max	158.837	1	595.555	3	217.459	1	.016	3	.424	1	.33	1
152			min	-74.873	5	-520.086	1	9.313	12	-.007	1	.018	12	-.439	3
153	M11	1	max	381.087	1	513.245	1	16.116	5	0	15	.461	1	.289	1
154			min	-316.273	3	-596.317	3	-222.359	1	-.006	1	-.147	5	-.528	3
155		2	max	381.087	1	371.932	1	19.101	5	0	15	.207	1	.133	3
156			min	-316.273	3	-439.741	3	-175.44	1	-.006	1	-.124	5	-.276	1
157		3	max	381.087	1	230.62	1	22.086	5	0	15	.019	2	.595	3
158			min	-316.273	3	-283.166	3	-128.522	1	-.006	1	-.098	5	-.661	1
159		4	max	381.087	1	89.308	1	25.071	5	0	15	.004	3	.857	3
160			min	-316.273	3	-126.59	3	-81.603	1	-.006	1	-.121	1	-.865	1
161		5	max	381.087	1	29.985	3	28.055	5	0	15	-.004	12	.919	3
162			min	-316.273	3	-52.005	1	-34.685	1	-.006	1	-.196	1	-.889	1
163		6	max	381.087	1	186.561	3	34.566	4	0	15	.004	5	.78	3
164			min	-316.273	3	-193.317	1	-3.208	3	-.006	1	-.21	1	-.732	1
165		7	max	381.087	1	343.136	3	59.152	1	0	15	.046	5	.442	3
166			min	-316.273	3	-334.63	1	-.314	3	-.006	1	-.164	1	-.395	1
167		8	max	381.087	1	499.712	3	106.071	1	0	15	.091	5	.123	1
168			min	-316.273	3	-475.942	1	1.981	12	-.006	1	-.059	1	-.096	3
169		9	max	381.087	1	656.287	3	152.989	1	0	15	.168	4	.821	1
170			min	-316.273	3	-617.254	1	3.91	12	-.006	1	-.007	3	-.835	3
171		10	max	381.087	1	758.567	1	17.108	5	.006	1	.332	1	1.7	1
172			min	-316.273	3	-812.863	3	-199.908	1	-.003	14	.002	3	-1.774	3
173		11	max	381.087	1	617.254	1	20.093	5	.006	1	.107	1	.821	1
174			min	-316.273	3	-656.287	3	-152.989	1	0	5	-.124	5	-.835	3
175		12	max	381.087	1	475.942	1	23.077	5	.006	1	-.007	12	.123	1
176			min	-316.273	3	-499.712	3	-106.071	1	0	5	-.108	4	-.096	3
177		13	max	381.087	1	334.63	1	26.062	5	.006	1	-.009	12	.442	3
178			min	-316.273	3	-343.136	3	-59.152	1	0	5	-.164	1	-.395	1
179		14	max	381.087	1	193.317	1	29.047	5	.006	1	-.008	12	.78	3
180			min	-316.273	3	-186.561	3	-12.234	1	0	5	-.21	1	-.732	1
181		15	max	381.087	1	52.005	1	39.019	4	.006	1	.009	5	.919	3
182			min	-316.273	3	-29.985	3	3.806	12	0	5	-.196	1	-.889	1
183		16	max	381.087	1	126.59	3	81.603	1	.006	1	.052	5	.857	3
184			min	-316.273	3	-89.308	1	5.736	12	0	5	-.121	1	-.865	1
185		17	max	381.087	1	283.166	3	128.522	1	.006	1	.099	4	.595	3
186			min	-316.273	3	-230.62	1	7.665	12	0	5	.002	9	-.661	1
187		18	max	381.087	1	439.741	3	175.44	1	.006	1	.207	1	.133	3
188			min	-316.273	3	-371.932	1	9.594	12	0	5	.022	12	-.276	1
189		19	max	381.087	1	596.317	3	222.359	1	.006	1	.461	1	.289	1
190			min	-316.273	3	-513.245	1	11.523	12	0	5	.035	12	-.528	3
191	M12	1	max	54.752	5	601.323	2	18.701	5	0	3	.486	1	.286	2
192			min	-19.54	9	-221.746	3	-225.637	1	-.007	1	-.161	5	.026	12
193		2	max	44.264	2	434.664	2	21.686	5	0	3	.228	1	.283	3
194			min	-19.54	9	-153.961	3	-178.719	1	-.007	1	-.135	5	-.393	1
195		3	max	44.264	2	268.006	2	24.671	5	0	3	.034	2	.437	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
196			min	-19.54	9	-86.176	3	-131.8	1	-.007	1	-.105	5	-.83	1
197		4	max	44.264	2	101.347	2	27.656	5	0	3	-.003	10	.504	3
198			min	-19.54	9	-18.39	3	-84.882	1	-.007	1	-.109	1	-1.061	2
199		5	max	44.264	2	49.395	3	30.64	5	0	3	-.008	12	.484	3
200			min	-19.54	9	-67.35	1	-37.963	1	-.007	1	-.188	1	-1.084	2
201		6	max	44.264	2	117.18	3	36.698	4	0	3	.007	5	.377	3
202			min	-20.524	14	-231.97	2	-3.371	10	-.007	1	-.206	1	-.894	2
203		7	max	44.264	2	184.965	3	55.874	1	0	3	.051	5	.184	3
204			min	-30.492	4	-398.628	2	1.614	12	-.007	1	-.165	1	-.491	2
205		8	max	44.264	2	252.751	3	102.792	1	0	3	.1	5	.125	2
206			min	-43.608	4	-565.287	2	3.543	12	-.007	1	-.063	1	-.095	3
207		9	max	44.264	2	320.536	3	149.711	1	0	3	.179	4	.954	2
208			min	-56.725	4	-731.945	2	5.472	12	-.007	1	-.008	10	-.462	3
209		10	max	44.264	2	898.604	2	124.973	14	.007	1	.319	1	1.995	2
210			min	-69.841	4	-388.321	3	-196.629	1	-.003	14	.009	12	-.915	3
211		11	max	45.808	5	731.945	2	22.968	5	.007	1	.098	1	.954	2
212			min	-19.54	9	-320.536	3	-149.711	1	0	5	-.138	5	-.462	3
213		12	max	44.264	2	565.287	2	25.953	5	.007	1	-.005	12	.125	2
214			min	-19.54	9	-252.751	3	-102.792	1	0	5	-.118	4	-.095	3
215		13	max	44.264	2	398.628	2	28.938	5	.007	1	-.009	12	.184	3
216			min	-19.54	9	-184.965	3	-55.874	1	0	5	-.165	1	-.491	2
217		14	max	44.264	2	231.97	2	31.923	5	.007	1	-.009	12	.377	3
218			min	-19.54	9	-117.18	3	-8.955	1	0	5	-.206	1	-.894	2
219		15	max	44.264	2	67.35	1	42.425	4	.007	1	.01	5	.484	3
220			min	-19.54	9	-49.395	3	2.245	12	0	5	-.188	1	-1.084	2
221		16	max	44.264	2	18.39	3	84.882	1	.007	1	.057	5	.504	3
222			min	-26.374	4	-101.347	2	4.174	12	0	5	-.109	1	-1.061	2
223		17	max	44.264	2	86.176	3	131.8	1	.007	1	.111	4	.437	3
224			min	-39.491	4	-268.006	2	6.103	12	0	5	.003	12	-.83	1
225		18	max	44.264	2	153.961	3	178.719	1	.007	1	.228	1	.283	3
226			min	-52.608	4	-434.664	2	8.032	12	0	5	.012	12	-.393	1
227		19	max	44.264	2	221.746	3	225.637	1	.007	1	.486	1	.286	2
228			min	-65.724	4	-601.323	2	9.961	12	0	5	.023	12	-.036	5
229	M13	1	max	47.621	5	610.946	2	13.216	5	.006	3	.416	1	.256	1
230			min	-207.649	1	-239.132	3	-216.59	1	-.019	1	-.135	5	-.064	3
231		2	max	34.504	5	444.288	2	16.201	5	.006	3	.17	1	.199	3
232			min	-207.649	1	-171.346	3	-169.671	1	-.019	1	-.116	5	-.42	2
233		3	max	21.387	5	277.63	2	19.185	5	.006	3	.008	2	.374	3
234			min	-207.649	1	-103.561	3	-122.753	1	-.019	1	-.1	4	-.881	2
235		4	max	8.271	5	111.993	1	22.17	5	.006	3	-.004	12	.463	3
236			min	-207.649	1	-35.776	3	-75.834	1	-.019	1	-.144	1	-1.13	2
237		5	max	-.446	3	32.009	3	25.155	5	.006	3	-.008	12	.466	3
238			min	-207.649	1	-55.687	2	-28.916	1	-.019	1	-.211	1	-1.165	2
239		6	max	-.446	3	99.795	3	32.944	4	.006	3	-.001	15	.382	3
240			min	-207.649	1	-222.346	2	-1.535	10	-.019	1	-.218	1	-.987	2
241		7	max	-.446	3	167.58	3	64.921	1	.006	3	.035	5	.211	3
242			min	-207.649	1	-389.004	2	1.789	12	-.019	1	-.165	1	-.602	1
243		8	max	-.446	3	235.365	3	111.84	1	.006	3	.077	5	.007	10
244			min	-207.649	1	-555.663	2	3.718	12	-.019	1	-.052	1	-.047	3
245		9	max	-.446	3	303.15	3	158.758	1	.006	3	.153	4	.823	2
246			min	-207.649	1	-722.321	2	5.647	12	-.019	1	-.003	10	-.391	3
247		10	max	-.446	3	888.98	2	136.705	9	.019	1	.354	1	1.853	2
248			min	-207.649	1	-370.936	3	-205.677	1	-.007	14	.009	12	-.821	3
249		11	max	33.145	5	722.321	2	16.432	5	.019	1	.121	1	.823	2
250			min	-207.649	1	-303.15	3	-158.758	1	-.006	3	-.105	5	-.391	3
251		12	max	20.029	5	555.663	2	19.417	5	.019	1	-.005	12	.007	10
252			min	-207.649	1	-235.365	3	-111.84	1	-.006	3	-.091	4	-.047	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
253		13	max	6.912	5	389.004	2	22.402	5	.019	1	-.009	12	.211	3
254			min	-207.649	1	-167.58	3	-64.921	1	-.006	3	-.165	1	-.602	1
255		14	max	-.446	3	222.346	2	25.386	5	.019	1	-.01	12	.382	3
256			min	-207.649	1	-99.795	3	-18.003	1	-.006	3	-.218	1	-.987	2
257		15	max	-.446	3	55.687	2	33.99	4	.019	1	.01	5	.466	3
258			min	-207.649	1	-32.009	3	2.069	12	-.006	3	-.211	1	-1.165	2
259		16	max	-.446	3	35.776	3	75.834	1	.019	1	.048	5	.463	3
260			min	-207.649	1	-111.993	1	3.998	12	-.006	3	-.144	1	-1.13	2
261		17	max	-.446	3	103.561	3	122.753	1	.019	1	.09	5	.374	3
262			min	-207.649	1	-277.63	2	5.928	12	-.006	3	-.018	9	-.881	2
263		18	max	-.446	3	171.346	3	169.671	1	.019	1	.17	4	.199	3
264			min	-207.649	1	-444.288	2	7.857	12	-.006	3	.011	12	-.42	2
265		19	max	-.446	3	239.132	3	216.59	1	.019	1	.416	1	.256	1
266			min	-207.649	1	-610.946	2	9.786	12	-.006	3	.022	12	-.064	3
267	M2	1	max	2472.806	1	753.918	3	331.103	1	.012	5	1.501	5	5.391	1
268			min	-1407.924	3	-542.883	2	-366.62	5	-.012	1	-.418	1	.52	15
269		2	max	2470.251	1	753.918	3	331.103	1	.012	5	1.399	5	5.43	1
270			min	-1409.84	3	-542.883	2	-364.405	5	-.012	1	-.325	1	.499	15
271		3	max	2467.696	1	753.918	3	331.103	1	.012	5	1.297	5	5.469	1
272			min	-1411.756	3	-542.883	2	-362.191	5	-.012	1	-.232	1	.478	15
273		4	max	1860.938	1	1257.374	1	255.806	1	.002	1	1.194	5	5.292	1
274			min	-1216.618	3	107.481	15	-344.999	5	-.001	3	-.197	1	.452	15
275		5	max	1858.383	1	1257.374	1	255.806	1	.002	1	1.098	5	4.939	1
276			min	-1218.534	3	107.481	15	-342.785	5	-.001	3	-.125	1	.422	15
277		6	max	1855.828	1	1257.374	1	255.806	1	.002	1	1.003	4	4.586	1
278			min	-1220.45	3	107.481	15	-340.571	5	-.001	3	-.053	1	.392	15
279		7	max	1853.274	1	1257.374	1	255.806	1	.002	1	.918	4	4.233	1
280			min	-1222.367	3	107.481	15	-338.357	5	-.001	3	-.073	3	.362	15
281		8	max	1850.719	1	1257.374	1	255.806	1	.002	1	.833	4	3.881	1
282			min	-1224.283	3	107.481	15	-336.142	5	-.001	3	-.145	3	.332	15
283		9	max	1848.164	1	1257.374	1	255.806	1	.002	1	.749	4	3.528	1
284			min	-1226.199	3	107.481	15	-333.928	5	-.001	3	-.217	3	.302	15
285		10	max	1845.609	1	1257.374	1	255.806	1	.002	1	.666	4	3.175	1
286			min	-1228.115	3	107.481	15	-331.714	5	-.001	3	-.289	3	.271	15
287		11	max	1843.054	1	1257.374	1	255.806	1	.002	1	.583	4	2.822	1
288			min	-1230.031	3	107.481	15	-329.5	5	-.001	3	-.361	3	.241	15
289		12	max	1840.499	1	1257.374	1	255.806	1	.002	1	.501	4	2.47	1
290			min	-1231.947	3	107.481	15	-327.286	5	-.001	3	-.433	3	.211	15
291		13	max	1837.944	1	1257.374	1	255.806	1	.002	1	.449	1	2.117	1
292			min	-1233.864	3	107.481	15	-325.071	5	-.001	3	-.506	3	.181	15
293		14	max	1835.389	1	1257.374	1	255.806	1	.002	1	.521	1	1.764	1
294			min	-1235.78	3	107.481	15	-322.857	5	-.001	3	-.578	3	.151	15
295		15	max	1832.834	1	1257.374	1	255.806	1	.002	1	.593	1	1.411	1
296			min	-1237.696	3	107.481	15	-320.643	5	-.001	3	-.65	3	.121	15
297		16	max	1830.28	1	1257.374	1	255.806	1	.002	1	.665	1	1.058	1
298			min	-1239.612	3	107.481	15	-318.429	5	-.001	3	-.722	3	.09	15
299		17	max	1827.725	1	1257.374	1	255.806	1	.002	1	.736	1	.706	1
300			min	-1241.528	3	107.481	15	-316.214	5	-.001	3	-.794	3	.06	15
301		18	max	1825.17	1	1257.374	1	255.806	1	.002	1	.808	1	.353	1
302			min	-1243.444	3	107.481	15	-314	5	-.001	3	-.866	3	.03	15
303		19	max	1822.615	1	1257.374	1	255.806	1	.002	1	.88	1	0	1
304			min	-1245.361	3	107.481	15	-311.786	5	-.001	3	-.938	3	0	1
305	M5	1	max	6682.345	1	2091.187	3	0	1	.013	4	1.582	4	11.213	1
306			min	-4225.212	3	-2056.763	2	-403.604	5	0	1	0	1	.394	15
307		2	max	6679.79	1	2091.187	3	0	1	.013	4	1.47	4	11.572	1
308			min	-4227.128	3	-2056.763	2	-401.39	5	0	1	0	1	.398	15
309		3	max	6677.235	1	2091.187	3	0	1	.013	4	1.358	4	11.932	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
310			min	-4229.044	3	-2056.763	2	-399.176	5	0	1	0	1	.402	15
311		4	max	4970.45	1	2771.492	1	0	1	0	1	1.25	4	11.664	1
312			min	-3551.893	3	92.442	15	-383.154	4	0	4	0	1	.389	15
313		5	max	4967.895	1	2771.492	1	0	1	0	1	1.143	4	10.887	1
314			min	-3553.809	3	92.442	15	-380.939	4	0	4	0	1	.363	15
315		6	max	4965.341	1	2771.492	1	0	1	0	1	1.036	4	10.109	1
316			min	-3555.726	3	92.442	15	-378.725	4	0	4	0	1	.337	15
317		7	max	4962.786	1	2771.492	1	0	1	0	1	.93	4	9.331	1
318			min	-3557.642	3	92.442	15	-376.511	4	0	4	0	1	.311	15
319		8	max	4960.231	1	2771.492	1	0	1	0	1	.825	4	8.554	1
320			min	-3559.558	3	92.442	15	-374.297	4	0	4	0	1	.285	15
321		9	max	4957.676	1	2771.492	1	0	1	0	1	.72	4	7.776	1
322			min	-3561.474	3	92.442	15	-372.082	4	0	4	0	1	.259	15
323		10	max	4955.121	1	2771.492	1	0	1	0	1	.616	4	6.999	1
324			min	-3563.39	3	92.442	15	-369.868	4	0	4	0	1	.233	15
325		11	max	4952.566	1	2771.492	1	0	1	0	1	.512	4	6.221	1
326			min	-3565.306	3	92.442	15	-367.654	4	0	4	0	1	.207	15
327		12	max	4950.011	1	2771.492	1	0	1	0	1	.41	4	5.443	1
328			min	-3567.223	3	92.442	15	-365.44	4	0	4	0	1	.182	15
329		13	max	4947.456	1	2771.492	1	0	1	0	1	.307	4	4.666	1
330			min	-3569.139	3	92.442	15	-363.226	4	0	4	0	1	.156	15
331		14	max	4944.901	1	2771.492	1	0	1	0	1	.206	4	3.888	1
332			min	-3571.055	3	92.442	15	-361.011	4	0	4	0	1	.13	15
333		15	max	4942.347	1	2771.492	1	0	1	0	1	.105	4	3.11	1
334			min	-3572.971	3	92.442	15	-358.797	4	0	4	0	1	.104	15
335		16	max	4939.792	1	2771.492	1	0	1	0	1	.004	4	2.333	1
336			min	-3574.887	3	92.442	15	-356.583	4	0	4	0	1	.078	15
337		17	max	4937.237	1	2771.492	1	0	1	0	1	0	1	1.555	1
338			min	-3576.803	3	92.442	15	-354.369	4	0	4	-.095	4	.052	15
339		18	max	4934.682	1	2771.492	1	0	1	0	1	0	1	.778	1
340			min	-3578.72	3	92.442	15	-352.154	4	0	4	-.194	4	.026	15
341		19	max	4932.127	1	2771.492	1	0	1	0	1	0	1	0	1
342			min	-3580.636	3	92.442	15	-349.94	4	0	4	-.293	4	0	1
343	M8	1	max	2472.806	1	753.918	3	286.882	3	.015	4	1.622	4	5.391	1
344			min	-1407.924	3	-542.883	2	-446.912	4	-.005	3	-.359	3	-.133	5
345		2	max	2470.251	1	753.918	3	286.882	3	.015	4	1.497	4	5.43	1
346			min	-1409.84	3	-542.883	2	-444.698	4	-.005	3	-.278	3	-.108	5
347		3	max	2467.696	1	753.918	3	286.882	3	.015	4	1.373	4	5.469	1
348			min	-1411.756	3	-542.883	2	-442.484	4	-.005	3	-.198	3	-.083	5
349		4	max	1860.938	1	1257.374	1	256.933	3	.001	3	1.26	4	5.292	1
350			min	-1216.618	3	-16.396	5	-411.16	4	-.002	1	-.143	3	-.069	5
351		5	max	1858.383	1	1257.374	1	256.933	3	.001	3	1.145	4	4.939	1
352			min	-1218.534	3	-16.396	5	-408.946	4	-.002	1	-.071	3	-.064	5
353		6	max	1855.828	1	1257.374	1	256.933	3	.001	3	1.03	4	4.586	1
354			min	-1220.45	3	-16.396	5	-406.732	4	-.002	1	0	12	-.06	5
355		7	max	1853.274	1	1257.374	1	256.933	3	.001	3	.917	4	4.233	1
356			min	-1222.367	3	-16.396	5	-404.517	4	-.002	1	-.035	2	-.055	5
357		8	max	1850.719	1	1257.374	1	256.933	3	.001	3	.805	5	3.881	1
358			min	-1224.283	3	-16.396	5	-402.303	4	-.002	1	-.098	2	-.051	5
359		9	max	1848.164	1	1257.374	1	256.933	3	.001	3	.705	5	3.528	1
360			min	-1226.199	3	-16.396	5	-400.089	4	-.002	1	-.162	1	-.046	5
361		10	max	1845.609	1	1257.374	1	256.933	3	.001	3	.605	5	3.175	1
362			min	-1228.115	3	-16.396	5	-397.875	4	-.002	1	-.234	1	-.041	5
363		11	max	1843.054	1	1257.374	1	256.933	3	.001	3	.506	5	2.822	1
364			min	-1230.031	3	-16.396	5	-395.66	4	-.002	1	-.306	1	-.037	5
365		12	max	1840.499	1	1257.374	1	256.933	3	.001	3	.433	3	2.47	1
366			min	-1231.947	3	-16.396	5	-393.446	4	-.002	1	-.378	1	-.032	5

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
367		13	max	1837.944	1	1257.374	1	256.933	3	.001	3	.506	3	2.117	1
368			min	-1233.864	3	-16.396	5	-391.232	4	-.002	1	-.449	1	-.028	5
369		14	max	1835.389	1	1257.374	1	256.933	3	.001	3	.578	3	1.764	1
370			min	-1235.78	3	-16.396	5	-389.018	4	-.002	1	-.521	1	-.023	5
371		15	max	1832.834	1	1257.374	1	256.933	3	.001	3	.65	3	1.411	1
372			min	-1237.696	3	-16.396	5	-386.803	4	-.002	1	-.593	1	-.018	5
373		16	max	1830.28	1	1257.374	1	256.933	3	.001	3	.722	3	1.058	1
374			min	-1239.612	3	-16.396	5	-384.589	4	-.002	1	-.665	1	-.014	5
375		17	max	1827.725	1	1257.374	1	256.933	3	.001	3	.794	3	.706	1
376			min	-1241.528	3	-16.396	5	-382.375	4	-.002	1	-.736	1	-.009	5
377		18	max	1825.17	1	1257.374	1	256.933	3	.001	3	.866	3	.353	1
378			min	-1243.444	3	-16.396	5	-380.161	4	-.002	1	-.808	1	-.005	5
379		19	max	1822.615	1	1257.374	1	256.933	3	.001	3	.938	3	0	1
380			min	-1245.361	3	-16.396	5	-377.947	4	-.002	1	-.88	1	0	1
381	M3	1	max	1552.166	2	4.588	6	74.312	1	.022	3	.014	4	0	1
382			min	-497.782	3	1.079	15	-30.466	3	-.048	2	-.003	3	0	1
383		2	max	1551.991	2	4.078	6	74.312	1	.022	3	.028	1	0	15
384			min	-497.913	3	.959	15	-30.466	3	-.048	2	-.012	3	-.001	6
385		3	max	1551.817	2	3.569	6	74.312	1	.022	3	.049	1	0	15
386			min	-498.044	3	.839	15	-30.466	3	-.048	2	-.021	3	-.002	6
387		4	max	1551.643	2	3.059	6	74.312	1	.022	3	.071	1	0	15
388			min	-498.175	3	.719	15	-30.466	3	-.048	2	-.03	3	-.003	6
389		5	max	1551.468	2	2.549	6	74.312	1	.022	3	.093	1	0	15
390			min	-498.305	3	.599	15	-30.466	3	-.048	2	-.039	3	-.004	6
391		6	max	1551.294	2	2.039	6	74.312	1	.022	3	.114	1	-.001	15
392			min	-498.436	3	.479	15	-30.466	3	-.048	2	-.048	3	-.005	6
393		7	max	1551.119	2	1.529	6	74.312	1	.022	3	.136	1	-.001	15
394			min	-498.567	3	.36	15	-30.466	3	-.048	2	-.057	3	-.005	6
395		8	max	1550.945	2	1.02	6	74.312	1	.022	3	.158	1	-.001	15
396			min	-498.698	3	.24	15	-30.466	3	-.048	2	-.065	3	-.006	6
397		9	max	1550.771	2	.51	6	74.312	1	.022	3	.18	1	-.001	15
398			min	-498.829	3	.12	15	-30.466	3	-.048	2	-.074	3	-.006	6
399		10	max	1550.596	2	0	1	74.312	1	.022	3	.201	1	-.001	15
400			min	-498.959	3	0	1	-30.466	3	-.048	2	-.083	3	-.006	6
401		11	max	1550.422	2	-.12	15	74.312	1	.022	3	.223	1	-.001	15
402			min	-499.09	3	-.51	4	-30.466	3	-.048	2	-.092	3	-.006	6
403		12	max	1550.247	2	-.24	15	74.312	1	.022	3	.245	1	-.001	15
404			min	-499.221	3	-1.02	4	-30.466	3	-.048	2	-.101	3	-.006	6
405		13	max	1550.073	2	-.36	15	74.312	1	.022	3	.267	1	-.001	15
406			min	-499.352	3	-1.529	4	-30.466	3	-.048	2	-.11	3	-.005	6
407		14	max	1549.899	2	-.479	15	74.312	1	.022	3	.288	1	-.001	15
408			min	-499.483	3	-2.039	4	-30.466	3	-.048	2	-.119	3	-.005	6
409		15	max	1549.724	2	-.599	15	74.312	1	.022	3	.31	1	0	15
410			min	-499.613	3	-2.549	4	-30.466	3	-.048	2	-.128	3	-.004	6
411		16	max	1549.55	2	-.719	15	74.312	1	.022	3	.332	1	0	15
412			min	-499.744	3	-3.059	4	-30.466	3	-.048	2	-.137	3	-.003	6
413		17	max	1549.376	2	-.839	15	74.312	1	.022	3	.353	1	0	15
414			min	-499.875	3	-3.569	4	-30.466	3	-.048	2	-.146	3	-.002	6
415		18	max	1549.201	2	-.959	15	74.312	1	.022	3	.375	1	0	15
416			min	-500.006	3	-4.078	4	-30.466	3	-.048	2	-.155	3	-.001	6
417		19	max	1549.027	2	-1.079	15	74.312	1	.022	3	.397	1	0	1
418			min	-500.136	3	-4.588	4	-30.466	3	-.048	2	-.163	3	0	1
419	M6	1	max	4503.053	2	4.588	6	0	1	.007	5	.013	4	0	1
420			min	-1704.071	3	1.079	15	-20.314	4	0	1	0	1	0	1
421		2	max	4502.878	2	4.078	6	0	1	.007	5	.007	4	0	15
422			min	-1704.201	3	.959	15	-19.938	4	0	1	0	1	-.001	6
423		3	max	4502.704	2	3.569	6	0	1	.007	5	.001	4	0	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
424			min	-1704.332	3	.839	15	-19.562	4	0	1	0	1	-.002	6
425		4	max	4502.529	2	3.059	6	0	1	.007	5	0	1	0	15
426			min	-1704.463	3	.719	15	-19.186	4	0	1	-.005	4	-.003	6
427		5	max	4502.355	2	2.549	6	0	1	.007	5	0	1	0	15
428			min	-1704.594	3	.599	15	-18.81	4	0	1	-.01	4	-.004	6
429		6	max	4502.181	2	2.039	6	0	1	.007	5	0	1	-.001	15
430			min	-1704.724	3	.479	15	-18.434	4	0	1	-.016	4	-.005	6
431		7	max	4502.006	2	1.529	6	0	1	.007	5	0	1	-.001	15
432			min	-1704.855	3	.36	15	-18.058	4	0	1	-.021	4	-.005	6
433		8	max	4501.832	2	1.02	6	0	1	.007	5	0	1	-.001	15
434			min	-1704.986	3	.24	15	-17.682	4	0	1	-.026	4	-.006	6
435		9	max	4501.658	2	.51	6	0	1	.007	5	0	1	-.001	15
436			min	-1705.117	3	.12	15	-17.306	4	0	1	-.031	4	-.006	6
437		10	max	4501.483	2	0	1	0	1	.007	5	0	1	-.001	15
438			min	-1705.248	3	0	1	-16.93	4	0	1	-.036	4	-.006	6
439		11	max	4501.309	2	-.12	15	0	1	.007	5	0	1	-.001	15
440			min	-1705.378	3	-.51	4	-16.554	4	0	1	-.041	4	-.006	6
441		12	max	4501.134	2	-.24	15	0	1	.007	5	0	1	-.001	15
442			min	-1705.509	3	-1.02	4	-16.178	4	0	1	-.046	4	-.006	6
443		13	max	4500.96	2	-.36	15	0	1	.007	5	0	1	-.001	15
444			min	-1705.64	3	-1.529	4	-15.802	4	0	1	-.051	4	-.005	6
445		14	max	4500.786	2	-.479	15	0	1	.007	5	0	1	-.001	15
446			min	-1705.771	3	-2.039	4	-15.426	4	0	1	-.055	4	-.005	6
447		15	max	4500.611	2	-.599	15	0	1	.007	5	0	1	0	15
448			min	-1705.902	3	-2.549	4	-15.05	4	0	1	-.06	4	-.004	6
449		16	max	4500.437	2	-.719	15	0	1	.007	5	0	1	0	15
450			min	-1706.032	3	-3.059	4	-14.674	4	0	1	-.064	4	-.003	6
451		17	max	4500.262	2	-.839	15	0	1	.007	5	0	1	0	15
452			min	-1706.163	3	-3.569	4	-14.298	4	0	1	-.068	4	-.002	6
453		18	max	4500.088	2	-.959	15	0	1	.007	5	0	1	0	15
454			min	-1706.294	3	-4.078	4	-13.922	4	0	1	-.072	4	-.001	6
455		19	max	4499.914	2	-1.079	15	0	1	.007	5	0	1	0	1
456			min	-1706.425	3	-4.588	4	-13.546	4	0	1	-.076	4	0	1
457	M9	1	max	1552.166	2	4.588	6	30.466	3	.048	2	.013	5	0	1
458			min	-497.782	3	1.079	15	-74.312	1	-.022	3	-.006	2	0	1
459		2	max	1551.991	2	4.078	6	30.466	3	.048	2	.012	3	0	15
460			min	-497.913	3	.959	15	-74.312	1	-.022	3	-.028	1	-.001	6
461		3	max	1551.817	2	3.569	6	30.466	3	.048	2	.021	3	0	15
462			min	-498.044	3	.839	15	-74.312	1	-.022	3	-.049	1	-.002	6
463		4	max	1551.643	2	3.059	6	30.466	3	.048	2	.03	3	0	15
464			min	-498.175	3	.719	15	-74.312	1	-.022	3	-.071	1	-.003	6
465		5	max	1551.468	2	2.549	6	30.466	3	.048	2	.039	3	0	15
466			min	-498.305	3	.599	15	-74.312	1	-.022	3	-.093	1	-.004	6
467		6	max	1551.294	2	2.039	6	30.466	3	.048	2	.048	3	-.001	15
468			min	-498.436	3	.479	15	-74.312	1	-.022	3	-.114	1	-.005	6
469		7	max	1551.119	2	1.529	6	30.466	3	.048	2	.057	3	-.001	15
470			min	-498.567	3	.36	15	-74.312	1	-.022	3	-.136	1	-.005	6
471		8	max	1550.945	2	1.02	6	30.466	3	.048	2	.065	3	-.001	15
472			min	-498.698	3	.24	15	-74.312	1	-.022	3	-.158	1	-.006	6
473		9	max	1550.771	2	.51	6	30.466	3	.048	2	.074	3	-.001	15
474			min	-498.829	3	.12	15	-74.312	1	-.022	3	-.18	1	-.006	6
475		10	max	1550.596	2	0	1	30.466	3	.048	2	.083	3	-.001	15
476			min	-498.959	3	0	1	-74.312	1	-.022	3	-.201	1	-.006	6
477		11	max	1550.422	2	-.12	15	30.466	3	.048	2	.092	3	-.001	15
478			min	-499.09	3	-.51	4	-74.312	1	-.022	3	-.223	1	-.006	6
479		12	max	1550.247	2	-.24	15	30.466	3	.048	2	.101	3	-.001	15
480			min	-499.221	3	-1.02	4	-74.312	1	-.022	3	-.245	1	-.006	6

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
481		13	max	1550.073	2	-.36	15	30.466	3	.048	2	.11	3	-.001	15
482			min	-499.352	3	-1.529	4	-74.312	1	-.022	3	-.267	1	-.005	6
483		14	max	1549.899	2	-.479	15	30.466	3	.048	2	.119	3	-.001	15
484			min	-499.483	3	-2.039	4	-74.312	1	-.022	3	-.288	1	-.005	6
485		15	max	1549.724	2	-.599	15	30.466	3	.048	2	.128	3	0	15
486			min	-499.613	3	-2.549	4	-74.312	1	-.022	3	-.31	1	-.004	6
487		16	max	1549.55	2	-.719	15	30.466	3	.048	2	.137	3	0	15
488			min	-499.744	3	-3.059	4	-74.312	1	-.022	3	-.332	1	-.003	6
489		17	max	1549.376	2	-.839	15	30.466	3	.048	2	.146	3	0	15
490			min	-499.875	3	-3.569	4	-74.312	1	-.022	3	-.353	1	-.002	6
491		18	max	1549.201	2	-.959	15	30.466	3	.048	2	.155	3	0	15
492			min	-500.006	3	-4.078	4	-74.312	1	-.022	3	-.375	1	-.001	6
493		19	max	1549.027	2	-1.079	15	30.466	3	.048	2	.163	3	0	1
494			min	-500.136	3	-4.588	4	-74.312	1	-.022	3	-.397	1	0	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M1	1	max	-.023	15	.025	3	.032	1	1.081e-2	3	NC	3	NC	3
2			min	-.267	1	-.646	1	-.652	5	-2.948e-2	1	191.055	1	249.13	5
3		2	max	-.023	15	.006	3	.01	1	1.081e-2	3	NC	12	NC	3
4			min	-.267	1	-.548	1	-.622	4	-2.948e-2	1	222.103	1	265.097	5
5		3	max	-.023	15	-.01	12	0	12	1.031e-2	3	6079.11	12	NC	2
6			min	-.267	1	-.45	1	-.592	4	-2.747e-2	1	265.253	1	284.073	5
7		4	max	-.023	15	-.02	12	0	12	9.544e-3	3	4149.065	12	NC	1
8			min	-.267	1	-.355	1	-.554	4	-2.438e-2	1	326.435	1	309.615	5
9		5	max	-.023	15	-.022	15	0	3	8.779e-3	3	3306.798	12	NC	1
10			min	-.267	1	-.269	1	-.511	4	-2.13e-2	1	412.747	1	343.569	5
11		6	max	-.023	15	-.017	15	.002	3	8.99e-3	3	3316.621	15	NC	1
12			min	-.266	1	-.198	1	-.465	4	-2.056e-2	1	529.204	1	388.07	5
13		7	max	-.023	15	-.013	15	.002	3	9.878e-3	3	5119.074	10	NC	2
14			min	-.266	1	-.14	1	-.42	4	-2.144e-2	1	684.935	1	445.023	5
15		8	max	-.023	15	-.01	15	0	3	1.076e-2	3	NC	10	NC	2
16			min	-.265	1	-.092	1	-.376	4	-2.232e-2	1	911.033	1	517.113	5
17		9	max	-.023	15	-.006	15	0	9	1.184e-2	3	NC	10	NC	2
18			min	-.265	1	-.052	3	-.337	4	-2.211e-2	1	1302.316	1	607.825	5
19		10	max	-.023	15	.003	10	0	1	1.325e-2	3	NC	2	NC	2
20			min	-.264	1	-.045	3	-.298	4	-1.996e-2	1	1926.054	3	738.306	5
21		11	max	-.023	15	.035	1	.002	3	1.466e-2	3	NC	11	NC	2
22			min	-.264	1	-.035	3	-.26	4	-1.781e-2	1	2239.543	3	933.014	5
23		12	max	-.023	15	.071	1	.007	3	1.2e-2	3	NC	9	NC	2
24			min	-.263	1	-.022	3	-.226	4	-1.344e-2	1	2092.233	2	1236.172	5
25		13	max	-.023	15	.102	1	.013	3	7.047e-3	3	NC	9	NC	2
26			min	-.262	1	-.001	3	-.192	4	-7.803e-3	1	1610.659	2	1792.177	5
27		14	max	-.023	15	.12	1	.013	3	2.319e-3	3	NC	3	NC	2
28			min	-.262	1	.011	15	-.163	4	-5.902e-3	4	1454.552	2	2832.113	5
29		15	max	-.023	15	.123	1	.008	3	7.605e-3	3	NC	4	NC	2
30			min	-.262	1	.013	15	-.143	5	-6.359e-3	1	1540.352	2	3754.113	1
31		16	max	-.023	15	.151	3	.012	1	1.289e-2	3	NC	4	NC	3
32			min	-.262	1	.016	15	-.131	5	-1.034e-2	1	1058.615	3	3301.54	1
33		17	max	-.023	15	.226	3	.008	1	1.818e-2	3	NC	4	NC	3
34			min	-.262	1	.012	10	-.123	5	-1.432e-2	1	665.87	3	3709.589	1
35		18	max	-.023	15	.304	3	-.001	12	2.163e-2	3	NC	4	NC	2
36			min	-.262	1	-.002	10	-.122	4	-1.691e-2	1	479.869	3	6819.983	1
37		19	max	-.023	15	.382	3	-.003	12	2.163e-2	3	NC	1	NC	1
38			min	-.262	1	-.015	10	-.122	4	-1.691e-2	1	375.215	3	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
39	M4	1	max	-.02	15	.164	3	0	1	1.664e-4	4	NC	3	NC	1
40			min	-.584	1	-1.528	1	-.649	4	0	1	88.78	1	250.958	4
41		2	max	-.02	15	.102	3	0	1	1.664e-4	4	3697.156	12	NC	1
42			min	-.584	1	-1.288	1	-.622	4	0	1	105.597	1	264.256	4
43		3	max	-.02	15	.04	3	0	1	0	1	3874.675	15	NC	1
44			min	-.584	1	-1.047	1	-.593	4	-9.466e-5	4	130.346	1	280.326	4
45		4	max	-.02	15	-.015	12	0	1	0	1	4831.999	15	NC	1
46			min	-.584	1	-.814	1	-.555	4	-4.951e-4	4	168.391	1	304.07	4
47		5	max	-.02	15	-.02	15	0	1	0	1	6230.941	15	NC	1
48			min	-.584	1	-.606	1	-.512	4	-8.956e-4	4	228.09	1	337.405	4
49		6	max	-.02	15	-.015	15	0	1	0	1	8210.329	15	NC	1
50			min	-.583	1	-.437	1	-.465	4	-8.568e-4	4	319.774	1	382.448	4
51		7	max	-.02	15	-.01	15	0	1	0	1	NC	15	NC	1
52			min	-.582	1	-.307	1	-.419	4	-5.143e-4	4	464.123	1	440.546	4
53		8	max	-.02	15	-.007	15	0	1	0	1	NC	5	NC	1
54			min	-.58	1	-.2	1	-.376	4	-1.718e-4	4	482.804	3	513.031	4
55		9	max	-.019	15	-.004	15	0	1	0	1	NC	5	NC	1
56			min	-.579	1	-.11	3	-.338	4	-2.811e-5	4	490.955	3	600.618	4
57		10	max	-.019	15	.003	10	0	1	0	1	NC	1	NC	1
58			min	-.578	1	-.1	3	-.298	4	-2.36e-4	4	508.113	3	729.497	4
59		11	max	-.019	15	.079	1	0	1	0	1	NC	4	NC	1
60			min	-.576	1	-.084	3	-.26	4	-4.439e-4	4	540.871	3	920.934	4
61		12	max	-.019	15	.162	1	0	1	0	1	NC	5	NC	1
62			min	-.575	1	-.06	3	-.226	4	-1.71e-3	4	598.903	2	1202.577	4
63		13	max	-.019	15	.228	1	0	1	0	1	NC	5	NC	1
64			min	-.573	1	-.017	3	-.193	4	-3.576e-3	4	494.783	2	1713.48	4
65		14	max	-.019	15	.261	1	0	1	0	1	NC	5	NC	1
66			min	-.572	1	.009	15	-.165	4	-5.371e-3	4	462.326	2	2627.375	4
67		15	max	-.019	15	.249	1	0	1	0	1	NC	5	NC	1
68			min	-.572	1	.009	15	-.147	4	-4.035e-3	4	497.942	2	4125.493	4
69		16	max	-.019	15	.354	3	0	1	0	1	NC	5	NC	1
70			min	-.572	1	.008	15	-.134	4	-2.699e-3	4	609.98	1	6773.493	4
71		17	max	-.019	15	.542	3	0	1	0	1	NC	5	NC	1
72			min	-.572	1	.006	15	-.126	4	-1.363e-3	4	354.526	3	NC	1
73		18	max	-.019	15	.737	3	0	1	0	1	NC	5	NC	1
74			min	-.572	1	-.025	10	-.12	4	-4.915e-4	4	233.732	3	NC	1
75		19	max	-.019	15	.932	3	0	1	0	1	NC	1	NC	1
76			min	-.572	1	-.094	2	-.114	4	-4.915e-4	4	174.453	3	NC	1
77	M7	1	max	.004	5	.025	3	-.001	12	2.948e-2	1	NC	3	NC	3
78			min	-.267	1	-.646	1	-.667	4	-1.081e-2	3	191.055	1	239.223	4
79		2	max	.004	5	.006	3	0	12	2.948e-2	1	NC	5	NC	3
80			min	-.267	1	-.548	1	-.627	4	-1.081e-2	3	222.103	1	257.528	4
81		3	max	.004	5	0	15	.009	1	2.747e-2	1	NC	5	NC	2
82			min	-.267	1	-.45	1	-.587	4	-1.031e-2	3	265.253	1	279.069	4
83		4	max	.004	5	0	15	.017	1	2.438e-2	1	NC	5	NC	1
84			min	-.267	1	-.355	1	-.545	5	-9.544e-3	3	326.435	1	305.559	4
85		5	max	.004	5	.002	5	.018	1	2.13e-2	1	NC	5	NC	1
86			min	-.267	1	-.269	1	-.502	5	-8.779e-3	3	412.747	1	338.749	4
87		6	max	.004	5	.003	5	.015	1	2.056e-2	1	NC	5	NC	1
88			min	-.266	1	-.198	1	-.458	4	-8.99e-3	3	529.204	1	380.641	4
89		7	max	.004	5	.003	5	.007	1	2.144e-2	1	NC	5	NC	2
90			min	-.266	1	-.14	1	-.417	4	-9.878e-3	3	684.935	1	432.093	4
91		8	max	.004	5	.003	5	.002	2	2.232e-2	1	NC	4	NC	2
92			min	-.265	1	-.092	1	-.376	4	-1.076e-2	3	911.033	1	496.58	4
93		9	max	.004	5	.003	5	0	1	2.211e-2	1	NC	4	NC	2
94			min	-.265	1	-.052	3	-.337	4	-1.184e-2	3	1302.316	1	580.381	4
95		10	max	.004	5	.003	10	0	3	1.996e-2	1	NC	2	NC	2

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
96			min	-.264	1	-.045	3	-.298	4	-1.325e-2	3	1926.054	3	698.268	4
97		11	max	.004	5	.035	1	.002	1	1.781e-2	1	NC	4	NC	2
98			min	-.264	1	-.035	3	-.26	4	-1.466e-2	3	2239.543	3	873.496	4
99		12	max	.004	5	.071	1	.009	1	1.344e-2	1	NC	5	NC	2
100			min	-.263	1	-.022	3	-.222	4	-1.2e-2	3	2092.233	2	1154.462	4
101		13	max	.004	5	.102	1	.011	1	7.803e-3	1	NC	5	NC	2
102			min	-.262	1	-.001	3	-.189	4	-7.047e-3	3	1610.659	2	1630.245	4
103		14	max	.004	5	.12	1	.006	2	2.38e-3	1	NC	3	NC	2
104			min	-.262	1	-.002	5	-.163	4	-5.258e-3	5	1454.552	2	2352.334	4
105		15	max	.004	5	.123	1	0	10	6.359e-3	1	NC	5	NC	2
106			min	-.262	1	-.005	5	-.148	4	-7.605e-3	3	1540.352	2	3237.335	4
107		16	max	.004	5	.151	3	-.001	10	1.034e-2	1	NC	5	NC	3
108			min	-.262	1	-.009	5	-.137	4	-1.289e-2	3	1058.615	3	3301.54	1
109		17	max	.004	5	.226	3	0	10	1.432e-2	1	NC	5	NC	3
110			min	-.262	1	-.014	5	-.128	4	-1.818e-2	3	665.87	3	3709.589	1
111		18	max	.004	5	.304	3	.009	1	1.691e-2	1	NC	4	NC	2
112			min	-.262	1	-.018	5	-.117	5	-2.163e-2	3	479.869	3	6819.983	1
113		19	max	.004	5	.382	3	.028	1	1.691e-2	1	NC	1	NC	1
114			min	-.262	1	-.023	5	-.111	5	-2.163e-2	3	375.215	3	NC	1
115	M10	1	max	.002	1	.277	3	.262	1	1.046e-2	3	NC	1	NC	1
116			min	-.121	4	-.017	5	-.004	5	-3.299e-3	2	NC	1	NC	1
117		2	max	.002	1	.621	3	.346	1	1.221e-2	3	NC	5	NC	3
118			min	-.121	4	-.209	2	.006	15	-4.051e-3	2	801.541	3	3276.159	1
119		3	max	.001	1	.939	3	.478	1	1.395e-2	3	NC	5	NC	3
120			min	-.121	4	-.422	1	.014	15	-4.803e-3	2	416.858	3	1280.273	1
121		4	max	.001	1	1.17	3	.607	1	1.57e-2	3	NC	5	NC	5
122			min	-.121	4	-.579	1	.019	15	-5.555e-3	2	308.876	3	799.825	1
123		5	max	0	1	1.282	3	.702	1	1.744e-2	3	NC	5	NC	15
124			min	-.121	4	-.627	1	.021	15	-6.307e-3	2	274.642	3	628.107	1
125		6	max	0	1	1.265	3	.743	1	1.919e-2	3	NC	5	NC	5
126			min	-.121	4	-.563	1	.021	15	-7.059e-3	2	279.247	3	573.939	1
127		7	max	0	1	1.139	3	.729	1	2.093e-2	3	NC	5	NC	5
128			min	-.122	4	-.413	2	.018	15	-7.811e-3	2	320.224	3	590.517	1
129		8	max	0	1	.946	3	.675	1	2.268e-2	3	NC	5	NC	5
130			min	-.122	4	-.235	2	.016	15	-8.563e-3	2	412.254	3	669.225	1
131		9	max	0	1	.758	3	.607	1	2.442e-2	3	NC	4	NC	5
132			min	-.122	4	-.069	2	.015	15	-9.319e-3	1	573.747	3	799.793	1
133		10	max	0	1	.669	3	.572	1	2.617e-2	3	NC	1	NC	5
134			min	-.122	4	-.011	10	.019	15	-1.015e-2	1	703.389	3	889.973	1
135		11	max	0	10	.758	3	.607	1	2.442e-2	3	NC	4	NC	5
136			min	-.122	4	-.069	2	.026	15	-9.319e-3	1	573.747	3	799.793	1
137		12	max	0	10	.946	3	.675	1	2.268e-2	3	NC	5	NC	15
138			min	-.122	4	-.235	2	.032	15	-8.563e-3	2	412.254	3	669.225	1
139		13	max	0	10	1.139	3	.729	1	2.093e-2	3	NC	15	NC	15
140			min	-.122	4	-.413	2	.035	15	-7.811e-3	2	320.224	3	590.517	1
141		14	max	0	10	1.265	3	.743	1	1.919e-2	3	9314.05	15	NC	15
142			min	-.122	4	-.563	1	.035	15	-7.059e-3	2	279.247	3	573.939	1
143		15	max	0	10	1.282	3	.702	1	1.744e-2	3	7657.266	15	NC	5
144			min	-.122	4	-.627	1	.032	15	-6.307e-3	2	274.642	3	628.107	1
145		16	max	0	10	1.17	3	.607	1	1.57e-2	3	7424.09	15	NC	5
146			min	-.122	4	-.579	1	.028	15	-5.555e-3	2	308.876	3	799.825	1
147		17	max	0	10	.939	3	.478	1	1.395e-2	3	8680.119	15	NC	3
148			min	-.122	4	-.422	1	.023	15	-4.803e-3	2	416.858	3	1280.273	1
149		18	max	0	10	.621	3	.346	1	1.221e-2	3	NC	15	NC	3
150			min	-.122	4	-.209	2	.02	15	-4.051e-3	2	801.541	3	3276.159	1
151		19	max	0	10	.277	3	.262	1	1.046e-2	3	NC	1	NC	1
152			min	-.122	4	.003	10	.023	15	-3.299e-3	2	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
153	M11	1	max	.004	1	.048	1	.263	1	4.984e-3	1	NC	1	NC	1
154			min	-.246	4	-.031	3	-.004	5	-9.585e-5	5	NC	1	NC	1
155		2	max	.004	1	.22	3	.331	1	5.672e-3	1	NC	5	NC	3
156			min	-.246	4	-.218	1	.034	15	-2.248e-5	15	1036.04	1	4101.054	1
157		3	max	.003	1	.456	3	.453	1	6.36e-3	1	NC	5	NC	3
158			min	-.246	4	-.451	1	.043	12	2.728e-5	15	553.125	1	1454.248	1
159		4	max	.003	1	.617	3	.58	1	7.048e-3	1	NC	5	NC	3
160			min	-.247	4	-.6	1	.047	15	7.703e-5	15	425.981	3	870.909	1
161		5	max	.002	1	.669	3	.677	1	7.736e-3	1	NC	5	NC	3
162			min	-.247	4	-.638	1	.033	15	1.268e-4	15	394.299	3	667.125	1
163		6	max	.002	1	.604	3	.724	1	8.424e-3	1	NC	5	NC	5
164			min	-.247	4	-.564	1	.013	15	1.766e-4	15	434.542	3	598.878	1
165		7	max	.001	1	.441	3	.718	1	9.113e-3	1	NC	5	NC	5
166			min	-.247	4	-.396	1	-.006	5	2.263e-4	15	585.533	3	607.105	1
167		8	max	0	1	.222	3	.67	1	9.801e-3	1	NC	5	NC	13
168			min	-.247	4	-.179	1	-.022	5	2.761e-4	15	1093.218	3	678.38	1
169		9	max	0	1	.019	1	.609	1	1.049e-2	1	NC	4	NC	7
170			min	-.247	4	-.002	5	-.014	5	3.258e-4	15	5723.645	3	799.888	1
171		10	max	0	1	.11	1	.576	1	1.118e-2	1	NC	4	NC	5
172			min	-.248	4	-.077	3	.019	15	3.756e-4	15	4473.758	1	883.78	1
173		11	max	0	3	.019	1	.609	1	1.049e-2	1	NC	4	8286.69	12
174			min	-.248	4	.003	15	.052	15	3.843e-4	15	5723.645	3	799.888	1
175		12	max	0	3	.222	3	.67	1	9.801e-3	1	NC	5	8506.322	12
176			min	-.248	4	-.179	1	.063	15	3.931e-4	15	1093.218	3	678.38	1
177		13	max	.001	3	.441	3	.718	1	9.113e-3	1	NC	5	9288.342	12
178			min	-.248	4	-.396	1	.057	15	4.019e-4	15	585.533	3	607.105	1
179		14	max	.002	3	.604	3	.724	1	8.424e-3	1	NC	15	NC	12
180			min	-.248	4	-.564	1	.04	15	4.106e-4	15	434.542	3	598.878	1
181		15	max	.002	3	.669	3	.677	1	7.736e-3	1	7950.442	15	NC	3
182			min	-.248	4	-.638	1	.018	15	4.194e-4	15	394.299	3	667.125	1
183		16	max	.002	3	.617	3	.58	1	7.048e-3	1	7490.661	15	NC	3
184			min	-.248	4	-.6	1	-.003	5	4.282e-4	15	425.981	3	870.909	1
185		17	max	.003	3	.456	3	.453	1	6.36e-3	1	8574.628	15	NC	3
186			min	-.248	4	-.451	1	-.02	5	4.369e-4	15	553.125	1	1454.248	1
187		18	max	.003	3	.22	3	.331	1	5.672e-3	1	NC	15	NC	3
188			min	-.248	4	-.218	1	-.012	5	4.457e-4	15	1036.04	1	4101.054	1
189		19	max	.003	3	.048	1	.263	1	4.984e-3	1	NC	1	NC	1
190			min	-.248	4	-.031	3	.023	15	4.545e-4	15	NC	1	NC	1
191	M12	1	max	0	2	.003	5	.265	1	5.923e-3	1	NC	1	NC	1
192			min	-.351	4	-.063	1	-.004	5	-4.418e-5	5	NC	1	NC	1
193		2	max	0	2	.112	3	.321	1	6.704e-3	1	NC	5	NC	2
194			min	-.351	4	-.415	1	.036	15	1.408e-5	15	784.688	1	4061.739	4
195		3	max	0	2	.241	3	.438	1	7.484e-3	1	NC	5	NC	3
196			min	-.351	4	-.718	1	.051	15	6.694e-5	15	421.522	1	1596.381	1
197		4	max	0	2	.315	3	.564	1	8.265e-3	1	NC	5	NC	12
198			min	-.351	4	-.916	1	.048	15	1.198e-4	15	323.72	1	924.411	1
199		5	max	0	2	.324	3	.662	1	9.046e-3	1	NC	5	NC	12
200			min	-.351	4	-.979	1	.033	15	1.727e-4	15	301.397	1	694.96	1
201		6	max	0	2	.271	3	.713	1	9.827e-3	1	NC	5	NC	5
202			min	-.351	4	-.905	1	.011	15	2.255e-4	15	327.86	1	615.812	1
203		7	max	0	2	.171	3	.712	1	1.061e-2	1	NC	5	NC	5
204			min	-.351	4	-.719	1	-.012	5	2.784e-4	15	421.029	1	617.623	1
205		8	max	0	2	.048	3	.669	1	1.139e-2	1	NC	5	NC	13
206			min	-.351	4	-.472	1	-.029	5	3.313e-4	15	675.423	1	683.193	1
207		9	max	0	2	-.006	15	.611	1	1.217e-2	1	NC	3	NC	4
208			min	-.351	4	-.243	1	-.019	5	3.841e-4	15	1533.887	1	797.892	1
209		10	max	0	1	-.005	15	.58	1	1.295e-2	1	NC	4	NC	5

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
210			min	-.351	4	-.139	1	.019	15	4.37e-4	15	3663.521	1	877.163	1
211		11	max	0	9	-.009	15	.611	1	1.217e-2	1	NC	3	8231.88	12
212			min	-.351	4	-.243	1	.056	15	4.423e-4	15	1533.887	1	797.892	1
213		12	max	0	9	.048	3	.669	1	1.139e-2	1	NC	5	8018.315	12
214			min	-.351	4	-.472	1	.067	15	4.476e-4	15	675.423	1	683.193	1
215		13	max	0	9	.171	3	.712	1	1.061e-2	1	NC	15	8124.175	12
216			min	-.351	4	-.719	1	.061	15	4.438e-4	12	421.029	1	617.623	1
217		14	max	0	9	.271	3	.713	1	9.827e-3	1	9063.434	15	NC	15
218			min	-.351	4	-.905	1	.042	15	4.35e-4	12	327.86	1	615.812	1
219		15	max	0	9	.324	3	.662	1	9.046e-3	1	7994.733	15	NC	5
220			min	-.351	4	-.979	1	.017	15	4.263e-4	12	301.397	1	694.96	1
221		16	max	0	9	.315	3	.564	1	8.265e-3	1	8170.285	15	NC	4
222			min	-.351	4	-.916	1	-.006	5	4.175e-4	12	323.72	1	924.411	1
223		17	max	0	9	.241	3	.438	1	7.484e-3	1	9994.166	15	NC	3
224			min	-.351	4	-.718	1	-.025	5	4.088e-4	12	421.522	1	1596.381	1
225		18	max	0	9	.112	3	.321	1	6.704e-3	1	NC	5	NC	2
226			min	-.351	4	-.415	1	-.016	5	4.e-4	12	784.688	1	4915.183	1
227		19	max	0	9	-.007	15	.265	1	5.923e-3	1	NC	1	NC	1
228			min	-.351	4	-.063	1	.023	15	3.912e-4	12	NC	1	NC	1
229	M13	1	max	0	3	0	3	.267	1	1.317e-2	1	NC	1	NC	1
230			min	-.613	4	-.514	1	-.004	5	-2.547e-3	3	NC	1	NC	1
231		2	max	0	3	.163	3	.356	1	1.529e-2	1	NC	5	NC	3
232			min	-.613	4	-.967	1	.034	15	-3.187e-3	3	609.693	1	3105.61	1
233		3	max	0	3	.301	3	.49	1	1.742e-2	1	NC	5	NC	3
234			min	-.613	4	-1.369	1	.051	15	-3.827e-3	3	322.949	1	1236.532	1
235		4	max	0	3	.392	3	.621	1	1.954e-2	1	NC	15	NC	12
236			min	-.613	4	-1.661	1	.051	15	-4.468e-3	3	240.697	1	778.862	1
237		5	max	0	3	.424	3	.716	1	2.167e-2	1	NC	15	NC	12
238			min	-.613	4	-1.811	1	.04	15	-5.108e-3	3	212.841	1	614.268	1
239		6	max	0	3	.397	3	.757	1	2.379e-2	1	9730.079	15	NC	15
240			min	-.613	4	-1.814	1	.023	15	-5.748e-3	3	212.333	1	562.531	1
241		7	max	0	3	.321	3	.743	1	2.592e-2	1	NC	15	NC	5
242			min	-.613	4	-1.692	1	.005	15	-6.388e-3	3	234.289	1	579.198	1
243		8	max	0	3	.219	3	.688	1	2.804e-2	1	NC	15	NC	5
244			min	-.613	4	-1.495	1	-.008	5	-7.028e-3	3	281.507	1	655.97	1
245		9	max	0	3	.124	3	.619	1	3.016e-2	1	NC	15	NC	5
246			min	-.612	4	-1.297	1	-.005	5	-7.668e-3	3	352.369	1	782.469	1
247		10	max	0	1	.08	3	.584	1	3.229e-2	1	NC	15	NC	5
248			min	-.612	4	-1.204	1	.02	15	-8.308e-3	3	400.117	1	869.388	1
249		11	max	0	1	.124	3	.619	1	3.016e-2	1	NC	15	8352.833	12
250			min	-.612	4	-1.297	1	.046	15	-7.668e-3	3	352.369	1	782.469	1
251		12	max	0	1	.219	3	.688	1	2.804e-2	1	9555.429	15	8081.615	12
252			min	-.612	4	-1.495	1	.055	15	-7.028e-3	3	281.507	1	655.97	1
253		13	max	0	1	.321	3	.743	1	2.592e-2	1	7730.612	15	8119.735	12
254			min	-.612	4	-1.692	1	.049	15	-6.388e-3	3	234.289	1	579.198	1
255		14	max	.001	1	.397	3	.757	1	2.379e-2	1	6803.319	15	NC	5
256			min	-.612	4	-1.814	1	.033	15	-5.748e-3	3	212.333	1	562.531	1
257		15	max	.001	1	.424	3	.716	1	2.167e-2	1	6606.033	15	NC	5
258			min	-.612	4	-1.811	1	.014	15	-5.108e-3	3	212.841	1	614.268	1
259		16	max	.002	1	.392	3	.621	1	1.954e-2	1	7202.666	15	NC	12
260			min	-.612	4	-1.661	1	-.005	5	-4.468e-3	3	240.697	1	778.862	1
261		17	max	.002	1	.301	3	.49	1	1.742e-2	1	9245.251	15	NC	3
262			min	-.612	4	-1.369	1	-.019	5	-3.827e-3	3	322.949	1	1236.532	1
263		18	max	.002	1	.163	3	.356	1	1.529e-2	1	NC	5	NC	3
264			min	-.612	4	-.967	1	-.01	5	-3.187e-3	3	609.693	1	3105.61	1
265		19	max	.002	1	0	3	.267	1	1.317e-2	1	NC	1	NC	1
266			min	-.612	4	-.514	1	.023	15	-2.547e-3	3	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
267	M2	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
268			min	0	1	0	1	0	1	0	1	NC	1	NC	1
269		2	max	0	3	0	15	0	5	3.208e-3	1	NC	1	NC	1
270			min	0	1	-.001	1	0	1	-3.479e-3	5	NC	1	NC	1
271		3	max	0	3	0	15	.003	5	6.416e-3	1	NC	1	NC	1
272			min	0	1	-.005	1	0	1	-6.957e-3	5	NC	1	NC	1
273		4	max	0	3	0	15	.007	5	7.504e-3	2	NC	3	NC	1
274			min	0	1	-.011	1	-.002	1	-8.394e-3	5	5757.712	1	8661.32	5
275		5	max	0	3	-.002	15	.012	5	6.881e-3	2	NC	3	NC	1
276			min	0	1	-.019	1	-.003	1	-8.174e-3	5	3226.217	1	5021.13	5
277		6	max	0	3	-.003	15	.018	5	6.259e-3	2	NC	5	NC	1
278			min	0	1	-.029	1	-.004	1	-7.953e-3	5	2077.538	1	3304.018	5
279		7	max	0	3	-.004	15	.026	5	5.637e-3	2	NC	5	NC	9
280			min	0	1	-.042	1	-.005	1	-7.733e-3	5	1459.614	1	2357.782	5
281		8	max	0	3	-.005	15	.034	5	5.015e-3	2	NC	15	NC	9
282			min	0	1	-.056	1	-.007	1	-7.512e-3	5	1088.381	1	1779.826	5
283		9	max	0	3	-.006	15	.043	5	4.392e-3	2	9522.825	15	NC	9
284			min	0	1	-.072	1	-.008	1	-7.292e-3	5	847.527	1	1400.275	5
285		10	max	0	3	-.008	15	.053	5	3.77e-3	2	7693.527	15	NC	9
286			min	0	1	-.089	1	-.009	1	-7.071e-3	5	682.126	1	1137.199	5
287		11	max	0	3	-.01	15	.064	5	3.148e-3	2	6374.597	15	NC	9
288			min	-.001	1	-.108	1	-.009	1	-6.851e-3	5	563.5	1	947.144	5
289		12	max	0	3	-.011	15	.075	5	2.526e-3	2	5391.71	15	NC	9
290			min	-.001	1	-.127	1	-.01	1	-6.63e-3	5	475.472	1	805.286	5
291		13	max	0	3	-.013	15	.087	5	1.904e-3	2	4639.108	15	NC	9
292			min	-.001	1	-.148	1	-.01	1	-6.41e-3	5	408.301	1	696.537	5
293		14	max	0	3	-.015	15	.099	5	1.281e-3	2	4049.788	15	NC	9
294			min	-.001	1	-.17	1	-.009	1	-6.189e-3	5	355.854	1	611.32	5
295		15	max	0	3	-.017	15	.112	5	6.59e-4	2	3579.551	15	NC	9
296			min	-.001	1	-.193	1	-.008	1	-6.048e-3	4	314.107	1	543.308	5
297		16	max	0	3	-.019	15	.124	4	6.376e-4	3	3198.402	15	NC	9
298			min	-.002	1	-.216	1	-.006	1	-5.923e-3	4	280.34	1	487.77	4
299		17	max	.001	3	-.021	15	.137	4	9.528e-4	3	2885.283	15	NC	9
300			min	-.002	1	-.24	1	-.004	1	-5.798e-3	4	252.651	1	441.061	4
301		18	max	.001	3	-.023	15	.151	4	1.268e-3	3	2625.063	15	NC	1
302			min	-.002	1	-.264	1	-.008	3	-5.673e-3	4	229.676	1	402.226	4
303		19	max	.001	3	-.025	15	.164	4	1.583e-3	3	2406.659	15	NC	1
304			min	-.002	1	-.288	1	-.013	3	-5.547e-3	4	210.42	1	369.623	4
305	M5	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
306			min	0	1	0	1	0	1	0	1	NC	1	NC	1
307		2	max	0	3	0	15	0	4	0	1	NC	1	NC	1
308			min	0	1	-.002	1	0	1	-3.734e-3	4	NC	1	NC	1
309		3	max	0	3	0	15	.003	4	0	1	NC	3	NC	1
310			min	0	1	-.009	1	0	1	-7.467e-3	4	6396.597	1	NC	1
311		4	max	0	3	0	15	.007	4	0	1	NC	4	NC	1
312			min	0	1	-.022	1	0	1	-8.993e-3	4	2741.155	1	8233.111	4
313		5	max	0	3	-.001	15	.013	4	0	1	NC	5	NC	1
314			min	-.001	1	-.04	1	0	1	-8.726e-3	4	1516.547	1	4777.376	4
315		6	max	.001	3	-.002	15	.019	4	0	1	NC	5	NC	1
316			min	-.002	1	-.063	1	0	1	-8.459e-3	4	969.614	1	3146.798	4
317		7	max	.001	3	-.003	15	.027	4	0	1	NC	5	NC	1
318			min	-.002	1	-.089	1	0	1	-8.191e-3	4	678.109	1	2248.124	4
319		8	max	.001	3	-.004	15	.036	4	0	1	NC	15	NC	1
320			min	-.002	1	-.12	1	0	1	-7.924e-3	4	504.041	1	1699.173	4
321		9	max	.002	3	-.005	15	.045	4	0	1	NC	15	NC	1
322			min	-.002	1	-.155	1	0	1	-7.657e-3	4	391.59	1	1338.654	4
323		10	max	.002	3	-.007	15	.056	4	0	1	9293.406	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
324			min	-.003	1	-.193	1	0	1	-7.39e-3	4	314.613	1	1088.776	4
325		11	max	.002	3	-.008	15	.067	4	0	1	7676.175	15	NC	1
326			min	-.003	1	-.234	1	0	1	-7.122e-3	4	259.541	1	908.274	4
327		12	max	.002	3	-.009	15	.078	4	0	1	6476.314	15	NC	1
328			min	-.003	1	-.277	1	0	1	-6.855e-3	4	218.754	1	773.575	4
329		13	max	.002	3	-.011	15	.09	4	0	1	5560.893	15	NC	1
330			min	-.003	1	-.323	1	0	1	-6.588e-3	4	187.681	1	670.352	4
331		14	max	.002	3	-.013	15	.103	4	0	1	4846.236	15	NC	1
332			min	-.004	1	-.371	1	0	1	-6.321e-3	4	163.452	1	589.509	4
333		15	max	.003	3	-.014	15	.115	4	0	1	4277.439	15	NC	1
334			min	-.004	1	-.42	1	0	1	-6.054e-3	4	144.187	1	525.043	4
335		16	max	.003	3	-.016	15	.128	4	0	1	3817.409	15	NC	1
336			min	-.004	1	-.471	1	0	1	-5.786e-3	4	128.619	1	472.866	4
337		17	max	.003	3	-.018	15	.141	4	0	1	3440.207	15	NC	1
338			min	-.004	1	-.523	1	0	1	-5.519e-3	4	115.864	1	430.108	4
339		18	max	.003	3	-.019	15	.154	4	0	1	3127.254	15	NC	1
340			min	-.005	1	-.576	1	0	1	-5.252e-3	4	105.289	1	394.707	4
341		19	max	.003	3	-.021	15	.166	4	0	1	2864.982	15	NC	1
342			min	-.005	1	-.628	1	0	1	-4.985e-3	4	96.431	1	365.154	4
343	M8	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
344			min	0	1	0	1	0	1	0	1	NC	1	NC	1
345		2	max	0	3	0	5	0	4	1.356e-3	3	NC	1	NC	1
346			min	0	1	-.001	1	0	3	-4.199e-3	4	NC	1	NC	1
347		3	max	0	3	0	5	.003	4	2.712e-3	3	NC	1	NC	1
348			min	0	1	-.005	1	0	3	-8.399e-3	4	NC	1	NC	1
349		4	max	0	3	0	5	.008	4	3.145e-3	3	NC	3	NC	1
350			min	0	1	-.011	1	-.001	3	-1.007e-2	4	5757.712	1	8066.79	4
351		5	max	0	3	0	5	.013	4	2.83e-3	3	NC	3	NC	1
352			min	0	1	-.019	1	-.002	3	-9.698e-3	4	3226.217	1	4691.531	4
353		6	max	0	3	0	5	.02	4	2.515e-3	3	NC	4	NC	1
354			min	0	1	-.029	1	-.003	3	-9.323e-3	4	2077.538	1	3096.165	4
355		7	max	0	3	0	5	.027	4	2.2e-3	3	NC	5	NC	9
356			min	0	1	-.042	1	-.004	3	-8.948e-3	4	1459.614	1	2215.928	4
357		8	max	0	3	0	5	.036	4	1.884e-3	3	NC	5	NC	9
358			min	0	1	-.056	1	-.005	3	-8.572e-3	4	1088.381	1	1677.826	4
359		9	max	0	3	.001	5	.046	4	1.569e-3	3	NC	5	NC	9
360			min	0	1	-.072	1	-.006	3	-8.197e-3	4	847.527	1	1324.24	4
361		10	max	0	3	.001	5	.056	4	1.254e-3	3	NC	5	NC	9
362			min	0	1	-.089	1	-.006	3	-7.822e-3	4	682.126	1	1079.083	4
363		11	max	0	3	.002	5	.067	4	9.386e-4	3	NC	5	NC	9
364			min	-.001	1	-.108	1	-.007	3	-7.446e-3	4	563.5	1	901.963	4
365		12	max	0	3	.002	5	.079	4	6.234e-4	3	NC	5	NC	9
366			min	-.001	1	-.127	1	-.006	3	-7.071e-3	4	475.472	1	769.793	4
367		13	max	0	3	.002	5	.091	4	3.081e-4	3	NC	5	NC	9
368			min	-.001	1	-.148	1	-.006	3	-6.696e-3	4	408.301	1	668.535	4
369		14	max	0	3	.003	5	.103	4	-5.499e-6	12	NC	5	NC	9
370			min	-.001	1	-.17	1	-.004	3	-6.32e-3	4	355.854	1	589.277	4
371		15	max	0	3	.003	5	.115	4	1.197e-4	9	NC	5	NC	9
372			min	-.001	1	-.193	1	-.003	3	-5.946e-3	5	314.107	1	526.133	4
373		16	max	0	3	.003	5	.128	4	4.795e-4	1	NC	5	NC	9
374			min	-.002	1	-.216	1	0	3	-5.669e-3	5	280.34	1	475.098	4
375		17	max	.001	3	.004	5	.14	4	1.143e-3	1	NC	5	NC	9
376			min	-.002	1	-.24	1	0	10	-5.392e-3	5	252.651	1	433.357	4
377		18	max	.001	3	.004	5	.152	4	1.807e-3	1	NC	5	NC	1
378			min	-.002	1	-.264	1	-.002	2	-5.115e-3	5	229.676	1	398.892	4
379		19	max	.001	3	.004	5	.164	4	2.471e-3	1	NC	5	NC	1
380			min	-.002	1	-.288	1	-.006	2	-4.839e-3	5	210.42	1	370.225	4

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
381	M3	1	max	.006	1	0	15	.005	5	2.977e-3	2	NC	1	NC	1
382			min	0	15	-.003	1	-.001	1	-2.426e-3	5	NC	1	NC	1
383		2	max	.006	1	-.002	15	.034	5	3.546e-3	2	NC	1	NC	5
384			min	0	15	-.023	1	-.027	1	-2.454e-3	5	NC	1	2379.721	1
385		3	max	.005	1	-.004	15	.063	5	4.115e-3	2	NC	1	NC	5
386			min	0	15	-.044	1	-.052	1	-2.481e-3	5	NC	1	1203.444	1
387		4	max	.005	1	-.006	15	.092	5	4.684e-3	2	NC	1	NC	13
388			min	0	15	-.064	1	-.075	1	-2.508e-3	5	NC	1	809.749	4
389		5	max	.004	1	-.008	15	.122	5	5.253e-3	2	NC	1	NC	13
390			min	0	15	-.084	1	-.098	1	-2.535e-3	5	NC	1	604.53	4
391		6	max	.004	1	-.009	15	.151	5	5.822e-3	2	NC	1	NC	13
392			min	0	10	-.104	1	-.118	1	-2.562e-3	5	NC	1	481.585	4
393		7	max	.003	3	-.011	15	.18	5	6.391e-3	2	NC	1	NC	13
394			min	0	10	-.124	1	-.136	1	-2.695e-3	3	NC	1	399.765	4
395		8	max	.003	3	-.013	15	.209	5	6.96e-3	2	NC	1	NC	13
396			min	0	10	-.144	1	-.151	1	-2.954e-3	3	NC	1	341.433	4
397		9	max	.004	3	-.015	15	.237	5	7.529e-3	2	NC	1	NC	13
398			min	0	10	-.164	1	-.162	1	-3.212e-3	3	NC	1	297.773	4
399		10	max	.004	3	-.016	15	.265	5	8.098e-3	2	NC	1	NC	13
400			min	0	10	-.184	1	-.169	1	-3.47e-3	3	NC	1	263.887	4
401		11	max	.004	3	-.018	15	.293	5	8.667e-3	2	NC	1	NC	13
402			min	-.001	2	-.203	1	-.173	2	-3.728e-3	3	NC	1	236.836	4
403		12	max	.004	3	-.02	15	.32	5	9.236e-3	2	NC	1	NC	13
404			min	-.002	2	-.223	1	-.171	2	-3.987e-3	3	NC	1	214.751	4
405		13	max	.004	3	-.021	15	.346	5	9.805e-3	2	NC	1	NC	13
406			min	-.002	2	-.242	1	-.165	2	-4.245e-3	3	NC	1	196.385	4
407		14	max	.004	3	-.023	15	.372	5	1.037e-2	2	NC	1	NC	13
408			min	-.003	2	-.262	1	-.152	2	-4.503e-3	3	NC	1	180.875	4
409		15	max	.005	3	-.024	15	.396	5	1.094e-2	2	NC	1	NC	13
410			min	-.003	2	-.281	1	-.134	2	-4.762e-3	3	NC	1	167.606	4
411		16	max	.005	3	-.026	15	.42	5	1.151e-2	2	NC	1	NC	13
412			min	-.004	2	-.3	1	-.109	2	-5.02e-3	3	NC	1	156.125	4
413		17	max	.005	3	-.027	15	.443	5	1.208e-2	2	NC	1	NC	13
414			min	-.004	2	-.319	1	-.077	2	-5.278e-3	3	NC	1	146.093	4
415		18	max	.005	3	-.029	15	.465	5	1.265e-2	2	NC	1	NC	5
416			min	-.005	2	-.338	1	-.037	2	-5.536e-3	3	NC	1	137.252	4
417		19	max	.005	3	-.03	15	.493	4	1.322e-2	2	NC	1	NC	1
418			min	-.005	2	-.357	1	0	3	-5.795e-3	3	NC	1	129.4	4
419	M6	1	max	.013	1	0	15	.005	4	0	1	NC	1	NC	1
420			min	0	15	-.007	1	0	1	-2.627e-3	4	NC	1	NC	1
421		2	max	.011	1	-.002	15	.036	4	0	1	NC	1	NC	1
422			min	0	15	-.051	1	0	1	-2.705e-3	4	NC	1	NC	1
423		3	max	.01	1	-.003	15	.067	4	0	1	NC	1	NC	1
424			min	0	15	-.095	1	0	1	-2.783e-3	4	NC	1	7719.088	4
425		4	max	.008	1	-.005	15	.099	4	0	1	NC	1	NC	1
426			min	0	15	-.139	1	0	1	-2.861e-3	4	NC	1	5104.603	4
427		5	max	.007	3	-.007	15	.13	4	0	1	NC	1	NC	1
428			min	0	15	-.183	1	0	1	-2.939e-3	4	NC	1	3835.978	4
429		6	max	.008	3	-.008	15	.161	4	0	1	NC	1	NC	1
430			min	0	10	-.227	1	0	1	-3.016e-3	4	NC	1	3105.606	4
431		7	max	.008	3	-.01	15	.191	4	0	1	NC	1	NC	1
432			min	0	10	-.27	1	0	1	-3.094e-3	4	NC	1	2645.851	4
433		8	max	.009	3	-.011	15	.222	4	0	1	NC	1	NC	1
434			min	-.002	2	-.314	1	0	1	-3.172e-3	4	NC	1	2343.533	4
435		9	max	.009	3	-.013	15	.251	4	0	1	NC	1	NC	1
436			min	-.003	2	-.358	1	0	1	-3.25e-3	4	NC	1	2143.784	4
437		10	max	.01	3	-.014	15	.28	4	0	1	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
438			min	-.005	2	-.401	1	0	1	-3.328e-3	4	NC	1	2018.315	4
439		11	max	.01	3	-.016	15	.308	4	0	1	NC	1	NC	1
440			min	-.006	2	-.445	1	0	1	-3.405e-3	4	NC	1	1953.223	4
441		12	max	.011	3	-.017	15	.336	4	0	1	NC	1	NC	1
442			min	-.008	2	-.488	1	0	1	-3.483e-3	4	NC	1	1944.346	4
443		13	max	.012	3	-.019	15	.362	4	0	1	NC	1	NC	1
444			min	-.009	2	-.531	1	0	1	-3.561e-3	4	NC	1	1996.703	4
445		14	max	.012	3	-.02	15	.387	4	0	1	NC	1	NC	1
446			min	-.011	2	-.574	1	0	1	-3.639e-3	4	NC	1	2128.094	4
447		15	max	.013	3	-.021	15	.411	4	0	1	NC	1	NC	1
448			min	-.012	2	-.617	1	0	1	-3.717e-3	4	NC	1	2381.107	4
449		16	max	.013	3	-.022	15	.434	4	0	1	NC	1	NC	1
450			min	-.014	2	-.66	1	0	1	-3.794e-3	4	NC	1	2861.264	4
451		17	max	.014	3	-.024	15	.455	4	0	1	NC	1	NC	1
452			min	-.016	2	-.703	1	0	1	-3.872e-3	4	NC	1	3891.424	4
453		18	max	.014	3	-.025	15	.475	4	0	1	NC	1	NC	1
454			min	-.017	2	-.746	1	0	1	-3.95e-3	4	NC	1	7094.673	4
455		19	max	.015	3	-.026	15	.493	4	0	1	NC	1	NC	1
456			min	-.019	2	-.789	1	0	1	-4.028e-3	4	NC	1	NC	1
457	M9	1	max	.006	1	0	5	.005	4	1.146e-3	3	NC	1	NC	1
458			min	0	5	-.003	1	-.001	3	-3.068e-3	4	NC	1	NC	1
459		2	max	.006	1	0	15	.04	4	1.404e-3	3	NC	1	NC	5
460			min	0	5	-.023	1	-.012	3	-3.546e-3	2	NC	1	2379.721	1
461		3	max	.005	1	0	15	.075	4	1.662e-3	3	NC	1	NC	15
462			min	0	5	-.044	1	-.023	3	-4.115e-3	2	NC	1	1203.444	1
463		4	max	.005	1	0	15	.11	4	1.921e-3	3	NC	1	6942.887	15
464			min	0	5	-.064	1	-.033	3	-4.684e-3	2	NC	1	816.524	1
465		5	max	.004	1	0	15	.144	4	2.179e-3	3	NC	1	5224.035	15
466			min	0	5	-.084	1	-.042	3	-5.253e-3	2	NC	1	627.356	1
467		6	max	.004	1	0	15	.178	4	2.437e-3	3	NC	1	4233.883	15
468			min	0	5	-.104	1	-.051	3	-5.822e-3	2	NC	1	517.781	1
469		7	max	.003	3	0	15	.211	4	2.695e-3	3	NC	1	3610.33	15
470			min	0	5	-.124	1	-.059	3	-6.391e-3	2	NC	1	448.592	1
471		8	max	.003	3	0	15	.243	4	2.954e-3	3	NC	1	3200.224	15
472			min	0	5	-.144	1	-.065	3	-6.96e-3	2	NC	1	403.203	1
473		9	max	.004	3	0	15	.274	4	3.212e-3	3	NC	1	2929.32	15
474			min	0	10	-.164	1	-.07	3	-7.529e-3	2	NC	1	373.602	1
475		10	max	.004	3	0	15	.304	4	3.47e-3	3	NC	1	2759.353	15
476			min	0	10	-.184	1	-.074	3	-8.098e-3	2	NC	1	355.716	1
477		11	max	.004	3	0	15	.332	4	3.728e-3	3	NC	1	2671.56	15
478			min	-.001	2	-.203	1	-.075	3	-8.667e-3	2	NC	1	347.656	1
479		12	max	.004	3	.001	5	.359	4	3.987e-3	3	NC	1	2660.41	15
480			min	-.002	2	-.223	1	-.075	3	-9.236e-3	2	NC	1	349.08	1
481		13	max	.004	3	.002	5	.384	4	4.245e-3	3	NC	1	2732.891	15
482			min	-.002	2	-.242	1	-.072	3	-9.805e-3	2	NC	1	361.201	1
483		14	max	.004	3	.002	5	.407	4	4.503e-3	3	NC	1	2913.455	15
484			min	-.003	2	-.262	1	-.067	3	-1.037e-2	2	NC	1	387.517	1
485		15	max	.005	3	.002	5	.427	4	4.762e-3	3	NC	1	3260.489	15
486			min	-.003	2	-.281	1	-.06	3	-1.094e-2	2	NC	1	436.083	1
487		16	max	.005	3	.003	5	.445	4	5.02e-3	3	NC	1	3918.576	15
488			min	-.004	2	-.3	1	-.049	3	-1.151e-2	2	NC	1	526.625	1
489		17	max	.005	3	.003	5	.461	4	5.278e-3	3	NC	1	5330.006	15
490			min	-.004	2	-.319	1	-.036	3	-1.208e-2	2	NC	1	719.284	1
491		18	max	.005	3	.004	5	.474	4	5.536e-3	3	NC	1	9718.166	15
492			min	-.005	2	-.338	1	-.019	3	-1.265e-2	2	NC	1	1316.126	1
493		19	max	.005	3	.005	5	.484	5	5.795e-3	3	NC	1	NC	1
494			min	-.005	2	-.357	1	-.018	1	-1.322e-2	2	NC	1	NC	1