

Schletter, Inc.		25° Tilt w/ Seismic Design
HCV	Standard PVMax Racking System	
	Representative Calculations - ASCE 7-05	

1. INTRODUCTION

1.1 Project Description

The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. PVMax ground mount system.

1.2 Construction

Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to aluminum struts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

	Maximum		Minimum	
Height =	2000	mm	1900	mm
Width =	1050	mm	970	mm
Dead Load =	3.00	psf	1.75	psf

Modules Per Row =	2
Module Tilt =	25°
Maximum Height Above Grade =	3 ft



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

1.3 Technical Codes

- ASCE 7-05 - Chapter 6, Wind Loads
- ASCE 7-05 - Chapter 7, Snow Loads
- ASCE 7-05 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2003, 2006, 2009
- Aluminum Design Manual, Eighth Edition, 2005

2. LOAD ACTIONS

2.1 Permanent Loads

g_{MAX} =	3.00	psf	*Self-weight of the PV modules.*
g_{MIN} =	1.75	psf	

2.2 Snow Loads

Ground Snow Load, P_g =	30.00	psf	
Sloped Roof Snow Load, P_s =	18.56	psf	*(ASCE 7-05, Eq. 7-2)*
I_s =	1.00		
C_s =	0.82		
C_e =	0.90		
C_t =	1.20		

2.3 Wind Loads

Design Wind Speed, V =	85	mph	Exposure Category = C
Height <	15	ft	Importance Category = II
Peak Velocity Pressure, q_z =	11.34	psf	*Including the gust factor, G=0.85. (ASCE 7-05, Eq. 6-15)*

Pressure Coefficients

$Cf+_{TOP}$ =	1.100	*(Pressure)*	*Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0611-1e. Negative forces are applied away from the surface.*
$Cf+_{BOTTOM}$ =	1.700		
$Cf-_{TOP, OUTER PURLIN}$ =	-2.500		
$Cf-_{TOP, INNER PURLIN}$ =	-1.900	*(Suction)*	
$Cf-_{BOTTOM}$ =	-1.000		

2.4 Seismic Loads

S_S =	2.50	R =	1.25	*ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.*
S_{DS} =	1.67	C_S =	0.8	
S_1 =	1.00	ρ =	1.3	
S_{D1} =	1.00	Ω =	1.25	
T_a =	0.06	C_d =	1.25	

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.8W
1.2D + 1.6W + 0.5S
0.9D + 1.6W [M]
1.54D + 1.3E + 0.2S [R]
0.56D + 1.3E [R]
1.54D + 1.25E + 0.2S [O]
0.56D + 1.25E [O]

(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S
1.0D + 1.0W
1.0D + 0.75L + 0.75W + 0.75S
0.6D + 1.0W [M]
1.238D + 0.875E [O]
1.1785D + 0.65625E + 0.75S [O]
0.362D + 0.875E [O]

(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)

[M] *Uses the minimum allowable module dead load.*
[R] *Include redundancy factor of 1.3.*
[O] *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location
M13	Top
M14	Mid-Top
M15	Mid-Bottom
M16	Bottom

Girders	Location
M1	Outer
M5	Inner
M9	Outer

Front Struts	Location
M4	Outer
M8	Inner
M12	Outer

Diagonal Struts	Location
M3	Outer
M7	Inner
M11	Outer

Rear Struts	Location
M2	Outer
M6	Inner
M10	Outer

Front Reactions	Location
N7	Outer
N15	Inner
N23	Outer

Rear Reactions	Location
N8	Outer
N16	Inner
N24	Outer

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type =	**S1.5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	117	in
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	25.07	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	23.08	ksi
S_y =	1.33	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	2.16	in^4
I_x =	1.07	in^4
A =	1.25	in^2
g =	1.50	lbs/ft
M_y =	1.766	k-ft
M_z =	0.372	k-ft
$M_{y\ allowable}$ =	2.779	k-ft
$M_{z\ allowable}$ =	1.154	k-ft
Utilization =	96%	



DETAIL VIEW

4.2 Girder Design

Loads from purlins are transferred using an inclined girder, which is connected to a set of aluminum struts. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type =	**BF0**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	104.56	in
$\Phi F_{ty\ AXIAL}$ =	31.09	ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	29.00	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	33.25	ksi
S_y =	1.42	in^3
S_x =	1.41	in^3
E =	10100	ksi
I_y =	2.39	in^4
I_x =	2.22	in^4
A =	1.88	in^2
g =	2.26	lbs/ft
M_y =	-3.207	k-ft
M_z =	0.000	k-ft
P_n =	-0.339	k
$M_{y\ allowable}$ =	3.422	k-ft
$M_{z\ allowable}$ =	3.907	k-ft
$P_{n\ allowable}$ =	58.535	k
Utilization =	94%	



4.3 Front Strut Design

The front aluminum strut connects a portion of the girder to the foundation. Vertical girder forces are then transferred down through the strut into the foundation. The strut is attached with single M12 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	24.80	in
$\Phi F_{ty\ AXIAL}$ =	28.03	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.000	k-ft
M_z =	-0.604	k-ft
P_n =	0.683	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	27.532	k
Utilization =	45%	



DETAIL VIEW

4.4 Diagonal Strut Design

A diagonal aluminum strut braces the support structure. It connects at a front portion of the girder and transfers horizontal forces to the rear foundation connection. The strut is attached with single M12 bolts at each end. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	98.03	in
$\Phi F_{ty\ AXIAL}$ =	6.11	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.011	k-ft
M_z =	0.000	k-ft
P_n =	1.693	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	6.000	k
Utilization =	29%	



DETAIL VIEW

4.5 Rear Strut Design

An aluminum strut connects the rear portion of the girder to the rear foundation connection. Both vertical and horizontal forces are transferred from the girder. The strut is attached with single M12 bolts at each end. See Appendix A.5 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	69.80	in
$\Phi F_{ty\ AXIAL}$ =	10.82	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	-0.010	k-ft
M_z =	0.000	k-ft
P_n =	3.309	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	10.629	k
Utilization =	32%	



5. FOUNDATION DESIGN CALCULATIONS

5.1 Helical Pile Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete foundation design.

Maximum	Front	Rear	
Tensile Load =	367.34	4595.72	k
Compressive Load =	3978.25	4613.77	k
Lateral Load =	405.38	2479.69	k
Moment (Weak Axis) =	0.82	0.39	k

5.2 Design of Ballast Foundations

Ballast foundations are used to secure the racking structure in place. The foundations are checked for potential overturning and sliding. Bearing pressures applied by the racking and ballast foundations are checked against the allowable bearing pressures provided by the IBC tables 1804.2 (2003, 2006) & 1806.2 (2009).



Concrete Properties

Weight of Concrete =	145 pcf
Compressive Strength =	2500 psi
Yield Strength =	60000 psi

Overturning Check

M_O =	129037.6 in-lbs
Resisting Force Required =	1804.72 lbs
S.F. =	1.67
Weight Required =	3007.87 lbs
Minimum Width =	35 in
Weight Provided =	7559.64 lbs

Sliding

Force =	595.81 lbs
Friction =	0.4
Weight Required =	1489.54 lbs
Resisting Weight =	7559.64 lbs
Additional Weight Required =	0 lbs

Cohesion

Sliding Force =	595.81 lbs
Cohesion =	130 psf
Area =	34.76 ft^2
Resisting =	3779.82 lbs
Additional Weight Required =	0 lbs

Shear Key

Additional Force =	0 lbs
Lateral Bearing Pressure =	200 psf/ft
Required Depth =	0.00 ft
f'_c =	2500 psi
Length =	8 in

Footing Reinforcement

Use fiber reinforcing with (2) #5 rebar.

A minimum 143in long x 35in wide x 18in tall ballast foundation is required to resist overturning.

Use a 143in long x 35in wide x 18in tall ballast foundation to resist sliding. Friction is OK.

Use a 143in long x 35in wide x 18in tall ballast foundation. Cohesion is OK.

Shear key is not required.

Bearing Pressure

	Ballast Width			
	35 in	36 in	37 in	38 in
P_{ftg} = (145 pcf)(11.92 ft)(1.5 ft)(2.92 ft) =	7560 lbs	7776 lbs	7992 lbs	8208 lbs

ASD LC	1.0D + 1.0S				1.0D + 1.0W				1.0D + 0.75L + 0.75W + 0.75S				0.6D + 1.0W			
Width	35 in	36 in	37 in	38 in	35 in	36 in	37 in	38 in	35 in	36 in	37 in	38 in	35 in	36 in	37 in	38 in
F_A	1537 lbs	1537 lbs	1537 lbs	1537 lbs	1177 lbs	1177 lbs	1177 lbs	1177 lbs	1895 lbs	1895 lbs	1895 lbs	1895 lbs	-170 lbs	-170 lbs	-170 lbs	-170 lbs
F_B	1604 lbs	1604 lbs	1604 lbs	1604 lbs	1662 lbs	1662 lbs	1662 lbs	1662 lbs	2304 lbs	2304 lbs	2304 lbs	2304 lbs	-2203 lbs	-2203 lbs	-2203 lbs	-2203 lbs
F_V	202 lbs	202 lbs	202 lbs	202 lbs	1087 lbs	1087 lbs	1087 lbs	1087 lbs	950 lbs	950 lbs	950 lbs	950 lbs	-1192 lbs	-1192 lbs	-1192 lbs	-1192 lbs
P_{total}	10700 lbs	10916 lbs	11132 lbs	11348 lbs	10399 lbs	10615 lbs	10831 lbs	11047 lbs	11758 lbs	11974 lbs	12190 lbs	12406 lbs	2163 lbs	2293 lbs	2422 lbs	2552 lbs
M	3731 lbs-ft	3731 lbs-ft	3731 lbs-ft	3731 lbs-ft	2981 lbs-ft	2981 lbs-ft	2981 lbs-ft	2981 lbs-ft	4691 lbs-ft	4691 lbs-ft	4691 lbs-ft	4691 lbs-ft	3794 lbs-ft	3794 lbs-ft	3794 lbs-ft	3794 lbs-ft
e	0.35 ft	0.34 ft	0.34 ft	0.33 ft	0.29 ft	0.28 ft	0.28 ft	0.27 ft	0.40 ft	0.39 ft	0.38 ft	0.38 ft	1.75 ft	1.65 ft	1.57 ft	1.49 ft
L/6	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft
f_{min}	253.8 psf	252.8 psf	251.9 psf	250.9 psf	256.0 psf	254.9 psf	253.9 psf	253.0 psf	270.3 psf	268.9 psf	267.5 psf	266.2 psf	7.3 psf	10.7 psf	13.9 psf	17.0 psf
f_{max}	361.9 psf	357.9 psf	354.1 psf	350.5 psf	342.4 psf	338.9 psf	335.6 psf	332.5 psf	406.3 psf	401.0 psf	396.1 psf	391.4 psf	117.2 psf	117.6 psf	117.9 psf	118.2 psf

Maximum Bearing Pressure = 406 psf
Allowable Bearing Pressure = 1500 psf

Use a 143in long x 35in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Seismic Design

Overturning Check

M_O =	3074.5 ft-lbs
Resisting Force Required =	2108.26 lbs
S.F. =	1.67
Weight Required =	3513.76 lbs
Minimum Width =	35 in in
Weight Provided =	7559.64 lbs

A minimum 143in long x 35in wide x 18in tall ballast foundation is required to resist overturning.



Bearing Pressure

ASD LC	1.238D + 0.875E			1.1785D + 0.65625E + 0.75S			0.362D + 0.875E		
Width	35 in			35 in			35 in		
Support	Outer	Inner	Outer	Outer	Inner	Outer	Outer	Inner	Outer
F_Y	324 lbs	710 lbs	230 lbs	952 lbs	2602 lbs	878 lbs	128 lbs	208 lbs	34 lbs
F_V	239 lbs	233 lbs	244 lbs	174 lbs	170 lbs	192 lbs	240 lbs	234 lbs	241 lbs
P_{total}	9683 lbs	10069 lbs	9589 lbs	9861 lbs	11511 lbs	9788 lbs	2864 lbs	2944 lbs	2771 lbs
M	963 lbs-ft	948 lbs-ft	979 lbs-ft	720 lbs-ft	719 lbs-ft	776 lbs-ft	961 lbs-ft	945 lbs-ft	967 lbs-ft
e	0.10 ft	0.09 ft	0.10 ft	0.07 ft	0.06 ft	0.08 ft	0.34 ft	0.32 ft	0.35 ft
L/6	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft
f_{min}	221.6 psf	233.6 psf	218.0 psf	241.1 psf	288.6 psf	235.7 psf	25.5 psf	28.8 psf	22.5 psf
f_{max}	335.6 psf	345.8 psf	333.8 psf	326.3 psf	373.8 psf	327.5 psf	139.3 psf	140.6 psf	137.0 psf

Maximum Bearing Pressure = 374 psf
Allowable Bearing Pressure = 1500 psf

Use a 143in long x 35in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Foundation Requirements: 143in long x 24in wide x 18in tall ballast foundation and fiber reinforcing with (2) #5 rebar.

5.3 Foundation Anchors

Threaded rods are anchored to the the ballast foundations using the Simpson AT-XP epoxy solution. LRFD load results are compared to the allowable strengths of the epoxy solution. Please see the supplementary calculations provided by the Simpson Anchor Designer software.

6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of 80mm mounting clamps. The reliability of calculations is uncertain due to limited standards, therefore the strength of the clamp fasteners has been evaluated by load testing.

Fastening of Modules to Purlins

Maximum Uplifting Force	=	0.495 k
Allowable Uplift	=	1.214 k
Utilization	=	41%



Fastening of Purlins to Girders

Maximum Uplifting Force	=	1.700 k
Allowable Uplift	=	4.357 k
Utilization	=	39%



6.2 Strut Connections

The aluminum struts connect the aluminum girder ends to custom brackets with mounting holes. Single M12 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Front Strut

Maximum Axial Load	=	3.060 k
M12 Bolt Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	41%

Rear Strut

Maximum Axial Load	=	3.309 k
M12 Bolt Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	45%

Diagonal Strut

Maximum Axial Load	=	1.771 k
M12 Bolt Shear Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	24%

Bolt and bearing capacities are accounting for double shear. (ASCE 8-02, Eq. 5.3.4-1)



Struts under compression are shown to demonstrate the load transfer from the girder. Single M12 bolts are located at each end of the strut and are subjected to double shear.

7. SEISMIC DESIGN

7.1 Seismic Drift

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx}	=	56.48 in
Allowable Story Drift for All Other Structures, Δ	= {	$0.020h_{sx}$
		1.130 in
Max Drift, Δ_{MAX}	=	0.883 in

0.883 ≤ 1.13, OK.

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **S1.5**

Strong Axis:		Weak Axis:	
3.4.14		**3.4.14**	
L_b =	117 in	L_b =	117
J =	0.432	J =	0.432
	323.677		205.839
$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$		$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$	
S1 =	0.51461	S1 =	0.51461
$S2 = \left(\frac{C_c}{1.6}\right)^2$		$S2 = \left(\frac{C_c}{1.6}\right)^2$	
S2 =	1701.56	S2 =	1701.56
φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]	φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L=	27.5 ksi	φF_L=	28.7
3.4.16		**3.4.16**	
b/t =	32.195	b/t =	37.0588
$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$		$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$	
S1 =	12.2	S1 =	12.2
$S2 = \frac{k_1 Bp}{1.6Dp}$		$S2 = \frac{k_1 Bp}{1.6Dp}$	
S2 =	46.7	S2 =	46.7
φF_L=	φb[Bp-1.6Dp*b/t]	φF_L=	φb[Bp-1.6Dp*b/t]
φF_L=	25.1 ksi	φF_L=	23.1 ksi
3.4.16.1	Not Used	**3.4.16.1**	
Rb/t =		N/A for Weak Direction	
$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$			
S1 =	1.1		
$S2 = C_t$			
S2 =	141.0		
φF_L=	1.17φyFcy		
φF_L=	38.9 ksi		
3.4.18		**3.4.18**	
h/t =	37.0588	h/t =	32.195
$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$		$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$	
S1 =	36.9	S1 =	36.9
m =	0.65	m =	0.65
C_0 =	40.985	C_0 =	45.5
Cc =	41.015	Cc =	45.5
$S2 = \frac{k_1 Bbr}{mDbr}$		$S2 = \frac{k_1 Bbr}{mDbr}$	
S2 =	77.2	S2 =	77.3
φF_L=	φb[Bbr-mDbr*h/t]	φF_L=	1.3φyFcy
φF_L=	43.2 ksi	φF_L=	43.2 ksi
φF_LSt=	25.1 ksi	φF_LWk=	23.1 ksi
Ix =	897074 mm^4	Iy =	446476 mm^4
	2.155 in^4		1.073 in^4
y =	41.015 mm	x =	45.5 mm
Sx =	1.335 in^3	Sy =	0.599 in^3
M_{max}St =	2.788 k-ft	M_{max}Wk =	1.152 k-ft

Compression

3.4.9

b/t = 32.195
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 25.1 ksi

b/t = 37.0588
S1 = 12.21
S2 = 32.70
φF_L = (φck2*√(BpE))/(1.6b/t)
φF_L = 21.9 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 21.94 ksi
A = 1215.13 mm^2
1.88 in^2
P_{max} = 41.32 kips

A.2 Design of Aluminum Girders - Aluminum Design Manual, 2005 Edition

Girder = **BF0**

Strong Axis:

3.4.14

L_b = 104.56 in
J = 1.08
179.85

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.0 ksi

3.4.16

b/t = 16.2

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 31.6 ksi

Weak Axis:

3.4.14

L_b = 104.56
J = 1.08
190.335

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 28.9

3.4.16

b/t = 7.4

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φyFcy
φF_L = 33.3 ksi

3.4.16.1 Used

Rb/t = 18.1

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= φb[Bt-Dt*√(Rb/t)]

φF_L= 31.1 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 7.4

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 35.2

m = 0.68

C_0 = 41.067

Cc = 43.717

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 73.8

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 29.0 ksi

Ix = 984962 mm^4

2.366 in^4

y = 43.717 mm

Sx = 1.375 in^3

$M_{max}St$ = 3.323 k-ft

3.4.18

h/t = 16.2

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 40

Cc = 40

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 33.3 ksi

Iy = 923544 mm^4

2.219 in^4

x = 40 mm

Sy = 1.409 in^3

$M_{max}Wk$ = 3.904 k-ft

Compression

3.4.9

b/t = 16.2

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 31.6 ksi

b/t = 7.4

S1 = 12.21

S2 = 32.70

φF_L= φyFcy

φF_L= 33.3 ksi

3.4.10

Rb/t = 18.1

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L= φc[Bt-Dt*√(Rb/t)]

φF_L= 31.09 ksi

φF_L= 31.09 ksi

A = 1215.13 mm^2

1.88 in^2

P_{max} = 58.55 kips

A.3 Design of Aluminum Struts (Front) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 24.8 in

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

Weak Axis:

3.4.14

L_b = 24.8

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 0.57371

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.87952

φF_L = φcc(Bc-Dc*λ)

φF_L = 28.0279 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 28.03 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 28.85 kips

A.4 Design of Aluminum Struts (Diagonal) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 98.03 in

J = 0.942

152.985

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L = 29.4 ksi

Weak Axis:

3.4.14

L_b = 98.03

J = 0.942

152.985

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L = 29.4

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17 \frac{\theta_y}{\theta_b} Fcy}{1.6Dt} \right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

$M_{max}St$ = 1.460 k-ft

$\varphi F_L Wk$= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

$M_{max}Wk$ = 1.460 k-ft

Compression

3.4.7

λ = 2.26776

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi} \sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.89749

φF_L= (φccFcy)/(λ²)

φF_L= 6.10803 ksi

3.4.9

b/t = 24.5
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

b/t = 24.5
S1 = 12.21
S2 = 32.70
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 6.11 ksi
A = 663.99 mm^2
1.03 in^2
P_{max} = 6.29 kips

A.5 Design of Aluminum Struts (Rear) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 69.80 in
J = 0.942
108.93

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.0 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

Weak Axis:

3.4.14

L_b = 69.8
J = 0.942
108.93

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.0

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 1.61471

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.80606

φF_L= (φccFcy)/(λ²)

φF_L= 10.8205 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 10.82 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 11.14 kips

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				4		
2	Dead Load, Min	DL		-1				4		
3	Snow Load	SL						4		
4	Wind Load - Pressure	WL						4		
5	Wind Load - Suction	WL						4		
6	Seismic - Lateral	EL			.8			8		

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-9.843	-9.843	0	0
2	M14	Y	-9.843	-9.843	0	0
3	M15	Y	-9.843	-9.843	0	0
4	M16	Y	-9.843	-9.843	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-5.454	-5.454	0	0
2	M14	Y	-5.454	-5.454	0	0
3	M15	Y	-5.454	-5.454	0	0
4	M16	Y	-5.454	-5.454	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-55.176	-55.176	0	0
2	M14	Y	-55.176	-55.176	0	0
3	M15	Y	-55.176	-55.176	0	0
4	M16	Y	-55.176	-55.176	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	-40.939	-40.939	0	0
2	M14	y	-40.939	-40.939	0	0
3	M15	y	-63.27	-63.27	0	0
4	M16	y	-63.27	-63.27	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	93.044	93.044	0	0
2	M14	y	70.714	70.714	0	0
3	M15	y	37.218	37.218	0	0
4	M16	y	37.218	37.218	0	0

Member Distributed Loads (BLC 6 : Seismic - Lateral)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Z	7.874	7.874	0	0
2	M14	Z	7.874	7.874	0	0
3	M15	Z	7.874	7.874	0	0
4	M16	Z	7.874	7.874	0	0
5	M13	Z	0	0	0	0
6	M14	Z	0	0	0	0
7	M15	Z	0	0	0	0
8	M16	Z	0	0	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.8W	Yes	Y		1	1.2	3	1.6	4	.8														
2	LRFD 1.2D + 1.6W + 0.5S	Yes	Y		1	1.2	3	.5	4	1.6														
3	LRFD 0.9D + 1.6W	Yes	Y		2	.9					5	1.6												
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3												
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3												
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25												
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25												
8																								
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																
10	ASD 1.0D + 1.0W	Yes	Y		1	1			4	1														
11	ASD 1.0D + 0.75L + 0.75W + 0....	Yes	Y		1	1	3	.75	4	.75														
12	ASD 0.6D + 1.0W	Yes	Y		2	.6					5	1												
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875												
14	LATERAL - ASD 1.1785D + 0.65...	Yes	Y		1	1.1...	3	.75			6	.656												
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875												

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N8	max	469.466	2	1070.021	1	.948	1	.004	1	0	1	0	1
2		min	-616.534	3	-1091.847	3	-54.629	5	-.295	4	0	1	0	1
3	N7	max	.043	9	1154.552	1	-.831	12	-.002	12	0	1	0	1
4		min	-.129	2	-61.371	3	-311.832	4	-.629	4	0	1	0	1
5	N15	max	0	15	3060.194	1	0	9	0	9	0	1	0	1
6		min	-1.516	2	-282.572	3	-293.68	4	-.604	4	0	1	0	1
7	N16	max	1810.976	2	3549.05	1	0	9	0	1	0	1	0	1
8		min	-1907.451	3	-3535.169	3	-54.337	5	-.298	4	0	1	0	1
9	N23	max	.053	14	1154.552	1	16.516	1	.033	1	0	1	0	1
10		min	-.129	2	-61.371	3	-300.393	5	-.611	4	0	1	0	1
11	N24	max	469.466	2	1070.021	1	-.06	12	0	12	0	1	0	1
12		min	-616.534	3	-1091.847	3	-55.453	5	-.298	4	0	1	0	1
13	Totals:	max	2748.135	2	11058.389	1	0	9						
14		min	-3140.752	3	-6124.178	3	-1062.256	5						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M13	1	max	99.684	1	450.118	1	-8.891	12	0	15	.28	1	0	4
2			min	5.193	12	-524.293	3	-200.313	1	-.014	1	.015	12	0	3
3		2	max	99.684	1	314.59	1	-6.98	12	0	15	.138	4	.484	3
4			min	5.193	12	-369.166	3	-153.661	1	-.014	1	.006	12	-.414	1
5		3	max	99.684	1	179.063	1	-5.068	12	0	15	.077	5	.8	3
6			min	5.193	12	-214.038	3	-107.008	1	-.014	1	-.053	1	-.682	1
7		4	max	99.684	1	43.535	1	-3.157	12	0	15	.041	5	.948	3
8			min	5.193	12	-58.91	3	-60.355	1	-.014	1	-.144	1	-.802	1
9		5	max	99.684	1	96.217	3	-1.082	10	0	15	.009	5	.927	3
10			min	5.193	12	-91.992	1	-32.062	4	-.014	1	-.184	1	-.776	1
11		6	max	99.684	1	251.345	3	32.95	1	0	15	-.008	12	.739	3
12			min	2.997	15	-227.52	1	-25.395	5	-.014	1	-.174	1	-.603	1
13		7	max	99.684	1	406.473	3	79.603	1	0	15	-.006	12	.383	3
14			min	-8.066	5	-363.047	1	-22.486	5	-.014	1	-.113	1	-.283	1
15		8	max	99.684	1	561.6	3	126.256	1	0	15	.001	2	.184	1
16			min	-20.85	5	-498.575	1	-19.576	5	-.014	1	-.071	4	-.141	3
17		9	max	99.684	1	716.728	3	172.908	1	0	15	.161	1	.797	1
18			min	-33.633	5	-634.102	1	-16.667	5	-.014	1	-.088	5	-.834	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
19		10	max	99.684	1	769.63	1	-8.312	12	.014	1	.373	1	1.558	1
20			min	5.193	12	-871.856	3	-219.561	1	-.001	3	.012	12	-1.694	3
21		11	max	99.684	1	634.102	1	-6.4	12	.014	1	.161	1	.797	1
22			min	5.193	12	-716.728	3	-172.908	1	0	15	.004	12	-.834	3
23		12	max	99.684	1	498.575	1	-4.489	12	.014	1	.069	4	.184	1
24			min	5.193	12	-561.6	3	-126.256	1	0	15	-.003	3	-.141	3
25		13	max	99.684	1	363.047	1	-2.577	12	.014	1	.032	5	.383	3
26			min	5.193	12	-406.473	3	-79.603	1	0	15	-.113	1	-.283	1
27		14	max	99.684	1	227.52	1	-.666	12	.014	1	0	15	.739	3
28			min	4.992	15	-251.345	3	-37.225	4	0	15	-.174	1	-.603	1
29		15	max	99.684	1	91.992	1	13.702	1	.014	1	-.007	12	.927	3
30			min	-5.211	5	-96.217	3	-26.546	5	0	15	-.184	1	-.776	1
31		16	max	99.684	1	58.91	3	60.355	1	.014	1	-.005	12	.948	3
32			min	-17.995	5	-43.535	1	-23.637	5	0	15	-.144	1	-.802	1
33		17	max	99.684	1	214.038	3	107.008	1	.014	1	0	12	.8	3
34			min	-30.779	5	-179.063	1	-20.727	5	0	15	-.097	4	-.682	1
35		18	max	99.684	1	369.166	3	153.661	1	.014	1	.088	1	.484	3
36			min	-43.563	5	-314.59	1	-17.818	5	0	15	-.104	5	-.414	1
37		19	max	99.684	1	524.293	3	200.313	1	.014	1	.28	1	0	1
38			min	-56.347	5	-450.118	1	-14.909	5	0	15	-.122	5	0	3
39	M14	1	max	61.485	4	491.262	1	-9.189	12	.008	3	.327	1	0	4
40			min	2.652	12	-411.081	3	-207.622	1	-.013	1	.017	12	0	3
41		2	max	54.932	1	355.735	1	-7.277	12	.008	3	.203	4	.382	3
42			min	2.652	12	-294.658	3	-160.969	1	-.013	1	.008	12	-.459	1
43		3	max	54.932	1	220.207	1	-5.366	12	.008	3	.116	5	.638	3
44			min	2.652	12	-178.236	3	-114.316	1	-.013	1	-.022	1	-.771	1
45		4	max	54.932	1	84.68	1	-3.455	12	.008	3	.064	5	.768	3
46			min	2.652	12	-61.814	3	-67.663	1	-.013	1	-.12	1	-.936	1
47		5	max	54.932	1	54.609	3	-1.543	12	.008	3	.014	5	.772	3
48			min	-1.594	5	-50.848	1	-49.655	4	-.013	1	-.168	1	-.954	1
49		6	max	54.932	1	171.031	3	25.642	1	.008	3	-.007	12	.65	3
50			min	-14.378	5	-186.375	1	-40.977	5	-.013	1	-.166	1	-.826	1
51		7	max	54.932	1	287.454	3	72.295	1	.008	3	-.006	12	.402	3
52			min	-27.162	5	-321.903	1	-38.068	5	-.013	1	-.113	1	-.55	1
53		8	max	54.932	1	403.876	3	118.947	1	.008	3	0	10	.027	3
54			min	-39.946	5	-457.43	1	-35.159	5	-.013	1	-.119	4	-.128	1
55		9	max	54.932	1	520.298	3	165.6	1	.008	3	.145	1	.441	1
56			min	-52.73	5	-592.958	1	-32.249	5	-.013	1	-.151	5	-.473	3
57		10	max	83.797	4	728.485	1	-8.014	12	.013	1	.35	1	1.156	1
58			min	2.652	12	-636.721	3	-212.253	1	-.008	3	.011	12	-1.1	3
59		11	max	71.013	4	592.958	1	-6.102	12	.013	1	.204	4	.441	1
60			min	2.652	12	-520.298	3	-165.6	1	-.008	3	.003	12	-.473	3
61		12	max	58.229	4	457.43	1	-4.191	12	.013	1	.114	4	.027	3
62			min	2.652	12	-403.876	3	-118.947	1	-.008	3	-.009	1	-.128	1
63		13	max	54.932	1	321.903	1	-2.28	12	.013	1	.06	5	.402	3
64			min	2.652	12	-287.454	3	-72.295	1	-.008	3	-.113	1	-.55	1
65		14	max	54.932	1	186.375	1	-.368	12	.013	1	.011	5	.65	3
66			min	2.652	12	-171.031	3	-50.727	4	-.008	3	-.166	1	-.826	1
67		15	max	54.932	1	50.848	1	21.011	1	.013	1	-.007	12	.772	3
68			min	2.652	12	-54.609	3	-41.218	5	-.008	3	-.168	1	-.954	1
69		16	max	54.932	1	61.814	3	67.663	1	.013	1	-.004	12	.768	3
70			min	-5.016	5	-84.68	1	-38.308	5	-.008	3	-.12	1	-.936	1
71		17	max	54.932	1	178.236	3	114.316	1	.013	1	.002	3	.638	3
72			min	-17.8	5	-220.207	1	-35.399	5	-.008	3	-.126	4	-.771	1
73		18	max	54.932	1	294.658	3	160.969	1	.013	1	.127	1	.382	3
74			min	-30.584	5	-355.735	1	-32.49	5	-.008	3	-.155	5	-.459	1
75		19	max	54.932	1	411.081	3	207.622	1	.013	1	.327	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
76			min	-43.368	5	-491.262	1	-29.58	5	-.008	3	-.189	5	0	3
77	M15	1	max	97.704	5	556.533	1	-9.129	12	.014	1	.375	4	0	2
78			min	-58.854	1	-215.514	3	-207.551	1	-.007	3	.016	12	0	3
79		2	max	84.92	5	401.652	1	-7.218	12	.014	1	.257	4	.202	3
80			min	-58.854	1	-157.151	3	-160.898	1	-.007	3	.008	12	-.519	1
81		3	max	72.136	5	246.771	1	-5.306	12	.014	1	.154	5	.34	3
82			min	-58.854	1	-98.788	3	-114.245	1	-.007	3	-.022	1	-.87	1
83		4	max	59.352	5	91.89	1	-3.395	12	.014	1	.087	5	.416	3
84			min	-58.854	1	-40.426	3	-76.509	4	-.007	3	-.121	1	-1.054	1
85		5	max	46.568	5	17.937	3	-1.483	12	.014	1	.023	5	.428	3
86			min	-58.854	1	-63.685	2	-63.456	4	-.007	3	-.169	1	-1.069	1
87		6	max	33.784	5	76.3	3	25.713	1	.014	1	-.007	12	.377	3
88			min	-58.854	1	-217.872	1	-54.738	5	-.007	3	-.166	1	-.917	1
89		7	max	21	5	134.662	3	72.366	1	.014	1	-.006	12	.263	3
90			min	-58.854	1	-372.753	1	-51.829	5	-.007	3	-.122	4	-.597	1
91		8	max	8.216	5	193.025	3	119.018	1	.014	1	0	10	.085	3
92			min	-58.854	1	-527.634	1	-48.92	5	-.007	3	-.155	4	-.11	1
93		9	max	-2.968	15	251.388	3	165.671	1	.014	1	.145	1	.552	2
94			min	-58.854	1	-682.515	1	-46.011	5	-.007	3	-.201	5	-.155	3
95		10	max	-3.118	12	837.396	1	-8.074	12	.007	3	.374	4	1.369	1
96			min	-58.854	1	-309.75	3	-212.324	1	-.014	1	.011	12	-.459	3
97		11	max	-2.1	15	682.515	1	-6.162	12	.007	3	.255	4	.552	2
98			min	-58.854	1	-251.388	3	-165.671	1	-.014	1	.004	12	-.155	3
99		12	max	-3.118	12	527.634	1	-4.251	12	.007	3	.15	4	.085	3
100			min	-58.854	1	-193.025	3	-119.018	1	-.014	1	-.009	1	-.11	1
101		13	max	-3.118	12	372.753	1	-2.339	12	.007	3	.081	5	.263	3
102			min	-58.854	1	-134.662	3	-77.626	4	-.014	1	-.113	1	-.597	1
103		14	max	-3.118	12	217.872	1	-.428	12	.007	3	.017	5	.377	3
104			min	-58.854	1	-76.3	3	-64.574	4	-.014	1	-.166	1	-.917	1
105		15	max	-3.118	12	63.685	2	20.94	1	.007	3	-.007	12	.428	3
106			min	-68.394	4	-17.937	3	-54.983	5	-.014	1	-.169	1	-1.069	1
107		16	max	-3.118	12	40.426	3	67.593	1	.007	3	-.004	12	.416	3
108			min	-81.178	4	-91.89	1	-52.073	5	-.014	1	-.13	4	-1.054	1
109		17	max	-3.118	12	98.788	3	114.245	1	.007	3	.001	3	.34	3
110			min	-93.961	4	-246.771	1	-49.164	5	-.014	1	-.165	4	-.87	1
111		18	max	-3.118	12	157.151	3	160.898	1	.007	3	.127	1	.202	3
112			min	-106.745	4	-401.652	1	-46.255	5	-.014	1	-.209	5	-.519	1
113		19	max	-3.118	12	215.514	3	207.551	1	.007	3	.326	1	0	2
114			min	-119.529	4	-556.533	1	-43.346	5	-.014	1	-.257	5	0	5
115	M16	1	max	92.69	5	515.802	1	-8.714	12	.012	1	.282	1	0	2
116			min	-111.329	1	-191.93	3	-200.775	1	-.009	3	.014	12	0	3
117		2	max	79.907	5	360.921	1	-6.803	12	.012	1	.18	4	.176	3
118			min	-111.329	1	-133.568	3	-154.122	1	-.009	3	.005	12	-.475	1
119		3	max	67.123	5	206.04	1	-4.892	12	.012	1	.107	5	.289	3
120			min	-111.329	1	-75.205	3	-107.47	1	-.009	3	-.052	1	-.782	1
121		4	max	54.339	5	51.159	1	-2.98	12	.012	1	.06	5	.339	3
122			min	-111.329	1	-16.842	3	-60.817	1	-.009	3	-.143	1	-.921	1
123		5	max	41.555	5	41.52	3	-1.069	12	.012	1	.017	5	.326	3
124			min	-111.329	1	-103.722	1	-42.852	4	-.009	3	-.183	1	-.893	1
125		6	max	28.771	5	99.883	3	32.488	1	.012	1	-.007	12	.249	3
126			min	-111.329	1	-258.603	1	-35.999	5	-.009	3	-.173	1	-.697	1
127		7	max	15.987	5	158.246	3	79.141	1	.012	1	-.006	12	.109	3
128			min	-111.329	1	-413.484	1	-33.09	5	-.009	3	-.113	1	-.333	1
129		8	max	3.203	5	216.608	3	125.794	1	.012	1	0	10	.199	1
130			min	-111.329	1	-568.365	1	-30.181	5	-.009	3	-.098	4	-.094	3
131		9	max	-5.498	12	274.971	3	172.447	1	.012	1	.16	1	.899	1
132			min	-111.329	1	-723.246	1	-27.271	5	-.009	3	-.127	5	-.36	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
133		10	max	-5.498	12	878.127	1	-8.488	12	.012	1	.372	1	1.766	1
134			min	-111.329	1	-333.333	3	-219.099	1	-.009	3	.013	12	-.689	3
135		11	max	-2.586	15	723.246	1	-6.577	12	.009	3	.184	4	.899	1
136			min	-111.329	1	-274.971	3	-172.447	1	-.012	1	.005	12	-.36	3
137		12	max	-5.498	12	568.365	1	-4.666	12	.009	3	.097	4	.199	1
138			min	-111.329	1	-216.608	3	-125.794	1	-.012	1	-.002	3	-.094	3
139		13	max	-5.498	12	413.484	1	-2.754	12	.009	3	.047	5	.109	3
140			min	-111.329	1	-158.246	3	-79.141	1	-.012	1	-.113	1	-.333	1
141		14	max	-5.498	12	258.603	1	-.843	12	.009	3	.002	5	.249	3
142			min	-111.329	1	-99.883	3	-47.823	4	-.012	1	-.173	1	-.697	1
143		15	max	-5.498	12	103.722	1	14.164	1	.009	3	-.007	12	.326	3
144			min	-111.329	1	-41.52	3	-37.122	5	-.012	1	-.183	1	-.893	1
145		16	max	-5.498	12	16.842	3	60.817	1	.009	3	-.005	12	.339	3
146			min	-111.329	1	-51.159	1	-34.213	5	-.012	1	-.143	1	-.921	1
147		17	max	-5.498	12	75.205	3	107.47	1	.009	3	0	12	.289	3
148			min	-111.329	1	-206.04	1	-31.304	5	-.012	1	-.127	4	-.782	1
149		18	max	-5.498	12	133.568	3	154.122	1	.009	3	.09	1	.176	3
150			min	-119.178	4	-360.921	1	-28.394	5	-.012	1	-.146	5	-.475	1
151		19	max	-5.498	12	191.93	3	200.775	1	.009	3	.282	1	0	2
152			min	-131.962	4	-515.802	1	-25.485	5	-.012	1	-.175	5	0	5
153	M2	1	max	1044.684	1	2.066	4	.797	1	0	12	0	3	0	1
154			min	-965.206	3	.504	15	-48.423	4	0	4	0	1	0	1
155		2	max	1045.157	1	2.029	4	.797	1	0	12	0	1	0	15
156			min	-964.851	3	.495	15	-48.834	4	0	4	-.016	4	0	4
157		3	max	1045.631	1	1.991	4	.797	1	0	12	0	1	0	15
158			min	-964.496	3	.487	15	-49.245	4	0	4	-.031	4	-.001	4
159		4	max	1046.105	1	1.954	4	.797	1	0	12	0	1	0	15
160			min	-964.14	3	.478	15	-49.657	4	0	4	-.047	4	-.002	4
161		5	max	1046.579	1	1.917	4	.797	1	0	12	.001	1	0	15
162			min	-963.785	3	.469	15	-50.068	4	0	4	-.063	4	-.003	4
163		6	max	1047.052	1	1.88	4	.797	1	0	12	.001	1	0	15
164			min	-963.43	3	.461	15	-50.479	4	0	4	-.079	4	-.003	4
165		7	max	1047.526	1	1.843	4	.797	1	0	12	.002	1	0	15
166			min	-963.074	3	.452	15	-50.891	4	0	4	-.095	4	-.004	4
167		8	max	1048	1	1.806	4	.797	1	0	12	.002	1	-.001	15
168			min	-962.719	3	.443	15	-51.302	4	0	4	-.112	4	-.004	4
169		9	max	1048.474	1	1.769	4	.797	1	0	12	.002	1	-.001	15
170			min	-962.364	3	.434	15	-51.713	4	0	4	-.128	4	-.005	4
171		10	max	1048.947	1	1.732	4	.797	1	0	12	.002	1	-.001	15
172			min	-962.009	3	.426	15	-52.125	4	0	4	-.145	4	-.005	4
173		11	max	1049.421	1	1.695	4	.797	1	0	12	.003	1	-.001	15
174			min	-961.653	3	.417	15	-52.536	4	0	4	-.161	4	-.006	4
175		12	max	1049.895	1	1.658	4	.797	1	0	12	.003	1	-.002	15
176			min	-961.298	3	.408	15	-52.947	4	0	4	-.178	4	-.007	4
177		13	max	1050.368	1	1.621	4	.797	1	0	12	.003	1	-.002	15
178			min	-960.943	3	.4	15	-53.359	4	0	4	-.195	4	-.007	4
179		14	max	1050.842	1	1.584	4	.797	1	0	12	.003	1	-.002	15
180			min	-960.587	3	.391	15	-53.77	4	0	4	-.213	4	-.008	4
181		15	max	1051.316	1	1.547	4	.797	1	0	12	.004	1	-.002	15
182			min	-960.232	3	.382	15	-54.181	4	0	4	-.23	4	-.008	4
183		16	max	1051.79	1	1.51	4	.797	1	0	12	.004	1	-.002	15
184			min	-959.877	3	.373	15	-54.593	4	0	4	-.247	4	-.009	4
185		17	max	1052.263	1	1.473	4	.797	1	0	12	.004	1	-.002	15
186			min	-959.521	3	.365	15	-55.004	4	0	4	-.265	4	-.009	4
187		18	max	1052.737	1	1.436	4	.797	1	0	12	.004	1	-.002	15
188			min	-959.166	3	.356	15	-55.415	4	0	4	-.282	4	-.01	4
189		19	max	1053.211	1	1.399	4	.797	1	0	12	.005	1	-.002	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
190			min	-958.811	3	.347	15	-55.827	4	0	4	-.3	4	-.01	4
191	M3	1	max	428.76	2	9.022	4	.344	1	0	12	0	1	.01	4
192			min	-574.642	3	2.133	15	-.717	5	0	4	-.019	4	.002	15
193		2	max	428.59	2	8.15	4	.344	1	0	12	0	1	.006	4
194			min	-574.77	3	1.928	15	-.11	5	0	4	-.019	4	.001	12
195		3	max	428.419	2	7.278	4	.641	4	0	12	0	1	.002	2
196			min	-574.898	3	1.723	15	.017	12	0	4	-.019	4	0	3
197		4	max	428.249	2	6.406	4	1.248	4	0	12	0	1	0	2
198			min	-575.026	3	1.518	15	.017	12	0	4	-.018	4	-.002	3
199		5	max	428.078	2	5.534	4	1.855	4	0	12	0	1	0	15
200			min	-575.153	3	1.313	15	.017	12	0	4	-.018	4	-.004	6
201		6	max	427.908	2	4.662	4	2.462	4	0	12	.001	1	-.001	15
202			min	-575.281	3	1.108	15	.017	12	0	4	-.017	5	-.006	6
203		7	max	427.738	2	3.79	4	3.069	4	0	12	.001	1	-.002	15
204			min	-575.409	3	.903	15	.017	12	0	4	-.015	5	-.008	6
205		8	max	427.567	2	2.918	4	3.676	4	0	12	.001	1	-.002	15
206			min	-575.537	3	.698	15	.017	12	0	4	-.014	5	-.01	6
207		9	max	427.397	2	2.046	4	4.283	4	0	12	.002	1	-.003	15
208			min	-575.664	3	.493	15	.017	12	0	4	-.012	5	-.011	6
209		10	max	427.227	2	1.174	4	4.891	4	0	12	.002	1	-.003	15
210			min	-575.792	3	.288	15	.017	12	0	4	-.01	5	-.012	6
211		11	max	427.056	2	.327	2	5.498	4	0	12	.002	1	-.003	15
212			min	-575.92	3	0	3	.017	12	0	4	-.008	5	-.012	6
213		12	max	426.886	2	-.122	15	6.105	4	0	12	.002	1	-.003	15
214			min	-576.048	3	-.572	6	.017	12	0	4	-.005	5	-.012	6
215		13	max	426.716	2	-.327	15	6.712	4	0	12	.002	1	-.003	15
216			min	-576.175	3	-1.444	6	.017	12	0	4	-.002	5	-.012	6
217		14	max	426.545	2	-.531	15	7.319	4	0	12	.002	1	-.002	15
218			min	-576.303	3	-2.316	6	.017	12	0	4	0	12	-.011	6
219		15	max	426.375	2	-.736	15	7.926	4	0	12	.005	4	-.002	15
220			min	-576.431	3	-3.188	6	.017	12	0	4	0	12	-.009	6
221		16	max	426.205	2	-.941	15	8.533	4	0	12	.009	4	-.002	15
222			min	-576.559	3	-4.06	6	.017	12	0	4	0	12	-.008	6
223		17	max	426.034	2	-1.146	15	9.14	4	0	12	.014	4	-.001	15
224			min	-576.686	3	-4.932	6	.017	12	0	4	0	12	-.005	6
225		18	max	425.864	2	-1.351	15	9.748	4	0	12	.018	4	0	15
226			min	-576.814	3	-5.804	6	.017	12	0	4	0	12	-.003	6
227		19	max	425.694	2	-1.556	15	10.355	4	0	12	.023	4	0	1
228			min	-576.942	3	-6.676	6	.017	12	0	4	0	12	0	1
229	M4	1	max	1151.486	1	0	1	-.83	12	0	1	.016	4	0	1
230			min	-63.671	3	0	1	-310.836	4	0	1	0	12	0	1
231		2	max	1151.656	1	0	1	-.83	12	0	1	0	1	0	1
232			min	-63.543	3	0	1	-310.983	4	0	1	-.02	4	0	1
233		3	max	1151.826	1	0	1	-.83	12	0	1	0	12	0	1
234			min	-63.415	3	0	1	-311.131	4	0	1	-.056	4	0	1
235		4	max	1151.997	1	0	1	-.83	12	0	1	0	12	0	1
236			min	-63.287	3	0	1	-311.279	4	0	1	-.091	4	0	1
237		5	max	1152.167	1	0	1	-.83	12	0	1	0	12	0	1
238			min	-63.16	3	0	1	-311.426	4	0	1	-.127	4	0	1
239		6	max	1152.337	1	0	1	-.83	12	0	1	0	12	0	1
240			min	-63.032	3	0	1	-311.574	4	0	1	-.163	4	0	1
241		7	max	1152.508	1	0	1	-.83	12	0	1	0	12	0	1
242			min	-62.904	3	0	1	-311.722	4	0	1	-.199	4	0	1
243		8	max	1152.678	1	0	1	-.83	12	0	1	0	12	0	1
244			min	-62.776	3	0	1	-311.869	4	0	1	-.234	4	0	1
245		9	max	1152.848	1	0	1	-.83	12	0	1	0	12	0	1
246			min	-62.649	3	0	1	-312.017	4	0	1	-.27	4	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
247		10	max	1153.019	1	0	1	-.83	12	0	1	0	12	0	1
248			min	-62.521	3	0	1	-312.165	4	0	1	-.306	4	0	1
249		11	max	1153.189	1	0	1	-.83	12	0	1	0	12	0	1
250			min	-62.393	3	0	1	-312.312	4	0	1	-.342	4	0	1
251		12	max	1153.359	1	0	1	-.83	12	0	1	0	12	0	1
252			min	-62.265	3	0	1	-312.46	4	0	1	-.378	4	0	1
253		13	max	1153.53	1	0	1	-.83	12	0	1	-.001	12	0	1
254			min	-62.138	3	0	1	-312.607	4	0	1	-.414	4	0	1
255		14	max	1153.7	1	0	1	-.83	12	0	1	-.001	12	0	1
256			min	-62.01	3	0	1	-312.755	4	0	1	-.45	4	0	1
257		15	max	1153.87	1	0	1	-.83	12	0	1	-.001	12	0	1
258			min	-61.882	3	0	1	-312.903	4	0	1	-.486	4	0	1
259		16	max	1154.041	1	0	1	-.83	12	0	1	-.001	12	0	1
260			min	-61.754	3	0	1	-313.05	4	0	1	-.521	4	0	1
261		17	max	1154.211	1	0	1	-.83	12	0	1	-.001	12	0	1
262			min	-61.627	3	0	1	-313.198	4	0	1	-.557	4	0	1
263		18	max	1154.382	1	0	1	-.83	12	0	1	-.002	12	0	1
264			min	-61.499	3	0	1	-313.346	4	0	1	-.593	4	0	1
265		19	max	1154.552	1	0	1	-.83	12	0	1	-.002	12	0	1
266			min	-61.371	3	0	1	-313.493	4	0	1	-.629	4	0	1
267	M6	1	max	3300.913	1	2.2	2	0	1	0	1	0	4	0	1
268			min	-3122.048	3	.328	12	-48.981	4	0	4	0	1	0	1
269		2	max	3301.387	1	2.171	2	0	1	0	1	0	1	0	12
270			min	-3121.693	3	.314	12	-49.393	4	0	4	-.016	4	0	2
271		3	max	3301.861	1	2.142	2	0	1	0	1	0	1	0	12
272			min	-3121.337	3	.299	12	-49.804	4	0	4	-.032	4	-.001	2
273		4	max	3302.334	1	2.113	2	0	1	0	1	0	1	0	12
274			min	-3120.982	3	.285	12	-50.215	4	0	4	-.048	4	-.002	2
275		5	max	3302.808	1	2.085	2	0	1	0	1	0	1	0	12
276			min	-3120.627	3	.27	12	-50.627	4	0	4	-.064	4	-.003	2
277		6	max	3303.282	1	2.056	2	0	1	0	1	0	1	0	12
278			min	-3120.272	3	.256	12	-51.038	4	0	4	-.08	4	-.003	2
279		7	max	3303.756	1	2.027	2	0	1	0	1	0	1	0	12
280			min	-3119.916	3	.241	12	-51.449	4	0	4	-.096	4	-.004	2
281		8	max	3304.229	1	1.998	2	0	1	0	1	0	1	0	12
282			min	-3119.561	3	.227	12	-51.861	4	0	4	-.113	4	-.005	2
283		9	max	3304.703	1	1.969	2	0	1	0	1	0	1	0	12
284			min	-3119.206	3	.213	12	-52.272	4	0	4	-.13	4	-.005	2
285		10	max	3305.177	1	1.94	2	0	1	0	1	0	1	0	12
286			min	-3118.85	3	.198	12	-52.683	4	0	4	-.146	4	-.006	2
287		11	max	3305.651	1	1.911	2	0	1	0	1	0	1	0	12
288			min	-3118.495	3	.184	12	-53.095	4	0	4	-.163	4	-.007	2
289		12	max	3306.124	1	1.883	2	0	1	0	1	0	1	0	12
290			min	-3118.14	3	.169	12	-53.506	4	0	4	-.18	4	-.007	2
291		13	max	3306.598	1	1.854	2	0	1	0	1	0	1	0	12
292			min	-3117.784	3	.155	12	-53.917	4	0	4	-.198	4	-.008	2
293		14	max	3307.072	1	1.825	2	0	1	0	1	0	1	0	12
294			min	-3117.429	3	.14	12	-54.329	4	0	4	-.215	4	-.008	2
295		15	max	3307.546	1	1.796	2	0	1	0	1	0	1	-.001	12
296			min	-3117.074	3	.126	12	-54.74	4	0	4	-.232	4	-.009	2
297		16	max	3308.019	1	1.767	2	0	1	0	1	0	1	-.001	12
298			min	-3116.719	3	.112	12	-55.151	4	0	4	-.25	4	-.01	2
299		17	max	3308.493	1	1.738	2	0	1	0	1	0	1	-.001	12
300			min	-3116.363	3	.097	12	-55.563	4	0	4	-.268	4	-.01	2
301		18	max	3308.967	1	1.709	2	0	1	0	1	0	1	-.001	12
302			min	-3116.008	3	.077	3	-55.974	4	0	4	-.285	4	-.011	2
303		19	max	3309.441	1	1.68	2	0	1	0	1	0	1	-.001	12

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
304			min	-3115.653	3	.056	3	-56.385	4	0	4	-.303	4	-.011	2
305	M7	1	max	1693.454	2	9.031	6	0	1	0	1	0	1	.011	2
306			min	-1768.481	3	2.12	15	-1.025	5	0	4	-.019	4	.001	12
307		2	max	1693.284	2	8.159	6	0	1	0	1	0	1	.008	2
308			min	-1768.609	3	1.915	15	-.418	5	0	4	-.019	4	0	3
309		3	max	1693.114	2	7.287	6	.249	4	0	1	0	1	.005	2
310			min	-1768.737	3	1.71	15	0	1	0	4	-.019	4	-.003	3
311		4	max	1692.943	2	6.415	6	.856	4	0	1	0	1	.002	2
312			min	-1768.865	3	1.505	15	0	1	0	4	-.019	4	-.004	3
313		5	max	1692.773	2	5.543	6	1.464	4	0	1	0	1	0	2
314			min	-1768.993	3	1.3	15	0	1	0	4	-.019	4	-.006	3
315		6	max	1692.603	2	4.671	6	2.071	4	0	1	0	1	-.001	15
316			min	-1769.12	3	1.095	15	0	1	0	4	-.018	4	-.007	3
317		7	max	1692.432	2	3.799	6	2.678	4	0	1	0	1	-.002	15
318			min	-1769.248	3	.89	15	0	1	0	4	-.017	4	-.008	4
319		8	max	1692.262	2	2.927	6	3.285	4	0	1	0	1	-.002	15
320			min	-1769.376	3	.685	15	0	1	0	4	-.015	4	-.01	4
321		9	max	1692.092	2	2.055	6	3.892	4	0	1	0	1	-.003	15
322			min	-1769.504	3	.474	12	0	1	0	4	-.013	4	-.011	4
323		10	max	1691.921	2	1.315	2	4.499	4	0	1	0	1	-.003	15
324			min	-1769.631	3	.134	12	0	1	0	4	-.012	4	-.012	4
325		11	max	1691.751	2	.635	2	5.106	4	0	1	0	1	-.003	15
326			min	-1769.759	3	-.34	3	0	1	0	4	-.009	4	-.012	4
327		12	max	1691.581	2	-.044	2	5.713	4	0	1	0	1	-.003	15
328			min	-1769.887	3	-.849	3	0	1	0	4	-.007	4	-.012	4
329		13	max	1691.41	2	-.34	15	6.321	4	0	1	0	1	-.003	15
330			min	-1770.015	3	-1.433	4	0	1	0	4	-.004	4	-.011	4
331		14	max	1691.24	2	-.545	15	6.928	4	0	1	0	1	-.002	15
332			min	-1770.142	3	-2.305	4	0	1	0	4	0	4	-.011	4
333		15	max	1691.07	2	-.75	15	7.535	4	0	1	.003	5	-.002	15
334			min	-1770.27	3	-3.177	4	0	1	0	4	0	1	-.009	4
335		16	max	1690.899	2	-.955	15	8.142	4	0	1	.006	4	-.002	15
336			min	-1770.398	3	-4.049	4	0	1	0	4	0	1	-.008	4
337		17	max	1690.729	2	-1.16	15	8.749	4	0	1	.01	4	-.001	15
338			min	-1770.526	3	-4.921	4	0	1	0	4	0	1	-.005	4
339		18	max	1690.558	2	-1.365	15	9.356	4	0	1	.015	4	0	15
340			min	-1770.653	3	-5.793	4	0	1	0	4	0	1	-.003	4
341		19	max	1690.388	2	-1.57	15	9.963	4	0	1	.019	4	0	1
342			min	-1770.781	3	-6.665	4	0	1	0	4	0	1	0	1
343	M8	1	max	3057.127	1	0	1	0	1	0	1	.013	4	0	1
344			min	-284.872	3	0	1	-297.207	4	0	1	0	1	0	1
345		2	max	3057.298	1	0	1	0	1	0	1	0	1	0	1
346			min	-284.744	3	0	1	-297.354	4	0	1	-.021	4	0	1
347		3	max	3057.468	1	0	1	0	1	0	1	0	1	0	1
348			min	-284.616	3	0	1	-297.502	4	0	1	-.055	4	0	1
349		4	max	3057.638	1	0	1	0	1	0	1	0	1	0	1
350			min	-284.489	3	0	1	-297.649	4	0	1	-.089	4	0	1
351		5	max	3057.809	1	0	1	0	1	0	1	0	1	0	1
352			min	-284.361	3	0	1	-297.797	4	0	1	-.123	4	0	1
353		6	max	3057.979	1	0	1	0	1	0	1	0	1	0	1
354			min	-284.233	3	0	1	-297.945	4	0	1	-.157	4	0	1
355		7	max	3058.15	1	0	1	0	1	0	1	0	1	0	1
356			min	-284.105	3	0	1	-298.092	4	0	1	-.192	4	0	1
357		8	max	3058.32	1	0	1	0	1	0	1	0	1	0	1
358			min	-283.978	3	0	1	-298.24	4	0	1	-.226	4	0	1
359		9	max	3058.49	1	0	1	0	1	0	1	0	1	0	1
360			min	-283.85	3	0	1	-298.388	4	0	1	-.26	4	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
361		10	max	3058.661	1	0	1	0	1	0	1	0	1	0	1
362			min	-283.722	3	0	1	-298.535	4	0	1	-.294	4	0	1
363		11	max	3058.831	1	0	1	0	1	0	1	0	1	0	1
364			min	-283.594	3	0	1	-298.683	4	0	1	-.329	4	0	1
365		12	max	3059.001	1	0	1	0	1	0	1	0	1	0	1
366			min	-283.466	3	0	1	-298.83	4	0	1	-.363	4	0	1
367		13	max	3059.172	1	0	1	0	1	0	1	0	1	0	1
368			min	-283.339	3	0	1	-298.978	4	0	1	-.397	4	0	1
369		14	max	3059.342	1	0	1	0	1	0	1	0	1	0	1
370			min	-283.211	3	0	1	-299.126	4	0	1	-.432	4	0	1
371		15	max	3059.512	1	0	1	0	1	0	1	0	1	0	1
372			min	-283.083	3	0	1	-299.273	4	0	1	-.466	4	0	1
373		16	max	3059.683	1	0	1	0	1	0	1	0	1	0	1
374			min	-282.955	3	0	1	-299.421	4	0	1	-.5	4	0	1
375		17	max	3059.853	1	0	1	0	1	0	1	0	1	0	1
376			min	-282.828	3	0	1	-299.569	4	0	1	-.535	4	0	1
377		18	max	3060.023	1	0	1	0	1	0	1	0	1	0	1
378			min	-282.7	3	0	1	-299.716	4	0	1	-.569	4	0	1
379		19	max	3060.194	1	0	1	0	1	0	1	0	1	0	1
380			min	-282.572	3	0	1	-299.864	4	0	1	-.604	4	0	1
381	M10	1	max	1044.684	1	1.981	6	-.04	12	0	1	0	4	0	1
382			min	-965.206	3	.447	15	-48.871	4	0	5	0	3	0	1
383		2	max	1045.157	1	1.944	6	-.04	12	0	1	0	10	0	15
384			min	-964.851	3	.439	15	-49.282	4	0	5	-.016	4	0	6
385		3	max	1045.631	1	1.907	6	-.04	12	0	1	0	12	0	15
386			min	-964.496	3	.43	15	-49.694	4	0	5	-.032	4	-.001	6
387		4	max	1046.105	1	1.87	6	-.04	12	0	1	0	12	0	15
388			min	-964.14	3	.421	15	-50.105	4	0	5	-.047	4	-.002	6
389		5	max	1046.579	1	1.833	6	-.04	12	0	1	0	12	0	15
390			min	-963.785	3	.413	15	-50.516	4	0	5	-.064	4	-.002	6
391		6	max	1047.052	1	1.796	6	-.04	12	0	1	0	12	0	15
392			min	-963.43	3	.404	15	-50.928	4	0	5	-.08	4	-.003	6
393		7	max	1047.526	1	1.759	6	-.04	12	0	1	0	12	0	15
394			min	-963.074	3	.395	15	-51.339	4	0	5	-.096	4	-.004	6
395		8	max	1048	1	1.721	6	-.04	12	0	1	0	12	0	15
396			min	-962.719	3	.386	15	-51.75	4	0	5	-.113	4	-.004	6
397		9	max	1048.474	1	1.684	6	-.04	12	0	1	0	12	-.001	15
398			min	-962.364	3	.378	15	-52.162	4	0	5	-.129	4	-.005	6
399		10	max	1048.947	1	1.647	6	-.04	12	0	1	0	12	-.001	15
400			min	-962.009	3	.369	15	-52.573	4	0	5	-.146	4	-.005	6
401		11	max	1049.421	1	1.61	6	-.04	12	0	1	0	12	-.001	15
402			min	-961.653	3	.36	15	-52.984	4	0	5	-.163	4	-.006	6
403		12	max	1049.895	1	1.573	6	-.04	12	0	1	0	12	-.001	15
404			min	-961.298	3	.352	15	-53.396	4	0	5	-.18	4	-.006	6
405		13	max	1050.368	1	1.536	6	-.04	12	0	1	0	12	-.002	15
406			min	-960.943	3	.343	15	-53.807	4	0	5	-.197	4	-.007	6
407		14	max	1050.842	1	1.499	6	-.04	12	0	1	0	12	-.002	15
408			min	-960.587	3	.334	15	-54.218	4	0	5	-.214	4	-.007	6
409		15	max	1051.316	1	1.462	6	-.04	12	0	1	0	12	-.002	15
410			min	-960.232	3	.325	15	-54.63	4	0	5	-.232	4	-.008	6
411		16	max	1051.79	1	1.425	6	-.04	12	0	1	0	12	-.002	15
412			min	-959.877	3	.317	15	-55.041	4	0	5	-.249	4	-.008	6
413		17	max	1052.263	1	1.388	6	-.04	12	0	1	0	12	-.002	15
414			min	-959.521	3	.308	15	-55.452	4	0	5	-.267	4	-.009	6
415		18	max	1052.737	1	1.351	6	-.04	12	0	1	0	12	-.002	15
416			min	-959.166	3	.299	15	-55.864	4	0	5	-.285	4	-.009	6
417		19	max	1053.211	1	1.314	6	-.04	12	0	1	0	12	-.002	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
418			min	-958.811	3	.291	15	-56.275	4	0	5	-.303	4	-.009	6
419	M11	1	max	428.76	2	8.964	6	-.017	12	0	1	0	12	.009	6
420			min	-574.642	3	2.095	15	-.766	4	0	4	-.019	4	.002	15
421		2	max	428.59	2	8.092	6	-.017	12	0	1	0	12	.005	6
422			min	-574.77	3	1.89	15	-.344	1	0	4	-.019	4	.001	15
423		3	max	428.419	2	7.22	6	.455	5	0	1	0	12	.002	2
424			min	-574.898	3	1.685	15	-.344	1	0	4	-.019	4	0	3
425		4	max	428.249	2	6.348	6	1.062	5	0	1	0	12	0	2
426			min	-575.026	3	1.48	15	-.344	1	0	4	-.019	4	-.002	3
427		5	max	428.078	2	5.476	6	1.669	5	0	1	0	12	-.001	15
428			min	-575.153	3	1.275	15	-.344	1	0	4	-.018	4	-.004	4
429		6	max	427.908	2	4.604	6	2.277	5	0	1	0	12	-.002	15
430			min	-575.281	3	1.07	15	-.344	1	0	4	-.017	4	-.007	4
431		7	max	427.738	2	3.732	6	2.884	5	0	1	0	12	-.002	15
432			min	-575.409	3	.865	15	-.344	1	0	4	-.016	4	-.009	4
433		8	max	427.567	2	2.86	6	3.491	5	0	1	0	12	-.002	15
434			min	-575.537	3	.66	15	-.344	1	0	4	-.014	4	-.01	4
435		9	max	427.397	2	1.988	6	4.098	5	0	1	0	12	-.003	15
436			min	-575.664	3	.455	15	-.344	1	0	4	-.013	4	-.011	4
437		10	max	427.227	2	1.116	6	4.705	5	0	1	0	12	-.003	15
438			min	-575.792	3	.25	15	-.344	1	0	4	-.011	4	-.012	4
439		11	max	427.056	2	.327	2	5.312	5	0	1	0	12	-.003	15
440			min	-575.92	3	0	3	-.344	1	0	4	-.008	4	-.012	4
441		12	max	426.886	2	-.16	15	5.919	5	0	1	0	12	-.003	15
442			min	-576.048	3	-.629	4	-.344	1	0	4	-.006	4	-.012	4
443		13	max	426.716	2	-.365	15	6.526	5	0	1	0	12	-.003	15
444			min	-576.175	3	-1.501	4	-.344	1	0	4	-.003	4	-.012	4
445		14	max	426.545	2	-.57	15	7.133	5	0	1	.001	5	-.003	15
446			min	-576.303	3	-2.373	4	-.344	1	0	4	-.002	1	-.011	4
447		15	max	426.375	2	-.775	15	7.741	5	0	1	.005	5	-.002	15
448			min	-576.431	3	-3.245	4	-.344	1	0	4	-.003	1	-.009	4
449		16	max	426.205	2	-.98	15	8.348	5	0	1	.008	5	-.002	15
450			min	-576.559	3	-4.117	4	-.344	1	0	4	-.003	1	-.008	4
451		17	max	426.034	2	-1.185	15	8.955	5	0	1	.012	5	-.001	15
452			min	-576.686	3	-4.989	4	-.344	1	0	4	-.003	1	-.006	4
453		18	max	425.864	2	-1.39	15	9.562	5	0	1	.017	5	0	15
454			min	-576.814	3	-5.861	4	-.344	1	0	4	-.003	1	-.003	4
455		19	max	425.694	2	-1.595	15	10.169	5	0	1	.021	5	0	1
456			min	-576.942	3	-6.733	4	-.344	1	0	4	-.003	1	0	1
457	M12	1	max	1151.486	1	0	1	17.078	1	0	1	.015	5	0	1
458			min	-63.671	3	0	1	-301.173	4	0	1	-.002	1	0	1
459		2	max	1151.656	1	0	1	17.078	1	0	1	0	12	0	1
460			min	-63.543	3	0	1	-301.32	4	0	1	-.02	4	0	1
461		3	max	1151.826	1	0	1	17.078	1	0	1	.002	1	0	1
462			min	-63.415	3	0	1	-301.468	4	0	1	-.055	4	0	1
463		4	max	1151.997	1	0	1	17.078	1	0	1	.004	1	0	1
464			min	-63.287	3	0	1	-301.616	4	0	1	-.089	4	0	1
465		5	max	1152.167	1	0	1	17.078	1	0	1	.006	1	0	1
466			min	-63.16	3	0	1	-301.763	4	0	1	-.124	4	0	1
467		6	max	1152.337	1	0	1	17.078	1	0	1	.008	1	0	1
468			min	-63.032	3	0	1	-301.911	4	0	1	-.159	4	0	1
469		7	max	1152.508	1	0	1	17.078	1	0	1	.01	1	0	1
470			min	-62.904	3	0	1	-302.059	4	0	1	-.193	4	0	1
471		8	max	1152.678	1	0	1	17.078	1	0	1	.012	1	0	1
472			min	-62.776	3	0	1	-302.206	4	0	1	-.228	4	0	1
473		9	max	1152.848	1	0	1	17.078	1	0	1	.013	1	0	1
474			min	-62.649	3	0	1	-302.354	4	0	1	-.263	4	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
475		10	max	1153.019	1	0	1	17.078	1	0	1	.015	1	0	1
476			min	-62.521	3	0	1	-302.502	4	0	1	-.297	4	0	1
477		11	max	1153.189	1	0	1	17.078	1	0	1	.017	1	0	1
478			min	-62.393	3	0	1	-302.649	4	0	1	-.332	4	0	1
479		12	max	1153.359	1	0	1	17.078	1	0	1	.019	1	0	1
480			min	-62.265	3	0	1	-302.797	4	0	1	-.367	4	0	1
481		13	max	1153.53	1	0	1	17.078	1	0	1	.021	1	0	1
482			min	-62.138	3	0	1	-302.944	4	0	1	-.402	4	0	1
483		14	max	1153.7	1	0	1	17.078	1	0	1	.023	1	0	1
484			min	-62.01	3	0	1	-303.092	4	0	1	-.436	4	0	1
485		15	max	1153.87	1	0	1	17.078	1	0	1	.025	1	0	1
486			min	-61.882	3	0	1	-303.24	4	0	1	-.471	4	0	1
487		16	max	1154.041	1	0	1	17.078	1	0	1	.027	1	0	1
488			min	-61.754	3	0	1	-303.387	4	0	1	-.506	4	0	1
489		17	max	1154.211	1	0	1	17.078	1	0	1	.029	1	0	1
490			min	-61.627	3	0	1	-303.535	4	0	1	-.541	4	0	1
491		18	max	1154.382	1	0	1	17.078	1	0	1	.031	1	0	1
492			min	-61.499	3	0	1	-303.683	4	0	1	-.576	4	0	1
493		19	max	1154.552	1	0	1	17.078	1	0	1	.033	1	0	1
494			min	-61.371	3	0	1	-303.83	4	0	1	-.611	4	0	1
495	M1	1	max	200.32	1	524.262	3	56.292	5	0	1	.28	1	0	15
496			min	-14.909	5	-447.795	1	-99.494	1	0	3	-.122	5	-.014	1
497		2	max	201.032	1	523.116	3	57.752	5	0	1	.218	1	.264	1
498			min	-14.577	5	-449.322	1	-99.494	1	0	3	-.087	5	-.326	3
499		3	max	369.174	3	516.795	1	12.304	5	0	3	.156	1	.533	1
500			min	-240.094	2	-377.943	3	-99.025	1	0	1	-.051	5	-.641	3
501		4	max	369.708	3	515.268	1	13.764	5	0	3	.095	1	.213	1
502			min	-239.382	2	-379.089	3	-99.025	1	0	1	-.043	5	-.406	3
503		5	max	370.242	3	513.741	1	15.224	5	0	3	.033	1	-.005	15
504			min	-238.67	2	-380.234	3	-99.025	1	0	1	-.034	5	-.17	3
505		6	max	370.776	3	512.214	1	16.684	5	0	3	-.001	12	.066	3
506			min	-237.958	2	-381.379	3	-99.025	1	0	1	-.03	4	-.425	1
507		7	max	371.31	3	510.687	1	18.144	5	0	3	-.005	12	.303	3
508			min	-237.246	2	-382.524	3	-99.025	1	0	1	-.09	1	-.742	1
509		8	max	371.844	3	509.161	1	19.604	5	0	3	0	15	.541	3
510			min	-236.534	2	-383.669	3	-99.025	1	0	1	-.151	1	-1.059	1
511		9	max	386.226	3	33.662	2	64.241	5	0	9	.094	1	.634	3
512			min	-152.506	2	.459	15	-154.016	1	0	3	-.161	5	-1.206	1
513		10	max	386.76	3	32.136	2	65.701	5	0	9	0	12	.617	3
514			min	-151.794	2	-.005	5	-154.016	1	0	3	-.122	4	-1.217	1
515		11	max	387.294	3	30.609	2	67.161	5	0	9	-.005	12	.6	3
516			min	-151.082	2	-1.885	4	-154.016	1	0	3	-.101	4	-1.228	1
517		12	max	401.583	3	243.239	3	173.923	5	0	1	.148	1	.523	3
518			min	-102.931	5	-545.667	1	-95.239	1	0	3	-.269	5	-1.084	1
519		13	max	402.117	3	242.094	3	175.383	5	0	1	.089	1	.373	3
520			min	-102.599	5	-547.194	1	-95.239	1	0	3	-.16	5	-.745	1
521		14	max	402.651	3	240.948	3	176.843	5	0	1	.03	1	.223	3
522			min	-102.266	5	-548.721	1	-95.239	1	0	3	-.051	5	-.405	1
523		15	max	403.185	3	239.803	3	178.304	5	0	1	.059	5	.073	3
524			min	-101.934	5	-550.248	1	-95.239	1	0	3	-.029	1	-.064	1
525		16	max	403.719	3	238.658	3	179.764	5	0	1	.17	5	.285	2
526			min	-101.602	5	-551.775	1	-95.239	1	0	3	-.088	1	-.075	3
527		17	max	404.253	3	237.513	3	181.224	5	0	1	.282	5	.621	1
528			min	-101.27	5	-553.302	1	-95.239	1	0	3	-.147	1	-.223	3
529		18	max	25.152	5	519.522	1	-5.498	12	0	5	.242	5	.31	1
530			min	-201.482	1	-190.862	3	-133.528	4	0	2	-.213	1	-.109	3
531		19	max	25.484	5	517.995	1	-5.498	12	0	5	.175	5	.009	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
532			min	-200.77	1	-192.008	3	-132.068	4	0	2	-.282	1	-.012	1
533	M5	1	max	439.109	1	1743.644	3	105.219	5	0	1	0	1	.028	1
534			min	16.624	12	-1527.516	1	0	1	0	4	-.262	4	0	15
535		2	max	439.821	1	1742.499	3	106.679	5	0	1	0	1	.977	1
536			min	16.98	12	-1529.043	1	0	1	0	4	-.197	4	-1.079	3
537		3	max	1169.842	3	1503.814	1	65.978	4	0	4	0	1	1.893	1
538			min	-837.15	2	-1182.903	3	0	1	0	1	-.131	4	-2.128	3
539		4	max	1170.376	3	1502.287	1	67.438	4	0	4	0	1	.96	1
540			min	-836.438	2	-1184.048	3	0	1	0	1	-.09	4	-1.394	3
541		5	max	1170.91	3	1500.76	1	68.898	4	0	4	0	1	.033	9
542			min	-835.726	2	-1185.194	3	0	1	0	1	-.047	4	-.659	3
543		6	max	1171.444	3	1499.233	1	70.358	4	0	4	0	1	.077	3
544			min	-835.014	2	-1186.339	3	0	1	0	1	-.004	5	-.903	1
545		7	max	1171.978	3	1497.706	1	71.819	4	0	4	.04	4	.814	3
546			min	-834.302	2	-1187.484	3	0	1	0	1	0	1	-1.833	1
547		8	max	1172.512	3	1496.179	1	73.279	4	0	4	.085	4	1.551	3
548			min	-833.59	2	-1188.629	3	0	1	0	1	0	1	-2.762	1
549		9	max	1196.957	3	111.836	2	212.688	4	0	1	0	1	1.792	3
550			min	-659.94	2	.465	15	0	1	0	1	-.24	4	-3.131	1
551		10	max	1197.491	3	110.309	2	214.149	4	0	1	0	1	1.729	3
552			min	-659.228	2	.004	15	0	1	0	1	-.107	4	-3.169	1
553		11	max	1198.025	3	108.782	2	215.609	4	0	1	.026	4	1.667	3
554			min	-658.516	2	-1.57	6	0	1	0	1	0	1	-3.207	1
555		12	max	1222.659	3	740.664	3	242.948	4	0	1	0	1	1.459	3
556			min	-484.879	2	-1619.007	1	0	1	0	4	-.387	4	-2.853	1
557		13	max	1223.193	3	739.518	3	244.408	4	0	1	0	1	1	3
558			min	-484.167	2	-1620.534	1	0	1	0	4	-.236	4	-1.848	1
559		14	max	1223.727	3	738.373	3	245.869	4	0	1	0	1	.541	3
560			min	-483.455	2	-1622.061	1	0	1	0	4	-.084	4	-.842	1
561		15	max	1224.261	3	737.228	3	247.329	4	0	1	.069	4	.223	2
562			min	-482.743	2	-1623.588	1	0	1	0	4	0	1	0	13
563		16	max	1224.795	3	736.083	3	248.789	4	0	1	.223	4	1.174	1
564			min	-482.031	2	-1625.115	1	0	1	0	4	0	1	-.374	3
565		17	max	1225.329	3	734.938	3	250.249	4	0	1	.378	4	2.183	1
566			min	-481.319	2	-1626.642	1	0	1	0	4	0	1	-.83	3
567		18	max	-17.332	12	1768.656	1	0	1	0	4	.382	4	1.122	1
568			min	-438.921	1	-665.933	3	-32.555	5	0	1	0	1	-.433	3
569		19	max	-16.976	12	1767.129	1	0	1	0	4	.363	4	.024	1
570			min	-438.209	1	-667.078	3	-31.095	5	0	1	0	1	-.019	3
571	M9	1	max	200.32	1	524.262	3	99.494	1	0	3	-.015	12	0	15
572			min	8.891	12	-447.795	1	5.193	12	0	4	-.28	1	-.014	1
573		2	max	201.032	1	523.116	3	99.494	1	0	3	-.011	12	.264	1
574			min	9.247	12	-449.322	1	5.193	12	0	4	-.218	1	-.326	3
575		3	max	369.174	3	516.795	1	99.025	1	0	1	-.008	12	.533	1
576			min	-240.094	2	-377.943	3	5.152	12	0	3	-.156	1	-.641	3
577		4	max	369.708	3	515.268	1	99.025	1	0	1	-.005	12	.213	1
578			min	-239.382	2	-379.089	3	5.152	12	0	3	-.095	1	-.406	3
579		5	max	370.242	3	513.741	1	99.025	1	0	1	-.002	12	-.005	15
580			min	-238.67	2	-380.234	3	5.152	12	0	3	-.046	4	-.17	3
581		6	max	370.776	3	512.214	1	99.025	1	0	1	.028	1	.066	3
582			min	-237.958	2	-381.379	3	5.152	12	0	3	-.02	5	-.425	1
583		7	max	371.31	3	510.687	1	99.025	1	0	1	.09	1	.303	3
584			min	-237.246	2	-382.524	3	5.152	12	0	3	-.002	5	-.742	1
585		8	max	371.844	3	509.161	1	99.025	1	0	1	.151	1	.541	3
586			min	-236.534	2	-383.669	3	5.152	12	0	3	.008	12	-1.059	1
587		9	max	386.226	3	33.662	2	154.016	1	0	3	-.005	12	.634	3
588			min	-152.506	2	.473	15	7.799	12	0	9	-.196	4	-1.206	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
589		10	max	386.76	3	32.136	2	154.016	1	0	3	.002	1	.617	3
590			min	-151.794	2	.012	15	7.799	12	0	9	-.121	4	-1.217	1
591		11	max	387.294	3	30.609	2	154.016	1	0	3	.097	1	.6	3
592			min	-151.082	2	-1.771	6	7.799	12	0	9	-.068	5	-1.228	1
593		12	max	401.583	3	243.239	3	210.052	4	0	3	-.007	12	.523	3
594			min	-89.473	10	-545.667	1	4.685	12	0	1	-.324	4	-1.084	1
595		13	max	402.117	3	242.094	3	211.512	4	0	3	-.004	12	.373	3
596			min	-88.88	10	-547.194	1	4.685	12	0	1	-.193	4	-.745	1
597		14	max	402.651	3	240.948	3	212.972	4	0	3	-.002	12	.223	3
598			min	-88.287	10	-548.721	1	4.685	12	0	1	-.062	4	-.405	1
599		15	max	403.185	3	239.803	3	214.433	4	0	3	.071	4	.073	3
600			min	-87.693	10	-550.248	1	4.685	12	0	1	.001	12	-.064	1
601		16	max	403.719	3	238.658	3	215.893	4	0	3	.205	4	.285	2
602			min	-87.1	10	-551.775	1	4.685	12	0	1	.004	12	-.075	3
603		17	max	404.253	3	237.513	3	217.353	4	0	3	.339	4	.621	1
604			min	-86.507	10	-553.302	1	4.685	12	0	1	.007	12	-.223	3
605		18	max	-9.071	12	519.522	1	111.508	1	0	2	.32	4	.31	1
606			min	-201.482	1	-190.862	3	-94.423	5	0	3	.01	12	-.109	3
607		19	max	-8.715	12	517.995	1	111.508	1	0	2	.282	1	.009	3
608			min	-200.77	1	-192.008	3	-92.963	5	0	3	.014	12	-.012	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M13	1	max	0	1	.175	1	.007	3	1.176e-2	1	NC	1	NC	1
2			min	-.917	4	-.023	3	-.003	2	-1.506e-3	3	NC	1	NC	1
3		2	max	0	1	.209	3	.046	1	1.31e-2	1	NC	5	NC	2
4			min	-.917	4	-.004	9	-.025	5	-1.379e-3	3	1008.321	3	5259.569	1
5		3	max	0	1	.397	3	.108	1	1.444e-2	1	NC	5	NC	3
6			min	-.917	4	-.128	1	-.031	5	-1.252e-3	3	556.651	3	2203.377	1
7		4	max	0	1	.512	3	.16	1	1.578e-2	1	NC	5	NC	3
8			min	-.917	4	-.199	1	-.023	5	-1.126e-3	3	436.986	3	1474.398	1
9		5	max	0	1	.541	3	.187	1	1.711e-2	1	NC	5	NC	3
10			min	-.917	4	-.196	1	-.007	5	-9.994e-4	3	415.155	3	1264.52	1
11		6	max	0	1	.484	3	.179	1	1.845e-2	1	NC	5	NC	3
12			min	-.918	4	-.122	1	.007	15	-8.729e-4	3	461.785	3	1316.687	1
13		7	max	0	1	.359	3	.14	1	1.979e-2	1	NC	5	NC	3
14			min	-.918	4	-.008	9	.008	10	-7.463e-4	3	612.129	3	1687.52	1
15		8	max	0	1	.2	3	.081	1	2.112e-2	1	NC	1	NC	3
16			min	-.918	4	.005	15	0	10	-6.198e-4	3	1047.172	3	2950.906	1
17		9	max	0	1	.297	1	.031	4	2.246e-2	1	NC	4	NC	1
18			min	-.918	4	.009	15	-.007	10	-4.932e-4	3	1917.399	1	7408.75	4
19		10	max	0	1	.358	1	.022	3	2.38e-2	1	NC	3	NC	1
20			min	-.918	4	-.009	3	-.015	2	-3.667e-4	3	1281.218	1	NC	1
21		11	max	0	12	.297	1	.024	3	2.246e-2	1	NC	4	NC	1
22			min	-.918	4	.009	15	-.02	5	-4.932e-4	3	1917.399	1	NC	1
23		12	max	0	12	.2	3	.081	1	2.112e-2	1	NC	1	NC	3
24			min	-.918	4	.005	15	-.02	5	-6.198e-4	3	1047.172	3	2950.906	1
25		13	max	0	12	.359	3	.14	1	1.979e-2	1	NC	5	NC	3
26			min	-.918	4	-.008	9	-.007	5	-7.463e-4	3	612.129	3	1687.52	1
27		14	max	0	12	.484	3	.179	1	1.845e-2	1	NC	5	NC	3
28			min	-.918	4	-.122	1	.008	15	-8.729e-4	3	461.785	3	1316.687	1
29		15	max	0	12	.541	3	.187	1	1.711e-2	1	NC	5	NC	3
30			min	-.918	4	-.196	1	.015	10	-9.994e-4	3	415.155	3	1264.52	1
31		16	max	0	12	.512	3	.16	1	1.578e-2	1	NC	5	NC	3
32			min	-.918	4	-.199	1	.013	10	-1.126e-3	3	436.986	3	1474.398	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
33		17	max	0	12	.397	3	.108	1	1.444e-2	1	NC	5	NC	3
34			min	-.918	4	-.128	1	.008	10	-1.252e-3	3	556.651	3	2203.377	1
35		18	max	0	12	.209	3	.046	1	1.31e-2	1	NC	5	NC	2
36			min	-.918	4	-.004	9	.002	10	-1.379e-3	3	1008.321	3	5259.569	1
37		19	max	0	12	.175	1	.007	3	1.176e-2	1	NC	1	NC	1
38			min	-.918	4	-.023	3	-.003	2	-1.506e-3	3	NC	1	NC	1
39	M14	1	max	0	1	.258	3	.007	3	7.146e-3	1	NC	1	NC	1
40			min	-.674	4	-.547	1	-.003	2	-4.005e-3	3	NC	1	NC	1
41		2	max	0	1	.504	3	.031	1	8.414e-3	1	NC	5	NC	2
42			min	-.674	4	-.885	1	-.038	5	-4.807e-3	3	692.317	1	6470.388	5
43		3	max	0	1	.715	3	.084	1	9.683e-3	1	NC	15	NC	3
44			min	-.674	4	-1.181	1	-.046	5	-5.609e-3	3	368.851	1	2840.125	1
45		4	max	0	1	.868	3	.134	1	1.095e-2	1	9360.268	15	NC	3
46			min	-.674	4	-1.407	1	-.032	5	-6.411e-3	3	272.04	1	1764.819	1
47		5	max	0	1	.95	3	.163	1	1.222e-2	1	8073.815	15	NC	3
48			min	-.674	4	-1.547	1	-.006	5	-7.213e-3	3	234.021	1	1452.977	1
49		6	max	0	1	.961	3	.161	1	1.349e-2	1	7703.531	15	NC	3
50			min	-.674	4	-1.599	1	.012	10	-8.015e-3	3	222.449	1	1473.794	1
51		7	max	0	1	.912	3	.128	1	1.476e-2	1	7921.524	15	NC	3
52			min	-.674	4	-1.575	1	.007	10	-8.817e-3	3	227.588	1	1853.661	1
53		8	max	0	1	.828	3	.075	1	1.603e-2	1	8589.384	15	NC	2
54			min	-.674	4	-1.501	1	0	10	-9.619e-3	3	245.205	1	3186.835	4
55		9	max	0	1	.741	3	.048	4	1.729e-2	1	9488.992	15	NC	1
56			min	-.674	4	-1.416	1	-.006	10	-1.042e-2	3	269.081	1	4777.601	4
57		10	max	0	1	.7	3	.02	3	1.856e-2	1	NC	15	NC	1
58			min	-.674	4	-1.374	1	-.014	2	-1.122e-2	3	282.906	1	NC	1
59		11	max	0	12	.741	3	.021	1	1.729e-2	1	9488.957	15	NC	1
60			min	-.674	4	-1.416	1	-.037	5	-1.042e-2	3	269.081	1	6564.116	5
61		12	max	0	12	.828	3	.075	1	1.603e-2	1	8589.284	15	NC	2
62			min	-.674	4	-1.501	1	-.043	5	-9.619e-3	3	245.205	1	3189.57	1
63		13	max	0	12	.912	3	.128	1	1.476e-2	1	7921.359	15	NC	3
64			min	-.674	4	-1.575	1	-.028	5	-8.817e-3	3	227.588	1	1853.661	1
65		14	max	0	12	.961	3	.161	1	1.349e-2	1	7703.298	15	NC	3
66			min	-.674	4	-1.599	1	-.001	5	-8.015e-3	3	222.449	1	1473.794	1
67		15	max	0	12	.95	3	.163	1	1.222e-2	1	8073.495	15	NC	3
68			min	-.675	4	-1.547	1	.013	10	-7.213e-3	3	234.021	1	1452.977	1
69		16	max	0	12	.868	3	.134	1	1.095e-2	1	9359.803	15	NC	3
70			min	-.675	4	-1.407	1	.011	10	-6.411e-3	3	272.04	1	1764.819	1
71		17	max	0	12	.715	3	.084	1	9.683e-3	1	NC	15	NC	3
72			min	-.675	4	-1.181	1	.006	10	-5.609e-3	3	368.851	1	2840.125	1
73		18	max	0	12	.504	3	.05	4	8.414e-3	1	NC	5	NC	2
74			min	-.675	4	-.885	1	0	10	-4.807e-3	3	692.317	1	4584.559	4
75		19	max	0	12	.258	3	.007	3	7.146e-3	1	NC	1	NC	1
76			min	-.675	4	-.547	1	-.003	2	-4.005e-3	3	NC	1	NC	1
77	M15	1	max	0	12	.265	3	.006	3	3.318e-3	3	NC	1	NC	1
78			min	-.539	4	-.546	1	-.003	2	-7.294e-3	1	NC	1	NC	1
79		2	max	0	12	.426	3	.031	1	3.982e-3	3	NC	5	NC	2
80			min	-.539	4	-.912	1	-.052	5	-8.599e-3	1	638.68	1	4647.619	5
81		3	max	0	12	.57	3	.085	1	4.647e-3	3	NC	15	NC	3
82			min	-.539	4	-1.232	1	-.064	5	-9.903e-3	1	341.244	1	2825.749	1
83		4	max	0	12	.682	3	.135	1	5.311e-3	3	9374.102	15	NC	3
84			min	-.539	4	-1.471	1	-.047	5	-1.121e-2	1	252.883	1	1757.952	1
85		5	max	0	12	.756	3	.163	1	5.975e-3	3	8087.153	15	NC	3
86			min	-.539	4	-1.614	1	-.013	5	-1.251e-2	1	219.081	1	1447.923	1
87		6	max	0	12	.79	3	.161	1	6.64e-3	3	7718.131	15	NC	3
88			min	-.539	4	-1.658	1	.012	10	-1.382e-2	1	210.321	1	1468.559	1
89		7	max	0	12	.79	3	.129	1	7.304e-3	3	7939.14	15	NC	3

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
90			min	-.539	4	-1.619	1	.008	10	-1.512e-2	1	218.09	1	1845.708	1
91		8	max	0	12	.766	3	.087	4	7.968e-3	3	8612.06	15	NC	2
92			min	-.539	4	-1.525	1	.001	10	-1.643e-2	1	239.02	1	2663.469	4
93		9	max	0	12	.734	3	.06	4	8.633e-3	3	9518.204	15	NC	1
94			min	-.539	4	-1.422	1	-.005	10	-1.773e-2	1	267.081	1	3839.888	4
95		10	max	0	1	.718	3	.018	3	9.297e-3	3	NC	15	NC	1
96			min	-.539	4	-1.371	1	-.013	2	-1.904e-2	1	283.491	1	NC	1
97		11	max	0	1	.734	3	.022	1	8.633e-3	3	9518.176	15	NC	1
98			min	-.539	4	-1.422	1	-.049	5	-1.773e-2	1	267.081	1	4902.503	5
99		12	max	0	1	.766	3	.076	1	7.968e-3	3	8611.987	15	NC	2
100			min	-.539	4	-1.525	1	-.058	5	-1.643e-2	1	239.02	1	3167.537	1
101		13	max	0	1	.79	3	.129	1	7.304e-3	3	7939.024	15	NC	3
102			min	-.539	4	-1.619	1	-.038	5	-1.512e-2	1	218.09	1	1845.708	1
103		14	max	0	1	.79	3	.161	1	6.64e-3	3	7717.97	15	NC	3
104			min	-.539	4	-1.658	1	-.004	5	-1.382e-2	1	210.321	1	1468.559	1
105		15	max	0	1	.756	3	.163	1	5.975e-3	3	8086.935	15	NC	3
106			min	-.539	4	-1.614	1	.013	10	-1.251e-2	1	219.081	1	1447.923	1
107		16	max	0	1	.682	3	.135	1	5.311e-3	3	9373.787	15	NC	3
108			min	-.539	4	-1.471	1	.011	10	-1.121e-2	1	252.883	1	1757.952	1
109		17	max	0	1	.57	3	.095	4	4.647e-3	3	NC	15	NC	3
110			min	-.539	4	-1.232	1	.006	10	-9.903e-3	1	341.244	1	2436.918	4
111		18	max	0	1	.426	3	.065	4	3.982e-3	3	NC	5	NC	2
112			min	-.539	4	-.912	1	0	10	-8.599e-3	1	638.68	1	3586.583	4
113		19	max	0	1	.265	3	.006	3	3.318e-3	3	NC	1	NC	1
114			min	-.539	4	-.546	1	-.003	2	-7.294e-3	1	NC	1	NC	1
115	M16	1	max	0	12	.17	1	.005	3	6.089e-3	3	NC	1	NC	1
116			min	-.15	4	-.091	3	-.003	2	-1.104e-2	1	NC	1	NC	1
117		2	max	0	12	.005	4	.045	1	6.991e-3	3	NC	5	NC	2
118			min	-.15	4	-.054	2	-.037	5	-1.221e-2	1	1166.982	1	5327.944	1
119		3	max	0	12	.025	3	.107	1	7.892e-3	3	NC	5	NC	3
120			min	-.15	4	-.211	2	-.047	5	-1.337e-2	1	653.431	1	2218.5	1
121		4	max	0	12	.048	3	.16	1	8.794e-3	3	NC	5	NC	3
122			min	-.15	4	-.299	2	-.036	5	-1.453e-2	1	526.817	1	1479.55	1
123		5	max	0	12	.04	3	.186	1	9.696e-3	3	NC	5	NC	3
124			min	-.15	4	-.305	2	-.014	5	-1.57e-2	1	520.348	2	1265.55	1
125		6	max	0	12	.004	12	.18	1	1.06e-2	3	NC	5	NC	3
126			min	-.15	4	-.23	2	.007	15	-1.686e-2	1	623.301	2	1313.815	1
127		7	max	0	12	.005	4	.141	1	1.15e-2	3	NC	5	NC	3
128			min	-.15	4	-.094	2	.01	10	-1.802e-2	1	979.322	2	1675.785	1
129		8	max	0	12	.122	1	.082	1	1.24e-2	3	NC	4	NC	3
130			min	-.15	4	-.128	3	.003	10	-1.919e-2	1	3205.164	2	2896	1
131		9	max	0	12	.276	1	.04	4	1.33e-2	3	NC	5	NC	1
132			min	-.15	4	-.189	3	-.004	10	-2.035e-2	1	2216.637	1	5800.725	4
133		10	max	0	1	.345	1	.016	3	1.42e-2	3	NC	5	NC	1
134			min	-.15	4	-.216	3	-.012	2	-2.151e-2	1	1343.296	1	NC	1
135		11	max	0	1	.276	1	.024	1	1.33e-2	3	NC	5	NC	1
136			min	-.15	4	-.189	3	-.029	5	-2.035e-2	1	2216.637	1	8574.298	5
137		12	max	0	1	.122	1	.082	1	1.24e-2	3	NC	4	NC	3
138			min	-.15	4	-.128	3	-.03	5	-1.919e-2	1	3205.164	2	2896	1
139		13	max	0	1	.005	6	.141	1	1.15e-2	3	NC	5	NC	3
140			min	-.15	4	-.094	2	-.013	5	-1.802e-2	1	979.322	2	1675.785	1
141		14	max	0	1	.004	12	.18	1	1.06e-2	3	NC	5	NC	3
142			min	-.15	4	-.23	2	.008	15	-1.686e-2	1	623.301	2	1313.815	1
143		15	max	0	1	.04	3	.186	1	9.696e-3	3	NC	5	NC	3
144			min	-.15	4	-.305	2	.014	12	-1.57e-2	1	520.348	2	1265.55	1
145		16	max	0	1	.048	3	.16	1	8.794e-3	3	NC	5	NC	3
146			min	-.15	4	-.299	2	.012	12	-1.453e-2	1	526.817	1	1479.55	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
147		17	max	0	1	.025	3	.107	1	7.892e-3	3	NC	5	NC	3
148			min	-.15	4	-.211	2	.009	12	-1.337e-2	1	653.431	1	2218.5	1
149		18	max	0	1	.004	6	.054	4	6.991e-3	3	NC	5	NC	2
150			min	-.15	4	-.054	2	.003	10	-1.221e-2	1	1166.982	1	4261.338	4
151		19	max	.001	1	.17	1	.005	3	6.089e-3	3	NC	1	NC	1
152			min	-.149	4	-.091	3	-.003	2	-1.104e-2	1	NC	1	NC	1
153	M2	1	max	.007	1	.006	2	.013	1	2.687e-3	5	NC	1	NC	2
154			min	-.006	3	-.01	3	-.857	4	-3.008e-4	1	NC	1	80.624	4
155		2	max	.007	1	.005	2	.012	1	2.729e-3	5	NC	1	NC	2
156			min	-.006	3	-.01	3	-.787	4	-2.838e-4	1	NC	1	87.822	4
157		3	max	.006	1	.004	2	.011	1	2.772e-3	5	NC	1	NC	2
158			min	-.006	3	-.01	3	-.717	4	-2.668e-4	1	NC	1	96.376	4
159		4	max	.006	1	.003	2	.01	1	2.814e-3	5	NC	1	NC	2
160			min	-.005	3	-.01	3	-.648	4	-2.498e-4	1	NC	1	106.643	4
161		5	max	.005	1	.002	2	.009	1	2.856e-3	5	NC	1	NC	2
162			min	-.005	3	-.01	3	-.58	4	-2.328e-4	1	NC	1	119.104	4
163		6	max	.005	1	.001	2	.008	1	2.898e-3	5	NC	1	NC	2
164			min	-.005	3	-.009	3	-.514	4	-2.157e-4	1	NC	1	134.43	4
165		7	max	.005	1	0	2	.007	1	2.941e-3	5	NC	1	NC	1
166			min	-.004	3	-.009	3	-.45	4	-1.987e-4	1	NC	1	153.574	4
167		8	max	.004	1	0	15	.006	1	2.986e-3	4	NC	1	NC	1
168			min	-.004	3	-.009	3	-.388	4	-1.817e-4	1	NC	1	177.928	4
169		9	max	.004	1	0	15	.005	1	3.033e-3	4	NC	1	NC	1
170			min	-.004	3	-.008	3	-.33	4	-1.647e-4	1	NC	1	209.589	4
171		10	max	.003	1	0	15	.004	1	3.081e-3	4	NC	1	NC	1
172			min	-.003	3	-.008	3	-.274	4	-1.476e-4	1	NC	1	251.845	4
173		11	max	.003	1	0	15	.003	1	3.129e-3	4	NC	1	NC	1
174			min	-.003	3	-.007	3	-.223	4	-1.306e-4	1	NC	1	310.087	4
175		12	max	.003	1	0	15	.003	1	3.176e-3	4	NC	1	NC	1
176			min	-.002	3	-.007	3	-.176	4	-1.136e-4	1	NC	1	393.67	4
177		13	max	.002	1	0	15	.002	1	3.224e-3	4	NC	1	NC	1
178			min	-.002	3	-.006	3	-.133	4	-9.659e-5	1	NC	1	520.033	4
179		14	max	.002	1	0	15	.001	1	3.272e-3	4	NC	1	NC	1
180			min	-.002	3	-.005	3	-.095	4	-7.957e-5	1	NC	1	724.84	4
181		15	max	.002	1	0	15	0	1	3.32e-3	4	NC	1	NC	1
182			min	-.001	3	-.004	3	-.063	4	-6.255e-5	1	NC	1	1090.925	4
183		16	max	.001	1	0	15	0	1	3.367e-3	4	NC	1	NC	1
184			min	-.001	3	-.004	6	-.037	4	-4.553e-5	1	NC	1	1849.778	4
185		17	max	0	1	0	15	0	1	3.415e-3	4	NC	1	NC	1
186			min	0	3	-.003	6	-.018	4	-2.851e-5	1	NC	1	3875.196	4
187		18	max	0	1	0	15	0	1	3.463e-3	4	NC	1	NC	1
188			min	0	3	-.001	6	-.005	4	-1.149e-5	1	NC	1	NC	1
189		19	max	0	1	0	1	0	1	3.511e-3	4	NC	1	NC	1
190			min	0	1	0	1	0	1	7.309e-8	12	NC	1	NC	1
191	M3	1	max	0	1	0	1	0	1	-1.173e-7	12	NC	1	NC	1
192			min	0	1	0	1	0	1	-7.29e-4	4	NC	1	NC	1
193		2	max	0	3	0	15	.019	4	6.575e-5	4	NC	1	NC	1
194			min	0	2	-.003	6	0	12	1.584e-6	12	NC	1	NC	1
195		3	max	0	3	-.001	15	.037	4	8.606e-4	4	NC	1	NC	1
196			min	0	2	-.005	6	0	12	3.286e-6	12	NC	1	9296.11	5
197		4	max	0	3	-.002	15	.054	4	1.655e-3	4	NC	1	NC	1
198			min	0	2	-.008	6	0	12	4.987e-6	12	NC	1	6859.282	5
199		5	max	.001	3	-.003	15	.07	4	2.45e-3	4	NC	1	NC	1
200			min	0	2	-.011	6	0	12	6.689e-6	12	8967.629	6	5752.015	5
201		6	max	.002	3	-.003	15	.084	4	3.245e-3	4	NC	2	NC	1
202			min	-.001	2	-.014	6	0	12	8.391e-6	12	7226.192	6	5204.65	5
203		7	max	.002	3	-.004	15	.098	4	4.04e-3	4	NC	5	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
204			min	-.001	2	-.017	6	0	12	1.009e-5	12	6179.516	6	4970.909	5
205		8	max	.002	3	-.004	15	.111	4	4.835e-3	4	NC	5	NC	1
206			min	-.002	2	-.019	6	0	12	1.179e-5	12	5533.513	6	4959.157	5
207		9	max	.003	3	-.004	15	.124	4	5.629e-3	4	NC	5	NC	1
208			min	-.002	2	-.02	6	0	12	1.35e-5	12	5149.918	6	5143.573	5
209		10	max	.003	3	-.005	15	.135	4	6.424e-3	4	NC	5	NC	1
210			min	-.002	2	-.021	6	0	12	1.52e-5	12	4961.461	6	5540.395	5
211		11	max	.003	3	-.005	15	.146	4	7.219e-3	4	NC	5	NC	1
212			min	-.002	2	-.021	6	0	12	1.69e-5	12	4940.222	6	6209.477	5
213		12	max	.003	3	-.004	15	.157	4	8.014e-3	4	NC	5	NC	1
214			min	-.003	2	-.02	6	0	12	1.86e-5	12	5086.902	6	7277.826	5
215		13	max	.004	3	-.004	15	.167	4	8.809e-3	4	NC	5	NC	1
216			min	-.003	2	-.019	6	0	12	2.03e-5	12	5432.45	6	9003.922	5
217		14	max	.004	3	-.004	15	.177	4	9.603e-3	4	NC	5	NC	1
218			min	-.003	2	-.017	6	0	12	2.2e-5	12	6054.268	6	NC	1
219		15	max	.004	3	-.003	15	.188	4	1.04e-2	4	NC	3	NC	1
220			min	-.003	2	-.014	6	0	12	2.37e-5	12	7124.537	6	NC	1
221		16	max	.005	3	-.002	15	.198	4	1.119e-2	4	NC	1	NC	1
222			min	-.003	2	-.011	6	0	12	2.541e-5	12	9060.747	6	NC	1
223		17	max	.005	3	-.002	15	.21	4	1.199e-2	4	NC	1	NC	1
224			min	-.004	2	-.008	1	0	12	2.711e-5	12	NC	1	NC	1
225		18	max	.005	3	0	15	.222	4	1.278e-2	4	NC	1	NC	2
226			min	-.004	2	-.006	1	0	12	2.881e-5	12	NC	1	9829.789	1
227		19	max	.006	3	0	5	.235	4	1.358e-2	4	NC	1	NC	2
228			min	-.004	2	-.003	1	0	12	3.051e-5	12	NC	1	8426.925	1
229	M4	1	max	.003	1	.004	2	0	12	1.568e-4	1	NC	1	NC	3
230			min	0	3	-.006	3	-.235	4	-9.801e-4	5	NC	1	105.669	4
231		2	max	.003	1	.004	2	0	12	1.568e-4	1	NC	1	NC	3
232			min	0	3	-.005	3	-.216	4	-9.801e-4	5	NC	1	115.014	4
233		3	max	.002	1	.003	2	0	12	1.568e-4	1	NC	1	NC	3
234			min	0	3	-.005	3	-.197	4	-9.801e-4	5	NC	1	126.129	4
235		4	max	.002	1	.003	2	0	12	1.568e-4	1	NC	1	NC	3
236			min	0	3	-.005	3	-.178	4	-9.801e-4	5	NC	1	139.475	4
237		5	max	.002	1	.003	2	0	12	1.568e-4	1	NC	1	NC	3
238			min	0	3	-.005	3	-.159	4	-9.801e-4	5	NC	1	155.678	4
239		6	max	.002	1	.003	2	0	12	1.568e-4	1	NC	1	NC	3
240			min	0	3	-.004	3	-.141	4	-9.801e-4	5	NC	1	175.607	4
241		7	max	.002	1	.003	2	0	12	1.568e-4	1	NC	1	NC	3
242			min	0	3	-.004	3	-.124	4	-9.801e-4	5	NC	1	200.495	4
243		8	max	.002	1	.002	2	0	12	1.568e-4	1	NC	1	NC	2
244			min	0	3	-.004	3	-.107	4	-9.801e-4	5	NC	1	232.141	4
245		9	max	.002	1	.002	2	0	12	1.568e-4	1	NC	1	NC	2
246			min	0	3	-.003	3	-.091	4	-9.801e-4	5	NC	1	273.252	4
247		10	max	.001	1	.002	2	0	12	1.568e-4	1	NC	1	NC	2
248			min	0	3	-.003	3	-.076	4	-9.801e-4	5	NC	1	328.06	4
249		11	max	.001	1	.002	2	0	12	1.568e-4	1	NC	1	NC	2
250			min	0	3	-.003	3	-.061	4	-9.801e-4	5	NC	1	403.491	4
251		12	max	.001	1	.001	2	0	12	1.568e-4	1	NC	1	NC	2
252			min	0	3	-.002	3	-.048	4	-9.801e-4	5	NC	1	511.526	4
253		13	max	0	1	.001	2	0	12	1.568e-4	1	NC	1	NC	1
254			min	0	3	-.002	3	-.037	4	-9.801e-4	5	NC	1	674.404	4
255		14	max	0	1	.001	2	0	12	1.568e-4	1	NC	1	NC	1
256			min	0	3	-.002	3	-.026	4	-9.801e-4	5	NC	1	937.376	4
257		15	max	0	1	0	2	0	12	1.568e-4	1	NC	1	NC	1
258			min	0	3	-.001	3	-.018	4	-9.801e-4	5	NC	1	1404.767	4
259		16	max	0	1	0	2	0	12	1.568e-4	1	NC	1	NC	1
260			min	0	3	0	3	-.01	4	-9.801e-4	5	NC	1	2365.028	4

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
261		17	max	0	1	0	2	0	12	1.568e-4	1	NC	1	NC	1
262			min	0	3	0	3	-.005	4	-9.801e-4	5	NC	1	4887.938	4
263		18	max	0	1	0	2	0	12	1.568e-4	1	NC	1	NC	1
264			min	0	3	0	3	-.002	4	-9.801e-4	5	NC	1	NC	1
265		19	max	0	1	0	1	0	1	1.568e-4	1	NC	1	NC	1
266			min	0	1	0	1	0	1	-9.801e-4	5	NC	1	NC	1
267	M6	1	max	.022	1	.024	2	0	1	2.834e-3	4	NC	3	NC	1
268			min	-.021	3	-.032	3	-.866	4	0	1	2895.486	2	79.759	4
269		2	max	.021	1	.022	2	0	1	2.873e-3	4	NC	3	NC	1
270			min	-.02	3	-.031	3	-.795	4	0	1	3198.006	2	86.881	4
271		3	max	.02	1	.019	2	0	1	2.912e-3	4	NC	3	NC	1
272			min	-.018	3	-.029	3	-.725	4	0	1	3567.75	2	95.344	4
273		4	max	.018	1	.017	2	0	1	2.951e-3	4	NC	3	NC	1
274			min	-.017	3	-.027	3	-.655	4	0	1	4025.64	2	105.501	4
275		5	max	.017	1	.015	2	0	1	2.99e-3	4	NC	3	NC	1
276			min	-.016	3	-.026	3	-.586	4	0	1	4601.734	2	117.83	4
277		6	max	.016	1	.013	2	0	1	3.03e-3	4	NC	3	NC	1
278			min	-.015	3	-.024	3	-.52	4	0	1	5340.517	2	132.994	4
279		7	max	.015	1	.011	2	0	1	3.069e-3	4	NC	1	NC	1
280			min	-.014	3	-.022	3	-.455	4	0	1	6310.208	2	151.936	4
281		8	max	.013	1	.009	2	0	1	3.108e-3	4	NC	1	NC	1
282			min	-.013	3	-.021	3	-.393	4	0	1	7620.023	2	176.032	4
283		9	max	.012	1	.007	2	0	1	3.147e-3	4	NC	1	NC	1
284			min	-.012	3	-.019	3	-.333	4	0	1	9454.411	2	207.359	4
285		10	max	.011	1	.006	2	0	1	3.186e-3	4	NC	1	NC	1
286			min	-.01	3	-.017	3	-.277	4	0	1	NC	1	249.169	4
287		11	max	.01	1	.004	2	0	1	3.225e-3	4	NC	1	NC	1
288			min	-.009	3	-.015	3	-.225	4	0	1	NC	1	306.797	4
289		12	max	.009	1	.003	2	0	1	3.264e-3	4	NC	1	NC	1
290			min	-.008	3	-.014	3	-.177	4	0	1	NC	1	389.502	4
291		13	max	.007	1	.002	2	0	1	3.304e-3	4	NC	1	NC	1
292			min	-.007	3	-.012	3	-.134	4	0	1	NC	1	514.539	4
293		14	max	.006	1	0	2	0	1	3.343e-3	4	NC	1	NC	1
294			min	-.006	3	-.01	3	-.096	4	0	1	NC	1	717.204	4
295		15	max	.005	1	0	2	0	1	3.382e-3	4	NC	1	NC	1
296			min	-.005	3	-.008	3	-.064	4	0	1	NC	1	1079.471	4
297		16	max	.004	1	0	2	0	1	3.421e-3	4	NC	1	NC	1
298			min	-.003	3	-.006	3	-.038	4	0	1	NC	1	1830.451	4
299		17	max	.002	1	0	2	0	1	3.46e-3	4	NC	1	NC	1
300			min	-.002	3	-.004	3	-.018	4	0	1	NC	1	3835.032	4
301		18	max	.001	1	0	2	0	1	3.499e-3	4	NC	1	NC	1
302			min	-.001	3	-.002	3	-.005	4	0	1	NC	1	NC	1
303		19	max	0	1	0	1	0	1	3.538e-3	4	NC	1	NC	1
304			min	0	1	0	1	0	1	0	1	NC	1	NC	1
305	M7	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
306			min	0	1	0	1	0	1	-7.345e-4	4	NC	1	NC	1
307		2	max	0	3	0	15	.019	4	3.498e-5	4	NC	1	NC	1
308			min	0	2	-.003	3	0	1	0	1	NC	1	NC	1
309		3	max	.002	3	-.001	15	.037	4	8.044e-4	4	NC	1	NC	1
310			min	-.002	2	-.006	3	0	1	0	1	NC	1	8378.195	4
311		4	max	.003	3	-.002	15	.054	4	1.574e-3	4	NC	1	NC	1
312			min	-.003	2	-.009	3	0	1	0	1	NC	1	6140.542	4
313		5	max	.004	3	-.003	15	.07	4	2.343e-3	4	NC	1	NC	1
314			min	-.004	2	-.012	4	0	1	0	1	9034.773	4	5109.906	4
315		6	max	.005	3	-.003	15	.085	4	3.113e-3	4	NC	1	NC	1
316			min	-.005	2	-.014	4	0	1	0	1	7275.181	4	4582.91	4
317		7	max	.006	3	-.004	15	.099	4	3.882e-3	4	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
318			min	-.006	2	-.017	4	0	1	0	1	6217.898	4	4332.213	4
319		8	max	.007	3	-.004	15	.112	4	4.652e-3	4	NC	5	NC	1
320			min	-.006	2	-.019	4	0	1	0	1	5565.315	4	4269.764	4
321		9	max	.008	3	-.005	15	.124	4	5.421e-3	4	NC	5	NC	1
322			min	-.007	2	-.02	4	0	1	0	1	5177.54	4	4364.598	4
323		10	max	.009	3	-.005	15	.135	4	6.191e-3	4	NC	5	NC	1
324			min	-.008	2	-.021	4	0	1	0	1	4986.484	4	4618.757	4
325		11	max	.01	3	-.005	15	.145	4	6.96e-3	4	NC	5	NC	1
326			min	-.009	2	-.021	4	0	1	0	1	4963.81	4	5063.601	4
327		12	max	.011	3	-.005	15	.155	4	7.729e-3	4	NC	5	NC	1
328			min	-.01	2	-.021	4	0	1	0	1	5110.043	4	5769.656	4
329		13	max	.012	3	-.005	15	.165	4	8.499e-3	4	NC	5	NC	1
330			min	-.011	2	-.02	4	0	1	0	1	5456.137	4	6876.04	4
331		14	max	.013	3	-.004	15	.175	4	9.268e-3	4	NC	5	NC	1
332			min	-.012	2	-.018	4	0	1	0	1	6079.717	4	8664.755	4
333		15	max	.014	3	-.004	15	.184	4	1.004e-2	4	NC	1	NC	1
334			min	-.013	2	-.015	4	0	1	0	1	7153.575	4	NC	1
335		16	max	.014	3	-.003	15	.194	4	1.081e-2	4	NC	1	NC	1
336			min	-.014	2	-.013	4	0	1	0	1	9096.768	4	NC	1
337		17	max	.015	3	-.002	15	.204	4	1.158e-2	4	NC	1	NC	1
338			min	-.015	2	-.01	1	0	1	0	1	NC	1	NC	1
339		18	max	.016	3	-.001	15	.214	4	1.235e-2	4	NC	1	NC	1
340			min	-.016	2	-.007	1	0	1	0	1	NC	1	NC	1
341		19	max	.017	3	0	15	.225	4	1.312e-2	4	NC	1	NC	1
342			min	-.017	2	-.005	1	0	1	0	1	NC	1	NC	1
343	M8	1	max	.007	1	.016	2	0	1	0	1	NC	1	NC	1
344			min	0	3	-.018	3	-.225	4	-1.155e-3	4	NC	1	110.019	4
345		2	max	.007	1	.015	2	0	1	0	1	NC	1	NC	1
346			min	0	3	-.017	3	-.207	4	-1.155e-3	4	NC	1	119.762	4
347		3	max	.006	1	.014	2	0	1	0	1	NC	1	NC	1
348			min	0	3	-.016	3	-.189	4	-1.155e-3	4	NC	1	131.351	4
349		4	max	.006	1	.013	2	0	1	0	1	NC	1	NC	1
350			min	0	3	-.015	3	-.171	4	-1.155e-3	4	NC	1	145.265	4
351		5	max	.006	1	.012	2	0	1	0	1	NC	1	NC	1
352			min	0	3	-.014	3	-.153	4	-1.155e-3	4	NC	1	162.157	4
353		6	max	.005	1	.011	2	0	1	0	1	NC	1	NC	1
354			min	0	3	-.013	3	-.136	4	-1.155e-3	4	NC	1	182.934	4
355		7	max	.005	1	.01	2	0	1	0	1	NC	1	NC	1
356			min	0	3	-.012	3	-.119	4	-1.155e-3	4	NC	1	208.88	4
357		8	max	.004	1	.01	2	0	1	0	1	NC	1	NC	1
358			min	0	3	-.011	3	-.103	4	-1.155e-3	4	NC	1	241.87	4
359		9	max	.004	1	.009	2	0	1	0	1	NC	1	NC	1
360			min	0	3	-.01	3	-.087	4	-1.155e-3	4	NC	1	284.728	4
361		10	max	.004	1	.008	2	0	1	0	1	NC	1	NC	1
362			min	0	3	-.009	3	-.073	4	-1.155e-3	4	NC	1	341.866	4
363		11	max	.003	1	.007	2	0	1	0	1	NC	1	NC	1
364			min	0	3	-.008	3	-.059	4	-1.155e-3	4	NC	1	420.504	4
365		12	max	.003	1	.006	2	0	1	0	1	NC	1	NC	1
366			min	0	3	-.007	3	-.047	4	-1.155e-3	4	NC	1	533.134	4
367		13	max	.002	1	.005	2	0	1	0	1	NC	1	NC	1
368			min	0	3	-.006	3	-.035	4	-1.155e-3	4	NC	1	702.944	4
369		14	max	.002	1	.004	2	0	1	0	1	NC	1	NC	1
370			min	0	3	-.005	3	-.025	4	-1.155e-3	4	NC	1	977.115	4
371		15	max	.002	1	.003	2	0	1	0	1	NC	1	NC	1
372			min	0	3	-.004	3	-.017	4	-1.155e-3	4	NC	1	1464.429	4
373		16	max	.001	1	.003	2	0	1	0	1	NC	1	NC	1
374			min	0	3	-.003	3	-.01	4	-1.155e-3	4	NC	1	2465.664	4

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
375		17	max	0	1	.002	2	0	1	0	1	NC	1	NC	1
376			min	0	3	-.002	3	-.005	4	-1.155e-3	4	NC	1	5096.387	4
377		18	max	0	1	0	2	0	1	0	1	NC	1	NC	1
378			min	0	3	0	3	-.001	4	-1.155e-3	4	NC	1	NC	1
379		19	max	0	1	0	1	0	1	0	1	NC	1	NC	1
380			min	0	1	0	1	0	1	-1.155e-3	4	NC	1	NC	1
381	M10	1	max	.007	1	.006	2	0	12	2.821e-3	4	NC	1	NC	2
382			min	-.006	3	-.01	3	-.864	4	1.631e-5	12	NC	1	79.94	4
383		2	max	.007	1	.005	2	0	12	2.859e-3	4	NC	1	NC	2
384			min	-.006	3	-.01	3	-.794	4	1.54e-5	12	NC	1	87.077	4
385		3	max	.006	1	.004	2	0	12	2.897e-3	4	NC	1	NC	2
386			min	-.006	3	-.01	3	-.723	4	1.449e-5	12	NC	1	95.56	4
387		4	max	.006	1	.003	2	0	12	2.935e-3	4	NC	1	NC	2
388			min	-.005	3	-.01	3	-.654	4	1.358e-5	12	NC	1	105.741	4
389		5	max	.005	1	.002	2	0	12	2.973e-3	4	NC	1	NC	2
390			min	-.005	3	-.01	3	-.585	4	1.267e-5	12	NC	1	118.098	4
391		6	max	.005	1	.001	2	0	12	3.011e-3	4	NC	1	NC	2
392			min	-.005	3	-.009	3	-.518	4	1.176e-5	12	NC	1	133.297	4
393		7	max	.005	1	0	2	0	12	3.049e-3	4	NC	1	NC	1
394			min	-.004	3	-.009	3	-.454	4	1.085e-5	12	NC	1	152.283	4
395		8	max	.004	1	0	2	0	12	3.088e-3	4	NC	1	NC	1
396			min	-.004	3	-.009	3	-.392	4	9.938e-6	12	NC	1	176.435	4
397		9	max	.004	1	-.001	2	0	12	3.126e-3	4	NC	1	NC	1
398			min	-.004	3	-.008	3	-.333	4	9.028e-6	12	NC	1	207.835	4
399		10	max	.003	1	-.002	2	0	12	3.164e-3	4	NC	1	NC	1
400			min	-.003	3	-.008	3	-.277	4	8.118e-6	12	NC	1	249.745	4
401		11	max	.003	1	-.002	15	0	12	3.202e-3	4	NC	1	NC	1
402			min	-.003	3	-.007	3	-.225	4	7.208e-6	12	NC	1	307.511	4
403		12	max	.003	1	-.002	15	0	12	3.24e-3	4	NC	1	NC	1
404			min	-.002	3	-.007	4	-.177	4	6.298e-6	12	NC	1	390.416	4
405		13	max	.002	1	-.002	15	0	12	3.278e-3	4	NC	1	NC	1
406			min	-.002	3	-.006	4	-.134	4	5.388e-6	12	NC	1	515.76	4
407		14	max	.002	1	-.002	15	0	12	3.316e-3	4	NC	1	NC	1
408			min	-.002	3	-.006	4	-.096	4	4.478e-6	12	NC	1	718.933	4
409		15	max	.002	1	-.001	15	0	12	3.354e-3	4	NC	1	NC	1
410			min	-.001	3	-.005	4	-.064	4	3.567e-6	12	NC	1	1082.135	4
411		16	max	.001	1	-.001	15	0	12	3.392e-3	4	NC	1	NC	1
412			min	-.001	3	-.004	4	-.038	4	2.657e-6	12	NC	1	1835.139	4
413		17	max	0	1	0	15	0	12	3.431e-3	4	NC	1	NC	1
414			min	0	3	-.003	4	-.018	4	1.747e-6	12	NC	1	3845.529	4
415		18	max	0	1	0	15	0	12	3.469e-3	4	NC	1	NC	1
416			min	0	3	-.002	4	-.005	4	8.37e-7	12	NC	1	NC	1
417		19	max	0	1	0	1	0	1	3.507e-3	4	NC	1	NC	1
418			min	0	1	0	1	0	1	-5.534e-6	1	NC	1	NC	1
419	M11	1	max	0	1	0	1	0	1	3.272e-6	1	NC	1	NC	1
420			min	0	1	0	1	0	1	-7.271e-4	4	NC	1	NC	1
421		2	max	0	3	0	15	.019	4	5.239e-5	5	NC	1	NC	1
422			min	0	2	-.003	4	0	1	-3.217e-5	1	NC	1	NC	1
423		3	max	0	3	-.001	15	.037	4	8.224e-4	4	NC	1	NC	1
424			min	0	2	-.006	4	0	1	-6.761e-5	1	NC	1	8817.504	4
425		4	max	0	3	-.002	15	.054	4	1.597e-3	4	NC	1	NC	1
426			min	0	2	-.009	4	0	1	-1.031e-4	1	NC	1	6489.438	4
427		5	max	.001	3	-.003	15	.069	4	2.372e-3	4	NC	1	NC	1
428			min	0	2	-.012	4	0	1	-1.385e-4	1	8618.074	4	5425.541	4
429		6	max	.002	3	-.004	15	.084	4	3.146e-3	4	NC	2	NC	1
430			min	-.001	2	-.015	4	0	1	-1.739e-4	1	6970.033	4	4891.898	4
431		7	max	.002	3	-.004	15	.098	4	3.921e-3	4	NC	5	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
432			min	-.001	2	-.018	4	0	1	-2.094e-4	1	5978.114	4	4652.603	4
433		8	max	.002	3	-.005	15	.111	4	4.696e-3	4	NC	5	NC	1
434			min	-.002	2	-.02	4	-.001	1	-2.448e-4	1	5366.156	4	4618.231	4
435		9	max	.003	3	-.005	15	.123	4	5.471e-3	4	NC	5	NC	1
436			min	-.002	2	-.021	4	-.002	1	-2.803e-4	1	5004.213	4	4760.611	4
437		10	max	.003	3	-.005	15	.134	4	6.245e-3	4	NC	5	NC	1
438			min	-.002	2	-.022	4	-.002	1	-3.157e-4	1	4829.203	4	5088.965	4
439		11	max	.003	3	-.005	15	.145	4	7.02e-3	4	NC	5	NC	1
440			min	-.002	2	-.022	4	-.003	1	-3.512e-4	1	4815.332	4	5648.719	4
441		12	max	.003	3	-.005	15	.155	4	7.795e-3	4	NC	5	NC	1
442			min	-.003	2	-.021	4	-.003	1	-3.866e-4	1	4964.208	4	6537.72	4
443		13	max	.004	3	-.005	15	.165	4	8.569e-3	4	NC	5	NC	1
444			min	-.003	2	-.02	4	-.004	1	-4.22e-4	1	5306.716	4	7951.41	4
445		14	max	.004	3	-.005	15	.174	4	9.344e-3	4	NC	5	NC	1
446			min	-.003	2	-.018	4	-.005	1	-4.575e-4	1	5919.047	4	NC	1
447		15	max	.004	3	-.004	15	.184	4	1.012e-2	4	NC	3	NC	1
448			min	-.003	2	-.016	4	-.006	1	-4.929e-4	1	6970.119	4	NC	1
449		16	max	.005	3	-.003	15	.194	4	1.089e-2	4	NC	1	NC	1
450			min	-.003	2	-.013	4	-.007	1	-5.284e-4	1	8869.073	4	NC	1
451		17	max	.005	3	-.002	15	.205	4	1.167e-2	4	NC	1	NC	1
452			min	-.004	2	-.009	4	-.009	1	-5.638e-4	1	NC	1	NC	1
453		18	max	.005	3	-.001	15	.216	4	1.244e-2	4	NC	1	NC	2
454			min	-.004	2	-.006	1	-.01	1	-5.993e-4	1	NC	1	9829.789	1
455		19	max	.006	3	0	10	.228	4	1.322e-2	4	NC	1	NC	2
456			min	-.004	2	-.003	1	-.012	1	-6.347e-4	1	NC	1	8426.925	1
457	M12	1	max	.003	1	.004	2	.012	1	-7.902e-6	12	NC	1	NC	3
458			min	0	3	-.006	3	-.228	4	-1.055e-3	4	NC	1	108.847	4
459		2	max	.003	1	.004	2	.011	1	-7.902e-6	12	NC	1	NC	3
460			min	0	3	-.005	3	-.209	4	-1.055e-3	4	NC	1	118.479	4
461		3	max	.002	1	.003	2	.01	1	-7.902e-6	12	NC	1	NC	3
462			min	0	3	-.005	3	-.191	4	-1.055e-3	4	NC	1	129.935	4
463		4	max	.002	1	.003	2	.009	1	-7.902e-6	12	NC	1	NC	3
464			min	0	3	-.005	3	-.173	4	-1.055e-3	4	NC	1	143.69	4
465		5	max	.002	1	.003	2	.008	1	-7.902e-6	12	NC	1	NC	3
466			min	0	3	-.005	3	-.155	4	-1.055e-3	4	NC	1	160.389	4
467		6	max	.002	1	.003	2	.007	1	-7.902e-6	12	NC	1	NC	3
468			min	0	3	-.004	3	-.137	4	-1.055e-3	4	NC	1	180.929	4
469		7	max	.002	1	.003	2	.006	1	-7.902e-6	12	NC	1	NC	3
470			min	0	3	-.004	3	-.12	4	-1.055e-3	4	NC	1	206.58	4
471		8	max	.002	1	.002	2	.006	1	-7.902e-6	12	NC	1	NC	2
472			min	0	3	-.004	3	-.104	4	-1.055e-3	4	NC	1	239.195	4
473		9	max	.002	1	.002	2	.005	1	-7.902e-6	12	NC	1	NC	2
474			min	0	3	-.003	3	-.088	4	-1.055e-3	4	NC	1	281.564	4
475		10	max	.001	1	.002	2	.004	1	-7.902e-6	12	NC	1	NC	2
476			min	0	3	-.003	3	-.073	4	-1.055e-3	4	NC	1	338.051	4
477		11	max	.001	1	.002	2	.003	1	-7.902e-6	12	NC	1	NC	2
478			min	0	3	-.003	3	-.06	4	-1.055e-3	4	NC	1	415.793	4
479		12	max	.001	1	.001	2	.003	1	-7.902e-6	12	NC	1	NC	2
480			min	0	3	-.002	3	-.047	4	-1.055e-3	4	NC	1	527.138	4
481		13	max	0	1	.001	2	.002	1	-7.902e-6	12	NC	1	NC	1
482			min	0	3	-.002	3	-.036	4	-1.055e-3	4	NC	1	695.008	4
483		14	max	0	1	.001	2	.001	1	-7.902e-6	12	NC	1	NC	1
484			min	0	3	-.002	3	-.026	4	-1.055e-3	4	NC	1	966.043	4
485		15	max	0	1	0	2	0	1	-7.902e-6	12	NC	1	NC	1
486			min	0	3	-.001	3	-.017	4	-1.055e-3	4	NC	1	1447.772	4
487		16	max	0	1	0	2	0	1	-7.902e-6	12	NC	1	NC	1
488			min	0	3	0	3	-.01	4	-1.055e-3	4	NC	1	2437.508	4

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
489		17	max	0	1	0	2	0	1	-7.902e-6	12	NC	1	NC	1
490			min	0	3	0	3	-.005	4	-1.055e-3	4	NC	1	5037.924	4
491		18	max	0	1	0	2	0	1	-7.902e-6	12	NC	1	NC	1
492			min	0	3	0	3	-.001	4	-1.055e-3	4	NC	1	NC	1
493		19	max	0	1	0	1	0	1	-7.902e-6	12	NC	1	NC	1
494			min	0	1	0	1	0	1	-1.055e-3	4	NC	1	NC	1
495	M1	1	max	.007	3	.175	1	.918	4	1.368e-2	1	NC	1	NC	1
496			min	-.003	2	-.023	3	0	12	-1.852e-2	3	NC	1	NC	1
497		2	max	.007	3	.087	1	.888	4	1.05e-2	4	NC	5	NC	1
498			min	-.003	2	-.011	3	-.009	1	-9.191e-3	3	1523.855	1	9144.624	5
499		3	max	.007	3	.01	3	.857	4	1.796e-2	4	NC	5	NC	2
500			min	-.003	2	-.009	2	-.013	1	-2.843e-4	1	731.458	1	5011.126	5
501		4	max	.007	3	.048	3	.825	4	1.563e-2	4	NC	15	NC	1
502			min	-.003	2	-.117	1	-.012	1	-3.674e-3	3	459.63	1	3599.266	5
503		5	max	.007	3	.096	3	.792	4	1.33e-2	4	9567.734	15	NC	1
504			min	-.003	2	-.232	1	-.008	1	-7.254e-3	3	330.24	1	2884.564	5
505		6	max	.007	3	.15	3	.759	4	1.466e-2	1	7552.593	15	NC	1
506			min	-.003	2	-.343	1	-.004	1	-1.083e-2	3	259.16	1	2450.544	5
507		7	max	.007	3	.201	3	.724	4	1.964e-2	1	6363.844	15	NC	1
508			min	-.003	2	-.443	1	0	3	-1.441e-2	3	217.318	1	2143.865	4
509		8	max	.007	3	.244	3	.689	4	2.462e-2	1	5660.922	15	NC	1
510			min	-.003	2	-.523	1	0	12	-1.799e-2	3	192.621	1	1915.794	4
511		9	max	.006	3	.272	3	.652	4	2.704e-2	1	5293.516	15	NC	1
512			min	-.003	2	-.573	1	0	1	-1.817e-2	3	179.764	1	1768.264	4
513		10	max	.006	3	.283	3	.611	4	2.775e-2	1	5181.324	15	NC	1
514			min	-.003	2	-.589	1	0	12	-1.607e-2	3	175.904	1	1725.478	4
515		11	max	.006	3	.276	3	.567	4	2.846e-2	1	5293.309	15	NC	1
516			min	-.003	2	-.572	1	0	12	-1.397e-2	3	179.984	1	1765.31	4
517		12	max	.006	3	.253	3	.519	4	2.68e-2	1	5660.432	15	NC	1
518			min	-.003	2	-.521	1	-.001	1	-1.176e-2	3	193.3	1	1896.094	4
519		13	max	.006	3	.216	3	.465	4	2.159e-2	1	6362.887	15	NC	1
520			min	-.003	2	-.44	1	0	1	-9.408e-3	3	218.979	1	2258.845	4
521		14	max	.006	3	.168	3	.407	4	1.639e-2	1	7550.829	15	NC	1
522			min	-.003	2	-.339	1	0	12	-7.054e-3	3	262.713	1	3064.571	4
523		15	max	.006	3	.114	3	.347	4	1.119e-2	1	9564.484	15	NC	1
524			min	-.003	2	-.226	1	0	12	-4.699e-3	3	337.528	1	5000.073	4
525		16	max	.005	3	.058	3	.289	4	1.08e-2	4	NC	15	NC	1
526			min	-.003	2	-.111	1	0	12	-2.345e-3	3	474.871	1	NC	1
527		17	max	.005	3	.003	3	.236	4	1.204e-2	4	NC	5	NC	1
528			min	-.003	2	-.005	2	0	12	8.104e-6	12	765.525	1	NC	1
529		18	max	.005	3	.087	1	.19	4	8.319e-3	1	NC	5	NC	1
530			min	-.003	2	-.045	3	0	12	-2.598e-3	3	1609.987	1	NC	1
531		19	max	.005	3	.17	1	.149	4	1.608e-2	1	NC	1	NC	1
532			min	-.003	2	-.091	3	-.001	1	-5.294e-3	3	NC	1	NC	1
533	M5	1	max	.022	3	.358	1	.918	4	0	1	NC	1	NC	1
534			min	-.015	2	-.009	3	0	1	-8.602e-6	4	NC	1	NC	1
535		2	max	.022	3	.177	1	.895	4	9.203e-3	4	NC	5	NC	1
536			min	-.015	2	-.004	3	0	1	0	1	746.093	1	6814.55	4
537		3	max	.022	3	.032	3	.866	4	1.819e-2	4	NC	15	NC	1
538			min	-.015	2	-.03	1	0	1	0	1	346.926	1	4001.292	4
539		4	max	.022	3	.122	3	.833	4	1.482e-2	4	6757.241	15	NC	1
540			min	-.015	2	-.285	1	0	1	0	1	209.365	1	3091.445	4
541		5	max	.021	3	.25	3	.798	4	1.145e-2	4	4711.957	15	NC	1
542			min	-.015	2	-.566	1	0	1	0	1	145.598	1	2651.275	4
543		6	max	.021	3	.396	3	.761	4	8.086e-3	4	3617.774	15	NC	1
544			min	-.014	2	-.848	1	0	1	0	1	111.534	1	2378.583	4
545		7	max	.021	3	.54	3	.724	4	4.717e-3	4	2987.517	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
546			min	-.014	2	-1.105	1	0	1	0	1	91.934	1	2160.934	4
547		8	max	.02	3	.662	3	.688	4	1.348e-3	4	2621.896	15	NC	1
548			min	-.014	2	-1.311	1	0	1	0	1	80.573	1	1945.574	4
549		9	max	.02	3	.741	3	.653	4	0	1	2434.489	15	NC	1
550			min	-.013	2	-1.441	1	0	1	-4.823e-6	5	74.757	1	1762.818	4
551		10	max	.019	3	.77	3	.611	4	0	1	2377.986	15	NC	1
552			min	-.013	2	-1.485	1	0	1	-4.621e-6	5	73.025	1	1739.941	4
553		11	max	.019	3	.751	3	.566	4	0	1	2434.576	15	NC	1
554			min	-.013	2	-1.44	1	0	1	-4.419e-6	5	74.862	1	1790.768	4
555		12	max	.018	3	.686	3	.521	4	8.49e-4	4	2622.108	15	NC	1
556			min	-.013	2	-1.307	1	0	1	0	1	80.924	1	1859	4
557		13	max	.018	3	.581	3	.467	4	2.972e-3	4	2987.958	15	NC	1
558			min	-.013	2	-1.095	1	0	1	0	1	92.852	1	2204.078	4
559		14	max	.017	3	.448	3	.406	4	5.096e-3	4	3618.649	15	NC	1
560			min	-.012	2	-.832	1	0	1	0	1	113.617	1	3152.496	4
561		15	max	.017	3	.3	3	.342	4	7.219e-3	4	4713.703	15	NC	1
562			min	-.012	2	-.545	1	0	1	0	1	150.159	1	6158.781	5
563		16	max	.016	3	.15	3	.281	4	9.343e-3	4	6760.927	15	NC	1
564			min	-.012	2	-.263	1	0	1	0	1	219.693	1	NC	1
565		17	max	.016	3	.01	3	.226	4	1.147e-2	4	NC	15	NC	1
566			min	-.012	2	-.015	2	0	1	0	1	372.3	1	NC	1
567		18	max	.016	3	.181	1	.183	4	5.801e-3	4	NC	5	NC	1
568			min	-.012	2	-.109	3	0	1	0	1	814.928	1	NC	1
569		19	max	.016	3	.345	1	.15	4	0	1	NC	1	NC	1
570			min	-.012	2	-.216	3	0	1	-4.688e-6	4	NC	1	NC	1
571	M9	1	max	.007	3	.175	1	.917	4	1.852e-2	3	NC	1	NC	1
572			min	-.003	2	-.023	3	0	1	-1.368e-2	1	NC	1	NC	1
573		2	max	.007	3	.087	1	.893	4	9.191e-3	3	NC	5	NC	1
574			min	-.003	2	-.011	3	0	12	-6.593e-3	1	1523.855	1	7300.338	4
575		3	max	.007	3	.01	3	.864	4	1.813e-2	4	NC	5	NC	2
576			min	-.003	2	-.009	2	0	12	8.233e-7	10	731.458	1	4210.823	4
577		4	max	.007	3	.048	3	.832	4	1.419e-2	5	NC	15	NC	1
578			min	-.003	2	-.117	1	0	12	-4.697e-3	1	459.63	1	3189.017	4
579		5	max	.007	3	.096	3	.797	4	1.069e-2	5	9526.033	15	NC	1
580			min	-.003	2	-.232	1	0	12	-9.677e-3	1	330.24	1	2683.612	4
581		6	max	.007	3	.15	3	.761	4	1.083e-2	3	7521.06	15	NC	1
582			min	-.003	2	-.343	1	0	12	-1.466e-2	1	259.16	1	2372.1	4
583		7	max	.007	3	.201	3	.724	4	1.441e-2	3	6338.129	15	NC	1
584			min	-.003	2	-.443	1	0	1	-1.964e-2	1	217.318	1	2139.142	4
585		8	max	.007	3	.244	3	.688	4	1.799e-2	3	5638.564	15	NC	1
586			min	-.003	2	-.523	1	-.001	1	-2.462e-2	1	192.621	1	1931.737	4
587		9	max	.006	3	.272	3	.652	4	1.817e-2	3	5272.87	15	NC	1
588			min	-.003	2	-.573	1	0	12	-2.704e-2	1	179.764	1	1762.343	4
589		10	max	.006	3	.283	3	.611	4	1.607e-2	3	5161.182	15	NC	1
590			min	-.003	2	-.589	1	0	1	-2.775e-2	1	175.904	1	1726.541	4
591		11	max	.006	3	.276	3	.567	4	1.397e-2	3	5272.671	15	NC	1
592			min	-.003	2	-.572	1	0	1	-2.846e-2	1	179.984	1	1772.87	4
593		12	max	.006	3	.253	3	.52	4	1.176e-2	3	5638.204	15	NC	1
594			min	-.003	2	-.521	1	0	12	-2.68e-2	1	193.3	1	1880.422	4
595		13	max	.006	3	.216	3	.465	4	9.408e-3	3	6337.616	15	NC	1
596			min	-.003	2	-.44	1	0	12	-2.159e-2	1	218.979	1	2258.808	4
597		14	max	.006	3	.168	3	.405	4	7.054e-3	3	7520.355	15	NC	1
598			min	-.003	2	-.339	1	-.003	1	-1.639e-2	1	262.713	1	3163.207	5
599		15	max	.006	3	.114	3	.343	4	6.83e-3	5	9525.043	15	NC	1
600			min	-.003	2	-.226	1	-.008	1	-1.119e-2	1	337.528	1	5569.337	5
601		16	max	.005	3	.058	3	.283	4	9.192e-3	5	NC	15	NC	1
602			min	-.003	2	-.111	1	-.011	1	-5.989e-3	1	474.871	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
603		17	max	.005	3	.003	3	.229	4	1.161e-2	4	NC	5	NC	1
604			min	-.003	2	-.005	2	-.012	1	-7.866e-4	1	765.525	1	NC	1
605		18	max	.005	3	.087	1	.185	4	5.535e-3	5	NC	5	NC	1
606			min	-.003	2	-.045	3	-.009	1	-8.319e-3	1	1609.987	1	NC	1
607		19	max	.005	3	.17	1	.15	4	5.294e-3	3	NC	1	NC	1
608			min	-.003	2	-.091	3	0	12	-1.608e-2	1	NC	1	NC	1

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 4.00 x 0.28

<Figure 1>



<Figure 2>

Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	1020.0	27.0	565.0	565.6
Sum	1020.0	27.0	565.0	565.6

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 1020
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	5.247	10215

$\phi N_{cb} = \phi (A_{Nc} / A_{Nco}) \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-4)

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cb} (lb)
220.36	247.75	0.967	1.00	1.000	10215	0.65	5710

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_a = \phi (A_{Na} / A_{Na0}) \Psi_{ed,Na} \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16a)

A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	ϕ	ϕN_a (lb)
109.66	109.66	1.000	1.000	9755	0.55	5365

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in y-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cby} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cby} (lb)
192.89	220.50	0.925	1.000	1.000	6947	0.70	3934

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cbx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbx} (lb)
165.27	278.72	0.878	1.000	1.000	8282	0.70	3018

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
192.89	220.50	1.000	1.000	1.000	6947	0.70	8508

Shear parallel to edge in y-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cby} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cby} (lb)
165.27	278.72	1.000	1.000	1.000	8282	0.70	6875

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cp} = \phi \min|k_{cp}N_a\,;\, k_{cp}N_{cb}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\,\Psi_{p,Na}N_{a0}\,;\, k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ed,N}\,\Psi_{c,N}\,\Psi_{cp,N}N_b|$ (Eq. D-30a)

k_{cp}	A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	109.66	109.66	1.000	1.000	9755	9755

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ	ϕV_{cp} (lb)
220.36	247.75	0.967	1.000	1.000	10215	8785	0.70	12298

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, ϕN_n (lb)	Ratio	Status
Steel	1020	6071	0.17	Pass
Concrete breakout	1020	5710	0.18	Pass
Adhesive	**1020**	**5365**	**0.19**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, ϕV_n (lb)	Ratio	Status
Steel	**566**	**3156**	**0.18**	**Pass (Governs)**
T Concrete breakout y+	565	3934	0.14	Pass
T Concrete breakout x+	27	3018	0.01	Pass
|| Concrete breakout y+	27	8508	0.00	Pass
|| Concrete breakout x+	565	6875	0.08	Pass
Concrete breakout, combined	-	-	0.14	Pass
Pryout	566	12298	0.05	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status
Sec. D.7.1	0.19	0.00	19.0 %	1.0	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 7.00 x 0.28

<Figure 1>



<Figure 2>



Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	2495.5	1558.5	0.0	1558.5
2	2495.5	1558.5	0.0	1558.5
Sum	4991.0	3117.0	0.0	3117.0

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 4991
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	6.000	12492

$\phi N_{cbg} = \phi (A_{Nc} / A_{Nco}) \Psi_{ec,N} \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-5)

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cbg} (lb)
378.00	324.00	1.000	0.972	1.00	1.000	12492	0.65	9208

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_{ag} = \phi (A_{Na} / A_{Na0}) \Psi_{ed,Na} \Psi_{g,Na} \Psi_{ec,Na} \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16b)

A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0}(lb)	ϕ	ϕN_{ag} (lb)
158.66	109.66	1.000	1.043	1.000	1.000	9755	0.55	8093

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	12.00	15593

$\phi V_{cbgx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ec,V}\Psi_{ed,V}\Psi_{c,V}\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-22)

A_{Vc} (in²)	A_{Vco} (in²)	$\Psi_{ec,V}$	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbgx} (lb)
378.00	648.00	1.000	0.836	1.000	1.000	15593	0.70	5323

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	8.16	8744

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\Psi_{c,V}\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in²)	A_{Vco} (in²)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
299.64	299.64	1.000	1.000	1.000	8744	0.70	12241

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cpg} = \phi \min|k_{cp}N_{ag}\,;\, k_{cp}N_{cbg}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\Psi_{g,Na}\Psi_{ec,Na}\Psi_{p,Na}N_{a0}\,;\, k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ec,N}\Psi_{ed,N}\Psi_{c,N}\Psi_{cp,N}N_b|$ (Eq. D-30b)

k_{cp}	A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	158.66	109.66	1.000	1.043	1.000	1.000	9755	14715

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ
378.00	324.00	1.000	0.972	1.000	1.000	12492	14166	0.70

ϕV_{cpg} (lb)
19833

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, øN_n (lb)	Ratio	Status
Steel	2496	6071	0.41	Pass
Concrete breakout	4991	9208	0.54	Pass
Adhesive	**4991**	**8093**	**0.62**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, øV_n (lb)	Ratio	Status
Steel	1559	3156	0.49	Pass
T Concrete breakout x+	**3117**	**5323**	**0.59**	**Pass (Governs)**

|| Concrete breakout y-	**1559**	**12241**	**0.13**	**Pass (Governs)**
Pryout	3117	19833	0.16	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status
Sec. D.7.3	0.62	0.59	120.2 %	1.2	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.