

Schletter, Inc.		25° Tilt w/o Seismic Design
HCV	Standard PVMini Racking System	
	Representative Calculations - ASCE 7-05	

1. INTRODUCTION

1.1 Project Description

The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. PVMini ground mount system.

1.2 Construction

Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to aluminum struts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

	Maximum		Minimum	
Height =	1700	mm	1550	mm
Width =	1050	mm	970	mm
Dead Load =	3.00	psf	1.75	psf

Modules Per Row =	1
Module Tilt =	25°
Maximum Height Above Grade =	3 ft



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

1.3 Technical Codes

- ASCE 7-05 - Chapter 6, Wind Loads
- ASCE 7-05 - Chapter 7, Snow Loads
- ASCE 7-05 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2003, 2006, 2009
- Aluminum Design Manual, Eighth Edition, 2005

2. LOAD ACTIONS

2.1 Permanent Loads

g_{MAX} =	3.00	psf	*Self-weight of the PV modules.*
g_{MIN} =	1.75	psf	

2.2 Snow Loads

Ground Snow Load, P_g =	30.00	psf	
Sloped Roof Snow Load, P_s =	18.56	psf	*(ASCE 7-05, Eq. 7-2)*
I_s =	1.00		
C_s =	0.82		
C_e =	0.90		
C_t =	1.20		

2.3 Wind Loads

Design Wind Speed, V =	100	mph	Exposure Category = C
Height ≤	15	ft	Importance Category = II

Peak Velocity Pressure, q_z =	15.70	psf	*Including the gust factor, G=0.85. (ASCE 7-05, Eq. 6-15)*

Pressure Coefficients

$Cf+_{TOP}$ =	1.1	*(Pressure)*	*Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0611-1e. Negative forces are applied away from the surface.*
$Cf+_{BOTTOM}$ =	1.7		
$Cf-_{TOP}$ =	-2.2	*(Suction)*	
$Cf-_{BOTTOM}$ =	-1		

2.4 Seismic Loads - N/A

S_S =	0.00	R =	1.25
S_{DS} =	0.00	C_S =	0
S_1 =	0.00	ρ =	1.3
S_{D1} =	0.00	Ω =	1.25
T_a =	0.00	C_d =	1.25

ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.8W
1.2D + 1.6W + 0.5S
0.9D + 1.6W [M]
1.54D + 1.3E + 0.2S [R]
0.56D + 1.3E [R]
1.54D + 1.25E + 0.2S [O]
0.56D + 1.25E [O]

(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S
1.0D + 1.0W
1.0D + 0.75L + 0.75W + 0.75S
0.6D + 1.0W [M]
1.238D + 0.875E [O]
1.1785D + 0.65625E + 0.75S [O]
0.362D + 0.875E [O]

(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)

[M] *Uses the minimum allowable module dead load.*
[R] *Include redundancy factor of 1.3.*
[O] *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location
M13	Top
M16	Bottom

Girders	Location
M1	Outer
M5	Inner
M9	Outer

Front Struts	Location
M4	Outer
M8	Inner
M12	Outer

Diagonal Struts	Location
M3	Outer
M7	Inner
M11	Outer

Rear Struts	Location
M2	Outer
M6	Inner
M10	Outer

Bracing
M15
M16A

Front Reactions	Location
N7	Outer
N15	Inner
N23	Outer

Rear Reactions	Location
N8	Outer
N16	Inner
N24	Outer

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type =	**ProfiPlus**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	72	in
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	28.91	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	28.47	ksi
S_y =	0.51	in^3
S_x =	0.37	in^3
E =	10100	ksi
I_y =	0.60	in^4
I_x =	0.29	in^4
A =	0.90	in^2
g =	1.08	lbs/ft
M_y =	0.634	k-ft
M_z =	0.135	k-ft
$M_{y\ allowable}$ =	1.230	k-ft
$M_{z\ allowable}$ =	0.871	k-ft
Utilization =	67%	



4.2 Girder Design

Loads from purlins are transferred using an inclined girder, which is connected to a set of aluminum struts. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type =	**Flex Profi**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	33.78	in
$\Phi F_{ty\ AXIAL}$ =	14.29	ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	29.36	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	13.46	ksi
S_y =	0.59	in^3
S_x =	0.46	in^3
E =	10100	ksi
I_y =	0.88	in^4
I_x =	0.52	in^4
A =	0.89	in^2
g =	1.07	lbs/ft
M_y =	0.555	k-ft
M_z =	0.000	k-ft
P_n =	0.293	k
$M_{y\ allowable}$ =	1.441	k-ft
$M_{z\ allowable}$ =	0.513	k-ft
$P_{n\ allowable}$ =	12.764	k
Utilization =	41%	



4.3 Front Strut Design

The front aluminum strut connects a portion of the girder to the foundation. Vertical girder forces are then transferred down through the strut into the foundation. The strut is attached with single M8 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**30x30x3**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	18.00	in
$\Phi F_{ty\ AXIAL}$ =	24.52	ksi
$\Phi F_{ty\ BENDING}$ =	31.19	ksi
S_y =	0.16	in^3
S_x =	0.16	in^3
E =	10100	ksi
I_y =	0.10	in^4
I_x =	0.10	in^4
A =	0.50	in^2
g =	0.60	lbs/ft
M_y =	0.000	k-ft
M_z =	0.001	k-ft
P_n =	1.110	k
$M_{y\ allowable}$ =	0.423	k-ft
$M_{z\ allowable}$ =	0.423	k-ft
$P_{n\ allowable}$ =	12.310	k
Utilization =	9%	



4.4 Diagonal Strut Design

A diagonal aluminum strut braces the support structure. It connects at a front portion of the girder and transfers horizontal forces to the rear foundation connection. The strut is attached with single M8 bolts at each end. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Strut Type =	**30x30x3**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	46.38	in
$\Phi F_{ty\ AXIAL}$ =	7.60	ksi
$\Phi F_{ty\ BENDING}$ =	29.80	ksi
S_y =	0.16	in^3
S_x =	0.16	in^3
E =	10100	ksi
I_y =	0.10	in^4
I_x =	0.10	in^4
A =	0.50	in^2
g =	0.60	lbs/ft
M_y =	0.000	k-ft
M_z =	0.000	k-ft
P_n =	0.474	k
$M_{y\ allowable}$ =	0.404	k-ft
$M_{z\ allowable}$ =	0.404	k-ft
$P_{n\ allowable}$ =	3.814	k
Utilization =	12%	



4.5 Rear Strut Design

An aluminum strut connects the rear portion of the girder to the rear foundation connection. Both vertical and horizontal forces are transferred from the girder. The strut is attached with single M8 bolts at each end. See Appendix A.5 for detailed member calculations. Section units are in (mm).

Strut Type =	**30x30x3**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	36.18	in
$\Phi F_{ty\ AXIAL}$ =	11.59	ksi
$\Phi F_{ty\ BENDING}$ =	30.23	ksi
S_y =	0.16	in^3
S_x =	0.16	in^3
E =	10100	ksi
I_y =	0.10	in^4
I_x =	0.10	in^4
A =	0.50	in^2
g =	0.60	lbs/ft
M_y =	0.000	k-ft
M_z =	0.000	k-ft
P_n =	0.909	k
$M_{y\ allowable}$ =	0.410	k-ft
$M_{z\ allowable}$ =	0.410	k-ft
$P_{n\ allowable}$ =	5.820	k
Utilization =	16%	



4.6 Cross Brace Design

In order to resist weak side loading, aluminum cross bracing kits are provided. The cross bracing is attached at one end of a rear aluminum strut diagonally down to the bottom end of an adjacent strut. Single M10 bolts are provided at each of the cross bracing. Section units are in (mm).

Brace Type =	**1.5x0.25**	
Aluminum Type =	6061-T6	
F_{ty} =	35	ksi
Φ =	0.90	
S_y =	0.02	in^3
E =	10100	ksi
I_y =	33.25	in^4
A =	0.38	in^2
g =	0.45	lbs/ft
M_y =	0.004	k-ft
P_n =	0.057	k
$M_{y\ allowable}$ =	0.046	k-ft
$P_{n\ allowable}$ =	11.813	k
Utilization =	9%	



A cross brace kit is required every 21 bays and is to be installed in centermost bays.

5. FOUNDATION DESIGN CALCULATIONS

5.1 Helical Pile Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete foundation design.

Maximum	Front	Rear	
Tensile Load =	164.14	1699.85	k
Compressive Load =	1442.58	1232.54	k
Lateral Load =	2.91	906.00	k
Moment (Weak Axis) =	0.01	0.00	k

5.2 Design of Ballast Foundations

Ballast foundations are used to secure the racking structure in place. The foundations are checked for potential overturning and sliding. Bearing pressures applied by the racking and ballast foundations are checked against the allowable bearing pressures provided by the IBC tables 1804.2 (2003, 2006) & 1806.2 (2009).



Concrete Properties

Weight of Concrete =	145 pcf
Compressive Strength =	2500 psi
Yield Strength =	60000 psi

Overturning Check

M_O =	25277.4 in-lbs
Resisting Force Required =	842.58 lbs
S.F. =	1.67
Weight Required =	1404.30 lbs
Minimum Width =	22 in in
Weight Provided =	1993.75 lbs

Sliding

Force =	217.72 lbs
Friction =	0.4
Weight Required =	544.29 lbs
Resisting Weight =	1993.75 lbs
Additional Weight Required =	0 lbs

Cohesion

Sliding Force =	217.72 lbs
Cohesion =	130 psf
Area =	9.17 ft^2
Resisting =	996.88 lbs
Additional Weight Required =	0 lbs

Shear Key

Additional Force =	0 lbs
Lateral Bearing Pressure =	200 psf/ft
Required Depth =	0.00 ft
f'_c =	2500 psi
Length =	8 in

Footing Reinforcement

Use fiber reinforcing with (1) #5 rebar.

A minimum 60in long x 22in wide x 18in tall ballast foundation is required to resist overturning.

Use a 60in long x 22in wide x 18in tall ballast foundation to resist sliding. Friction is OK.

Use a 60in long x 22in wide x 18in tall ballast foundation. Cohesion is OK.

Shear key is not required.

Bearing Pressure

	Ballast Width			
	22 in	23 in	24 in	25 in
P_{ftg} = (145 pcf)(5 ft)(1.5 ft)(1.83 ft) =	1994 lbs	2084 lbs	2175 lbs	2266 lbs

ASD LC	1.0D + 1.0S				1.0D + 1.0W				1.0D + 0.75L + 0.75W + 0.75S				0.6D + 1.0W			
Width	22 in	23 in	24 in	25 in	22 in	23 in	24 in	25 in	22 in	23 in	24 in	25 in	22 in	23 in	24 in	25 in
F_A	524 lbs	524 lbs	524 lbs	524 lbs	469 lbs	469 lbs	469 lbs	469 lbs	701 lbs	701 lbs	701 lbs	701 lbs	-77 lbs	-77 lbs	-77 lbs	-77 lbs
F_B	376 lbs	376 lbs	376 lbs	376 lbs	511 lbs	511 lbs	511 lbs	511 lbs	633 lbs	633 lbs	633 lbs	633 lbs	-816 lbs	-816 lbs	-816 lbs	-816 lbs
F_V	53 lbs	53 lbs	53 lbs	53 lbs	392 lbs	392 lbs	392 lbs	392 lbs	330 lbs	330 lbs	330 lbs	330 lbs	-435 lbs	-435 lbs	-435 lbs	-435 lbs
P_{total}	2893 lbs	2984 lbs	3075 lbs	3165 lbs	2973 lbs	3064 lbs	3154 lbs	3245 lbs	3328 lbs	3419 lbs	3510 lbs	3600 lbs	304 lbs	358 lbs	412 lbs	467 lbs
M	369 lbs-ft	369 lbs-ft	369 lbs-ft	369 lbs-ft	532 lbs-ft	532 lbs-ft	532 lbs-ft	532 lbs-ft	648 lbs-ft	648 lbs-ft	648 lbs-ft	648 lbs-ft	675 lbs-ft	675 lbs-ft	675 lbs-ft	675 lbs-ft
e	0.13 ft	0.12 ft	0.12 ft	0.12 ft	0.18 ft	0.17 ft	0.17 ft	0.16 ft	0.19 ft	0.19 ft	0.18 ft	0.18 ft	2.22 ft	1.89 ft	1.64 ft	1.45 ft
L/6	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft
f_{min}	267.4 psf	265.2 psf	263.2 psf	261.4 psf	254.6 psf	253.0 psf	251.5 psf	250.2 psf	278.2 psf	275.6 psf	273.2 psf	270.9 psf	0.0 psf	0.0 psf	0.0 psf	0.0 psf
f_{max}	363.9 psf	357.6 psf	351.7 psf	346.4 psf	394.0 psf	386.4 psf	379.3 psf	372.8 psf	447.9 psf	437.9 psf	428.7 psf	420.3 psf	398.8 psf	202.6 psf	159.2 psf	141.7 psf

Maximum Bearing Pressure = 448 psf
Allowable Bearing Pressure = 1500 psf

Use a 60in long x 22in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Weak Side Design

Overturning Check

M_O =	218.1 ft-lbs
Resisting Force Required =	237.90 lbs
S.F. =	1.67
Weight Required =	396.49 lbs
Minimum Width =	22 in in
Weight Provided =	1993.75 lbs

A minimum 60in long x 22in wide x 18in tall ballast foundation is required to resist overturning.



Bearing Pressure

ASD LC	1.238D + 0.875E			1.1785D + 0.65625E + 0.75S			0.362D + 0.875E		
Width	22 in			22 in			22 in		
Support	Outer	Inner	Outer	Outer	Inner	Outer	Outer	Inner	Outer
F_Y	71 lbs	185 lbs	67 lbs	252 lbs	739 lbs	248 lbs	21 lbs	54 lbs	20 lbs
F_V	1 lbs	1 lbs	0 lbs	7 lbs	7 lbs	1 lbs	0 lbs	0 lbs	0 lbs
P_{total}	2539 lbs	2653 lbs	2535 lbs	2602 lbs	3088 lbs	2598 lbs	742 lbs	776 lbs	741 lbs
M	2 lbs-ft	2 lbs-ft	0 lbs-ft	13 lbs-ft	10 lbs-ft	1 lbs-ft	1 lbs-ft	1 lbs-ft	0 lbs-ft
e	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft
L/6	0.31 ft	1.83 ft	1.83 ft	1.82 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft
f_{min}	276.2 sqft	288.7 sqft	276.5 sqft	279.2 sqft	333.4 sqft	283.1 sqft	80.8 sqft	84.4 sqft	80.8 sqft
f_{max}	277.8 psf	290.1 psf	276.6 psf	288.4 psf	340.5 psf	283.7 psf	81.2 psf	84.8 psf	80.9 psf

Maximum Bearing Pressure = 340 psf
Allowable Bearing Pressure = 1500 psf

Use a 60in long x 22in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Foundation Requirements: 60in long x 22in wide x 18in tall ballast foundation and fiber reinforcing with (1) #5 rebar.

5.3 Foundation Anchors

Threaded rods are anchored to the the ballast foundations using the Simpson AT-XP epoxy solution. LRFD load results are compared to the allowable strengths of the epoxy solution. Please see the supplementary calculations provided by the Simpson Anchor Designer software.

6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of a Schletter, Inc. Klicktop connector. The reliability of calculations is uncertain due to limited standards, therefore the strength of the fasteners has been evaluated by load testing.

Fastening of Modules to Purlins

Maximum Uplifting Force	=	0.516 k
Allowable Uplift	=	1.214 k
Utilization	=	42%



Fastening of Purlins to Girders

Maximum Uplifting Force	=	1.096 k
Allowable Uplift	=	1.116 k
Utilization	=	98%



6.2 Bolted Connections

The aluminum struts connect the aluminum girder ends to custom brackets with mounting holes. Cross bracing is attached to rear struts to provide lateral stability. Single M8 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Front Strut

Maximum Axial Load	=	1.110 k
M8 Bolt Capacity	=	5.692 k
Strut Bearing Capacity	=	7.952 k
Utilization	=	19%

Rear Strut

Maximum Axial Load	=	1.166 k
M8 Bolt Capacity	=	5.692 k
Strut Bearing Capacity	=	7.952 k
Utilization	=	20%

Diagonal Strut

Maximum Axial Load	=	0.474 k
M8 Bolt Shear Capacity	=	5.692 k
Strut Bearing Capacity	=	7.952 k
Utilization	=	8%

Bracing

Maximum Axial Load	=	0.057 k
M10 Bolt Capacity	=	8.894 k
Strut Bearing Capacity	=	7.952 k
Utilization	=	1%



Bolt and bearing capacities are accounting for double shear (ASCE 8-02, Eq. 5.3.4-1). Struts under compression are shown to demonstrate the load transfer from the girder. Single M8 bolts are located at each end of the strut and are subjected to double shear.

7. SEISMIC DESIGN

7.1 Seismic Drift - N/A

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx}	=	30.83 in
Allowable Story Drift for All Other Structures, Δ	= {	$0.020h_{sx}$
		0.617 in
Max Drift, Δ_{MAX}	=	0.024 in

N/A

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **ProfiPlus**

Strong Axis:

3.4.14

L_b = 72.00 in

J = 0.255

187.484

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 28.9 ksi

3.4.16

b/t = 7.4

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φyFcy

φF_L= 33.3 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

Weak Axis:

3.4.14

L_b = 72.00 in

J = 0.255

194.691

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 28.8

3.4.16

b/t = 23.9

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.5 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 23.9

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9
m = 0.65
C_0 = 30
Cc = 30

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3
φF_L = 1.3φyFcy
φF_L = 43.2 ksi

φF_LSt = 28.9 ksi
Ix = 250988 mm^4
0.603 in^4
y = 30 mm
Sx = 0.511 in^3
M_{max}St = 1.230 k-ft

3.4.18

h/t = 7.4

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9
m = 0.65
C_0 = 20
Cc = 20

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3
φF_L = 1.3φyFcy
φF_L = 43.2 ksi

φF_LWk = 28.5 ksi
Iy = 120291 mm^4
0.289 in^4
x = 20 mm
Sy = 0.367 in^3
M_{max}Wk = 0.871 k-ft

Compression

3.4.9

b/t = 7.4
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φyFcy
φF_L = 33.3 ksi

b/t = 23.9
S1 = 12.21
S2 = 32.70
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.5 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 28.47 ksi
A = 578.06 mm^2
0.90 in^2
P_{max} = 25.51 kips

A.2 Design of Aluminum Girders - Aluminum Design Manual, 2005 Edition

Girder = **Flex Profi**

Strong Axis:

3.4.11

L_b = 33.78 in
ry = 1.374
Cb = 1.08
23.7085

$$S1 = \frac{1.2(Bc - \frac{\theta_y}{\theta_b} Fcy)}{Dc}$$

S1 = 1.37733

$$S2 = 1.2C_c$$

S2 = 79.2
φF_L= φb[Bc-Dc*Lb/(1.2*ry*√(Cb))
φF_L= 29.4 ksi

3.4.15

N/A for Strong Direction

3.4.16

b/t = 4.29

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L= φyFcy
φF_L= 33.3 ksi

3.4.16

N/A for Strong Direction

Weak Axis:

3.4.11

L_b = 33.78 in
ry = 1.374
Cb = 1.08
24.5845

$$S1 = \frac{1.2(Bc - \frac{\theta_y}{\theta_b} Fcy)}{Dc}$$

S1 = 1.37733

$$S2 = 1.2C_c$$

S2 = 79.2
φF_L= φb[Bc-Dc*Lb/(1.2*ry*√(Cb))
φF_L= 29.4 ksi

3.4.15

b/t = 24.46

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{5.1Dp}$$

S1 = 3.8

$$S2 = \frac{k_1 Bp}{5.1Dp}$$

S2 = 14.7
F_{UT}= (φbk2*√(BpE))/(5.1b/t)
F_{UT}= 9.4 ksi

3.4.16

N/A for Weak Direction

3.4.16

b/t = 24.46

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
F_{ST}= φb[Bp-1.6Dp*b/t]
F_{ST}= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.16.2

N/A for Strong Direction

3.4.16.2

b/t = 24.46

t = 2.6

ds = 6.05

rs = 3.49

S = 21.70

ρst = 0.22

F_{UT}= 9.37

F_{ST}= 28.24

φF_L= Fut + (Fst - Fut)ρst < Fst

φF_L= 13.5 ksi

3.4.18

h/t = 24.46

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 34.4

m = 0.70

C_0 = 34.23

Cc = 37.77

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 72.1

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 29.4 ksi

Ix = 364470 mm^4

0.876 in^4

y = 37.77 mm

Sx = 0.589 in^3

$M_{max}St$ = 1.441 k-ft

3.4.18

h/t = 4.29

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 29

Cc = 29

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 13.5 ksi

Iy = 217168 mm^4

0.522 in^4

x = 29 mm

Sy = 0.457 in^3

$M_{max}Wk$ = 0.513 k-ft

Compression

3.4.7

λ = 0.46067

r = 1.374 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.90326

φF_L= φcc(Bc-Dc*λ)

φF_L= 30.1251 ksi

3.4.8

b/t = 24.46
S1 = 3.83
S2 = 10.30
φF_L = (φck2*√(BpE))/(5.1b/t)
φF_L = 10.4 ksi

3.4.9

b/t = 4.29
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φyFcy
φF_L = 33.3 ksi

b/t = 24.46
S1 = 12.21
S2 = 32.70
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.9.1

b/t = 24.46
t = 2.6
ds = 6.05
rs = 3.49
S = 21.70
ρst = 0.22
F_{UT} = 10.43
F_{ST} = 28.24
φF_L = Fut + (Fst - Fut)ρst < Fst
φF_L = 14.3 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 14.29 ksi
A = 576.21 mm^2
0.89 in^2
P_{max} = 12.76 kips

A.3 Design of Aluminum Struts (Front) - Aluminum Design Manual, 2005 Edition

Strut = **30x30x3**

Strong Axis:

3.4.14

L_b = 18.00 in

J = 0.16

47.2194

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.2 ksi

3.4.16

b/t = 7.75

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φyFcy

φF_L= 33.3 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$S2 = C_t$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 7.75

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 15

Cc = 15

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 31.2 ksi

Ix = 39958.2 mm^4

0.096 in^4

y = 15 mm

Sx = 0.163 in^3

M_{max}St = 0.423 k-ft

Weak Axis:

3.4.14

L_b = 18.00 in

J = 0.16

47.2194

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.2

3.4.16

b/t = 7.75

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φyFcy

φF_L= 33.3 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 7.75

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 15

Cc = 15

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 31.2 ksi

Iy = 39958.2 mm^4

0.096 in^4

x = 15 mm

Sy = 0.163 in^3

M_{max}Wk = 0.423 k-ft

Compression

3.4.7

λ = 0.77182

r = 0.437 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.83792

φF_L = φcc(Bc-Dc*λ)

φF_L = 24.5226 ksi

3.4.9

b/t = 7.75

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φyFcy

φF_L = 33.3 ksi

b/t = 7.75

S1 = 12.21

S2 = 32.70

φF_L = φyFcy

φF_L = 33.3 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 24.52 ksi

A = 323.87 mm^2

0.50 in^2

P_{max} = 12.31 kips

A.4 Design of Aluminum Struts (Diagonal) - Aluminum Design Manual, 2005 Edition

Strut = **30x30x3**

Strong Axis:

3.4.14

L_b = 46.38 in

J = 0.16

121.663

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 29.8 ksi

3.4.16

b/t = 7.75

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φyFcy

φF_L= 33.3 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$S2 = C_t$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 7.75

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 15

Cc = 15

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 29.8 ksi

Ix = 39958.2 mm^4

0.096 in^4

y = 15 mm

Sx = 0.163 in^3

$M_{max}St$ = 0.404 k-ft

Weak Axis:

3.4.14

L_b = 46.38 in

J = 0.16

121.663

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 29.8

3.4.16

b/t = 7.75

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φyFcy

φF_L= 33.3 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 7.75

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 15

Cc = 15

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 33.3 ksi

Iy = 39958.2 mm^4

0.096 in^4

x = 15 mm

Sy = 0.163 in^3

$M_{max}Wk$ = 0.450 k-ft

Compression

3.4.7

λ = 1.98863

r = 0.437 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.85841

$\varphi F_L = (\varphi ccFcy)/(\lambda^2)$

φF_L = 7.59722 ksi

3.4.9

b/t = 7.75

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

$\varphi F_L = \varphi yFcy$

φF_L = 33.3 ksi

b/t = 7.75

S1 = 12.21

S2 = 32.70

$\varphi F_L = \varphi yFcy$

φF_L = 33.3 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

$\varphi F_L = \varphi yFcy$

φF_L = 33.25 ksi

φF_L = 7.60 ksi

A = 323.87 mm^2

0.50 in^2

P_{max} = 3.81 kips

A.5 Design of Aluminum Struts (Rear) - Aluminum Design Manual, 2005 Edition

Strut = **30x30x3**

Strong Axis:

3.4.14

L_b = 36.18 in

J = 0.16

94.9139

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 30.2 ksi

3.4.16

b/t = 7.75

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φyFcy

φF_L= 33.3 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$S2 = C_t$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 7.75

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 15

Cc = 15

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 30.2 ksi

Ix = 39958.2 mm^4

0.096 in^4

y = 15 mm

Sx = 0.163 in^3

M_{max}St = 0.410 k-ft

Weak Axis:

3.4.14

L_b = 36.18 in

J = 0.16

94.9139

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 30.2

3.4.16

b/t = 7.75

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φyFcy

φF_L= 33.3 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 7.75

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 15

Cc = 15

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 33.3 ksi

Iy = 39958.2 mm^4

0.096 in^4

x = 15 mm

Sy = 0.163 in^3

M_{max}Wk = 0.450 k-ft

Compression

3.4.7

λ = 1.5514
r = 0.437 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671
φcc = 0.7972
$\varphi F_L = (\varphi ccFcy)/(\lambda^2)$
φF_L = 11.5927 ksi

3.4.9

b/t = 7.75
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
$\varphi F_L = \varphi yFcy$
φF_L = 33.3 ksi

b/t = 7.75
S1 = 12.21
S2 = 32.70
$\varphi F_L = \varphi yFcy$
φF_L = 33.3 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
$\varphi F_L = \varphi yFcy$
φF_L = 33.25 ksi

φF_L = 11.59 ksi
A = 323.87 mm^2
0.50 in^2
P_{max} = 5.82 kips

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				2		
2	Dead Load, Min	DL		-1				2		
3	Snow Load	SL						2		
4	Wind Load - Pressure	WL						2		
5	Wind Load - Suction	WL						2		
6	Seismic - Lateral	EL								

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-8.366	-8.366	0	0
2	M16	Y	-8.366	-8.366	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-4.45	-4.45	0	0
2	M16	Y	-4.45	-4.45	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-51.748	-51.748	0	0
2	M16	Y	-51.748	-51.748	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	-48.164	-48.164	0	0
2	M16	y	-74.435	-74.435	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	96.328	96.328	0	0
2	M16	y	43.785	43.785	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.8W	Yes	Y		1	1.2	3	1.6	4	.8																
2	LRFD 1.2D + 1.6W + 0.5S	Yes	Y		1	1.2	3	.5	4	1.6																
3	LRFD 0.9D + 1.6W	Yes	Y		2	.9					5	1.6														
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3														
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3														
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25														
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25														
8																										
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																		
10	ASD 1.0D + 1.0W	Yes	Y		1	1			4	1																
11	ASD 1.0D + 0.75L + 0.75W + 0....	Yes	Y		1	1	3	.75	4	.75																
12	ASD 0.6D + 1.0W	Yes	Y		2	.6					5	1														
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875														
14	LATERAL - ASD 1.1785D + 0.65...	Yes	Y		1	1.1...	3	.75			6	.656														
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875														

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N8	max	174.568	2	281.533	2	0	15	0	1	0	1	0	1
2		min	-219.812	3	-398.889	3	-.122	3	0	3	0	1	0	1
3	N7	max	0	15	400.693	1	-.041	15	0	15	0	1	0	1
4		min	-.144	2	-29.51	3	-.969	1	-.002	1	0	1	0	1
5	N15	max	0	15	1109.676	1	.538	1	.001	1	0	1	0	1
6		min	-1.531	2	-126.258	3	-.436	3	0	3	0	1	0	1
7	N16	max	647.232	2	948.107	2	0	10	0	1	0	1	0	1
8		min	-696.924	3	-1307.578	3	-50.103	3	0	3	0	1	0	1
9	N23	max	0	15	400.388	1	2.238	1	.004	1	0	1	0	1
10		min	-.144	2	-29.041	3	.089	15	0	15	0	1	0	1
11	N24	max	174.821	2	285.013	2	50.496	3	.001	1	0	1	0	1
12		min	-219.999	3	-396.901	3	.009	10	0	3	0	1	0	1
13	Totals:	max	994.801	2	3366.511	1	0	3						
14		min	-1136.915	3	-2288.176	3	0	10						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M2	1	max	281.464	1	.643	4	.428	1	0	15	0	3	0	1
2			min	-360.344	3	.152	15	-.062	3	0	1	0	1	0	1
3		2	max	281.58	1	.597	4	.428	1	0	15	0	15	0	15
4			min	-360.257	3	.141	15	-.062	3	0	1	0	1	0	4
5		3	max	281.696	1	.551	4	.428	1	0	15	0	1	0	15
6			min	-360.17	3	.13	15	-.062	3	0	1	0	3	0	4
7		4	max	281.813	1	.506	4	.428	1	0	15	0	1	0	15
8			min	-360.082	3	.119	15	-.062	3	0	1	0	3	0	4
9		5	max	281.929	1	.46	4	.428	1	0	15	0	1	0	15
10			min	-359.995	3	.109	15	-.062	3	0	1	0	3	0	4
11		6	max	282.046	1	.414	4	.428	1	0	15	0	1	0	15
12			min	-359.908	3	.098	15	-.062	3	0	1	0	3	0	4
13		7	max	282.162	1	.369	4	.428	1	0	15	0	1	0	15
14			min	-359.82	3	.087	15	-.062	3	0	1	0	3	0	4
15		8	max	282.278	1	.323	4	.428	1	0	15	0	1	0	15
16			min	-359.733	3	.076	15	-.062	3	0	1	0	3	0	4
17		9	max	282.395	1	.277	4	.428	1	0	15	0	1	0	15
18			min	-359.646	3	.066	15	-.062	3	0	1	0	3	0	4
19		10	max	282.511	1	.232	4	.428	1	0	15	0	1	0	15
20			min	-359.559	3	.055	15	-.062	3	0	1	0	3	0	4
21		11	max	282.628	1	.186	4	.428	1	0	15	0	1	0	15
22			min	-359.471	3	.044	15	-.062	3	0	1	0	3	0	4
23		12	max	282.744	1	.14	4	.428	1	0	15	0	1	0	15
24			min	-359.384	3	.033	15	-.062	3	0	1	0	3	0	4
25		13	max	282.86	1	.101	2	.428	1	0	15	0	1	0	15
26			min	-359.297	3	.018	12	-.062	3	0	1	0	3	0	4
27		14	max	282.977	1	.065	2	.428	1	0	15	0	1	0	15
28			min	-359.209	3	-.002	3	-.062	3	0	1	0	3	0	4
29		15	max	283.093	1	.03	2	.428	1	0	15	0	1	0	15
30			min	-359.122	3	-.029	3	-.062	3	0	1	0	3	0	4
31		16	max	283.21	1	-.006	2	.428	1	0	15	0	1	0	15
32			min	-359.035	3	-.056	3	-.062	3	0	1	0	3	0	4
33		17	max	283.326	1	-.02	15	.428	1	0	15	.001	1	0	15
34			min	-358.947	3	-.088	4	-.062	3	0	1	0	3	0	4
35		18	max	283.442	1	-.031	15	.428	1	0	15	.001	1	0	15
36			min	-358.86	3	-.134	4	-.062	3	0	1	0	3	0	4
37		19	max	283.559	1	-.042	15	.428	1	0	15	.001	1	0	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
38			min	-358.773	3	-.179	4	-.062	3	0	1	0	3	0	4
39	M3	1	max	118.108	2	1.778	4	-.015	15	0	15	.001	1	0	4
40			min	-127.599	3	.418	15	-.401	1	0	1	0	15	0	15
41		2	max	118.039	2	1.601	4	-.015	15	0	15	.001	1	0	2
42			min	-127.65	3	.377	15	-.401	1	0	1	0	15	0	12
43		3	max	117.971	2	1.423	4	-.015	15	0	15	.001	1	0	2
44			min	-127.702	3	.335	15	-.401	1	0	1	0	15	0	3
45		4	max	117.902	2	1.246	4	-.015	15	0	15	.001	1	0	15
46			min	-127.753	3	.293	15	-.401	1	0	1	0	15	0	4
47		5	max	117.834	2	1.069	4	-.015	15	0	15	0	1	0	15
48			min	-127.805	3	.252	15	-.401	1	0	1	0	15	0	4
49		6	max	117.765	2	.892	4	-.015	15	0	15	0	1	0	15
50			min	-127.856	3	.21	15	-.401	1	0	1	0	15	0	4
51		7	max	117.696	2	.714	4	-.015	15	0	15	0	1	0	15
52			min	-127.907	3	.168	15	-.401	1	0	1	0	15	0	4
53		8	max	117.628	2	.537	4	-.015	15	0	15	0	1	0	15
54			min	-127.959	3	.127	15	-.401	1	0	1	0	15	-.001	4
55		9	max	117.559	2	.36	4	-.015	15	0	15	0	1	0	15
56			min	-128.01	3	.085	15	-.401	1	0	1	0	15	-.001	4
57		10	max	117.491	2	.183	4	-.015	15	0	15	0	1	0	15
58			min	-128.062	3	.043	15	-.401	1	0	1	0	15	-.001	4
59		11	max	117.422	2	.026	2	-.015	15	0	15	0	1	0	15
60			min	-128.113	3	-.021	3	-.401	1	0	1	0	15	-.001	4
61		12	max	117.353	2	-.04	15	-.015	15	0	15	0	1	0	15
62			min	-128.165	3	-.172	4	-.401	1	0	1	0	15	-.001	4
63		13	max	117.285	2	-.082	15	-.015	15	0	15	0	1	0	15
64			min	-128.216	3	-.349	4	-.401	1	0	1	0	15	-.001	4
65		14	max	117.216	2	-.123	15	-.015	15	0	15	0	1	0	15
66			min	-128.268	3	-.526	4	-.401	1	0	1	0	15	-.001	4
67		15	max	117.148	2	-.165	15	-.015	15	0	15	0	1	0	15
68			min	-128.319	3	-.703	4	-.401	1	0	1	0	10	0	4
69		16	max	117.079	2	-.207	15	-.015	15	0	15	0	15	0	15
70			min	-128.371	3	-.88	4	-.401	1	0	1	0	1	0	4
71		17	max	117.01	2	-.248	15	-.015	15	0	15	0	15	0	15
72			min	-128.422	3	-1.058	4	-.401	1	0	1	0	1	0	4
73		18	max	116.942	2	-.29	15	-.015	15	0	15	0	15	0	15
74			min	-128.473	3	-1.235	4	-.401	1	0	1	0	1	0	4
75		19	max	116.873	2	-.332	15	-.015	15	0	15	0	15	0	1
76			min	-128.525	3	-1.412	4	-.401	1	0	1	0	1	0	1
77	M4	1	max	399.528	1	0	1	-.041	15	0	1	0	3	0	1
78			min	-30.383	3	0	1	-1.039	1	0	1	0	2	0	1
79		2	max	399.593	1	0	1	-.041	15	0	1	0	15	0	1
80			min	-30.335	3	0	1	-1.039	1	0	1	0	1	0	1
81		3	max	399.658	1	0	1	-.041	15	0	1	0	15	0	1
82			min	-30.286	3	0	1	-1.039	1	0	1	0	1	0	1
83		4	max	399.722	1	0	1	-.041	15	0	1	0	15	0	1
84			min	-30.238	3	0	1	-1.039	1	0	1	0	1	0	1
85		5	max	399.787	1	0	1	-.041	15	0	1	0	15	0	1
86			min	-30.189	3	0	1	-1.039	1	0	1	0	1	0	1
87		6	max	399.852	1	0	1	-.041	15	0	1	0	15	0	1
88			min	-30.141	3	0	1	-1.039	1	0	1	0	1	0	1
89		7	max	399.917	1	0	1	-.041	15	0	1	0	15	0	1
90			min	-30.092	3	0	1	-1.039	1	0	1	0	1	0	1
91		8	max	399.981	1	0	1	-.041	15	0	1	0	15	0	1
92			min	-30.044	3	0	1	-1.039	1	0	1	0	1	0	1
93		9	max	400.046	1	0	1	-.041	15	0	1	0	15	0	1
94			min	-29.995	3	0	1	-1.039	1	0	1	0	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
95		10	max	400.111	1	0	1	-.041	15	0	1	0	15	0	1
96			min	-29.947	3	0	1	-1.039	1	0	1	0	1	0	1
97		11	max	400.175	1	0	1	-.041	15	0	1	0	15	0	1
98			min	-29.898	3	0	1	-1.039	1	0	1	0	1	0	1
99		12	max	400.24	1	0	1	-.041	15	0	1	0	15	0	1
100			min	-29.85	3	0	1	-1.039	1	0	1	-.001	1	0	1
101		13	max	400.305	1	0	1	-.041	15	0	1	0	15	0	1
102			min	-29.801	3	0	1	-1.039	1	0	1	-.001	1	0	1
103		14	max	400.37	1	0	1	-.041	15	0	1	0	15	0	1
104			min	-29.752	3	0	1	-1.039	1	0	1	-.001	1	0	1
105		15	max	400.434	1	0	1	-.041	15	0	1	0	15	0	1
106			min	-29.704	3	0	1	-1.039	1	0	1	-.001	1	0	1
107		16	max	400.499	1	0	1	-.041	15	0	1	0	15	0	1
108			min	-29.655	3	0	1	-1.039	1	0	1	-.001	1	0	1
109		17	max	400.564	1	0	1	-.041	15	0	1	0	15	0	1
110			min	-29.607	3	0	1	-1.039	1	0	1	-.002	1	0	1
111		18	max	400.628	1	0	1	-.041	15	0	1	0	15	0	1
112			min	-29.558	3	0	1	-1.039	1	0	1	-.002	1	0	1
113		19	max	400.693	1	0	1	-.041	15	0	1	0	15	0	1
114			min	-29.51	3	0	1	-1.039	1	0	1	-.002	1	0	1
115	M6	1	max	907.19	1	.642	4	.197	1	0	3	0	3	0	1
116			min	-1165.83	3	.151	15	-.177	3	0	10	0	1	0	1
117		2	max	907.307	1	.597	4	.197	1	0	3	0	3	0	15
118			min	-1165.743	3	.141	15	-.177	3	0	10	0	1	0	4
119		3	max	907.423	1	.551	4	.197	1	0	3	0	3	0	15
120			min	-1165.656	3	.13	15	-.177	3	0	10	0	1	0	4
121		4	max	907.54	1	.505	4	.197	1	0	3	0	3	0	15
122			min	-1165.569	3	.119	15	-.177	3	0	10	0	10	0	4
123		5	max	907.656	1	.46	4	.197	1	0	3	0	11	0	15
124			min	-1165.481	3	.108	15	-.177	3	0	10	0	10	0	4
125		6	max	907.772	1	.414	2	.197	1	0	3	0	1	0	15
126			min	-1165.394	3	.098	15	-.177	3	0	10	0	3	0	4
127		7	max	907.889	1	.379	2	.197	1	0	3	0	1	0	15
128			min	-1165.307	3	.083	12	-.177	3	0	10	0	3	0	4
129		8	max	908.005	1	.343	2	.197	1	0	3	0	1	0	15
130			min	-1165.219	3	.065	12	-.177	3	0	10	0	3	0	4
131		9	max	908.122	1	.308	2	.197	1	0	3	0	1	0	15
132			min	-1165.132	3	.047	12	-.177	3	0	10	0	3	0	4
133		10	max	908.238	1	.272	2	.197	1	0	3	0	1	0	15
134			min	-1165.045	3	.03	12	-.177	3	0	10	0	3	0	4
135		11	max	908.355	1	.236	2	.197	1	0	3	0	1	0	15
136			min	-1164.957	3	.012	3	-.177	3	0	10	0	3	0	2
137		12	max	908.471	1	.201	2	.197	1	0	3	0	1	0	12
138			min	-1164.87	3	-.015	3	-.177	3	0	10	0	3	0	2
139		13	max	908.587	1	.165	2	.197	1	0	3	0	1	0	12
140			min	-1164.783	3	-.042	3	-.177	3	0	10	0	3	0	2
141		14	max	908.704	1	.13	2	.197	1	0	3	0	1	0	12
142			min	-1164.696	3	-.068	3	-.177	3	0	10	0	3	0	2
143		15	max	908.82	1	.094	2	.197	1	0	3	0	1	0	12
144			min	-1164.608	3	-.095	3	-.177	3	0	10	0	3	0	2
145		16	max	908.937	1	.058	2	.197	1	0	3	0	1	0	12
146			min	-1164.521	3	-.122	3	-.177	3	0	10	0	3	0	2
147		17	max	909.053	1	.023	2	.197	1	0	3	0	1	0	12
148			min	-1164.434	3	-.148	3	-.177	3	0	10	0	3	0	2
149		18	max	909.169	1	-.013	2	.197	1	0	3	0	1	0	12
150			min	-1164.346	3	-.175	3	-.177	3	0	10	0	3	0	2
151		19	max	909.286	1	-.042	15	.197	1	0	3	0	1	0	12

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
152			min	-1164.259	3	-.202	3	-.177	3	0	10	0	3	0	2
153	M7	1	max	473.885	2	1.78	4	.01	3	0	1	0	1	0	2
154			min	-388.375	3	.419	15	-.01	2	0	3	0	3	0	12
155		2	max	473.816	2	1.602	4	.01	3	0	1	0	1	0	2
156			min	-388.426	3	.377	15	-.01	2	0	3	0	3	0	3
157		3	max	473.747	2	1.425	4	.01	3	0	1	0	1	0	2
158			min	-388.478	3	.335	15	-.01	2	0	3	0	3	0	3
159		4	max	473.679	2	1.248	4	.01	3	0	1	0	1	0	2
160			min	-388.529	3	.294	15	-.01	2	0	3	0	3	0	3
161		5	max	473.61	2	1.071	4	.01	3	0	1	0	1	0	15
162			min	-388.58	3	.252	15	-.01	2	0	3	0	3	0	3
163		6	max	473.542	2	.894	4	.01	3	0	1	0	1	0	15
164			min	-388.632	3	.21	15	-.01	2	0	3	0	3	0	4
165		7	max	473.473	2	.716	4	.01	3	0	1	0	1	0	15
166			min	-388.683	3	.169	15	-.01	2	0	3	0	3	0	4
167		8	max	473.404	2	.539	4	.01	3	0	1	0	1	0	15
168			min	-388.735	3	.127	15	-.01	2	0	3	0	3	-.001	4
169		9	max	473.336	2	.362	4	.01	3	0	1	0	1	0	15
170			min	-388.786	3	.085	15	-.01	2	0	3	0	3	-.001	4
171		10	max	473.267	2	.222	2	.01	3	0	1	0	1	0	15
172			min	-388.838	3	.019	12	-.01	2	0	3	0	3	-.001	4
173		11	max	473.199	2	.084	2	.01	3	0	1	0	1	0	15
174			min	-388.889	3	-.08	3	-.01	2	0	3	0	3	-.001	4
175		12	max	473.13	2	-.04	15	.01	3	0	1	0	1	0	15
176			min	-388.941	3	-.183	3	-.01	2	0	3	0	3	-.001	4
177		13	max	473.061	2	-.081	15	.01	3	0	1	0	1	0	15
178			min	-388.992	3	-.347	4	-.01	2	0	3	0	3	-.001	4
179		14	max	472.993	2	-.123	15	.01	3	0	1	0	1	0	15
180			min	-389.044	3	-.524	4	-.01	2	0	3	0	3	-.001	4
181		15	max	472.924	2	-.165	15	.01	3	0	1	0	1	0	15
182			min	-389.095	3	-.701	4	-.01	2	0	3	0	3	0	4
183		16	max	472.856	2	-.206	15	.01	3	0	1	0	1	0	15
184			min	-389.146	3	-.878	4	-.01	2	0	3	0	3	0	4
185		17	max	472.787	2	-.248	15	.01	3	0	1	0	1	0	15
186			min	-389.198	3	-1.056	4	-.01	2	0	3	0	3	0	4
187		18	max	472.718	2	-.29	15	.01	3	0	1	0	1	0	15
188			min	-389.249	3	-1.233	4	-.01	2	0	3	0	3	0	4
189		19	max	472.65	2	-.331	15	.01	3	0	1	0	1	0	1
190			min	-389.301	3	-1.41	4	-.01	2	0	3	0	3	0	1
191	M8	1	max	1108.511	1	0	1	.656	1	0	1	0	10	0	1
192			min	-127.132	3	0	1	-.427	3	0	1	0	1	0	1
193		2	max	1108.576	1	0	1	.656	1	0	1	0	1	0	1
194			min	-127.083	3	0	1	-.427	3	0	1	0	3	0	1
195		3	max	1108.64	1	0	1	.656	1	0	1	0	1	0	1
196			min	-127.035	3	0	1	-.427	3	0	1	0	3	0	1
197		4	max	1108.705	1	0	1	.656	1	0	1	0	1	0	1
198			min	-126.986	3	0	1	-.427	3	0	1	0	3	0	1
199		5	max	1108.77	1	0	1	.656	1	0	1	0	1	0	1
200			min	-126.938	3	0	1	-.427	3	0	1	0	3	0	1
201		6	max	1108.834	1	0	1	.656	1	0	1	0	1	0	1
202			min	-126.889	3	0	1	-.427	3	0	1	0	3	0	1
203		7	max	1108.899	1	0	1	.656	1	0	1	0	1	0	1
204			min	-126.841	3	0	1	-.427	3	0	1	0	3	0	1
205		8	max	1108.964	1	0	1	.656	1	0	1	0	1	0	1
206			min	-126.792	3	0	1	-.427	3	0	1	0	3	0	1
207		9	max	1109.028	1	0	1	.656	1	0	1	0	1	0	1
208			min	-126.743	3	0	1	-.427	3	0	1	0	3	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
209		10	max	1109.093	1	0	1	.656	1	0	1	0	1	0	1
210			min	-126.695	3	0	1	-.427	3	0	1	0	3	0	1
211		11	max	1109.158	1	0	1	.656	1	0	1	0	1	0	1
212			min	-126.646	3	0	1	-.427	3	0	1	0	3	0	1
213		12	max	1109.223	1	0	1	.656	1	0	1	0	1	0	1
214			min	-126.598	3	0	1	-.427	3	0	1	0	3	0	1
215		13	max	1109.287	1	0	1	.656	1	0	1	0	1	0	1
216			min	-126.549	3	0	1	-.427	3	0	1	0	3	0	1
217		14	max	1109.352	1	0	1	.656	1	0	1	0	1	0	1
218			min	-126.501	3	0	1	-.427	3	0	1	0	3	0	1
219		15	max	1109.417	1	0	1	.656	1	0	1	0	1	0	1
220			min	-126.452	3	0	1	-.427	3	0	1	0	3	0	1
221		16	max	1109.481	1	0	1	.656	1	0	1	0	1	0	1
222			min	-126.404	3	0	1	-.427	3	0	1	0	3	0	1
223		17	max	1109.546	1	0	1	.656	1	0	1	0	1	0	1
224			min	-126.355	3	0	1	-.427	3	0	1	0	3	0	1
225		18	max	1109.611	1	0	1	.656	1	0	1	0	1	0	1
226			min	-126.307	3	0	1	-.427	3	0	1	0	3	0	1
227		19	max	1109.676	1	0	1	.656	1	0	1	.001	1	0	1
228			min	-126.258	3	0	1	-.427	3	0	1	0	3	0	1
229	M10	1	max	284.46	1	.636	4	-.004	15	0	1	0	1	0	1
230			min	-333.864	3	.151	15	-.109	1	0	3	0	3	0	1
231		2	max	284.576	1	.59	4	-.004	15	0	1	0	1	0	15
232			min	-333.777	3	.14	15	-.109	1	0	3	0	3	0	4
233		3	max	284.693	1	.545	4	-.004	15	0	1	0	1	0	15
234			min	-333.689	3	.129	15	-.109	1	0	3	0	3	0	4
235		4	max	284.809	1	.499	4	-.004	15	0	1	0	1	0	15
236			min	-333.602	3	.118	15	-.109	1	0	3	0	3	0	4
237		5	max	284.925	1	.453	4	-.004	15	0	1	0	1	0	15
238			min	-333.515	3	.108	15	-.109	1	0	3	0	3	0	4
239		6	max	285.042	1	.408	4	-.004	15	0	1	0	1	0	15
240			min	-333.427	3	.097	15	-.109	1	0	3	0	3	0	4
241		7	max	285.158	1	.362	4	-.004	15	0	1	0	1	0	15
242			min	-333.34	3	.086	15	-.109	1	0	3	0	3	0	4
243		8	max	285.275	1	.316	4	-.004	15	0	1	0	1	0	15
244			min	-333.253	3	.075	15	-.109	1	0	3	0	3	0	4
245		9	max	285.391	1	.271	4	-.004	15	0	1	0	1	0	15
246			min	-333.165	3	.065	15	-.109	1	0	3	0	3	0	4
247		10	max	285.507	1	.225	4	-.004	15	0	1	0	1	0	15
248			min	-333.078	3	.054	15	-.109	1	0	3	0	3	0	4
249		11	max	285.624	1	.179	4	-.004	15	0	1	0	1	0	15
250			min	-332.991	3	.043	15	-.109	1	0	3	0	3	0	4
251		12	max	285.74	1	.137	2	-.004	15	0	1	0	15	0	15
252			min	-332.904	3	.032	15	-.109	1	0	3	0	3	0	4
253		13	max	285.857	1	.101	2	-.004	15	0	1	0	15	0	15
254			min	-332.816	3	.022	15	-.109	1	0	3	0	3	0	4
255		14	max	285.973	1	.065	2	-.004	15	0	1	0	15	0	15
256			min	-332.729	3	.006	1	-.109	1	0	3	0	3	0	4
257		15	max	286.089	1	.03	2	-.004	15	0	1	0	15	0	15
258			min	-332.642	3	-.03	1	-.109	1	0	3	0	3	0	4
259		16	max	286.206	1	-.006	2	-.004	15	0	1	0	15	0	15
260			min	-332.554	3	-.065	1	-.109	1	0	3	0	3	0	4
261		17	max	286.322	1	-.021	15	-.004	15	0	1	0	15	0	15
262			min	-332.467	3	-.101	1	-.109	1	0	3	0	3	0	4
263		18	max	286.439	1	-.032	15	-.004	15	0	1	0	15	0	15
264			min	-332.38	3	-.14	4	-.109	1	0	3	0	3	0	4
265		19	max	286.555	1	-.043	15	-.004	15	0	1	0	15	0	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
266			min	-332.292	3	-.186	4	-.109	1	0	3	0	3	0	4
267	M11	1	max	117.771	2	1.782	4	.489	1	0	1	0	3	0	4
268			min	-128.217	3	.419	15	-.012	3	0	15	-.001	1	0	15
269		2	max	117.702	2	1.605	4	.489	1	0	1	0	3	0	4
270			min	-128.268	3	.377	15	-.012	3	0	15	-.001	1	0	12
271		3	max	117.634	2	1.427	4	.489	1	0	1	0	3	0	2
272			min	-128.32	3	.336	15	-.012	3	0	15	-.001	1	0	3
273		4	max	117.565	2	1.25	4	.489	1	0	1	0	3	0	15
274			min	-128.371	3	.294	15	-.012	3	0	15	-.001	1	0	3
275		5	max	117.496	2	1.073	4	.489	1	0	1	0	3	0	15
276			min	-128.423	3	.252	15	-.012	3	0	15	-.001	1	0	4
277		6	max	117.428	2	.896	4	.489	1	0	1	0	3	0	15
278			min	-128.474	3	.211	15	-.012	3	0	15	0	1	0	4
279		7	max	117.359	2	.719	4	.489	1	0	1	0	3	0	15
280			min	-128.526	3	.169	15	-.012	3	0	15	0	1	0	4
281		8	max	117.291	2	.541	4	.489	1	0	1	0	3	0	15
282			min	-128.577	3	.127	15	-.012	3	0	15	0	1	-.001	4
283		9	max	117.222	2	.364	4	.489	1	0	1	0	3	0	15
284			min	-128.628	3	.086	15	-.012	3	0	15	0	1	-.001	4
285		10	max	117.153	2	.187	4	.489	1	0	1	0	3	0	15
286			min	-128.68	3	.044	15	-.012	3	0	15	0	1	-.001	4
287		11	max	117.085	2	.026	2	.489	1	0	1	0	3	0	15
288			min	-128.731	3	-.039	3	-.012	3	0	15	0	1	-.001	4
289		12	max	117.016	2	-.039	15	.489	1	0	1	0	3	0	15
290			min	-128.783	3	-.167	4	-.012	3	0	15	0	1	-.001	4
291		13	max	116.947	2	-.081	15	.489	1	0	1	0	3	0	15
292			min	-128.834	3	-.345	4	-.012	3	0	15	0	1	-.001	4
293		14	max	116.879	2	-.123	15	.489	1	0	1	0	3	0	15
294			min	-128.886	3	-.522	4	-.012	3	0	15	0	1	-.001	4
295		15	max	116.81	2	-.164	15	.489	1	0	1	0	3	0	15
296			min	-128.937	3	-.699	4	-.012	3	0	15	0	10	0	4
297		16	max	116.742	2	-.206	15	.489	1	0	1	0	3	0	15
298			min	-128.989	3	-.876	4	-.012	3	0	15	0	10	0	4
299		17	max	116.673	2	-.248	15	.489	1	0	1	0	3	0	15
300			min	-129.04	3	-1.053	4	-.012	3	0	15	0	15	0	4
301		18	max	116.604	2	-.289	15	.489	1	0	1	0	1	0	15
302			min	-129.092	3	-1.231	4	-.012	3	0	15	0	15	0	4
303		19	max	116.536	2	-.331	15	.489	1	0	1	0	1	0	1
304			min	-129.143	3	-1.408	4	-.012	3	0	15	0	15	0	1
305	M12	1	max	399.223	1	0	1	2.396	1	0	1	0	2	0	1
306			min	-29.914	3	0	1	.089	15	0	1	0	3	0	1
307		2	max	399.288	1	0	1	2.396	1	0	1	0	1	0	1
308			min	-29.866	3	0	1	.089	15	0	1	0	15	0	1
309		3	max	399.352	1	0	1	2.396	1	0	1	0	1	0	1
310			min	-29.817	3	0	1	.089	15	0	1	0	15	0	1
311		4	max	399.417	1	0	1	2.396	1	0	1	0	1	0	1
312			min	-29.769	3	0	1	.089	15	0	1	0	15	0	1
313		5	max	399.482	1	0	1	2.396	1	0	1	0	1	0	1
314			min	-29.72	3	0	1	.089	15	0	1	0	15	0	1
315		6	max	399.546	1	0	1	2.396	1	0	1	.001	1	0	1
316			min	-29.672	3	0	1	.089	15	0	1	0	15	0	1
317		7	max	399.611	1	0	1	2.396	1	0	1	.001	1	0	1
318			min	-29.623	3	0	1	.089	15	0	1	0	15	0	1
319		8	max	399.676	1	0	1	2.396	1	0	1	.002	1	0	1
320			min	-29.575	3	0	1	.089	15	0	1	0	15	0	1
321		9	max	399.741	1	0	1	2.396	1	0	1	.002	1	0	1
322			min	-29.526	3	0	1	.089	15	0	1	0	15	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
323		10	max	399.805	1	0	1	2.396	1	0	1	.002	1	0	1
324			min	-29.478	3	0	1	.089	15	0	1	0	15	0	1
325		11	max	399.87	1	0	1	2.396	1	0	1	.002	1	0	1
326			min	-29.429	3	0	1	.089	15	0	1	0	15	0	1
327		12	max	399.935	1	0	1	2.396	1	0	1	.002	1	0	1
328			min	-29.381	3	0	1	.089	15	0	1	0	15	0	1
329		13	max	399.999	1	0	1	2.396	1	0	1	.003	1	0	1
330			min	-29.332	3	0	1	.089	15	0	1	0	15	0	1
331		14	max	400.064	1	0	1	2.396	1	0	1	.003	1	0	1
332			min	-29.284	3	0	1	.089	15	0	1	0	15	0	1
333		15	max	400.129	1	0	1	2.396	1	0	1	.003	1	0	1
334			min	-29.235	3	0	1	.089	15	0	1	0	15	0	1
335		16	max	400.194	1	0	1	2.396	1	0	1	.003	1	0	1
336			min	-29.186	3	0	1	.089	15	0	1	0	15	0	1
337		17	max	400.258	1	0	1	2.396	1	0	1	.003	1	0	1
338			min	-29.138	3	0	1	.089	15	0	1	0	15	0	1
339		18	max	400.323	1	0	1	2.396	1	0	1	.004	1	0	1
340			min	-29.089	3	0	1	.089	15	0	1	0	15	0	1
341		19	max	400.388	1	0	1	2.396	1	0	1	.004	1	0	1
342			min	-29.041	3	0	1	.089	15	0	1	0	15	0	1
343	M1	1	max	112.534	1	339.316	3	-1.766	15	0	1	.093	1	0	1
344			min	4.116	15	-281.556	1	-47.479	1	0	3	.003	15	0	3
345		2	max	112.652	1	339.126	3	-1.766	15	0	1	.083	1	.061	1
346			min	4.152	15	-281.809	1	-47.479	1	0	3	.003	15	-.074	3
347		3	max	74.047	1	5.938	9	-1.751	15	0	12	.072	1	.121	1
348			min	-5.344	10	-18.516	2	-47.284	1	0	1	.003	15	-.146	3
349		4	max	74.165	1	5.727	9	-1.751	15	0	12	.062	1	.122	1
350			min	-5.246	10	-18.77	2	-47.284	1	0	1	.002	15	-.142	3
351		5	max	74.283	1	5.516	9	-1.751	15	0	12	.051	1	.123	1
352			min	-5.147	10	-19.023	2	-47.284	1	0	1	.002	15	-.138	3
353		6	max	74.401	1	5.305	9	-1.751	15	0	12	.041	1	.123	1
354			min	-5.049	10	-19.276	2	-47.284	1	0	1	.002	15	-.134	3
355		7	max	74.519	1	5.094	9	-1.751	15	0	12	.031	1	.125	2
356			min	-4.951	10	-19.529	2	-47.284	1	0	1	.001	15	-.13	3
357		8	max	74.637	1	4.883	9	-1.751	15	0	12	.021	1	.129	2
358			min	-4.852	10	-19.782	2	-47.284	1	0	1	0	15	-.126	3
359		9	max	74.755	1	4.672	9	-1.751	15	0	12	.01	1	.134	2
360			min	-4.754	10	-20.035	2	-47.284	1	0	1	0	15	-.122	3
361		10	max	74.873	1	4.461	9	-1.751	15	0	12	.001	3	.138	2
362			min	-4.656	10	-20.288	2	-47.284	1	0	1	0	15	-.118	3
363		11	max	74.991	1	4.25	9	-1.751	15	0	12	0	3	.143	2
364			min	-4.557	10	-20.541	2	-47.284	1	0	1	-.01	1	-.114	3
365		12	max	75.109	1	4.04	9	-1.751	15	0	12	0	12	.147	2
366			min	-4.459	10	-20.794	2	-47.284	1	0	1	-.02	1	-.109	3
367		13	max	75.227	1	3.829	9	-1.751	15	0	12	-.001	12	.152	2
368			min	-4.361	10	-21.047	2	-47.284	1	0	1	-.031	1	-.105	3
369		14	max	75.345	1	3.618	9	-1.751	15	0	12	-.002	15	.156	2
370			min	-4.262	10	-21.3	2	-47.284	1	0	1	-.041	1	-.101	3
371		15	max	75.463	1	3.407	9	-1.751	15	0	12	-.002	15	.161	2
372			min	-4.164	10	-21.553	2	-47.284	1	0	1	-.051	1	-.096	3
373		16	max	86.479	2	69.2	2	-1.766	15	0	1	-.002	15	.165	2
374			min	-19.712	3	-121.3	3	-47.633	1	0	12	-.062	1	-.091	3
375		17	max	86.597	2	68.947	2	-1.766	15	0	1	-.003	15	.15	2
376			min	-19.624	3	-121.49	3	-47.633	1	0	12	-.072	1	-.065	3
377		18	max	-4.142	15	347.116	2	-1.807	15	0	3	-.003	15	.076	2
378			min	-112.613	1	-149.252	3	-48.749	1	0	2	-.083	1	-.033	3
379		19	max	-4.107	15	346.862	2	-1.807	15	0	3	-.003	15	0	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
380			min	-112.495	1	-149.442	3	-48.749	1	0	2	-.093	1	0	3
381	M5	1	max	252.742	1	1116.966	3	0	10	0	1	.005	3	0	3
382			min	6.514	12	-926.705	1	-45.11	3	0	3	0	10	0	1
383		2	max	252.86	1	1116.776	3	0	10	0	1	.001	1	.201	1
384			min	6.573	12	-926.958	1	-45.11	3	0	3	-.004	3	-.242	3
385		3	max	175.71	3	6.405	9	5.124	3	0	3	0	1	.398	1
386			min	-25.405	10	-70.219	2	-.675	1	0	1	-.014	3	-.479	3
387		4	max	175.798	3	6.194	9	5.124	3	0	3	0	1	.404	1
388			min	-25.307	10	-70.472	2	-.675	1	0	1	-.013	3	-.465	3
389		5	max	175.887	3	5.983	9	5.124	3	0	3	0	1	.41	1
390			min	-25.208	10	-70.725	2	-.675	1	0	1	-.012	3	-.451	3
391		6	max	175.975	3	5.772	9	5.124	3	0	3	0	1	.416	1
392			min	-25.11	10	-70.979	2	-.675	1	0	1	-.01	3	-.437	3
393		7	max	176.064	3	5.561	9	5.124	3	0	3	0	1	.422	1
394			min	-25.012	10	-71.232	2	-.675	1	0	1	-.009	3	-.423	3
395		8	max	176.152	3	5.35	9	5.124	3	0	3	0	1	.432	2
396			min	-24.913	10	-71.485	2	-.675	1	0	1	-.008	3	-.409	3
397		9	max	176.241	3	5.139	9	5.124	3	0	3	0	11	.448	2
398			min	-24.815	10	-71.738	2	-.675	1	0	1	-.007	3	-.394	3
399		10	max	176.329	3	4.929	9	5.124	3	0	3	0	10	.463	2
400			min	-24.717	10	-71.991	2	-.675	1	0	1	-.006	3	-.38	3
401		11	max	176.418	3	4.718	9	5.124	3	0	3	0	10	.479	2
402			min	-24.618	10	-72.244	2	-.675	1	0	1	-.005	3	-.366	3
403		12	max	176.506	3	4.507	9	5.124	3	0	3	0	10	.495	2
404			min	-24.52	10	-72.497	2	-.675	1	0	1	-.004	3	-.352	3
405		13	max	176.595	3	4.296	9	5.124	3	0	3	0	10	.51	2
406			min	-24.422	10	-72.75	2	-.675	1	0	1	-.003	3	-.337	3
407		14	max	176.683	3	4.085	9	5.124	3	0	3	0	10	.526	2
408			min	-24.323	10	-73.003	2	-.675	1	0	1	-.002	3	-.323	3
409		15	max	176.772	3	3.874	9	5.124	3	0	3	0	10	.542	2
410			min	-24.225	10	-73.256	2	-.675	1	0	1	0	1	-.308	3
411		16	max	293.314	2	298.931	2	5.093	3	0	1	0	3	.555	2
412			min	-65.354	3	-371.269	3	-.679	1	0	10	0	1	-.291	3
413		17	max	293.432	2	298.678	2	5.093	3	0	1	.001	3	.49	2
414			min	-65.265	3	-371.459	3	-.679	1	0	10	-.001	1	-.211	3
415		18	max	-7.801	12	1138.542	2	4.669	3	0	3	.002	3	.246	2
416			min	-252.907	1	-487.355	3	-.126	1	0	1	-.001	1	-.105	3
417		19	max	-7.742	12	1138.289	2	4.669	3	0	3	.003	3	0	3
418			min	-252.789	1	-487.545	3	-.126	1	0	1	-.001	1	0	2
419	M9	1	max	112.091	1	339.282	3	49.277	3	0	3	-.003	15	0	1
420			min	4.097	15	-281.554	1	2.086	15	0	1	-.092	1	0	3
421		2	max	112.209	1	339.092	3	49.277	3	0	3	-.001	12	.061	1
422			min	4.133	15	-281.807	1	2.086	15	0	1	-.081	1	-.074	3
423		3	max	74.088	1	5.913	9	46.048	1	0	1	.008	3	.121	1
424			min	-4.902	10	-18.528	2	-.538	3	0	15	-.07	1	-.146	3
425		4	max	74.206	1	5.703	9	46.048	1	0	1	.008	3	.122	1
426			min	-4.803	10	-18.781	2	-.538	3	0	15	-.06	1	-.142	3
427		5	max	74.324	1	5.492	9	46.048	1	0	1	.008	3	.123	1
428			min	-4.705	10	-19.034	2	-.538	3	0	15	-.05	1	-.138	3
429		6	max	74.442	1	5.281	9	46.048	1	0	1	.008	3	.123	1
430			min	-4.607	10	-19.287	2	-.538	3	0	15	-.04	1	-.134	3
431		7	max	74.56	1	5.07	9	46.048	1	0	1	.008	3	.125	2
432			min	-4.508	10	-19.54	2	-.538	3	0	15	-.03	1	-.13	3
433		8	max	74.678	1	4.859	9	46.048	1	0	1	.008	3	.129	2
434			min	-4.41	10	-19.793	2	-.538	3	0	15	-.02	1	-.126	3
435		9	max	74.796	1	4.648	9	46.048	1	0	1	.008	3	.134	2
436			min	-4.312	10	-20.046	2	-.538	3	0	15	-.01	1	-.122	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
437		10	max	74.914	1	4.437	9	46.048	1	0	1	.007	3	.138	2
438			min	-4.213	10	-20.299	2	-.538	3	0	15	0	2	-.118	3
439		11	max	75.032	1	4.226	9	46.048	1	0	1	.01	1	.142	2
440			min	-4.115	10	-20.552	2	-.538	3	0	15	0	15	-.114	3
441		12	max	75.15	1	4.015	9	46.048	1	0	1	.02	1	.147	2
442			min	-4.017	10	-20.806	2	-.538	3	0	15	0	15	-.109	3
443		13	max	75.268	1	3.804	9	46.048	1	0	1	.03	1	.151	2
444			min	-3.918	10	-21.059	2	-.538	3	0	15	.001	15	-.105	3
445		14	max	75.386	1	3.594	9	46.048	1	0	1	.04	1	.156	2
446			min	-3.82	10	-21.312	2	-.538	3	0	15	.001	15	-.101	3
447		15	max	75.504	1	3.383	9	46.048	1	0	1	.05	1	.161	2
448			min	-3.722	10	-21.565	2	-.538	3	0	15	.002	15	-.096	3
449		16	max	86.697	2	68.926	2	46.492	1	0	15	.061	1	.165	2
450			min	-20.009	3	-121.722	3	-.542	3	0	1	.002	15	-.091	3
451		17	max	86.815	2	68.673	2	46.492	1	0	15	.071	1	.15	2
452			min	-19.92	3	-121.912	3	-.542	3	0	1	.003	15	-.065	3
453		18	max	-4.13	15	347.116	2	48.892	1	0	2	.081	1	.076	2
454			min	-112.201	1	-149.248	3	-.127	3	0	3	.003	15	-.033	3
455		19	max	-4.094	15	346.863	2	48.892	1	0	2	.092	1	0	2
456			min	-112.083	1	-149.438	3	-.127	3	0	3	.003	15	0	3
457	M13	1	max	49.274	3	281.202	1	-4.097	15	0	1	.092	1	0	1
458			min	2.087	15	-339.289	3	-112.081	1	0	3	.003	15	0	3
459		2	max	49.274	3	198.641	1	-3.134	15	0	1	.026	1	.193	3
460			min	2.087	15	-239.545	3	-85.561	1	0	3	.001	15	-.16	1
461		3	max	49.274	3	116.08	1	-2.171	15	0	1	.004	3	.319	3
462			min	2.087	15	-139.801	3	-59.04	1	0	3	-.022	1	-.265	1
463		4	max	49.274	3	33.52	1	-1.208	15	0	1	.002	3	.379	3
464			min	2.087	15	-40.057	3	-32.52	1	0	3	-.053	1	-.315	1
465		5	max	49.274	3	59.687	3	.133	10	0	1	0	3	.373	3
466			min	2.087	15	-49.041	1	-5.999	1	0	3	-.065	1	-.31	1
467		6	max	49.274	3	159.431	3	20.521	1	0	1	0	12	.3	3
468			min	2.087	15	-131.602	1	-.663	3	0	3	-.061	1	-.249	1
469		7	max	49.274	3	259.175	3	47.042	1	0	1	0	12	.16	3
470			min	2.087	15	-214.163	1	.564	12	0	3	-.038	1	-.134	1
471		8	max	49.274	3	358.919	3	73.562	1	0	1	.003	2	.036	1
472			min	2.087	15	-296.724	1	1.498	12	0	3	0	3	-.046	3
473		9	max	49.274	3	458.663	3	100.083	1	0	1	.06	1	.262	1
474			min	2.087	15	-379.284	1	2.433	12	0	3	.001	12	-.318	3
475		10	max	49.274	3	558.407	3	126.603	1	0	1	.136	1	.542	1
476			min	2.087	15	-461.845	1	3.367	12	0	3	.003	12	-.657	3
477		11	max	47.604	1	379.284	1	-2.208	12	0	3	.059	1	.262	1
478			min	1.766	15	-458.663	3	-99.639	1	0	1	-.003	3	-.318	3
479		12	max	47.604	1	296.724	1	-1.274	12	0	3	.003	2	.036	1
480			min	1.766	15	-358.919	3	-73.119	1	0	1	-.005	3	-.046	3
481		13	max	47.604	1	214.163	1	-.339	12	0	3	-.001	15	.16	3
482			min	1.766	15	-259.175	3	-46.599	1	0	1	-.039	1	-.134	1
483		14	max	47.604	1	131.602	1	1.019	3	0	3	-.002	15	.3	3
484			min	1.766	15	-159.431	3	-20.078	1	0	1	-.061	1	-.249	1
485		15	max	47.604	1	49.041	1	6.442	1	0	3	-.002	15	.373	3
486			min	1.766	15	-59.687	3	-.133	10	0	1	-.065	1	-.31	1
487		16	max	47.604	1	40.057	3	32.963	1	0	3	-.002	12	.379	3
488			min	1.766	15	-33.52	1	1.227	15	0	1	-.052	1	-.315	1
489		17	max	47.604	1	139.801	3	59.483	1	0	3	0	3	.319	3
490			min	1.766	15	-116.081	1	2.19	15	0	1	-.021	1	-.265	1
491		18	max	47.604	1	239.545	3	86.004	1	0	3	.027	1	.193	3
492			min	1.766	15	-198.641	1	3.153	15	0	1	.001	10	-.16	1
493		19	max	47.604	1	339.289	3	112.524	1	0	3	.093	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
494			min	1.766	15	-281.202	1	4.116	15	0	1	.003	15	0	3
495	M16	1	max	.129	3	347.028	2	-4.094	15	0	3	.092	1	0	2
496			min	-48.759	1	-149.458	3	-112.094	1	0	2	.003	15	0	3
497		2	max	.129	3	245.15	2	-3.131	15	0	3	.026	1	.085	3
498			min	-48.759	1	-105.76	3	-85.574	1	0	2	0	15	-.197	2
499		3	max	.129	3	143.273	2	-2.168	15	0	3	0	12	.141	3
500			min	-48.759	1	-62.062	3	-59.053	1	0	2	-.022	1	-.327	2
501		4	max	.129	3	41.395	2	-1.205	15	0	3	-.002	15	.168	3
502			min	-48.759	1	-18.363	3	-32.533	1	0	2	-.053	1	-.388	2
503		5	max	.129	3	25.335	3	.126	10	0	3	-.002	15	.165	3
504			min	-48.759	1	-60.483	2	-6.012	1	0	2	-.066	1	-.382	2
505		6	max	.129	3	69.033	3	20.508	1	0	3	-.002	15	.134	3
506			min	-48.759	1	-162.36	2	-.103	3	0	2	-.061	1	-.308	2
507		7	max	.129	3	112.731	3	47.029	1	0	3	-.001	15	.073	3
508			min	-48.759	1	-264.238	2	.914	12	0	2	-.038	1	-.166	2
509		8	max	.129	3	156.429	3	73.549	1	0	3	.003	2	.045	2
510			min	-48.759	1	-366.115	2	1.848	12	0	2	-.003	3	-.016	3
511		9	max	.129	3	200.127	3	100.07	1	0	3	.06	1	.323	2
512			min	-48.759	1	-467.993	2	2.783	12	0	2	-.001	3	-.135	3
513		10	max	-1.807	15	-11.557	15	126.59	1	0	15	.135	1	.669	2
514			min	-48.759	1	-569.871	2	-5.999	3	0	2	.004	12	-.283	3
515		11	max	-1.807	15	467.993	2	-3.091	12	0	2	.059	1	.323	2
516			min	-48.626	1	-200.127	3	-99.658	1	0	3	.001	12	-.135	3
517		12	max	-1.807	15	366.115	2	-2.156	12	0	2	.003	2	.045	2
518			min	-48.626	1	-156.429	3	-73.137	1	0	3	0	3	-.016	3
519		13	max	-1.807	15	264.238	2	-1.222	12	0	2	-.001	15	.073	3
520			min	-48.626	1	-112.731	3	-46.617	1	0	3	-.038	1	-.166	2
521		14	max	-1.807	15	162.36	2	-.288	12	0	2	-.002	12	.134	3
522			min	-48.626	1	-69.033	3	-20.096	1	0	3	-.061	1	-.308	2
523		15	max	-1.807	15	60.482	2	6.424	1	0	2	-.002	12	.165	3
524			min	-48.626	1	-25.335	3	-.126	10	0	3	-.065	1	-.382	2
525		16	max	-1.807	15	18.363	3	32.945	1	0	2	-.001	12	.168	3
526			min	-48.626	1	-41.395	2	1.217	15	0	3	-.052	1	-.388	2
527		17	max	-1.807	15	62.062	3	59.465	1	0	2	0	3	.141	3
528			min	-48.626	1	-143.273	2	2.18	15	0	3	-.021	1	-.327	2
529		18	max	-1.807	15	105.76	3	85.985	1	0	2	.027	1	.085	3
530			min	-48.626	1	-245.15	2	3.144	15	0	3	.001	15	-.197	2
531		19	max	-1.807	15	149.458	3	112.506	1	0	2	.093	1	0	2
532			min	-48.626	1	-347.028	2	4.107	15	0	3	.003	15	0	3
533	M15	1	max	.228	1	2.102	4	.059	3	0	1	0	1	0	1
534			min	-56.005	3	0	2	-.056	1	0	3	0	3	0	1
535		2	max	.141	1	1.868	4	.059	3	0	1	0	1	0	2
536			min	-56.07	3	0	2	-.056	1	0	3	0	3	0	4
537		3	max	.054	1	1.635	4	.059	3	0	1	0	1	0	2
538			min	-56.135	3	0	2	-.056	1	0	3	0	3	-.001	4
539		4	max	0	2	1.401	4	.059	3	0	1	0	1	0	2
540			min	-56.201	3	0	2	-.056	1	0	3	0	3	-.002	4
541		5	max	0	2	1.168	4	.059	3	0	1	0	1	0	2
542			min	-56.266	3	0	2	-.056	1	0	3	0	3	-.002	4
543		6	max	0	2	.934	4	.059	3	0	1	0	1	0	2
544			min	-56.331	3	0	2	-.056	1	0	3	0	3	-.003	4
545		7	max	0	2	.701	4	.059	3	0	1	0	3	0	2
546			min	-56.396	3	0	2	-.056	1	0	3	0	1	-.003	4
547		8	max	0	2	.467	4	.059	3	0	1	0	3	0	2
548			min	-56.461	3	0	2	-.056	1	0	3	0	1	-.003	4
549		9	max	0	2	.234	4	.059	3	0	1	0	3	0	2
550			min	-56.527	3	0	2	-.056	1	0	3	0	1	-.003	4

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
551		10	max	0	2	0	1	.059	3	0	1	0	3	0	2
552			min	-56.592	3	0	1	-.056	1	0	3	0	1	-.004	4
553		11	max	0	2	0	2	.059	3	0	1	0	3	0	2
554			min	-56.657	3	-.234	4	-.056	1	0	3	0	1	-.003	4
555		12	max	0	2	0	2	.059	3	0	1	0	3	0	2
556			min	-56.722	3	-.467	4	-.056	1	0	3	0	1	-.003	4
557		13	max	0	2	0	2	.059	3	0	1	0	3	0	2
558			min	-56.787	3	-.701	4	-.056	1	0	3	0	1	-.003	4
559		14	max	0	2	0	2	.059	3	0	1	0	3	0	2
560			min	-56.852	3	-.934	4	-.056	1	0	3	0	1	-.003	4
561		15	max	0	2	0	2	.059	3	0	1	0	3	0	2
562			min	-56.918	3	-1.168	4	-.056	1	0	3	0	1	-.002	4
563		16	max	0	2	0	2	.059	3	0	1	0	3	0	2
564			min	-56.983	3	-1.401	4	-.056	1	0	3	0	1	-.002	4
565		17	max	0	2	0	2	.059	3	0	1	0	3	0	2
566			min	-57.048	3	-1.635	4	-.056	1	0	3	0	1	-.001	4
567		18	max	0	2	0	2	.059	3	0	1	0	3	0	2
568			min	-57.113	3	-1.868	4	-.056	1	0	3	0	1	0	4
569		19	max	0	2	0	2	.059	3	0	1	0	3	0	1
570			min	-57.178	3	-2.102	4	-.056	1	0	3	0	1	0	1
571	M16A	1	max	0	10	2.102	4	.028	1	0	3	0	3	0	1
572			min	-56.366	3	0	10	-.023	3	0	2	0	1	0	1
573		2	max	0	10	1.868	4	.028	1	0	3	0	3	0	10
574			min	-56.301	3	0	10	-.023	3	0	2	0	1	0	4
575		3	max	0	10	1.635	4	.028	1	0	3	0	3	0	10
576			min	-56.236	3	0	10	-.023	3	0	2	0	1	-.001	4
577		4	max	0	10	1.401	4	.028	1	0	3	0	3	0	10
578			min	-56.17	3	0	10	-.023	3	0	2	0	1	-.002	4
579		5	max	0	10	1.168	4	.028	1	0	3	0	3	0	10
580			min	-56.105	3	0	10	-.023	3	0	2	0	1	-.002	4
581		6	max	0	10	.934	4	.028	1	0	3	0	3	0	10
582			min	-56.04	3	0	10	-.023	3	0	2	0	1	-.003	4
583		7	max	0	10	.701	4	.028	1	0	3	0	3	0	10
584			min	-55.975	3	0	10	-.023	3	0	2	0	1	-.003	4
585		8	max	0	10	.467	4	.028	1	0	3	0	3	0	10
586			min	-55.91	3	0	10	-.023	3	0	2	0	1	-.003	4
587		9	max	0	10	.234	4	.028	1	0	3	0	3	0	10
588			min	-55.844	3	0	10	-.023	3	0	2	0	1	-.003	4
589		10	max	0	10	0	1	.028	1	0	3	0	3	0	10
590			min	-55.779	3	0	1	-.023	3	0	2	0	1	-.004	4
591		11	max	0	10	0	10	.028	1	0	3	0	3	0	10
592			min	-55.714	3	-.234	4	-.023	3	0	2	0	1	-.003	4
593		12	max	0	10	0	10	.028	1	0	3	0	3	0	10
594			min	-55.649	3	-.467	4	-.023	3	0	2	0	1	-.003	4
595		13	max	0	10	0	10	.028	1	0	3	0	2	0	10
596			min	-55.584	3	-.701	4	-.023	3	0	2	0	4	-.003	4
597		14	max	0	10	0	10	.028	1	0	3	0	2	0	10
598			min	-55.519	3	-.934	4	-.023	3	0	2	0	3	-.003	4
599		15	max	0	10	0	10	.028	1	0	3	0	1	0	10
600			min	-55.453	3	-1.168	4	-.023	3	0	2	0	3	-.002	4
601		16	max	0	10	0	10	.028	1	0	3	0	1	0	10
602			min	-55.388	3	-1.401	4	-.023	3	0	2	0	3	-.002	4
603		17	max	.078	2	0	10	.028	1	0	3	0	1	0	10
604			min	-55.323	3	-1.635	4	-.023	3	0	2	0	3	-.001	4
605		18	max	.165	2	0	10	.028	1	0	3	0	1	0	10
606			min	-55.258	3	-1.868	4	-.023	3	0	2	0	3	0	4
607		19	max	.252	2	0	10	.028	1	0	3	0	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
608			min	-55.193	3	-2.102	4	-.023	3	0	2	0	3	0	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M2	1	max	.003	1	.008	2	.01	1	-2.695e-5	15	NC	3	NC	2
2			min	-.003	3	-.008	3	-.001	3	-7.177e-4	1	4612.206	2	3742.124	1
3		2	max	.002	1	.007	2	.009	1	-2.582e-5	15	NC	3	NC	2
4			min	-.003	3	-.007	3	-.001	3	-6.879e-4	1	5025.729	2	4043.121	1
5		3	max	.002	1	.007	2	.008	1	-2.469e-5	15	NC	3	NC	2
6			min	-.003	3	-.007	3	0	3	-6.581e-4	1	5516.183	2	4398.218	1
7		4	max	.002	1	.006	2	.008	1	-2.355e-5	15	NC	1	NC	2
8			min	-.003	3	-.007	3	0	3	-6.283e-4	1	6101.984	2	4820.514	1
9		5	max	.002	1	.005	2	.007	1	-2.242e-5	15	NC	1	NC	2
10			min	-.003	3	-.006	3	0	3	-5.985e-4	1	6807.642	2	5327.515	1
11		6	max	.002	1	.005	2	.006	1	-2.128e-5	15	NC	1	NC	2
12			min	-.002	3	-.006	3	0	3	-5.687e-4	1	7666.311	2	5943.032	1
13		7	max	.002	1	.004	2	.005	1	-2.015e-5	15	NC	1	NC	2
14			min	-.002	3	-.006	3	0	3	-5.389e-4	1	8723.707	2	6700.143	1
15		8	max	.002	1	.004	2	.005	1	-1.902e-5	15	NC	1	NC	2
16			min	-.002	3	-.005	3	0	3	-5.091e-4	1	NC	1	7645.904	1
17		9	max	.001	1	.003	2	.004	1	-1.788e-5	15	NC	1	NC	2
18			min	-.002	3	-.005	3	0	3	-4.793e-4	1	NC	1	8849.176	1
19		10	max	.001	1	.003	2	.003	1	-1.675e-5	15	NC	1	NC	1
20			min	-.002	3	-.005	3	0	3	-4.495e-4	1	NC	1	NC	1
21		11	max	.001	1	.002	2	.003	1	-1.561e-5	15	NC	1	NC	1
22			min	-.001	3	-.004	3	0	3	-4.197e-4	1	NC	1	NC	1
23		12	max	0	1	.002	2	.002	1	-1.448e-5	15	NC	1	NC	1
24			min	-.001	3	-.004	3	0	3	-3.899e-4	1	NC	1	NC	1
25		13	max	0	1	.001	2	.002	1	-1.335e-5	15	NC	1	NC	1
26			min	-.001	3	-.003	3	0	3	-3.601e-4	1	NC	1	NC	1
27		14	max	0	1	.001	2	.001	1	-1.221e-5	15	NC	1	NC	1
28			min	0	3	-.003	3	0	3	-3.304e-4	1	NC	1	NC	1
29		15	max	0	1	0	2	.001	1	-1.108e-5	15	NC	1	NC	1
30			min	0	3	-.002	3	0	3	-3.006e-4	1	NC	1	NC	1
31		16	max	0	1	0	2	0	1	-9.944e-6	15	NC	1	NC	1
32			min	0	3	-.002	3	0	3	-2.708e-4	1	NC	1	NC	1
33		17	max	0	1	0	2	0	1	-8.81e-6	15	NC	1	NC	1
34			min	0	3	-.001	3	0	3	-2.41e-4	1	NC	1	NC	1
35		18	max	0	1	0	2	0	1	-7.676e-6	15	NC	1	NC	1
36			min	0	3	0	3	0	3	-2.112e-4	1	NC	1	NC	1
37		19	max	0	1	0	1	0	1	-6.452e-6	12	NC	1	NC	1
38			min	0	1	0	1	0	1	-1.814e-4	1	NC	1	NC	1
39	M3	1	max	0	1	0	1	0	1	8.434e-5	1	NC	1	NC	1
40			min	0	1	0	1	0	1	3.044e-6	15	NC	1	NC	1
41		2	max	0	3	0	2	0	12	1.04e-4	1	NC	1	NC	1
42			min	0	2	0	3	0	1	3.786e-6	15	NC	1	NC	1
43		3	max	0	3	0	2	0	12	1.237e-4	1	NC	1	NC	1
44			min	0	2	-.002	3	0	1	4.528e-6	15	NC	1	NC	1
45		4	max	0	3	0	2	0	12	1.434e-4	1	NC	1	NC	1
46			min	0	2	-.002	3	0	1	5.27e-6	15	NC	1	NC	1
47		5	max	0	3	0	2	0	3	1.631e-4	1	NC	1	NC	1
48			min	0	2	-.003	3	0	1	6.013e-6	15	NC	1	NC	1
49		6	max	0	3	0	2	0	3	1.828e-4	1	NC	1	NC	1
50			min	0	2	-.004	3	0	1	6.755e-6	15	NC	1	NC	1
51		7	max	0	3	0	2	0	3	2.025e-4	1	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
52			min	0	2	-.005	3	0	1	7.497e-6	15	NC	1	NC	1
53		8	max	0	3	0	2	0	3	2.222e-4	1	NC	1	NC	1
54			min	0	2	-.005	3	0	1	8.239e-6	15	NC	1	NC	1
55		9	max	0	3	.001	2	0	3	2.419e-4	1	NC	1	NC	1
56			min	0	2	-.006	3	0	1	8.982e-6	15	NC	1	NC	1
57		10	max	0	3	.002	2	0	2	2.616e-4	1	NC	1	NC	1
58			min	0	2	-.006	3	0	15	9.724e-6	15	NC	1	NC	1
59		11	max	0	3	.002	2	0	1	2.813e-4	1	NC	1	NC	1
60			min	0	2	-.007	3	0	15	1.047e-5	15	NC	1	NC	1
61		12	max	0	3	.003	2	.001	1	3.01e-4	1	NC	1	NC	1
62			min	0	2	-.007	3	0	15	1.121e-5	15	NC	1	NC	1
63		13	max	0	3	.003	2	.002	1	3.207e-4	1	NC	1	NC	1
64			min	0	2	-.007	3	0	15	1.195e-5	15	NC	1	NC	1
65		14	max	.001	3	.004	2	.002	1	3.404e-4	1	NC	1	NC	1
66			min	0	2	-.007	3	0	15	1.269e-5	15	NC	1	NC	1
67		15	max	.001	3	.005	2	.003	1	3.601e-4	1	NC	1	NC	1
68			min	-.001	2	-.007	3	0	15	1.343e-5	15	9658.459	2	NC	1
69		16	max	.001	3	.006	2	.003	1	3.798e-4	1	NC	1	NC	1
70			min	-.001	2	-.008	3	0	15	1.418e-5	15	8138.898	2	NC	1
71		17	max	.001	3	.007	2	.004	1	3.995e-4	1	NC	1	NC	1
72			min	-.001	2	-.008	3	0	15	1.492e-5	15	6972.478	2	NC	1
73		18	max	.001	3	.008	2	.004	1	4.192e-4	1	NC	3	NC	1
74			min	-.001	2	-.008	3	0	15	1.566e-5	15	6065.967	2	NC	1
75		19	max	.001	3	.009	2	.005	1	4.389e-4	1	NC	3	NC	1
76			min	-.001	2	-.008	3	0	15	1.64e-5	15	5354.565	2	NC	1
77	M4	1	max	.002	1	.009	2	0	15	-2.173e-5	15	NC	1	NC	2
78			min	0	3	-.008	3	-.003	1	-5.943e-4	1	NC	1	5743.222	1
79		2	max	.002	1	.009	2	0	15	-2.173e-5	15	NC	1	NC	2
80			min	0	3	-.007	3	-.003	1	-5.943e-4	1	NC	1	6266.023	1
81		3	max	.002	1	.008	2	0	15	-2.173e-5	15	NC	1	NC	2
82			min	0	3	-.007	3	-.003	1	-5.943e-4	1	NC	1	6888.208	1
83		4	max	.002	1	.008	2	0	15	-2.173e-5	15	NC	1	NC	2
84			min	0	3	-.006	3	-.003	1	-5.943e-4	1	NC	1	7635.997	1
85		5	max	.001	1	.007	2	0	15	-2.173e-5	15	NC	1	NC	2
86			min	0	3	-.006	3	-.002	1	-5.943e-4	1	NC	1	8545.11	1
87		6	max	.001	1	.007	2	0	15	-2.173e-5	15	NC	1	NC	2
88			min	0	3	-.005	3	-.002	1	-5.943e-4	1	NC	1	9665.23	1
89		7	max	.001	1	.006	2	0	15	-2.173e-5	15	NC	1	NC	1
90			min	0	3	-.005	3	-.002	1	-5.943e-4	1	NC	1	NC	1
91		8	max	.001	1	.006	2	0	15	-2.173e-5	15	NC	1	NC	1
92			min	0	3	-.005	3	-.002	1	-5.943e-4	1	NC	1	NC	1
93		9	max	.001	1	.005	2	0	15	-2.173e-5	15	NC	1	NC	1
94			min	0	3	-.004	3	-.001	1	-5.943e-4	1	NC	1	NC	1
95		10	max	0	1	.005	2	0	15	-2.173e-5	15	NC	1	NC	1
96			min	0	3	-.004	3	-.001	1	-5.943e-4	1	NC	1	NC	1
97		11	max	0	1	.004	2	0	15	-2.173e-5	15	NC	1	NC	1
98			min	0	3	-.003	3	0	1	-5.943e-4	1	NC	1	NC	1
99		12	max	0	1	.004	2	0	15	-2.173e-5	15	NC	1	NC	1
100			min	0	3	-.003	3	0	1	-5.943e-4	1	NC	1	NC	1
101		13	max	0	1	.003	2	0	15	-2.173e-5	15	NC	1	NC	1
102			min	0	3	-.003	3	0	1	-5.943e-4	1	NC	1	NC	1
103		14	max	0	1	.003	2	0	15	-2.173e-5	15	NC	1	NC	1
104			min	0	3	-.002	3	0	1	-5.943e-4	1	NC	1	NC	1
105		15	max	0	1	.002	2	0	15	-2.173e-5	15	NC	1	NC	1
106			min	0	3	-.002	3	0	1	-5.943e-4	1	NC	1	NC	1
107		16	max	0	1	.002	2	0	15	-2.173e-5	15	NC	1	NC	1
108			min	0	3	-.001	3	0	1	-5.943e-4	1	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
109		17	max	0	1	.001	2	0	15	-2.173e-5	15	NC	1	NC	1
110			min	0	3	0	3	0	1	-5.943e-4	1	NC	1	NC	1
111		18	max	0	1	0	2	0	15	-2.173e-5	15	NC	1	NC	1
112			min	0	3	0	3	0	1	-5.943e-4	1	NC	1	NC	1
113		19	max	0	1	0	1	0	1	-2.173e-5	15	NC	1	NC	1
114			min	0	1	0	1	0	1	-5.943e-4	1	NC	1	NC	1
115	M6	1	max	.008	1	.028	2	.004	1	3.071e-4	3	NC	3	NC	2
116			min	-.01	3	-.024	3	-.004	3	-6.052e-8	10	1298.978	2	8819.733	1
117		2	max	.008	1	.026	2	.004	1	2.981e-4	3	NC	3	NC	2
118			min	-.01	3	-.023	3	-.004	3	-5.719e-8	10	1388.386	2	9506.55	1
119		3	max	.007	1	.024	2	.004	1	2.891e-4	3	NC	3	NC	1
120			min	-.009	3	-.021	3	-.003	3	-5.386e-8	10	1490.639	2	NC	1
121		4	max	.007	1	.023	2	.003	1	2.801e-4	3	NC	3	NC	1
122			min	-.009	3	-.02	3	-.003	3	-1.205e-6	2	1608.31	2	NC	1
123		5	max	.006	1	.021	2	.003	1	2.712e-4	3	NC	3	NC	1
124			min	-.008	3	-.019	3	-.003	3	-3.028e-6	2	1744.712	2	NC	1
125		6	max	.006	1	.019	2	.003	1	2.622e-4	3	NC	3	NC	1
126			min	-.008	3	-.018	3	-.003	3	-4.852e-6	2	1904.18	2	NC	1
127		7	max	.005	1	.017	2	.002	1	2.532e-4	3	NC	3	NC	1
128			min	-.007	3	-.016	3	-.002	3	-6.675e-6	2	2092.503	2	NC	1
129		8	max	.005	1	.016	2	.002	1	2.442e-4	3	NC	3	NC	1
130			min	-.006	3	-.015	3	-.002	3	-1.256e-5	1	2317.578	2	NC	1
131		9	max	.005	1	.014	2	.002	1	2.352e-4	3	NC	3	NC	1
132			min	-.006	3	-.014	3	-.002	3	-1.847e-5	1	2590.463	2	NC	1
133		10	max	.004	1	.012	2	.002	1	2.262e-4	3	NC	3	NC	1
134			min	-.005	3	-.012	3	-.002	3	-2.438e-5	1	2927.132	2	NC	1
135		11	max	.004	1	.011	2	.001	1	2.173e-4	3	NC	3	NC	1
136			min	-.005	3	-.011	3	-.001	3	-3.029e-5	1	3351.548	2	NC	1
137		12	max	.003	1	.009	2	.001	1	2.083e-4	3	NC	3	NC	1
138			min	-.004	3	-.01	3	-.001	3	-3.62e-5	1	3901.364	2	NC	1
139		13	max	.003	1	.008	2	0	1	1.993e-4	3	NC	3	NC	1
140			min	-.003	3	-.008	3	0	3	-4.211e-5	1	4639.33	2	NC	1
141		14	max	.002	1	.006	2	0	1	1.903e-4	3	NC	3	NC	1
142			min	-.003	3	-.007	3	0	3	-4.801e-5	1	5678.38	2	NC	1
143		15	max	.002	1	.005	2	0	1	1.813e-4	3	NC	1	NC	1
144			min	-.002	3	-.006	3	0	3	-5.392e-5	1	7244.365	2	NC	1
145		16	max	.001	1	.004	2	0	1	1.723e-4	3	NC	1	NC	1
146			min	-.002	3	-.004	3	0	3	-5.983e-5	1	9864.227	2	NC	1
147		17	max	0	1	.002	2	0	1	1.634e-4	3	NC	1	NC	1
148			min	-.001	3	-.003	3	0	3	-6.574e-5	1	NC	1	NC	1
149		18	max	0	1	.001	2	0	1	1.544e-4	3	NC	1	NC	1
150			min	0	3	-.001	3	0	3	-7.165e-5	1	NC	1	NC	1
151		19	max	0	1	0	1	0	1	1.454e-4	3	NC	1	NC	1
152			min	0	1	0	1	0	1	-7.756e-5	1	NC	1	NC	1
153	M7	1	max	0	1	0	1	0	1	3.569e-5	1	NC	1	NC	1
154			min	0	1	0	1	0	1	-6.733e-5	3	NC	1	NC	1
155		2	max	0	3	.001	2	0	3	2.987e-5	1	NC	1	NC	1
156			min	0	2	-.002	3	0	1	-5.03e-5	3	NC	1	NC	1
157		3	max	0	3	.003	2	0	3	2.405e-5	1	NC	1	NC	1
158			min	0	2	-.004	3	0	1	-3.327e-5	3	NC	1	NC	1
159		4	max	0	3	.004	2	0	3	1.823e-5	1	NC	1	NC	1
160			min	0	2	-.005	3	0	1	-1.625e-5	3	NC	1	NC	1
161		5	max	0	3	.005	2	.001	3	1.241e-5	1	NC	1	NC	1
162			min	-.001	2	-.007	3	0	1	0	10	8468.963	2	NC	1
163		6	max	.001	3	.007	2	.001	3	1.781e-5	3	NC	3	NC	1
164			min	-.001	2	-.009	3	0	1	0	10	6791.746	2	NC	1
165		7	max	.001	3	.008	2	.002	3	3.484e-5	3	NC	3	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
166			min	-.002	2	-.01	3	0	1	0	10	5645.15	2	NC	1
167		8	max	.002	3	.01	2	.002	3	5.186e-5	3	NC	3	NC	1
168			min	-.002	2	-.012	3	-.001	1	-5.049e-6	1	4804.763	2	NC	1
169		9	max	.002	3	.011	2	.002	3	6.889e-5	3	NC	3	NC	1
170			min	-.002	2	-.013	3	-.001	1	-1.087e-5	1	4158.781	2	NC	1
171		10	max	.002	3	.013	2	.002	3	8.592e-5	3	NC	3	NC	1
172			min	-.003	2	-.015	3	-.001	1	-1.669e-5	1	3645.247	2	NC	1
173		11	max	.002	3	.014	2	.002	3	1.029e-4	3	NC	3	NC	1
174			min	-.003	2	-.016	3	-.002	1	-2.251e-5	1	3226.973	2	NC	1
175		12	max	.003	3	.016	2	.002	3	1.2e-4	3	NC	3	NC	1
176			min	-.003	2	-.017	3	-.002	1	-2.833e-5	1	2880.173	2	NC	1
177		13	max	.003	3	.018	2	.002	3	1.37e-4	3	NC	3	NC	1
178			min	-.004	2	-.018	3	-.002	1	-3.414e-5	1	2588.815	2	NC	1
179		14	max	.003	3	.02	2	.002	3	1.54e-4	3	NC	3	NC	1
180			min	-.004	2	-.019	3	-.002	1	-3.996e-5	1	2341.604	2	NC	1
181		15	max	.003	3	.022	2	.002	3	1.711e-4	3	NC	3	NC	1
182			min	-.004	2	-.02	3	-.002	1	-4.578e-5	1	2130.289	2	NC	1
183		16	max	.004	3	.024	2	.002	3	1.881e-4	3	NC	3	NC	1
184			min	-.004	2	-.021	3	-.002	1	-5.16e-5	1	1948.647	2	NC	1
185		17	max	.004	3	.026	2	.002	3	2.051e-4	3	NC	3	NC	1
186			min	-.005	2	-.022	3	-.002	1	-5.742e-5	1	1791.875	2	NC	1
187		18	max	.004	3	.028	2	.002	3	2.221e-4	3	NC	3	NC	1
188			min	-.005	2	-.023	3	-.002	1	-6.324e-5	1	1656.185	2	NC	1
189		19	max	.004	3	.03	2	.002	3	2.392e-4	3	NC	3	NC	1
190			min	-.005	2	-.024	3	-.002	1	-6.906e-5	1	1538.553	2	NC	1
191	M8	1	max	.005	1	.032	2	.002	1	-8.341e-8	10	NC	1	NC	2
192			min	0	3	-.024	3	-.001	3	-1.845e-4	3	NC	1	9333.752	1
193		2	max	.005	1	.03	2	.002	1	-8.341e-8	10	NC	1	NC	1
194			min	0	3	-.023	3	-.001	3	-1.845e-4	3	NC	1	NC	1
195		3	max	.005	1	.028	2	.002	1	-8.341e-8	10	NC	1	NC	1
196			min	0	3	-.021	3	-.001	3	-1.845e-4	3	NC	1	NC	1
197		4	max	.004	1	.026	2	.002	1	-8.341e-8	10	NC	1	NC	1
198			min	0	3	-.02	3	-.001	3	-1.845e-4	3	NC	1	NC	1
199		5	max	.004	1	.025	2	.001	1	-8.341e-8	10	NC	1	NC	1
200			min	0	3	-.019	3	0	3	-1.845e-4	3	NC	1	NC	1
201		6	max	.004	1	.023	2	.001	1	-8.341e-8	10	NC	1	NC	1
202			min	0	3	-.017	3	0	3	-1.845e-4	3	NC	1	NC	1
203		7	max	.004	1	.021	2	.001	1	-8.341e-8	10	NC	1	NC	1
204			min	0	3	-.016	3	0	3	-1.845e-4	3	NC	1	NC	1
205		8	max	.003	1	.019	2	0	1	-8.341e-8	10	NC	1	NC	1
206			min	0	3	-.015	3	0	3	-1.845e-4	3	NC	1	NC	1
207		9	max	.003	1	.018	2	0	1	-8.341e-8	10	NC	1	NC	1
208			min	0	3	-.013	3	0	3	-1.845e-4	3	NC	1	NC	1
209		10	max	.003	1	.016	2	0	1	-8.341e-8	10	NC	1	NC	1
210			min	0	3	-.012	3	0	3	-1.845e-4	3	NC	1	NC	1
211		11	max	.002	1	.014	2	0	1	-8.341e-8	10	NC	1	NC	1
212			min	0	3	-.011	3	0	3	-1.845e-4	3	NC	1	NC	1
213		12	max	.002	1	.012	2	0	1	-8.341e-8	10	NC	1	NC	1
214			min	0	3	-.009	3	0	3	-1.845e-4	3	NC	1	NC	1
215		13	max	.002	1	.011	2	0	1	-8.341e-8	10	NC	1	NC	1
216			min	0	3	-.008	3	0	3	-1.845e-4	3	NC	1	NC	1
217		14	max	.001	1	.009	2	0	1	-8.341e-8	10	NC	1	NC	1
218			min	0	3	-.007	3	0	3	-1.845e-4	3	NC	1	NC	1
219		15	max	.001	1	.007	2	0	1	-8.341e-8	10	NC	1	NC	1
220			min	0	3	-.005	3	0	3	-1.845e-4	3	NC	1	NC	1
221		16	max	0	1	.005	2	0	1	-8.341e-8	10	NC	1	NC	1
222			min	0	3	-.004	3	0	3	-1.845e-4	3	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
223		17	max	0	1	.004	2	0	1	-8.341e-8	10	NC	1	NC	1
224			min	0	3	-.003	3	0	3	-1.845e-4	3	NC	1	NC	1
225		18	max	0	1	.002	2	0	1	-8.341e-8	10	NC	1	NC	1
226			min	0	3	-.001	3	0	3	-1.845e-4	3	NC	1	NC	1
227		19	max	0	1	0	1	0	1	-8.341e-8	10	NC	1	NC	1
228			min	0	1	0	1	0	1	-1.845e-4	3	NC	1	NC	1
229	M10	1	max	.003	1	.008	2	0	3	7.486e-4	1	NC	3	NC	1
230			min	-.003	3	-.008	3	-.001	1	-3.489e-4	3	4617.652	2	NC	1
231		2	max	.002	1	.007	2	0	3	7.123e-4	1	NC	3	NC	1
232			min	-.003	3	-.007	3	-.001	1	-3.378e-4	3	5031.824	2	NC	1
233		3	max	.002	1	.007	2	0	3	6.76e-4	1	NC	3	NC	1
234			min	-.003	3	-.007	3	-.001	1	-3.268e-4	3	5523.076	2	NC	1
235		4	max	.002	1	.006	2	0	3	6.397e-4	1	NC	1	NC	1
236			min	-.002	3	-.007	3	-.001	1	-3.158e-4	3	6109.87	2	NC	1
237		5	max	.002	1	.005	2	0	3	6.034e-4	1	NC	1	NC	1
238			min	-.002	3	-.006	3	-.001	1	-3.048e-4	3	6816.776	2	NC	1
239		6	max	.002	1	.005	2	0	3	5.671e-4	1	NC	1	NC	1
240			min	-.002	3	-.006	3	-.001	1	-2.938e-4	3	7677.032	2	NC	1
241		7	max	.002	1	.004	2	0	3	5.308e-4	1	NC	1	NC	1
242			min	-.002	3	-.006	3	0	1	-2.828e-4	3	8736.477	2	NC	1
243		8	max	.002	1	.004	2	0	3	4.945e-4	1	NC	1	NC	1
244			min	-.002	3	-.005	3	0	1	-2.718e-4	3	NC	1	NC	1
245		9	max	.001	1	.003	2	0	3	4.583e-4	1	NC	1	NC	1
246			min	-.002	3	-.005	3	0	1	-2.608e-4	3	NC	1	NC	1
247		10	max	.001	1	.003	2	0	3	4.22e-4	1	NC	1	NC	1
248			min	-.001	3	-.005	3	0	1	-2.498e-4	3	NC	1	NC	1
249		11	max	.001	1	.002	2	0	3	3.857e-4	1	NC	1	NC	1
250			min	-.001	3	-.004	3	0	1	-2.387e-4	3	NC	1	NC	1
251		12	max	0	1	.002	2	0	3	3.494e-4	1	NC	1	NC	1
252			min	-.001	3	-.004	3	0	1	-2.277e-4	3	NC	1	NC	1
253		13	max	0	1	.001	2	0	3	3.131e-4	1	NC	1	NC	1
254			min	0	3	-.003	3	0	1	-2.167e-4	3	NC	1	NC	1
255		14	max	0	1	.001	2	0	3	2.768e-4	1	NC	1	NC	1
256			min	0	3	-.003	3	0	1	-2.057e-4	3	NC	1	NC	1
257		15	max	0	1	0	2	0	3	2.405e-4	1	NC	1	NC	1
258			min	0	3	-.002	3	0	1	-1.947e-4	3	NC	1	NC	1
259		16	max	0	1	0	2	0	3	2.042e-4	1	NC	1	NC	1
260			min	0	3	-.002	3	0	1	-1.837e-4	3	NC	1	NC	1
261		17	max	0	1	0	2	0	3	1.68e-4	1	NC	1	NC	1
262			min	0	3	-.001	3	0	1	-1.727e-4	3	NC	1	NC	1
263		18	max	0	1	0	2	0	3	1.317e-4	1	NC	1	NC	1
264			min	0	3	0	3	0	1	-1.617e-4	3	NC	1	NC	1
265		19	max	0	1	0	1	0	1	9.538e-5	1	NC	1	NC	1
266			min	0	1	0	1	0	1	-1.506e-4	3	NC	1	NC	1
267	M11	1	max	0	1	0	1	0	1	7.017e-5	3	NC	1	NC	1
268			min	0	1	0	1	0	1	-4.524e-5	1	NC	1	NC	1
269		2	max	0	3	0	2	0	1	5.257e-5	3	NC	1	NC	1
270			min	0	2	0	3	0	3	-7.769e-5	1	NC	1	NC	1
271		3	max	0	3	0	2	0	1	3.497e-5	3	NC	1	NC	1
272			min	0	2	-.002	3	0	3	-1.101e-4	1	NC	1	NC	1
273		4	max	0	3	0	2	0	1	1.737e-5	3	NC	1	NC	1
274			min	0	2	-.002	3	0	3	-1.426e-4	1	NC	1	NC	1
275		5	max	0	3	0	2	0	10	-2.336e-7	3	NC	1	NC	1
276			min	0	2	-.003	3	-.001	3	-1.75e-4	1	NC	1	NC	1
277		6	max	0	3	0	2	0	10	-7.517e-6	15	NC	1	NC	1
278			min	0	2	-.004	3	-.001	3	-2.075e-4	1	NC	1	NC	1
279		7	max	0	3	0	2	0	10	-8.809e-6	15	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
280			min	0	2	-.005	3	-.002	3	-2.399e-4	1	NC	1	NC	1
281		8	max	0	3	0	2	0	10	-1.01e-5	15	NC	1	NC	1
282			min	0	2	-.005	3	-.002	3	-2.724e-4	1	NC	1	NC	1
283		9	max	0	3	.001	2	0	10	-1.139e-5	15	NC	1	NC	1
284			min	0	2	-.006	3	-.002	3	-3.048e-4	1	NC	1	NC	1
285		10	max	0	3	.002	2	0	15	-1.268e-5	15	NC	1	NC	1
286			min	0	2	-.006	3	-.003	1	-3.373e-4	1	NC	1	NC	1
287		11	max	0	3	.002	2	0	15	-1.397e-5	15	NC	1	NC	1
288			min	0	2	-.007	3	-.003	1	-3.697e-4	1	NC	1	NC	1
289		12	max	0	3	.003	2	0	15	-1.527e-5	15	NC	1	NC	1
290			min	0	2	-.007	3	-.004	1	-4.022e-4	1	NC	1	NC	1
291		13	max	0	3	.003	2	0	15	-1.656e-5	15	NC	1	NC	2
292			min	0	2	-.007	3	-.005	1	-4.346e-4	1	NC	1	9886.57	1
293		14	max	.001	3	.004	2	0	15	-1.785e-5	15	NC	1	NC	2
294			min	0	2	-.007	3	-.005	1	-4.671e-4	1	NC	1	8509.007	1
295		15	max	.001	3	.005	2	0	15	-1.914e-5	15	NC	1	NC	2
296			min	-.001	2	-.008	3	-.006	1	-4.995e-4	1	9674.019	2	7460.093	1
297		16	max	.001	3	.006	2	0	15	-2.043e-5	15	NC	1	NC	2
298			min	-.001	2	-.008	3	-.007	1	-5.32e-4	1	8150.681	2	6644.986	1
299		17	max	.001	3	.007	2	0	15	-2.172e-5	15	NC	1	NC	2
300			min	-.001	2	-.008	3	-.008	1	-5.645e-4	1	6981.663	2	6001.647	1
301		18	max	.001	3	.008	2	0	15	-2.301e-5	15	NC	3	NC	2
302			min	-.001	2	-.008	3	-.008	1	-5.969e-4	1	6073.323	2	5488.141	1
303		19	max	.001	3	.009	2	0	15	-2.43e-5	15	NC	3	NC	2
304			min	-.001	2	-.008	3	-.009	1	-6.294e-4	1	5360.612	2	5075.376	1
305	M12	1	max	.002	1	.009	2	.008	1	5.441e-4	1	NC	1	NC	3
306			min	0	3	-.008	3	0	15	2.165e-5	15	NC	1	2527.198	1
307		2	max	.002	1	.009	2	.007	1	5.441e-4	1	NC	1	NC	3
308			min	0	3	-.007	3	0	15	2.165e-5	15	NC	1	2756.193	1
309		3	max	.002	1	.008	2	.006	1	5.441e-4	1	NC	1	NC	3
310			min	0	3	-.007	3	0	15	2.165e-5	15	NC	1	3028.77	1
311		4	max	.002	1	.008	2	.006	1	5.441e-4	1	NC	1	NC	2
312			min	0	3	-.006	3	0	15	2.165e-5	15	NC	1	3356.416	1
313		5	max	.001	1	.007	2	.005	1	5.441e-4	1	NC	1	NC	2
314			min	0	3	-.006	3	0	15	2.165e-5	15	NC	1	3754.782	1
315		6	max	.001	1	.007	2	.005	1	5.441e-4	1	NC	1	NC	2
316			min	0	3	-.005	3	0	15	2.165e-5	15	NC	1	4245.638	1
317		7	max	.001	1	.006	2	.004	1	5.441e-4	1	NC	1	NC	2
318			min	0	3	-.005	3	0	15	2.165e-5	15	NC	1	4859.99	1
319		8	max	.001	1	.006	2	.003	1	5.441e-4	1	NC	1	NC	2
320			min	0	3	-.005	3	0	15	2.165e-5	15	NC	1	5643.245	1
321		9	max	.001	1	.005	2	.003	1	5.441e-4	1	NC	1	NC	2
322			min	0	3	-.004	3	0	15	2.165e-5	15	NC	1	6664.09	1
323		10	max	0	1	.005	2	.002	1	5.441e-4	1	NC	1	NC	2
324			min	0	3	-.004	3	0	15	2.165e-5	15	NC	1	8030.51	1
325		11	max	0	1	.004	2	.002	1	5.441e-4	1	NC	1	NC	2
326			min	0	3	-.003	3	0	15	2.165e-5	15	NC	1	9920.378	1
327		12	max	0	1	.004	2	.002	1	5.441e-4	1	NC	1	NC	1
328			min	0	3	-.003	3	0	15	2.165e-5	15	NC	1	NC	1
329		13	max	0	1	.003	2	.001	1	5.441e-4	1	NC	1	NC	1
330			min	0	3	-.003	3	0	15	2.165e-5	15	NC	1	NC	1
331		14	max	0	1	.003	2	0	1	5.441e-4	1	NC	1	NC	1
332			min	0	3	-.002	3	0	15	2.165e-5	15	NC	1	NC	1
333		15	max	0	1	.002	2	0	1	5.441e-4	1	NC	1	NC	1
334			min	0	3	-.002	3	0	15	2.165e-5	15	NC	1	NC	1
335		16	max	0	1	.002	2	0	1	5.441e-4	1	NC	1	NC	1
336			min	0	3	-.001	3	0	15	2.165e-5	15	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
337		17	max	0	1	.001	2	0	1	5.441e-4	1	NC	1	NC	1
338			min	0	3	0	3	0	15	2.165e-5	15	NC	1	NC	1
339		18	max	0	1	0	2	0	1	5.441e-4	1	NC	1	NC	1
340			min	0	3	0	3	0	15	2.165e-5	15	NC	1	NC	1
341		19	max	0	1	0	1	0	1	5.441e-4	1	NC	1	NC	1
342			min	0	1	0	1	0	1	2.165e-5	15	NC	1	NC	1
343	M1	1	max	.007	3	.023	3	.002	3	1.424e-2	1	NC	1	NC	1
344			min	-.007	2	-.021	2	-.004	1	-1.701e-2	3	NC	1	NC	1
345		2	max	.007	3	.013	3	.002	3	6.825e-3	1	NC	4	NC	1
346			min	-.007	2	-.012	2	-.007	1	-8.413e-3	3	4915.433	2	NC	1
347		3	max	.007	3	.004	3	.001	3	2.905e-5	3	NC	4	NC	2
348			min	-.008	2	-.003	2	-.01	1	-4.514e-4	1	2525.093	2	7857.959	1
349		4	max	.007	3	.005	2	0	3	3.099e-5	3	NC	4	NC	2
350			min	-.008	2	-.003	3	-.011	1	-3.845e-4	1	1769.402	2	6515.711	1
351		5	max	.007	3	.011	2	0	3	3.293e-5	3	NC	5	NC	2
352			min	-.008	2	-.01	3	-.011	1	-3.176e-4	1	1404.101	2	6274.521	1
353		6	max	.007	3	.017	2	0	3	3.487e-5	3	NC	5	NC	2
354			min	-.008	2	-.015	3	-.01	1	-2.506e-4	1	1195.741	2	6742.358	1
355		7	max	.007	3	.021	2	0	3	3.68e-5	3	NC	5	NC	2
356			min	-.008	2	-.019	3	-.009	1	-1.837e-4	1	1067.597	2	8084.053	1
357		8	max	.007	3	.024	2	0	3	3.874e-5	3	NC	5	NC	1
358			min	-.008	2	-.021	3	-.007	1	-1.167e-4	1	987.634	2	NC	1
359		9	max	.007	3	.026	2	0	3	4.068e-5	3	NC	5	NC	1
360			min	-.008	2	-.023	3	-.005	1	-4.98e-5	1	940.755	2	NC	1
361		10	max	.007	3	.027	2	0	3	4.262e-5	3	NC	5	NC	1
362			min	-.008	2	-.023	3	-.003	1	1.006e-6	15	919.79	2	NC	1
363		11	max	.007	3	.027	2	0	3	8.408e-5	1	NC	5	NC	1
364			min	-.008	2	-.022	3	-.001	1	3.458e-6	15	922.214	2	NC	1
365		12	max	.007	3	.025	2	.001	1	1.51e-4	1	NC	5	NC	1
366			min	-.008	2	-.02	3	0	15	5.91e-6	15	949.183	2	NC	1
367		13	max	.007	3	.022	2	.003	1	2.18e-4	1	NC	5	NC	2
368			min	-.008	2	-.017	3	0	15	8.361e-6	15	1006.143	2	8352.781	1
369		14	max	.007	3	.017	2	.004	1	2.849e-4	1	NC	5	NC	2
370			min	-.008	2	-.014	3	0	15	1.081e-5	15	1105.546	2	6908.47	1
371		15	max	.007	3	.011	2	.005	1	3.518e-4	1	NC	4	NC	2
372			min	-.008	2	-.009	3	0	15	1.326e-5	15	1274.626	2	6396.309	1
373		16	max	.007	3	.004	2	.004	1	3.997e-4	1	NC	4	NC	2
374			min	-.008	2	-.003	3	0	15	1.503e-5	15	1579.7	2	6615.539	1
375		17	max	.007	3	.003	3	.003	1	3.659e-5	3	NC	4	NC	2
376			min	-.008	2	-.005	2	0	15	-7.166e-6	1	2230.614	2	7957.373	1
377		18	max	.007	3	.01	3	.001	1	8.719e-3	2	NC	4	NC	1
378			min	-.008	2	-.015	2	0	15	-3.846e-3	3	4317.765	2	NC	1
379		19	max	.007	3	.018	3	0	3	1.758e-2	2	NC	1	NC	1
380			min	-.008	2	-.027	2	-.002	1	-7.801e-3	3	NC	1	NC	1
381	M5	1	max	.022	3	.074	3	.002	3	1.917e-6	3	NC	1	NC	1
382			min	-.027	2	-.071	1	-.004	1	3.924e-8	15	NC	1	NC	1
383		2	max	.022	3	.043	3	.003	3	8.25e-5	3	NC	5	NC	1
384			min	-.027	2	-.04	1	-.004	1	-7.092e-5	1	1473.599	1	NC	1
385		3	max	.022	3	.013	3	.004	3	1.615e-4	3	NC	5	NC	1
386			min	-.027	2	-.01	1	-.004	1	-1.406e-4	1	758.73	2	NC	1
387		4	max	.022	3	.015	2	.005	3	1.577e-4	3	NC	5	NC	1
388			min	-.027	2	-.011	3	-.004	1	-1.343e-4	1	531.185	2	NC	1
389		5	max	.022	3	.037	2	.005	3	1.539e-4	3	NC	5	NC	1
390			min	-.027	2	-.032	3	-.004	1	-1.279e-4	1	421.145	2	NC	1
391		6	max	.022	3	.056	2	.005	3	1.501e-4	3	NC	5	NC	1
392			min	-.027	2	-.048	3	-.004	1	-1.216e-4	1	358.349	2	NC	1
393		7	max	.022	3	.07	2	.005	3	1.463e-4	3	NC	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
394			min	-.027	2	-.06	3	-.004	1	-1.153e-4	1	319.697	2	NC	1
395		8	max	.022	3	.081	2	.005	3	1.425e-4	3	NC	15	NC	1
396			min	-.027	2	-.068	3	-.003	1	-1.09e-4	1	295.543	2	NC	1
397		9	max	.022	3	.088	2	.005	3	1.387e-4	3	NC	15	NC	1
398			min	-.027	2	-.073	3	-.003	1	-1.027e-4	1	281.336	2	NC	1
399		10	max	.022	3	.091	2	.005	3	1.348e-4	3	NC	15	NC	1
400			min	-.027	2	-.074	3	-.003	1	-9.634e-5	1	274.913	2	NC	1
401		11	max	.022	3	.089	2	.005	3	1.31e-4	3	NC	15	NC	1
402			min	-.027	2	-.071	3	-.003	1	-9.002e-5	1	275.506	2	NC	1
403		12	max	.022	3	.084	2	.004	3	1.272e-4	3	NC	15	NC	1
404			min	-.027	2	-.065	3	-.003	1	-8.37e-5	1	283.454	2	NC	1
405		13	max	.022	3	.073	2	.004	3	1.234e-4	3	NC	5	NC	1
406			min	-.027	2	-.056	3	-.003	1	-7.738e-5	1	300.38	2	NC	1
407		14	max	.022	3	.058	2	.003	3	1.196e-4	3	NC	5	NC	1
408			min	-.027	2	-.044	3	-.002	1	-7.106e-5	1	330.01	2	NC	1
409		15	max	.021	3	.038	2	.002	3	1.158e-4	3	NC	5	NC	1
410			min	-.027	2	-.029	3	-.002	1	-6.474e-5	1	380.503	2	NC	1
411		16	max	.021	3	.013	2	.002	3	1.085e-4	3	NC	5	NC	1
412			min	-.027	2	-.011	3	-.002	1	-6.25e-5	1	471.776	2	NC	1
413		17	max	.021	3	.01	3	.001	3	1.78e-5	3	NC	5	NC	1
414			min	-.027	2	-.017	2	-.002	1	-1.574e-4	1	667.275	2	NC	1
415		18	max	.021	3	.033	3	0	3	7.97e-6	3	NC	5	NC	1
416			min	-.027	2	-.052	2	-.002	1	-8.032e-5	1	1292.651	2	NC	1
417		19	max	.021	3	.057	3	0	3	0	1	NC	1	NC	1
418			min	-.027	2	-.089	2	-.002	1	-3.337e-7	3	NC	1	NC	1
419	M9	1	max	.007	3	.023	3	.002	3	1.702e-2	3	NC	1	NC	1
420			min	-.007	2	-.021	2	-.005	1	-1.424e-2	1	NC	1	NC	1
421		2	max	.007	3	.013	3	0	3	8.42e-3	3	NC	4	NC	1
422			min	-.007	2	-.012	2	-.001	1	-6.992e-3	1	4918.15	2	NC	1
423		3	max	.007	3	.004	3	.001	1	1.19e-4	1	NC	4	NC	2
424			min	-.007	2	-.003	2	0	3	-1.901e-5	3	2526.527	2	8110.804	1
425		4	max	.007	3	.005	2	.003	1	6.397e-5	1	NC	4	NC	2
426			min	-.008	2	-.004	3	-.001	3	-2.635e-5	3	1770.428	2	6737.245	1
427		5	max	.007	3	.011	2	.003	1	2.318e-5	2	NC	5	NC	2
428			min	-.008	2	-.01	3	-.002	3	-3.37e-5	3	1404.914	2	6500.565	1
429		6	max	.007	3	.017	2	.003	1	7.783e-6	10	NC	5	NC	2
430			min	-.008	2	-.015	3	-.002	3	-4.607e-5	1	1196.426	2	7004.023	1
431		7	max	.007	3	.021	2	.002	1	3.178e-6	10	NC	5	NC	2
432			min	-.008	2	-.019	3	-.003	3	-1.011e-4	1	1068.2	2	8433.995	1
433		8	max	.007	3	.024	2	0	2	-1.427e-6	10	NC	5	NC	1
434			min	-.008	2	-.021	3	-.003	3	-1.561e-4	1	988.183	2	NC	1
435		9	max	.007	3	.026	2	0	10	-6.033e-6	10	NC	5	NC	1
436			min	-.008	2	-.023	3	-.003	3	-2.111e-4	1	941.267	2	NC	1
437		10	max	.007	3	.027	2	0	10	-9.823e-6	15	NC	5	NC	1
438			min	-.008	2	-.023	3	-.004	3	-2.662e-4	1	920.281	2	NC	1
439		11	max	.007	3	.027	2	0	10	-1.187e-5	15	NC	5	NC	1
440			min	-.008	2	-.022	3	-.005	1	-3.212e-4	1	922.696	2	NC	1
441		12	max	.007	3	.025	2	0	15	-1.392e-5	15	NC	5	NC	1
442			min	-.008	2	-.02	3	-.007	1	-3.762e-4	1	949.668	2	NC	1
443		13	max	.007	3	.022	2	0	15	-1.596e-5	15	NC	5	NC	2
444			min	-.008	2	-.017	3	-.008	1	-4.312e-4	1	1006.644	2	8418.724	1
445		14	max	.007	3	.017	2	0	15	-1.801e-5	15	NC	5	NC	2
446			min	-.008	2	-.014	3	-.009	1	-4.862e-4	1	1106.082	2	6992.039	1
447		15	max	.007	3	.011	2	0	15	-2.006e-5	15	NC	4	NC	2
448			min	-.008	2	-.009	3	-.009	1	-5.413e-4	1	1275.226	2	6488.636	1
449		16	max	.007	3	.004	2	0	15	-2.159e-5	15	NC	4	NC	2
450			min	-.008	2	-.003	3	-.009	1	-5.831e-4	1	1580.414	2	6719.298	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
451		17	max	.007	3	.003	3	0	15	1.549e-5	3	NC	4	NC	2
452			min	-.008	2	-.005	2	-.008	1	-3.099e-4	1	2231.555	2	8087.314	1
453		18	max	.007	3	.01	3	0	15	3.873e-3	3	NC	4	NC	1
454			min	-.008	2	-.015	2	-.005	1	-8.757e-3	2	4319.527	2	NC	1
455		19	max	.007	3	.018	3	0	3	7.8e-3	3	NC	1	NC	1
456			min	-.008	2	-.027	2	-.002	1	-1.758e-2	2	NC	1	NC	1
457	M13	1	max	.005	1	.023	3	.007	3	3.686e-3	3	NC	1	NC	1
458			min	-.002	3	-.021	2	-.007	2	-3.498e-3	2	NC	1	NC	1
459		2	max	.005	1	.154	3	.018	1	4.612e-3	3	NC	5	NC	2
460			min	-.002	3	-.131	1	-.003	10	-4.423e-3	1	1095.25	3	6382.592	1
461		3	max	.005	1	.262	3	.048	1	5.538e-3	3	NC	5	NC	3
462			min	-.002	3	-.221	1	0	10	-5.351e-3	1	601.595	3	2749.655	1
463		4	max	.005	1	.33	3	.073	1	6.463e-3	3	NC	5	NC	3
464			min	-.002	3	-.279	1	0	10	-6.278e-3	1	467.924	3	1876.358	1
465		5	max	.005	1	.352	3	.084	1	7.389e-3	3	NC	5	NC	3
466			min	-.002	3	-.298	1	0	10	-7.206e-3	1	437.605	3	1642.827	1
467		6	max	.005	1	.327	3	.078	1	8.315e-3	3	NC	5	NC	3
468			min	-.002	3	-.278	1	-.002	10	-8.133e-3	1	473.445	3	1762.113	1
469		7	max	.004	1	.265	3	.056	1	9.24e-3	3	NC	5	NC	2
470			min	-.002	3	-.228	1	-.006	10	-9.061e-3	1	594.537	3	2391.358	1
471		8	max	.004	1	.184	3	.025	1	1.017e-2	3	NC	5	NC	2
472			min	-.002	3	-.161	1	-.01	10	-9.988e-3	1	895.599	3	4953.616	1
473		9	max	.004	1	.109	3	.02	3	1.109e-2	3	NC	4	NC	1
474			min	-.002	3	-.099	1	-.021	2	-1.092e-2	1	1677.651	3	NC	1
475		10	max	.004	1	.074	3	.022	3	1.202e-2	3	NC	4	NC	4
476			min	-.002	3	-.071	1	-.027	2	-1.184e-2	1	2787.522	3	7491.618	2
477		11	max	.004	1	.109	3	.025	3	1.109e-2	3	NC	4	NC	1
478			min	-.002	3	-.099	1	-.021	2	-1.092e-2	1	1677.65	3	8213.161	3
479		12	max	.004	1	.184	3	.026	3	1.017e-2	3	NC	5	NC	2
480			min	-.002	3	-.161	1	-.01	10	-9.988e-3	1	895.598	3	4865.001	1
481		13	max	.004	1	.265	3	.057	1	9.243e-3	3	NC	5	NC	2
482			min	-.002	3	-.228	1	-.006	10	-9.061e-3	1	594.537	3	2373.714	1
483		14	max	.004	1	.327	3	.078	1	8.318e-3	3	NC	5	NC	5
484			min	-.002	3	-.278	1	-.002	10	-8.133e-3	1	473.445	3	1756.991	1
485		15	max	.004	1	.352	3	.083	1	7.393e-3	3	NC	5	NC	5
486			min	-.002	3	-.298	1	0	10	-7.206e-3	1	437.604	3	1643.217	1
487		16	max	.004	1	.331	3	.072	1	6.468e-3	3	NC	5	NC	3
488			min	-.002	3	-.279	1	0	10	-6.278e-3	1	467.924	3	1882.538	1
489		17	max	.004	1	.262	3	.048	1	5.543e-3	3	NC	5	NC	3
490			min	-.002	3	-.221	1	0	10	-5.351e-3	1	601.594	3	2769.609	1
491		18	max	.004	1	.154	3	.018	1	4.619e-3	3	NC	5	NC	2
492			min	-.002	3	-.131	1	-.003	10	-4.423e-3	1	1095.25	3	6474.204	1
493		19	max	.004	1	.023	3	.007	3	3.694e-3	3	NC	1	NC	1
494			min	-.002	3	-.021	2	-.007	2	-3.5e-3	2	NC	1	NC	1
495	M16	1	max	.002	1	.018	3	.007	3	4.229e-3	2	NC	1	NC	1
496			min	0	3	-.027	2	-.008	2	-2.825e-3	3	NC	1	NC	1
497		2	max	.002	1	.078	3	.018	1	5.331e-3	2	NC	5	NC	2
498			min	0	3	-.163	2	-.003	10	-3.52e-3	3	1059.453	2	6376.983	1
499		3	max	.002	1	.128	3	.048	1	6.433e-3	2	NC	5	NC	3
500			min	0	3	-.274	2	0	10	-4.215e-3	3	581.34	2	2747.918	1
501		4	max	.002	1	.161	3	.072	1	7.535e-3	2	NC	5	NC	3
502			min	0	3	-.346	2	0	10	-4.91e-3	3	451.335	2	1875.441	1
503		5	max	.002	1	.172	3	.083	1	8.637e-3	2	NC	5	NC	5
504			min	0	3	-.369	2	0	10	-5.605e-3	3	420.783	2	1642.25	1
505		6	max	.002	1	.163	3	.077	1	9.739e-3	2	NC	5	NC	5
506			min	0	3	-.345	2	-.002	10	-6.299e-3	3	452.828	2	1761.883	1
507		7	max	.002	1	.138	3	.056	1	1.084e-2	2	NC	5	NC	2

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
508			min	0	3	-.282	2	-.006	10	-6.994e-3	3	563.044	2	2392.354	1
509		8	max	.002	1	.104	3	.025	1	1.194e-2	2	NC	5	NC	2
510			min	0	3	-.2	2	-.01	10	-7.689e-3	3	830.575	2	4967.071	1
511		9	max	.002	1	.072	3	.023	3	1.304e-2	2	NC	4	NC	1
512			min	0	3	-.124	2	-.021	2	-8.384e-3	3	1479.688	2	8880.776	3
513		10	max	.002	1	.057	3	.021	3	1.415e-2	2	NC	4	NC	4
514			min	0	3	-.089	2	-.027	2	-9.079e-3	3	2300.783	2	7488.857	2
515		11	max	.002	1	.072	3	.021	3	1.304e-2	2	NC	4	NC	1
516			min	0	3	-.124	2	-.021	2	-8.383e-3	3	1479.688	2	NC	1
517		12	max	.002	1	.104	3	.025	1	1.194e-2	2	NC	5	NC	2
518			min	0	3	-.2	2	-.01	10	-7.687e-3	3	830.575	2	4929.958	1
519		13	max	.002	1	.138	3	.056	1	1.084e-2	2	NC	5	NC	2
520			min	0	3	-.282	2	-.006	10	-6.992e-3	3	563.044	2	2389.819	1
521		14	max	.002	1	.163	3	.077	1	9.74e-3	2	NC	5	NC	3
522			min	0	3	-.345	2	-.002	10	-6.296e-3	3	452.828	2	1765.553	1
523		15	max	.002	1	.172	3	.083	1	8.638e-3	2	NC	5	NC	3
524			min	0	3	-.369	2	0	10	-5.6e-3	3	420.783	2	1649.979	1
525		16	max	.002	1	.161	3	.072	1	7.536e-3	2	NC	5	NC	3
526			min	0	3	-.346	2	0	10	-4.905e-3	3	451.335	2	1889.875	1
527		17	max	.002	1	.128	3	.047	1	6.434e-3	2	NC	5	NC	3
528			min	0	3	-.274	2	0	10	-4.209e-3	3	581.34	2	2781.069	1
529		18	max	.002	1	.078	3	.018	1	5.333e-3	2	NC	5	NC	2
530			min	0	3	-.163	2	-.003	10	-3.513e-3	3	1059.454	2	6507.614	1
531		19	max	.002	1	.018	3	.007	3	4.231e-3	2	NC	1	NC	1
532			min	0	3	-.027	2	-.008	2	-2.818e-3	3	NC	1	NC	1
533	M15	1	max	0	1	0	1	0	1	3.516e-4	3	NC	1	NC	1
534			min	0	1	0	1	0	1	-6.001e-5	2	NC	1	NC	1
535		2	max	0	3	-.002	15	.001	1	8.372e-4	3	NC	1	NC	1
536			min	0	2	-.009	4	0	3	-5.719e-4	2	9029.93	4	NC	1
537		3	max	0	3	-.004	15	.004	1	1.323e-3	3	NC	5	NC	1
538			min	0	2	-.018	4	-.003	3	-1.084e-3	2	4595.023	4	NC	1
539		4	max	0	3	-.006	15	.008	1	1.808e-3	3	NC	15	NC	4
540			min	0	2	-.026	4	-.007	3	-1.596e-3	2	3152.454	4	7129.531	1
541		5	max	0	3	-.008	15	.012	1	2.294e-3	3	NC	15	NC	4
542			min	0	2	-.033	4	-.011	3	-2.107e-3	1	2459.892	4	4700.523	3
543		6	max	0	3	-.009	15	.017	1	2.78e-3	3	8807.18	15	NC	4
544			min	0	2	-.039	4	-.016	3	-2.624e-3	1	2070.259	4	3423.134	3
545		7	max	0	3	-.01	15	.022	1	3.265e-3	3	7810.38	15	NC	4
546			min	0	2	-.044	4	-.021	3	-3.141e-3	1	1835.946	4	2676.269	3
547		8	max	0	3	-.011	15	.027	1	3.751e-3	3	7212.15	15	NC	4
548			min	0	2	-.048	4	-.026	3	-3.658e-3	1	1695.324	4	2206.805	3
549		9	max	0	3	-.012	15	.031	1	4.237e-3	3	6890.147	15	NC	4
550			min	-.001	2	-.05	4	-.031	3	-4.175e-3	1	1619.632	4	1899.603	3
551		10	max	0	3	-.012	15	.035	1	4.722e-3	3	6788.281	15	NC	5
552			min	-.001	2	-.051	4	-.035	3	-4.692e-3	1	1595.687	4	1696.846	3
553		11	max	0	3	-.012	15	.037	1	5.208e-3	3	6890.147	15	NC	5
554			min	-.001	2	-.05	4	-.037	3	-5.209e-3	1	1619.632	4	1568.185	3
555		12	max	0	3	-.011	15	.038	1	5.693e-3	3	7212.15	15	NC	5
556			min	-.001	2	-.048	4	-.038	3	-5.726e-3	1	1695.324	4	1498.558	3
557		13	max	0	3	-.01	15	.037	1	6.179e-3	3	7810.38	15	NC	5
558			min	-.002	2	-.045	4	-.037	3	-6.243e-3	1	1835.946	4	1483.59	3
559		14	max	0	3	-.009	15	.034	1	6.665e-3	3	8807.18	15	NC	5
560			min	-.002	2	-.04	4	-.034	3	-6.759e-3	1	2070.259	4	1529.74	3
561		15	max	0	3	-.008	15	.029	1	7.15e-3	3	NC	15	NC	4
562			min	-.002	2	-.034	4	-.028	3	-7.276e-3	1	2459.892	4	1660.766	3
563		16	max	.001	3	-.006	15	.021	1	7.636e-3	3	NC	15	NC	4
564			min	-.002	2	-.026	4	-.02	3	-7.793e-3	1	3152.454	4	1941.197	3

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
565		17	max	.001	3	-.004	15	.01	1	8.122e-3	3	NC	5	NC	4
566			min	-.002	2	-.018	4	-.008	3	-8.31e-3	1	4595.023	4	2573.492	3
567		18	max	.001	3	-.002	12	.007	3	8.607e-3	3	NC	1	NC	4
568			min	-.002	2	-.01	4	-.011	2	-8.827e-3	1	9029.93	4	4581.853	3
569		19	max	.001	3	.003	2	.026	3	9.093e-3	3	NC	1	NC	1
570			min	-.002	2	-.002	9	-.029	2	-9.344e-3	1	NC	1	NC	1
571	M16A	1	max	0	10	0	10	.008	3	2.677e-3	3	NC	1	NC	1
572			min	-.001	3	-.001	9	-.008	2	-2.662e-3	2	NC	1	NC	1
573		2	max	0	10	-.002	15	.003	9	2.567e-3	3	NC	1	NC	1
574			min	-.001	3	-.009	4	-.002	2	-2.543e-3	2	9029.93	4	NC	1
575		3	max	0	10	-.004	15	.009	1	2.457e-3	3	NC	5	NC	4
576			min	-.001	3	-.018	4	-.004	3	-2.424e-3	2	4595.023	4	6068.951	1
577		4	max	0	10	-.006	15	.013	1	2.347e-3	3	NC	15	NC	4
578			min	0	3	-.026	4	-.008	3	-2.305e-3	2	3152.454	4	4609.509	1
579		5	max	0	10	-.008	15	.016	1	2.237e-3	3	NC	15	NC	4
580			min	0	3	-.033	4	-.01	3	-2.186e-3	2	2459.892	4	3974.662	1
581		6	max	0	10	-.009	15	.018	1	2.127e-3	3	8807.18	15	NC	4
582			min	0	3	-.039	4	-.012	3	-2.067e-3	2	2070.259	4	3694.195	1
583		7	max	0	10	-.01	15	.019	1	2.017e-3	3	7810.38	15	NC	4
584			min	0	3	-.044	4	-.013	3	-1.948e-3	2	1835.946	4	3620.358	1
585		8	max	0	10	-.011	15	.019	1	1.908e-3	3	7212.15	15	NC	4
586			min	0	3	-.048	4	-.013	3	-1.829e-3	2	1695.324	4	3701.983	1
587		9	max	0	10	-.012	15	.018	1	1.798e-3	3	6890.147	15	NC	4
588			min	0	3	-.05	4	-.012	3	-1.71e-3	2	1619.632	4	3930.921	1
589		10	max	0	10	-.012	15	.016	1	1.688e-3	3	6788.281	15	NC	4
590			min	0	3	-.051	4	-.011	3	-1.591e-3	2	1595.687	4	4329.221	1
591		11	max	0	10	-.012	15	.014	1	1.578e-3	3	6890.147	15	NC	4
592			min	0	3	-.05	4	-.009	3	-1.472e-3	2	1619.632	4	4953.434	1
593		12	max	0	10	-.011	15	.012	1	1.468e-3	3	7212.15	15	NC	4
594			min	0	3	-.048	4	-.008	3	-1.353e-3	2	1695.324	4	5915.841	1
595		13	max	0	10	-.01	15	.009	1	1.358e-3	3	7810.38	15	NC	2
596			min	0	3	-.044	4	-.006	3	-1.234e-3	2	1835.946	4	7438.801	1
597		14	max	0	10	-.009	15	.007	1	1.248e-3	3	8807.18	15	NC	2
598			min	0	3	-.039	4	-.004	3	-1.116e-3	2	2070.259	4	9997.282	1
599		15	max	0	10	-.008	15	.004	1	1.138e-3	3	NC	15	NC	1
600			min	0	3	-.033	4	-.002	3	-9.966e-4	2	2459.892	4	NC	1
601		16	max	0	10	-.006	15	.002	1	1.029e-3	3	NC	15	NC	1
602			min	0	3	-.026	4	0	3	-8.776e-4	2	3152.454	4	NC	1
603		17	max	0	10	-.004	15	0	9	9.186e-4	3	NC	5	NC	1
604			min	0	3	-.018	4	0	2	-7.587e-4	2	4595.023	4	NC	1
605		18	max	0	10	-.002	15	0	4	8.087e-4	3	NC	1	NC	1
606			min	0	3	-.009	4	0	2	-6.397e-4	2	9029.93	4	NC	1
607		19	max	0	1	0	1	0	1	6.988e-4	3	NC	1	NC	1
608			min	0	1	0	1	0	1	-5.208e-4	2	NC	1	NC	1

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 4.00 x 0.28

<Figure 1>



<Figure 2>



Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	405.0	6.0	101.0	101.2
Sum	405.0	6.0	101.0	101.2

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 405
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	5.333	10469

$\phi N_{cb} = \phi \, (A_{Nc} / A_{Nco}) \, \Psi_{ed,N} \, \Psi_{c,N} \, \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-4)

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cb} (lb)
253.92	256.00	0.995	1.00	1.000	10469	0.65	6717

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_a = \phi \, (A_{Na} / A_{Na0}) \, \Psi_{ed,Na} \, \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16a)

A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	ϕ	ϕN_a (lb)
109.66	109.66	1.000	1.000	9755	0.55	5365

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in y-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	8.00	8488

$\phi V_{cby} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cby} (lb)
238.44	288.00	0.897	1.000	1.000	8488	0.70	4411

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cbx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbx} (lb)
188.88	278.72	0.903	1.000	1.000	8282	0.70	3549

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	8.00	8488

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
238.44	288.00	1.000	1.000	1.000	8488	0.70	9838

Shear parallel to edge in y-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cby} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cby} (lb)
188.88	278.72	1.000	1.000	1.000	8282	0.70	7858

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cp} = \phi \min|k_{cp}N_a\,;\,k_{cp}N_{cb}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\,\Psi_{p,Na}N_{a0}\,;\,k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ed,N}\,\Psi_{c,N}\,\Psi_{cp,N}N_b|$ (Eq. D-30a)

k_{cp}	A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	109.66	109.66	1.000	1.000	9755	9755

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ	ϕV_{cp} (lb)
253.92	256.00	0.995	1.000	1.000	10469	10334	0.70	13657

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, ϕN_n (lb)	Ratio	Status
Steel	405	6071	0.07	Pass
Concrete breakout	405	6717	0.06	Pass
Adhesive	**405**	**5365**	**0.08**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, ϕV_n (lb)	Ratio	Status
Steel	**101**	**3156**	**0.03**	**Pass (Governs)**
T Concrete breakout y+	101	4411	0.02	Pass
T Concrete breakout x+	6	3549	0.00	Pass
|| Concrete breakout y+	6	9838	0.00	Pass
|| Concrete breakout x+	101	7858	0.01	Pass
Concrete breakout, combined	-	-	0.02	Pass
Pryout	101	13657	0.01	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status
Sec. D.7.1	0.08	0.00	7.5 %	1.0	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 9.00 x 4.00 x 0.28

<Figure 1>



<Figure 2>



Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	732.5	499.5	0.0	499.5
2	732.5	499.5	0.0	499.5
Sum	1465.0	999.0	0.0	999.0

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 1465
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	5.333	10469

$\phi N_{cbg} = \phi (A_{Nc} / A_{Nco}) \Psi_{ec,N} \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-5)

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cbg} (lb)
314.72	256.00	1.000	0.865	1.00	1.000	10469	0.65	7233

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_{ag} = \phi (A_{Na} / A_{Na0}) \Psi_{ed,Na} \Psi_{g,Na} \Psi_{ec,Na} \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16b)

A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0}(lb)	ϕ	ϕN_{ag} (lb)
177.03	109.66	0.952	1.021	1.000	1.000	9755	0.55	8418

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	12.00	15593

$\phi V_{cbx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in²)	A_{Vco} (in²)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbx} (lb)
288.00	648.00	0.833	1.000	1.000	15593	0.70	4043

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	8.00	8488

$\phi V_{cbgx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ec,V}\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-22)

A_{Vc} (in²)	A_{Vco} (in²)	$\Psi_{ec,V}$	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbgx} (lb)
284.04	288.00	1.000	1.000	1.000	1.000	8488	0.70	11720

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cpg} = \phi \min|k_{cp}N_{ag}\,;\, k_{cp}N_{cbg}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\,\Psi_{g,Na}\,\Psi_{ec,Na}\,\Psi_{p,Na}N_{a0}\,;\, k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ec,N}\,\Psi_{ed,N}\,\Psi_{c,N}\,\Psi_{cp,N}N_b|$ (Eq. D-30b)

k_{cp}	A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	177.03	109.66	0.952	1.021	1.000	1.000	9755	15305

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ
314.72	256.00	1.000	0.865	1.000	1.000	10469	11128	0.70

ϕV_{cpg} (lb)
15580

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, øN_n (lb)	Ratio	Status
Steel	733	6071	0.12	Pass
Concrete breakout	**1465**	**7233**	**0.20**	**Pass (Governs)**
Adhesive	1465	8418	0.17	Pass

Shear	Factored Load, V_{ua} (lb)	Design Strength, øV_n (lb)	Ratio	Status
Steel	500	3156	0.16	Pass
T Concrete breakout x+	**999**	**4043**	**0.25**	**Pass (Governs)**
|| Concrete breakout y-	**999**	**11720**	**0.09**	**Pass (Governs)**
Pryout	999	15580	0.06	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status

Sec. D.7.3	0.20	0.25	45.0 %	1.2	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.