

Schletter, Inc.		20° Tilt w/o Seismic Design
HCV	Standard PVMax Racking System	
	Representative Calculations - ASCE 7-10	

1. INTRODUCTION

1.1 Project Description

The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. PVMax ground mount system.

1.2 Construction

Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to aluminum struts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

	Maximum		Minimum
Height =	2000 mm	Height =	1900 mm
Width =	1050 mm	Width =	970 mm
Dead Load =	3.00 psf	Dead Load =	1.75 psf

Modules Per Row =	2
Module Tilt =	20°
Maximum Height Above Grade =	3 ft



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

1.3 Technical Codes

- ASCE 7-10 - Chapter 26-31, Wind Loads
- ASCE 7-10 - Chapter 7, Snow Loads
- ASCE 7-10 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2012, 2015
- Aluminum Design Manual, Eighth Edition, 2005

2. LOAD ACTIONS

2.1 Permanent Loads

g_{MAX} =	3.00 psf	*Self-weight of the PV modules.*
g_{MIN} =	1.75 psf	

2.2 Snow Loads

Ground Snow Load, P_g =	30.00 psf	
Sloped Roof Snow Load, P_s =	20.62 psf	*(ASCE 7-10, Eq. 7.4-1)*
I_s =	1.00	
C_s =	0.91	
C_e =	0.90	
C_t =	1.20	

2.3 Wind Loads

Design Wind Speed, V =	115 mph	Exposure Category = C
Height <	15 ft	Importance Category = II

Peak Velocity Pressure, q_z = 20.76 psf *Including the gust factor, G=0.85. (ASCE 7-10, Eq. 27.3-1)*

Pressure Coefficients

$Cf+_{TOP}$	=	1.050	*(Pressure)*
$Cf+_{BOTTOM}$	=	1.650	
$Cf-_{TOP, OUTER PURLIN}$	=	-2.400	
$Cf-_{TOP, INNER PURLIN}$	=	-1.840	*(Suction)*
$Cf-_{BOTTOM}$	=	-1.000	

Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0611-1e. Negative forces are applied away from the surface.

2.4 Seismic Loads - N/A

S_S =	0.00	R =	1.25
S_{DS} =	0.00	C_S =	0
S_1 =	0.00	ρ =	1.3
S_{D1} =	0.00	Ω =	1.25
T_a =	0.00	C_d =	1.25

ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.5W
1.2D + 1.0W + 0.5S
0.9D + 1.0W [M]
1.54D + 1.3E + 0.2S [R]
0.56D + 1.3E [R]
1.54D + 1.25E + 0.2S [O]
0.56D + 1.25E [O]

(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S
1.0D + 0.6W
1.0D + 0.75L + 0.45W + 0.75S
0.6D + 0.6W [M]
1.238D + 0.875E [O]
1.1785D + 0.65625E + 0.75S [O]
0.362D + 0.875E [O]

(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)

[M] *Uses the minimum allowable module dead load.*
[R] *Include redundancy factor of 1.3.*
[O] *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location
M13	Top
M14	Mid-Top
M15	Mid-Bottom
M16	Bottom

Girders	Location
M1	Outer
M5	Inner
M9	Outer

Front Struts	Location
M4	Outer
M8	Inner
M12	Outer

Diagonal Struts	Location
M3	Outer
M7	Inner
M11	Outer

Rear Struts	Location
M2	Outer
M6	Inner
M10	Outer

Front Reactions	Location
N7	Outer
N15	Inner
N23	Outer

Rear Reactions	Location
N8	Outer
N16	Inner
N24	Outer

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type	=	**S1.5**
Aluminum Type	=	6105-T5
F_{ty}	=	35 ksi
L_b	=	108 in
$\Phi F_{ty\ STRONG\text{-}AXIS}$	=	25.07 ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$	=	23.08 ksi
S_y	=	1.33 in^3
S_x	=	0.60 in^3
E	=	10100 ksi
I_y	=	2.16 in^4
I_x	=	1.07 in^4
A	=	1.25 in^2
g	=	1.50 lbs/ft
M_y	=	1.742 k-ft
M_z	=	0.292 k-ft
$M_{y\ allowable}$	=	2.779 k-ft
$M_{z\ allowable}$	=	1.154 k-ft
Utilization	=	88%



DETAIL VIEW

4.2 Girder Design

Loads from purlins are transferred using an inclined girder, which is connected to a set of aluminum struts. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type	=	**BF0**
Aluminum Type	=	6105-T5
F_{ty}	=	35 ksi
L_b	=	104.56 in
$\Phi F_{ty\ AXIAL}$	=	31.09 ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$	=	29.00 ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$	=	33.25 ksi
S_y	=	1.42 in^3
S_x	=	1.41 in^3
E	=	10100 ksi
I_y	=	2.39 in^4
I_x	=	2.22 in^4
A	=	1.88 in^2
g	=	2.26 lbs/ft
M_y	=	-3.349 k-ft
M_z	=	0.000 k-ft
P_n	=	-0.384 k
$M_{y\ allowable}$	=	3.422 k-ft
$M_{z\ allowable}$	=	3.907 k-ft
$P_{n\ allowable}$	=	58.535 k
Utilization	=	99%



4.3 Front Strut Design

The front aluminum strut connects a portion of the girder to the foundation. Vertical girder forces are then transferred down through the strut into the foundation. The strut is attached with single M12 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	24.80	in
$\Phi F_{ty\ AXIAL}$ =	28.03	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.000	k-ft
M_z =	0.000	k-ft
P_n =	3.272	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	27.532	k
Utilization =	12%	



4.4 Diagonal Strut Design

A diagonal aluminum strut braces the support structure. It connects at a front portion of the girder and transfers horizontal forces to the rear foundation connection. The strut is attached with single M12 bolts at each end. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	98.03	in
$\Phi F_{ty\ AXIAL}$ =	6.11	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.012	k-ft
M_z =	0.000	k-ft
P_n =	1.485	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	6.000	k
Utilization =	26%	



4.5 Rear Strut Design

An aluminum strut connects the rear portion of the girder to the rear foundation connection. Both vertical and horizontal forces are transferred from the girder. The strut is attached with single M12 bolts at each end. See Appendix A.5 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	61.10	in
$\Phi F_{ty\ AXIAL}$ =	13.63	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	-0.011	k-ft
M_z =	0.000	k-ft
P_n =	3.448	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	13.386	k
Utilization =	27%	



5. FOUNDATION DESIGN CALCULATIONS

5.1 Helical Pile Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete foundation design.

Maximum	Front	Rear	
Tensile Load =	784.03	4550.94	k
Compressive Load =	4252.95	4782.65	k
Lateral Load =	15.96	2057.86	k
Moment (Weak Axis) =	0.03	0.01	k

5.2 Design of Ballast Foundations

Ballast foundations are used to secure the racking structure in place. The foundations are checked for potential overturning and sliding. Bearing pressures applied by the racking and ballast foundations are checked against the allowable bearing pressures provided by the IBC table 1806.2 (2012, 2015).



Concrete Properties

Weight of Concrete =	145 pcf
Compressive Strength =	2500 psi
Yield Strength =	60000 psi

Overturning Check

M_O =	121841.1 in-lbs
Resisting Force Required =	1704.07 lbs
S.F. =	1.67
Weight Required =	2840.12 lbs
Minimum Width =	35 in in
Weight Provided =	7559.64 lbs

Sliding

Force =	474.56 lbs
Friction =	0.4
Weight Required =	1186.40 lbs
Resisting Weight =	7559.64 lbs
Additional Weight Required =	0 lbs

Cohesion

Sliding Force =	474.56 lbs
Cohesion =	130 psf
Area =	34.76 ft^2
Resisting =	3779.82 lbs
Additional Weight Required =	0 lbs

Shear Key

Additional Force =	0 lbs
Lateral Bearing Pressure =	200 psf/ft
Required Depth =	0.00 ft
f'_c =	2500 psi
Length =	8 in

Footing Reinforcement

Use fiber reinforcing with (2) #5 rebar.

A minimum 143in long x 35in wide x 18in tall ballast foundation is required to resist overturning.

Use a 143in long x 35in wide x 18in tall ballast foundation to resist sliding. Friction is OK.

Use a 143in long x 35in wide x 18in tall ballast foundation. Cohesion is OK.

Shear key is not required.

Bearing Pressure

	Ballast Width			
	35 in	36 in	37 in	38 in
P_{ftg} = (145 pcf)(11.92 ft)(1.5 ft)(2.92 ft) =	7560 lbs	7776 lbs	7992 lbs	8208 lbs

ASD LC	1.0D + 1.0S				1.0D + 0.6W				1.0D + 0.75L + 0.45W + 0.75S				0.6D + 0.6W			
Width	35 in	36 in	37 in	38 in	35 in	36 in	37 in	38 in	35 in	36 in	37 in	38 in	35 in	36 in	37 in	38 in
F_A	1582 lbs	1582 lbs	1582 lbs	1582 lbs	1273 lbs	1273 lbs	1273 lbs	1273 lbs	2012 lbs	2012 lbs	2012 lbs	2012 lbs	-352 lbs	-352 lbs	-352 lbs	-352 lbs
F_B	1703 lbs	1703 lbs	1703 lbs	1703 lbs	1550 lbs	1550 lbs	1550 lbs	1550 lbs	2302 lbs	2302 lbs	2302 lbs	2302 lbs	-2090 lbs	-2090 lbs	-2090 lbs	-2090 lbs
F_V	170 lbs	170 lbs	170 lbs	170 lbs	855 lbs	855 lbs	855 lbs	855 lbs	756 lbs	756 lbs	756 lbs	756 lbs	-949 lbs	-949 lbs	-949 lbs	-949 lbs
P_{total}	10845 lbs	11061 lbs	11277 lbs	11493 lbs	10383 lbs	10599 lbs	10815 lbs	11031 lbs	11874 lbs	12090 lbs	12306 lbs	12522 lbs	2094 lbs	2223 lbs	2353 lbs	2482 lbs
M	3593 lbs-ft	3593 lbs-ft	3593 lbs-ft	3593 lbs-ft	3436 lbs-ft	3436 lbs-ft	3436 lbs-ft	3436 lbs-ft	4978 lbs-ft	4978 lbs-ft	4978 lbs-ft	4978 lbs-ft	2909 lbs-ft	2909 lbs-ft	2909 lbs-ft	2909 lbs-ft
e	0.33 ft	0.32 ft	0.32 ft	0.31 ft	0.33 ft	0.32 ft	0.32 ft	0.31 ft	0.42 ft	0.41 ft	0.40 ft	0.40 ft	1.39 ft	1.31 ft	1.24 ft	1.17 ft
L/6	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft
f_{min}	260.0 psf	258.8 psf	257.7 psf	256.6 psf	249.0 psf	248.1 psf	247.3 psf	246.5 psf	269.5 psf	268.1 psf	266.7 psf	265.4 psf	18.1 psf	21.2 psf	24.2 psf	27.0 psf
f_{max}	364.1 psf	360.0 psf	356.2 psf	352.5 psf	348.5 psf	344.9 psf	341.4 psf	338.2 psf	413.7 psf	408.3 psf	403.1 psf	398.2 psf	102.4 psf	103.2 psf	103.9 psf	104.6 psf

Maximum Bearing Pressure = 414 psf
Allowable Bearing Pressure = 1500 psf

Use a 143in long x 35in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Weak Side Design

Overturning Check

M_O =	1335.7 ft-lbs
Resisting Force Required =	915.90 lbs
S.F. =	1.67
Weight Required =	1526.50 lbs
Minimum Width =	35 in in
Weight Provided =	7559.64 lbs

A minimum 143in long x 35in wide x 18in tall ballast foundation is required to resist overturning.



Bearing Pressure

ASD LC	1.238D + 0.875E			1.1785D + 0.65625E + 0.75S			0.362D + 0.875E		
Width	35 in			35 in			35 in		
Support	Outer	Inner	Outer	Outer	Inner	Outer	Outer	Inner	Outer
F_Y	257 lbs	663 lbs	257 lbs	930 lbs	2694 lbs	930 lbs	75 lbs	194 lbs	75 lbs
F_V	1 lbs	0 lbs	1 lbs	6 lbs	0 lbs	6 lbs	0 lbs	0 lbs	0 lbs
P_{total}	9616 lbs	7560 lbs	9616 lbs	9839 lbs	7560 lbs	9839 lbs	2812 lbs	7560 lbs	2812 lbs
M	5 lbs-ft	0 lbs-ft	5 lbs-ft	20 lbs-ft	0 lbs-ft	20 lbs-ft	1 lbs-ft	0 lbs-ft	1 lbs-ft
e	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft
L/6	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft
f_{min}	276.4 psf	217.5 psf	276.4 psf	281.9 psf	217.5 psf	281.9 psf	80.9 psf	217.5 psf	80.9 psf
f_{max}	277.0 psf	217.5 psf	277.0 psf	284.3 psf	217.5 psf	284.3 psf	80.9 psf	217.5 psf	80.9 psf

Maximum Bearing Pressure = 284 psf
Allowable Bearing Pressure = 1500 psf

Use a 143in long x 35in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Foundation Requirements: 143in long x 23in wide x 18in tall ballast foundation and fiber reinforcing with (1) #5 rebar.

5.3 Foundation Anchors

Threaded rods are anchored to the the ballast foundations using the Simpson AT-XP epoxy solution. LRFD load results are compared to the allowable strengths of the epoxy solution. Please see the supplementary calculations provided by the Simpson Anchor Designer software.

6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of 80mm mounting clamps. The reliability of calculations is uncertain due to limited standards, therefore the strength of the clamp fasteners has been evaluated by load testing.

Fastening of Modules to Purlins

Maximum Uplifting Force	=	0.545 k
Allowable Uplift	=	1.214 k
Utilization	=	45%



Fastening of Purlins to Girders

Maximum Uplifting Force	=	1.730 k
Allowable Uplift	=	4.357 k
Utilization	=	40%



6.2 Strut Connections

The aluminum struts connect the aluminum girder ends to custom brackets with mounting holes. Single M12 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Front Strut

Maximum Axial Load	=	3.272 k
M12 Bolt Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	44%

Rear Strut

Maximum Axial Load	=	3.448 k
M12 Bolt Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	46%

Diagonal Strut

Maximum Axial Load	=	1.579 k
M12 Bolt Shear Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	21%

Bolt and bearing capacities are accounting for double shear. (ASCE 8-02, Eq. 5.3.4-1)



Struts under compression are shown to demonstrate the load transfer from the girder. Single M12 bolts are located at each end of the strut and are subjected to double shear.

7. SEISMIC DESIGN

7.1 Seismic Drift - N/A

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx}	=	51.89 in
Allowable Story Drift for All Other Structures, Δ	= {	$0.020h_{sx}$
		1.038 in
Max Drift, Δ_{MAX}	=	0.034 in

N/A

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **S1.5**

Strong Axis:		Weak Axis:	
3.4.14		**3.4.14**	
L_b =	108 in	L_b =	108
J =	0.432	J =	0.432
	298.779		190.005
$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$		$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$	
S1 =	0.51461	S1 =	0.51461
$S2 = \left(\frac{C_c}{1.6}\right)^2$		$S2 = \left(\frac{C_c}{1.6}\right)^2$	
S2 =	1701.56	S2 =	1701.56
φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]	φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L=	27.7 ksi	φF_L=	28.9
3.4.16		**3.4.16**	
b/t =	32.195	b/t =	37.0588
$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$		$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$	
S1 =	12.2	S1 =	12.2
$S2 = \frac{k_1 Bp}{1.6Dp}$		$S2 = \frac{k_1 Bp}{1.6Dp}$	
S2 =	46.7	S2 =	46.7
φF_L=	φb[Bp-1.6Dp*b/t]	φF_L=	φb[Bp-1.6Dp*b/t]
φF_L=	25.1 ksi	φF_L=	23.1 ksi
3.4.16.1	Not Used	**3.4.16.1**	
Rb/t =		N/A for Weak Direction	
$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$			
S1 =	1.1		
$S2 = C_t$			
S2 =	141.0		
φF_L=	1.17φyFcy		
φF_L=	38.9 ksi		
3.4.18		**3.4.18**	
h/t =	37.0588	h/t =	32.195
$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$		$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$	
S1 =	36.9	S1 =	36.9
m =	0.65	m =	0.65
C_0 =	40.985	C_0 =	45.5
Cc =	41.015	Cc =	45.5
$S2 = \frac{k_1 Bbr}{mDbr}$		$S2 = \frac{k_1 Bbr}{mDbr}$	
S2 =	77.2	S2 =	77.3
φF_L=	φb[Bbr-mDbr*h/t]	φF_L=	1.3φyFcy
φF_L=	43.2 ksi	φF_L=	43.2 ksi
φF_LSt=	25.1 ksi	φF_LWk=	23.1 ksi
Ix =	897074 mm^4	Iy =	446476 mm^4
	2.155 in^4		1.073 in^4
y =	41.015 mm	x =	45.5 mm
Sx =	1.335 in^3	Sy =	0.599 in^3
M_{max}St =	2.788 k-ft	M_{max}Wk =	1.152 k-ft

Compression

3.4.9

b/t = 32.195
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 25.1 ksi

b/t = 37.0588
S1 = 12.21
S2 = 32.70
φF_L = (φck2*√(BpE))/(1.6b/t)
φF_L = 21.9 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 21.94 ksi
A = 1215.13 mm^2
1.88 in^2
P_{max} = 41.32 kips

A.2 Design of Aluminum Girders - Aluminum Design Manual, 2005 Edition

Girder = **BF0**

Strong Axis:

3.4.14

L_b = 104.56 in
J = 1.08
179.85

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.0 ksi

3.4.16

b/t = 16.2

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 31.6 ksi

Weak Axis:

3.4.14

L_b = 104.56
J = 1.08
190.335

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 28.9

3.4.16

b/t = 7.4

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φyFcy
φF_L = 33.3 ksi

3.4.16.1 Used

Rb/t = 18.1

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= φb[Bt-Dt*√(Rb/t)]

φF_L= 31.1 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 7.4

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 35.2

m = 0.68

C_0 = 41.067

Cc = 43.717

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 73.8

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 29.0 ksi

Ix = 984962 mm^4

2.366 in^4

y = 43.717 mm

Sx = 1.375 in^3

$M_{max}St$ = 3.323 k-ft

3.4.18

h/t = 16.2

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 40

Cc = 40

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 33.3 ksi

Iy = 923544 mm^4

2.219 in^4

x = 40 mm

Sy = 1.409 in^3

$M_{max}Wk$ = 3.904 k-ft

Compression

3.4.9

b/t = 16.2

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 31.6 ksi

b/t = 7.4

S1 = 12.21

S2 = 32.70

φF_L= φyFcy

φF_L= 33.3 ksi

3.4.10

Rb/t = 18.1

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L= φc[Bt-Dt*√(Rb/t)]

φF_L= 31.09 ksi

φF_L= 31.09 ksi

A = 1215.13 mm^2

1.88 in^2

P_{max} = 58.55 kips

A.3 Design of Aluminum Struts (Front) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 24.8 in

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

Weak Axis:

3.4.14

L_b = 24.8

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 0.57371

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

S1* = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

S2* = 1.23671

φcc = 0.87952

φF_L = φcc(Bc-Dc*λ)

φF_L = 28.0279 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 28.03 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 28.85 kips

A.4 Design of Aluminum Struts (Diagonal) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 98.03 in

J = 0.942

152.985

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L = 29.4 ksi

Weak Axis:

3.4.14

L_b = 98.03

J = 0.942

152.985

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L = 29.4

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17 \frac{\theta_y}{\theta_b} Fcy}{1.6Dt} \right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

$M_{max}St$ = 1.460 k-ft

$\varphi F_L Wk$= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

$M_{max}Wk$ = 1.460 k-ft

Compression

3.4.7

λ = 2.26776

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi} \sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.89749

φF_L= (φccFcy)/(λ²)

φF_L= 6.10803 ksi

3.4.9

b/t = 24.5
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

b/t = 24.5
S1 = 12.21
S2 = 32.70
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 6.11 ksi
A = 663.99 mm^2
1.03 in^2
P_{max} = 6.29 kips

A.5 Design of Aluminum Struts (Rear) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 61.10 in
J = 0.942
95.3524

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.2 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

Weak Axis:

3.4.14

L_b = 61.1
J = 0.942
95.3524

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.2

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

$M_{max}St$ = 1.460 k-ft

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

$M_{max}Wk$ = 1.460 k-ft

Compression

3.4.7

λ = 1.41345

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.77788

φF_L= (φccFcy)/(λ²)

φF_L= 13.6277 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 13.63 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 14.03 kips

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				4		
2	Dead Load, Min	DL		-1				4		
3	Snow Load	SL						4		
4	Wind Load - Pressure	WL						4		
5	Wind Load - Suction	WL						4		
6	Seismic - Lateral	EL								

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-9.843	-9.843	0	0
2	M14	Y	-9.843	-9.843	0	0
3	M15	Y	-9.843	-9.843	0	0
4	M16	Y	-9.843	-9.843	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-5.454	-5.454	0	0
2	M14	Y	-5.454	-5.454	0	0
3	M15	Y	-5.454	-5.454	0	0
4	M16	Y	-5.454	-5.454	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-63.565	-63.565	0	0
2	M14	Y	-63.565	-63.565	0	0
3	M15	Y	-63.565	-63.565	0	0
4	M16	Y	-63.565	-63.565	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	-71.531	-71.531	0	0
2	M14	y	-71.531	-71.531	0	0
3	M15	y	-112.406	-112.406	0	0
4	M16	y	-112.406	-112.406	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	163.5	163.5	0	0
2	M14	y	125.35	125.35	0	0
3	M15	y	68.125	68.125	0	0
4	M16	y	68.125	68.125	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.5W	Yes	Y		1	1.2	3	1.6	4	.5																
2	LRFD 1.2D + 1.0W + 0.5S	Yes	Y		1	1.2	3	.5	4	1																
3	LRFD 0.9D + 1.0W	Yes	Y		2	.9					5	1														
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3														
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3														
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25														
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25														

Load Combinations (Continued)

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
8																										
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																		
10	ASD 1.0D + 0.6W	Yes	Y		1	1			4	.6																
11	ASD 1.0D + 0.75L + 0.45W + 0....	Yes	Y		1	1	3	.75	4	.45																
12	ASD 0.6D + 0.6W	Yes	Y		2	.6					5	.6														
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875														
14	LATERAL - ASD 1.1785D + 0.65...	Yes	Y		1	1.1...	3	.75			6	.656														
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875														

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N8	max	390.238	2	1131.52	1	.941	1	.005	1	0	1	0	1
2		min	-516.826	3	-1089.649	3	.04	15	0	15	0	1	0	1
3	N7	max	.033	9	1180.671	1	-.454	15	0	15	0	1	0	1
4		min	-.123	2	-167.954	3	-12.274	1	-.025	1	0	1	0	1
5	N15	max	0	15	3271.5	1	0	3	0	3	0	1	0	1
6		min	-1.444	2	-603.098	3	0	2	0	2	0	1	0	1
7	N16	max	1485.979	2	3678.961	1	0	14	0	1	0	1	0	1
8		min	-1582.967	3	-3500.724	3	0	3	0	3	0	1	0	1
9	N23	max	.033	9	1180.671	1	12.274	1	.025	1	0	1	0	1
10		min	-.123	2	-167.954	3	.454	15	0	15	0	1	0	1
11	N24	max	390.238	2	1131.52	1	-.04	15	0	15	0	1	0	1
12		min	-516.826	3	-1089.649	3	-.941	1	-.005	1	0	1	0	1
13	Totals:	max	2264.766	2	11574.842	1	0	1						
14		min	-2617.07	3	-6619.029	3	0	2						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M13	1	max	76.717	1	477.427	1	-6.023	15	0	15	.214	1	0	1
2			min	2.757	15	-532.854	3	-168.665	1	-.014	1	.008	15	0	3
3		2	max	76.717	1	333.296	1	-4.618	15	0	15	.065	1	.454	3
4			min	2.757	15	-375.238	3	-129.223	1	-.014	1	.002	15	-.405	1
5		3	max	76.717	1	189.165	1	-3.213	15	0	15	0	3	.75	3
6			min	2.757	15	-217.623	3	-89.781	1	-.014	1	-.044	1	-.667	1
7		4	max	76.717	1	45.033	1	-1.809	15	0	15	-.003	12	.889	3
8			min	2.757	15	-60.008	3	-50.339	1	-.014	1	-.114	1	-.784	1
9		5	max	76.717	1	97.608	3	-.404	15	0	15	-.005	12	.87	3
10			min	2.757	15	-99.098	1	-10.897	1	-.014	1	-.145	1	-.757	1
11		6	max	76.717	1	255.223	3	28.545	1	0	15	-.005	15	.694	3
12			min	2.757	15	-243.23	1	.296	12	-.014	1	-.136	1	-.585	1
13		7	max	76.717	1	412.838	3	67.987	1	0	15	-.003	15	.36	3
14			min	2.757	15	-387.361	1	1.724	12	-.014	1	-.088	1	-.27	1
15		8	max	76.717	1	570.454	3	107.429	1	0	15	.002	2	.189	1
16			min	2.757	15	-531.492	1	3.152	12	-.014	1	-.003	3	-.132	3
17		9	max	76.717	1	728.069	3	146.871	1	0	15	.127	1	.793	1
18			min	2.757	15	-675.624	1	4.58	12	-.014	1	.002	12	-.781	3
19		10	max	76.717	1	885.685	3	186.313	1	.014	1	.294	1	1.54	1
20			min	2.757	15	-819.755	1	6.008	12	-.002	3	.007	12	-1.588	3
21		11	max	76.717	1	675.624	1	-4.58	12	.014	1	.127	1	.793	1
22			min	2.757	15	-728.069	3	-146.871	1	0	15	.002	12	-.781	3
23		12	max	76.717	1	531.492	1	-3.152	12	.014	1	.002	2	.189	1
24			min	2.757	15	-570.454	3	-107.429	1	0	15	-.003	3	-.132	3
25		13	max	76.717	1	387.361	1	-1.724	12	.014	1	-.003	15	.36	3
26			min	2.757	15	-412.838	3	-67.987	1	0	15	-.088	1	-.27	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
27		14	max	76.717	1	243.23	1	-.296	12	.014	1	-.005	15	.694	3
28			min	2.757	15	-255.223	3	-28.545	1	0	15	-.136	1	-.585	1
29		15	max	76.717	1	99.098	1	10.897	1	.014	1	-.005	12	.87	3
30			min	2.757	15	-97.608	3	.404	15	0	15	-.145	1	-.757	1
31		16	max	76.717	1	60.008	3	50.339	1	.014	1	-.003	12	.889	3
32			min	2.757	15	-45.033	1	1.809	15	0	15	-.114	1	-.784	1
33		17	max	76.717	1	217.623	3	89.781	1	.014	1	0	3	.75	3
34			min	2.757	15	-189.165	1	3.213	15	0	15	-.044	1	-.667	1
35		18	max	76.717	1	375.238	3	129.223	1	.014	1	.065	1	.454	3
36			min	2.757	15	-333.296	1	4.618	15	0	15	.002	15	-.405	1
37		19	max	76.717	1	532.854	3	168.665	1	.014	1	.214	1	0	1
38			min	2.757	15	-477.427	1	6.023	15	0	15	.008	15	0	3
39	M14	1	max	44.496	1	529.876	1	-6.257	15	.009	3	.254	1	0	1
40			min	1.602	15	-426.053	3	-175.215	1	-.015	1	.009	15	0	3
41		2	max	44.496	1	385.745	1	-4.852	15	.009	3	.098	1	.366	3
42			min	1.602	15	-306.587	3	-135.773	1	-.015	1	.004	15	-.458	1
43		3	max	44.496	1	241.613	1	-3.447	15	.009	3	.002	3	.613	3
44			min	1.602	15	-187.122	3	-96.331	1	-.015	1	-.018	1	-.771	1
45		4	max	44.496	1	97.482	1	-2.042	15	.009	3	-.002	12	.741	3
46			min	1.602	15	-67.657	3	-56.889	1	-.015	1	-.095	1	-.941	1
47		5	max	44.496	1	51.809	3	-.637	15	.009	3	-.004	12	.748	3
48			min	1.602	15	-46.649	1	-17.447	1	-.015	1	-.132	1	-.966	1
49		6	max	44.496	1	171.274	3	21.995	1	.009	3	-.005	15	.637	3
50			min	1.602	15	-190.781	1	-.038	3	-.015	1	-.13	1	-.848	1
51		7	max	44.496	1	290.739	3	61.437	1	.009	3	-.003	15	.406	3
52			min	1.602	15	-334.912	1	1.482	12	-.015	1	-.088	1	-.585	1
53		8	max	44.496	1	410.205	3	100.879	1	.009	3	0	10	.055	3
54			min	1.602	15	-479.044	1	2.91	12	-.015	1	-.007	1	-.178	1
55		9	max	44.496	1	529.67	3	140.321	1	.009	3	.114	1	.373	1
56			min	1.602	15	-623.175	1	4.338	12	-.015	1	.002	12	-.414	3
57		10	max	44.496	1	649.135	3	179.763	1	.015	1	.274	1	1.068	1
58			min	1.602	15	-767.306	1	5.766	12	-.009	3	.007	12	-1.004	3
59		11	max	44.496	1	623.175	1	-4.338	12	.015	1	.114	1	.373	1
60			min	1.602	15	-529.67	3	-140.321	1	-.009	3	.002	12	-.414	3
61		12	max	44.496	1	479.044	1	-2.91	12	.015	1	0	10	.055	3
62			min	1.602	15	-410.205	3	-100.879	1	-.009	3	-.007	1	-.178	1
63		13	max	44.496	1	334.912	1	-1.482	12	.015	1	-.003	15	.406	3
64			min	1.602	15	-290.739	3	-61.437	1	-.009	3	-.088	1	-.585	1
65		14	max	44.496	1	190.781	1	.038	3	.015	1	-.005	15	.637	3
66			min	1.602	15	-171.274	3	-21.995	1	-.009	3	-.13	1	-.848	1
67		15	max	44.496	1	46.649	1	17.447	1	.015	1	-.004	12	.748	3
68			min	1.602	15	-51.809	3	.637	15	-.009	3	-.132	1	-.966	1
69		16	max	44.496	1	67.657	3	56.889	1	.015	1	-.002	12	.741	3
70			min	1.602	15	-97.482	1	2.042	15	-.009	3	-.095	1	-.941	1
71		17	max	44.496	1	187.122	3	96.331	1	.015	1	.002	3	.613	3
72			min	1.602	15	-241.613	1	3.447	15	-.009	3	-.018	1	-.771	1
73		18	max	44.496	1	306.587	3	135.773	1	.015	1	.098	1	.366	3
74			min	1.602	15	-385.745	1	4.852	15	-.009	3	.004	15	-.458	1
75		19	max	44.496	1	426.053	3	175.215	1	.015	1	.254	1	0	1
76			min	1.602	15	-529.876	1	6.257	15	-.009	3	.009	15	0	3
77	M15	1	max	-1.708	15	598.817	1	-6.254	15	.015	1	.253	1	0	2
78			min	-47.367	1	-233.412	3	-175.17	1	-.008	3	.009	15	0	3
79		2	max	-1.708	15	434.248	1	-4.849	15	.015	1	.098	1	.202	3
80			min	-47.367	1	-171.172	3	-135.728	1	-.008	3	.004	15	-.517	1
81		3	max	-1.708	15	269.68	1	-3.444	15	.015	1	.002	3	.342	3
82			min	-47.367	1	-108.931	3	-96.286	1	-.008	3	-.018	1	-.868	1
83		4	max	-1.708	15	105.111	1	-2.039	15	.015	1	-.002	12	.42	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
84			min	-47.367	1	-46.691	3	-56.844	1	-.008	3	-.095	1	-1.056	1
85		5	max	-1.708	15	15.549	3	-.635	15	.015	1	-.004	12	.436	3
86			min	-47.367	1	-59.458	1	-17.402	1	-.008	3	-.132	1	-1.079	1
87		6	max	-1.708	15	77.79	3	22.04	1	.015	1	-.005	15	.389	3
88			min	-47.367	1	-224.027	1	.066	3	-.008	3	-.13	1	-.937	1
89		7	max	-1.708	15	140.03	3	61.482	1	.015	1	-.003	15	.28	3
90			min	-47.367	1	-388.596	1	1.545	12	-.008	3	-.088	1	-.631	1
91		8	max	-1.708	15	202.27	3	100.924	1	.015	1	0	10	.109	3
92			min	-47.367	1	-553.165	1	2.973	12	-.008	3	-.007	1	-.16	1
93		9	max	-1.708	15	264.511	3	140.366	1	.015	1	.114	1	.476	1
94			min	-47.367	1	-717.734	1	4.401	12	-.008	3	.002	12	-.124	3
95		10	max	-1.708	15	326.751	3	179.808	1	.008	3	.274	1	1.276	1
96			min	-47.367	1	-882.303	1	5.829	12	-.015	1	.007	12	-.42	3
97		11	max	-1.708	15	717.734	1	-4.401	12	.008	3	.114	1	.476	1
98			min	-47.367	1	-264.511	3	-140.366	1	-.015	1	.002	12	-.124	3
99		12	max	-1.708	15	553.165	1	-2.973	12	.008	3	0	10	.109	3
100			min	-47.367	1	-202.27	3	-100.924	1	-.015	1	-.007	1	-.16	1
101		13	max	-1.708	15	388.596	1	-1.545	12	.008	3	-.003	15	.28	3
102			min	-47.367	1	-140.03	3	-61.482	1	-.015	1	-.088	1	-.631	1
103		14	max	-1.708	15	224.027	1	-.066	3	.008	3	-.005	15	.389	3
104			min	-47.367	1	-77.79	3	-22.04	1	-.015	1	-.13	1	-.937	1
105		15	max	-1.708	15	59.458	1	17.402	1	.008	3	-.004	12	.436	3
106			min	-47.367	1	-15.549	3	.635	15	-.015	1	-.132	1	-1.079	1
107		16	max	-1.708	15	46.691	3	56.844	1	.008	3	-.002	12	.42	3
108			min	-47.367	1	-105.111	1	2.039	15	-.015	1	-.095	1	-1.056	1
109		17	max	-1.708	15	108.931	3	96.286	1	.008	3	.002	3	.342	3
110			min	-47.367	1	-269.68	1	3.444	15	-.015	1	-.018	1	-.868	1
111		18	max	-1.708	15	171.172	3	135.728	1	.008	3	.098	1	.202	3
112			min	-47.367	1	-434.248	1	4.849	15	-.015	1	.004	15	-.517	1
113		19	max	-1.708	15	233.412	3	175.17	1	.008	3	.253	1	0	2
114			min	-47.367	1	-598.817	1	6.254	15	-.015	1	.009	15	0	3
115	M16	1	max	-3.067	15	547.015	1	-6.036	15	.012	1	.217	1	0	1
116			min	-85.179	1	-203.944	3	-169.118	1	-.01	3	.008	15	0	3
117		2	max	-3.067	15	382.446	1	-4.631	15	.012	1	.067	1	.173	3
118			min	-85.179	1	-141.704	3	-129.676	1	-.01	3	.002	15	-.465	1
119		3	max	-3.067	15	217.877	1	-3.226	15	.012	1	0	3	.283	3
120			min	-85.179	1	-79.464	3	-90.234	1	-.01	3	-.043	1	-.765	1
121		4	max	-3.067	15	53.308	1	-1.821	15	.012	1	-.003	12	.332	3
122			min	-85.179	1	-17.223	3	-50.792	1	-.01	3	-.113	1	-.9	1
123		5	max	-3.067	15	45.017	3	-.417	15	.012	1	-.005	12	.318	3
124			min	-85.179	1	-111.261	1	-11.35	1	-.01	3	-.144	1	-.872	1
125		6	max	-3.067	15	107.258	3	28.092	1	.012	1	-.005	15	.242	3
126			min	-85.179	1	-275.829	1	.488	12	-.01	3	-.136	1	-.678	1
127		7	max	-3.067	15	169.498	3	67.534	1	.012	1	-.003	15	.103	3
128			min	-85.179	1	-440.398	1	1.916	12	-.01	3	-.088	1	-.32	1
129		8	max	-3.067	15	231.738	3	106.975	1	.012	1	.001	2	.203	1
130			min	-85.179	1	-604.967	1	3.344	12	-.01	3	-.002	3	-.097	3
131		9	max	-3.067	15	293.979	3	146.417	1	.012	1	.126	1	.89	1
132			min	-85.179	1	-769.536	1	4.772	12	-.01	3	.003	12	-.36	3
133		10	max	-3.067	15	356.219	3	185.859	1	.01	3	.292	1	1.742	1
134			min	-85.179	1	-934.105	1	6.2	12	-.012	1	.008	12	-.685	3
135		11	max	-3.067	15	769.536	1	-4.772	12	.01	3	.126	1	.89	1
136			min	-85.179	1	-293.979	3	-146.417	1	-.012	1	.003	12	-.36	3
137		12	max	-3.067	15	604.967	1	-3.344	12	.01	3	.001	2	.203	1
138			min	-85.179	1	-231.738	3	-106.975	1	-.012	1	-.002	3	-.097	3
139		13	max	-3.067	15	440.398	1	-1.916	12	.01	3	-.003	15	.103	3
140			min	-85.179	1	-169.498	3	-67.534	1	-.012	1	-.088	1	-.32	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
141		14	max	-3.067	15	275.829	1	-.488	12	.01	3	-.005	15	.242	3
142			min	-85.179	1	-107.258	3	-28.092	1	-.012	1	-.136	1	-.678	1
143		15	max	-3.067	15	111.261	1	11.35	1	.01	3	-.005	12	.318	3
144			min	-85.179	1	-45.017	3	.417	15	-.012	1	-.144	1	-.872	1
145		16	max	-3.067	15	17.223	3	50.792	1	.01	3	-.003	12	.332	3
146			min	-85.179	1	-53.308	1	1.821	15	-.012	1	-.113	1	-.9	1
147		17	max	-3.067	15	79.464	3	90.234	1	.01	3	0	3	.283	3
148			min	-85.179	1	-217.877	1	3.226	15	-.012	1	-.043	1	-.765	1
149		18	max	-3.067	15	141.704	3	129.676	1	.01	3	.067	1	.173	3
150			min	-85.179	1	-382.446	1	4.631	15	-.012	1	.002	15	-.465	1
151		19	max	-3.067	15	203.944	3	169.118	1	.01	3	.217	1	0	1
152			min	-85.179	1	-547.015	1	6.036	15	-.012	1	.008	15	0	3
153	M2	1	max	1099.328	1	2.156	4	.906	1	0	3	0	3	0	1
154			min	-975.26	3	.507	15	.032	15	0	1	0	1	0	1
155		2	max	1099.744	1	2.147	4	.906	1	0	3	0	1	0	15
156			min	-974.948	3	.505	15	.032	15	0	1	0	15	0	4
157		3	max	1100.16	1	2.139	4	.906	1	0	3	0	1	0	15
158			min	-974.636	3	.503	15	.032	15	0	1	0	15	-.001	4
159		4	max	1100.575	1	2.13	4	.906	1	0	3	0	1	0	15
160			min	-974.324	3	.501	15	.032	15	0	1	0	15	-.002	4
161		5	max	1100.991	1	2.121	4	.906	1	0	3	.001	1	0	15
162			min	-974.012	3	.499	15	.032	15	0	1	0	15	-.002	4
163		6	max	1101.407	1	2.113	4	.906	1	0	3	.001	1	0	15
164			min	-973.7	3	.497	15	.032	15	0	1	0	15	-.003	4
165		7	max	1101.823	1	2.104	4	.906	1	0	3	.002	1	0	15
166			min	-973.388	3	.495	15	.032	15	0	1	0	15	-.004	4
167		8	max	1102.239	1	2.095	4	.906	1	0	3	.002	1	0	15
168			min	-973.077	3	.493	15	.032	15	0	1	0	15	-.004	4
169		9	max	1102.655	1	2.086	4	.906	1	0	3	.002	1	-.001	15
170			min	-972.765	3	.491	15	.032	15	0	1	0	15	-.005	4
171		10	max	1103.071	1	2.078	4	.906	1	0	3	.002	1	-.001	15
172			min	-972.453	3	.489	15	.032	15	0	1	0	15	-.005	4
173		11	max	1103.487	1	2.069	4	.906	1	0	3	.003	1	-.001	15
174			min	-972.141	3	.486	15	.032	15	0	1	0	15	-.006	4
175		12	max	1103.902	1	2.06	4	.906	1	0	3	.003	1	-.002	15
176			min	-971.829	3	.484	15	.032	15	0	1	0	15	-.007	4
177		13	max	1104.318	1	2.052	4	.906	1	0	3	.003	1	-.002	15
178			min	-971.517	3	.482	15	.032	15	0	1	0	15	-.007	4
179		14	max	1104.734	1	2.043	4	.906	1	0	3	.003	1	-.002	15
180			min	-971.205	3	.48	15	.032	15	0	1	0	15	-.008	4
181		15	max	1105.15	1	2.034	4	.906	1	0	3	.004	1	-.002	15
182			min	-970.893	3	.478	15	.032	15	0	1	0	15	-.008	4
183		16	max	1105.566	1	2.025	4	.906	1	0	3	.004	1	-.002	15
184			min	-970.581	3	.476	15	.032	15	0	1	0	15	-.009	4
185		17	max	1105.982	1	2.017	4	.906	1	0	3	.004	1	-.002	15
186			min	-970.269	3	.474	15	.032	15	0	1	0	15	-.009	4
187		18	max	1106.398	1	2.008	4	.906	1	0	3	.004	1	-.002	15
188			min	-969.957	3	.472	15	.032	15	0	1	0	15	-.01	4
189		19	max	1106.814	1	1.999	4	.906	1	0	3	.005	1	-.002	15
190			min	-969.646	3	.47	15	.032	15	0	1	0	15	-.01	4
191	M3	1	max	387.1	2	9.1	4	.21	1	0	5	0	1	.01	4
192			min	-515.886	3	2.139	15	.008	15	0	1	0	15	.002	15
193		2	max	386.93	2	8.226	4	.21	1	0	5	0	1	.006	4
194			min	-516.014	3	1.934	15	.008	15	0	1	0	15	.002	15
195		3	max	386.759	2	7.352	4	.21	1	0	5	0	1	.003	2
196			min	-516.142	3	1.728	15	.008	15	0	1	0	15	0	12
197		4	max	386.589	2	6.477	4	.21	1	0	5	0	1	0	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
198			min	-516.27	3	1.523	15	.008	15	0	1	0	15	-.002	3
199		5	max	386.419	2	5.603	4	.21	1	0	5	0	1	0	15
200			min	-516.397	3	1.317	15	.008	15	0	1	0	15	-.003	4
201		6	max	386.248	2	4.728	4	.21	1	0	5	0	1	-.001	15
202			min	-516.525	3	1.112	15	.008	15	0	1	0	15	-.006	4
203		7	max	386.078	2	3.854	4	.21	1	0	5	0	1	-.002	15
204			min	-516.653	3	.906	15	.008	15	0	1	0	15	-.008	4
205		8	max	385.907	2	2.979	4	.21	1	0	5	0	1	-.002	15
206			min	-516.781	3	.7	15	.008	15	0	1	0	15	-.01	4
207		9	max	385.737	2	2.105	4	.21	1	0	5	0	1	-.003	15
208			min	-516.908	3	.495	15	.008	15	0	1	0	15	-.011	4
209		10	max	385.567	2	1.23	4	.21	1	0	5	0	1	-.003	15
210			min	-517.036	3	.289	15	.008	15	0	1	0	15	-.012	4
211		11	max	385.396	2	.399	2	.21	1	0	5	.001	1	-.003	15
212			min	-517.164	3	.037	12	.008	15	0	1	0	15	-.012	4
213		12	max	385.226	2	-.122	15	.21	1	0	5	.001	1	-.003	15
214			min	-517.292	3	-.518	4	.008	15	0	1	0	15	-.012	4
215		13	max	385.056	2	-.327	15	.21	1	0	5	.001	1	-.003	15
216			min	-517.419	3	-1.393	4	.008	15	0	1	0	15	-.011	4
217		14	max	384.885	2	-.533	15	.21	1	0	5	.001	1	-.002	15
218			min	-517.547	3	-2.267	4	.008	15	0	1	0	15	-.011	4
219		15	max	384.715	2	-.738	15	.21	1	0	5	.001	1	-.002	15
220			min	-517.675	3	-3.142	4	.008	15	0	1	0	15	-.009	4
221		16	max	384.545	2	-.944	15	.21	1	0	5	.002	1	-.002	15
222			min	-517.803	3	-4.016	4	.008	15	0	1	0	15	-.008	4
223		17	max	384.374	2	-1.15	15	.21	1	0	5	.002	1	-.001	15
224			min	-517.93	3	-4.891	4	.008	15	0	1	0	15	-.005	4
225		18	max	384.204	2	-1.355	15	.21	1	0	5	.002	1	0	15
226			min	-518.058	3	-5.765	4	.008	15	0	1	0	15	-.003	4
227		19	max	384.034	2	-1.561	15	.21	1	0	5	.002	1	0	1
228			min	-518.186	3	-6.64	4	.008	15	0	1	0	15	0	1
229	M4	1	max	1177.604	1	0	1	-.455	15	0	1	.001	1	0	1
230			min	-170.254	3	0	1	-12.717	1	0	1	0	15	0	1
231		2	max	1177.775	1	0	1	-.455	15	0	1	0	12	0	1
232			min	-170.126	3	0	1	-12.717	1	0	1	0	1	0	1
233		3	max	1177.945	1	0	1	-.455	15	0	1	0	15	0	1
234			min	-169.998	3	0	1	-12.717	1	0	1	-.002	1	0	1
235		4	max	1178.115	1	0	1	-.455	15	0	1	0	15	0	1
236			min	-169.871	3	0	1	-12.717	1	0	1	-.003	1	0	1
237		5	max	1178.286	1	0	1	-.455	15	0	1	0	15	0	1
238			min	-169.743	3	0	1	-12.717	1	0	1	-.005	1	0	1
239		6	max	1178.456	1	0	1	-.455	15	0	1	0	15	0	1
240			min	-169.615	3	0	1	-12.717	1	0	1	-.006	1	0	1
241		7	max	1178.626	1	0	1	-.455	15	0	1	0	15	0	1
242			min	-169.487	3	0	1	-12.717	1	0	1	-.008	1	0	1
243		8	max	1178.797	1	0	1	-.455	15	0	1	0	15	0	1
244			min	-169.359	3	0	1	-12.717	1	0	1	-.009	1	0	1
245		9	max	1178.967	1	0	1	-.455	15	0	1	0	15	0	1
246			min	-169.232	3	0	1	-12.717	1	0	1	-.011	1	0	1
247		10	max	1179.137	1	0	1	-.455	15	0	1	0	15	0	1
248			min	-169.104	3	0	1	-12.717	1	0	1	-.012	1	0	1
249		11	max	1179.308	1	0	1	-.455	15	0	1	0	15	0	1
250			min	-168.976	3	0	1	-12.717	1	0	1	-.014	1	0	1
251		12	max	1179.478	1	0	1	-.455	15	0	1	0	15	0	1
252			min	-168.848	3	0	1	-12.717	1	0	1	-.015	1	0	1
253		13	max	1179.648	1	0	1	-.455	15	0	1	0	15	0	1
254			min	-168.721	3	0	1	-12.717	1	0	1	-.016	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
255		14	max	1179.819	1	0	1	-.455	15	0	1	0	15	0	1
256			min	-168.593	3	0	1	-12.717	1	0	1	-.018	1	0	1
257		15	max	1179.989	1	0	1	-.455	15	0	1	0	15	0	1
258			min	-168.465	3	0	1	-12.717	1	0	1	-.019	1	0	1
259		16	max	1180.159	1	0	1	-.455	15	0	1	0	15	0	1
260			min	-168.337	3	0	1	-12.717	1	0	1	-.021	1	0	1
261		17	max	1180.33	1	0	1	-.455	15	0	1	0	15	0	1
262			min	-168.21	3	0	1	-12.717	1	0	1	-.022	1	0	1
263		18	max	1180.5	1	0	1	-.455	15	0	1	0	15	0	1
264			min	-168.082	3	0	1	-12.717	1	0	1	-.024	1	0	1
265		19	max	1180.671	1	0	1	-.455	15	0	1	0	15	0	1
266			min	-167.954	3	0	1	-12.717	1	0	1	-.025	1	0	1
267	M6	1	max	3440.295	1	2.428	2	0	1	0	1	0	1	0	1
268			min	-3129.045	3	.31	12	0	1	0	1	0	1	0	1
269		2	max	3440.711	1	2.422	2	0	1	0	1	0	1	0	12
270			min	-3128.733	3	.306	12	0	1	0	1	0	1	0	2
271		3	max	3441.127	1	2.415	2	0	1	0	1	0	1	0	12
272			min	-3128.421	3	.303	12	0	1	0	1	0	1	-.001	2
273		4	max	3441.543	1	2.408	2	0	1	0	1	0	1	0	12
274			min	-3128.109	3	.3	12	0	1	0	1	0	1	-.002	2
275		5	max	3441.959	1	2.401	2	0	1	0	1	0	1	0	12
276			min	-3127.797	3	.296	12	0	1	0	1	0	1	-.003	2
277		6	max	3442.375	1	2.394	2	0	1	0	1	0	1	0	12
278			min	-3127.485	3	.293	12	0	1	0	1	0	1	-.003	2
279		7	max	3442.791	1	2.388	2	0	1	0	1	0	1	0	12
280			min	-3127.173	3	.289	12	0	1	0	1	0	1	-.004	2
281		8	max	3443.206	1	2.381	2	0	1	0	1	0	1	0	12
282			min	-3126.861	3	.286	12	0	1	0	1	0	1	-.005	2
283		9	max	3443.622	1	2.374	2	0	1	0	1	0	1	0	12
284			min	-3126.549	3	.283	12	0	1	0	1	0	1	-.005	2
285		10	max	3444.038	1	2.367	2	0	1	0	1	0	1	0	12
286			min	-3126.237	3	.279	12	0	1	0	1	0	1	-.006	2
287		11	max	3444.454	1	2.36	2	0	1	0	1	0	1	0	12
288			min	-3125.926	3	.276	12	0	1	0	1	0	1	-.007	2
289		12	max	3444.87	1	2.354	2	0	1	0	1	0	1	0	12
290			min	-3125.614	3	.272	12	0	1	0	1	0	1	-.007	2
291		13	max	3445.286	1	2.347	2	0	1	0	1	0	1	0	12
292			min	-3125.302	3	.269	12	0	1	0	1	0	1	-.008	2
293		14	max	3445.702	1	2.34	2	0	1	0	1	0	1	-.001	12
294			min	-3124.99	3	.266	12	0	1	0	1	0	1	-.009	2
295		15	max	3446.118	1	2.333	2	0	1	0	1	0	1	-.001	12
296			min	-3124.678	3	.262	12	0	1	0	1	0	1	-.009	2
297		16	max	3446.533	1	2.327	2	0	1	0	1	0	1	-.001	12
298			min	-3124.366	3	.259	12	0	1	0	1	0	1	-.01	2
299		17	max	3446.949	1	2.32	2	0	1	0	1	0	1	-.001	12
300			min	-3124.054	3	.255	12	0	1	0	1	0	1	-.011	2
301		18	max	3447.365	1	2.313	2	0	1	0	1	0	1	-.001	12
302			min	-3123.742	3	.252	12	0	1	0	1	0	1	-.011	2
303		19	max	3447.781	1	2.306	2	0	1	0	1	0	1	-.001	12
304			min	-3123.43	3	.249	12	0	1	0	1	0	1	-.012	2
305	M7	1	max	1485.025	2	9.141	4	0	1	0	1	0	1	.012	2
306			min	-1576.74	3	2.145	15	0	1	0	1	0	1	.001	12
307		2	max	1484.854	2	8.267	4	0	1	0	1	0	1	.009	2
308			min	-1576.867	3	1.939	15	0	1	0	1	0	1	0	3
309		3	max	1484.684	2	7.392	4	0	1	0	1	0	1	.005	2
310			min	-1576.995	3	1.734	15	0	1	0	1	0	1	-.002	3
311		4	max	1484.514	2	6.518	4	0	1	0	1	0	1	.003	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
312			min	-1577.123	3	1.528	15	0	1	0	1	0	1	-.004	3
313		5	max	1484.343	2	5.643	4	0	1	0	1	0	1	0	2
314			min	-1577.251	3	1.323	15	0	1	0	1	0	1	-.005	3
315		6	max	1484.173	2	4.769	4	0	1	0	1	0	1	-.001	15
316			min	-1577.378	3	1.117	15	0	1	0	1	0	1	-.007	3
317		7	max	1484.003	2	3.895	4	0	1	0	1	0	1	-.002	15
318			min	-1577.506	3	.912	15	0	1	0	1	0	1	-.008	4
319		8	max	1483.832	2	3.02	4	0	1	0	1	0	1	-.002	15
320			min	-1577.634	3	.706	15	0	1	0	1	0	1	-.009	4
321		9	max	1483.662	2	2.146	4	0	1	0	1	0	1	-.002	15
322			min	-1577.762	3	.5	15	0	1	0	1	0	1	-.011	4
323		10	max	1483.491	2	1.402	2	0	1	0	1	0	1	-.003	15
324			min	-1577.89	3	.165	12	0	1	0	1	0	1	-.011	4
325		11	max	1483.321	2	.721	2	0	1	0	1	0	1	-.003	15
326			min	-1578.017	3	-.316	3	0	1	0	1	0	1	-.012	4
327		12	max	1483.151	2	.039	2	0	1	0	1	0	1	-.003	15
328			min	-1578.145	3	-.827	3	0	1	0	1	0	1	-.012	4
329		13	max	1482.98	2	-.322	15	0	1	0	1	0	1	-.003	15
330			min	-1578.273	3	-1.352	4	0	1	0	1	0	1	-.011	4
331		14	max	1482.81	2	-.527	15	0	1	0	1	0	1	-.002	15
332			min	-1578.401	3	-2.227	4	0	1	0	1	0	1	-.01	4
333		15	max	1482.64	2	-.733	15	0	1	0	1	0	1	-.002	15
334			min	-1578.528	3	-3.101	4	0	1	0	1	0	1	-.009	4
335		16	max	1482.469	2	-.938	15	0	1	0	1	0	1	-.002	15
336			min	-1578.656	3	-3.975	4	0	1	0	1	0	1	-.008	4
337		17	max	1482.299	2	-1.144	15	0	1	0	1	0	1	-.001	15
338			min	-1578.784	3	-4.85	4	0	1	0	1	0	1	-.005	4
339		18	max	1482.129	2	-1.35	15	0	1	0	1	0	1	0	15
340			min	-1578.912	3	-5.724	4	0	1	0	1	0	1	-.003	4
341		19	max	1481.958	2	-1.555	15	0	1	0	1	0	1	0	1
342			min	-1579.039	3	-6.599	4	0	1	0	1	0	1	0	1
343	M8	1	max	3268.434	1	0	1	0	1	0	1	0	1	0	1
344			min	-605.398	3	0	1	0	1	0	1	0	1	0	1
345		2	max	3268.604	1	0	1	0	1	0	1	0	1	0	1
346			min	-605.27	3	0	1	0	1	0	1	0	1	0	1
347		3	max	3268.774	1	0	1	0	1	0	1	0	1	0	1
348			min	-605.143	3	0	1	0	1	0	1	0	1	0	1
349		4	max	3268.945	1	0	1	0	1	0	1	0	1	0	1
350			min	-605.015	3	0	1	0	1	0	1	0	1	0	1
351		5	max	3269.115	1	0	1	0	1	0	1	0	1	0	1
352			min	-604.887	3	0	1	0	1	0	1	0	1	0	1
353		6	max	3269.285	1	0	1	0	1	0	1	0	1	0	1
354			min	-604.759	3	0	1	0	1	0	1	0	1	0	1
355		7	max	3269.456	1	0	1	0	1	0	1	0	1	0	1
356			min	-604.631	3	0	1	0	1	0	1	0	1	0	1
357		8	max	3269.626	1	0	1	0	1	0	1	0	1	0	1
358			min	-604.504	3	0	1	0	1	0	1	0	1	0	1
359		9	max	3269.796	1	0	1	0	1	0	1	0	1	0	1
360			min	-604.376	3	0	1	0	1	0	1	0	1	0	1
361		10	max	3269.967	1	0	1	0	1	0	1	0	1	0	1
362			min	-604.248	3	0	1	0	1	0	1	0	1	0	1
363		11	max	3270.137	1	0	1	0	1	0	1	0	1	0	1
364			min	-604.12	3	0	1	0	1	0	1	0	1	0	1
365		12	max	3270.307	1	0	1	0	1	0	1	0	1	0	1
366			min	-603.993	3	0	1	0	1	0	1	0	1	0	1
367		13	max	3270.478	1	0	1	0	1	0	1	0	1	0	1
368			min	-603.865	3	0	1	0	1	0	1	0	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
369		14	max	3270.648	1	0	1	0	1	0	1	0	1	0	1
370			min	-603.737	3	0	1	0	1	0	1	0	1	0	1
371		15	max	3270.818	1	0	1	0	1	0	1	0	1	0	1
372			min	-603.609	3	0	1	0	1	0	1	0	1	0	1
373		16	max	3270.989	1	0	1	0	1	0	1	0	1	0	1
374			min	-603.482	3	0	1	0	1	0	1	0	1	0	1
375		17	max	3271.159	1	0	1	0	1	0	1	0	1	0	1
376			min	-603.354	3	0	1	0	1	0	1	0	1	0	1
377		18	max	3271.33	1	0	1	0	1	0	1	0	1	0	1
378			min	-603.226	3	0	1	0	1	0	1	0	1	0	1
379		19	max	3271.5	1	0	1	0	1	0	1	0	1	0	1
380			min	-603.098	3	0	1	0	1	0	1	0	1	0	1
381	M10	1	max	1099.328	1	2.156	4	-.032	15	0	1	0	1	0	1
382			min	-975.26	3	.507	15	-.906	1	0	3	0	3	0	1
383		2	max	1099.744	1	2.147	4	-.032	15	0	1	0	15	0	15
384			min	-974.948	3	.505	15	-.906	1	0	3	0	1	0	4
385		3	max	1100.16	1	2.139	4	-.032	15	0	1	0	15	0	15
386			min	-974.636	3	.503	15	-.906	1	0	3	0	1	-.001	4
387		4	max	1100.575	1	2.13	4	-.032	15	0	1	0	15	0	15
388			min	-974.324	3	.501	15	-.906	1	0	3	0	1	-.002	4
389		5	max	1100.991	1	2.121	4	-.032	15	0	1	0	15	0	15
390			min	-974.012	3	.499	15	-.906	1	0	3	-.001	1	-.002	4
391		6	max	1101.407	1	2.113	4	-.032	15	0	1	0	15	0	15
392			min	-973.7	3	.497	15	-.906	1	0	3	-.001	1	-.003	4
393		7	max	1101.823	1	2.104	4	-.032	15	0	1	0	15	0	15
394			min	-973.388	3	.495	15	-.906	1	0	3	-.002	1	-.004	4
395		8	max	1102.239	1	2.095	4	-.032	15	0	1	0	15	0	15
396			min	-973.077	3	.493	15	-.906	1	0	3	-.002	1	-.004	4
397		9	max	1102.655	1	2.086	4	-.032	15	0	1	0	15	-.001	15
398			min	-972.765	3	.491	15	-.906	1	0	3	-.002	1	-.005	4
399		10	max	1103.071	1	2.078	4	-.032	15	0	1	0	15	-.001	15
400			min	-972.453	3	.489	15	-.906	1	0	3	-.002	1	-.005	4
401		11	max	1103.487	1	2.069	4	-.032	15	0	1	0	15	-.001	15
402			min	-972.141	3	.486	15	-.906	1	0	3	-.003	1	-.006	4
403		12	max	1103.902	1	2.06	4	-.032	15	0	1	0	15	-.002	15
404			min	-971.829	3	.484	15	-.906	1	0	3	-.003	1	-.007	4
405		13	max	1104.318	1	2.052	4	-.032	15	0	1	0	15	-.002	15
406			min	-971.517	3	.482	15	-.906	1	0	3	-.003	1	-.007	4
407		14	max	1104.734	1	2.043	4	-.032	15	0	1	0	15	-.002	15
408			min	-971.205	3	.48	15	-.906	1	0	3	-.003	1	-.008	4
409		15	max	1105.15	1	2.034	4	-.032	15	0	1	0	15	-.002	15
410			min	-970.893	3	.478	15	-.906	1	0	3	-.004	1	-.008	4
411		16	max	1105.566	1	2.025	4	-.032	15	0	1	0	15	-.002	15
412			min	-970.581	3	.476	15	-.906	1	0	3	-.004	1	-.009	4
413		17	max	1105.982	1	2.017	4	-.032	15	0	1	0	15	-.002	15
414			min	-970.269	3	.474	15	-.906	1	0	3	-.004	1	-.009	4
415		18	max	1106.398	1	2.008	4	-.032	15	0	1	0	15	-.002	15
416			min	-969.957	3	.472	15	-.906	1	0	3	-.004	1	-.01	4
417		19	max	1106.814	1	1.999	4	-.032	15	0	1	0	15	-.002	15
418			min	-969.646	3	.47	15	-.906	1	0	3	-.005	1	-.01	4
419	M11	1	max	387.1	2	9.1	4	-.008	15	0	1	0	15	.01	4
420			min	-515.886	3	2.139	15	-.21	1	0	5	0	1	.002	15
421		2	max	386.93	2	8.226	4	-.008	15	0	1	0	15	.006	4
422			min	-516.014	3	1.934	15	-.21	1	0	5	0	1	.002	15
423		3	max	386.759	2	7.352	4	-.008	15	0	1	0	15	.003	2
424			min	-516.142	3	1.728	15	-.21	1	0	5	0	1	0	12
425		4	max	386.589	2	6.477	4	-.008	15	0	1	0	15	0	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
426			min	-516.27	3	1.523	15	-.21	1	0	5	0	1	-.002	3
427		5	max	386.419	2	5.603	4	-.008	15	0	1	0	15	0	15
428			min	-516.397	3	1.317	15	-.21	1	0	5	0	1	-.003	4
429		6	max	386.248	2	4.728	4	-.008	15	0	1	0	15	-.001	15
430			min	-516.525	3	1.112	15	-.21	1	0	5	0	1	-.006	4
431		7	max	386.078	2	3.854	4	-.008	15	0	1	0	15	-.002	15
432			min	-516.653	3	.906	15	-.21	1	0	5	0	1	-.008	4
433		8	max	385.907	2	2.979	4	-.008	15	0	1	0	15	-.002	15
434			min	-516.781	3	.7	15	-.21	1	0	5	0	1	-.01	4
435		9	max	385.737	2	2.105	4	-.008	15	0	1	0	15	-.003	15
436			min	-516.908	3	.495	15	-.21	1	0	5	0	1	-.011	4
437		10	max	385.567	2	1.23	4	-.008	15	0	1	0	15	-.003	15
438			min	-517.036	3	.289	15	-.21	1	0	5	0	1	-.012	4
439		11	max	385.396	2	.399	2	-.008	15	0	1	0	15	-.003	15
440			min	-517.164	3	.037	12	-.21	1	0	5	-.001	1	-.012	4
441		12	max	385.226	2	-.122	15	-.008	15	0	1	0	15	-.003	15
442			min	-517.292	3	-.518	4	-.21	1	0	5	-.001	1	-.012	4
443		13	max	385.056	2	-.327	15	-.008	15	0	1	0	15	-.003	15
444			min	-517.419	3	-1.393	4	-.21	1	0	5	-.001	1	-.011	4
445		14	max	384.885	2	-.533	15	-.008	15	0	1	0	15	-.002	15
446			min	-517.547	3	-2.267	4	-.21	1	0	5	-.001	1	-.011	4
447		15	max	384.715	2	-.738	15	-.008	15	0	1	0	15	-.002	15
448			min	-517.675	3	-3.142	4	-.21	1	0	5	-.001	1	-.009	4
449		16	max	384.545	2	-.944	15	-.008	15	0	1	0	15	-.002	15
450			min	-517.803	3	-4.016	4	-.21	1	0	5	-.002	1	-.008	4
451		17	max	384.374	2	-1.15	15	-.008	15	0	1	0	15	-.001	15
452			min	-517.93	3	-4.891	4	-.21	1	0	5	-.002	1	-.005	4
453		18	max	384.204	2	-1.355	15	-.008	15	0	1	0	15	0	15
454			min	-518.058	3	-5.765	4	-.21	1	0	5	-.002	1	-.003	4
455		19	max	384.034	2	-1.561	15	-.008	15	0	1	0	15	0	1
456			min	-518.186	3	-6.64	4	-.21	1	0	5	-.002	1	0	1
457	M12	1	max	1177.604	1	0	1	12.717	1	0	1	0	15	0	1
458			min	-170.254	3	0	1	.455	15	0	1	-.001	1	0	1
459		2	max	1177.775	1	0	1	12.717	1	0	1	0	1	0	1
460			min	-170.126	3	0	1	.455	15	0	1	0	12	0	1
461		3	max	1177.945	1	0	1	12.717	1	0	1	.002	1	0	1
462			min	-169.998	3	0	1	.455	15	0	1	0	15	0	1
463		4	max	1178.115	1	0	1	12.717	1	0	1	.003	1	0	1
464			min	-169.871	3	0	1	.455	15	0	1	0	15	0	1
465		5	max	1178.286	1	0	1	12.717	1	0	1	.005	1	0	1
466			min	-169.743	3	0	1	.455	15	0	1	0	15	0	1
467		6	max	1178.456	1	0	1	12.717	1	0	1	.006	1	0	1
468			min	-169.615	3	0	1	.455	15	0	1	0	15	0	1
469		7	max	1178.626	1	0	1	12.717	1	0	1	.008	1	0	1
470			min	-169.487	3	0	1	.455	15	0	1	0	15	0	1
471		8	max	1178.797	1	0	1	12.717	1	0	1	.009	1	0	1
472			min	-169.359	3	0	1	.455	15	0	1	0	15	0	1
473		9	max	1178.967	1	0	1	12.717	1	0	1	.011	1	0	1
474			min	-169.232	3	0	1	.455	15	0	1	0	15	0	1
475		10	max	1179.137	1	0	1	12.717	1	0	1	.012	1	0	1
476			min	-169.104	3	0	1	.455	15	0	1	0	15	0	1
477		11	max	1179.308	1	0	1	12.717	1	0	1	.014	1	0	1
478			min	-168.976	3	0	1	.455	15	0	1	0	15	0	1
479		12	max	1179.478	1	0	1	12.717	1	0	1	.015	1	0	1
480			min	-168.848	3	0	1	.455	15	0	1	0	15	0	1
481		13	max	1179.648	1	0	1	12.717	1	0	1	.016	1	0	1
482			min	-168.721	3	0	1	.455	15	0	1	0	15	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
483		14	max	1179.819	1	0	1	12.717	1	0	1	.018	1	0	1
484			min	-168.593	3	0	1	.455	15	0	1	0	15	0	1
485		15	max	1179.989	1	0	1	12.717	1	0	1	.019	1	0	1
486			min	-168.465	3	0	1	.455	15	0	1	0	15	0	1
487		16	max	1180.159	1	0	1	12.717	1	0	1	.021	1	0	1
488			min	-168.337	3	0	1	.455	15	0	1	0	15	0	1
489		17	max	1180.33	1	0	1	12.717	1	0	1	.022	1	0	1
490			min	-168.21	3	0	1	.455	15	0	1	0	15	0	1
491		18	max	1180.5	1	0	1	12.717	1	0	1	.024	1	0	1
492			min	-168.082	3	0	1	.455	15	0	1	0	15	0	1
493		19	max	1180.671	1	0	1	12.717	1	0	1	.025	1	0	1
494			min	-167.954	3	0	1	.455	15	0	1	0	15	0	1
495	M1	1	max	168.67	1	532.823	3	-2.757	15	0	1	.214	1	0	15
496			min	6.023	15	-475.27	1	-76.595	1	0	3	.008	15	-.014	1
497		2	max	169.246	1	531.636	3	-2.757	15	0	1	.167	1	.281	1
498			min	6.197	15	-476.853	1	-76.595	1	0	3	.006	15	-.332	3
499		3	max	330.584	3	556.181	1	-2.725	15	0	3	.119	1	.566	1
500			min	-224.245	2	-393.223	3	-75.945	1	0	1	.004	15	-.652	3
501		4	max	331.016	3	554.598	1	-2.725	15	0	3	.072	1	.221	1
502			min	-223.669	2	-394.41	3	-75.945	1	0	1	.003	15	-.407	3
503		5	max	331.448	3	553.015	1	-2.725	15	0	3	.025	1	-.005	15
504			min	-223.093	2	-395.597	3	-75.945	1	0	1	0	15	-.162	3
505		6	max	331.88	3	551.432	1	-2.725	15	0	3	0	15	.084	3
506			min	-222.517	2	-396.785	3	-75.945	1	0	1	-.022	1	-.465	1
507		7	max	332.313	3	549.848	1	-2.725	15	0	3	-.002	15	.331	3
508			min	-221.941	2	-397.972	3	-75.945	1	0	1	-.069	1	-.807	1
509		8	max	332.745	3	548.265	1	-2.725	15	0	3	-.004	15	.578	3
510			min	-221.364	2	-399.16	3	-75.945	1	0	1	-.116	1	-1.147	1
511		9	max	343.924	3	35.288	2	-4.328	15	0	9	.073	1	.676	3
512			min	-152.515	2	.482	15	-120.49	1	0	3	.003	15	-1.306	1
513		10	max	344.356	3	33.705	2	-4.328	15	0	9	0	15	.659	3
514			min	-151.939	2	.004	15	-120.49	1	0	3	-.001	1	-1.318	1
515		11	max	344.788	3	32.121	2	-4.328	15	0	9	-.003	15	.643	3
516			min	-151.363	2	-1.922	4	-120.49	1	0	3	-.076	1	-1.329	1
517		12	max	355.863	3	260.249	3	-2.62	15	0	1	.114	1	.561	3
518			min	-84.391	10	-586.552	1	-73.163	1	0	3	.004	15	-1.174	1
519		13	max	356.296	3	259.062	3	-2.62	15	0	1	.069	1	.4	3
520			min	-83.911	10	-588.135	1	-73.163	1	0	3	.002	15	-.809	1
521		14	max	356.728	3	257.874	3	-2.62	15	0	1	.023	1	.24	3
522			min	-83.431	10	-589.718	1	-73.163	1	0	3	0	15	-.444	1
523		15	max	357.16	3	256.687	3	-2.62	15	0	1	0	15	.08	3
524			min	-82.951	10	-591.302	1	-73.163	1	0	3	-.022	1	-.077	1
525		16	max	357.592	3	255.5	3	-2.62	15	0	1	-.002	15	.29	2
526			min	-82.47	10	-592.885	1	-73.163	1	0	3	-.068	1	-.079	3
527		17	max	358.024	3	254.312	3	-2.62	15	0	1	-.004	15	.659	1
528			min	-81.99	10	-594.468	1	-73.163	1	0	3	-.113	1	-.237	3
529		18	max	-6.21	15	550.643	1	-3.067	15	0	3	-.006	15	.329	1
530			min	-169.69	1	-202.821	3	-85.295	1	0	1	-.164	1	-.117	3
531		19	max	-6.036	15	549.06	1	-3.067	15	0	3	-.008	15	.01	3
532			min	-169.114	1	-204.009	3	-85.295	1	0	1	-.217	1	-.012	1
533	M5	1	max	372.615	1	1771.315	3	0	1	0	1	0	1	.029	1
534			min	12.016	12	-1629.299	1	0	1	0	1	0	1	0	15
535		2	max	373.191	1	1770.127	3	0	1	0	1	0	1	1.041	1
536			min	12.304	12	-1630.882	1	0	1	0	1	0	1	-1.096	3
537		3	max	1039.71	3	1583.667	1	0	1	0	1	0	1	2.018	1
538			min	-762.014	2	-1206.521	3	0	1	0	1	0	1	-2.161	3
539		4	max	1040.142	3	1582.084	1	0	1	0	1	0	1	1.036	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
540			min	-761.438	2	-1207.708	3	0	1	0	1	0	1	-1.412	3
541		5	max	1040.574	3	1580.5	1	0	1	0	1	0	1	.054	1
542			min	-760.862	2	-1208.895	3	0	1	0	1	0	1	-.662	3
543		6	max	1041.006	3	1578.917	1	0	1	0	1	0	1	.089	3
544			min	-760.285	2	-1210.083	3	0	1	0	1	0	1	-.926	1
545		7	max	1041.438	3	1577.334	1	0	1	0	1	0	1	.84	3
546			min	-759.709	2	-1211.27	3	0	1	0	1	0	1	-1.906	1
547		8	max	1041.871	3	1575.751	1	0	1	0	1	0	1	1.592	3
548			min	-759.133	2	-1212.458	3	0	1	0	1	0	1	-2.884	1
549		9	max	1059.362	3	117.681	2	0	1	0	1	0	1	1.838	3
550			min	-615.609	2	.48	15	0	1	0	1	0	1	-3.271	1
551		10	max	1059.794	3	116.098	2	0	1	0	1	0	1	1.775	3
552			min	-615.033	2	.002	15	0	1	0	1	0	1	-3.311	1
553		11	max	1060.226	3	114.515	2	0	1	0	1	0	1	1.713	3
554			min	-614.457	2	-1.727	4	0	1	0	1	0	1	-3.349	1
555		12	max	1077.926	3	771.72	3	0	1	0	1	0	1	1.499	3
556			min	-470.98	2	-1702.959	1	0	1	0	1	0	1	-2.979	1
557		13	max	1078.358	3	770.533	3	0	1	0	1	0	1	1.021	3
558			min	-470.404	2	-1704.542	1	0	1	0	1	0	1	-1.921	1
559		14	max	1078.79	3	769.345	3	0	1	0	1	0	1	.543	3
560			min	-469.827	2	-1706.125	1	0	1	0	1	0	1	-.863	1
561		15	max	1079.222	3	768.158	3	0	1	0	1	0	1	.248	2
562			min	-469.251	2	-1707.708	1	0	1	0	1	0	1	0	15
563		16	max	1079.654	3	766.97	3	0	1	0	1	0	1	1.257	1
564			min	-468.675	2	-1709.291	1	0	1	0	1	0	1	-.411	3
565		17	max	1080.086	3	765.783	3	0	1	0	1	0	1	2.318	1
566			min	-468.099	2	-1710.875	1	0	1	0	1	0	1	-.886	3
567		18	max	-12.688	12	1879.209	1	0	1	0	1	0	1	1.191	1
568			min	-372.303	1	-711.551	3	0	1	0	1	0	1	-.461	3
569		19	max	-12.4	12	1877.626	1	0	1	0	1	0	1	.025	1
570			min	-371.727	1	-712.738	3	0	1	0	1	0	1	-.019	3
571	M9	1	max	168.67	1	532.823	3	76.595	1	0	3	-.008	15	0	15
572			min	6.023	15	-475.27	1	2.757	15	0	1	-.214	1	-.014	1
573		2	max	169.246	1	531.636	3	76.595	1	0	3	-.006	15	.281	1
574			min	6.197	15	-476.853	1	2.757	15	0	1	-.167	1	-.332	3
575		3	max	330.584	3	556.181	1	75.945	1	0	1	-.004	15	.566	1
576			min	-224.245	2	-393.223	3	2.725	15	0	3	-.119	1	-.652	3
577		4	max	331.016	3	554.598	1	75.945	1	0	1	-.003	15	.221	1
578			min	-223.669	2	-394.41	3	2.725	15	0	3	-.072	1	-.407	3
579		5	max	331.448	3	553.015	1	75.945	1	0	1	0	15	-.005	15
580			min	-223.093	2	-395.597	3	2.725	15	0	3	-.025	1	-.162	3
581		6	max	331.88	3	551.432	1	75.945	1	0	1	.022	1	.084	3
582			min	-222.517	2	-396.785	3	2.725	15	0	3	0	15	-.465	1
583		7	max	332.313	3	549.848	1	75.945	1	0	1	.069	1	.331	3
584			min	-221.941	2	-397.972	3	2.725	15	0	3	.002	15	-.807	1
585		8	max	332.745	3	548.265	1	75.945	1	0	1	.116	1	.578	3
586			min	-221.364	2	-399.16	3	2.725	15	0	3	.004	15	-1.147	1
587		9	max	343.924	3	35.288	2	120.49	1	0	3	-.003	15	.676	3
588			min	-152.515	2	.482	15	4.328	15	0	9	-.073	1	-1.306	1
589		10	max	344.356	3	33.705	2	120.49	1	0	3	.001	1	.659	3
590			min	-151.939	2	.004	15	4.328	15	0	9	0	15	-1.318	1
591		11	max	344.788	3	32.121	2	120.49	1	0	3	.076	1	.643	3
592			min	-151.363	2	-1.922	4	4.328	15	0	9	.003	15	-1.329	1
593		12	max	355.863	3	260.249	3	73.163	1	0	3	-.004	15	.561	3
594			min	-84.391	10	-586.552	1	2.62	15	0	1	-.114	1	-1.174	1
595		13	max	356.296	3	259.062	3	73.163	1	0	3	-.002	15	.4	3
596			min	-83.911	10	-588.135	1	2.62	15	0	1	-.069	1	-.809	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
597		14	max	356.728	3	257.874	3	73.163	1	0	3	0	15	.24	3
598			min	-83.431	10	-589.718	1	2.62	15	0	1	-.023	1	-.444	1
599		15	max	357.16	3	256.687	3	73.163	1	0	3	.022	1	.08	3
600			min	-82.951	10	-591.302	1	2.62	15	0	1	0	15	-.077	1
601		16	max	357.592	3	255.5	3	73.163	1	0	3	.068	1	.29	2
602			min	-82.47	10	-592.885	1	2.62	15	0	1	.002	15	-.079	3
603		17	max	358.024	3	254.312	3	73.163	1	0	3	.113	1	.659	1
604			min	-81.99	10	-594.468	1	2.62	15	0	1	.004	15	-.237	3
605		18	max	-6.21	15	550.643	1	85.295	1	0	1	.164	1	.329	1
606			min	-169.69	1	-202.821	3	3.067	15	0	3	.006	15	-.117	3
607		19	max	-6.036	15	549.06	1	85.295	1	0	1	.217	1	.01	3
608			min	-169.114	1	-204.009	3	3.067	15	0	3	.008	15	-.012	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M13	1	max	0	1	.193	1	.007	3	1.29e-2	1	NC	1	NC	1
2			min	0	15	-.032	3	-.003	2	-2.024e-3	3	NC	1	NC	1
3		2	max	0	1	.153	3	.031	1	1.417e-2	1	NC	5	NC	2
4			min	0	15	.002	15	0	10	-1.872e-3	3	1162.051	3	7129.355	1
5		3	max	0	1	.304	3	.073	1	1.544e-2	1	NC	5	NC	3
6			min	0	15	-.053	1	.003	15	-1.72e-3	3	641.39	3	3018.857	1
7		4	max	0	1	.397	3	.107	1	1.672e-2	1	NC	5	NC	3
8			min	0	15	-.108	1	.004	15	-1.569e-3	3	503.323	3	2032.006	1
9		5	max	0	1	.42	3	.124	1	1.799e-2	1	NC	5	NC	3
10			min	0	15	-.102	1	.005	15	-1.417e-3	3	477.875	3	1750.8	1
11		6	max	0	1	.374	3	.119	1	1.926e-2	1	NC	5	NC	3
12			min	0	15	-.037	1	.004	15	-1.265e-3	3	530.949	3	1832.248	1
13		7	max	0	1	.275	3	.092	1	2.053e-2	1	NC	5	NC	3
14			min	0	15	.003	15	.003	10	-1.114e-3	3	702.207	3	2367.038	1
15		8	max	0	1	.204	1	.052	1	2.181e-2	1	NC	1	NC	2
16			min	0	15	.006	15	-.002	10	-9.622e-4	3	1194.322	3	4221.718	1
17		9	max	0	1	.319	1	.021	3	2.308e-2	1	NC	5	NC	1
18			min	0	15	.009	15	-.006	10	-8.105e-4	3	1706.33	1	NC	1
19		10	max	0	1	.371	1	.02	3	2.435e-2	1	NC	3	NC	1
20			min	0	1	-.019	3	-.014	2	-6.589e-4	3	1215.001	1	NC	1
21		11	max	0	15	.319	1	.021	3	2.308e-2	1	NC	5	NC	1
22			min	0	1	.009	15	-.006	10	-8.105e-4	3	1706.33	1	NC	1
23		12	max	0	15	.204	1	.052	1	2.181e-2	1	NC	1	NC	2
24			min	0	1	.006	15	-.002	10	-9.622e-4	3	1194.322	3	4221.718	1
25		13	max	0	15	.275	3	.092	1	2.053e-2	1	NC	5	NC	3
26			min	0	1	.003	15	.003	10	-1.114e-3	3	702.207	3	2367.038	1
27		14	max	0	15	.374	3	.119	1	1.926e-2	1	NC	5	NC	3
28			min	0	1	-.037	1	.004	15	-1.265e-3	3	530.949	3	1832.248	1
29		15	max	0	15	.42	3	.124	1	1.799e-2	1	NC	5	NC	3
30			min	0	1	-.102	1	.005	15	-1.417e-3	3	477.875	3	1750.8	1
31		16	max	0	15	.397	3	.107	1	1.672e-2	1	NC	5	NC	3
32			min	0	1	-.108	1	.004	15	-1.569e-3	3	503.323	3	2032.006	1
33		17	max	0	15	.304	3	.073	1	1.544e-2	1	NC	5	NC	3
34			min	0	1	-.053	1	.003	15	-1.72e-3	3	641.39	3	3018.857	1
35		18	max	0	15	.153	3	.031	1	1.417e-2	1	NC	5	NC	2
36			min	0	1	.002	15	0	10	-1.872e-3	3	1162.051	3	7129.355	1
37		19	max	0	15	.193	1	.007	3	1.29e-2	1	NC	1	NC	1
38			min	0	1	-.032	3	-.003	2	-2.024e-3	3	NC	1	NC	1
39	M14	1	max	0	1	.276	3	.006	3	7.746e-3	1	NC	1	NC	1
40			min	0	15	-.593	1	-.003	2	-4.264e-3	3	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
41		2	max	0	1	.488	3	.021	1	9.043e-3	1	NC	5	NC	1
42			min	0	15	-.899	1	0	10	-5.068e-3	3	704.823	1	NC	1
43		3	max	0	1	.672	3	.056	1	1.034e-2	1	NC	15	NC	2
44			min	0	15	-1.171	1	.002	15	-5.872e-3	3	373.998	1	3936.24	1
45		4	max	0	1	.808	3	.089	1	1.164e-2	1	NC	15	NC	3
46			min	0	15	-1.381	1	.003	15	-6.676e-3	3	273.987	1	2453.401	1
47		5	max	0	1	.885	3	.108	1	1.294e-2	1	8959.162	15	NC	3
48			min	0	15	-1.518	1	.004	15	-7.48e-3	3	233.399	1	2025.446	1
49		6	max	0	1	.905	3	.106	1	1.423e-2	1	8431.834	15	NC	3
50			min	0	15	-1.58	1	.004	15	-8.285e-3	3	218.888	1	2061.958	1
51		7	max	0	1	.874	3	.084	1	1.553e-2	1	8513.583	15	NC	3
52			min	0	15	-1.575	1	.002	10	-9.089e-3	3	219.995	1	2610.638	1
53		8	max	0	1	.812	3	.049	1	1.683e-2	1	9024.625	15	NC	2
54			min	0	15	-1.524	1	-.002	10	-9.893e-3	3	231.905	1	4571.851	1
55		9	max	0	1	.746	3	.018	3	1.812e-2	1	9740.072	15	NC	1
56			min	0	15	-1.461	1	-.006	10	-1.07e-2	3	248.898	1	NC	1
57		10	max	0	1	.715	3	.018	3	1.942e-2	1	NC	15	NC	1
58			min	0	1	-1.428	1	-.012	2	-1.15e-2	3	258.743	1	NC	1
59		11	max	0	15	.746	3	.018	3	1.812e-2	1	9740.072	15	NC	1
60			min	0	1	-1.461	1	-.006	10	-1.07e-2	3	248.898	1	NC	1
61		12	max	0	15	.812	3	.049	1	1.683e-2	1	9024.625	15	NC	2
62			min	0	1	-1.524	1	-.002	10	-9.893e-3	3	231.905	1	4571.851	1
63		13	max	0	15	.874	3	.084	1	1.553e-2	1	8513.583	15	NC	3
64			min	0	1	-1.575	1	.002	10	-9.089e-3	3	219.995	1	2610.638	1
65		14	max	0	15	.905	3	.106	1	1.423e-2	1	8431.834	15	NC	3
66			min	0	1	-1.58	1	.004	15	-8.285e-3	3	218.888	1	2061.958	1
67		15	max	0	15	.885	3	.108	1	1.294e-2	1	8959.162	15	NC	3
68			min	0	1	-1.518	1	.004	15	-7.48e-3	3	233.399	1	2025.446	1
69		16	max	0	15	.808	3	.089	1	1.164e-2	1	NC	15	NC	3
70			min	0	1	-1.381	1	.003	15	-6.676e-3	3	273.987	1	2453.401	1
71		17	max	0	15	.672	3	.056	1	1.034e-2	1	NC	15	NC	2
72			min	0	1	-1.171	1	.002	15	-5.872e-3	3	373.998	1	3936.24	1
73		18	max	0	15	.488	3	.021	1	9.043e-3	1	NC	5	NC	1
74			min	0	1	-.899	1	0	10	-5.068e-3	3	704.823	1	NC	1
75		19	max	0	15	.276	3	.006	3	7.746e-3	1	NC	1	NC	1
76			min	0	1	-.593	1	-.003	2	-4.264e-3	3	NC	1	NC	1
77	M15	1	max	0	15	.283	3	.005	3	3.56e-3	3	NC	1	NC	1
78			min	0	1	-.592	1	-.003	2	-7.887e-3	1	NC	1	NC	1
79		2	max	0	15	.43	3	.021	1	4.227e-3	3	NC	5	NC	1
80			min	0	1	-.922	1	0	10	-9.217e-3	1	654.399	1	NC	1
81		3	max	0	15	.562	3	.056	1	4.894e-3	3	NC	15	NC	2
82			min	0	1	-1.212	1	.002	15	-1.055e-2	1	348.248	1	3914.574	1
83		4	max	0	15	.667	3	.09	1	5.561e-3	3	NC	15	NC	3
84			min	0	1	-1.435	1	.003	15	-1.188e-2	1	256.353	1	2442.542	1
85		5	max	0	15	.738	3	.108	1	6.228e-3	3	8973.006	15	NC	3
86			min	0	1	-1.574	1	.004	15	-1.321e-2	1	219.908	1	2017.011	1
87		6	max	0	15	.776	3	.107	1	6.895e-3	3	8446.558	15	NC	3
88			min	0	1	-1.63	1	.004	15	-1.454e-2	1	208.221	1	2052.662	1
89		7	max	0	15	.783	3	.085	1	7.562e-3	3	8530.692	15	NC	3
90			min	0	1	-1.611	1	.003	10	-1.587e-2	1	211.926	1	2595.452	1
91		8	max	0	15	.768	3	.049	1	8.229e-3	3	9045.654	15	NC	2
92			min	0	1	-1.544	1	-.001	10	-1.72e-2	1	226.86	1	4525.672	1
93		9	max	0	15	.745	3	.017	3	8.895e-3	3	9765.912	15	NC	1
94			min	0	1	-1.466	1	-.005	10	-1.852e-2	1	247.297	1	NC	1
95		10	max	0	1	.733	3	.016	3	9.562e-3	3	NC	15	NC	1
96			min	0	1	-1.426	1	-.011	2	-1.985e-2	1	259.119	1	NC	1
97		11	max	0	1	.745	3	.017	3	8.895e-3	3	9765.912	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
98			min	0	15	-1.466	1	-.005	10	-1.852e-2	1	247.297	1	NC	1
99		12	max	0	1	.768	3	.049	1	8.229e-3	3	9045.654	15	NC	2
100			min	0	15	-1.544	1	-.001	10	-1.72e-2	1	226.86	1	4525.672	1
101		13	max	0	1	.783	3	.085	1	7.562e-3	3	8530.692	15	NC	3
102			min	0	15	-1.611	1	.003	10	-1.587e-2	1	211.926	1	2595.452	1
103		14	max	0	1	.776	3	.107	1	6.895e-3	3	8446.558	15	NC	3
104			min	0	15	-1.63	1	.004	15	-1.454e-2	1	208.221	1	2052.662	1
105		15	max	0	1	.738	3	.108	1	6.228e-3	3	8973.006	15	NC	3
106			min	0	15	-1.574	1	.004	15	-1.321e-2	1	219.908	1	2017.011	1
107		16	max	0	1	.667	3	.09	1	5.561e-3	3	NC	15	NC	3
108			min	0	15	-1.435	1	.003	15	-1.188e-2	1	256.353	1	2442.542	1
109		17	max	0	1	.562	3	.056	1	4.894e-3	3	NC	15	NC	2
110			min	0	15	-1.212	1	.002	15	-1.055e-2	1	348.248	1	3914.574	1
111		18	max	0	1	.43	3	.021	1	4.227e-3	3	NC	5	NC	1
112			min	0	15	-.922	1	0	10	-9.217e-3	1	654.399	1	NC	1
113		19	max	0	1	.283	3	.005	3	3.56e-3	3	NC	1	NC	1
114			min	0	15	-.592	1	-.003	2	-7.887e-3	1	NC	1	NC	1
115	M16	1	max	0	15	.187	1	.005	3	6.556e-3	3	NC	1	NC	1
116			min	0	1	-.098	3	-.002	2	-1.212e-2	1	NC	1	NC	1
117		2	max	0	15	.023	9	.031	1	7.402e-3	3	NC	5	NC	2
118			min	0	1	-.046	3	0	10	-1.321e-2	1	1315.942	1	7209.674	1
119		3	max	0	15	0	15	.072	1	8.248e-3	3	NC	5	NC	3
120			min	0	1	-.13	2	.003	15	-1.43e-2	1	738.481	1	3034.32	1
121		4	max	0	15	.011	3	.107	1	9.094e-3	3	NC	5	NC	3
122			min	0	1	-.198	2	.004	15	-1.539e-2	1	597.95	1	2034.945	1
123		5	max	0	15	.004	12	.125	1	9.94e-3	3	NC	5	NC	3
124			min	0	1	-.201	2	.005	15	-1.648e-2	1	600.655	1	1747.634	1
125		6	max	0	15	0	13	.12	1	1.079e-2	3	NC	5	NC	3
126			min	0	1	-.138	2	.004	15	-1.757e-2	1	736.08	2	1821.522	1
127		7	max	0	15	.03	9	.094	1	1.163e-2	3	NC	3	NC	3
128			min	0	1	-.083	3	.004	15	-1.866e-2	1	1193.801	2	2336.661	1
129		8	max	0	15	.166	1	.054	1	1.248e-2	3	NC	1	NC	2
130			min	0	1	-.143	3	0	10	-1.975e-2	1	4804.841	3	4091.558	1
131		9	max	0	15	.295	1	.015	3	1.332e-2	3	NC	5	NC	1
132			min	0	1	-.195	3	-.004	10	-2.084e-2	1	1986.893	1	NC	1
133		10	max	0	1	.353	1	.014	3	1.417e-2	3	NC	5	NC	1
134			min	0	1	-.218	3	-.01	2	-2.193e-2	1	1297.245	1	NC	1
135		11	max	0	1	.295	1	.015	3	1.332e-2	3	NC	5	NC	1
136			min	0	15	-.195	3	-.004	10	-2.084e-2	1	1986.893	1	NC	1
137		12	max	0	1	.166	1	.054	1	1.248e-2	3	NC	1	NC	2
138			min	0	15	-.143	3	0	10	-1.975e-2	1	4804.841	3	4091.558	1
139		13	max	0	1	.03	9	.094	1	1.163e-2	3	NC	3	NC	3
140			min	0	15	-.083	3	.004	15	-1.866e-2	1	1193.801	2	2336.661	1
141		14	max	0	1	0	13	.12	1	1.079e-2	3	NC	5	NC	3
142			min	0	15	-.138	2	.004	15	-1.757e-2	1	736.08	2	1821.522	1
143		15	max	0	1	.004	12	.125	1	9.94e-3	3	NC	5	NC	3
144			min	0	15	-.201	2	.005	15	-1.648e-2	1	600.655	1	1747.634	1
145		16	max	0	1	.011	3	.107	1	9.094e-3	3	NC	5	NC	3
146			min	0	15	-.198	2	.004	15	-1.539e-2	1	597.95	1	2034.945	1
147		17	max	0	1	0	15	.072	1	8.248e-3	3	NC	5	NC	3
148			min	0	15	-.13	2	.003	15	-1.43e-2	1	738.481	1	3034.32	1
149		18	max	0	1	.023	9	.031	1	7.402e-3	3	NC	5	NC	2
150			min	0	15	-.046	3	0	10	-1.321e-2	1	1315.942	1	7209.674	1
151		19	max	0	1	.187	1	.005	3	6.556e-3	3	NC	1	NC	1
152			min	0	15	-.098	3	-.002	2	-1.212e-2	1	NC	1	NC	1
153	M2	1	max	.006	1	.005	2	.01	1	-8.051e-6	15	NC	1	NC	2
154			min	-.006	3	-.009	3	0	15	-2.246e-4	1	NC	1	6069.211	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
155		2	max	.006	1	.004	2	.009	1	-7.542e-6	15	NC	1	NC	2
156			min	-.005	3	-.009	3	0	15	-2.104e-4	1	NC	1	6617.517	1
157		3	max	.006	1	.004	2	.008	1	-7.032e-6	15	NC	1	NC	2
158			min	-.005	3	-.009	3	0	15	-1.961e-4	1	NC	1	7270.489	1
159		4	max	.005	1	.003	2	.008	1	-6.523e-6	15	NC	1	NC	2
160			min	-.005	3	-.008	3	0	15	-1.819e-4	1	NC	1	8055.747	1
161		5	max	.005	1	.002	2	.007	1	-6.013e-6	15	NC	1	NC	2
162			min	-.004	3	-.008	3	0	15	-1.677e-4	1	NC	1	9010.939	1
163		6	max	.005	1	.001	2	.006	1	-5.504e-6	15	NC	1	NC	1
164			min	-.004	3	-.008	3	0	15	-1.535e-4	1	NC	1	NC	1
165		7	max	.004	1	0	2	.005	1	-4.995e-6	15	NC	1	NC	1
166			min	-.004	3	-.007	3	0	15	-1.392e-4	1	NC	1	NC	1
167		8	max	.004	1	0	2	.004	1	-4.485e-6	15	NC	1	NC	1
168			min	-.003	3	-.007	3	0	15	-1.25e-4	1	NC	1	NC	1
169		9	max	.004	1	0	2	.004	1	-3.976e-6	15	NC	1	NC	1
170			min	-.003	3	-.007	3	0	15	-1.108e-4	1	NC	1	NC	1
171		10	max	.003	1	-.001	15	.003	1	-3.466e-6	15	NC	1	NC	1
172			min	-.003	3	-.006	3	0	15	-9.653e-5	1	NC	1	NC	1
173		11	max	.003	1	-.001	15	.003	1	-2.957e-6	15	NC	1	NC	1
174			min	-.003	3	-.006	3	0	15	-8.229e-5	1	NC	1	NC	1
175		12	max	.002	1	-.001	15	.002	1	-2.448e-6	15	NC	1	NC	1
176			min	-.002	3	-.005	3	0	15	-6.806e-5	1	NC	1	NC	1
177		13	max	.002	1	-.001	15	.001	1	-1.938e-6	15	NC	1	NC	1
178			min	-.002	3	-.005	3	0	15	-5.383e-5	1	NC	1	NC	1
179		14	max	.002	1	0	15	.001	1	-1.429e-6	15	NC	1	NC	1
180			min	-.002	3	-.004	3	0	15	-3.96e-5	1	NC	1	NC	1
181		15	max	.001	1	0	15	0	1	-9.194e-7	15	NC	1	NC	1
182			min	-.001	3	-.004	4	0	15	-2.537e-5	1	NC	1	NC	1
183		16	max	.001	1	0	15	0	1	-4.1e-7	15	NC	1	NC	1
184			min	0	3	-.003	4	0	15	-1.114e-5	1	NC	1	NC	1
185		17	max	0	1	0	15	0	1	3.096e-6	1	NC	1	NC	1
186			min	0	3	-.002	4	0	15	-3.291e-7	3	NC	1	NC	1
187		18	max	0	1	0	15	0	1	1.733e-5	1	NC	1	NC	1
188			min	0	3	-.001	4	0	15	5.474e-7	12	NC	1	NC	1
189		19	max	0	1	0	1	0	1	3.156e-5	1	NC	1	NC	1
190			min	0	1	0	1	0	1	1.118e-6	15	NC	1	NC	1
191	M3	1	max	0	1	0	1	0	1	-3.417e-7	15	NC	1	NC	1
192			min	0	1	0	1	0	1	-9.62e-6	1	NC	1	NC	1
193		2	max	0	3	0	15	0	1	1.903e-5	1	NC	1	NC	1
194			min	0	2	-.002	4	0	15	6.82e-7	15	NC	1	NC	1
195		3	max	0	3	-.001	15	0	1	4.767e-5	1	NC	1	NC	1
196			min	0	2	-.005	4	0	15	1.706e-6	15	NC	1	NC	1
197		4	max	0	3	-.002	15	0	1	7.632e-5	1	NC	1	NC	1
198			min	0	2	-.008	4	0	15	2.729e-6	15	NC	1	NC	1
199		5	max	.001	3	-.003	15	0	1	1.05e-4	1	NC	1	NC	1
200			min	0	2	-.011	4	0	15	3.753e-6	15	9252.221	4	NC	1
201		6	max	.001	3	-.003	15	.001	1	1.336e-4	1	NC	1	NC	1
202			min	-.001	2	-.014	4	0	15	4.777e-6	15	7427.588	4	NC	1
203		7	max	.002	3	-.004	15	.001	1	1.623e-4	1	NC	5	NC	1
204			min	-.001	2	-.016	4	0	15	5.8e-6	15	6332.673	4	NC	1
205		8	max	.002	3	-.004	15	.002	1	1.909e-4	1	NC	5	NC	1
206			min	-.001	2	-.018	4	0	15	6.824e-6	15	5656.78	4	NC	1
207		9	max	.002	3	-.005	15	.002	1	2.196e-4	1	NC	5	NC	1
208			min	-.002	2	-.02	4	0	15	7.848e-6	15	5253.997	4	NC	1
209		10	max	.003	3	-.005	15	.002	1	2.482e-4	1	NC	5	NC	1
210			min	-.002	2	-.021	4	0	15	8.872e-6	15	5053.202	4	NC	1
211		11	max	.003	3	-.005	15	.003	1	2.768e-4	1	NC	5	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
212			min	-.002	2	-.021	4	0	15	9.895e-6	15	5024.463	4	NC	1
213		12	max	.003	3	-.005	15	.003	1	3.055e-4	1	NC	5	NC	1
214			min	-.002	2	-.02	4	0	15	1.092e-5	15	5167.51	4	NC	1
215		13	max	.003	3	-.004	15	.004	1	3.341e-4	1	NC	5	NC	1
216			min	-.003	2	-.019	4	0	15	1.194e-5	15	5513.056	4	NC	1
217		14	max	.004	3	-.004	15	.005	1	3.628e-4	1	NC	5	NC	1
218			min	-.003	2	-.017	4	0	15	1.297e-5	15	6139.043	4	NC	1
219		15	max	.004	3	-.003	15	.005	1	3.914e-4	1	NC	3	NC	1
220			min	-.003	2	-.015	4	0	15	1.399e-5	15	7219.459	4	NC	1
221		16	max	.004	3	-.003	15	.006	1	4.201e-4	1	NC	1	NC	1
222			min	-.003	2	-.012	4	0	15	1.501e-5	15	9176.637	4	NC	1
223		17	max	.005	3	-.002	15	.007	1	4.487e-4	1	NC	1	NC	1
224			min	-.003	2	-.008	4	0	15	1.604e-5	15	NC	1	NC	1
225		18	max	.005	3	-.001	15	.008	1	4.774e-4	1	NC	1	NC	1
226			min	-.004	2	-.006	1	0	15	1.706e-5	15	NC	1	NC	1
227		19	max	.005	3	0	15	.009	1	5.06e-4	1	NC	1	NC	1
228			min	-.004	2	-.003	1	0	15	1.808e-5	15	NC	1	NC	1
229	M4	1	max	.003	1	.003	2	0	15	7.75e-5	1	NC	1	NC	3
230			min	0	3	-.005	3	-.009	1	2.792e-6	15	NC	1	2661.539	1
231		2	max	.003	1	.003	2	0	15	7.75e-5	1	NC	1	NC	3
232			min	0	3	-.005	3	-.009	1	2.792e-6	15	NC	1	2894.807	1
233		3	max	.003	1	.003	2	0	15	7.75e-5	1	NC	1	NC	3
234			min	0	3	-.005	3	-.008	1	2.792e-6	15	NC	1	3172.399	1
235		4	max	.002	1	.003	2	0	15	7.75e-5	1	NC	1	NC	3
236			min	0	3	-.004	3	-.007	1	2.792e-6	15	NC	1	3505.834	1
237		5	max	.002	1	.003	2	0	15	7.75e-5	1	NC	1	NC	2
238			min	0	3	-.004	3	-.006	1	2.792e-6	15	NC	1	3910.769	1
239		6	max	.002	1	.002	2	0	15	7.75e-5	1	NC	1	NC	2
240			min	0	3	-.004	3	-.006	1	2.792e-6	15	NC	1	4408.914	1
241		7	max	.002	1	.002	2	0	15	7.75e-5	1	NC	1	NC	2
242			min	0	3	-.003	3	-.005	1	2.792e-6	15	NC	1	5031.088	1
243		8	max	.002	1	.002	2	0	15	7.75e-5	1	NC	1	NC	2
244			min	0	3	-.003	3	-.004	1	2.792e-6	15	NC	1	5822.237	1
245		9	max	.002	1	.002	2	0	15	7.75e-5	1	NC	1	NC	2
246			min	0	3	-.003	3	-.004	1	2.792e-6	15	NC	1	6850.031	1
247		10	max	.001	1	.002	2	0	15	7.75e-5	1	NC	1	NC	2
248			min	0	3	-.003	3	-.003	1	2.792e-6	15	NC	1	8220.25	1
249		11	max	.001	1	.001	2	0	15	7.75e-5	1	NC	1	NC	1
250			min	0	3	-.002	3	-.002	1	2.792e-6	15	NC	1	NC	1
251		12	max	.001	1	.001	2	0	15	7.75e-5	1	NC	1	NC	1
252			min	0	3	-.002	3	-.002	1	2.792e-6	15	NC	1	NC	1
253		13	max	0	1	.001	2	0	15	7.75e-5	1	NC	1	NC	1
254			min	0	3	-.002	3	-.001	1	2.792e-6	15	NC	1	NC	1
255		14	max	0	1	0	2	0	15	7.75e-5	1	NC	1	NC	1
256			min	0	3	-.001	3	-.001	1	2.792e-6	15	NC	1	NC	1
257		15	max	0	1	0	2	0	15	7.75e-5	1	NC	1	NC	1
258			min	0	3	-.001	3	0	1	2.792e-6	15	NC	1	NC	1
259		16	max	0	1	0	2	0	15	7.75e-5	1	NC	1	NC	1
260			min	0	3	0	3	0	1	2.792e-6	15	NC	1	NC	1
261		17	max	0	1	0	2	0	15	7.75e-5	1	NC	1	NC	1
262			min	0	3	0	3	0	1	2.792e-6	15	NC	1	NC	1
263		18	max	0	1	0	2	0	15	7.75e-5	1	NC	1	NC	1
264			min	0	3	0	3	0	1	2.792e-6	15	NC	1	NC	1
265		19	max	0	1	0	1	0	1	7.75e-5	1	NC	1	NC	1
266			min	0	1	0	1	0	1	2.792e-6	15	NC	1	NC	1
267	M6	1	max	.02	1	.02	2	0	1	0	1	NC	3	NC	1
268			min	-.018	3	-.027	3	0	1	0	1	2984.363	2	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
269		2	max	.019	1	.018	2	0	1	0	1	NC	3	NC	1
270			min	-.017	3	-.026	3	0	1	0	1	3284.413	2	NC	1
271		3	max	.018	1	.017	2	0	1	0	1	NC	3	NC	1
272			min	-.016	3	-.025	3	0	1	0	1	3648.54	2	NC	1
273		4	max	.017	1	.015	2	0	1	0	1	NC	3	NC	1
274			min	-.015	3	-.023	3	0	1	0	1	4095.908	2	NC	1
275		5	max	.016	1	.013	2	0	1	0	1	NC	3	NC	1
276			min	-.014	3	-.022	3	0	1	0	1	4653.671	2	NC	1
277		6	max	.014	1	.011	2	0	1	0	1	NC	3	NC	1
278			min	-.013	3	-.02	3	0	1	0	1	5361.362	2	NC	1
279		7	max	.013	1	.01	2	0	1	0	1	NC	1	NC	1
280			min	-.012	3	-.019	3	0	1	0	1	6278.413	2	NC	1
281		8	max	.012	1	.008	2	0	1	0	1	NC	1	NC	1
282			min	-.011	3	-.017	3	0	1	0	1	7497.673	2	NC	1
283		9	max	.011	1	.007	2	0	1	0	1	NC	1	NC	1
284			min	-.01	3	-.016	3	0	1	0	1	9171.131	2	NC	1
285		10	max	.01	1	.005	2	0	1	0	1	NC	1	NC	1
286			min	-.009	3	-.014	3	0	1	0	1	NC	1	NC	1
287		11	max	.009	1	.004	2	0	1	0	1	NC	1	NC	1
288			min	-.008	3	-.013	3	0	1	0	1	NC	1	NC	1
289		12	max	.008	1	.003	2	0	1	0	1	NC	1	NC	1
290			min	-.007	3	-.011	3	0	1	0	1	NC	1	NC	1
291		13	max	.007	1	.002	2	0	1	0	1	NC	1	NC	1
292			min	-.006	3	-.01	3	0	1	0	1	NC	1	NC	1
293		14	max	.006	1	.001	2	0	1	0	1	NC	1	NC	1
294			min	-.005	3	-.008	3	0	1	0	1	NC	1	NC	1
295		15	max	.004	1	0	2	0	1	0	1	NC	1	NC	1
296			min	-.004	3	-.007	3	0	1	0	1	NC	1	NC	1
297		16	max	.003	1	0	2	0	1	0	1	NC	1	NC	1
298			min	-.003	3	-.005	3	0	1	0	1	NC	1	NC	1
299		17	max	.002	1	0	2	0	1	0	1	NC	1	NC	1
300			min	-.002	3	-.003	3	0	1	0	1	NC	1	NC	1
301		18	max	.001	1	0	2	0	1	0	1	NC	1	NC	1
302			min	-.001	3	-.002	3	0	1	0	1	NC	1	NC	1
303		19	max	0	1	0	1	0	1	0	1	NC	1	NC	1
304			min	0	1	0	1	0	1	0	1	NC	1	NC	1
305	M7	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
306			min	0	1	0	1	0	1	0	1	NC	1	NC	1
307		2	max	0	3	0	15	0	1	0	1	NC	1	NC	1
308			min	0	2	-.003	3	0	1	0	1	NC	1	NC	1
309		3	max	.002	3	-.001	15	0	1	0	1	NC	1	NC	1
310			min	-.002	2	-.006	3	0	1	0	1	NC	1	NC	1
311		4	max	.003	3	-.002	15	0	1	0	1	NC	1	NC	1
312			min	-.002	2	-.009	3	0	1	0	1	NC	1	NC	1
313		5	max	.003	3	-.003	15	0	1	0	1	NC	1	NC	1
314			min	-.003	2	-.011	3	0	1	0	1	9537.57	4	NC	1
315		6	max	.004	3	-.003	15	0	1	0	1	NC	1	NC	1
316			min	-.004	2	-.014	4	0	1	0	1	7633.753	4	NC	1
317		7	max	.005	3	-.004	15	0	1	0	1	NC	1	NC	1
318			min	-.005	2	-.016	4	0	1	0	1	6492.938	4	NC	1
319		8	max	.006	3	-.004	15	0	1	0	1	NC	2	NC	1
320			min	-.006	2	-.018	4	0	1	0	1	5788.726	4	NC	1
321		9	max	.007	3	-.005	15	0	1	0	1	NC	5	NC	1
322			min	-.006	2	-.02	4	0	1	0	1	5367.997	4	NC	1
323		10	max	.008	3	-.005	15	0	1	0	1	NC	5	NC	1
324			min	-.007	2	-.021	4	0	1	0	1	5156.024	4	NC	1
325		11	max	.009	3	-.005	15	0	1	0	1	NC	5	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
326			min	-.008	2	-.021	4	0	1	0	1	5121.038	4	NC	1
327		12	max	.009	3	-.005	15	0	1	0	1	NC	5	NC	1
328			min	-.009	2	-.02	4	0	1	0	1	5261.962	4	NC	1
329		13	max	.01	3	-.004	15	0	1	0	1	NC	5	NC	1
330			min	-.01	2	-.019	4	0	1	0	1	5609.486	4	NC	1
331		14	max	.011	3	-.004	15	0	1	0	1	NC	2	NC	1
332			min	-.011	2	-.017	4	0	1	0	1	6242.426	4	NC	1
333		15	max	.012	3	-.003	15	0	1	0	1	NC	1	NC	1
334			min	-.011	2	-.015	4	0	1	0	1	7337.22	4	NC	1
335		16	max	.013	3	-.003	15	0	1	0	1	NC	1	NC	1
336			min	-.012	2	-.012	4	0	1	0	1	9322.52	4	NC	1
337		17	max	.014	3	-.002	15	0	1	0	1	NC	1	NC	1
338			min	-.013	2	-.01	1	0	1	0	1	NC	1	NC	1
339		18	max	.015	3	-.001	15	0	1	0	1	NC	1	NC	1
340			min	-.014	2	-.008	1	0	1	0	1	NC	1	NC	1
341		19	max	.016	3	0	15	0	1	0	1	NC	1	NC	1
342			min	-.015	2	-.006	1	0	1	0	1	NC	1	NC	1
343	M8	1	max	.008	1	.013	2	0	1	0	1	NC	1	NC	1
344			min	-.001	3	-.016	3	0	1	0	1	NC	1	NC	1
345		2	max	.007	1	.013	2	0	1	0	1	NC	1	NC	1
346			min	-.001	3	-.015	3	0	1	0	1	NC	1	NC	1
347		3	max	.007	1	.012	2	0	1	0	1	NC	1	NC	1
348			min	-.001	3	-.014	3	0	1	0	1	NC	1	NC	1
349		4	max	.007	1	.011	2	0	1	0	1	NC	1	NC	1
350			min	-.001	3	-.013	3	0	1	0	1	NC	1	NC	1
351		5	max	.006	1	.01	2	0	1	0	1	NC	1	NC	1
352			min	-.001	3	-.012	3	0	1	0	1	NC	1	NC	1
353		6	max	.006	1	.01	2	0	1	0	1	NC	1	NC	1
354			min	-.001	3	-.011	3	0	1	0	1	NC	1	NC	1
355		7	max	.005	1	.009	2	0	1	0	1	NC	1	NC	1
356			min	0	3	-.01	3	0	1	0	1	NC	1	NC	1
357		8	max	.005	1	.008	2	0	1	0	1	NC	1	NC	1
358			min	0	3	-.01	3	0	1	0	1	NC	1	NC	1
359		9	max	.004	1	.007	2	0	1	0	1	NC	1	NC	1
360			min	0	3	-.009	3	0	1	0	1	NC	1	NC	1
361		10	max	.004	1	.007	2	0	1	0	1	NC	1	NC	1
362			min	0	3	-.008	3	0	1	0	1	NC	1	NC	1
363		11	max	.003	1	.006	2	0	1	0	1	NC	1	NC	1
364			min	0	3	-.007	3	0	1	0	1	NC	1	NC	1
365		12	max	.003	1	.005	2	0	1	0	1	NC	1	NC	1
366			min	0	3	-.006	3	0	1	0	1	NC	1	NC	1
367		13	max	.003	1	.004	2	0	1	0	1	NC	1	NC	1
368			min	0	3	-.005	3	0	1	0	1	NC	1	NC	1
369		14	max	.002	1	.004	2	0	1	0	1	NC	1	NC	1
370			min	0	3	-.004	3	0	1	0	1	NC	1	NC	1
371		15	max	.002	1	.003	2	0	1	0	1	NC	1	NC	1
372			min	0	3	-.003	3	0	1	0	1	NC	1	NC	1
373		16	max	.001	1	.002	2	0	1	0	1	NC	1	NC	1
374			min	0	3	-.003	3	0	1	0	1	NC	1	NC	1
375		17	max	0	1	.001	2	0	1	0	1	NC	1	NC	1
376			min	0	3	-.002	3	0	1	0	1	NC	1	NC	1
377		18	max	0	1	0	2	0	1	0	1	NC	1	NC	1
378			min	0	3	0	3	0	1	0	1	NC	1	NC	1
379		19	max	0	1	0	1	0	1	0	1	NC	1	NC	1
380			min	0	1	0	1	0	1	0	1	NC	1	NC	1
381	M10	1	max	.006	1	.005	2	0	15	2.246e-4	1	NC	1	NC	2
382			min	-.006	3	-.009	3	-.01	1	8.051e-6	15	NC	1	6069.211	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
383		2	max	.006	1	.004	2	0	15	2.104e-4	1	NC	1	NC	2
384			min	-.005	3	-.009	3	-.009	1	7.542e-6	15	NC	1	6617.517	1
385		3	max	.006	1	.004	2	0	15	1.961e-4	1	NC	1	NC	2
386			min	-.005	3	-.009	3	-.008	1	7.032e-6	15	NC	1	7270.489	1
387		4	max	.005	1	.003	2	0	15	1.819e-4	1	NC	1	NC	2
388			min	-.005	3	-.008	3	-.008	1	6.523e-6	15	NC	1	8055.747	1
389		5	max	.005	1	.002	2	0	15	1.677e-4	1	NC	1	NC	2
390			min	-.004	3	-.008	3	-.007	1	6.013e-6	15	NC	1	9010.939	1
391		6	max	.005	1	.001	2	0	15	1.535e-4	1	NC	1	NC	1
392			min	-.004	3	-.008	3	-.006	1	5.504e-6	15	NC	1	NC	1
393		7	max	.004	1	0	2	0	15	1.392e-4	1	NC	1	NC	1
394			min	-.004	3	-.007	3	-.005	1	4.995e-6	15	NC	1	NC	1
395		8	max	.004	1	0	2	0	15	1.25e-4	1	NC	1	NC	1
396			min	-.003	3	-.007	3	-.004	1	4.485e-6	15	NC	1	NC	1
397		9	max	.004	1	0	2	0	15	1.108e-4	1	NC	1	NC	1
398			min	-.003	3	-.007	3	-.004	1	3.976e-6	15	NC	1	NC	1
399		10	max	.003	1	-.001	15	0	15	9.653e-5	1	NC	1	NC	1
400			min	-.003	3	-.006	3	-.003	1	3.466e-6	15	NC	1	NC	1
401		11	max	.003	1	-.001	15	0	15	8.229e-5	1	NC	1	NC	1
402			min	-.003	3	-.006	3	-.003	1	2.957e-6	15	NC	1	NC	1
403		12	max	.002	1	-.001	15	0	15	6.806e-5	1	NC	1	NC	1
404			min	-.002	3	-.005	3	-.002	1	2.448e-6	15	NC	1	NC	1
405		13	max	.002	1	-.001	15	0	15	5.383e-5	1	NC	1	NC	1
406			min	-.002	3	-.005	3	-.001	1	1.938e-6	15	NC	1	NC	1
407		14	max	.002	1	0	15	0	15	3.96e-5	1	NC	1	NC	1
408			min	-.002	3	-.004	3	-.001	1	1.429e-6	15	NC	1	NC	1
409		15	max	.001	1	0	15	0	15	2.537e-5	1	NC	1	NC	1
410			min	-.001	3	-.004	4	0	1	9.194e-7	15	NC	1	NC	1
411		16	max	.001	1	0	15	0	15	1.114e-5	1	NC	1	NC	1
412			min	0	3	-.003	4	0	1	4.1e-7	15	NC	1	NC	1
413		17	max	0	1	0	15	0	15	3.291e-7	3	NC	1	NC	1
414			min	0	3	-.002	4	0	1	-3.096e-6	1	NC	1	NC	1
415		18	max	0	1	0	15	0	15	-5.474e-7	12	NC	1	NC	1
416			min	0	3	-.001	4	0	1	-1.733e-5	1	NC	1	NC	1
417		19	max	0	1	0	1	0	1	-1.118e-6	15	NC	1	NC	1
418			min	0	1	0	1	0	1	-3.156e-5	1	NC	1	NC	1
419	M11	1	max	0	1	0	1	0	1	9.62e-6	1	NC	1	NC	1
420			min	0	1	0	1	0	1	3.417e-7	15	NC	1	NC	1
421		2	max	0	3	0	15	0	15	-6.82e-7	15	NC	1	NC	1
422			min	0	2	-.002	4	0	1	-1.903e-5	1	NC	1	NC	1
423		3	max	0	3	-.001	15	0	15	-1.706e-6	15	NC	1	NC	1
424			min	0	2	-.005	4	0	1	-4.767e-5	1	NC	1	NC	1
425		4	max	0	3	-.002	15	0	15	-2.729e-6	15	NC	1	NC	1
426			min	0	2	-.008	4	0	1	-7.632e-5	1	NC	1	NC	1
427		5	max	.001	3	-.003	15	0	15	-3.753e-6	15	NC	1	NC	1
428			min	0	2	-.011	4	0	1	-1.05e-4	1	9252.221	4	NC	1
429		6	max	.001	3	-.003	15	0	15	-4.777e-6	15	NC	1	NC	1
430			min	-.001	2	-.014	4	-.001	1	-1.336e-4	1	7427.588	4	NC	1
431		7	max	.002	3	-.004	15	0	15	-5.8e-6	15	NC	5	NC	1
432			min	-.001	2	-.016	4	-.001	1	-1.623e-4	1	6332.673	4	NC	1
433		8	max	.002	3	-.004	15	0	15	-6.824e-6	15	NC	5	NC	1
434			min	-.001	2	-.018	4	-.002	1	-1.909e-4	1	5656.78	4	NC	1
435		9	max	.002	3	-.005	15	0	15	-7.848e-6	15	NC	5	NC	1
436			min	-.002	2	-.02	4	-.002	1	-2.196e-4	1	5253.997	4	NC	1
437		10	max	.003	3	-.005	15	0	15	-8.872e-6	15	NC	5	NC	1
438			min	-.002	2	-.021	4	-.002	1	-2.482e-4	1	5053.202	4	NC	1
439		11	max	.003	3	-.005	15	0	15	-9.895e-6	15	NC	5	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
440			min	-.002	2	-.021	4	-.003	1	-2.768e-4	1	5024.463	4	NC	1
441		12	max	.003	3	-.005	15	0	15	-1.092e-5	15	NC	5	NC	1
442			min	-.002	2	-.02	4	-.003	1	-3.055e-4	1	5167.51	4	NC	1
443		13	max	.003	3	-.004	15	0	15	-1.194e-5	15	NC	5	NC	1
444			min	-.003	2	-.019	4	-.004	1	-3.341e-4	1	5513.056	4	NC	1
445		14	max	.004	3	-.004	15	0	15	-1.297e-5	15	NC	5	NC	1
446			min	-.003	2	-.017	4	-.005	1	-3.628e-4	1	6139.043	4	NC	1
447		15	max	.004	3	-.003	15	0	15	-1.399e-5	15	NC	3	NC	1
448			min	-.003	2	-.015	4	-.005	1	-3.914e-4	1	7219.459	4	NC	1
449		16	max	.004	3	-.003	15	0	15	-1.501e-5	15	NC	1	NC	1
450			min	-.003	2	-.012	4	-.006	1	-4.201e-4	1	9176.637	4	NC	1
451		17	max	.005	3	-.002	15	0	15	-1.604e-5	15	NC	1	NC	1
452			min	-.003	2	-.008	4	-.007	1	-4.487e-4	1	NC	1	NC	1
453		18	max	.005	3	-.001	15	0	15	-1.706e-5	15	NC	1	NC	1
454			min	-.004	2	-.006	1	-.008	1	-4.774e-4	1	NC	1	NC	1
455		19	max	.005	3	0	15	0	15	-1.808e-5	15	NC	1	NC	1
456			min	-.004	2	-.003	1	-.009	1	-5.06e-4	1	NC	1	NC	1
457	M12	1	max	.003	1	.003	2	.009	1	-2.792e-6	15	NC	1	NC	3
458			min	0	3	-.005	3	0	15	-7.75e-5	1	NC	1	2661.539	1
459		2	max	.003	1	.003	2	.009	1	-2.792e-6	15	NC	1	NC	3
460			min	0	3	-.005	3	0	15	-7.75e-5	1	NC	1	2894.807	1
461		3	max	.003	1	.003	2	.008	1	-2.792e-6	15	NC	1	NC	3
462			min	0	3	-.005	3	0	15	-7.75e-5	1	NC	1	3172.399	1
463		4	max	.002	1	.003	2	.007	1	-2.792e-6	15	NC	1	NC	3
464			min	0	3	-.004	3	0	15	-7.75e-5	1	NC	1	3505.834	1
465		5	max	.002	1	.003	2	.006	1	-2.792e-6	15	NC	1	NC	2
466			min	0	3	-.004	3	0	15	-7.75e-5	1	NC	1	3910.769	1
467		6	max	.002	1	.002	2	.006	1	-2.792e-6	15	NC	1	NC	2
468			min	0	3	-.004	3	0	15	-7.75e-5	1	NC	1	4408.914	1
469		7	max	.002	1	.002	2	.005	1	-2.792e-6	15	NC	1	NC	2
470			min	0	3	-.003	3	0	15	-7.75e-5	1	NC	1	5031.088	1
471		8	max	.002	1	.002	2	.004	1	-2.792e-6	15	NC	1	NC	2
472			min	0	3	-.003	3	0	15	-7.75e-5	1	NC	1	5822.237	1
473		9	max	.002	1	.002	2	.004	1	-2.792e-6	15	NC	1	NC	2
474			min	0	3	-.003	3	0	15	-7.75e-5	1	NC	1	6850.031	1
475		10	max	.001	1	.002	2	.003	1	-2.792e-6	15	NC	1	NC	2
476			min	0	3	-.003	3	0	15	-7.75e-5	1	NC	1	8220.25	1
477		11	max	.001	1	.001	2	.002	1	-2.792e-6	15	NC	1	NC	1
478			min	0	3	-.002	3	0	15	-7.75e-5	1	NC	1	NC	1
479		12	max	.001	1	.001	2	.002	1	-2.792e-6	15	NC	1	NC	1
480			min	0	3	-.002	3	0	15	-7.75e-5	1	NC	1	NC	1
481		13	max	0	1	.001	2	.001	1	-2.792e-6	15	NC	1	NC	1
482			min	0	3	-.002	3	0	15	-7.75e-5	1	NC	1	NC	1
483		14	max	0	1	0	2	.001	1	-2.792e-6	15	NC	1	NC	1
484			min	0	3	-.001	3	0	15	-7.75e-5	1	NC	1	NC	1
485		15	max	0	1	0	2	0	1	-2.792e-6	15	NC	1	NC	1
486			min	0	3	-.001	3	0	15	-7.75e-5	1	NC	1	NC	1
487		16	max	0	1	0	2	0	1	-2.792e-6	15	NC	1	NC	1
488			min	0	3	0	3	0	15	-7.75e-5	1	NC	1	NC	1
489		17	max	0	1	0	2	0	1	-2.792e-6	15	NC	1	NC	1
490			min	0	3	0	3	0	15	-7.75e-5	1	NC	1	NC	1
491		18	max	0	1	0	2	0	1	-2.792e-6	15	NC	1	NC	1
492			min	0	3	0	3	0	15	-7.75e-5	1	NC	1	NC	1
493		19	max	0	1	0	1	0	1	-2.792e-6	15	NC	1	NC	1
494			min	0	1	0	1	0	1	-7.75e-5	1	NC	1	NC	1
495	M1	1	max	.007	3	.193	1	0	1	1.206e-2	1	NC	1	NC	1
496			min	-.003	2	-.032	3	0	15	-1.607e-2	3	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
497		2	max	.007	3	.096	1	0	15	5.823e-3	1	NC	5	NC	1
498			min	-.003	2	-.016	3	-.007	1	-7.977e-3	3	1390.803	1	NC	1
499		3	max	.007	3	.009	3	0	15	6.84e-6	10	NC	5	NC	1
500			min	-.003	2	-.008	1	-.01	1	-2.197e-4	1	668.391	1	NC	1
501		4	max	.006	3	.051	3	0	15	4.655e-3	1	NC	15	NC	1
502			min	-.003	2	-.127	1	-.009	1	-3.423e-3	3	420.727	1	NC	1
503		5	max	.006	3	.104	3	0	15	9.53e-3	1	9566.769	15	NC	1
504			min	-.003	2	-.251	1	-.006	1	-6.763e-3	3	302.735	1	NC	1
505		6	max	.006	3	.161	3	0	15	1.44e-2	1	7564.703	15	NC	1
506			min	-.003	2	-.373	1	-.003	1	-1.01e-2	3	237.844	1	NC	1
507		7	max	.006	3	.216	3	0	1	1.928e-2	1	6382.264	15	NC	1
508			min	-.003	2	-.481	1	0	3	-1.344e-2	3	199.61	1	NC	1
509		8	max	.006	3	.262	3	0	1	2.415e-2	1	5682.415	15	NC	1
510			min	-.003	2	-.567	1	0	15	-1.678e-2	3	177.027	1	NC	1
511		9	max	.006	3	.292	3	0	15	2.649e-2	1	5316.258	15	NC	1
512			min	-.003	2	-.621	1	0	1	-1.707e-2	3	165.263	1	NC	1
513		10	max	.006	3	.303	3	0	1	2.713e-2	1	5204.358	15	NC	1
514			min	-.003	2	-.639	1	0	15	-1.531e-2	3	161.732	1	NC	1
515		11	max	.006	3	.296	3	0	1	2.777e-2	1	5316.065	15	NC	1
516			min	-.003	2	-.621	1	0	15	-1.356e-2	3	165.466	1	NC	1
517		12	max	.005	3	.271	3	0	15	2.611e-2	1	5682.007	15	NC	1
518			min	-.003	2	-.566	1	-.001	1	-1.158e-2	3	177.643	1	NC	1
519		13	max	.005	3	.231	3	0	15	2.101e-2	1	6381.55	15	NC	1
520			min	-.003	2	-.478	1	0	1	-9.262e-3	3	201.106	1	NC	1
521		14	max	.005	3	.18	3	.002	1	1.591e-2	1	7563.497	15	NC	1
522			min	-.003	2	-.368	1	0	15	-6.947e-3	3	241.024	1	NC	1
523		15	max	.005	3	.121	3	.006	1	1.082e-2	1	9564.689	15	NC	1
524			min	-.002	2	-.245	1	0	15	-4.633e-3	3	309.222	1	NC	1
525		16	max	.005	3	.061	3	.009	1	5.721e-3	1	NC	15	NC	1
526			min	-.002	2	-.121	1	0	15	-2.318e-3	3	434.225	1	NC	1
527		17	max	.005	3	.003	3	.009	1	6.247e-4	1	NC	5	NC	1
528			min	-.002	2	-.005	2	0	15	-3.164e-6	3	698.411	1	NC	1
529		18	max	.005	3	.096	1	.007	1	7.345e-3	1	NC	5	NC	1
530			min	-.002	2	-.049	3	0	15	-2.267e-3	3	1466.467	1	NC	1
531		19	max	.005	3	.187	1	0	15	1.428e-2	1	NC	1	NC	1
532			min	-.002	2	-.098	3	0	1	-4.613e-3	3	NC	1	NC	1
533	M5	1	max	.02	3	.371	1	0	1	0	1	NC	1	NC	1
534			min	-.014	2	-.019	3	0	1	0	1	NC	1	NC	1
535		2	max	.02	3	.186	1	0	1	0	1	NC	5	NC	1
536			min	-.014	2	-.011	3	0	1	0	1	729.577	1	NC	1
537		3	max	.02	3	.027	3	0	1	0	1	NC	15	NC	1
538			min	-.014	2	-.028	1	0	1	0	1	338.251	1	NC	1
539		4	max	.02	3	.12	3	0	1	0	1	7176.111	15	NC	1
540			min	-.014	2	-.292	1	0	1	0	1	203.36	1	NC	1
541		5	max	.019	3	.253	3	0	1	0	1	4996.893	15	NC	1
542			min	-.013	2	-.584	1	0	1	0	1	141.005	1	NC	1
543		6	max	.019	3	.403	3	0	1	0	1	3832.696	15	NC	1
544			min	-.013	2	-.878	1	0	1	0	1	107.785	1	NC	1
545		7	max	.018	3	.551	3	0	1	0	1	3162.848	15	NC	1
546			min	-.013	2	-1.146	1	0	1	0	1	88.711	1	NC	1
547		8	max	.018	3	.676	3	0	1	0	1	2774.575	15	NC	1
548			min	-.012	2	-1.362	1	0	1	0	1	77.672	1	NC	1
549		9	max	.018	3	.757	3	0	1	0	1	2575.675	15	NC	1
550			min	-.012	2	-1.498	1	0	1	0	1	72.027	1	NC	1
551		10	max	.017	3	.786	3	0	1	0	1	2515.722	15	NC	1
552			min	-.012	2	-1.544	1	0	1	0	1	70.348	1	NC	1
553		11	max	.017	3	.767	3	0	1	0	1	2575.766	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
554			min	-.012	2	-1.498	1	0	1	0	1	72.128	1	NC	1
555		12	max	.016	3	.7	3	0	1	0	1	2774.793	15	NC	1
556			min	-.011	2	-1.359	1	0	1	0	1	78.008	1	NC	1
557		13	max	.016	3	.592	3	0	1	0	1	3163.292	15	NC	1
558			min	-.011	2	-1.137	1	0	1	0	1	89.593	1	NC	1
559		14	max	.015	3	.456	3	0	1	0	1	3833.561	15	NC	1
560			min	-.011	2	-.863	1	0	1	0	1	109.796	1	NC	1
561		15	max	.015	3	.304	3	0	1	0	1	4998.604	15	NC	1
562			min	-.011	2	-.565	1	0	1	0	1	145.428	1	NC	1
563		16	max	.015	3	.151	3	0	1	0	1	7179.701	15	NC	1
564			min	-.011	2	-.272	1	0	1	0	1	213.441	1	NC	1
565		17	max	.014	3	.009	3	0	1	0	1	NC	15	NC	1
566			min	-.01	2	-.014	2	0	1	0	1	363.218	1	NC	1
567		18	max	.014	3	.186	1	0	1	0	1	NC	5	NC	1
568			min	-.01	2	-.111	3	0	1	0	1	797.729	1	NC	1
569		19	max	.014	3	.353	1	0	1	0	1	NC	1	NC	1
570			min	-.01	2	-.218	3	0	1	0	1	NC	1	NC	1
571	M9	1	max	.007	3	.193	1	0	15	1.607e-2	3	NC	1	NC	1
572			min	-.003	2	-.032	3	0	1	-1.206e-2	1	NC	1	NC	1
573		2	max	.007	3	.096	1	.007	1	7.977e-3	3	NC	5	NC	1
574			min	-.003	2	-.016	3	0	15	-5.823e-3	1	1390.803	1	NC	1
575		3	max	.007	3	.009	3	.01	1	2.197e-4	1	NC	5	NC	1
576			min	-.003	2	-.008	1	0	15	-6.84e-6	10	668.391	1	NC	1
577		4	max	.006	3	.051	3	.009	1	3.423e-3	3	NC	15	NC	1
578			min	-.003	2	-.127	1	0	15	-4.655e-3	1	420.727	1	NC	1
579		5	max	.006	3	.104	3	.006	1	6.763e-3	3	9566.769	15	NC	1
580			min	-.003	2	-.251	1	0	15	-9.53e-3	1	302.735	1	NC	1
581		6	max	.006	3	.161	3	.003	1	1.01e-2	3	7564.703	15	NC	1
582			min	-.003	2	-.373	1	0	15	-1.44e-2	1	237.844	1	NC	1
583		7	max	.006	3	.216	3	0	3	1.344e-2	3	6382.264	15	NC	1
584			min	-.003	2	-.481	1	0	1	-1.928e-2	1	199.61	1	NC	1
585		8	max	.006	3	.262	3	0	15	1.678e-2	3	5682.415	15	NC	1
586			min	-.003	2	-.567	1	0	1	-2.415e-2	1	177.027	1	NC	1
587		9	max	.006	3	.292	3	0	1	1.707e-2	3	5316.258	15	NC	1
588			min	-.003	2	-.621	1	0	15	-2.649e-2	1	165.263	1	NC	1
589		10	max	.006	3	.303	3	0	15	1.531e-2	3	5204.358	15	NC	1
590			min	-.003	2	-.639	1	0	1	-2.713e-2	1	161.732	1	NC	1
591		11	max	.006	3	.296	3	0	15	1.356e-2	3	5316.065	15	NC	1
592			min	-.003	2	-.621	1	0	1	-2.777e-2	1	165.466	1	NC	1
593		12	max	.005	3	.271	3	.001	1	1.158e-2	3	5682.007	15	NC	1
594			min	-.003	2	-.566	1	0	15	-2.611e-2	1	177.643	1	NC	1
595		13	max	.005	3	.231	3	0	1	9.262e-3	3	6381.55	15	NC	1
596			min	-.003	2	-.478	1	0	15	-2.101e-2	1	201.106	1	NC	1
597		14	max	.005	3	.18	3	0	15	6.947e-3	3	7563.497	15	NC	1
598			min	-.003	2	-.368	1	-.002	1	-1.591e-2	1	241.024	1	NC	1
599		15	max	.005	3	.121	3	0	15	4.633e-3	3	9564.689	15	NC	1
600			min	-.002	2	-.245	1	-.006	1	-1.082e-2	1	309.222	1	NC	1
601		16	max	.005	3	.061	3	0	15	2.318e-3	3	NC	15	NC	1
602			min	-.002	2	-.121	1	-.009	1	-5.721e-3	1	434.225	1	NC	1
603		17	max	.005	3	.003	3	0	15	3.164e-6	3	NC	5	NC	1
604			min	-.002	2	-.005	2	-.009	1	-6.247e-4	1	698.411	1	NC	1
605		18	max	.005	3	.096	1	0	15	2.267e-3	3	NC	5	NC	1
606			min	-.002	2	-.049	3	-.007	1	-7.345e-3	1	1466.467	1	NC	1
607		19	max	.005	3	.187	1	0	1	4.613e-3	3	NC	1	NC	1
608			min	-.002	2	-.098	3	0	15	-1.428e-2	1	NC	1	NC	1

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 4.00 x 0.28

<Figure 1>



<Figure 2>

Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	1020.0	27.0	565.0	565.6
Sum	1020.0	27.0	565.0	565.6

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 1020
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	5.247	10215

$\phi N_{cb} = \phi (A_{Nc} / A_{Nco}) \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-4)

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cb} (lb)
220.36	247.75	0.967	1.00	1.000	10215	0.65	5710

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_a = \phi (A_{Na} / A_{Na0}) \Psi_{ed,Na} \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16a)

A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	ϕ	ϕN_a (lb)
109.66	109.66	1.000	1.000	9755	0.55	5365

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in y-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cby} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cby} (lb)
192.89	220.50	0.925	1.000	1.000	6947	0.70	3934

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cbx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbx} (lb)
165.27	278.72	0.878	1.000	1.000	8282	0.70	3018

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
192.89	220.50	1.000	1.000	1.000	6947	0.70	8508

Shear parallel to edge in y-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cby} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cby} (lb)
165.27	278.72	1.000	1.000	1.000	8282	0.70	6875

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cp} = \phi \min|k_{cp}N_a\,;\, k_{cp}N_{cb}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\,\Psi_{p,Na}N_{a0}\,;\, k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ed,N}\,\Psi_{c,N}\,\Psi_{cp,N}N_b|$ (Eq. D-30a)

k_{cp}	A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	109.66	109.66	1.000	1.000	9755	9755

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ	ϕV_{cp} (lb)
220.36	247.75	0.967	1.000	1.000	10215	8785	0.70	12298

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, ϕN_n (lb)	Ratio	Status
Steel	1020	6071	0.17	Pass
Concrete breakout	1020	5710	0.18	Pass
Adhesive	**1020**	**5365**	**0.19**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, ϕV_n (lb)	Ratio	Status
Steel	**566**	**3156**	**0.18**	**Pass (Governs)**
T Concrete breakout y+	565	3934	0.14	Pass
T Concrete breakout x+	27	3018	0.01	Pass
|| Concrete breakout y+	27	8508	0.00	Pass
|| Concrete breakout x+	565	6875	0.08	Pass
Concrete breakout, combined	-	-	0.14	Pass
Pryout	566	12298	0.05	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status
Sec. D.7.1	0.19	0.00	19.0 %	1.0	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 7.00 x 0.28

<Figure 1>



<Figure 2>



Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	2495.5	1558.5	0.0	1558.5
2	2495.5	1558.5	0.0	1558.5
Sum	4991.0	3117.0	0.0	3117.0

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 4991
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	6.000	12492

$\phi N_{cbg} = \phi (A_{Nc} / A_{Nco}) \Psi_{ec,N} \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-5)

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cbg} (lb)
378.00	324.00	1.000	0.972	1.00	1.000	12492	0.65	9208

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_{ag} = \phi (A_{Na} / A_{Na0}) \Psi_{ed,Na} \Psi_{g,Na} \Psi_{ec,Na} \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16b)

A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0}(lb)	ϕ	ϕN_{ag} (lb)
158.66	109.66	1.000	1.043	1.000	1.000	9755	0.55	8093

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	12.00	15593

$\phi V_{cbgx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ec,V}\Psi_{ed,V}\Psi_{c,V}\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-22)

A_{Vc} (in²)	A_{Vco} (in²)	$\Psi_{ec,V}$	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbgx} (lb)
378.00	648.00	1.000	0.836	1.000	1.000	15593	0.70	5323

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	8.16	8744

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\Psi_{c,V}\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in²)	A_{Vco} (in²)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
299.64	299.64	1.000	1.000	1.000	8744	0.70	12241

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cpg} = \phi \min|k_{cp}N_{ag}\,;\, k_{cp}N_{cbg}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\Psi_{g,Na}\Psi_{ec,Na}\Psi_{p,Na}N_{a0}\,;\, k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ec,N}\Psi_{ed,N}\Psi_{c,N}\Psi_{cp,N}N_b|$ (Eq. D-30b)

k_{cp}	A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	158.66	109.66	1.000	1.043	1.000	1.000	9755	14715

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ
378.00	324.00	1.000	0.972	1.000	1.000	12492	14166	0.70

ϕV_{cpg} (lb)
19833

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, øN_n (lb)	Ratio	Status
Steel	2496	6071	0.41	Pass
Concrete breakout	4991	9208	0.54	Pass
Adhesive	**4991**	**8093**	**0.62**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, øV_n (lb)	Ratio	Status
Steel	1559	3156	0.49	Pass
T Concrete breakout x+	**3117**	**5323**	**0.59**	**Pass (Governs)**

|| Concrete breakout y-	**1559**	**12241**	**0.13**	**Pass (Governs)**
Pryout	3117	19833	0.16	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status
Sec. D.7.3	0.62	0.59	120.2 %	1.2	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.