

Schletter, Inc.		25ÁTilt w/o Seismic Design
HCV	Standard PVMini Racking System	
	Representative Calculations - ASCE 7-10	

1. INTRODUCTION

1.1 Project Description

The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. PVMini ground mount system.

1.2 Construction

Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to aluminum struts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

	Maximum			Minimum	
Height =	1700	mm	Height =	1550	mm
Width =	1050	mm	Width =	970	mm
Dead Load =	3.00	psf	Dead Load =	1.75	psf

Modules Per Row =	1
Module Tilt =	25°
Maximum Height Above Grade =	3 ft



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

1.3 Technical Codes

- ASCE 7-10 - Chapter 26-31, Wind Loads
- ASCE 7-10 - Chapter 7, Snow Loads
- ASCE 7-10 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2012, 2015
- Aluminum Design Manual, Eighth Edition, 2005

2. LOAD ACTIONS

2.1 Permanent Loads

g_{MAX} =	3.00	psf	*Self-weight of the PV modules.*
g_{MIN} =	1.75	psf	

2.2 Snow Loads

Ground Snow Load, P_g =	30.00	psf	
Sloped Roof Snow Load, P_s =	18.56	psf	*(ASCE 7-10, Eq. 7.4-1)*
I_s =	1.00		
C_s =	0.82		
C_e =	0.90		
C_t =	1.20		

2.3 Wind Loads

Design Wind Speed, V =	150	mph	Exposure Category = C
Height ≤	15	ft	Importance Category = II

Peak Velocity Pressure, q_z = 35.33 psf *Including the gust factor, G=0.85. (ASCE 7-10, Eq. 27.3-1)*

Pressure Coefficients

$Cf+_{TOP}$	=	1.1	*(Pressure)*
$Cf+_{BOTTOM}$	=	1.7	
$Cf-_{TOP}$	=	-2.2	*(Suction)*
$Cf-_{BOTTOM}$	=	-1	

Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0611-1e. Negative forces are applied away from the surface.

2.4 Seismic Loads - N/A

S_S =	0.00	R =	1.25
S_{DS} =	0.00	C_S =	0
S_1 =	0.00	ρ =	1.3
S_{D1} =	0.00	Ω =	1.25
T_a =	0.00	C_d =	1.25

ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.5W
1.2D + 1.0W + 0.5S
0.9D + 1.0W ^{M}
1.54D + 1.3E + 0.2S ^{R}
0.56D + 1.3E ^{R}
1.54D + 1.25E + 0.2S ^{O}
0.56D + 1.25E ^{O}

(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S
1.0D + 0.6W
1.0D + 0.75L + 0.45W + 0.75S
0.6D + 0.6W ^{M}
1.238D + 0.875E ^{O}
1.1785D + 0.65625E + 0.75S ^{O}
0.362D + 0.875E ^{O}

(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)

^{M} *Uses the minimum allowable module dead load.*
^{R} *Include redundancy factor of 1.3.*
^{O} *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location	**Diagonal Struts**	Location	**Front Reactions**	Location
M13	Top	M3	Outer	N7	Outer
M16	Bottom	M7	Inner	N15	Inner
		M11	Outer	N23	Outer

Girders	Location	**Rear Struts**	Location	**Rear Reactions**	Location
M1	Outer	M2	Outer	N8	Outer
M5	Inner	M6	Inner	N16	Inner
M9	Outer	M10	Outer	N24	Outer

Front Struts	Location	**Bracing**
M4	Outer	M15
M8	Inner	M16A
M12	Outer	

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type =	**ProfiPlus**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	51	in
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	29.63	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	28.47	ksi
S_y =	0.51	in^3
S_x =	0.37	in^3
E =	10100	ksi
I_y =	0.60	in^4
I_x =	0.29	in^4
A =	0.90	in^2
g =	1.08	lbs/ft
M_y =	0.420	k-ft
M_z =	0.035	k-ft
$M_{y\ allowable}$ =	1.261	k-ft
$M_{z\ allowable}$ =	0.871	k-ft
Utilization =	37%	



4.2 Girder Design

Loads from purlins are transferred using an inclined girder, which is connected to a set of aluminum struts. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type =	**Flex Profi**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	33.78	in
$\Phi F_{ty\ AXIAL}$ =	14.29	ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	29.77	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	13.46	ksi
S_y =	0.59	in^3
S_x =	0.46	in^3
E =	10100	ksi
I_y =	0.88	in^4
I_x =	0.52	in^4
A =	0.89	in^2
g =	1.07	lbs/ft
M_y =	-0.477	k-ft
M_z =	-0.019	k-ft
P_n =	0.166	k
$M_{y\ allowable}$ =	1.461	k-ft
$M_{z\ allowable}$ =	0.513	k-ft
$P_{n\ allowable}$ =	12.764	k
Utilization =	38%	



4.3 Front Strut Design

The front aluminum strut connects a portion of the girder to the foundation. Vertical girder forces are then transferred down through the strut into the foundation. The strut is attached with single M8 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**30x30x3**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	18.00	in
$\Phi F_{ty\ AXIAL}$ =	24.52	ksi
$\Phi F_{ty\ BENDING}$ =	31.19	ksi
S_y =	0.16	in^3
S_x =	0.16	in^3
E =	10100	ksi
I_y =	0.10	in^4
I_x =	0.10	in^4
A =	0.50	in^2
g =	0.60	lbs/ft
M_y =	0.000	k-ft
M_z =	0.000	k-ft
P_n =	0.880	k
$M_{y\ allowable}$ =	0.423	k-ft
$M_{z\ allowable}$ =	0.423	k-ft
$P_{n\ allowable}$ =	12.310	k
Utilization =	7%	



4.4 Diagonal Strut Design

A diagonal aluminum strut braces the support structure. It connects at a front portion of the girder and transfers horizontal forces to the rear foundation connection. The strut is attached with single M8 bolts at each end. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Strut Type =	**30x30x3**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	46.38	in
$\Phi F_{ty\ AXIAL}$ =	7.60	ksi
$\Phi F_{ty\ BENDING}$ =	29.80	ksi
S_y =	0.16	in^3
S_x =	0.16	in^3
E =	10100	ksi
I_y =	0.10	in^4
I_x =	0.10	in^4
A =	0.50	in^2
g =	0.60	lbs/ft
M_y =	0.000	k-ft
M_z =	0.000	k-ft
P_n =	0.468	k
$M_{y\ allowable}$ =	0.404	k-ft
$M_{z\ allowable}$ =	0.404	k-ft
$P_{n\ allowable}$ =	3.814	k
Utilization =	12%	



4.5 Rear Strut Design

An aluminum strut connects the rear portion of the girder to the rear foundation connection. Both vertical and horizontal forces are transferred from the girder. The strut is attached with single M8 bolts at each end. See Appendix A.5 for detailed member calculations. Section units are in (mm).

Strut Type =	**30x30x3**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	36.18	in
$\Phi F_{ty\ AXIAL}$ =	11.59	ksi
$\Phi F_{ty\ BENDING}$ =	30.23	ksi
S_y =	0.16	in^3
S_x =	0.16	in^3
E =	10100	ksi
I_y =	0.10	in^4
I_x =	0.10	in^4
A =	0.50	in^2
g =	0.60	lbs/ft
M_y =	0.000	k-ft
M_z =	0.000	k-ft
P_n =	0.712	k
$M_{y\ allowable}$ =	0.410	k-ft
$M_{z\ allowable}$ =	0.410	k-ft
$P_{n\ allowable}$ =	5.820	k
Utilization =	12%	



4.6 Cross Brace Design

In order to resist weak side loading, aluminum cross bracing kits are provided. The cross bracing is attached at one end of a rear aluminum strut diagonally down to the bottom end of an adjacent strut. Single M10 bolts are provided at each of the cross bracing. Section units are in (mm).

Brace Type =	**1.5x0.25**	
Aluminum Type =	6061-T6	
F_{ty} =	35	ksi
Φ =	0.90	
S_y =	0.02	in^3
E =	10100	ksi
I_y =	33.25	in^4
A =	0.38	in^2
g =	0.45	lbs/ft
M_y =	0.002	k-ft
P_n =	0.092	k
$M_{y\ allowable}$ =	0.046	k-ft
$P_{n\ allowable}$ =	11.813	k
Utilization =	5%	



A cross brace kit is required every 38 bays and is to be installed in centermost bays.

5. FOUNDATION DESIGN CALCULATIONS

5.1 Helical Pile Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete foundation design.

Maximum	Front	Rear	
Tensile Load =	183.62	1686.23	k
Compressive Load =	1144.30	1124.58	k
Lateral Load =	1.68	885.47	k
Moment (Weak Axis) =	0.00	0.00	k

5.2 Design of Ballast Foundations

Ballast foundations are used to secure the racking structure in place. The foundations are checked for potential overturning and sliding. Bearing pressures applied by the racking and ballast foundations are checked against the allowable bearing pressures provided by the IBC table 1806.2 (2012, 2015).



Concrete Properties

Weight of Concrete =	145 pcf
Compressive Strength =	2500 psi
Yield Strength =	60000 psi

Footing Reinforcement

Use fiber reinforcing with (1) #5 rebar.

Overturning Check

M_O =	24044.7 in-lbs
Resisting Force Required =	801.49 lbs
S.F. =	1.67
Weight Required =	1335.81 lbs
Minimum Width =	21 in in
Weight Provided =	1903.13 lbs

A minimum 60in long x 21in wide x 18in tall ballast foundation is required to resist overturning.

Sliding

Force =	204.28 lbs
Friction =	0.4
Weight Required =	510.69 lbs
Resisting Weight =	1903.13 lbs
Additional Weight Required =	0 lbs

Use a 60in long x 21in wide x 18in tall ballast foundation to resist sliding. Friction is OK.

Cohesion

Sliding Force =	204.28 lbs
Cohesion =	130 psf
Area =	8.75 ft^2
Resisting =	951.56 lbs
Additional Weight Required =	0 lbs

Use a 60in long x 21in wide x 18in tall ballast foundation. Cohesion is OK.

Shear Key

Additional Force =	0 lbs
Lateral Bearing Pressure =	200 psf/ft
Required Depth =	0.00 ft
f'_c =	2500 psi
Length =	8 in

Shear key is not required.

Bearing Pressure

	Ballast Width			
	21 in	22 in	23 in	24 in
P_{ftg} = (145 pcf)(5 ft)(1.5 ft)(1.75 ft) =	1903 lbs	1994 lbs	2084 lbs	2175 lbs

ASD LC	1.0D + 1.0S				1.0D + 0.6W				1.0D + 0.75L + 0.45W + 0.75S				0.6D + 0.6W			
Width	21 in	22 in	23 in	24 in	21 in	22 in	23 in	24 in	21 in	22 in	23 in	24 in	21 in	22 in	23 in	24 in
F_A	375 lbs	375 lbs	375 lbs	375 lbs	429 lbs	429 lbs	429 lbs	429 lbs	572 lbs	572 lbs	572 lbs	572 lbs	-82 lbs	-82 lbs	-82 lbs	-82 lbs
F_B	263 lbs	263 lbs	263 lbs	263 lbs	466 lbs	466 lbs	466 lbs	466 lbs	524 lbs	524 lbs	524 lbs	524 lbs	-777 lbs	-777 lbs	-777 lbs	-777 lbs
F_V	31 lbs	31 lbs	31 lbs	31 lbs	364 lbs	364 lbs	364 lbs	364 lbs	294 lbs	294 lbs	294 lbs	294 lbs	-409 lbs	-409 lbs	-409 lbs	-409 lbs
P_{total}	2541 lbs	2631 lbs	2722 lbs	2813 lbs	2799 lbs	2890 lbs	2980 lbs	3071 lbs	2999 lbs	3090 lbs	3181 lbs	3271 lbs	283 lbs	337 lbs	392 lbs	446 lbs
M	265 lbs-ft	265 lbs-ft	265 lbs-ft	265 lbs-ft	497 lbs-ft	497 lbs-ft	497 lbs-ft	497 lbs-ft	551 lbs-ft	551 lbs-ft	551 lbs-ft	551 lbs-ft	634 lbs-ft	634 lbs-ft	634 lbs-ft	634 lbs-ft
e	0.10 ft	0.10 ft	0.10 ft	0.09 ft	0.18 ft	0.17 ft	0.17 ft	0.16 ft	0.18 ft	0.18 ft	0.17 ft	0.17 ft	2.24 ft	1.88 ft	1.62 ft	1.42 ft
L/6	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft	0.83 ft
f_{min}	254.0 psf	252.4 psf	250.9 psf	249.5 psf	251.7 psf	250.2 psf	248.7 psf	247.4 psf	267.2 psf	264.9 psf	262.9 psf	261.0 psf	0.0 psf	0.0 psf	0.0 psf	0.0 psf
f_{max}	326.7 psf	321.7 psf	317.2 psf	313.0 psf	388.0 psf	380.3 psf	373.2 psf	366.7 psf	418.4 psf	409.2 psf	400.9 psf	393.3 psf	418.4 psf	198.1 psf	154.8 psf	138.0 psf

Maximum Bearing Pressure =	418 psf
Allowable Bearing Pressure =	1500 psf

Use a 60in long x 21in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Weak Side Design

Overturning Check

M_O =	0.0 ft-lbs
Resisting Force Required =	0.00 lbs
S.F. =	1.67
Weight Required =	0.00 lbs
Minimum Width =	21 in in
Weight Provided =	1903.13 lbs

A minimum 60in long x 21in wide x 18in tall ballast foundation is required to resist overturning.



Bearing Pressure

ASD LC	1.238D + 0.875E			1.1785D + 0.65625E + 0.75S			0.362D + 0.875E		
Width	21 in			21 in			21 in		
Support	Outer	Inner	Outer	Outer	Inner	Outer	Outer	Inner	Outer
F_Y	54 lbs	134 lbs	51 lbs	183 lbs	525 lbs	180 lbs	16 lbs	39 lbs	15 lbs
F_V	0 lbs	0 lbs	0 lbs	1 lbs	0 lbs	0 lbs	0 lbs	0 lbs	0 lbs
P_{total}	2410 lbs	2490 lbs	2407 lbs	2426 lbs	2767 lbs	2423 lbs	705 lbs	728 lbs	704 lbs
M	0 lbs-ft	0 lbs-ft	0 lbs-ft	1 lbs-ft	1 lbs-ft	0 lbs-ft	0 lbs-ft	0 lbs-ft	0 lbs-ft
e	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft
L/6	0.29 ft	1.75 ft	1.75 ft	1.75 ft	1.75 ft	1.75 ft	1.75 ft	1.75 ft	1.75 ft
f_{min}	275.4 sqft	284.5 sqft	275.1 sqft	276.9 sqft	316.1 sqft	276.7 sqft	80.5 sqft	83.2 sqft	80.4 sqft
f_{max}	275.5 psf	284.6 psf	275.1 psf	277.6 psf	316.5 psf	277.1 psf	80.6 psf	83.2 psf	80.5 psf

Maximum Bearing Pressure = 316 psf
Allowable Bearing Pressure = 1500 psf

Use a 60in long x 21in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Foundation Requirements: 60in long x 21in wide x 18in tall ballast foundation and fiber reinforcing with (1) #5 rebar.

5.3 Foundation Anchors

Threaded rods are anchored to the the ballast foundations using the Simpson AT-XP epoxy solution. LRFD load results are compared to the allowable strengths of the epoxy solution. Please see the supplementary calculations provided by the Simpson Anchor Designer software.

6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of a Schletter, Inc. Klicktop connector. The reliability of calculations is uncertain due to limited standards, therefore the strength of the fasteners has been evaluated by load testing.

Fastening of Modules to Purlins	
Maximum Uplifting Force =	0.732 k
Allowable Uplift =	1.214 k
Utilization =	60%



Fastening of Purlins to Girders	
Maximum Uplifting Force =	1.109 k
Allowable Uplift =	1.116 k
Utilization =	99%



6.2 Bolted Connections

The aluminum struts connect the aluminum girder ends to custom brackets with mounting holes. Cross bracing is attached to rear struts to provide lateral stability. Single M8 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Front Strut	
Maximum Axial Load =	0.880 k
M8 Bolt Capacity =	5.692 k
Strut Bearing Capacity =	7.952 k
Utilization =	15%

Rear Strut	
Maximum Axial Load =	1.135 k
M8 Bolt Capacity =	5.692 k
Strut Bearing Capacity =	7.952 k
Utilization =	20%

Diagonal Strut	
Maximum Axial Load =	0.468 k
M8 Bolt Shear Capacity =	5.692 k
Strut Bearing Capacity =	7.952 k
Utilization =	8%

Bracing	
Maximum Axial Load =	0.092 k
M10 Bolt Capacity =	8.894 k
Strut Bearing Capacity =	7.952 k
Utilization =	1%



Bolt and bearing capacities are accounting for double shear (ASCE 8-02, Eq. 5.3.4-1). Struts under compression are shown to demonstrate the load transfer from the girder. Single M8 bolts are located at each end of the strut and are subjected to double shear.

7. SEISMIC DESIGN

7.1 Seismic Drift - N/A

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx} =	30.83 in
Allowable Story Drift for All Other Structures, Δ = {	$0.020h_{sx}$
	0.617 in
Max Drift, Δ_{MAX} =	0.006 in
N/A	

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **ProfiPlus**

Strong Axis:

3.4.14

L_b = 51.00 in

J = 0.255

132.801

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 29.6 ksi

3.4.16

b/t = 7.4

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φyFcy

φF_L= 33.3 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

Weak Axis:

3.4.14

L_b = 51.00 in

J = 0.255

137.906

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 29.6

3.4.16

b/t = 23.9

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.5 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 23.9

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 30

Cc = 30

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 29.6 ksi

Ix = 250988 mm^4

0.603 in^4

y = 30 mm

Sx = 0.511 in^3

$M_{max}St$ = 1.261 k-ft

3.4.18

h/t = 7.4

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 20

Cc = 20

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 28.5 ksi

Iy = 120291 mm^4

0.289 in^4

x = 20 mm

Sy = 0.367 in^3

$M_{max}Wk$ = 0.871 k-ft

Compression

3.4.9

b/t = 7.4

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φyFcy

φF_L= 33.3 ksi

b/t = 23.9

S1 = 12.21

S2 = 32.70

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.5 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L= φyFcy

φF_L= 33.25 ksi

φF_L= 28.47 ksi

A = 578.06 mm^2

0.90 in^2

P_{max} = 25.51 kips

Girder = **Flex Profi**

Strong Axis:

3.4.11

L_b = 33.78 in
ry = 1.374
Cb = 1.33
21.3453

$$S1 = \frac{1.2(Bc - \frac{\theta_y}{\theta_b}Fcy)}{Dc}$$

S1 = 1.37733

$$S2 = 1.2C_c$$

S2 = 79.2
φF_L= φb[Bc-Dc*Lb/(1.2*ry*√(Cb))
φF_L= 29.8 ksi

3.4.15

N/A for Strong Direction

3.4.16

b/t = 4.29

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L= φyFcy
φF_L= 33.3 ksi

3.4.16

N/A for Strong Direction

Weak Axis:

3.4.11

L_b = 33.78 in
ry = 1.374
Cb = 1.33
24.5845

$$S1 = \frac{1.2(Bc - \frac{\theta_y}{\theta_b}Fcy)}{Dc}$$

S1 = 1.37733

$$S2 = 1.2C_c$$

S2 = 79.2
φF_L= φb[Bc-Dc*Lb/(1.2*ry*√(Cb))
φF_L= 29.8 ksi

3.4.15

b/t = 24.46

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{5.1Dp}$$

S1 = 3.8

$$S2 = \frac{k_1 Bp}{5.1Dp}$$

S2 = 14.7
F_{UT}= (φbk2*√(BpE))/(5.1b/t)
F_{UT}= 9.4 ksi

3.4.16

N/A for Weak Direction

3.4.16

b/t = 24.46

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
F_{ST}= φb[Bp-1.6Dp*b/t]
F_{ST}= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.16.2

N/A for Strong Direction

3.4.16.2

b/t = 24.46

t = 2.6

ds = 6.05

rs = 3.49

S = 21.70

ρst = 0.22

F_{UT}= 9.37

F_{ST}= 28.24

φF_L= Fut + (Fst - Fut)ρst < Fst

φF_L= 13.5 ksi

3.4.18

h/t = 24.46

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 34.4

m = 0.70

C_0 = 34.23

Cc = 37.77

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 72.1

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

3.4.18

h/t = 4.29

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 29

Cc = 29

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 29.8 ksi

Ix = 364470 mm^4

0.876 in^4

y = 37.77 mm

Sx = 0.589 in^3

M_{max}St = 1.461 k-ft

φF_LWk= 13.5 ksi

Iy = 217168 mm^4

0.522 in^4

x = 29 mm

Sy = 0.457 in^3

M_{max}Wk = 0.513 k-ft

Compression

3.4.7

λ = 0.46067

r = 1.374 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.90326

φF_L= φcc(Bc-Dc*λ)

φF_L= 30.1251 ksi

3.4.8

b/t = 24.46
S1 = 3.83
S2 = 10.30
φF_L = (φck2*√(BpE))/(5.1b/t)
φF_L = 10.4 ksi

3.4.9

b/t = 4.29
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φyFcy
φF_L = 33.3 ksi

b/t = 24.46
S1 = 12.21
S2 = 32.70
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.9.1

b/t = 24.46
t = 2.6
ds = 6.05
rs = 3.49
S = 21.70
ρst = 0.22
F_{UT} = 10.43
F_{ST} = 28.24
φF_L = Fut + (Fst - Fut)ρst < Fst
φF_L = 14.3 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 14.29 ksi
A = 576.21 mm^2
0.89 in^2
P_{max} = 12.76 kips

A.3 Design of Aluminum Struts (Front) - Aluminum Design Manual, 2005 Edition

Strut = **30x30x3**

Strong Axis:

3.4.14

L_b = 18.00 in
J = 0.16
47.2194

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L= 31.2 ksi

3.4.16

b/t = 7.75

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L= φyFcy
φF_L= 33.3 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0
φF_L= 1.17φyFcy
φF_L= 38.9 ksi

3.4.18

h/t = 7.75

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9
m = 0.65
C_0 = 15
Cc = 15

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3
φF_L= 1.3φyFcy
φF_L= 43.2 ksi

φF_LSt= 31.2 ksi
Ix = 39958.2 mm^4
0.096 in^4
y = 15 mm
Sx = 0.163 in^3
M_{max}St = 0.423 k-ft

Weak Axis:

3.4.14

L_b = 18.00 in
J = 0.16
47.2194

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L= 31.2

3.4.16

b/t = 7.75

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L= φyFcy
φF_L= 33.3 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 7.75

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9
m = 0.65
C_0 = 15
Cc = 15

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3
φF_L= 1.3φyFcy
φF_L= 43.2 ksi

φF_LWk= 31.2 ksi
Iy = 39958.2 mm^4
0.096 in^4
x = 15 mm
Sy = 0.163 in^3
M_{max}Wk = 0.423 k-ft

Compression

3.4.7

λ = 0.77182

r = 0.437 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.83792

φF_L= φcc(Bc-Dc*λ)

φF_L= 24.5226 ksi

3.4.9

b/t = 7.75

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φyFcy

φF_L= 33.3 ksi

b/t = 7.75

S1 = 12.21

S2 = 32.70

φF_L= φyFcy

φF_L= 33.3 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L= φyFcy

φF_L= 33.25 ksi

φF_L= 24.52 ksi

A = 323.87 mm^2

0.50 in^2

P_{max} = 12.31 kips

A.4 Design of Aluminum Struts (Diagonal) - Aluminum Design Manual, 2005 Edition

Strut = **30x30x3**

Strong Axis:

3.4.14

$L_b =$ 46.38 in

J = 0.16

121.663

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

$\varphi F_L =$ φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

$\varphi F_L =$ 29.8 ksi

3.4.16

b/t = 7.75

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

$\varphi F_L =$ φyFcy

$\varphi F_L =$ 33.3 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

$\varphi F_L =$ 1.17φyFcy

$\varphi F_L =$ 38.9 ksi

3.4.18

h/t = 7.75

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

$C_0 =$ 15

Cc = 15

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

$\varphi F_L =$ 1.3φyFcy

$\varphi F_L =$ 43.2 ksi

$\varphi F_L St =$ 29.8 ksi

Ix = 39958.2 mm^4

0.096 in^4

y = 15 mm

Sx = 0.163 in^3

$M_{max}St =$ 0.404 k-ft

Weak Axis:

3.4.14

$L_b =$ 46.38 in

J = 0.16

121.663

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

$\varphi F_L =$ φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

$\varphi F_L =$ 29.8

3.4.16

b/t = 7.75

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

$\varphi F_L =$ φyFcy

$\varphi F_L =$ 33.3 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 7.75

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

$C_0 =$ 15

Cc = 15

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

$\varphi F_L =$ 1.3φyFcy

$\varphi F_L =$ 43.2 ksi

$\varphi F_L Wk =$ 33.3 ksi

Iy = 39958.2 mm^4

0.096 in^4

x = 15 mm

Sy = 0.163 in^3

$M_{max}Wk =$ 0.450 k-ft

Compression

3.4.7

$\lambda =$ 1.98863

r = 0.437 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^* =$ 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^* =$ 1.23671

$\varphi cc =$ 0.85841

$\varphi F_L = (\varphi ccFcy)/(\lambda^2)$

$\varphi F_L =$ 7.59722 ksi

3.4.9

b/t = 7.75

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

$\varphi F_L = \varphi yFcy$

$\varphi F_L =$ 33.3 ksi

b/t = 7.75

S1 = 12.21

S2 = 32.70

$\varphi F_L = \varphi yFcy$

$\varphi F_L =$ 33.3 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

$\varphi F_L = \varphi yFcy$

$\varphi F_L =$ 33.25 ksi

$\varphi F_L =$ 7.60 ksi

A = 323.87 mm^2

0.50 in^2

$P_{max} =$ 3.81 kips

A.5 Design of Aluminum Struts (Rear) - Aluminum Design Manual, 2005 Edition

Strut = **30x30x3**

Strong Axis:		Weak Axis:	
3.4.14		**3.4.14**	
L_b =	36.18 in	L_b =	36.18 in
J =	0.16	J =	0.16
	94.9139		94.9139
$S1 = \left(\frac{Bc-\frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$		$S1 = \left(\frac{Bc-\frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$	
S1 =	0.51461	S1 =	0.51461
$S2 = \left(\frac{C_c}{1.6}\right)^2$		$S2 = \left(\frac{C_c}{1.6}\right)^2$	
S2 =	1701.56	S2 =	1701.56
φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]	φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L=	30.2 ksi	φF_L=	30.2
3.4.16		**3.4.16**	
b/t =	7.75	b/t =	7.75
$S1 = \frac{Bp-\frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$		$S1 = \frac{Bp-\frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$	
S1 =	12.2	S1 =	12.2
$S2 = \frac{k_1Bp}{1.6Dp}$		$S2 = \frac{k_1Bp}{1.6Dp}$	
S2 =	46.7	S2 =	46.7
φF_L=	φyFcy	φF_L=	φyFcy
φF_L=	33.3 ksi	φF_L=	33.3 ksi
3.4.16.1	Not Used	**3.4.16.1**	
Rb/t =	0.0	N/A for Weak Direction	
$S1 = \left(\frac{Bt-1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$			
S1 =	1.1		
$S2 = C_t$			
S2 =	141.0		
φF_L=	1.17φyFcy		
φF_L=	38.9 ksi		
3.4.18		**3.4.18**	
h/t =	7.75	h/t =	7.75
$S1 = \frac{Bbr-\frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$		$S1 = \frac{Bbr-\frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$	
S1 =	36.9	S1 =	36.9
m =	0.65	m =	0.65
C_0 =	15	C_0 =	15
Cc =	15	Cc =	15
$S2 = \frac{k_1Bbr}{mDbr}$		$S2 = \frac{k_1Bbr}{mDbr}$	
S2 =	77.3	S2 =	77.3
φF_L=	1.3φyFcy	φF_L=	1.3φyFcy
φF_L=	43.2 ksi	φF_L=	43.2 ksi
φF_LSt=	30.2 ksi	φF_LWk=	33.3 ksi
Ix =	39958.2 mm^4	Iy =	39958.2 mm^4
	0.096 in^4		0.096 in^4
y =	15 mm	x =	15 mm
Sx =	0.163 in^3	Sy =	0.163 in^3
M_{max}St =	0.410 k-ft	M_{max}Wk =	0.450 k-ft

Compression

3.4.7

$\lambda =$ 1.5514

r = 0.437 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.7972

$\varphi F_L = (\varphi ccFcy)/(\lambda^2)$

φF_L = 11.5927 ksi

3.4.9

b/t = 7.75

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

$\varphi F_L = \varphi yFcy$

φF_L = 33.3 ksi

b/t = 7.75

S1 = 12.21

S2 = 32.70

$\varphi F_L = \varphi yFcy$

φF_L = 33.3 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

$\varphi F_L = \varphi yFcy$

φF_L = 33.25 ksi

φF_L = 11.59 ksi

A = 323.87 mm^2

0.50 in^2

P_{max} = 5.82 kips

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				2		
2	Dead Load, Min	DL		-1				2		
3	Snow Load	SL						2		
4	Wind Load - Pressure	WL						2		
5	Wind Load - Suction	WL						2		
6	Seismic - Lateral	EL								

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-8.366	-8.366	0	0
2	M16	Y	-8.366	-8.366	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-4.45	-4.45	0	0
2	M16	Y	-4.45	-4.45	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-51.748	-51.748	0	0
2	M16	Y	-51.748	-51.748	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	-108.369	-108.369	0	0
2	M16	y	-167.479	-167.479	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	216.738	216.738	0	0
2	M16	y	98.517	98.517	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.5W	Yes	Y		1	1.2	3	1.6	4	.5														
2	LRFD 1.2D + 1.0W + 0.5S	Yes	Y		1	1.2	3	.5	4	1														
3	LRFD 0.9D + 1.0W	Yes	Y		2	.9					5	1												
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3												
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3												
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25												
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25												
8																								
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																
10	ASD 1.0D + 0.6W	Yes	Y		1	1			4	.6														
11	ASD 1.0D + 0.75L + 0.45W + 0....	Yes	Y		1	1	3	.75	4	.45														
12	ASD 0.6D + 0.6W	Yes	Y		2	.6					5	.6												
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875												
14	LATERAL - ASD 1.1785D + 0.65...	Yes	Y		1	1.1...	3	.75			6	.656												
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875												

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N8	max	187.411	2	271.142	2	.002	10	0	10	0	1	0	1
2		min	-225.361	3	-406.535	3	-.156	3	0	3	0	1	0	1
3	N7	max	0	15	309.778	1	0	10	0	10	0	1	0	1
4		min	-.128	2	-32.422	3	-.539	1	0	1	0	1	0	1
5	N15	max	0	15	880.228	1	.167	9	0	9	0	1	0	1
6		min	-1.295	2	-141.243	3	-.588	3	0	3	0	1	0	1
7	N16	max	617.646	2	865.059	2	0	2	0	9	0	1	0	1
8		min	-681.127	3	-1297.098	3	-73.782	3	0	3	0	1	0	1
9	N23	max	0	15	309.893	1	.867	1	.001	1	0	1	0	1
10		min	-.128	2	-31.894	3	0	10	0	10	0	1	0	1
11	N24	max	187.411	2	273.618	2	74.388	3	0	1	0	1	0	1
12		min	-225.789	3	-405.506	3	-.002	10	0	3	0	1	0	1
13	Totals:	max	990.916	2	2796.644	2	0	10						
14		min	-1132.476	3	-2314.699	3	0	3						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M2	1	max	225.137	1	.644	4	.153	1	0	10	0	15	0	1
2			min	-366.377	3	.152	15	-.087	3	0	1	0	1	0	1
3		2	max	225.254	1	.599	4	.153	1	0	10	0	15	0	15
4			min	-366.29	3	.141	15	-.087	3	0	1	0	3	0	4
5		3	max	225.37	1	.553	4	.153	1	0	10	0	9	0	15
6			min	-366.203	3	.13	15	-.087	3	0	1	0	3	0	4
7		4	max	225.487	1	.507	4	.153	1	0	10	0	9	0	15
8			min	-366.115	3	.12	15	-.087	3	0	1	0	3	0	4
9		5	max	225.603	1	.462	4	.153	1	0	10	0	1	0	15
10			min	-366.028	3	.109	15	-.087	3	0	1	0	3	0	4
11		6	max	225.719	1	.416	4	.153	1	0	10	0	1	0	15
12			min	-365.941	3	.098	15	-.087	3	0	1	0	3	0	4
13		7	max	225.836	1	.37	4	.153	1	0	10	0	1	0	15
14			min	-365.854	3	.087	15	-.087	3	0	1	0	3	0	4
15		8	max	225.952	1	.325	4	.153	1	0	10	0	1	0	15
16			min	-365.766	3	.077	15	-.087	3	0	1	0	3	0	4
17		9	max	226.069	1	.279	4	.153	1	0	10	0	1	0	15
18			min	-365.679	3	.066	15	-.087	3	0	1	0	3	0	4
19		10	max	226.185	1	.233	4	.153	1	0	10	0	1	0	15
20			min	-365.592	3	.055	15	-.087	3	0	1	0	3	0	4
21		11	max	226.301	1	.188	4	.153	1	0	10	0	1	0	15
22			min	-365.504	3	.044	15	-.087	3	0	1	0	3	0	4
23		12	max	226.418	1	.142	4	.153	1	0	10	0	1	0	15
24			min	-365.417	3	.034	15	-.087	3	0	1	0	3	0	4
25		13	max	226.534	1	.105	2	.153	1	0	10	0	1	0	15
26			min	-365.33	3	.018	12	-.087	3	0	1	0	3	0	4
27		14	max	226.651	1	.069	2	.153	1	0	10	0	1	0	15
28			min	-365.242	3	-.003	3	-.087	3	0	1	0	3	0	4
29		15	max	226.767	1	.034	2	.153	1	0	10	0	1	0	15
30			min	-365.155	3	-.03	3	-.087	3	0	1	0	3	0	4
31		16	max	226.883	1	-.002	2	.153	1	0	10	0	1	0	15
32			min	-365.068	3	-.057	3	-.087	3	0	1	0	3	0	4
33		17	max	227	1	-.02	15	.153	1	0	10	0	1	0	15
34			min	-364.981	3	-.086	4	-.087	3	0	1	0	3	0	4
35		18	max	227.116	1	-.031	15	.153	1	0	10	0	1	0	15
36			min	-364.893	3	-.132	4	-.087	3	0	1	0	3	0	4
37		19	max	227.233	1	-.041	15	.153	1	0	10	0	1	0	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
38			min	-364.806	3	-.178	4	-.087	3	0	1	0	3	0	4
39	M3	1	max	139.194	2	1.779	4	-.002	10	0	10	0	1	0	4
40			min	-131.821	3	.418	15	-.175	1	0	1	0	10	0	15
41		2	max	139.126	2	1.602	4	-.002	10	0	10	0	1	0	2
42			min	-131.872	3	.377	15	-.175	1	0	1	0	10	0	12
43		3	max	139.057	2	1.425	4	-.002	10	0	10	0	1	0	2
44			min	-131.924	3	.335	15	-.175	1	0	1	0	10	0	3
45		4	max	138.989	2	1.247	4	-.002	10	0	10	0	1	0	15
46			min	-131.975	3	.293	15	-.175	1	0	1	0	10	0	4
47		5	max	138.92	2	1.07	4	-.002	10	0	10	0	1	0	15
48			min	-132.026	3	.252	15	-.175	1	0	1	0	10	0	4
49		6	max	138.851	2	.893	4	-.002	10	0	10	0	1	0	15
50			min	-132.078	3	.21	15	-.175	1	0	1	0	10	0	4
51		7	max	138.783	2	.716	4	-.002	10	0	10	0	1	0	15
52			min	-132.129	3	.169	15	-.175	1	0	1	0	10	0	4
53		8	max	138.714	2	.539	4	-.002	10	0	10	0	1	0	15
54			min	-132.181	3	.127	15	-.175	1	0	1	0	10	-.001	4
55		9	max	138.646	2	.361	4	-.002	10	0	10	0	1	0	15
56			min	-132.232	3	.085	15	-.175	1	0	1	0	10	-.001	4
57		10	max	138.577	2	.184	4	-.002	10	0	10	0	1	0	15
58			min	-132.284	3	.044	15	-.175	1	0	1	0	10	-.001	4
59		11	max	138.508	2	.029	2	-.002	10	0	10	0	1	0	15
60			min	-132.335	3	-.022	3	-.175	1	0	1	0	10	-.001	4
61		12	max	138.44	2	-.04	15	-.002	10	0	10	0	1	0	15
62			min	-132.387	3	-.17	4	-.175	1	0	1	0	10	-.001	4
63		13	max	138.371	2	-.081	15	-.002	10	0	10	0	1	0	15
64			min	-132.438	3	-.347	4	-.175	1	0	1	0	10	-.001	4
65		14	max	138.303	2	-.123	15	-.002	10	0	10	0	1	0	15
66			min	-132.49	3	-.525	4	-.175	1	0	1	0	10	-.001	4
67		15	max	138.234	2	-.165	15	-.002	10	0	10	0	9	0	15
68			min	-132.541	3	-.702	4	-.175	1	0	1	0	10	0	4
69		16	max	138.165	2	-.206	15	-.002	10	0	10	0	10	0	15
70			min	-132.592	3	-.879	4	-.175	1	0	1	0	1	0	4
71		17	max	138.097	2	-.248	15	-.002	10	0	10	0	10	0	15
72			min	-132.644	3	-1.056	4	-.175	1	0	1	0	1	0	4
73		18	max	138.028	2	-.29	15	-.002	10	0	10	0	10	0	15
74			min	-132.695	3	-1.233	4	-.175	1	0	1	0	1	0	4
75		19	max	137.96	2	-.331	15	-.002	10	0	10	0	10	0	1
76			min	-132.747	3	-1.411	4	-.175	1	0	1	0	1	0	1
77	M4	1	max	308.614	1	0	1	0	10	0	1	0	3	0	1
78			min	-33.296	3	0	1	-.568	1	0	1	0	2	0	1
79		2	max	308.678	1	0	1	0	10	0	1	0	15	0	1
80			min	-33.247	3	0	1	-.568	1	0	1	0	1	0	1
81		3	max	308.743	1	0	1	0	10	0	1	0	15	0	1
82			min	-33.199	3	0	1	-.568	1	0	1	0	1	0	1
83		4	max	308.808	1	0	1	0	10	0	1	0	15	0	1
84			min	-33.15	3	0	1	-.568	1	0	1	0	1	0	1
85		5	max	308.873	1	0	1	0	10	0	1	0	15	0	1
86			min	-33.102	3	0	1	-.568	1	0	1	0	1	0	1
87		6	max	308.937	1	0	1	0	10	0	1	0	10	0	1
88			min	-33.053	3	0	1	-.568	1	0	1	0	1	0	1
89		7	max	309.002	1	0	1	0	10	0	1	0	10	0	1
90			min	-33.005	3	0	1	-.568	1	0	1	0	1	0	1
91		8	max	309.067	1	0	1	0	10	0	1	0	10	0	1
92			min	-32.956	3	0	1	-.568	1	0	1	0	1	0	1
93		9	max	309.131	1	0	1	0	10	0	1	0	10	0	1
94			min	-32.908	3	0	1	-.568	1	0	1	0	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
95		10	max	309.196	1	0	1	0	10	0	1	0	10	0	1
96			min	-32.859	3	0	1	-.568	1	0	1	0	1	0	1
97		11	max	309.261	1	0	1	0	10	0	1	0	10	0	1
98			min	-32.811	3	0	1	-.568	1	0	1	0	1	0	1
99		12	max	309.326	1	0	1	0	10	0	1	0	10	0	1
100			min	-32.762	3	0	1	-.568	1	0	1	0	1	0	1
101		13	max	309.39	1	0	1	0	10	0	1	0	10	0	1
102			min	-32.714	3	0	1	-.568	1	0	1	0	1	0	1
103		14	max	309.455	1	0	1	0	10	0	1	0	10	0	1
104			min	-32.665	3	0	1	-.568	1	0	1	0	1	0	1
105		15	max	309.52	1	0	1	0	10	0	1	0	10	0	1
106			min	-32.617	3	0	1	-.568	1	0	1	0	1	0	1
107		16	max	309.584	1	0	1	0	10	0	1	0	10	0	1
108			min	-32.568	3	0	1	-.568	1	0	1	0	1	0	1
109		17	max	309.649	1	0	1	0	10	0	1	0	10	0	1
110			min	-32.52	3	0	1	-.568	1	0	1	0	1	0	1
111		18	max	309.714	1	0	1	0	10	0	1	0	10	0	1
112			min	-32.471	3	0	1	-.568	1	0	1	0	1	0	1
113		19	max	309.778	1	0	1	0	10	0	1	0	10	0	1
114			min	-32.422	3	0	1	-.568	1	0	1	0	1	0	1
115	M6	1	max	709.746	1	.643	4	.036	9	0	3	0	3	0	1
116			min	-1135.021	3	.151	15	-.261	3	0	2	0	2	0	1
117		2	max	709.863	1	.597	4	.036	9	0	3	0	3	0	15
118			min	-1134.934	3	.141	15	-.261	3	0	2	0	2	0	4
119		3	max	709.979	1	.551	4	.036	9	0	3	0	3	0	15
120			min	-1134.846	3	.13	15	-.261	3	0	2	0	2	0	4
121		4	max	710.095	1	.506	4	.036	9	0	3	0	3	0	15
122			min	-1134.759	3	.119	15	-.261	3	0	2	0	2	0	4
123		5	max	710.212	1	.46	4	.036	9	0	3	0	3	0	15
124			min	-1134.672	3	.108	15	-.261	3	0	2	0	2	0	4
125		6	max	710.328	1	.417	2	.036	9	0	3	0	9	0	15
126			min	-1134.585	3	.098	15	-.261	3	0	2	0	3	0	4
127		7	max	710.445	1	.382	2	.036	9	0	3	0	9	0	15
128			min	-1134.497	3	.085	12	-.261	3	0	2	0	3	0	4
129		8	max	710.561	1	.346	2	.036	9	0	3	0	9	0	15
130			min	-1134.41	3	.067	12	-.261	3	0	2	0	3	0	4
131		9	max	710.677	1	.311	2	.036	9	0	3	0	9	0	15
132			min	-1134.323	3	.05	12	-.261	3	0	2	0	3	0	4
133		10	max	710.794	1	.275	2	.036	9	0	3	0	9	0	15
134			min	-1134.235	3	.032	12	-.261	3	0	2	0	3	0	4
135		11	max	710.91	1	.239	2	.036	9	0	3	0	9	0	15
136			min	-1134.148	3	.011	3	-.261	3	0	2	0	3	0	2
137		12	max	711.027	1	.204	2	.036	9	0	3	0	9	0	15
138			min	-1134.061	3	-.016	3	-.261	3	0	2	0	3	0	2
139		13	max	711.143	1	.168	2	.036	9	0	3	0	9	0	12
140			min	-1133.973	3	-.042	3	-.261	3	0	2	0	3	0	2
141		14	max	711.259	1	.133	2	.036	9	0	3	0	9	0	12
142			min	-1133.886	3	-.069	3	-.261	3	0	2	0	3	0	2
143		15	max	711.376	1	.097	2	.036	9	0	3	0	9	0	12
144			min	-1133.799	3	-.096	3	-.261	3	0	2	0	3	0	2
145		16	max	711.492	1	.062	2	.036	9	0	3	0	9	0	12
146			min	-1133.712	3	-.122	3	-.261	3	0	2	0	3	0	2
147		17	max	711.609	1	.026	2	.036	9	0	3	0	9	0	12
148			min	-1133.624	3	-.149	3	-.261	3	0	2	0	3	0	2
149		18	max	711.725	1	-.01	2	.036	9	0	3	0	9	0	12
150			min	-1133.537	3	-.176	3	-.261	3	0	2	0	3	0	2
151		19	max	711.841	1	-.042	15	.036	9	0	3	0	9	0	12

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
152			min	-1133.45	3	-.202	3	-.261	3	0	2	0	3	0	2
153	M7	1	max	467.999	2	1.78	4	.021	3	0	9	0	1	0	2
154			min	-371.993	3	.419	15	-.013	1	0	3	0	3	0	12
155		2	max	467.93	2	1.603	4	.021	3	0	9	0	1	0	2
156			min	-372.044	3	.377	15	-.013	1	0	3	0	3	0	3
157		3	max	467.862	2	1.426	4	.021	3	0	9	0	1	0	2
158			min	-372.095	3	.335	15	-.013	1	0	3	0	3	0	3
159		4	max	467.793	2	1.248	4	.021	3	0	9	0	1	0	2
160			min	-372.147	3	.294	15	-.013	1	0	3	0	3	0	3
161		5	max	467.724	2	1.071	4	.021	3	0	9	0	1	0	15
162			min	-372.198	3	.252	15	-.013	1	0	3	0	3	0	3
163		6	max	467.656	2	.894	4	.021	3	0	9	0	1	0	15
164			min	-372.25	3	.21	15	-.013	1	0	3	0	3	0	4
165		7	max	467.587	2	.717	4	.021	3	0	9	0	1	0	15
166			min	-372.301	3	.169	15	-.013	1	0	3	0	3	0	4
167		8	max	467.519	2	.54	4	.021	3	0	9	0	1	0	15
168			min	-372.353	3	.127	15	-.013	1	0	3	0	3	-.001	4
169		9	max	467.45	2	.362	4	.021	3	0	9	0	1	0	15
170			min	-372.404	3	.085	15	-.013	1	0	3	0	3	-.001	4
171		10	max	467.381	2	.217	2	.021	3	0	9	0	1	0	15
172			min	-372.456	3	.025	12	-.013	1	0	3	0	3	-.001	4
173		11	max	467.313	2	.079	2	.021	3	0	9	0	1	0	15
174			min	-372.507	3	-.073	3	-.013	1	0	3	0	3	-.001	4
175		12	max	467.244	2	-.04	15	.021	3	0	9	0	1	0	15
176			min	-372.559	3	-.177	3	-.013	1	0	3	0	3	-.001	4
177		13	max	467.176	2	-.081	15	.021	3	0	9	0	1	0	15
178			min	-372.61	3	-.346	4	-.013	1	0	3	0	3	-.001	4
179		14	max	467.107	2	-.123	15	.021	3	0	9	0	1	0	15
180			min	-372.661	3	-.524	4	-.013	1	0	3	0	3	-.001	4
181		15	max	467.038	2	-.164	15	.021	3	0	9	0	1	0	15
182			min	-372.713	3	-.701	4	-.013	1	0	3	0	3	0	4
183		16	max	466.97	2	-.206	15	.021	3	0	9	0	1	0	15
184			min	-372.764	3	-.878	4	-.013	1	0	3	0	3	0	4
185		17	max	466.901	2	-.248	15	.021	3	0	9	0	1	0	15
186			min	-372.816	3	-1.055	4	-.013	1	0	3	0	3	0	4
187		18	max	466.832	2	-.289	15	.021	3	0	9	0	1	0	15
188			min	-372.867	3	-1.232	4	-.013	1	0	3	0	3	0	4
189		19	max	466.764	2	-.331	15	.021	3	0	9	0	9	0	1
190			min	-372.919	3	-1.41	4	-.013	1	0	3	0	3	0	1
191	M8	1	max	879.063	1	0	1	.178	9	0	1	0	2	0	1
192			min	-142.117	3	0	1	-.575	3	0	1	0	3	0	1
193		2	max	879.128	1	0	1	.178	9	0	1	0	9	0	1
194			min	-142.068	3	0	1	-.575	3	0	1	0	3	0	1
195		3	max	879.192	1	0	1	.178	9	0	1	0	9	0	1
196			min	-142.02	3	0	1	-.575	3	0	1	0	3	0	1
197		4	max	879.257	1	0	1	.178	9	0	1	0	9	0	1
198			min	-141.971	3	0	1	-.575	3	0	1	0	3	0	1
199		5	max	879.322	1	0	1	.178	9	0	1	0	9	0	1
200			min	-141.923	3	0	1	-.575	3	0	1	0	3	0	1
201		6	max	879.386	1	0	1	.178	9	0	1	0	9	0	1
202			min	-141.874	3	0	1	-.575	3	0	1	0	3	0	1
203		7	max	879.451	1	0	1	.178	9	0	1	0	9	0	1
204			min	-141.826	3	0	1	-.575	3	0	1	0	3	0	1
205		8	max	879.516	1	0	1	.178	9	0	1	0	9	0	1
206			min	-141.777	3	0	1	-.575	3	0	1	0	3	0	1
207		9	max	879.58	1	0	1	.178	9	0	1	0	9	0	1
208			min	-141.729	3	0	1	-.575	3	0	1	0	3	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
209		10	max	879.645	1	0	1	.178	9	0	1	0	9	0	1
210			min	-141.68	3	0	1	-.575	3	0	1	0	3	0	1
211		11	max	879.71	1	0	1	.178	9	0	1	0	9	0	1
212			min	-141.632	3	0	1	-.575	3	0	1	0	3	0	1
213		12	max	879.775	1	0	1	.178	9	0	1	0	9	0	1
214			min	-141.583	3	0	1	-.575	3	0	1	0	3	0	1
215		13	max	879.839	1	0	1	.178	9	0	1	0	9	0	1
216			min	-141.534	3	0	1	-.575	3	0	1	0	3	0	1
217		14	max	879.904	1	0	1	.178	9	0	1	0	9	0	1
218			min	-141.486	3	0	1	-.575	3	0	1	0	3	0	1
219		15	max	879.969	1	0	1	.178	9	0	1	0	9	0	1
220			min	-141.437	3	0	1	-.575	3	0	1	0	3	0	1
221		16	max	880.033	1	0	1	.178	9	0	1	0	9	0	1
222			min	-141.389	3	0	1	-.575	3	0	1	0	3	0	1
223		17	max	880.098	1	0	1	.178	9	0	1	0	9	0	1
224			min	-141.34	3	0	1	-.575	3	0	1	0	3	0	1
225		18	max	880.163	1	0	1	.178	9	0	1	0	9	0	1
226			min	-141.292	3	0	1	-.575	3	0	1	0	3	0	1
227		19	max	880.228	1	0	1	.178	9	0	1	0	9	0	1
228			min	-141.243	3	0	1	-.575	3	0	1	0	3	0	1
229	M10	1	max	226.777	1	.644	4	-.003	15	0	1	0	1	0	1
230			min	-312.981	3	.152	15	-.109	1	0	3	0	3	0	1
231		2	max	226.893	1	.599	4	-.003	15	0	1	0	1	0	15
232			min	-312.894	3	.141	15	-.109	1	0	3	0	3	0	4
233		3	max	227.01	1	.553	4	-.003	15	0	1	0	1	0	15
234			min	-312.807	3	.13	15	-.109	1	0	3	0	3	0	4
235		4	max	227.126	1	.507	4	-.003	15	0	1	0	1	0	15
236			min	-312.719	3	.12	15	-.109	1	0	3	0	3	0	4
237		5	max	227.243	1	.462	4	-.003	15	0	1	0	1	0	15
238			min	-312.632	3	.109	15	-.109	1	0	3	0	3	0	4
239		6	max	227.359	1	.416	4	-.003	15	0	1	0	1	0	15
240			min	-312.545	3	.098	15	-.109	1	0	3	0	3	0	4
241		7	max	227.475	1	.37	4	-.003	15	0	1	0	9	0	15
242			min	-312.457	3	.087	15	-.109	1	0	3	0	3	0	4
243		8	max	227.592	1	.325	4	-.003	15	0	1	0	10	0	15
244			min	-312.37	3	.077	15	-.109	1	0	3	0	3	0	4
245		9	max	227.708	1	.279	4	-.003	15	0	1	0	10	0	15
246			min	-312.283	3	.066	15	-.109	1	0	3	0	3	0	4
247		10	max	227.825	1	.233	4	-.003	15	0	1	0	10	0	15
248			min	-312.195	3	.055	15	-.109	1	0	3	0	3	0	4
249		11	max	227.941	1	.188	4	-.003	15	0	1	0	10	0	15
250			min	-312.108	3	.044	15	-.109	1	0	3	0	3	0	4
251		12	max	228.057	1	.142	4	-.003	15	0	1	0	10	0	15
252			min	-312.021	3	.034	15	-.109	1	0	3	0	3	0	4
253		13	max	228.174	1	.105	2	-.003	15	0	1	0	10	0	15
254			min	-311.934	3	.023	15	-.109	1	0	3	0	3	0	4
255		14	max	228.29	1	.069	2	-.003	15	0	1	0	10	0	15
256			min	-311.846	3	.012	15	-.109	1	0	3	0	3	0	4
257		15	max	228.407	1	.034	2	-.003	15	0	1	0	10	0	15
258			min	-311.759	3	-.007	3	-.109	1	0	3	0	3	0	4
259		16	max	228.523	1	-.002	2	-.003	15	0	1	0	10	0	15
260			min	-311.672	3	-.041	4	-.109	1	0	3	0	3	0	4
261		17	max	228.639	1	-.02	15	-.003	15	0	1	0	10	0	15
262			min	-311.584	3	-.086	4	-.109	1	0	3	0	3	0	4
263		18	max	228.756	1	-.031	15	-.003	15	0	1	0	10	0	15
264			min	-311.497	3	-.132	4	-.109	1	0	3	0	3	0	4
265		19	max	228.872	1	-.041	15	-.003	15	0	1	0	10	0	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
266			min	-311.41	3	-.178	4	-.109	1	0	3	0	3	0	4
267	M11	1	max	138.766	2	1.779	4	.187	1	0	3	0	3	0	4
268			min	-132.544	3	.418	15	-.04	3	0	10	0	1	0	15
269		2	max	138.697	2	1.602	4	.187	1	0	3	0	3	0	2
270			min	-132.595	3	.377	15	-.04	3	0	10	0	1	0	12
271		3	max	138.628	2	1.425	4	.187	1	0	3	0	3	0	2
272			min	-132.647	3	.335	15	-.04	3	0	10	0	1	0	3
273		4	max	138.56	2	1.247	4	.187	1	0	3	0	3	0	15
274			min	-132.698	3	.293	15	-.04	3	0	10	0	1	0	3
275		5	max	138.491	2	1.07	4	.187	1	0	3	0	3	0	15
276			min	-132.75	3	.252	15	-.04	3	0	10	0	1	0	4
277		6	max	138.423	2	.893	4	.187	1	0	3	0	3	0	15
278			min	-132.801	3	.21	15	-.04	3	0	10	0	1	0	4
279		7	max	138.354	2	.716	4	.187	1	0	3	0	3	0	15
280			min	-132.852	3	.169	15	-.04	3	0	10	0	1	0	4
281		8	max	138.285	2	.539	4	.187	1	0	3	0	3	0	15
282			min	-132.904	3	.127	15	-.04	3	0	10	0	1	-.001	4
283		9	max	138.217	2	.361	4	.187	1	0	3	0	3	0	15
284			min	-132.955	3	.085	15	-.04	3	0	10	0	1	-.001	4
285		10	max	138.148	2	.184	4	.187	1	0	3	0	3	0	15
286			min	-133.007	3	.044	15	-.04	3	0	10	0	1	-.001	4
287		11	max	138.08	2	.029	2	.187	1	0	3	0	3	0	15
288			min	-133.058	3	-.034	3	-.04	3	0	10	0	1	-.001	4
289		12	max	138.011	2	-.04	15	.187	1	0	3	0	3	0	15
290			min	-133.11	3	-.17	4	-.04	3	0	10	0	1	-.001	4
291		13	max	137.942	2	-.081	15	.187	1	0	3	0	3	0	15
292			min	-133.161	3	-.347	4	-.04	3	0	10	0	1	-.001	4
293		14	max	137.874	2	-.123	15	.187	1	0	3	0	3	0	15
294			min	-133.213	3	-.525	4	-.04	3	0	10	0	1	-.001	4
295		15	max	137.805	2	-.165	15	.187	1	0	3	0	3	0	15
296			min	-133.264	3	-.702	4	-.04	3	0	10	0	2	0	4
297		16	max	137.737	2	-.206	15	.187	1	0	3	0	3	0	15
298			min	-133.316	3	-.879	4	-.04	3	0	10	0	10	0	4
299		17	max	137.668	2	-.248	15	.187	1	0	3	0	3	0	15
300			min	-133.367	3	-1.056	4	-.04	3	0	10	0	10	0	4
301		18	max	137.599	2	-.29	15	.187	1	0	3	0	3	0	15
302			min	-133.418	3	-1.233	4	-.04	3	0	10	0	10	0	4
303		19	max	137.531	2	-.331	15	.187	1	0	3	0	3	0	1
304			min	-133.47	3	-1.411	4	-.04	3	0	10	0	10	0	1
305	M12	1	max	308.728	1	0	1	.913	1	0	1	0	2	0	1
306			min	-32.767	3	0	1	0	10	0	1	0	3	0	1
307		2	max	308.793	1	0	1	.913	1	0	1	0	1	0	1
308			min	-32.719	3	0	1	0	10	0	1	0	15	0	1
309		3	max	308.858	1	0	1	.913	1	0	1	0	1	0	1
310			min	-32.67	3	0	1	0	10	0	1	0	15	0	1
311		4	max	308.923	1	0	1	.913	1	0	1	0	1	0	1
312			min	-32.622	3	0	1	0	10	0	1	0	10	0	1
313		5	max	308.987	1	0	1	.913	1	0	1	0	1	0	1
314			min	-32.573	3	0	1	0	10	0	1	0	10	0	1
315		6	max	309.052	1	0	1	.913	1	0	1	0	1	0	1
316			min	-32.524	3	0	1	0	10	0	1	0	10	0	1
317		7	max	309.117	1	0	1	.913	1	0	1	0	1	0	1
318			min	-32.476	3	0	1	0	10	0	1	0	10	0	1
319		8	max	309.181	1	0	1	.913	1	0	1	0	1	0	1
320			min	-32.427	3	0	1	0	10	0	1	0	10	0	1
321		9	max	309.246	1	0	1	.913	1	0	1	0	1	0	1
322			min	-32.379	3	0	1	0	10	0	1	0	10	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
323		10	max	309.311	1	0	1	.913	1	0	1	0	1	0	1
324			min	-32.33	3	0	1	0	10	0	1	0	10	0	1
325		11	max	309.376	1	0	1	.913	1	0	1	0	1	0	1
326			min	-32.282	3	0	1	0	10	0	1	0	10	0	1
327		12	max	309.44	1	0	1	.913	1	0	1	0	1	0	1
328			min	-32.233	3	0	1	0	10	0	1	0	10	0	1
329		13	max	309.505	1	0	1	.913	1	0	1	0	1	0	1
330			min	-32.185	3	0	1	0	10	0	1	0	10	0	1
331		14	max	309.57	1	0	1	.913	1	0	1	.001	1	0	1
332			min	-32.136	3	0	1	0	10	0	1	0	10	0	1
333		15	max	309.634	1	0	1	.913	1	0	1	.001	1	0	1
334			min	-32.088	3	0	1	0	10	0	1	0	10	0	1
335		16	max	309.699	1	0	1	.913	1	0	1	.001	1	0	1
336			min	-32.039	3	0	1	0	10	0	1	0	10	0	1
337		17	max	309.764	1	0	1	.913	1	0	1	.001	1	0	1
338			min	-31.991	3	0	1	0	10	0	1	0	10	0	1
339		18	max	309.829	1	0	1	.913	1	0	1	.001	1	0	1
340			min	-31.942	3	0	1	0	10	0	1	0	10	0	1
341		19	max	309.893	1	0	1	.913	1	0	1	.001	1	0	1
342			min	-31.894	3	0	1	0	10	0	1	0	10	0	1
343	M1	1	max	76.594	1	345.479	3	-.189	10	0	2	.04	1	0	2
344			min	2.845	15	-232.724	2	-20.15	1	0	3	0	10	0	3
345		2	max	76.712	1	345.29	3	-.189	10	0	2	.035	1	.051	2
346			min	2.88	15	-232.977	2	-20.15	1	0	3	0	10	-.075	3
347		3	max	60.729	3	4.47	9	-.186	10	0	3	.031	1	.1	2
348			min	-8.842	10	-19.894	2	-20.063	1	0	1	0	10	-.149	3
349		4	max	60.818	3	4.259	9	-.186	10	0	3	.026	1	.105	2
350			min	-8.744	10	-20.147	2	-20.063	1	0	1	0	10	-.145	3
351		5	max	60.906	3	4.048	9	-.186	10	0	3	.022	1	.109	2
352			min	-8.646	10	-20.4	2	-20.063	1	0	1	0	10	-.141	3
353		6	max	60.995	3	3.837	9	-.186	10	0	3	.018	1	.114	2
354			min	-8.547	10	-20.653	2	-20.063	1	0	1	0	10	-.137	3
355		7	max	61.083	3	3.626	9	-.186	10	0	3	.013	1	.118	2
356			min	-8.449	10	-20.906	2	-20.063	1	0	1	0	10	-.133	3
357		8	max	61.172	3	3.415	9	-.186	10	0	3	.009	1	.123	2
358			min	-8.351	10	-21.159	2	-20.063	1	0	1	0	10	-.129	3
359		9	max	61.26	3	3.205	9	-.186	10	0	3	.004	1	.127	2
360			min	-8.252	10	-21.412	2	-20.063	1	0	1	0	10	-.125	3
361		10	max	61.349	3	2.994	9	-.186	10	0	3	.002	3	.132	2
362			min	-8.154	10	-21.665	2	-20.063	1	0	1	0	10	-.121	3
363		11	max	61.437	3	2.783	9	-.186	10	0	3	0	3	.137	2
364			min	-8.056	10	-21.918	2	-20.063	1	0	1	-.004	1	-.117	3
365		12	max	61.526	3	2.572	9	-.186	10	0	3	0	10	.142	2
366			min	-7.957	10	-22.171	2	-20.063	1	0	1	-.009	1	-.112	3
367		13	max	61.614	3	2.361	9	-.186	10	0	3	0	10	.146	2
368			min	-7.859	10	-22.425	2	-20.063	1	0	1	-.013	1	-.108	3
369		14	max	61.703	3	2.15	9	-.186	10	0	3	0	10	.151	2
370			min	-7.761	10	-22.678	2	-20.063	1	0	1	-.017	1	-.104	3
371		15	max	61.791	3	1.939	9	-.186	10	0	3	0	10	.156	2
372			min	-7.662	10	-22.931	2	-20.063	1	0	1	-.022	1	-.1	3
373		16	max	86.69	2	84.298	2	-.188	10	0	1	0	10	.16	2
374			min	-20.253	3	-124.414	3	-20.22	1	0	10	-.026	1	-.094	3
375		17	max	86.808	2	84.045	2	-.188	10	0	1	0	10	.142	2
376			min	-20.164	3	-124.604	3	-20.22	1	0	10	-.031	1	-.067	3
377		18	max	-2.879	15	328.871	2	-.187	10	0	3	0	10	.072	2
378			min	-76.697	1	-155.01	3	-20.805	1	0	2	-.035	1	-.034	3
379		19	max	-2.844	15	328.618	2	-.187	10	0	3	0	10	0	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
380			min	-76.579	1	-155.2	3	-20.805	1	0	2	-.04	1	0	3
381	M5	1	max	185.084	1	1113.127	3	0	2	0	9	.009	3	0	3
382			min	.045	3	-743.315	2	-66.769	3	0	3	0	10	0	2
383		2	max	185.202	1	1112.937	3	0	2	0	9	0	9	.161	2
384			min	.133	3	-743.568	2	-66.769	3	0	3	-.005	3	-.241	3
385		3	max	165.703	3	5.401	9	7.271	3	0	3	0	9	.319	2
386			min	-25.064	10	-69.435	2	-.206	9	0	1	-.019	3	-.477	3
387		4	max	165.791	3	5.191	9	7.271	3	0	3	0	9	.334	2
388			min	-24.965	10	-69.689	2	-.206	9	0	1	-.017	3	-.463	3
389		5	max	165.88	3	4.98	9	7.271	3	0	3	0	9	.35	2
390			min	-24.867	10	-69.942	2	-.206	9	0	1	-.016	3	-.449	3
391		6	max	165.968	3	4.769	9	7.271	3	0	3	0	9	.365	2
392			min	-24.769	10	-70.195	2	-.206	9	0	1	-.014	3	-.435	3
393		7	max	166.057	3	4.558	9	7.271	3	0	3	0	9	.38	2
394			min	-24.67	10	-70.448	2	-.206	9	0	1	-.013	3	-.421	3
395		8	max	166.145	3	4.347	9	7.271	3	0	3	0	9	.395	2
396			min	-24.572	10	-70.701	2	-.206	9	0	1	-.011	3	-.406	3
397		9	max	166.234	3	4.136	9	7.271	3	0	3	0	1	.411	2
398			min	-24.474	10	-70.954	2	-.206	9	0	1	-.009	3	-.392	3
399		10	max	166.322	3	3.925	9	7.271	3	0	3	0	2	.426	2
400			min	-24.375	10	-71.207	2	-.206	9	0	1	-.008	3	-.378	3
401		11	max	166.411	3	3.714	9	7.271	3	0	3	0	2	.442	2
402			min	-24.277	10	-71.46	2	-.206	9	0	1	-.006	3	-.364	3
403		12	max	166.499	3	3.503	9	7.271	3	0	3	0	2	.457	2
404			min	-24.179	10	-71.713	2	-.206	9	0	1	-.005	3	-.349	3
405		13	max	166.588	3	3.292	9	7.271	3	0	3	0	2	.473	2
406			min	-24.08	10	-71.966	2	-.206	9	0	1	-.003	3	-.335	3
407		14	max	166.676	3	3.082	9	7.271	3	0	3	0	2	.488	2
408			min	-23.982	10	-72.219	2	-.206	9	0	1	-.001	3	-.32	3
409		15	max	166.765	3	2.871	9	7.271	3	0	3	0	3	.504	2
410			min	-23.884	10	-72.472	2	-.206	9	0	1	0	9	-.306	3
411		16	max	277.785	2	294.666	2	7.238	3	0	3	.001	3	.517	2
412			min	-65.141	3	-358.678	3	-.205	9	0	2	0	9	-.289	3
413		17	max	277.903	2	294.413	2	7.238	3	0	3	.003	3	.453	2
414			min	-65.053	3	-358.868	3	-.205	9	0	2	0	9	-.211	3
415		18	max	-3.679	12	1051.979	2	6.667	3	0	3	.004	3	.227	2
416			min	-185.237	1	-488.406	3	-.045	1	0	9	0	9	-.106	3
417		19	max	-3.62	12	1051.726	2	6.667	3	0	3	.006	3	0	3
418			min	-185.119	1	-488.595	3	-.045	1	0	9	0	9	0	2
419	M9	1	max	76.457	1	345.41	3	70.848	3	0	3	0	10	0	2
420			min	2.836	15	-232.724	2	.189	10	0	2	-.039	1	0	3
421		2	max	76.575	1	345.22	3	70.848	3	0	3	0	10	.051	2
422			min	2.872	15	-232.977	2	.189	10	0	2	-.035	1	-.075	3
423		3	max	60.35	3	4.455	9	19.769	1	0	1	.014	3	.1	2
424			min	-8.499	10	-19.869	2	-2.539	3	0	10	-.03	1	-.148	3
425		4	max	60.438	3	4.244	9	19.769	1	0	1	.013	3	.105	2
426			min	-8.401	10	-20.122	2	-2.539	3	0	10	-.026	1	-.145	3
427		5	max	60.527	3	4.033	9	19.769	1	0	1	.013	3	.109	2
428			min	-8.302	10	-20.375	2	-2.539	3	0	10	-.022	1	-.141	3
429		6	max	60.615	3	3.822	9	19.769	1	0	1	.012	3	.114	2
430			min	-8.204	10	-20.628	2	-2.539	3	0	10	-.017	1	-.137	3
431		7	max	60.704	3	3.611	9	19.769	1	0	1	.012	3	.118	2
432			min	-8.106	10	-20.881	2	-2.539	3	0	10	-.013	1	-.133	3
433		8	max	60.792	3	3.4	9	19.769	1	0	1	.011	3	.123	2
434			min	-8.007	10	-21.134	2	-2.539	3	0	10	-.009	1	-.129	3
435		9	max	60.881	3	3.189	9	19.769	1	0	1	.01	3	.127	2
436			min	-7.909	10	-21.387	2	-2.539	3	0	10	-.004	1	-.125	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
437		10	max	60.969	3	2.978	9	19.769	1	0	1	.01	3	.132	2
438			min	-7.811	10	-21.64	2	-2.539	3	0	10	0	1	-.121	3
439		11	max	61.058	3	2.768	9	19.769	1	0	1	.009	3	.137	2
440			min	-7.712	10	-21.893	2	-2.539	3	0	10	0	10	-.117	3
441		12	max	61.146	3	2.557	9	19.769	1	0	1	.009	3	.141	2
442			min	-7.614	10	-22.146	2	-2.539	3	0	10	0	10	-.112	3
443		13	max	61.235	3	2.346	9	19.769	1	0	1	.013	1	.146	2
444			min	-7.516	10	-22.399	2	-2.539	3	0	10	0	10	-.108	3
445		14	max	61.323	3	2.135	9	19.769	1	0	1	.017	1	.151	2
446			min	-7.417	10	-22.652	2	-2.539	3	0	10	0	10	-.104	3
447		15	max	61.412	3	1.924	9	19.769	1	0	1	.021	1	.156	2
448			min	-7.319	10	-22.905	2	-2.539	3	0	10	0	10	-.1	3
449		16	max	86.835	2	83.989	2	19.937	1	0	10	.026	1	.16	2
450			min	-21.074	3	-124.886	3	-2.57	3	0	3	0	10	-.094	3
451		17	max	86.953	2	83.736	2	19.937	1	0	10	.03	1	.142	2
452			min	-20.986	3	-125.076	3	-2.57	3	0	3	0	10	-.067	3
453		18	max	-2.871	15	328.871	2	20.852	1	0	2	.035	1	.072	2
454			min	-76.555	1	-155.002	3	-2.138	3	0	3	0	10	-.034	3
455		19	max	-2.835	15	328.618	2	20.852	1	0	2	.039	1	0	2
456			min	-76.437	1	-155.192	3	-2.138	3	0	3	0	10	0	3
457	M13	1	max	70.843	3	232.638	2	-2.836	15	0	2	.039	1	0	2
458			min	.189	10	-345.449	3	-76.452	1	0	3	0	10	0	3
459		2	max	70.843	3	165.54	2	-2.154	15	0	2	.012	3	.139	3
460			min	.189	10	-245.229	3	-57.667	1	0	3	-.002	10	-.094	2
461		3	max	70.843	3	98.442	2	-1.472	15	0	2	.009	3	.232	3
462			min	.189	10	-145.01	3	-38.881	1	0	3	-.015	1	-.156	2
463		4	max	70.843	3	31.345	2	-.186	10	0	2	.006	3	.276	3
464			min	.189	10	-44.791	3	-20.096	1	0	3	-.029	1	-.187	2
465		5	max	70.843	3	55.429	3	2.144	2	0	2	.004	3	.274	3
466			min	.189	10	-35.753	2	-4.593	3	0	3	-.034	1	-.186	2
467		6	max	70.843	3	155.648	3	17.475	1	0	2	.002	3	.224	3
468			min	.189	10	-102.851	2	-3.6	3	0	3	-.03	1	-.153	2
469		7	max	70.843	3	255.867	3	36.26	1	0	2	0	3	.127	3
470			min	.189	10	-169.949	2	-2.607	3	0	3	-.018	1	-.089	2
471		8	max	70.843	3	356.087	3	55.045	1	0	2	.005	2	.009	1
472			min	.189	10	-237.047	2	-1.614	3	0	3	0	3	-.018	3
473		9	max	70.843	3	456.306	3	73.831	1	0	2	.034	1	.135	2
474			min	.189	10	-304.144	2	-.621	3	0	3	-.001	3	-.209	3
475		10	max	70.843	3	556.526	3	92.616	1	0	2	.074	1	.295	2
476			min	.189	10	-371.242	2	.372	3	0	3	-.011	3	-.449	3
477		11	max	20.187	1	304.144	2	1.341	3	0	3	.034	1	.135	2
478			min	.189	10	-456.306	3	-73.693	1	0	2	-.01	3	-.209	3
479		12	max	20.187	1	237.047	2	2.334	3	0	3	.005	2	.009	1
480			min	.189	10	-356.087	3	-54.908	1	0	2	-.009	3	-.018	3
481		13	max	20.187	1	169.949	2	3.327	3	0	3	0	10	.127	3
482			min	.189	10	-255.867	3	-36.123	1	0	2	-.018	1	-.089	2
483		14	max	20.187	1	102.851	2	4.32	3	0	3	-.001	15	.224	3
484			min	.189	10	-155.648	3	-17.337	1	0	2	-.03	1	-.153	2
485		15	max	20.187	1	35.753	2	5.313	3	0	3	-.001	15	.274	3
486			min	.189	10	-55.429	3	-2.144	2	0	2	-.034	1	-.186	2
487		16	max	20.187	1	44.791	3	20.233	1	0	3	0	12	.276	3
488			min	.189	10	-31.345	2	.186	10	0	2	-.029	1	-.187	2
489		17	max	20.187	1	145.01	3	39.019	1	0	3	.002	3	.232	3
490			min	.189	10	-98.442	2	1.48	15	0	2	-.015	1	-.156	2
491		18	max	20.187	1	245.229	3	57.804	1	0	3	.008	1	.139	3
492			min	.189	10	-165.54	2	2.163	15	0	2	-.002	10	-.094	2
493		19	max	20.187	1	345.449	3	76.589	1	0	3	.04	1	0	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
494			min	.189	10	-232.638	2	2.845	15	0	2	0	10	0	3
495	M16	1	max	2.14	3	328.723	2	-2.835	15	0	3	.039	1	0	2
496			min	-20.815	1	-155.214	3	-76.442	1	0	2	0	10	0	3
497		2	max	2.14	3	233.712	2	-2.153	15	0	3	.008	1	.063	3
498			min	-20.815	1	-110.821	3	-57.657	1	0	2	-.002	10	-.133	2
499		3	max	2.14	3	138.701	2	-1.471	15	0	3	0	3	.105	3
500			min	-20.815	1	-66.428	3	-38.871	1	0	2	-.015	1	-.221	2
501		4	max	2.14	3	43.69	2	-.191	10	0	3	-.001	15	.126	3
502			min	-20.815	1	-22.035	3	-20.086	1	0	2	-.029	1	-.264	2
503		5	max	2.14	3	22.357	3	2.134	2	0	3	-.001	15	.125	3
504			min	-20.815	1	-51.321	2	-3.002	3	0	2	-.034	1	-.262	2
505		6	max	2.14	3	66.75	3	17.485	1	0	3	-.001	15	.104	3
506			min	-20.815	1	-146.331	2	-2.009	3	0	2	-.03	1	-.215	2
507		7	max	2.14	3	111.143	3	36.27	1	0	3	0	10	.062	3
508			min	-20.815	1	-241.342	2	-1.016	3	0	2	-.018	1	-.124	2
509		8	max	2.14	3	155.536	3	55.055	1	0	3	.005	2	.013	2
510			min	-20.815	1	-336.353	2	-.023	3	0	2	-.006	3	0	3
511		9	max	2.14	3	199.928	3	73.841	1	0	3	.034	1	.194	2
512			min	-20.815	1	-431.364	2	.836	12	0	2	-.006	3	-.084	3
513		10	max	-.187	10	-8.113	15	92.626	1	0	15	.074	1	.42	2
514			min	-20.815	1	-526.375	2	-3.009	3	0	2	-.005	3	-.189	3
515		11	max	-.187	10	431.364	2	-1.46	12	0	2	.034	1	.194	2
516			min	-20.769	1	-199.928	3	-73.698	1	0	3	0	3	-.084	3
517		12	max	-.187	10	336.353	2	-.799	12	0	2	.005	2	.013	2
518			min	-20.769	1	-155.536	3	-54.913	1	0	3	-.001	3	0	3
519		13	max	-.187	10	241.342	2	-.03	3	0	2	0	10	.062	3
520			min	-20.769	1	-111.143	3	-36.128	1	0	3	-.018	1	-.124	2
521		14	max	-.187	10	146.331	2	.962	3	0	2	0	12	.104	3
522			min	-20.769	1	-66.75	3	-17.342	1	0	3	-.03	1	-.215	2
523		15	max	-.187	10	51.321	2	2.058	9	0	2	0	12	.125	3
524			min	-20.769	1	-22.357	3	-2.134	2	0	3	-.034	1	-.262	2
525		16	max	-.187	10	22.035	3	20.228	1	0	2	0	3	.126	3
526			min	-20.769	1	-43.69	2	.191	10	0	3	-.029	1	-.264	2
527		17	max	-.187	10	66.428	3	39.014	1	0	2	.002	3	.105	3
528			min	-20.769	1	-138.701	2	1.479	15	0	3	-.015	1	-.221	2
529		18	max	-.187	10	110.821	3	57.799	1	0	2	.008	1	.063	3
530			min	-20.769	1	-233.712	2	2.162	15	0	3	-.002	10	-.133	2
531		19	max	-.187	10	155.214	3	76.584	1	0	2	.04	1	0	2
532			min	-20.769	1	-328.723	2	2.844	15	0	3	0	10	0	3
533	M15	1	max	0	1	.879	3	.124	3	0	1	0	1	0	1
534			min	-90.83	3	0	1	0	1	0	3	0	3	0	1
535		2	max	0	1	.781	3	.124	3	0	1	0	1	0	1
536			min	-90.895	3	0	1	0	1	0	3	0	3	0	3
537		3	max	0	1	.684	3	.124	3	0	1	0	1	0	1
538			min	-90.961	3	0	1	0	1	0	3	0	3	0	3
539		4	max	0	1	.586	3	.124	3	0	1	0	1	0	1
540			min	-91.026	3	0	1	0	1	0	3	0	3	0	3
541		5	max	0	1	.488	3	.124	3	0	1	0	1	0	1
542			min	-91.091	3	0	1	0	1	0	3	0	3	0	3
543		6	max	0	1	.391	3	.124	3	0	1	0	1	0	1
544			min	-91.156	3	0	1	0	1	0	3	0	3	0	3
545		7	max	0	1	.293	3	.124	3	0	1	0	3	0	1
546			min	-91.221	3	0	1	0	1	0	3	0	1	-.001	3
547		8	max	0	1	.195	3	.124	3	0	1	0	3	0	1
548			min	-91.287	3	0	1	0	1	0	3	0	1	-.001	3
549		9	max	0	1	.098	3	.124	3	0	1	0	3	0	1
550			min	-91.352	3	0	1	0	1	0	3	0	1	-.001	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
551		10	max	0	1	0	1	.124	3	0	1	0	3	0	1
552			min	-91.417	3	0	1	0	1	0	3	0	1	-.001	3
553		11	max	0	1	0	1	.124	3	0	1	0	3	0	1
554			min	-91.482	3	-.098	3	0	1	0	3	0	1	-.001	3
555		12	max	0	1	0	1	.124	3	0	1	0	3	0	1
556			min	-91.547	3	-.195	3	0	1	0	3	0	1	-.001	3
557		13	max	0	1	0	1	.124	3	0	1	0	3	0	1
558			min	-91.613	3	-.293	3	0	1	0	3	0	1	-.001	3
559		14	max	0	1	0	1	.124	3	0	1	0	3	0	1
560			min	-91.678	3	-.391	3	0	1	0	3	0	1	0	3
561		15	max	0	1	0	1	.124	3	0	1	0	3	0	1
562			min	-91.743	3	-.488	3	0	1	0	3	0	1	0	3
563		16	max	0	1	0	1	.124	3	0	1	0	3	0	1
564			min	-91.808	3	-.586	3	0	1	0	3	0	1	0	3
565		17	max	0	1	0	1	.124	3	0	1	0	3	0	1
566			min	-91.873	3	-.684	3	0	1	0	3	0	1	0	3
567		18	max	0	1	0	1	.124	3	0	1	0	3	0	1
568			min	-91.938	3	-.781	3	0	1	0	3	0	1	0	3
569		19	max	0	1	0	1	.124	3	0	1	0	3	0	1
570			min	-92.004	3	-.879	3	0	1	0	3	0	1	0	1
571	M16A	1	max	0	2	1.504	4	.039	1	0	3	0	3	0	1
572			min	-90.658	3	0	2	-.05	3	0	1	0	1	0	1
573		2	max	0	2	1.337	4	.039	1	0	3	0	3	0	2
574			min	-90.593	3	0	2	-.05	3	0	1	0	1	0	4
575		3	max	0	2	1.17	4	.039	1	0	3	0	3	0	2
576			min	-90.528	3	0	2	-.05	3	0	1	0	1	0	4
577		4	max	0	2	1.003	4	.039	1	0	3	0	3	0	2
578			min	-90.463	3	0	2	-.05	3	0	1	0	1	-.001	4
579		5	max	0	2	.836	4	.039	1	0	3	0	3	0	2
580			min	-90.398	3	0	2	-.05	3	0	1	0	1	-.001	4
581		6	max	0	2	.669	4	.039	1	0	3	0	3	0	2
582			min	-90.332	3	0	2	-.05	3	0	1	0	1	-.002	4
583		7	max	0	2	.501	4	.039	1	0	3	0	3	0	2
584			min	-90.267	3	0	2	-.05	3	0	1	0	1	-.002	4
585		8	max	0	2	.334	4	.039	1	0	3	0	3	0	2
586			min	-90.202	3	0	2	-.05	3	0	1	0	1	-.002	4
587		9	max	0	2	.167	4	.039	1	0	3	0	3	0	2
588			min	-90.137	3	0	2	-.05	3	0	1	0	1	-.002	4
589		10	max	0	2	0	1	.039	1	0	3	0	3	0	2
590			min	-90.072	3	0	1	-.05	3	0	1	0	1	-.002	4
591		11	max	0	2	0	2	.039	1	0	3	0	3	0	2
592			min	-90.007	3	-.167	4	-.05	3	0	1	0	1	-.002	4
593		12	max	.044	13	0	2	.039	1	0	3	0	3	0	2
594			min	-89.941	3	-.334	4	-.05	3	0	1	0	1	-.002	4
595		13	max	.134	13	0	2	.039	1	0	3	0	1	0	2
596			min	-89.876	3	-.501	4	-.05	3	0	1	0	4	-.002	4
597		14	max	.224	13	0	2	.039	1	0	3	0	1	0	2
598			min	-89.811	3	-.669	4	-.05	3	0	1	0	3	-.002	4
599		15	max	.313	13	0	2	.039	1	0	3	0	1	0	2
600			min	-89.746	3	-.836	4	-.05	3	0	1	0	3	-.001	4
601		16	max	.403	13	0	2	.039	1	0	3	0	1	0	2
602			min	-89.681	3	-1.003	4	-.05	3	0	1	0	3	-.001	4
603		17	max	.493	13	0	2	.039	1	0	3	0	1	0	2
604			min	-89.615	3	-1.17	4	-.05	3	0	1	0	3	0	4
605		18	max	.589	4	0	2	.039	1	0	3	0	1	0	2
606			min	-89.55	3	-1.337	4	-.05	3	0	1	0	3	0	4
607		19	max	.701	4	0	2	.039	1	0	3	0	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
608			min	-89.485	3	-1.504	4	-.05	3	0	1	0	3	0	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M2	1	max	.002	1	.008	2	.003	1	-2.712e-6	10	NC	3	NC	1
2			min	-.003	3	-.008	3	-.002	3	-3.111e-4	1	4524.743	2	NC	1
3		2	max	.002	1	.007	2	.003	1	-2.59e-6	10	NC	3	NC	1
4			min	-.003	3	-.007	3	-.002	3	-2.975e-4	1	4929.118	2	NC	1
5		3	max	.002	1	.007	2	.003	1	-2.468e-6	10	NC	3	NC	1
6			min	-.003	3	-.007	3	-.002	3	-2.839e-4	1	5408.483	2	NC	1
7		4	max	.002	1	.006	2	.003	1	-2.346e-6	10	NC	1	NC	1
8			min	-.003	3	-.007	3	-.001	3	-2.703e-4	1	5980.745	2	NC	1
9		5	max	.002	1	.005	2	.002	1	-2.224e-6	10	NC	1	NC	1
10			min	-.003	3	-.006	3	-.001	3	-2.566e-4	1	6669.722	2	NC	1
11		6	max	.001	1	.005	2	.002	1	-2.102e-6	10	NC	1	NC	1
12			min	-.002	3	-.006	3	-.001	3	-2.43e-4	1	7507.614	2	NC	1
13		7	max	.001	1	.004	2	.002	1	-1.98e-6	10	NC	1	NC	1
14			min	-.002	3	-.006	3	0	3	-2.294e-4	1	8538.79	2	NC	1
15		8	max	.001	1	.004	2	.002	1	-1.858e-6	10	NC	1	NC	1
16			min	-.002	3	-.005	3	0	3	-2.158e-4	1	9825.769	2	NC	1
17		9	max	.001	1	.003	2	.001	1	-1.736e-6	10	NC	1	NC	1
18			min	-.002	3	-.005	3	0	3	-2.021e-4	1	NC	1	NC	1
19		10	max	.001	1	.003	2	.001	1	-1.614e-6	10	NC	1	NC	1
20			min	-.002	3	-.005	3	0	3	-1.885e-4	1	NC	1	NC	1
21		11	max	0	1	.002	2	.001	1	-1.492e-6	10	NC	1	NC	1
22			min	-.001	3	-.004	3	0	3	-1.749e-4	1	NC	1	NC	1
23		12	max	0	1	.002	2	0	1	-1.371e-6	10	NC	1	NC	1
24			min	-.001	3	-.004	3	0	3	-1.613e-4	1	NC	1	NC	1
25		13	max	0	1	.001	2	0	1	-1.249e-6	10	NC	1	NC	1
26			min	-.001	3	-.003	3	0	3	-1.477e-4	1	NC	1	NC	1
27		14	max	0	1	.001	2	0	1	-1.127e-6	10	NC	1	NC	1
28			min	0	3	-.003	3	0	3	-1.34e-4	1	NC	1	NC	1
29		15	max	0	1	0	2	0	1	-1.005e-6	10	NC	1	NC	1
30			min	0	3	-.002	3	0	3	-1.204e-4	1	NC	1	NC	1
31		16	max	0	1	0	2	0	1	-8.828e-7	10	NC	1	NC	1
32			min	0	3	-.002	3	0	3	-1.068e-4	1	NC	1	NC	1
33		17	max	0	1	0	2	0	1	-7.609e-7	10	NC	1	NC	1
34			min	0	3	-.001	3	0	3	-9.316e-5	1	NC	1	NC	1
35		18	max	0	1	0	2	0	1	-6.389e-7	10	NC	1	NC	1
36			min	0	3	0	3	0	3	-7.954e-5	1	NC	1	NC	1
37		19	max	0	1	0	1	0	1	-5.17e-7	10	NC	1	NC	1
38			min	0	1	0	1	0	1	-6.592e-5	1	NC	1	NC	1
39	M3	1	max	0	1	0	1	0	1	3.073e-5	1	NC	1	NC	1
40			min	0	1	0	1	0	1	2.409e-7	10	NC	1	NC	1
41		2	max	0	3	0	2	0	10	4.028e-5	1	NC	1	NC	1
42			min	0	2	0	3	0	1	3.582e-7	10	NC	1	NC	1
43		3	max	0	3	0	2	0	10	4.982e-5	1	NC	1	NC	1
44			min	0	2	-.002	3	0	1	4.754e-7	10	NC	1	NC	1
45		4	max	0	3	0	2	0	10	5.937e-5	1	NC	1	NC	1
46			min	0	2	-.002	3	0	1	5.927e-7	10	NC	1	NC	1
47		5	max	0	3	0	2	0	3	6.891e-5	1	NC	1	NC	1
48			min	0	2	-.003	3	0	1	7.1e-7	10	NC	1	NC	1
49		6	max	0	3	0	2	0	3	7.846e-5	1	NC	1	NC	1
50			min	0	2	-.004	3	0	9	8.272e-7	10	NC	1	NC	1
51		7	max	0	3	0	2	0	3	8.8e-5	1	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
52			min	0	2	-.005	3	0	9	9.445e-7	10	NC	1	NC	1
53		8	max	0	3	0	2	0	3	9.755e-5	1	NC	1	NC	1
54			min	0	2	-.005	3	0	9	1.062e-6	10	NC	1	NC	1
55		9	max	0	3	.001	2	0	3	1.071e-4	1	NC	1	NC	1
56			min	0	2	-.006	3	0	15	1.179e-6	10	NC	1	NC	1
57		10	max	0	3	.002	2	0	1	1.166e-4	1	NC	1	NC	1
58			min	0	2	-.006	3	0	10	1.296e-6	10	NC	1	NC	1
59		11	max	0	3	.002	2	0	1	1.262e-4	1	NC	1	NC	1
60			min	0	2	-.007	3	0	10	1.414e-6	10	NC	1	NC	1
61		12	max	0	3	.003	2	0	1	1.357e-4	1	NC	1	NC	1
62			min	0	2	-.007	3	0	10	1.531e-6	10	NC	1	NC	1
63		13	max	.001	3	.003	2	0	1	1.453e-4	1	NC	1	NC	1
64			min	-.001	2	-.007	3	0	10	1.648e-6	10	NC	1	NC	1
65		14	max	.001	3	.004	2	.001	1	1.548e-4	1	NC	1	NC	1
66			min	-.001	2	-.007	3	0	10	1.765e-6	10	NC	1	NC	1
67		15	max	.001	3	.005	2	.001	1	1.644e-4	1	NC	1	NC	1
68			min	-.001	2	-.008	3	0	10	1.883e-6	10	9674.547	2	NC	1
69		16	max	.001	3	.006	2	.002	1	1.739e-4	1	NC	1	NC	1
70			min	-.001	2	-.008	3	0	10	2.e-6	10	8156.831	2	NC	1
71		17	max	.001	3	.007	2	.002	1	1.835e-4	1	NC	1	NC	1
72			min	-.001	2	-.008	3	0	10	2.117e-6	10	6990.62	2	NC	1
73		18	max	.001	3	.008	2	.002	1	1.93e-4	1	NC	3	NC	1
74			min	-.001	2	-.008	3	0	10	2.234e-6	10	6083.569	2	NC	1
75		19	max	.002	3	.009	2	.002	1	2.026e-4	1	NC	3	NC	1
76			min	-.002	2	-.008	3	0	10	2.352e-6	10	5371.337	2	NC	1
77	M4	1	max	.001	1	.009	2	0	10	-2.164e-6	10	NC	1	NC	1
78			min	0	3	-.008	3	-.002	1	-2.478e-4	1	NC	1	NC	1
79		2	max	.001	1	.009	2	0	10	-2.164e-6	10	NC	1	NC	1
80			min	0	3	-.007	3	-.002	1	-2.478e-4	1	NC	1	NC	1
81		3	max	.001	1	.008	2	0	10	-2.164e-6	10	NC	1	NC	1
82			min	0	3	-.007	3	-.002	1	-2.478e-4	1	NC	1	NC	1
83		4	max	.001	1	.008	2	0	10	-2.164e-6	10	NC	1	NC	1
84			min	0	3	-.006	3	-.001	1	-2.478e-4	1	NC	1	NC	1
85		5	max	.001	1	.007	2	0	10	-2.164e-6	10	NC	1	NC	1
86			min	0	3	-.006	3	-.001	1	-2.478e-4	1	NC	1	NC	1
87		6	max	.001	1	.007	2	0	10	-2.164e-6	10	NC	1	NC	1
88			min	0	3	-.006	3	-.001	1	-2.478e-4	1	NC	1	NC	1
89		7	max	0	1	.006	2	0	10	-2.164e-6	10	NC	1	NC	1
90			min	0	3	-.005	3	0	1	-2.478e-4	1	NC	1	NC	1
91		8	max	0	1	.006	2	0	10	-2.164e-6	10	NC	1	NC	1
92			min	0	3	-.005	3	0	1	-2.478e-4	1	NC	1	NC	1
93		9	max	0	1	.005	2	0	10	-2.164e-6	10	NC	1	NC	1
94			min	0	3	-.004	3	0	1	-2.478e-4	1	NC	1	NC	1
95		10	max	0	1	.005	2	0	10	-2.164e-6	10	NC	1	NC	1
96			min	0	3	-.004	3	0	1	-2.478e-4	1	NC	1	NC	1
97		11	max	0	1	.004	2	0	10	-2.164e-6	10	NC	1	NC	1
98			min	0	3	-.003	3	0	1	-2.478e-4	1	NC	1	NC	1
99		12	max	0	1	.004	2	0	10	-2.164e-6	10	NC	1	NC	1
100			min	0	3	-.003	3	0	1	-2.478e-4	1	NC	1	NC	1
101		13	max	0	1	.003	2	0	10	-2.164e-6	10	NC	1	NC	1
102			min	0	3	-.003	3	0	1	-2.478e-4	1	NC	1	NC	1
103		14	max	0	1	.003	2	0	10	-2.164e-6	10	NC	1	NC	1
104			min	0	3	-.002	3	0	1	-2.478e-4	1	NC	1	NC	1
105		15	max	0	1	.002	2	0	10	-2.164e-6	10	NC	1	NC	1
106			min	0	3	-.002	3	0	1	-2.478e-4	1	NC	1	NC	1
107		16	max	0	1	.002	2	0	10	-2.164e-6	10	NC	1	NC	1
108			min	0	3	-.001	3	0	1	-2.478e-4	1	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
109		17	max	0	1	.001	2	0	10	-2.164e-6	10	NC	1	NC	1
110			min	0	3	0	3	0	1	-2.478e-4	1	NC	1	NC	1
111		18	max	0	1	0	2	0	10	-2.164e-6	10	NC	1	NC	1
112			min	0	3	0	3	0	1	-2.478e-4	1	NC	1	NC	1
113		19	max	0	1	0	1	0	1	-2.164e-6	10	NC	1	NC	1
114			min	0	1	0	1	0	1	-2.478e-4	1	NC	1	NC	1
115	M6	1	max	.006	1	.026	2	.001	9	4.076e-4	3	NC	3	NC	1
116			min	-.01	3	-.023	3	-.005	3	-8.236e-8	2	1380.738	2	6747.974	3
117		2	max	.006	1	.025	2	0	9	3.959e-4	3	NC	3	NC	1
118			min	-.01	3	-.022	3	-.005	3	-3.755e-7	11	1476.759	2	7189.562	3
119		3	max	.006	1	.023	2	0	9	3.843e-4	3	NC	3	NC	1
120			min	-.009	3	-.021	3	-.005	3	-1.262e-6	11	1586.71	2	7711.135	3
121		4	max	.005	1	.021	2	0	9	3.726e-4	3	NC	3	NC	1
122			min	-.008	3	-.02	3	-.004	3	-2.837e-6	1	1713.389	2	8330.186	3
123		5	max	.005	1	.02	2	0	9	3.61e-4	3	NC	3	NC	1
124			min	-.008	3	-.018	3	-.004	3	-4.828e-6	1	1860.405	2	9069.861	3
125		6	max	.005	1	.018	2	0	9	3.493e-4	3	NC	3	NC	1
126			min	-.007	3	-.017	3	-.004	3	-6.819e-6	1	2032.481	2	9961.257	3
127		7	max	.004	1	.016	2	0	9	3.377e-4	3	NC	3	NC	1
128			min	-.007	3	-.016	3	-.003	3	-8.811e-6	1	2235.923	2	NC	1
129		8	max	.004	1	.015	2	0	9	3.26e-4	3	NC	3	NC	1
130			min	-.006	3	-.015	3	-.003	3	-1.08e-5	1	2479.337	2	NC	1
131		9	max	.004	1	.013	2	0	9	3.144e-4	3	NC	3	NC	1
132			min	-.006	3	-.013	3	-.003	3	-1.279e-5	1	2774.779	2	NC	1
133		10	max	.003	1	.012	2	0	9	3.027e-4	3	NC	3	NC	1
134			min	-.005	3	-.012	3	-.002	3	-1.478e-5	1	3139.666	2	NC	1
135		11	max	.003	1	.01	2	0	9	2.911e-4	3	NC	3	NC	1
136			min	-.005	3	-.011	3	-.002	3	-1.678e-5	1	3600.128	2	NC	1
137		12	max	.002	1	.009	2	0	1	2.795e-4	3	NC	3	NC	1
138			min	-.004	3	-.01	3	-.002	3	-1.877e-5	1	4197.227	2	NC	1
139		13	max	.002	1	.007	2	0	1	2.678e-4	3	NC	3	NC	1
140			min	-.003	3	-.008	3	-.001	3	-2.076e-5	1	4999.401	2	NC	1
141		14	max	.002	1	.006	2	0	1	2.562e-4	3	NC	3	NC	1
142			min	-.003	3	-.007	3	-.001	3	-2.275e-5	1	6129.825	2	NC	1
143		15	max	.001	1	.005	2	0	1	2.445e-4	3	NC	1	NC	1
144			min	-.002	3	-.006	3	0	3	-2.474e-5	1	7834.837	2	NC	1
145		16	max	.001	1	.003	2	0	1	2.329e-4	3	NC	1	NC	1
146			min	-.002	3	-.004	3	0	3	-2.673e-5	1	NC	1	NC	1
147		17	max	0	1	.002	2	0	1	2.212e-4	3	NC	1	NC	1
148			min	-.001	3	-.003	3	0	3	-2.872e-5	1	NC	1	NC	1
149		18	max	0	1	.001	2	0	1	2.096e-4	3	NC	1	NC	1
150			min	0	3	-.001	3	0	3	-3.071e-5	1	NC	1	NC	1
151		19	max	0	1	0	1	0	1	1.979e-4	3	NC	1	NC	1
152			min	0	1	0	1	0	1	-3.271e-5	1	NC	1	NC	1
153	M7	1	max	0	1	0	1	0	1	1.516e-5	1	NC	1	NC	1
154			min	0	1	0	1	0	1	-9.165e-5	3	NC	1	NC	1
155		2	max	0	3	.001	2	0	3	1.375e-5	1	NC	1	NC	1
156			min	0	2	-.002	3	0	1	-6.944e-5	3	NC	1	NC	1
157		3	max	0	3	.003	2	0	3	1.234e-5	1	NC	1	NC	1
158			min	0	2	-.004	3	0	1	-4.724e-5	3	NC	1	NC	1
159		4	max	0	3	.004	2	.001	3	1.094e-5	1	NC	1	NC	1
160			min	0	2	-.005	3	0	1	-2.503e-5	3	NC	1	NC	1
161		5	max	0	3	.005	2	.002	3	9.526e-6	1	NC	1	NC	1
162			min	-.001	2	-.007	3	0	1	-2.824e-6	3	9270.493	2	NC	1
163		6	max	.001	3	.006	2	.002	3	1.938e-5	3	NC	1	NC	1
164			min	-.001	2	-.009	3	0	1	0	2	7431.354	2	NC	1
165		7	max	.001	3	.007	2	.002	3	4.159e-5	3	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
166			min	-.002	2	-.01	3	0	1	0	5	6171.395	2	NC	1
167		8	max	.002	3	.009	2	.002	3	6.38e-5	3	NC	3	NC	1
168			min	-.002	2	-.012	3	0	1	-3.023e-7	4	5246.116	2	NC	1
169		9	max	.002	3	.01	2	.003	3	8.6e-5	3	NC	3	NC	1
170			min	-.002	2	-.013	3	0	1	-1.669e-6	9	4533.765	2	NC	1
171		10	max	.002	3	.012	2	.003	3	1.082e-4	3	NC	3	NC	1
172			min	-.003	2	-.015	3	0	1	-3.156e-6	9	3966.879	2	NC	1
173		11	max	.002	3	.013	2	.003	3	1.304e-4	3	NC	3	NC	1
174			min	-.003	2	-.016	3	0	1	-4.642e-6	9	3504.933	2	NC	1
175		12	max	.003	3	.015	2	.003	3	1.526e-4	3	NC	3	NC	1
176			min	-.003	2	-.017	3	0	1	-6.129e-6	9	3121.964	2	NC	1
177		13	max	.003	3	.016	2	.003	3	1.748e-4	3	NC	3	NC	1
178			min	-.004	2	-.018	3	0	1	-7.615e-6	9	2800.42	2	NC	1
179		14	max	.003	3	.018	2	.003	3	1.97e-4	3	NC	3	NC	1
180			min	-.004	2	-.019	3	0	1	-9.102e-6	9	2527.895	2	NC	1
181		15	max	.003	3	.02	2	.003	3	2.192e-4	3	NC	3	NC	1
182			min	-.004	2	-.02	3	0	1	-1.059e-5	9	2295.28	2	NC	1
183		16	max	.004	3	.022	2	.003	3	2.414e-4	3	NC	3	NC	1
184			min	-.004	2	-.021	3	0	1	-1.208e-5	9	2095.685	2	NC	1
185		17	max	.004	3	.024	2	.003	3	2.637e-4	3	NC	3	NC	1
186			min	-.005	2	-.022	3	0	9	-1.356e-5	9	1923.765	2	NC	1
187		18	max	.004	3	.026	2	.003	3	2.859e-4	3	NC	3	NC	1
188			min	-.005	2	-.023	3	0	9	-1.505e-5	9	1775.297	2	NC	1
189		19	max	.004	3	.028	2	.003	3	3.081e-4	3	NC	3	NC	1
190			min	-.005	2	-.024	3	0	9	-1.654e-5	9	1646.898	2	NC	1
191	M8	1	max	.004	1	.03	2	0	9	-9.356e-8	10	NC	1	NC	1
192			min	0	3	-.024	3	-.002	3	-2.313e-4	3	NC	1	NC	1
193		2	max	.004	1	.028	2	0	9	-9.356e-8	10	NC	1	NC	1
194			min	0	3	-.022	3	-.002	3	-2.313e-4	3	NC	1	NC	1
195		3	max	.004	1	.026	2	0	9	-9.356e-8	10	NC	1	NC	1
196			min	0	3	-.021	3	-.002	3	-2.313e-4	3	NC	1	NC	1
197		4	max	.003	1	.025	2	0	9	-9.356e-8	10	NC	1	NC	1
198			min	0	3	-.02	3	-.001	3	-2.313e-4	3	NC	1	NC	1
199		5	max	.003	1	.023	2	0	9	-9.356e-8	10	NC	1	NC	1
200			min	0	3	-.018	3	-.001	3	-2.313e-4	3	NC	1	NC	1
201		6	max	.003	1	.021	2	0	9	-9.356e-8	10	NC	1	NC	1
202			min	0	3	-.017	3	-.001	3	-2.313e-4	3	NC	1	NC	1
203		7	max	.003	1	.02	2	0	9	-9.356e-8	10	NC	1	NC	1
204			min	0	3	-.016	3	0	3	-2.313e-4	3	NC	1	NC	1
205		8	max	.003	1	.018	2	0	9	-9.356e-8	10	NC	1	NC	1
206			min	0	3	-.014	3	0	3	-2.313e-4	3	NC	1	NC	1
207		9	max	.002	1	.017	2	0	9	-9.356e-8	10	NC	1	NC	1
208			min	0	3	-.013	3	0	3	-2.313e-4	3	NC	1	NC	1
209		10	max	.002	1	.015	2	0	9	-9.356e-8	10	NC	1	NC	1
210			min	0	3	-.012	3	0	3	-2.313e-4	3	NC	1	NC	1
211		11	max	.002	1	.013	2	0	9	-9.356e-8	10	NC	1	NC	1
212			min	0	3	-.01	3	0	3	-2.313e-4	3	NC	1	NC	1
213		12	max	.002	1	.012	2	0	9	-9.356e-8	10	NC	1	NC	1
214			min	0	3	-.009	3	0	3	-2.313e-4	3	NC	1	NC	1
215		13	max	.001	1	.01	2	0	9	-9.356e-8	10	NC	1	NC	1
216			min	0	3	-.008	3	0	3	-2.313e-4	3	NC	1	NC	1
217		14	max	.001	1	.008	2	0	9	-9.356e-8	10	NC	1	NC	1
218			min	0	3	-.007	3	0	3	-2.313e-4	3	NC	1	NC	1
219		15	max	0	1	.007	2	0	9	-9.356e-8	10	NC	1	NC	1
220			min	0	3	-.005	3	0	3	-2.313e-4	3	NC	1	NC	1
221		16	max	0	1	.005	2	0	9	-9.356e-8	10	NC	1	NC	1
222			min	0	3	-.004	3	0	3	-2.313e-4	3	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
223		17	max	0	1	.003	2	0	9	-9.356e-8	10	NC	1	NC	1
224			min	0	3	-.003	3	0	3	-2.313e-4	3	NC	1	NC	1
225		18	max	0	1	.002	2	0	9	-9.356e-8	10	NC	1	NC	1
226			min	0	3	-.001	3	0	3	-2.313e-4	3	NC	1	NC	1
227		19	max	0	1	0	1	0	1	-9.356e-8	10	NC	1	NC	1
228			min	0	1	0	1	0	1	-2.313e-4	3	NC	1	NC	1
229	M10	1	max	.002	1	.008	2	0	3	3.139e-4	1	NC	3	NC	1
230			min	-.003	3	-.008	3	-.001	1	-4.953e-4	3	4530.212	2	NC	1
231		2	max	.002	1	.007	2	0	3	2.985e-4	1	NC	3	NC	1
232			min	-.003	3	-.007	3	-.001	1	-4.793e-4	3	4935.224	2	NC	1
233		3	max	.002	1	.007	2	0	3	2.83e-4	1	NC	3	NC	1
234			min	-.002	3	-.007	3	-.001	1	-4.633e-4	3	5415.372	2	NC	1
235		4	max	.002	1	.006	2	0	3	2.675e-4	1	NC	1	NC	1
236			min	-.002	3	-.007	3	-.001	1	-4.473e-4	3	5988.605	2	NC	1
237		5	max	.002	1	.005	2	0	3	2.521e-4	1	NC	1	NC	1
238			min	-.002	3	-.007	3	-.001	1	-4.313e-4	3	6678.798	2	NC	1
239		6	max	.001	1	.005	2	0	3	2.366e-4	1	NC	1	NC	1
240			min	-.002	3	-.006	3	-.001	1	-4.153e-4	3	7518.231	2	NC	1
241		7	max	.001	1	.004	2	0	3	2.212e-4	1	NC	1	NC	1
242			min	-.002	3	-.006	3	0	1	-3.993e-4	3	8551.39	2	NC	1
243		8	max	.001	1	.004	2	0	3	2.057e-4	1	NC	1	NC	1
244			min	-.002	3	-.006	3	0	1	-3.833e-4	3	9840.963	2	NC	1
245		9	max	.001	1	.003	2	0	3	1.903e-4	1	NC	1	NC	1
246			min	-.002	3	-.005	3	0	1	-3.673e-4	3	NC	1	NC	1
247		10	max	.001	1	.003	2	0	3	1.748e-4	1	NC	1	NC	1
248			min	-.001	3	-.005	3	0	1	-3.513e-4	3	NC	1	NC	1
249		11	max	0	1	.002	2	0	3	1.594e-4	1	NC	1	NC	1
250			min	-.001	3	-.004	3	0	1	-3.353e-4	3	NC	1	NC	1
251		12	max	0	1	.002	2	0	3	1.439e-4	1	NC	1	NC	1
252			min	-.001	3	-.004	3	0	1	-3.193e-4	3	NC	1	NC	1
253		13	max	0	1	.001	2	0	3	1.285e-4	1	NC	1	NC	1
254			min	0	3	-.003	3	0	1	-3.033e-4	3	NC	1	NC	1
255		14	max	0	1	.001	2	0	3	1.13e-4	1	NC	1	NC	1
256			min	0	3	-.003	3	0	1	-2.873e-4	3	NC	1	NC	1
257		15	max	0	1	0	2	0	3	9.756e-5	1	NC	1	NC	1
258			min	0	3	-.002	3	0	1	-2.713e-4	3	NC	1	NC	1
259		16	max	0	1	0	2	0	3	8.21e-5	1	NC	1	NC	1
260			min	0	3	-.002	3	0	1	-2.553e-4	3	NC	1	NC	1
261		17	max	0	1	0	2	0	3	6.665e-5	1	NC	1	NC	1
262			min	0	3	-.001	3	0	1	-2.393e-4	3	NC	1	NC	1
263		18	max	0	1	0	2	0	3	5.12e-5	1	NC	1	NC	1
264			min	0	3	0	3	0	1	-2.233e-4	3	NC	1	NC	1
265		19	max	0	1	0	1	0	1	3.574e-5	1	NC	1	NC	1
266			min	0	1	0	1	0	1	-2.073e-4	3	NC	1	NC	1
267	M11	1	max	0	1	0	1	0	1	9.662e-5	3	NC	1	NC	1
268			min	0	1	0	1	0	1	-1.686e-5	1	NC	1	NC	1
269		2	max	0	3	0	2	0	1	7.467e-5	3	NC	1	NC	1
270			min	0	2	0	3	0	3	-2.925e-5	1	NC	1	NC	1
271		3	max	0	3	0	2	0	1	5.272e-5	3	NC	1	NC	1
272			min	0	2	-.002	3	0	3	-4.164e-5	1	NC	1	NC	1
273		4	max	0	3	0	2	0	11	3.077e-5	3	NC	1	NC	1
274			min	0	2	-.002	3	-.001	3	-5.403e-5	1	NC	1	NC	1
275		5	max	0	3	0	2	0	2	8.819e-6	3	NC	1	NC	1
276			min	0	2	-.003	3	-.002	3	-6.643e-5	1	NC	1	NC	1
277		6	max	0	3	0	2	0	2	-7.827e-7	10	NC	1	NC	1
278			min	0	2	-.004	3	-.002	3	-7.882e-5	1	NC	1	NC	1
279		7	max	0	3	0	2	0	10	-8.912e-7	10	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
280			min	0	2	-.005	3	-.002	3	-9.121e-5	1	NC	1	NC	1
281		8	max	0	3	0	2	0	10	-9.998e-7	10	NC	1	NC	1
282			min	0	2	-.005	3	-.002	3	-1.036e-4	1	NC	1	NC	1
283		9	max	0	3	.001	2	0	10	-1.108e-6	10	NC	1	NC	1
284			min	0	2	-.006	3	-.003	3	-1.16e-4	1	NC	1	NC	1
285		10	max	0	3	.002	2	0	10	-1.217e-6	10	NC	1	NC	1
286			min	0	2	-.006	3	-.003	3	-1.284e-4	1	NC	1	NC	1
287		11	max	0	3	.002	2	0	10	-1.325e-6	10	NC	1	NC	1
288			min	0	2	-.007	3	-.003	3	-1.408e-4	1	NC	1	NC	1
289		12	max	0	3	.003	2	0	10	-1.434e-6	10	NC	1	NC	1
290			min	0	2	-.007	3	-.003	3	-1.532e-4	1	NC	1	NC	1
291		13	max	.001	3	.003	2	0	10	-1.542e-6	10	NC	1	NC	1
292			min	-.001	2	-.007	3	-.003	3	-1.668e-4	3	NC	1	NC	1
293		14	max	.001	3	.004	2	0	10	-1.651e-6	10	NC	1	NC	1
294			min	-.001	2	-.008	3	-.003	3	-1.887e-4	3	NC	1	NC	1
295		15	max	.001	3	.005	2	0	10	-1.76e-6	10	NC	1	NC	1
296			min	-.001	2	-.008	3	-.003	3	-2.107e-4	3	9688.504	2	NC	1
297		16	max	.001	3	.006	2	0	10	-1.868e-6	10	NC	1	NC	1
298			min	-.001	2	-.008	3	-.003	1	-2.326e-4	3	8167.362	2	NC	1
299		17	max	.001	3	.007	2	0	10	-1.977e-6	10	NC	1	NC	1
300			min	-.001	2	-.008	3	-.003	1	-2.546e-4	3	6998.799	2	NC	1
301		18	max	.001	3	.008	2	0	10	-2.085e-6	10	NC	3	NC	1
302			min	-.001	2	-.008	3	-.003	1	-2.765e-4	3	6090.098	2	NC	1
303		19	max	.002	3	.009	2	0	10	-2.194e-6	10	NC	3	NC	1
304			min	-.002	2	-.008	3	-.003	1	-2.985e-4	3	5376.688	2	NC	1
305	M12	1	max	.001	1	.009	2	.003	1	3.115e-4	3	NC	1	NC	2
306			min	0	3	-.008	3	0	10	1.977e-6	10	NC	1	6612.163	1
307		2	max	.001	1	.009	2	.003	1	3.115e-4	3	NC	1	NC	2
308			min	0	3	-.007	3	0	10	1.977e-6	10	NC	1	7211.767	1
309		3	max	.001	1	.008	2	.002	1	3.115e-4	3	NC	1	NC	2
310			min	0	3	-.007	3	0	10	1.977e-6	10	NC	1	7925.462	1
311		4	max	.001	1	.008	2	.002	1	3.115e-4	3	NC	1	NC	2
312			min	0	3	-.007	3	0	10	1.977e-6	10	NC	1	8783.329	1
313		5	max	.001	1	.007	2	.002	1	3.115e-4	3	NC	1	NC	2
314			min	0	3	-.006	3	0	10	1.977e-6	10	NC	1	9826.345	1
315		6	max	.001	1	.007	2	.002	1	3.115e-4	3	NC	1	NC	1
316			min	0	3	-.006	3	0	10	1.977e-6	10	NC	1	NC	1
317		7	max	0	1	.006	2	.002	1	3.115e-4	3	NC	1	NC	1
318			min	0	3	-.005	3	0	10	1.977e-6	10	NC	1	NC	1
319		8	max	0	1	.006	2	.001	1	3.115e-4	3	NC	1	NC	1
320			min	0	3	-.005	3	0	10	1.977e-6	10	NC	1	NC	1
321		9	max	0	1	.005	2	.001	1	3.115e-4	3	NC	1	NC	1
322			min	0	3	-.004	3	0	10	1.977e-6	10	NC	1	NC	1
323		10	max	0	1	.005	2	0	1	3.115e-4	3	NC	1	NC	1
324			min	0	3	-.004	3	0	10	1.977e-6	10	NC	1	NC	1
325		11	max	0	1	.004	2	0	1	3.115e-4	3	NC	1	NC	1
326			min	0	3	-.003	3	0	10	1.977e-6	10	NC	1	NC	1
327		12	max	0	1	.004	2	0	1	3.115e-4	3	NC	1	NC	1
328			min	0	3	-.003	3	0	10	1.977e-6	10	NC	1	NC	1
329		13	max	0	1	.003	2	0	1	3.115e-4	3	NC	1	NC	1
330			min	0	3	-.003	3	0	10	1.977e-6	10	NC	1	NC	1
331		14	max	0	1	.003	2	0	1	3.115e-4	3	NC	1	NC	1
332			min	0	3	-.002	3	0	10	1.977e-6	10	NC	1	NC	1
333		15	max	0	1	.002	2	0	1	3.115e-4	3	NC	1	NC	1
334			min	0	3	-.002	3	0	10	1.977e-6	10	NC	1	NC	1
335		16	max	0	1	.002	2	0	1	3.115e-4	3	NC	1	NC	1
336			min	0	3	-.001	3	0	10	1.977e-6	10	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
337		17	max	0	1	.001	2	0	1	3.115e-4	3	NC	1	NC	1
338			min	0	3	0	3	0	10	1.977e-6	10	NC	1	NC	1
339		18	max	0	1	0	2	0	1	3.115e-4	3	NC	1	NC	1
340			min	0	3	0	3	0	10	1.977e-6	10	NC	1	NC	1
341		19	max	0	1	0	1	0	1	3.115e-4	3	NC	1	NC	1
342			min	0	1	0	1	0	1	1.977e-6	10	NC	1	NC	1
343	M1	1	max	.007	3	.023	3	.003	3	6.681e-3	2	NC	1	NC	1
344			min	-.008	2	-.02	2	-.001	9	-9.542e-3	3	NC	1	NC	1
345		2	max	.007	3	.013	3	.002	3	3.293e-3	2	NC	4	NC	1
346			min	-.008	2	-.011	2	-.002	1	-4.699e-3	3	4835.977	3	NC	1
347		3	max	.007	3	.004	3	.002	3	5.459e-5	3	NC	4	NC	1
348			min	-.008	2	-.003	2	-.003	1	-1.625e-4	1	2508.32	3	NC	1
349		4	max	.007	3	.004	2	.001	3	5.47e-5	3	NC	4	NC	1
350			min	-.008	2	-.004	3	-.004	1	-1.352e-4	1	1792.041	3	NC	1
351		5	max	.007	3	.011	2	.001	3	5.48e-5	3	NC	4	NC	1
352			min	-.008	2	-.01	3	-.004	1	-1.079e-4	1	1451.421	3	NC	1
353		6	max	.007	3	.016	2	0	3	5.49e-5	3	NC	4	NC	1
354			min	-.008	2	-.015	3	-.004	1	-8.061e-5	1	1258.068	2	NC	1
355		7	max	.007	3	.02	2	0	3	5.501e-5	3	NC	4	NC	1
356			min	-.008	2	-.019	3	-.003	1	-5.331e-5	1	1121.846	2	NC	1
357		8	max	.007	3	.023	2	0	3	5.511e-5	3	NC	4	NC	1
358			min	-.008	2	-.022	3	-.003	1	-3.007e-5	9	1036.56	2	NC	1
359		9	max	.007	3	.025	2	0	3	5.521e-5	3	NC	5	NC	1
360			min	-.008	2	-.023	3	-.002	1	-1.023e-5	9	986.194	2	NC	1
361		10	max	.007	3	.026	2	0	3	5.532e-5	3	NC	5	NC	1
362			min	-.008	2	-.023	3	0	9	7.442e-7	15	963.121	2	NC	1
363		11	max	.007	3	.026	2	0	3	5.588e-5	1	NC	4	NC	1
364			min	-.008	2	-.023	3	0	9	1.212e-6	10	964.607	2	NC	1
365		12	max	.007	3	.024	2	0	1	8.318e-5	1	NC	4	NC	1
366			min	-.008	2	-.021	3	0	10	1.401e-6	10	991.796	2	NC	1
367		13	max	.007	3	.021	2	.002	1	1.105e-4	1	NC	4	NC	1
368			min	-.008	2	-.018	3	0	10	1.591e-6	10	1050.315	2	NC	1
369		14	max	.007	3	.017	2	.002	1	1.378e-4	1	NC	4	NC	1
370			min	-.008	2	-.014	3	0	10	1.78e-6	10	1153.119	2	NC	1
371		15	max	.007	3	.011	2	.002	1	1.651e-4	1	NC	4	NC	1
372			min	-.008	2	-.009	3	0	10	1.97e-6	10	1328.608	2	NC	1
373		16	max	.007	3	.004	2	.002	1	1.849e-4	1	NC	4	NC	1
374			min	-.008	2	-.003	3	0	10	2.117e-6	10	1646.138	2	NC	1
375		17	max	.007	3	.003	3	.002	1	5.452e-5	3	NC	4	NC	1
376			min	-.008	2	-.005	2	0	10	5.576e-7	15	2326.663	2	NC	1
377		18	max	.007	3	.011	3	0	1	4.622e-3	2	NC	4	NC	1
378			min	-.008	2	-.015	2	0	10	-2.299e-3	3	4505.275	2	NC	1
379		19	max	.007	3	.018	3	0	3	9.313e-3	2	NC	1	NC	1
380			min	-.008	2	-.026	2	0	1	-4.698e-3	3	NC	1	NC	1
381	M5	1	max	.022	3	.074	3	.003	3	5.465e-6	3	NC	1	NC	1
382			min	-.025	2	-.064	2	-.001	9	0	11	NC	1	NC	1
383		2	max	.022	3	.042	3	.004	3	1.115e-4	3	NC	4	NC	1
384			min	-.025	2	-.036	2	-.001	9	-1.975e-5	9	1529.063	3	NC	1
385		3	max	.022	3	.013	3	.005	3	2.154e-4	3	NC	5	NC	1
386			min	-.025	2	-.009	2	-.001	9	-3.921e-5	9	793.46	3	NC	1
387		4	max	.022	3	.014	2	.006	3	2.098e-4	3	NC	5	NC	1
388			min	-.025	2	-.012	3	-.001	9	-3.728e-5	9	567.516	3	NC	1
389		5	max	.022	3	.034	2	.007	3	2.041e-4	3	NC	5	NC	1
390			min	-.025	2	-.032	3	0	9	-3.535e-5	9	460.161	2	NC	1
391		6	max	.022	3	.051	2	.007	3	1.984e-4	3	NC	5	NC	1
392			min	-.025	2	-.048	3	0	9	-3.342e-5	9	391.198	2	9718.469	3
393		7	max	.021	3	.064	2	.007	3	1.927e-4	3	NC	5	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
394			min	-.025	2	-.06	3	0	9	-3.149e-5	9	348.697	2	9231.653	3
395		8	max	.021	3	.075	2	.007	3	1.871e-4	3	NC	5	NC	1
396			min	-.025	2	-.068	3	0	9	-2.957e-5	9	322.076	2	9121.321	3
397		9	max	.021	3	.081	2	.007	3	1.814e-4	3	NC	5	NC	1
398			min	-.025	2	-.073	3	0	9	-2.764e-5	9	306.337	2	9315.619	3
399		10	max	.021	3	.084	2	.007	3	1.757e-4	3	NC	5	NC	1
400			min	-.025	2	-.074	3	0	9	-2.571e-5	9	299.1	2	9805.662	3
401		11	max	.021	3	.082	2	.006	3	1.7e-4	3	NC	5	NC	1
402			min	-.025	2	-.071	3	0	9	-2.378e-5	9	299.509	2	NC	1
403		12	max	.021	3	.077	2	.005	3	1.644e-4	3	NC	5	NC	1
404			min	-.025	2	-.065	3	0	9	-2.185e-5	9	307.917	2	NC	1
405		13	max	.021	3	.067	2	.005	3	1.587e-4	3	NC	5	NC	1
406			min	-.025	2	-.056	3	0	9	-1.992e-5	9	326.07	2	NC	1
407		14	max	.021	3	.054	2	.004	3	1.53e-4	3	NC	5	NC	1
408			min	-.025	2	-.044	3	0	9	-1.799e-5	9	357.995	2	NC	1
409		15	max	.021	3	.035	2	.003	3	1.474e-4	3	NC	5	NC	1
410			min	-.025	2	-.029	3	0	9	-1.606e-5	9	412.527	2	NC	1
411		16	max	.021	3	.012	2	.003	3	1.376e-4	3	NC	5	NC	1
412			min	-.025	2	-.011	3	0	9	-1.533e-5	9	511.255	2	NC	1
413		17	max	.021	3	.01	3	.002	3	3.079e-5	3	NC	5	NC	1
414			min	-.025	2	-.016	2	0	9	-4.331e-5	9	723.136	2	NC	1
415		18	max	.021	3	.033	3	.001	3	1.411e-5	3	NC	4	NC	1
416			min	-.025	2	-.048	2	0	9	-2.214e-5	9	1400.849	2	NC	1
417		19	max	.021	3	.057	3	0	3	0	15	NC	1	NC	1
418			min	-.025	2	-.083	2	0	9	-8.688e-7	3	NC	1	NC	1
419	M9	1	max	.007	3	.023	3	.003	3	9.553e-3	3	NC	1	NC	1
420			min	-.008	2	-.02	2	-.001	9	-6.681e-3	2	NC	1	NC	1
421		2	max	.007	3	.013	3	.001	3	4.719e-3	3	NC	4	NC	1
422			min	-.008	2	-.011	2	0	9	-3.293e-3	2	4838.109	3	NC	1
423		3	max	.007	3	.004	3	.001	1	8.18e-5	1	NC	4	NC	1
424			min	-.008	2	-.003	2	0	3	-2.539e-5	3	2509.448	3	NC	1
425		4	max	.007	3	.004	2	.002	1	5.797e-5	1	NC	4	NC	1
426			min	-.008	2	-.004	3	-.001	3	-3.295e-5	3	1792.831	3	NC	1
427		5	max	.007	3	.011	2	.002	1	3.415e-5	1	NC	4	NC	1
428			min	-.008	2	-.01	3	-.002	3	-4.05e-5	3	1452.019	3	NC	1
429		6	max	.007	3	.016	2	.002	1	1.208e-5	2	NC	4	NC	1
430			min	-.008	2	-.016	3	-.003	3	-4.806e-5	3	1258.363	2	9049.828	3
431		7	max	.007	3	.02	2	.002	1	5.359e-6	2	NC	4	NC	1
432			min	-.008	2	-.019	3	-.004	3	-5.561e-5	3	1122.121	2	8278.807	3
433		8	max	.007	3	.023	2	0	1	-5.093e-7	10	NC	4	NC	1
434			min	-.008	2	-.022	3	-.004	3	-6.317e-5	3	1036.825	2	7855.769	3
435		9	max	.007	3	.025	2	0	11	-7.064e-7	10	NC	4	NC	1
436			min	-.008	2	-.023	3	-.004	3	-7.072e-5	3	986.455	2	7680.821	3
437		10	max	.007	3	.026	2	0	2	-9.036e-7	10	NC	5	NC	1
438			min	-.008	2	-.024	3	-.005	3	-8.5e-5	1	963.384	2	7711.894	3
439		11	max	.007	3	.026	2	0	10	-1.101e-6	10	NC	4	NC	1
440			min	-.008	2	-.023	3	-.004	3	-1.088e-4	1	964.879	2	7942.66	3
441		12	max	.007	3	.024	2	0	10	-1.298e-6	10	NC	4	NC	1
442			min	-.008	2	-.021	3	-.004	3	-1.327e-4	1	992.083	2	8398.188	3
443		13	max	.007	3	.021	2	0	10	-1.495e-6	10	NC	4	NC	1
444			min	-.008	2	-.018	3	-.004	3	-1.565e-4	1	1050.625	2	9143.801	3
445		14	max	.007	3	.017	2	0	10	-1.692e-6	10	NC	4	NC	1
446			min	-.008	2	-.014	3	-.003	3	-1.803e-4	1	1153.465	2	NC	1
447		15	max	.007	3	.011	2	0	10	-1.89e-6	10	NC	4	NC	1
448			min	-.008	2	-.009	3	-.004	1	-2.041e-4	1	1329.01	2	NC	1
449		16	max	.007	3	.004	2	0	10	-2.052e-6	10	NC	4	NC	1
450			min	-.008	2	-.003	3	-.003	1	-2.225e-4	1	1646.631	2	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
451		17	max	.007	3	.003	3	0	10	3.53e-5	3	NC	4	NC	1
452			min	-.008	2	-.005	2	-.003	1	-1.104e-4	1	2327.31	2	NC	1
453		18	max	.007	3	.011	3	0	10	2.345e-3	3	NC	4	NC	1
454			min	-.008	2	-.015	2	-.002	1	-4.622e-3	2	4506.486	2	NC	1
455		19	max	.007	3	.018	3	0	3	4.696e-3	3	NC	1	NC	1
456			min	-.008	2	-.026	2	0	9	-9.313e-3	2	NC	1	NC	1
457	M13	1	max	.001	9	.023	3	.007	3	3.76e-3	3	NC	1	NC	1
458			min	-.003	3	-.02	2	-.008	2	-3.302e-3	2	NC	1	NC	1
459		2	max	.001	9	.075	3	.005	3	4.67e-3	3	NC	4	NC	1
460			min	-.003	3	-.056	2	-.006	2	-4.112e-3	2	1949.082	3	NC	1
461		3	max	.001	9	.119	3	.009	9	5.58e-3	3	NC	5	NC	2
462			min	-.003	3	-.087	2	-.005	2	-4.922e-3	2	1061.336	3	7912.701	1
463		4	max	.001	9	.148	3	.014	1	6.49e-3	3	NC	5	NC	2
464			min	-.003	3	-.109	2	-.005	10	-5.732e-3	2	812.757	3	5670.633	1
465		5	max	.001	9	.161	3	.015	1	7.4e-3	3	NC	5	NC	2
466			min	-.003	3	-.118	2	-.007	10	-6.542e-3	2	740.836	3	5273.049	1
467		6	max	.001	9	.156	3	.014	9	8.31e-3	3	NC	5	NC	2
468			min	-.003	3	-.116	2	-.009	2	-7.352e-3	2	767.99	3	6260.694	1
469		7	max	.001	9	.137	3	.014	3	9.22e-3	3	NC	5	NC	1
470			min	-.003	3	-.105	2	-.014	2	-8.162e-3	2	894.402	3	NC	1
471		8	max	.001	9	.111	3	.016	3	1.013e-2	3	NC	4	NC	1
472			min	-.003	3	-.088	2	-.019	2	-8.972e-3	2	1165.646	3	9149.272	2
473		9	max	.001	9	.085	3	.019	3	1.104e-2	3	NC	4	NC	1
474			min	-.003	3	-.071	2	-.023	2	-9.782e-3	2	1636.5	3	6552.551	2
475		10	max	.001	9	.074	3	.022	3	1.195e-2	3	NC	4	NC	4
476			min	-.003	3	-.064	2	-.025	2	-1.059e-2	2	2014.703	3	5824.413	2
477		11	max	.001	9	.086	3	.023	3	1.104e-2	3	NC	4	NC	1
478			min	-.003	3	-.071	2	-.023	2	-9.782e-3	2	1636.498	3	6280.576	3
479		12	max	.001	9	.111	3	.024	3	1.013e-2	3	NC	4	NC	1
480			min	-.003	3	-.088	2	-.019	2	-8.972e-3	2	1165.645	3	6107.53	3
481		13	max	.001	9	.137	3	.023	3	9.225e-3	3	NC	5	NC	1
482			min	-.003	3	-.105	2	-.014	2	-8.162e-3	2	894.401	3	6398.315	3
483		14	max	.001	9	.156	3	.021	3	8.317e-3	3	NC	5	NC	2
484			min	-.003	3	-.116	2	-.009	2	-7.352e-3	2	767.99	3	6255.933	1
485		15	max	.001	9	.161	3	.019	3	7.408e-3	3	NC	5	NC	2
486			min	-.003	3	-.118	2	-.007	10	-6.542e-3	2	740.836	3	5277.448	1
487		16	max	.001	9	.149	3	.016	3	6.5e-3	3	NC	5	NC	2
488			min	-.003	3	-.109	2	-.005	10	-5.732e-3	2	812.756	3	5683.328	1
489		17	max	.001	9	.119	3	.012	3	5.592e-3	3	NC	5	NC	2
490			min	-.003	3	-.087	2	-.005	2	-4.922e-3	2	1061.335	3	7944.266	1
491		18	max	.001	9	.076	3	.009	3	4.684e-3	3	NC	4	NC	1
492			min	-.003	3	-.056	2	-.006	2	-4.112e-3	2	1949.081	3	NC	1
493		19	max	.001	9	.023	3	.007	3	3.775e-3	3	NC	1	NC	1
494			min	-.003	3	-.02	2	-.008	2	-3.303e-3	2	NC	1	NC	1
495	M16	1	max	0	9	.018	3	.007	3	4.063e-3	2	NC	1	NC	1
496			min	0	3	-.026	2	-.008	2	-2.917e-3	3	NC	1	NC	1
497		2	max	0	9	.044	3	.01	3	5.065e-3	2	NC	4	NC	1
498			min	0	3	-.077	2	-.006	2	-3.597e-3	3	1996.432	2	NC	1
499		3	max	0	9	.066	3	.012	3	6.066e-3	2	NC	5	NC	2
500			min	0	3	-.12	2	-.005	2	-4.276e-3	3	1084.747	2	7947.561	1
501		4	max	0	9	.082	3	.015	3	7.068e-3	2	NC	5	NC	2
502			min	0	3	-.149	2	-.005	10	-4.956e-3	3	827.48	2	5697.196	1
503		5	max	0	9	.089	3	.018	3	8.069e-3	2	NC	5	NC	2
504			min	0	3	-.162	2	-.007	10	-5.635e-3	3	749.586	2	5303.132	1
505		6	max	0	9	.089	3	.02	3	9.07e-3	2	NC	5	NC	2
506			min	0	3	-.158	2	-.009	2	-6.314e-3	3	769.39	2	6312.416	1
507		7	max	0	9	.082	3	.021	3	1.007e-2	2	NC	5	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
508			min	0	3	-.141	2	-.014	2	-6.994e-3	3	881.543	2	7079.823	3
509		8	max	0	9	.072	3	.022	3	1.107e-2	2	NC	4	NC	1
510			min	0	3	-.117	2	-.019	2	-7.673e-3	3	1117.715	2	6766.841	3
511		9	max	0	9	.062	3	.022	3	1.207e-2	2	NC	4	NC	1
512			min	0	3	-.093	2	-.023	2	-8.353e-3	3	1503.479	2	6549.596	2
513		10	max	0	9	.057	3	.021	3	1.308e-2	2	NC	4	NC	4
514			min	0	3	-.083	2	-.025	2	-9.032e-3	3	1792.27	2	5822.328	2
515		11	max	0	9	.062	3	.02	3	1.207e-2	2	NC	4	NC	1
516			min	0	3	-.093	2	-.023	2	-8.351e-3	3	1503.479	2	6549.608	2
517		12	max	0	9	.072	3	.019	3	1.107e-2	2	NC	4	NC	1
518			min	0	3	-.117	2	-.019	2	-7.67e-3	3	1117.715	2	8849.946	3
519		13	max	0	9	.082	3	.017	3	1.007e-2	2	NC	5	NC	1
520			min	0	3	-.141	2	-.014	2	-6.989e-3	3	881.543	2	NC	1
521		14	max	0	9	.089	3	.015	3	9.071e-3	2	NC	5	NC	2
522			min	0	3	-.158	2	-.009	2	-6.308e-3	3	769.39	2	6320.59	1
523		15	max	0	9	.089	3	.015	1	8.07e-3	2	NC	5	NC	2
524			min	0	3	-.162	2	-.007	10	-5.627e-3	3	749.586	2	5317.077	1
525		16	max	0	1	.082	3	.013	1	7.069e-3	2	NC	5	NC	2
526			min	0	3	-.149	2	-.005	10	-4.946e-3	3	827.48	2	5720.199	1
527		17	max	0	1	.066	3	.01	3	6.067e-3	2	NC	5	NC	2
528			min	0	3	-.12	2	-.005	2	-4.265e-3	3	1084.747	2	7995.33	1
529		18	max	0	1	.044	3	.008	3	5.066e-3	2	NC	4	NC	1
530			min	0	3	-.077	2	-.006	2	-3.584e-3	3	1996.432	2	NC	1
531		19	max	0	1	.018	3	.007	3	4.065e-3	2	NC	1	NC	1
532			min	0	3	-.026	2	-.008	2	-2.903e-3	3	NC	1	NC	1
533	M15	1	max	0	1	0	1	0	1	3.793e-4	3	NC	1	NC	1
534			min	0	1	0	1	0	1	-5.21e-5	2	NC	1	NC	1
535		2	max	0	3	0	15	0	1	8.102e-4	3	NC	1	NC	1
536			min	0	2	-.003	4	0	3	-4.78e-4	2	NC	1	NC	1
537		3	max	0	3	-.001	15	.003	1	1.241e-3	3	NC	1	NC	1
538			min	0	2	-.006	4	-.003	3	-9.039e-4	2	NC	1	NC	1
539		4	max	0	3	-.002	15	.006	1	1.672e-3	3	NC	3	NC	4
540			min	0	2	-.009	4	-.007	3	-1.33e-3	2	7304.134	4	5653.622	3
541		5	max	0	3	-.003	15	.009	1	2.103e-3	3	NC	5	NC	4
542			min	0	2	-.011	4	-.011	3	-1.756e-3	2	5699.49	4	3713.444	3
543		6	max	0	3	-.003	15	.013	1	2.534e-3	3	NC	5	NC	4
544			min	0	2	-.013	4	-.016	3	-2.182e-3	2	4796.723	4	2705.251	3
545		7	max	0	3	-.003	15	.017	2	2.964e-3	3	NC	5	NC	4
546			min	-.001	2	-.015	4	-.021	3	-2.607e-3	2	4253.828	4	2115.56	3
547		8	max	0	3	-.004	15	.021	2	3.395e-3	3	NC	5	NC	4
548			min	-.001	2	-.016	4	-.026	3	-3.033e-3	2	3928.009	4	1744.798	3
549		9	max	0	3	-.004	15	.024	2	3.826e-3	3	NC	5	NC	4
550			min	-.002	2	-.017	4	-.03	3	-3.459e-3	2	3752.634	4	1502.144	3
551		10	max	0	3	-.004	15	.027	2	4.257e-3	3	NC	5	NC	4
552			min	-.002	2	-.017	4	-.034	3	-3.885e-3	2	3697.154	4	1341.979	3
553		11	max	0	3	-.004	15	.029	1	4.688e-3	3	NC	5	NC	5
554			min	-.002	2	-.017	4	-.036	3	-4.311e-3	2	3752.634	4	1240.354	3
555		12	max	0	3	-.004	15	.03	1	5.119e-3	3	NC	5	NC	5
556			min	-.002	2	-.016	4	-.037	3	-4.737e-3	2	3928.009	4	1185.386	3
557		13	max	.001	3	-.004	15	.029	1	5.55e-3	3	NC	5	NC	5
558			min	-.002	2	-.015	4	-.036	3	-5.163e-3	2	4253.828	4	1173.633	3
559		14	max	.001	3	-.003	15	.027	1	5.981e-3	3	NC	5	NC	4
560			min	-.003	2	-.013	4	-.033	3	-5.589e-3	2	4796.723	4	1210.218	3
561		15	max	.001	3	-.003	15	.022	1	6.411e-3	3	NC	5	NC	4
562			min	-.003	2	-.011	4	-.028	3	-6.015e-3	2	5699.49	4	1313.95	3
563		16	max	.001	3	-.002	15	.016	1	6.842e-3	3	NC	3	NC	4
564			min	-.003	2	-.009	4	-.019	3	-6.441e-3	2	7304.134	4	1535.894	3

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
565		17	max	.001	3	0	2	.007	1	7.273e-3	3	NC	1	NC	4
566			min	-.003	2	-.006	4	-.008	3	-6.866e-3	2	NC	1	2036.26	3
567		18	max	.001	3	.002	2	.007	3	7.704e-3	3	NC	1	NC	4
568			min	-.003	2	-.004	4	-.01	2	-7.292e-3	2	NC	1	3625.504	3
569		19	max	.002	3	.005	2	.026	3	8.135e-3	3	NC	1	NC	1
570			min	-.004	2	-.001	9	-.026	2	-7.718e-3	2	NC	1	NC	1
571	M16A	1	max	0	2	0	2	.008	3	2.35e-3	3	NC	1	NC	1
572			min	-.001	3	0	9	-.008	2	-2.355e-3	2	NC	1	NC	1
573		2	max	0	2	0	15	.001	3	2.257e-3	3	NC	1	NC	1
574			min	-.001	3	-.003	4	-.003	2	-2.247e-3	2	NC	1	NC	1
575		3	max	0	2	-.001	15	.004	1	2.165e-3	3	NC	1	NC	4
576			min	-.001	3	-.006	4	-.004	3	-2.14e-3	2	NC	1	5741.39	3
577		4	max	0	2	-.002	15	.007	1	2.072e-3	3	NC	3	NC	4
578			min	-.001	3	-.009	4	-.008	3	-2.033e-3	2	7304.134	4	4367.818	3
579		5	max	0	2	-.003	15	.009	1	1.979e-3	3	NC	5	NC	4
580			min	-.001	3	-.011	4	-.01	3	-1.926e-3	2	5699.49	4	3773.299	3
581		6	max	0	2	-.003	15	.01	1	1.887e-3	3	NC	5	NC	4
582			min	-.001	3	-.013	4	-.012	3	-1.819e-3	2	4796.723	4	3514.647	3
583		7	max	0	2	-.004	15	.011	1	1.794e-3	3	NC	5	NC	4
584			min	0	3	-.015	4	-.013	3	-1.711e-3	2	4253.828	4	3453.169	3
585		8	max	0	2	-.004	15	.011	1	1.701e-3	3	NC	5	NC	4
586			min	0	3	-.016	4	-.013	3	-1.604e-3	2	3928.009	4	3541.731	3
587		9	max	0	2	-.004	15	.01	1	1.609e-3	3	NC	5	NC	4
588			min	0	3	-.017	4	-.012	3	-1.497e-3	2	3752.634	4	3774.566	3
589		10	max	0	2	-.004	15	.009	1	1.516e-3	3	NC	5	NC	4
590			min	0	3	-.017	4	-.011	3	-1.39e-3	2	3697.154	4	4175.883	3
591		11	max	0	2	-.004	15	.008	1	1.424e-3	3	NC	5	NC	4
592			min	0	3	-.017	4	-.009	3	-1.283e-3	2	3752.634	4	4805.46	3
593		12	max	0	2	-.004	15	.006	1	1.331e-3	3	NC	5	NC	4
594			min	0	3	-.016	4	-.008	3	-1.175e-3	2	3928.009	4	5782.305	3
595		13	max	0	2	-.003	15	.005	1	1.238e-3	3	NC	5	NC	2
596			min	0	3	-.015	4	-.006	3	-1.068e-3	2	4253.828	4	7345.599	3
597		14	max	0	2	-.003	15	.003	1	1.146e-3	3	NC	5	NC	1
598			min	0	3	-.013	4	-.004	3	-9.609e-4	2	4796.723	4	NC	1
599		15	max	0	2	-.003	15	.002	1	1.053e-3	3	NC	5	NC	1
600			min	0	3	-.011	4	-.002	3	-8.536e-4	2	5699.49	4	NC	1
601		16	max	0	2	-.002	15	.001	9	9.603e-4	3	NC	3	NC	1
602			min	0	3	-.009	4	0	3	-7.464e-4	2	7304.134	4	NC	1
603		17	max	0	2	-.001	15	0	4	8.677e-4	3	NC	1	NC	1
604			min	0	3	-.006	4	0	2	-6.392e-4	2	NC	1	NC	1
605		18	max	0	2	0	15	0	3	7.751e-4	3	NC	1	NC	1
606			min	0	3	-.003	4	0	2	-5.32e-4	2	NC	1	NC	1
607		19	max	0	1	0	1	0	1	6.824e-4	3	NC	1	NC	1
608			min	0	1	0	1	0	1	-4.248e-4	2	NC	1	NC	1

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 4.00 x 0.28

<Figure 1>



<Figure 2>



Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	405.0	6.0	101.0	101.2
Sum	405.0	6.0	101.0	101.2

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 405
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	5.333	10469

$\phi N_{cb} = \phi\ (A_{Nc} / A_{Nco})\ \Psi_{ed,N}\ \Psi_{c,N}\ \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-4)

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cb} (lb)
253.92	256.00	0.995	1.00	1.000	10469	0.65	6717

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_a = \phi\ (A_{Na} / A_{Na0})\ \Psi_{ed,Na}\ \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16a)

A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	ϕ	ϕN_a (lb)
109.66	109.66	1.000	1.000	9755	0.55	5365

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in y-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	8.00	8488

$\phi V_{cby} = \phi\ (A_{Vc} / A_{Vco})\Psi_{ed,V}\Psi_{c,V}\Psi_{h,V}V_{by}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cby} (lb)
238.44	288.00	0.897	1.000	1.000	8488	0.70	4411

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cbx} = \phi\ (A_{Vc} / A_{Vco})\Psi_{ed,V}\Psi_{c,V}\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbx} (lb)
188.88	278.72	0.903	1.000	1.000	8282	0.70	3549

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	8.00	8488

$\phi V_{cbx} = \phi\ (2)(A_{Vc} / A_{Vco})\Psi_{ed,V}\Psi_{c,V}\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
238.44	288.00	1.000	1.000	1.000	8488	0.70	9838

Shear parallel to edge in y-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cby} = \phi\ (2)(A_{Vc} / A_{Vco})\Psi_{ed,V}\Psi_{c,V}\Psi_{h,V}V_{bx}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cby} (lb)
188.88	278.72	1.000	1.000	1.000	8282	0.70	7858

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cp} = \phi\ \mathrm{min}|k_{cp}N_a\ ;\ k_{cp}N_{cb}| = \phi\ \mathrm{min}|k_{cp}(A_{Na} / A_{Na0})\Psi_{ed,Na}\Psi_{p,Na}N_{a0}\ ;\ k_{cp}(A_{Nc} / A_{Nco})\Psi_{ed,N}\Psi_{c,N}\Psi_{cp,N}N_b|$ (Eq. D-30a)

k_{cp}	A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	109.66	109.66	1.000	1.000	9755	9755

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ	ϕV_{cp} (lb)
253.92	256.00	0.995	1.000	1.000	10469	10334	0.70	13657

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, $øN_n$ (lb)	Ratio	Status
Steel	405	6071	0.07	Pass
Concrete breakout	405	6717	0.06	Pass
Adhesive	**405**	**5365**	**0.08**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, $øV_n$ (lb)	Ratio	Status
Steel	**101**	**3156**	**0.03**	**Pass (Governs)**
T Concrete breakout y+	101	4411	0.02	Pass
T Concrete breakout x+	6	3549	0.00	Pass
|| Concrete breakout y+	6	9838	0.00	Pass
|| Concrete breakout x+	101	7858	0.01	Pass
Concrete breakout, combined	-	-	0.02	Pass
Pryout	101	13657	0.01	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status
Sec. D.7.1	0.08	0.00	7.5 %	1.0	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 9.00 x 4.00 x 0.28

<Figure 1>



<Figure 2>



Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	732.5	499.5	0.0	499.5
2	732.5	499.5	0.0	499.5
Sum	1465.0	999.0	0.0	999.0

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 1465
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	5.333	10469

$\phi N_{cbg} = \phi\, (A_{Nc} / A_{Nco})\, \Psi_{ec,N}\, \Psi_{ed,N}\, \Psi_{c,N}\, \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-5)

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cbg} (lb)
314.72	256.00	1.000	0.865	1.00	1.000	10469	0.65	7233

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_{ag} = \phi\, (A_{Na} / A_{Na0})\, \Psi_{ed,Na}\, \Psi_{g,Na}\, \Psi_{ec,Na}\, \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16b)

A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0}(lb)	ϕ	ϕN_{ag} (lb)
177.03	109.66	0.952	1.021	1.000	1.000	9755	0.55	8418

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	12.00	15593

$\phi V_{cbx} = \phi\, (A_{Vc} / A_{Vco})\Psi_{ed,V}\Psi_{c,V}\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in²)	A_{Vco} (in²)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbx} (lb)
288.00	648.00	0.833	1.000	1.000	15593	0.70	4043

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	8.00	8488

$\phi V_{cbgx} = \phi\, (2)(A_{Vc} / A_{Vco})\Psi_{ec,V}\Psi_{ed,V}\Psi_{c,V}\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-22)

A_{Vc} (in²)	A_{Vco} (in²)	$\Psi_{ec,V}$	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbgx} (lb)
284.04	288.00	1.000	1.000	1.000	1.000	8488	0.70	11720

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cpg} = \phi\,\min|k_{cp}N_{ag}\,;\, k_{cp}N_{cbg}| = \phi\,\min|k_{cp}(A_{Na} / A_{Na0})\Psi_{ed,Na}\Psi_{g,Na}\Psi_{ec,Na}\Psi_{p,Na}N_{a0}\,;\, k_{cp}(A_{Nc} / A_{Nco})\Psi_{ec,N}\Psi_{ed,N}\Psi_{c,N}\Psi_{cp,N}N_b|$ (Eq. D-30b)

k_{cp}	A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	177.03	109.66	0.952	1.021	1.000	1.000	9755	15305

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ
314.72	256.00	1.000	0.865	1.000	1.000	10469	11128	0.70

ϕV_{cpg} (lb)
15580

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, $øN_n$ (lb)	Ratio	Status
Steel	733	6071	0.12	Pass
Concrete breakout	**1465**	**7233**	**0.20**	**Pass (Governs)**
Adhesive	1465	8418	0.17	Pass

Shear	Factored Load, V_{ua} (lb)	Design Strength, $øV_n$ (lb)	Ratio	Status
Steel	500	3156	0.16	Pass
T Concrete breakout x+	**999**	**4043**	**0.25**	**Pass (Governs)**
|| Concrete breakout y-	**999**	**11720**	**0.09**	**Pass (Governs)**
Pryout	999	15580	0.06	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status

Sec. D.7.3	0.20	0.25	45.0 %	1.2	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer’s product literature for hole cleaning and installation instructions.