

Schletter, Inc.		30° Tilt w/ Seismic Design
HCV	Standard PVMax Racking System	
	Representative Calculations - ASCE 7-10	

1. INTRODUCTION

1.1 Project Description

The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. PVMax ground mount system.

1.2 Construction

Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to aluminum struts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

Maximum			Minimum		
Height =	1700	mm	Height =	1550	mm
Width =	1050	mm	Width =	970	mm
Dead Load =	3.00	psf	Dead Load =	1.75	psf

Modules Per Row =	2
Module Tilt =	30°
Maximum Height Above Grade =	3 ft

1.3 Technical Codes

- ASCE 7-10 - Chapter 26-31, Wind Loads
- ASCE 7-10 - Chapter 7, Snow Loads
- ASCE 7-10 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2012, 2015
- Aluminum Design Manual, Eighth Edition, 2005



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

2. LOAD ACTIONS

2.1 Permanent Loads

g_{MAX} =	3.00	psf	*Self-weight of the PV modules.*
g_{MIN} =	1.75	psf	

2.2 Snow Loads

Ground Snow Load, P_g =	30.00	psf	
Sloped Roof Snow Load, P_s =	16.49	psf	*(ASCE 7-10, Eq. 7.4-1)*
I_s =	1.00		
C_s =	0.73		
C_e =	0.90		
C_t =	1.20		

2.3 Wind Loads

Design Wind Speed, V =	110	mph	Exposure Category = C
Height <	15	ft	Importance Category = II
Peak Velocity Pressure, q_z =	19.00	psf	*Including the gust factor, G=0.85. (ASCE 7-10, Eq. 27.3-1)*

Pressure Coefficients

$Cf+_{TOP}$ =	1.150	*(Pressure)*	*Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0611-1e. Negative forces are applied away from the surface.*
$Cf+_{BOTTOM}$ =	1.850		
$Cf-_{TOP, OUTER PURLIN}$ =	-2.600		
$Cf-_{TOP, INNER PURLIN}$ =	-2.000	*(Suction)*	
$Cf-_{BOTTOM}$ =	-1.100		

2.4 Seismic Loads

S_S =	2.50	R =	1.25
S_{DS} =	1.67	C_S =	0.8
S_1 =	1.00	ρ =	1.3
S_{D1} =	1.00	Ω =	1.25
T_a =	0.06	C_d =	1.25

ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.5W	
1.2D + 1.0W + 0.5S	
0.9D + 1.0W [M]	
1.54D + 1.3E + 0.2S [R]	*(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)*
0.56D + 1.3E [R]	
1.54D + 1.25E + 0.2S [O]	
0.56D + 1.25E [O]	

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S	
1.0D + 0.6W	
1.0D + 0.75L + 0.45W + 0.75S	
0.6D + 0.6W [M]	*(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)*
1.238D + 0.875E [O]	
1.1785D + 0.65625E + 0.75S [O]	
0.362D + 0.875E [O]	

[M] *Uses the minimum allowable module dead load.*
[R] *Include redundancy factor of 1.3.*
[O] *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location
M13	Top
M14	Mid-Top
M15	Mid-Bottom
M16	Bottom

Diagonal Struts	Location
M3	Outer
M7	Inner
M11	Outer

Front Reactions	Location
N7	Outer
N15	Inner
N23	Outer

Girders	Location
M1	Outer
M5	Inner
M9	Outer

Rear Struts	Location
M2	Outer
M6	Inner
M10	Outer

Rear Reactions	Location
N8	Outer
N16	Inner
N24	Outer

Front Struts	Location
M4	Outer
M8	Inner
M12	Outer

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type =	**S1.5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	132	in
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	25.07	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	23.08	ksi
S_y =	1.33	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	2.16	in^4
I_x =	1.07	in^4
A =	1.25	in^2
g =	1.50	lbs/ft
M_y =	1.767	k-ft
M_z =	0.408	k-ft
$M_{y\ allowable}$ =	2.779	k-ft
$M_{z\ allowable}$ =	1.154	k-ft
Utilization =	99%	



4.2 Girder Design

Loads from purlins are transferred using an inclined girder, which is connected to a set of aluminum struts. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type =	**BF0**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	88.90	in
$\Phi F_{ty\ AXIAL}$ =	31.09	ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	29.35	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	33.25	ksi
S_y =	1.42	in^3
S_x =	1.41	in^3
E =	10100	ksi
I_y =	2.39	in^4
I_x =	2.22	in^4
A =	1.88	in^2
g =	2.26	lbs/ft
M_y =	-2.584	k-ft
M_z =	0.000	k-ft
P_n =	-0.663	k
$M_{y\ allowable}$ =	3.464	k-ft
$M_{z\ allowable}$ =	3.907	k-ft
$P_{n\ allowable}$ =	58.535	k
Utilization =	76%	



4.3 Front Strut Design

The front aluminum strut connects a portion of the girder to the foundation. Vertical girder forces are then transferred down through the strut into the foundation. The strut is attached with single M12 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	24.80	in
$\Phi F_{ty\ AXIAL}$ =	28.03	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.000	k-ft
M_z =	-0.593	k-ft
P_n =	0.649	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	27.532	k
Utilization =	44%	



DETAIL VIEW

4.4 Diagonal Strut Design

A diagonal aluminum strut braces the support structure. It connects at a front portion of the girder and transfers horizontal forces to the rear foundation connection. The strut is attached with single M12 bolts at each end. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	86.60	in
$\Phi F_{ty\ AXIAL}$ =	7.50	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.009	k-ft
M_z =	0.000	k-ft
P_n =	1.995	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	7.371	k
Utilization =	28%	



DETAIL VIEW

4.5 Rear Strut Design

An aluminum strut connects the rear portion of the girder to the rear foundation connection. Both vertical and horizontal forces are transferred from the girder. The strut is attached with single M12 bolts at each end. See Appendix A.5 for detailed member calculations. Section units are in (mm).

Strut Type	=	**55x55**	
Aluminum Type	=	6105-T5	
F_{ty}	=	35	ksi
L_b	=	70.83	in
$\Phi F_{ty\ AXIAL}$	=	10.55	ksi
$\Phi F_{ty\ BENDING}$	=	28.22	ksi
S_y	=	0.60	in^3
S_x	=	0.60	in^3
E	=	10100	ksi
I_y	=	0.67	in^4
I_x	=	0.67	in^4
A	=	0.98	in^2
g	=	1.18	lbs/ft
M_y	=	-0.008	k-ft
M_z	=	0.000	k-ft
P_n	=	2.914	k
$M_{y\ allowable}$	=	1.408	k-ft
$M_{z\ allowable}$	=	1.408	k-ft
$P_{n\ allowable}$	=	10.365	k
Utilization	=	29%	



5. FOUNDATION DESIGN CALCULATIONS

5.1 Helical Pile Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete foundation design.

Maximum		Front	Rear	
Tensile Load	=	115.94	5013.26	k
Compressive Load	=	3499.81	4270.44	k
Lateral Load	=	409.83	3161.07	k
Moment (Weak Axis)	=	0.80	0.30	k

5.2 Design of Ballast Foundations

Ballast foundations are used to secure the racking structure in place. The foundations are checked for potential overturning and sliding. Bearing pressures applied by the racking and ballast foundations are checked against the allowable bearing pressures provided by the IBC table 1806.2 (2012, 2015).



Concrete Properties		
Weight of Concrete =	145	pcf
Compressive Strength =	2500	psi
Yield Strength =	60000	psi
Overturning Check		
M_O =	122264.4	in-lbs
Resisting Force Required =	1852.49	lbs
S.F. =	1.67	
Weight Required =	3087.48	lbs
Minimum Width =	25 in	in
Weight Provided =	4984.38	lbs
Sliding		
Force =	728.80	lbs
Friction =	0.4	
Weight Required =	1822.00	lbs
Resisting Weight =	4984.38	lbs
Additional Weight Required =	0	lbs
Cohesion		
Sliding Force =	728.80	lbs
Cohesion =	130	psf
Area =	22.92	ft^2
Resisting =	2492.19	lbs
Additional Weight Required =	0	lbs
Shear Key		
Additional Force =	0	lbs
Lateral Bearing Pressure =	200	psf/ft
Required Depth =	0.00	ft
f'_c =	2500	psi
Length =	8	in

Footing Reinforcement

Use fiber reinforcing with (2) #5 rebar.

A minimum 132in long x 25in wide x 18in tall ballast foundation is required to resist overturning.

Use a 132in long x 25in wide x 18in tall ballast foundation to resist sliding. Friction is OK.

Use a 132in long x 25in wide x 18in tall ballast foundation. Cohesion is OK.

Shear key is not required.

Bearing Pressure

	Ballast Width			
	25 in	26 in	27 in	28 in
P_{ftg} = (145 pcf)(11 ft)(1.5 ft)(2.08 ft) =	4984 lbs	5184 lbs	5383 lbs	5583 lbs

ASD LC	1.0D + 1.0S				1.0D + 0.6W				1.0D + 0.75L + 0.45W + 0.75S				0.6D + 0.6W			
Width	25 in	26 in	27 in	28 in	25 in	26 in	27 in	28 in	25 in	26 in	27 in	28 in	25 in	26 in	27 in	28 in
F_A	1347 lbs	1347 lbs	1347 lbs	1347 lbs	1068 lbs	1068 lbs	1068 lbs	1068 lbs	1669 lbs	1669 lbs	1669 lbs	1669 lbs	-43 lbs	-43 lbs	-43 lbs	-43 lbs
F_B	1286 lbs	1286 lbs	1286 lbs	1286 lbs	1742 lbs	1742 lbs	1742 lbs	1742 lbs	2135 lbs	2135 lbs	2135 lbs	2135 lbs	-2304 lbs	-2304 lbs	-2304 lbs	-2304 lbs
F_V	208 lbs	208 lbs	208 lbs	208 lbs	1340 lbs	1340 lbs	1340 lbs	1340 lbs	1141 lbs	1141 lbs	1141 lbs	1141 lbs	-1458 lbs	-1458 lbs	-1458 lbs	-1458 lbs
P_{total}	7617 lbs	7816 lbs	8016 lbs	8215 lbs	7794 lbs	7993 lbs	8193 lbs	8392 lbs	8788 lbs	8988 lbs	9187 lbs	9387 lbs	644 lbs	764 lbs	883 lbs	1003 lbs
M	3770 lbs-ft	3770 lbs-ft	3770 lbs-ft	3770 lbs-ft	3030 lbs-ft	3030 lbs-ft	3030 lbs-ft	3030 lbs-ft	4703 lbs-ft	4703 lbs-ft	4703 lbs-ft	4703 lbs-ft	3099 lbs-ft	3099 lbs-ft	3099 lbs-ft	3099 lbs-ft
e	0.49 ft	0.48 ft	0.47 ft	0.46 ft	0.39 ft	0.38 ft	0.37 ft	0.36 ft	0.54 ft	0.52 ft	0.51 ft	0.50 ft	4.81 ft	4.06 ft	3.51 ft	3.09 ft
L/6	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft
f_{min}	242.6 psf	241.7 psf	240.8 psf	239.9 psf	268.0 psf	266.0 psf	264.3 psf	262.6 psf	271.6 psf	269.5 psf	267.6 psf	265.8 psf	0.0 psf	0.0 psf	0.0 psf	0.0 psf
f_{max}	422.1 psf	414.2 psf	407.0 psf	400.2 psf	412.2 psf	404.7 psf	397.8 psf	391.3 psf	495.4 psf	484.7 psf	474.8 psf	465.6 psf	299.2 psf	162.9 psf	131.4 psf	118.9 psf

Maximum Bearing Pressure = 495 psf
Allowable Bearing Pressure = 1500 psf

Use a 132in long x 25in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Seismic Design

Overturning Check

M_O =	1631.3	ft-lbs
Resisting Force Required =	1566.09	lbs
S.F. =	1.67	
Weight Required =	2610.16	lbs
Minimum Width =	25 in	in
Weight Provided =	4984.38	lbs

A minimum 132in long x 25in wide x 18in tall ballast foundation is required to resist overturning.



Bearing Pressure

ASD LC	1.238D + 0.875E			1.1785D + 0.65625E + 0.75S			0.362D + 0.875E		
Width	25 in			25 in			25 in		
Support	Outer	Inner	Outer	Outer	Inner	Outer	Outer	Inner	Outer
F_Y	314 lbs	687 lbs	224 lbs	827 lbs	2213 lbs	757 lbs	123 lbs	201 lbs	34 lbs
F_V	231 lbs	226 lbs	236 lbs	169 lbs	166 lbs	184 lbs	232 lbs	228 lbs	234 lbs
P_{total}	6485 lbs	6858 lbs	6395 lbs	6701 lbs	8087 lbs	6631 lbs	1928 lbs	2005 lbs	1838 lbs
M	902 lbs-ft	892 lbs-ft	918 lbs-ft	670 lbs-ft	674 lbs-ft	720 lbs-ft	902 lbs-ft	888 lbs-ft	906 lbs-ft
e	0.14 ft	0.13 ft	0.14 ft	0.10 ft	0.08 ft	0.11 ft	0.47 ft	0.44 ft	0.49 ft
L/6	0.35 ft	0.35 ft	0.35 ft	0.35 ft	0.35 ft	0.35 ft	0.35 ft	0.35 ft	0.35 ft
f_{min}	169.6 psf	187.2 psf	163.7 psf	208.2 psf	268.2 psf	198.8 psf	0.0 psf	0.0 psf	0.0 psf
f_{max}	396.4 psf	411.3 psf	394.4 psf	376.6 psf	437.5 psf	379.9 psf	203.6 psf	203.0 psf	203.1 psf

Maximum Bearing Pressure = 438 psf
Allowable Bearing Pressure = 1500 psf

Use a 132in long x 25in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Foundation Requirements: 132in long x 25in wide x 18in tall ballast foundation and fiber reinforcing with (2) #5 rebar.

5.3 Foundation Anchors

Threaded rods are anchored to the the ballast foundations using the Simpson AT-XP epoxy solution. LRFD load results are compared to the allowable strengths of the epoxy solution. Please see the supplementary calculations provided by the Simpson Anchor Designer software.

6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of 80mm mounting clamps. The reliability of calculations is uncertain due to limited standards, therefore the strength of the clamp fasteners has been evaluated by load testing.

Fastening of Modules to Purlins

Maximum Uplifting Force	=	0.459 k
Allowable Uplift	=	1.214 k
Utilization	=	38%



Fastening of Purlins to Girders

Maximum Uplifting Force	=	1.789 k
Allowable Uplift	=	4.357 k
Utilization	=	41%



6.2 Strut Connections

The aluminum struts connect the aluminum girder ends to custom brackets with mounting holes. Single M12 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Front Strut

Maximum Axial Load	=	2.692 k
M12 Bolt Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	36%

Rear Strut

Maximum Axial Load	=	3.337 k
M12 Bolt Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	45%

Diagonal Strut

Maximum Axial Load	=	2.047 k
M12 Bolt Shear Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	28%

Bolt and bearing capacities are accounting for double shear. (ASCE 8-02, Eq. 5.3.4-1)



Struts under compression are shown to demonstrate the load transfer from the girder. Single M12 bolts are located at each end of the strut and are subjected to double shear.

7. SEISMIC DESIGN

7.1 Seismic Drift

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx}	=	48.27 in
Allowable Story Drift for All Other Structures, Δ	= {	$0.020h_{sx}$
		0.965 in
Max Drift, Δ_{MAX}	=	0.756 in

0.756 ≤ 0.965, OK.

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **S1.5**

Strong Axis:

3.4.14

L_b = 132 in

J = 0.432

365.174

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 27.1 ksi

3.4.16

b/t = 32.195

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 25.1 ksi

3.4.16.1 Not Used

Rb/t =

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 37.0588

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 40.985

Cc = 41.015

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.2

φF_L= φb[Bbr-mDbr*h/t]

φF_L= 43.2 ksi

φF_LSt= 25.1 ksi

Ix = 897074 mm^4

2.155 in^4

y = 41.015 mm

Sx = 1.335 in^3

M_{max}St = 2.788 k-ft

Weak Axis:

3.4.14

L_b = 132

J = 0.432

232.229

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 28.4

3.4.16

b/t = 37.0588

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 23.1 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 32.195

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 45.5

Cc = 45.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 23.1 ksi

Iy = 446476 mm^4

1.073 in^4

x = 45.5 mm

Sy = 0.599 in^3

M_{max}Wk = 1.152 k-ft

Compression

3.4.9

b/t = 32.195
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 25.1 ksi

b/t = 37.0588
S1 = 12.21
S2 = 32.70
φF_L = (φck2*√(BpE))/(1.6b/t)
φF_L = 21.9 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 21.94 ksi
A = 1215.13 mm^2
1.88 in^2
P_{max} = 41.32 kips

A.2 Design of Aluminum Girders - Aluminum Design Manual, 2005 Edition

Girder = **BF0**

Strong Axis:

3.4.14

L_b = 88.9 in
J = 1.08
152.913

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.4 ksi

3.4.16

b/t = 16.2

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 31.6 ksi

Weak Axis:

3.4.14

L_b = 88.9
J = 1.08
161.829

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.2

3.4.16

b/t = 7.4

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φyFcy
φF_L = 33.3 ksi

3.4.16.1 Used

Rb/t = 18.1

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L = φb[Bt-Dt*√(Rb/t)]

φF_L = 31.1 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 7.4

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 35.2

m = 0.68

C_0 = 41.067

Cc = 43.717

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 73.8

φF_L = 1.3φyFcy

φF_L = 43.2 ksi

$\varphi F_L St$ = 29.4 ksi

Ix = 984962 mm^4

2.366 in^4

y = 43.717 mm

Sx = 1.375 in^3

$M_{max}St$ = 3.363 k-ft

3.4.18

h/t = 16.2

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 40

Cc = 40

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L = 1.3φyFcy

φF_L = 43.2 ksi

$\varphi F_L Wk$ = 33.3 ksi

Iy = 923544 mm^4

2.219 in^4

x = 40 mm

Sy = 1.409 in^3

$M_{max}Wk$ = 3.904 k-ft

Compression

3.4.9

b/t = 16.2

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 31.6 ksi

b/t = 7.4

S1 = 12.21

S2 = 32.70

φF_L = φyFcy

φF_L = 33.3 ksi

3.4.10

Rb/t = 18.1

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φc[Bt-Dt*√(Rb/t)]

φF_L = 31.09 ksi

φF_L = 31.09 ksi

A = 1215.13 mm^2

1.88 in^2

P_{max} = 58.55 kips

A.3 Design of Aluminum Struts (Front) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 24.8 in

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

$M_{max}St$ = 1.460 k-ft

Weak Axis:

3.4.14

L_b = 24.8

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

$M_{max}Wk$ = 1.460 k-ft

Compression

3.4.7

λ = 0.57371

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

S1* = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

S2* = 1.23671

φcc = 0.87952

φF_L = φcc(Bc-Dc*λ)

φF_L = 28.0279 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 28.03 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 28.85 kips

A.4 Design of Aluminum Struts (Diagonal) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 86.60 in

J = 0.942

135.148

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L = 29.6 ksi

Weak Axis:

3.4.14

L_b = 86.6

J = 0.942

135.148

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L = 29.6

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17 \frac{\theta_y}{\theta_b} Fcy}{1.6Dt} \right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

$M_{max}St$ = 1.460 k-ft

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

$M_{max}Wk$ = 1.460 k-ft

Compression

3.4.7

λ = 2.00335

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi} \sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.86047

φF_L= (φccFcy)/(λ²)

φF_L= 7.50396 ksi

3.4.9

b/t = 24.5
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

b/t = 24.5
S1 = 12.21
S2 = 32.70
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 7.50 ksi
A = 663.99 mm^2
1.03 in^2
P_{max} = 7.72 kips

A.5 Design of Aluminum Struts (Rear) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 70.83 in
J = 0.942
110.537

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.0 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

Weak Axis:

3.4.14

L_b = 70.83
J = 0.942
110.537

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.0

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

$M_{max}St$ = 1.460 k-ft

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

$M_{max}Wk$ = 1.460 k-ft

Compression

3.4.7

λ = 1.63853

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.80939

φF_L= (φccFcy)/(λ²)

φF_L= 10.5516 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

$\varphi F_L = \varphi y Fcy$

φF_L = 33.25 ksi

φF_L = 10.55 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 10.86 kips

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				4		
2	Dead Load, Min	DL		-1				4		
3	Snow Load	SL						4		
4	Wind Load - Pressure	WL						4		
5	Wind Load - Suction	WL						4		
6	Seismic - Lateral	EL			.8			8		

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-8.366	-8.366	0	0
2	M14	Y	-8.366	-8.366	0	0
3	M15	Y	-8.366	-8.366	0	0
4	M16	Y	-8.366	-8.366	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-4.45	-4.45	0	0
2	M14	Y	-4.45	-4.45	0	0
3	M15	Y	-4.45	-4.45	0	0
4	M16	Y	-4.45	-4.45	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-39.836	-39.836	0	0
2	M14	Y	-39.836	-39.836	0	0
3	M15	Y	-39.836	-39.836	0	0
4	M16	Y	-39.836	-39.836	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	-60.928	-60.928	0	0
2	M14	y	-60.928	-60.928	0	0
3	M15	y	-98.014	-98.014	0	0
4	M16	y	-98.014	-98.014	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	137.749	137.749	0	0
2	M14	y	105.961	105.961	0	0
3	M15	y	58.278	58.278	0	0
4	M16	y	58.278	58.278	0	0

Member Distributed Loads (BLC 6 : Seismic - Lateral)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Z	6.693	6.693	0	0
2	M14	Z	6.693	6.693	0	0
3	M15	Z	6.693	6.693	0	0
4	M16	Z	6.693	6.693	0	0
5	M13	Z	0	0	0	0
6	M14	Z	0	0	0	0
7	M15	Z	0	0	0	0
8	M16	Z	0	0	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.5W	Yes	Y		1	1.2	3	1.6	4	.5														
2	LRFD 1.2D + 1.0W + 0.5S	Yes	Y		1	1.2	3	.5	4	1														
3	LRFD 0.9D + 1.0W	Yes	Y		2	.9					5	1												
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3												
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3												
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25												
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25												
8																								
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																
10	ASD 1.0D + 0.6W	Yes	Y		1	1			4	.6														
11	ASD 1.0D + 0.75L + 0.45W + 0....	Yes	Y		1	1	3	.75	4	.45														
12	ASD 0.6D + 0.6W	Yes	Y		2	.6					5	.6												
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875												
14	LATERAL - ASD 1.1785D + 0.65...	Yes	Y		1	1.1...	3	.75			6	.656												
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875												

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N8	max	599.861	2	995.079	2	.788	1	.003	1	0	1	0	1
2		min	-765.634	3	-1172.543	3	-38.577	5	-.232	4	0	1	0	1
3	N7	max	.044	9	1059.711	1	-.758	12	-.001	12	0	1	0	1
4		min	-.124	2	-27.109	5	-315.254	4	-.614	4	0	1	0	1
5	N15	max	.035	9	2692.165	1	0	10	0	10	0	1	0	1
6		min	-1.448	2	-89.185	3	-299.934	4	-.593	4	0	1	0	1
7	N16	max	2298.697	2	3284.953	2	0	2	0	11	0	1	0	1
8		min	-2431.593	3	-3856.355	3	-38.309	5	-.234	4	0	1	0	1
9	N23	max	.047	14	1059.711	1	13.971	1	.028	1	0	1	0	1
10		min	-.124	2	3.833	3	-305.14	5	-.598	4	0	1	0	1
11	N24	max	599.861	2	995.079	2	-.049	12	0	12	0	1	0	1
12		min	-765.634	3	-1172.543	3	-39.29	5	-.234	4	0	1	0	1
13	Totals:	max	3496.724	2	9825.325	1	0	10						
14		min	-3962.926	3	-6282.961	3	-1029.826	4						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M13	1	max	136.622	1	392.302	1	-9.939	12	0	3	.327	1	0	4
2			min	7.471	12	-549.171	3	-200.382	1	-.011	2	.018	12	0	3
3		2	max	136.622	1	275.068	1	-7.756	12	0	3	.14	4	.572	3
4			min	7.471	12	-386.483	3	-154.193	1	-.011	2	.007	12	-.408	1
5		3	max	136.622	1	157.833	1	-5.573	12	0	3	.072	5	.945	3
6			min	7.471	12	-223.795	3	-108.005	1	-.011	2	-.05	1	-.672	1
7		4	max	136.622	1	40.599	1	-3.39	12	0	3	.036	5	1.119	3
8			min	7.471	12	-61.107	3	-61.817	1	-.011	2	-.154	1	-.794	1
9		5	max	136.622	1	101.581	3	-1.206	12	0	3	.004	5	1.094	3
10			min	7.471	12	-76.635	1	-28.578	4	-.011	2	-.201	1	-.772	1
11		6	max	136.622	1	264.268	3	30.56	1	0	3	-.009	12	.871	3
12			min	3.713	15	-193.87	1	-21.039	5	-.011	2	-.192	1	-.606	1
13		7	max	136.622	1	426.956	3	76.749	1	0	3	-.007	12	.448	3
14			min	-6.626	5	-311.104	1	-17.661	5	-.011	2	-.126	1	-.298	1
15		8	max	136.622	1	589.644	3	122.937	1	0	3	0	10	.154	1
16			min	-19.172	5	-428.338	1	-14.283	5	-.011	2	-.07	4	-.173	3
17		9	max	136.622	1	752.332	3	169.125	1	0	3	.174	1	.749	1
18			min	-31.719	5	-545.573	1	-10.905	5	-.011	2	-.083	5	-.993	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
19		10	max	136.622	1	915.02	3	215.314	1	.011	2	.409	1	1.488	1
20			min	7.471	12	-662.807	1	-130.288	14	0	3	.017	12	-2.012	3
21		11	max	136.622	1	545.573	1	-7.526	12	.011	2	.174	1	.749	1
22			min	7.471	12	-752.332	3	-169.125	1	0	3	.006	12	-.993	3
23		12	max	136.622	1	428.338	1	-5.343	12	.011	2	.066	5	.154	1
24			min	7.471	12	-589.644	3	-122.937	1	0	3	-.004	1	-.173	3
25		13	max	136.622	1	311.104	1	-3.16	12	.011	2	.029	5	.448	3
26			min	7.471	12	-426.956	3	-76.749	1	0	3	-.126	1	-.298	1
27		14	max	136.622	1	193.87	1	-.977	12	.011	2	-.002	15	.871	3
28			min	7.471	12	-264.268	3	-32.977	4	0	3	-.192	1	-.606	1
29		15	max	136.622	1	76.635	1	15.628	1	.011	2	-.009	12	1.094	3
30			min	.73	15	-101.581	3	-22.089	5	0	3	-.201	1	-.772	1
31		16	max	136.622	1	61.107	3	61.817	1	.011	2	-.007	12	1.119	3
32			min	-11.136	5	-40.599	1	-18.711	5	0	3	-.154	1	-.794	1
33		17	max	136.622	1	223.795	3	108.005	1	.011	2	-.001	12	.945	3
34			min	-23.682	5	-157.833	1	-15.333	5	0	3	-.092	4	-.672	1
35		18	max	136.622	1	386.483	3	154.193	1	.011	2	.11	1	.572	3
36			min	-36.228	5	-275.068	1	-11.955	5	0	3	-.096	5	-.408	1
37		19	max	136.622	1	549.171	3	200.382	1	.011	2	.327	1	0	1
38			min	-48.775	5	-392.302	1	-8.577	5	0	3	-.108	5	0	3
39	M14	1	max	66.178	4	410.46	1	-10.2	12	.006	3	.369	1	0	4
40			min	3.106	12	-427.719	3	-206.123	1	-.008	2	.02	12	0	3
41		2	max	59.818	1	293.225	1	-8.017	12	.006	3	.196	4	.447	3
42			min	3.106	12	-303.883	3	-159.934	1	-.008	2	.009	12	-.43	1
43		3	max	59.818	1	175.991	1	-5.834	12	.006	3	.105	5	.743	3
44			min	3.106	12	-180.047	3	-113.746	1	-.008	2	-.022	1	-.717	1
45		4	max	59.818	1	58.756	1	-3.651	12	.006	3	.055	5	.887	3
46			min	3.106	12	-56.211	3	-67.557	1	-.008	2	-.133	1	-.86	1
47		5	max	59.818	1	67.625	3	-1.468	12	.006	3	.009	5	.88	3
48			min	1.292	15	-58.478	1	-41.596	4	-.008	2	-.187	1	-.86	1
49		6	max	59.818	1	191.46	3	24.819	1	.006	3	-.009	12	.722	3
50			min	-10.549	5	-175.712	1	-32.487	5	-.008	2	-.185	1	-.717	1
51		7	max	59.818	1	315.296	3	71.008	1	.006	3	-.007	12	.412	3
52			min	-23.095	5	-292.947	1	-29.109	5	-.008	2	-.126	1	-.431	1
53		8	max	59.818	1	439.132	3	117.196	1	.006	3	0	10	.004	9
54			min	-35.641	5	-410.181	1	-25.731	5	-.008	2	-.109	4	-.049	3
55		9	max	59.818	1	562.968	3	163.384	1	.006	3	.16	1	.572	1
56			min	-48.188	5	-527.415	1	-22.353	5	-.008	2	-.134	5	-.661	3
57		10	max	83.067	4	686.804	3	209.573	1	.008	2	.388	1	1.288	1
58			min	3.106	12	-644.65	1	-132.932	14	-.006	3	.016	12	-1.425	3
59		11	max	70.521	4	527.415	1	-7.265	12	.008	2	.197	4	.572	1
60			min	3.106	12	-562.968	3	-163.384	1	-.006	3	.006	12	-.661	3
61		12	max	59.818	1	410.181	1	-5.082	12	.008	2	.102	5	.004	9
62			min	3.106	12	-439.132	3	-117.196	1	-.006	3	-.011	1	-.049	3
63		13	max	59.818	1	292.947	1	-2.899	12	.008	2	.052	5	.412	3
64			min	3.106	12	-315.296	3	-71.008	1	-.006	3	-.126	1	-.431	1
65		14	max	59.818	1	175.712	1	-.715	12	.008	2	.006	5	.722	3
66			min	3.106	12	-191.46	3	-42.476	4	-.006	3	-.185	1	-.717	1
67		15	max	59.818	1	58.478	1	21.369	1	.008	2	-.009	12	.88	3
68			min	3.106	12	-67.625	3	-32.697	5	-.006	3	-.187	1	-.86	1
69		16	max	59.818	1	56.211	3	67.557	1	.008	2	-.005	12	.887	3
70			min	-6.282	5	-58.756	1	-29.319	5	-.006	3	-.133	1	-.86	1
71		17	max	59.818	1	180.047	3	113.746	1	.008	2	0	3	.743	3
72			min	-18.829	5	-175.991	1	-25.942	5	-.006	3	-.115	4	-.717	1
73		18	max	59.818	1	303.883	3	159.934	1	.008	2	.145	1	.447	3
74			min	-31.375	5	-293.225	1	-22.564	5	-.006	3	-.137	5	-.43	1
75		19	max	59.818	1	427.719	3	206.123	1	.008	2	.369	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
76			min	-43.922	5	-410.46	1	-19.186	5	-.006	3	-.163	5	0	3
77	M15	1	max	91.775	5	532.64	2	-10.164	12	.009	2	.369	1	0	2
78			min	-63.143	1	-231.135	3	-206.087	1	-.005	3	.02	12	0	12
79		2	max	79.229	5	379.226	2	-7.98	12	.009	2	.234	4	.242	3
80			min	-63.143	1	-165.578	3	-159.898	1	-.005	3	.009	12	-.557	2
81		3	max	66.683	5	225.812	2	-5.797	12	.009	2	.132	5	.405	3
82			min	-63.143	1	-100.021	3	-113.71	1	-.005	3	-.022	1	-.927	2
83		4	max	54.136	5	72.398	2	-3.614	12	.009	2	.071	5	.487	3
84			min	-63.143	1	-34.465	3	-67.522	1	-.005	3	-.133	1	-1.109	2
85		5	max	41.59	5	31.092	3	-1.431	12	.009	2	.015	5	.489	3
86			min	-63.143	1	-81.016	2	-50.446	4	-.005	3	-.187	1	-1.104	2
87		6	max	29.044	5	96.648	3	24.855	1	.009	2	-.009	12	.411	3
88			min	-63.143	1	-234.43	2	-41.298	5	-.005	3	-.185	1	-.911	2
89		7	max	16.497	5	162.205	3	71.044	1	.009	2	-.007	12	.253	3
90			min	-63.143	1	-387.844	2	-37.92	5	-.005	3	-.127	1	-.531	2
91		8	max	3.951	5	227.761	3	117.232	1	.009	2	0	10	.037	2
92			min	-63.143	1	-541.259	2	-34.542	5	-.005	3	-.136	4	0	15
93		9	max	-3.518	12	293.318	3	163.42	1	.009	2	.16	1	.792	2
94			min	-63.143	1	-694.673	2	-31.165	5	-.005	3	-.171	5	-.304	3
95		10	max	-3.518	12	358.875	3	209.609	1	.005	3	.388	1	1.735	2
96			min	-63.143	1	-848.087	2	-137.459	14	-.009	2	.016	12	-.703	3
97		11	max	-.564	15	694.673	2	-7.302	12	.005	3	.234	4	.792	2
98			min	-63.143	1	-293.318	3	-163.42	1	-.009	2	.006	12	-.304	3
99		12	max	-3.518	12	541.259	2	-5.119	12	.005	3	.129	5	.037	2
100			min	-63.143	1	-227.761	3	-117.232	1	-.009	2	-.011	1	0	15
101		13	max	-3.518	12	387.844	2	-2.935	12	.005	3	.068	5	.253	3
102			min	-63.143	1	-162.205	3	-71.044	1	-.009	2	-.127	1	-.531	2
103		14	max	-3.518	12	234.43	2	-.752	12	.005	3	.011	5	.411	3
104			min	-63.143	1	-96.648	3	-51.356	4	-.009	2	-.185	1	-.911	2
105		15	max	-3.518	12	81.016	2	21.333	1	.005	3	-.009	12	.489	3
106			min	-66.882	4	-31.092	3	-41.513	5	-.009	2	-.187	1	-1.104	2
107		16	max	-3.518	12	34.465	3	67.522	1	.005	3	-.006	12	.487	3
108			min	-79.428	4	-72.398	2	-38.135	5	-.009	2	-.133	1	-1.109	2
109		17	max	-3.518	12	100.021	3	113.71	1	.005	3	0	3	.405	3
110			min	-91.975	4	-225.812	2	-34.758	5	-.009	2	-.142	4	-.927	2
111		18	max	-3.518	12	165.578	3	159.898	1	.005	3	.145	1	.242	3
112			min	-104.521	4	-379.226	2	-31.38	5	-.009	2	-.176	5	-.557	2
113		19	max	-3.518	12	231.135	3	206.087	1	.005	3	.369	1	0	2
114			min	-117.067	4	-532.64	2	-28.002	5	-.009	2	-.212	5	0	5
115	M16	1	max	89.656	5	514.84	2	-9.822	12	.009	1	.328	1	0	2
116			min	-146.479	1	-218.531	3	-200.612	1	-.008	3	.017	12	0	3
117		2	max	77.109	5	361.426	2	-7.639	12	.009	1	.181	4	.227	3
118			min	-146.479	1	-152.974	3	-154.423	1	-.008	3	.007	12	-.535	2
119		3	max	64.563	5	208.012	2	-5.456	12	.009	1	.101	5	.374	3
120			min	-146.479	1	-87.417	3	-108.235	1	-.008	3	-.049	1	-.883	2
121		4	max	52.017	5	54.597	2	-3.273	12	.009	1	.054	5	.441	3
122			min	-146.479	1	-21.861	3	-62.047	1	-.008	3	-.153	1	-1.044	2
123		5	max	39.47	5	43.696	3	-1.09	12	.009	1	.011	5	.427	3
124			min	-146.479	1	-98.817	2	-37.801	4	-.008	3	-.201	1	-1.017	2
125		6	max	26.924	5	109.252	3	30.33	1	.009	1	-.009	12	.334	3
126			min	-146.479	1	-252.231	2	-30.12	5	-.008	3	-.192	1	-.802	2
127		7	max	14.378	5	174.809	3	76.518	1	.009	1	-.007	12	.16	3
128			min	-146.479	1	-405.645	2	-26.742	5	-.008	3	-.127	1	-.4	2
129		8	max	1.831	5	240.365	3	122.707	1	.009	1	0	10	.189	2
130			min	-146.479	1	-559.059	2	-23.364	5	-.008	3	-.096	4	-.093	3
131		9	max	-6.999	15	305.922	3	168.895	1	.009	1	.173	1	.966	2
132			min	-146.479	1	-712.473	2	-19.987	5	-.008	3	-.12	5	-.427	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
133		10	max	-7.767	12	371.479	3	215.084	1	.008	3	.408	1	1.931	2
134			min	-146.479	1	-865.887	2	-134.873	14	-.009	1	.017	12	-.841	3
135		11	max	-6.929	15	712.473	2	-7.643	12	.008	3	.188	4	.966	2
136			min	-146.479	1	-305.922	3	-168.895	1	-.009	1	.007	12	-.427	3
137		12	max	-7.767	12	559.059	2	-5.46	12	.008	3	.093	4	.189	2
138			min	-146.479	1	-240.365	3	-122.707	1	-.009	1	-.005	1	-.093	3
139		13	max	-7.767	12	405.645	2	-3.277	12	.008	3	.044	5	.16	3
140			min	-146.479	1	-174.809	3	-76.518	1	-.009	1	-.127	1	-.4	2
141		14	max	-7.767	12	252.231	2	-1.094	12	.008	3	0	15	.334	3
142			min	-146.479	1	-109.252	3	-42.101	4	-.009	1	-.192	1	-.802	2
143		15	max	-7.767	12	98.817	2	15.858	1	.008	3	-.009	12	.427	3
144			min	-146.479	1	-43.696	3	-31.151	5	-.009	1	-.201	1	-1.017	2
145		16	max	-7.767	12	21.861	3	62.047	1	.008	3	-.007	12	.441	3
146			min	-146.479	1	-54.597	2	-27.773	5	-.009	1	-.153	1	-1.044	2
147		17	max	-7.767	12	87.417	3	108.235	1	.008	3	-.001	12	.374	3
148			min	-146.479	1	-208.012	2	-24.395	5	-.009	1	-.121	4	-.883	2
149		18	max	-7.767	12	152.974	3	154.423	1	.008	3	.111	1	.227	3
150			min	-146.479	1	-361.426	2	-21.018	5	-.009	1	-.136	5	-.535	2
151		19	max	-7.767	12	218.531	3	200.612	1	.008	3	.328	1	0	2
152			min	-146.522	4	-514.84	2	-17.64	5	-.009	1	-.16	5	0	5
153	M2	1	max	898.513	1	1.957	4	.629	1	0	12	0	3	0	1
154			min	-1014.41	3	.473	15	-38.097	4	0	4	0	1	0	1
155		2	max	898.989	1	1.871	4	.629	1	0	12	0	1	0	15
156			min	-1014.054	3	.453	15	-38.514	4	0	4	-.012	4	0	4
157		3	max	899.465	1	1.785	4	.629	1	0	12	0	1	0	15
158			min	-1013.697	3	.432	15	-38.93	4	0	4	-.025	4	-.001	4
159		4	max	899.941	1	1.7	4	.629	1	0	12	0	1	0	15
160			min	-1013.34	3	.412	15	-39.346	4	0	4	-.038	4	-.002	4
161		5	max	900.416	1	1.614	4	.629	1	0	12	0	1	0	15
162			min	-1012.983	3	.392	15	-39.763	4	0	4	-.05	4	-.002	4
163		6	max	900.892	1	1.529	4	.629	1	0	12	.001	1	0	15
164			min	-1012.626	3	.372	15	-40.179	4	0	4	-.063	4	-.003	4
165		7	max	901.368	1	1.443	4	.629	1	0	12	.001	1	0	15
166			min	-1012.27	3	.352	15	-40.595	4	0	4	-.076	4	-.003	4
167		8	max	901.844	1	1.357	4	.629	1	0	12	.001	1	0	15
168			min	-1011.913	3	.332	15	-41.012	4	0	4	-.09	4	-.004	4
169		9	max	902.319	1	1.272	4	.629	1	0	12	.002	1	-.001	15
170			min	-1011.556	3	.312	15	-41.428	4	0	4	-.103	4	-.004	4
171		10	max	902.795	1	1.186	4	.629	1	0	12	.002	1	-.001	15
172			min	-1011.199	3	.292	15	-41.844	4	0	4	-.116	4	-.005	4
173		11	max	903.271	1	1.101	4	.629	1	0	12	.002	1	-.001	15
174			min	-1010.842	3	.272	15	-42.261	4	0	4	-.13	4	-.005	4
175		12	max	903.747	1	1.015	4	.629	1	0	12	.002	1	-.001	15
176			min	-1010.486	3	.246	12	-42.677	4	0	4	-.144	4	-.005	4
177		13	max	904.222	1	.93	4	.629	1	0	12	.002	1	-.001	15
178			min	-1010.129	3	.213	12	-43.093	4	0	4	-.158	4	-.006	4
179		14	max	904.698	1	.844	4	.629	1	0	12	.003	1	-.001	15
180			min	-1009.772	3	.179	12	-43.51	4	0	4	-.172	4	-.006	4
181		15	max	905.174	1	.758	4	.629	1	0	12	.003	1	-.002	15
182			min	-1009.415	3	.146	12	-43.926	4	0	4	-.186	4	-.006	4
183		16	max	905.65	1	.673	4	.629	1	0	12	.003	1	-.002	15
184			min	-1009.058	3	.113	12	-44.342	4	0	4	-.2	4	-.006	4
185		17	max	906.125	1	.604	2	.629	1	0	12	.003	1	-.002	15
186			min	-1008.701	3	.079	12	-44.759	4	0	4	-.215	4	-.007	4
187		18	max	906.601	1	.537	2	.629	1	0	12	.003	1	-.002	15
188			min	-1008.345	3	.046	3	-45.175	4	0	4	-.229	4	-.007	4
189		19	max	907.077	1	.47	2	.629	1	0	12	.004	1	-.002	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
190			min	-1007.988	3	-.004	3	-45.592	4	0	4	-.244	4	-.007	4
191	M3	1	max	501.131	2	7.8	4	5.911	4	0	12	0	1	.007	4
192			min	-649.373	3	1.843	15	.015	12	0	4	-.035	4	.002	15
193		2	max	500.961	2	7.035	4	6.448	4	0	12	0	1	.004	4
194			min	-649.501	3	1.664	15	.015	12	0	4	-.033	4	0	12
195		3	max	500.79	2	6.271	4	6.985	4	0	12	0	1	.002	2
196			min	-649.628	3	1.484	15	.015	12	0	4	-.03	4	0	3
197		4	max	500.62	2	5.507	4	7.522	4	0	12	0	1	0	15
198			min	-649.756	3	1.304	15	.015	12	0	4	-.027	4	-.002	3
199		5	max	500.45	2	4.742	4	8.059	4	0	12	.001	1	0	15
200			min	-649.884	3	1.125	15	.015	12	0	4	-.024	4	-.004	6
201		6	max	500.279	2	3.978	4	8.596	4	0	12	.001	1	-.001	15
202			min	-650.012	3	.945	15	.015	12	0	4	-.02	4	-.005	6
203		7	max	500.109	2	3.213	4	9.133	4	0	12	.001	1	-.002	15
204			min	-650.139	3	.765	15	.015	12	0	4	-.016	5	-.007	6
205		8	max	499.939	2	2.449	4	9.67	4	0	12	.001	1	-.002	15
206			min	-650.267	3	.586	15	.015	12	0	4	-.013	5	-.008	6
207		9	max	499.768	2	1.684	4	10.207	4	0	12	.001	1	-.002	15
208			min	-650.395	3	.406	15	.015	12	0	4	-.009	5	-.009	6
209		10	max	499.598	2	.92	4	10.744	4	0	12	.002	1	-.002	15
210			min	-650.523	3	.226	15	.015	12	0	4	-.004	5	-.009	6
211		11	max	499.428	2	.235	2	11.28	4	0	12	.002	1	-.002	15
212			min	-650.65	3	-.101	3	.015	12	0	4	0	12	-.01	6
213		12	max	499.257	2	-.133	15	11.817	4	0	12	.006	4	-.002	15
214			min	-650.778	3	-.61	6	.015	12	0	4	0	12	-.01	6
215		13	max	499.087	2	-.313	15	12.354	4	0	12	.011	4	-.002	15
216			min	-650.906	3	-1.374	6	.015	12	0	4	0	12	-.009	6
217		14	max	498.917	2	-.493	15	12.891	4	0	12	.016	4	-.002	15
218			min	-651.034	3	-2.139	6	.015	12	0	4	0	12	-.008	6
219		15	max	498.746	2	-.672	15	13.428	4	0	12	.021	4	-.002	15
220			min	-651.161	3	-2.903	6	.015	12	0	4	0	12	-.007	6
221		16	max	498.576	2	-.852	15	13.965	4	0	12	.027	4	-.001	15
222			min	-651.289	3	-3.668	6	.015	12	0	4	0	12	-.006	6
223		17	max	498.406	2	-1.032	15	14.502	4	0	12	.033	4	-.001	15
224			min	-651.417	3	-4.432	6	.015	12	0	4	0	12	-.004	6
225		18	max	498.235	2	-1.211	15	15.039	4	0	12	.039	4	0	15
226			min	-651.545	3	-5.197	6	.015	12	0	4	0	12	-.002	6
227		19	max	498.065	2	-1.391	15	15.576	4	0	12	.046	4	0	1
228			min	-651.673	3	-5.961	6	.015	12	0	4	0	12	0	1
229	M4	1	max	1056.644	1	0	1	-.759	12	0	1	.038	4	0	1
230			min	-28.54	5	0	1	-314.267	4	0	1	0	12	0	1
231		2	max	1056.815	1	0	1	-.759	12	0	1	.002	4	0	1
232			min	-28.46	5	0	1	-314.415	4	0	1	0	12	0	1
233		3	max	1056.985	1	0	1	-.759	12	0	1	0	12	0	1
234			min	-28.381	5	0	1	-314.562	4	0	1	-.034	4	0	1
235		4	max	1057.155	1	0	1	-.759	12	0	1	0	12	0	1
236			min	-28.301	5	0	1	-314.71	4	0	1	-.071	4	0	1
237		5	max	1057.326	1	0	1	-.759	12	0	1	0	12	0	1
238			min	-28.222	5	0	1	-314.858	4	0	1	-.107	4	0	1
239		6	max	1057.496	1	0	1	-.759	12	0	1	0	12	0	1
240			min	-28.142	5	0	1	-315.005	4	0	1	-.143	4	0	1
241		7	max	1057.666	1	0	1	-.759	12	0	1	0	12	0	1
242			min	-28.063	5	0	1	-315.153	4	0	1	-.179	4	0	1
243		8	max	1057.837	1	0	1	-.759	12	0	1	0	12	0	1
244			min	-27.983	5	0	1	-315.3	4	0	1	-.215	4	0	1
245		9	max	1058.007	1	0	1	-.759	12	0	1	0	12	0	1
246			min	-27.904	5	0	1	-315.448	4	0	1	-.251	4	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
247		10	max	1058.177	1	0	1	-.759	12	0	1	0	12	0	1
248			min	-27.824	5	0	1	-315.596	4	0	1	-.288	4	0	1
249		11	max	1058.348	1	0	1	-.759	12	0	1	0	12	0	1
250			min	-27.745	5	0	1	-315.743	4	0	1	-.324	4	0	1
251		12	max	1058.518	1	0	1	-.759	12	0	1	0	12	0	1
252			min	-27.666	5	0	1	-315.891	4	0	1	-.36	4	0	1
253		13	max	1058.689	1	0	1	-.759	12	0	1	0	12	0	1
254			min	-27.586	5	0	1	-316.039	4	0	1	-.396	4	0	1
255		14	max	1058.859	1	0	1	-.759	12	0	1	-.001	12	0	1
256			min	-27.507	5	0	1	-316.186	4	0	1	-.433	4	0	1
257		15	max	1059.029	1	0	1	-.759	12	0	1	-.001	12	0	1
258			min	-27.427	5	0	1	-316.334	4	0	1	-.469	4	0	1
259		16	max	1059.2	1	0	1	-.759	12	0	1	-.001	12	0	1
260			min	-27.348	5	0	1	-316.481	4	0	1	-.505	4	0	1
261		17	max	1059.37	1	0	1	-.759	12	0	1	-.001	12	0	1
262			min	-27.268	5	0	1	-316.629	4	0	1	-.542	4	0	1
263		18	max	1059.54	1	0	1	-.759	12	0	1	-.001	12	0	1
264			min	-27.189	5	0	1	-316.777	4	0	1	-.578	4	0	1
265		19	max	1059.711	1	0	1	-.759	12	0	1	-.001	12	0	1
266			min	-27.109	5	0	1	-316.924	4	0	1	-.614	4	0	1
267	M6	1	max	2905.381	1	2.124	2	0	1	0	1	0	4	0	1
268			min	-3336.998	3	.304	12	-38.512	4	0	4	0	1	0	1
269		2	max	2905.857	1	2.058	2	0	1	0	1	0	1	0	12
270			min	-3336.641	3	.271	12	-38.929	4	0	4	-.013	4	0	2
271		3	max	2906.332	1	1.991	2	0	1	0	1	0	1	0	12
272			min	-3336.284	3	.237	12	-39.345	4	0	4	-.025	4	-.001	2
273		4	max	2906.808	1	1.924	2	0	1	0	1	0	1	0	12
274			min	-3335.928	3	.204	12	-39.761	4	0	4	-.038	4	-.002	2
275		5	max	2907.284	1	1.858	2	0	1	0	1	0	1	0	12
276			min	-3335.571	3	.171	12	-40.178	4	0	4	-.051	4	-.003	2
277		6	max	2907.76	1	1.791	2	0	1	0	1	0	1	0	12
278			min	-3335.214	3	.13	3	-40.594	4	0	4	-.064	4	-.003	2
279		7	max	2908.235	1	1.724	2	0	1	0	1	0	1	0	12
280			min	-3334.857	3	.08	3	-41.01	4	0	4	-.077	4	-.004	2
281		8	max	2908.711	1	1.658	2	0	1	0	1	0	1	0	12
282			min	-3334.5	3	.03	3	-41.427	4	0	4	-.091	4	-.004	2
283		9	max	2909.187	1	1.591	2	0	1	0	1	0	1	0	12
284			min	-3334.144	3	-.02	3	-41.843	4	0	4	-.104	4	-.005	2
285		10	max	2909.663	1	1.524	2	0	1	0	1	0	1	0	12
286			min	-3333.787	3	-.07	3	-42.259	4	0	4	-.118	4	-.005	2
287		11	max	2910.138	1	1.458	2	0	1	0	1	0	1	0	3
288			min	-3333.43	3	-.12	3	-42.676	4	0	4	-.131	4	-.006	2
289		12	max	2910.614	1	1.391	2	0	1	0	1	0	1	0	3
290			min	-3333.073	3	-.17	3	-43.092	4	0	4	-.145	4	-.006	2
291		13	max	2911.09	1	1.324	2	0	1	0	1	0	1	0	3
292			min	-3332.716	3	-.22	3	-43.508	4	0	4	-.159	4	-.007	2
293		14	max	2911.566	1	1.258	2	0	1	0	1	0	1	0	3
294			min	-3332.359	3	-.27	3	-43.925	4	0	4	-.174	4	-.007	2
295		15	max	2912.041	1	1.191	2	0	1	0	1	0	1	0	3
296			min	-3332.003	3	-.32	3	-44.341	4	0	4	-.188	4	-.008	2
297		16	max	2912.517	1	1.124	2	0	1	0	1	0	1	0	3
298			min	-3331.646	3	-.37	3	-44.757	4	0	4	-.202	4	-.008	2
299		17	max	2912.993	1	1.057	2	0	1	0	1	0	1	0	3
300			min	-3331.289	3	-.42	3	-45.174	4	0	4	-.217	4	-.008	2
301		18	max	2913.469	1	.991	2	0	1	0	1	0	1	0	3
302			min	-3330.932	3	-.47	3	-45.59	4	0	4	-.231	4	-.009	2
303		19	max	2913.944	1	.924	2	0	1	0	1	0	1	0	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
304			min	-3330.575	3	-.52	3	-46.006	4	0	4	-.246	4	-.009	2
305	M7	1	max	1994.642	2	7.814	6	5.581	4	0	1	0	1	.009	2
306			min	-2044.86	3	1.834	15	0	1	0	4	-.036	4	0	3
307		2	max	1994.472	2	7.049	6	6.118	4	0	1	0	1	.006	2
308			min	-2044.988	3	1.655	15	0	1	0	4	-.033	4	-.002	3
309		3	max	1994.301	2	6.285	6	6.655	4	0	1	0	1	.004	2
310			min	-2045.116	3	1.475	15	0	1	0	4	-.03	4	-.003	3
311		4	max	1994.131	2	5.521	6	7.192	4	0	1	0	1	.002	2
312			min	-2045.243	3	1.295	15	0	1	0	4	-.028	4	-.005	3
313		5	max	1993.961	2	4.756	6	7.729	4	0	1	0	1	0	2
314			min	-2045.371	3	1.116	15	0	1	0	4	-.024	4	-.006	3
315		6	max	1993.79	2	3.992	6	8.266	4	0	1	0	1	-.001	15
316			min	-2045.499	3	.936	15	0	1	0	4	-.021	4	-.006	3
317		7	max	1993.62	2	3.227	6	8.803	4	0	1	0	1	-.002	15
318			min	-2045.627	3	.756	15	0	1	0	4	-.018	4	-.007	3
319		8	max	1993.45	2	2.463	6	9.34	4	0	1	0	1	-.002	15
320			min	-2045.754	3	.576	15	0	1	0	4	-.014	4	-.008	4
321		9	max	1993.279	2	1.778	2	9.877	4	0	1	0	1	-.002	15
322			min	-2045.882	3	.301	12	0	1	0	4	-.01	4	-.009	4
323		10	max	1993.109	2	1.182	2	10.414	4	0	1	0	1	-.002	15
324			min	-2046.01	3	-.054	3	0	1	0	4	-.006	4	-.009	4
325		11	max	1992.939	2	.586	2	10.951	4	0	1	0	1	-.002	15
326			min	-2046.138	3	-.501	3	0	1	0	4	-.001	5	-.01	4
327		12	max	1992.768	2	-.009	2	11.488	4	0	1	.004	4	-.002	15
328			min	-2046.265	3	-.948	3	0	1	0	4	0	1	-.01	4
329		13	max	1992.598	2	-.322	15	12.025	4	0	1	.009	4	-.002	15
330			min	-2046.393	3	-1.395	3	0	1	0	4	0	1	-.009	4
331		14	max	1992.428	2	-.502	15	12.562	4	0	1	.014	4	-.002	15
332			min	-2046.521	3	-2.124	4	0	1	0	4	0	1	-.008	4
333		15	max	1992.257	2	-.681	15	13.099	4	0	1	.019	4	-.002	15
334			min	-2046.649	3	-2.888	4	0	1	0	4	0	1	-.007	4
335		16	max	1992.087	2	-.861	15	13.635	4	0	1	.025	4	-.001	15
336			min	-2046.776	3	-3.653	4	0	1	0	4	0	1	-.006	4
337		17	max	1991.917	2	-1.041	15	14.172	4	0	1	.03	4	-.001	15
338			min	-2046.904	3	-4.417	4	0	1	0	4	0	1	-.004	4
339		18	max	1991.746	2	-1.22	15	14.709	4	0	1	.036	4	0	15
340			min	-2047.032	3	-5.182	4	0	1	0	4	0	1	-.002	4
341		19	max	1991.576	2	-1.4	15	15.246	4	0	1	.043	4	0	1
342			min	-2047.16	3	-5.946	4	0	1	0	4	0	1	0	1
343	M8	1	max	2689.099	1	0	1	0	1	0	1	.035	4	0	1
344			min	-91.484	3	0	1	-302.952	4	0	1	0	1	0	1
345		2	max	2689.269	1	0	1	0	1	0	1	0	5	0	1
346			min	-91.357	3	0	1	-303.099	4	0	1	0	1	0	1
347		3	max	2689.44	1	0	1	0	1	0	1	0	1	0	1
348			min	-91.229	3	0	1	-303.247	4	0	1	-.034	4	0	1
349		4	max	2689.61	1	0	1	0	1	0	1	0	1	0	1
350			min	-91.101	3	0	1	-303.395	4	0	1	-.069	4	0	1
351		5	max	2689.78	1	0	1	0	1	0	1	0	1	0	1
352			min	-90.973	3	0	1	-303.542	4	0	1	-.104	4	0	1
353		6	max	2689.951	1	0	1	0	1	0	1	0	1	0	1
354			min	-90.846	3	0	1	-303.69	4	0	1	-.139	4	0	1
355		7	max	2690.121	1	0	1	0	1	0	1	0	1	0	1
356			min	-90.718	3	0	1	-303.837	4	0	1	-.174	4	0	1
357		8	max	2690.292	1	0	1	0	1	0	1	0	1	0	1
358			min	-90.59	3	0	1	-303.985	4	0	1	-.208	4	0	1
359		9	max	2690.462	1	0	1	0	1	0	1	0	1	0	1
360			min	-90.462	3	0	1	-304.133	4	0	1	-.243	4	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
361		10	max	2690.632	1	0	1	0	1	0	1	0	1	0	1
362			min	-90.335	3	0	1	-304.28	4	0	1	-.278	4	0	1
363		11	max	2690.803	1	0	1	0	1	0	1	0	1	0	1
364			min	-90.207	3	0	1	-304.428	4	0	1	-.313	4	0	1
365		12	max	2690.973	1	0	1	0	1	0	1	0	1	0	1
366			min	-90.079	3	0	1	-304.576	4	0	1	-.348	4	0	1
367		13	max	2691.143	1	0	1	0	1	0	1	0	1	0	1
368			min	-89.951	3	0	1	-304.723	4	0	1	-.383	4	0	1
369		14	max	2691.314	1	0	1	0	1	0	1	0	1	0	1
370			min	-89.824	3	0	1	-304.871	4	0	1	-.418	4	0	1
371		15	max	2691.484	1	0	1	0	1	0	1	0	1	0	1
372			min	-89.696	3	0	1	-305.019	4	0	1	-.453	4	0	1
373		16	max	2691.654	1	0	1	0	1	0	1	0	1	0	1
374			min	-89.568	3	0	1	-305.166	4	0	1	-.488	4	0	1
375		17	max	2691.825	1	0	1	0	1	0	1	0	1	0	1
376			min	-89.44	3	0	1	-305.314	4	0	1	-.523	4	0	1
377		18	max	2691.995	1	0	1	0	1	0	1	0	1	0	1
378			min	-89.313	3	0	1	-305.461	4	0	1	-.558	4	0	1
379		19	max	2692.165	1	0	1	0	1	0	1	0	1	0	1
380			min	-89.185	3	0	1	-305.609	4	0	1	-.593	4	0	1
381	M10	1	max	898.513	1	1.9	6	-.031	12	0	1	0	4	0	1
382			min	-1014.41	3	.435	15	-38.484	4	0	5	0	3	0	1
383		2	max	898.989	1	1.815	6	-.031	12	0	1	0	10	0	15
384			min	-1014.054	3	.415	15	-38.9	4	0	5	-.013	4	0	6
385		3	max	899.465	1	1.729	6	-.031	12	0	1	0	12	0	15
386			min	-1013.697	3	.395	15	-39.317	4	0	5	-.025	4	-.001	6
387		4	max	899.941	1	1.644	6	-.031	12	0	1	0	12	0	15
388			min	-1013.34	3	.375	15	-39.733	4	0	5	-.038	4	-.002	6
389		5	max	900.416	1	1.558	6	-.031	12	0	1	0	12	0	15
390			min	-1012.983	3	.354	15	-40.15	4	0	5	-.051	4	-.002	6
391		6	max	900.892	1	1.472	6	-.031	12	0	1	0	12	0	15
392			min	-1012.626	3	.334	15	-40.566	4	0	5	-.064	4	-.003	6
393		7	max	901.368	1	1.387	6	-.031	12	0	1	0	12	0	15
394			min	-1012.27	3	.314	15	-40.982	4	0	5	-.077	4	-.003	6
395		8	max	901.844	1	1.301	6	-.031	12	0	1	0	12	0	15
396			min	-1011.913	3	.294	15	-41.399	4	0	5	-.091	4	-.004	6
397		9	max	902.319	1	1.216	6	-.031	12	0	1	0	12	0	15
398			min	-1011.556	3	.274	15	-41.815	4	0	5	-.104	4	-.004	6
399		10	max	902.795	1	1.13	6	-.031	12	0	1	0	12	-.001	15
400			min	-1011.199	3	.254	15	-42.231	4	0	5	-.118	4	-.004	6
401		11	max	903.271	1	1.045	6	-.031	12	0	1	0	12	-.001	15
402			min	-1010.842	3	.234	15	-42.648	4	0	5	-.131	4	-.005	6
403		12	max	903.747	1	.959	6	-.031	12	0	1	0	12	-.001	15
404			min	-1010.486	3	.214	15	-43.064	4	0	5	-.145	4	-.005	6
405		13	max	904.222	1	.873	6	-.031	12	0	1	0	12	-.001	15
406			min	-1010.129	3	.193	15	-43.48	4	0	5	-.159	4	-.005	6
407		14	max	904.698	1	.804	2	-.031	12	0	1	0	12	-.001	15
408			min	-1009.772	3	.173	15	-43.897	4	0	5	-.173	4	-.006	6
409		15	max	905.174	1	.737	2	-.031	12	0	1	0	12	-.001	15
410			min	-1009.415	3	.146	12	-44.313	4	0	5	-.188	4	-.006	6
411		16	max	905.65	1	.671	2	-.031	12	0	1	0	12	-.001	15
412			min	-1009.058	3	.113	12	-44.729	4	0	5	-.202	4	-.006	6
413		17	max	906.125	1	.604	2	-.031	12	0	1	0	12	-.001	15
414			min	-1008.701	3	.079	12	-45.146	4	0	5	-.217	4	-.006	6
415		18	max	906.601	1	.537	2	-.031	12	0	1	0	12	-.001	15
416			min	-1008.345	3	.046	3	-45.562	4	0	5	-.231	4	-.006	6
417		19	max	907.077	1	.47	2	-.031	12	0	1	0	12	-.001	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
418			min	-1007.988	3	-.004	3	-45.978	4	0	5	-.246	4	-.007	6
419	M11	1	max	501.131	2	7.756	6	5.734	4	0	1	0	12	.007	6
420			min	-649.373	3	1.814	15	-.289	1	0	4	-.036	4	.001	15
421		2	max	500.961	2	6.992	6	6.27	4	0	1	0	12	.004	2
422			min	-649.501	3	1.634	15	-.289	1	0	4	-.033	4	0	12
423		3	max	500.79	2	6.227	6	6.807	4	0	1	0	12	.002	2
424			min	-649.628	3	1.455	15	-.289	1	0	4	-.03	4	0	3
425		4	max	500.62	2	5.463	6	7.344	4	0	1	0	12	0	2
426			min	-649.756	3	1.275	15	-.289	1	0	4	-.027	4	-.002	3
427		5	max	500.45	2	4.699	6	7.881	4	0	1	0	12	0	15
428			min	-649.884	3	1.095	15	-.289	1	0	4	-.024	4	-.004	4
429		6	max	500.279	2	3.934	6	8.418	4	0	1	0	12	-.001	15
430			min	-650.012	3	.916	15	-.289	1	0	4	-.021	4	-.006	4
431		7	max	500.109	2	3.17	6	8.955	4	0	1	0	12	-.002	15
432			min	-650.139	3	.736	15	-.289	1	0	4	-.017	4	-.007	4
433		8	max	499.939	2	2.405	6	9.492	4	0	1	0	12	-.002	15
434			min	-650.267	3	.556	15	-.289	1	0	4	-.013	4	-.008	4
435		9	max	499.768	2	1.641	6	10.029	4	0	1	0	12	-.002	15
436			min	-650.395	3	.377	15	-.289	1	0	4	-.009	4	-.009	4
437		10	max	499.598	2	.876	6	10.566	4	0	1	0	12	-.002	15
438			min	-650.523	3	.197	15	-.289	1	0	4	-.005	4	-.01	4
439		11	max	499.428	2	.235	2	11.103	4	0	1	0	15	-.002	15
440			min	-650.65	3	-.101	3	-.289	1	0	4	-.002	1	-.01	4
441		12	max	499.257	2	-.163	15	11.64	4	0	1	.005	5	-.002	15
442			min	-650.778	3	-.653	4	-.289	1	0	4	-.002	1	-.01	4
443		13	max	499.087	2	-.342	15	12.177	4	0	1	.01	5	-.002	15
444			min	-650.906	3	-1.418	4	-.289	1	0	4	-.002	1	-.009	4
445		14	max	498.917	2	-.522	15	12.714	4	0	1	.015	5	-.002	15
446			min	-651.034	3	-2.182	4	-.289	1	0	4	-.002	1	-.009	4
447		15	max	498.746	2	-.702	15	13.251	4	0	1	.02	5	-.002	15
448			min	-651.161	3	-2.947	4	-.289	1	0	4	-.002	1	-.007	4
449		16	max	498.576	2	-.881	15	13.788	4	0	1	.026	5	-.001	15
450			min	-651.289	3	-3.711	4	-.289	1	0	4	-.002	1	-.006	4
451		17	max	498.406	2	-1.061	15	14.325	4	0	1	.032	5	-.001	15
452			min	-651.417	3	-4.476	4	-.289	1	0	4	-.002	1	-.004	4
453		18	max	498.235	2	-1.241	15	14.862	4	0	1	.038	5	0	15
454			min	-651.545	3	-5.24	4	-.289	1	0	4	-.003	1	-.002	4
455		19	max	498.065	2	-1.42	15	15.399	4	0	1	.044	5	0	1
456			min	-651.673	3	-6.005	4	-.289	1	0	4	-.003	1	0	1
457	M12	1	max	1056.644	1	0	1	14.398	1	0	1	.036	5	0	1
458			min	1.533	3	0	1	-305.39	4	0	1	-.002	1	0	1
459		2	max	1056.815	1	0	1	14.398	1	0	1	.002	5	0	1
460			min	1.661	3	0	1	-305.537	4	0	1	0	1	0	1
461		3	max	1056.985	1	0	1	14.398	1	0	1	.001	1	0	1
462			min	1.788	3	0	1	-305.685	4	0	1	-.034	4	0	1
463		4	max	1057.155	1	0	1	14.398	1	0	1	.003	1	0	1
464			min	1.916	3	0	1	-305.832	4	0	1	-.069	4	0	1
465		5	max	1057.326	1	0	1	14.398	1	0	1	.004	1	0	1
466			min	2.044	3	0	1	-305.98	4	0	1	-.104	4	0	1
467		6	max	1057.496	1	0	1	14.398	1	0	1	.006	1	0	1
468			min	2.172	3	0	1	-306.128	4	0	1	-.139	4	0	1
469		7	max	1057.666	1	0	1	14.398	1	0	1	.008	1	0	1
470			min	2.3	3	0	1	-306.275	4	0	1	-.174	4	0	1
471		8	max	1057.837	1	0	1	14.398	1	0	1	.009	1	0	1
472			min	2.427	3	0	1	-306.423	4	0	1	-.209	4	0	1
473		9	max	1058.007	1	0	1	14.398	1	0	1	.011	1	0	1
474			min	2.555	3	0	1	-306.571	4	0	1	-.245	4	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
475		10	max	1058.177	1	0	1	14.398	1	0	1	.013	1	0	1
476			min	2.683	3	0	1	-306.718	4	0	1	-.28	4	0	1
477		11	max	1058.348	1	0	1	14.398	1	0	1	.014	1	0	1
478			min	2.811	3	0	1	-306.866	4	0	1	-.315	4	0	1
479		12	max	1058.518	1	0	1	14.398	1	0	1	.016	1	0	1
480			min	2.938	3	0	1	-307.014	4	0	1	-.35	4	0	1
481		13	max	1058.689	1	0	1	14.398	1	0	1	.018	1	0	1
482			min	3.066	3	0	1	-307.161	4	0	1	-.386	4	0	1
483		14	max	1058.859	1	0	1	14.398	1	0	1	.019	1	0	1
484			min	3.194	3	0	1	-307.309	4	0	1	-.421	4	0	1
485		15	max	1059.029	1	0	1	14.398	1	0	1	.021	1	0	1
486			min	3.322	3	0	1	-307.456	4	0	1	-.456	4	0	1
487		16	max	1059.2	1	0	1	14.398	1	0	1	.023	1	0	1
488			min	3.449	3	0	1	-307.604	4	0	1	-.491	4	0	1
489		17	max	1059.37	1	0	1	14.398	1	0	1	.024	1	0	1
490			min	3.577	3	0	1	-307.752	4	0	1	-.527	4	0	1
491		18	max	1059.54	1	0	1	14.398	1	0	1	.026	1	0	1
492			min	3.705	3	0	1	-307.899	4	0	1	-.562	4	0	1
493		19	max	1059.711	1	0	1	14.398	1	0	1	.028	1	0	1
494			min	3.833	3	0	1	-308.047	4	0	1	-.598	4	0	1
495	M1	1	max	200.388	1	549.146	3	48.742	5	0	1	.327	1	0	3
496			min	-8.577	5	-390.964	1	-136.43	1	0	3	-.108	5	-.011	2
497		2	max	201.104	1	548.215	3	49.984	5	0	1	.255	1	.196	1
498			min	-8.243	5	-392.205	1	-136.43	1	0	3	-.082	5	-.289	3
499		3	max	397.085	3	437.582	1	14.133	5	0	3	.183	1	.393	1
500			min	-232.453	2	-394.656	3	-136.086	1	0	1	-.056	5	-.566	3
501		4	max	397.622	3	436.342	1	15.375	5	0	3	.111	1	.163	1
502			min	-231.737	2	-395.587	3	-136.086	1	0	1	-.048	5	-.358	3
503		5	max	398.16	3	435.101	1	16.616	5	0	3	.039	1	-.003	15
504			min	-231.021	2	-396.517	3	-136.086	1	0	1	-.04	5	-.149	3
505		6	max	398.697	3	433.861	1	17.857	5	0	3	-.002	12	.061	3
506			min	-230.305	2	-397.448	3	-136.086	1	0	1	-.038	4	-.307	2
507		7	max	399.234	3	432.62	1	19.099	5	0	3	-.006	12	.27	3
508			min	-229.589	2	-398.378	3	-136.086	1	0	1	-.104	1	-.528	2
509		8	max	399.771	3	431.38	1	20.34	5	0	3	-.007	15	.481	3
510			min	-228.872	2	-399.308	3	-136.086	1	0	1	-.176	1	-.753	1
511		9	max	415.682	3	38.862	2	65.383	5	0	9	.102	1	.562	3
512			min	-141.993	2	.375	15	-195.942	1	0	3	-.148	5	-.859	1
513		10	max	416.219	3	37.622	2	66.625	5	0	9	0	12	.547	3
514			min	-141.277	2	0	15	-195.942	1	0	3	-.115	4	-.878	2
515		11	max	416.756	3	36.381	2	67.866	5	0	9	-.006	12	.532	3
516			min	-140.561	2	-1.527	4	-195.942	1	0	3	-.105	1	-.897	2
517		12	max	432.607	3	259.792	3	170.407	5	0	2	.174	1	.463	3
518			min	-78.626	10	-497.179	2	-132.892	1	0	3	-.232	5	-.795	2
519		13	max	433.144	3	258.861	3	171.649	5	0	2	.104	1	.326	3
520			min	-78.029	10	-498.419	2	-132.892	1	0	3	-.142	5	-.533	2
521		14	max	433.682	3	257.931	3	172.89	5	0	2	.034	1	.19	3
522			min	-77.432	10	-499.66	2	-132.892	1	0	3	-.051	5	-.278	1
523		15	max	434.219	3	257	3	174.132	5	0	2	.04	5	.054	3
524			min	-76.835	10	-500.9	2	-132.892	1	0	3	-.037	1	-.027	1
525		16	max	434.756	3	256.07	3	175.373	5	0	2	.132	5	.259	2
526			min	-76.238	10	-502.141	2	-132.892	1	0	3	-.107	1	-.081	3
527		17	max	435.293	3	255.14	3	176.615	5	0	2	.225	5	.524	2
528			min	-75.641	10	-503.381	2	-132.892	1	0	3	-.177	1	-.216	3
529		18	max	17.305	5	516.585	2	-7.768	12	0	5	.218	5	.264	2
530			min	-201.323	1	-217.662	3	-147.937	4	0	2	-.251	1	-.107	3
531		19	max	17.639	5	515.344	2	-7.768	12	0	5	.16	5	.008	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
532			min	-200.607	1	-218.593	3	-146.696	4	0	2	-.328	1	-.009	1
533	M5	1	max	430.615	1	1829.933	3	108.52	5	0	1	0	1	.022	2
534			min	19.42	12	-1317.419	1	0	1	0	4	-.252	4	-.002	3
535		2	max	431.331	1	1829.003	3	109.762	5	0	1	0	1	.716	1
536			min	19.778	12	-1318.66	1	0	1	0	4	-.194	4	-.967	3
537		3	max	1280.113	3	1351.303	1	77.679	4	0	4	0	1	1.38	1
538			min	-846.048	2	-1283.589	3	0	1	0	1	-.137	4	-1.894	3
539		4	max	1280.65	3	1350.063	1	78.92	4	0	4	0	1	.668	1
540			min	-845.332	2	-1284.52	3	0	1	0	1	-.095	4	-1.217	3
541		5	max	1281.187	3	1348.822	1	80.161	4	0	4	0	1	.002	9
542			min	-844.616	2	-1285.45	3	0	1	0	1	-.053	4	-.539	3
543		6	max	1281.724	3	1347.582	1	81.403	4	0	4	0	1	.14	3
544			min	-843.9	2	-1286.38	3	0	1	0	1	-.011	5	-.781	2
545		7	max	1282.261	3	1346.341	1	82.644	4	0	4	.032	4	.819	3
546			min	-843.183	2	-1287.311	3	0	1	0	1	0	1	-1.467	2
547		8	max	1282.798	3	1345.101	1	83.886	4	0	4	.076	4	1.498	3
548			min	-842.467	2	-1288.241	3	0	1	0	1	0	1	-2.177	1
549		9	max	1311.534	3	129.121	2	215.596	4	0	1	0	1	1.725	3
550			min	-664.696	2	.377	15	0	1	0	1	-.219	4	-2.465	1
551		10	max	1312.071	3	127.88	2	216.837	4	0	1	0	1	1.671	3
552			min	-663.98	2	.002	15	0	1	0	1	-.105	4	-2.517	2
553		11	max	1312.608	3	126.64	2	218.079	4	0	1	.009	4	1.618	3
554			min	-663.264	2	-1.32	6	0	1	0	1	0	1	-2.584	2
555		12	max	1341.464	3	837.023	3	251.5	4	0	1	0	1	1.422	3
556			min	-485.505	2	-1559.465	2	0	1	0	4	-.346	4	-2.313	2
557		13	max	1342.001	3	836.093	3	252.741	4	0	1	0	1	.98	3
558			min	-484.789	2	-1560.705	2	0	1	0	4	-.213	4	-1.49	2
559		14	max	1342.538	3	835.162	3	253.983	4	0	1	0	1	.539	3
560			min	-484.073	2	-1561.946	2	0	1	0	4	-.08	4	-.696	1
561		15	max	1343.075	3	834.232	3	255.224	4	0	1	.055	4	.158	2
562			min	-483.357	2	-1563.186	2	0	1	0	4	0	1	-.004	13
563		16	max	1343.613	3	833.301	3	256.466	4	0	1	.19	4	.983	2
564			min	-482.64	2	-1564.427	2	0	1	0	4	0	1	-.341	3
565		17	max	1344.15	3	832.371	3	257.707	4	0	1	.325	4	1.809	2
566			min	-481.924	2	-1565.667	2	0	1	0	4	0	1	-.781	3
567		18	max	-20.01	12	1736.014	2	0	1	0	4	.363	4	.933	2
568			min	-430.894	1	-742.432	3	-26.389	5	0	1	0	1	-.408	3
569		19	max	-19.652	12	1734.774	2	0	1	0	4	.35	4	.018	1
570			min	-430.177	1	-743.362	3	-25.147	5	0	1	0	1	-.016	3
571	M9	1	max	200.388	1	549.146	3	136.43	1	0	3	-.018	12	0	3
572			min	9.939	12	-390.964	1	7.47	12	0	4	-.327	1	-.011	2
573		2	max	201.104	1	548.215	3	136.43	1	0	3	-.014	12	.196	1
574			min	10.297	12	-392.205	1	7.47	12	0	4	-.255	1	-.289	3
575		3	max	397.085	3	437.582	1	136.086	1	0	1	-.01	12	.393	1
576			min	-232.453	2	-394.656	3	7.439	12	0	3	-.183	1	-.566	3
577		4	max	397.622	3	436.342	1	136.086	1	0	1	-.006	12	.163	1
578			min	-231.737	2	-395.587	3	7.439	12	0	3	-.111	1	-.358	3
579		5	max	398.16	3	435.101	1	136.086	1	0	1	-.002	12	-.003	15
580			min	-231.021	2	-396.517	3	7.439	12	0	3	-.055	4	-.149	3
581		6	max	398.697	3	433.861	1	136.086	1	0	1	.032	1	.061	3
582			min	-230.305	2	-397.448	3	7.439	12	0	3	-.026	5	-.307	2
583		7	max	399.234	3	432.62	1	136.086	1	0	1	.104	1	.27	3
584			min	-229.589	2	-398.378	3	7.439	12	0	3	-.005	5	-.528	2
585		8	max	399.771	3	431.38	1	136.086	1	0	1	.176	1	.481	3
586			min	-228.872	2	-399.308	3	7.439	12	0	3	.01	12	-.753	1
587		9	max	415.682	3	38.862	2	195.942	1	0	3	-.005	12	.562	3
588			min	-141.993	2	.382	15	10.539	12	0	9	-.189	4	-.859	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
589		10	max	416.219	3	37.622	2	195.942	1	0	3	.001	1	.547	3
590			min	-141.277	2	.008	15	10.539	12	0	9	-.114	4	-.878	2
591		11	max	416.756	3	36.381	2	195.942	1	0	3	.105	1	.532	3
592			min	-140.561	2	-1.476	6	10.539	12	0	9	-.063	5	-.897	2
593		12	max	432.607	3	259.792	3	223.811	4	0	3	-.009	12	.463	3
594			min	-78.626	10	-497.179	2	7.026	12	0	2	-.302	4	-.795	2
595		13	max	433.144	3	258.861	3	225.052	4	0	3	-.006	12	.326	3
596			min	-78.029	10	-498.419	2	7.026	12	0	2	-.184	4	-.533	2
597		14	max	433.682	3	257.931	3	226.293	4	0	3	-.002	12	.19	3
598			min	-77.432	10	-499.66	2	7.026	12	0	2	-.064	4	-.278	1
599		15	max	434.219	3	257	3	227.535	4	0	3	.055	4	.054	3
600			min	-76.835	10	-500.9	2	7.026	12	0	2	.002	12	-.027	1
601		16	max	434.756	3	256.07	3	228.776	4	0	3	.176	4	.259	2
602			min	-76.238	10	-502.141	2	7.026	12	0	2	.006	12	-.081	3
603		17	max	435.293	3	255.14	3	230.018	4	0	3	.297	4	.524	2
604			min	-75.641	10	-503.381	2	7.026	12	0	2	.009	12	-.216	3
605		18	max	-10.181	12	516.585	2	146.665	1	0	2	.318	4	.264	2
606			min	-201.323	1	-217.662	3	-91.154	5	0	3	.013	12	-.107	3
607		19	max	-9.823	12	515.344	2	146.665	1	0	2	.328	1	.008	3
608			min	-200.607	1	-218.593	3	-89.913	5	0	3	.017	12	-.009	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M13	1	max	.001	1	.087	2	.007	3	7.28e-3	2	NC	1	NC	1
2			min	-.786	4	-.01	3	-.003	2	-1.114e-3	3	NC	1	NC	1
3		2	max	.001	1	.335	3	.06	1	8.471e-3	2	NC	5	NC	2
4			min	-.786	4	-.144	1	-.03	5	-1.197e-3	3	763.649	3	4568.487	1
5		3	max	.001	1	.615	3	.145	1	9.661e-3	2	NC	5	NC	3
6			min	-.786	4	-.326	1	-.035	5	-1.28e-3	3	421.993	3	1846.802	1
7		4	max	0	1	.785	3	.219	1	1.085e-2	2	NC	5	NC	3
8			min	-.786	4	-.43	1	-.022	5	-1.363e-3	3	331.879	3	1214.787	1
9		5	max	0	1	.824	3	.258	1	1.204e-2	2	NC	15	NC	3
10			min	-.786	4	-.441	1	-.001	5	-1.446e-3	3	316.291	3	1030.506	1
11		6	max	0	1	.736	3	.25	1	1.323e-2	2	NC	5	NC	5
12			min	-.786	4	-.362	1	.013	15	-1.528e-3	3	353.818	3	1063.379	1
13		7	max	0	1	.546	3	.198	1	1.442e-2	2	NC	5	NC	3
14			min	-.786	4	-.212	1	.019	10	-1.611e-3	3	474.489	3	1348.751	1
15		8	max	0	1	.305	3	.116	1	1.562e-2	2	NC	5	NC	3
16			min	-.786	4	-.029	1	.007	10	-1.694e-3	3	836.834	3	2311.35	1
17		9	max	0	1	.147	2	.041	4	1.681e-2	2	NC	4	NC	2
18			min	-.786	4	.004	15	-.004	10	-1.777e-3	3	2720.2	3	6394.894	4
19		10	max	0	1	.215	2	.022	3	1.8e-2	2	NC	3	NC	1
20			min	-.786	4	-.012	3	-.015	2	-1.86e-3	3	2076.352	2	NC	1
21		11	max	0	12	.147	2	.035	1	1.681e-2	2	NC	4	NC	2
22			min	-.786	4	.004	15	-.024	5	-1.777e-3	3	2720.2	3	8054.048	1
23		12	max	0	12	.305	3	.116	1	1.562e-2	2	NC	5	NC	3
24			min	-.786	4	-.029	1	-.024	5	-1.694e-3	3	836.834	3	2311.35	1
25		13	max	0	12	.546	3	.198	1	1.442e-2	2	NC	5	NC	3
26			min	-.786	4	-.212	1	-.007	5	-1.611e-3	3	474.489	3	1348.751	1
27		14	max	0	12	.736	3	.25	1	1.323e-2	2	NC	5	NC	5
28			min	-.786	4	-.362	1	.011	15	-1.528e-3	3	353.818	3	1063.379	1
29		15	max	0	12	.824	3	.258	1	1.204e-2	2	NC	15	NC	3
30			min	-.787	4	-.441	1	.02	12	-1.446e-3	3	316.291	3	1030.506	1
31		16	max	0	12	.785	3	.219	1	1.085e-2	2	NC	5	NC	3
32			min	-.787	4	-.43	1	.017	12	-1.363e-3	3	331.879	3	1214.787	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
33		17	max	0	12	.615	3	.145	1	9.661e-3	2	NC	5	NC	3
34			min	-.787	4	-.326	1	.012	12	-1.28e-3	3	421.993	3	1846.802	1
35		18	max	0	12	.335	3	.06	1	8.471e-3	2	NC	5	NC	2
36			min	-.787	4	-.144	1	.005	10	-1.197e-3	3	763.649	3	4568.487	1
37		19	max	0	12	.087	2	.007	3	7.28e-3	2	NC	1	NC	1
38			min	-.787	4	-.01	3	-.003	2	-1.114e-3	3	NC	1	NC	1
39	M14	1	max	0	1	.168	3	.006	3	4.337e-3	2	NC	1	NC	1
40			min	-.578	4	-.287	2	-.003	2	-2.967e-3	3	NC	1	NC	1
41		2	max	0	1	.488	3	.042	1	5.236e-3	2	NC	5	NC	2
42			min	-.578	4	-.618	1	-.043	5	-3.642e-3	3	787.58	1	5876.056	5
43		3	max	0	1	.756	3	.118	1	6.134e-3	2	NC	15	NC	3
44			min	-.578	4	-.904	1	-.051	5	-4.317e-3	3	425.225	1	2277.097	1
45		4	max	0	1	.938	3	.19	1	7.032e-3	2	NC	15	NC	3
46			min	-.578	4	-1.106	1	-.033	5	-4.992e-3	3	320.802	1	1406.926	1
47		5	max	0	1	1.016	3	.231	1	7.93e-3	2	9108.546	15	NC	3
48			min	-.578	4	-1.207	1	-.002	5	-5.666e-3	3	285.569	1	1153.656	1
49		6	max	0	1	.992	3	.229	1	8.828e-3	2	9151.845	15	NC	3
50			min	-.578	4	-1.208	1	.019	12	-6.341e-3	3	285.274	1	1165.167	1
51		7	max	0	1	.883	3	.183	1	9.727e-3	2	NC	15	NC	3
52			min	-.578	4	-1.126	1	.017	10	-7.016e-3	3	313.253	1	1455.644	1
53		8	max	0	1	.727	3	.109	1	1.062e-2	2	NC	15	NC	3
54			min	-.578	4	-.993	1	.007	10	-7.691e-3	3	371.595	1	2463.966	1
55		9	max	0	1	.578	3	.059	4	1.152e-2	2	NC	15	NC	2
56			min	-.578	4	-.863	2	-.003	10	-8.365e-3	3	455.639	1	4484.265	4
57		10	max	0	1	.509	3	.02	3	1.242e-2	2	NC	5	NC	1
58			min	-.578	4	-.807	2	-.013	2	-9.04e-3	3	507.611	2	NC	1
59		11	max	0	12	.578	3	.033	1	1.152e-2	2	NC	15	NC	2
60			min	-.578	4	-.863	2	-.042	5	-8.365e-3	3	455.639	1	6196.186	5
61		12	max	0	12	.727	3	.109	1	1.062e-2	2	NC	15	NC	3
62			min	-.578	4	-.993	1	-.048	5	-7.691e-3	3	371.595	1	2463.966	1
63		13	max	0	12	.883	3	.183	1	9.727e-3	2	NC	15	NC	3
64			min	-.578	4	-1.126	1	-.029	5	-7.016e-3	3	313.253	1	1455.644	1
65		14	max	0	12	.992	3	.229	1	8.828e-3	2	9151.485	15	NC	3
66			min	-.578	4	-1.208	1	.002	15	-6.341e-3	3	285.274	1	1165.167	1
67		15	max	0	12	1.016	3	.231	1	7.93e-3	2	9108.1	15	NC	3
68			min	-.578	4	-1.207	1	.018	12	-5.666e-3	3	285.569	1	1153.656	1
69		16	max	0	12	.938	3	.19	1	7.032e-3	2	NC	15	NC	3
70			min	-.578	4	-1.106	1	.015	12	-4.992e-3	3	320.802	1	1406.926	1
71		17	max	0	12	.756	3	.118	1	6.134e-3	2	NC	15	NC	3
72			min	-.578	4	-.904	1	.01	12	-4.317e-3	3	425.225	1	2277.097	1
73		18	max	0	12	.488	3	.061	4	5.236e-3	2	NC	5	NC	2
74			min	-.578	4	-.618	1	.003	10	-3.642e-3	3	787.58	1	4305.902	4
75		19	max	0	12	.168	3	.006	3	4.337e-3	2	NC	1	NC	1
76			min	-.578	4	-.287	2	-.003	2	-2.967e-3	3	NC	1	NC	1
77	M15	1	max	0	12	.172	3	.006	3	2.557e-3	3	NC	1	NC	1
78			min	-.466	4	-.286	2	-.003	2	-4.527e-3	2	NC	1	NC	1
79		2	max	0	12	.368	3	.042	1	3.145e-3	3	NC	5	NC	2
80			min	-.466	4	-.698	2	-.056	5	-5.468e-3	2	640.175	2	4592.388	5
81		3	max	0	12	.537	3	.118	1	3.732e-3	3	NC	15	NC	3
82			min	-.466	4	-1.047	2	-.067	5	-6.409e-3	2	347.108	2	2271.201	1
83		4	max	0	12	.659	3	.19	1	4.319e-3	3	NC	15	NC	3
84			min	-.466	4	-1.287	2	-.046	5	-7.351e-3	2	263.811	2	1404.147	1
85		5	max	0	12	.724	3	.231	1	4.907e-3	3	9122.413	15	NC	3
86			min	-.466	4	-1.397	2	-.008	5	-8.292e-3	2	237.575	2	1151.631	1
87		6	max	0	12	.731	3	.229	1	5.494e-3	3	9168.679	15	NC	3
88			min	-.466	4	-1.379	2	.019	12	-9.233e-3	2	241.599	2	1163.092	1
89		7	max	0	12	.691	3	.184	1	6.081e-3	3	NC	15	NC	3

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
90			min	-.466	4	-1.254	2	.018	10	-1.017e-2	2	272.712	2	1452.542	1
91		8	max	0	12	.622	3	.11	1	6.669e-3	3	NC	15	NC	3
92			min	-.466	4	-1.068	2	.007	10	-1.112e-2	2	337.465	2	2455.66	1
93		9	max	0	12	.551	3	.07	4	7.256e-3	3	NC	15	NC	2
94			min	-.466	4	-.889	2	-.003	10	-1.206e-2	2	437.972	2	3838.946	4
95		10	max	0	1	.518	3	.018	3	7.843e-3	3	NC	5	NC	1
96			min	-.466	4	-.805	2	-.013	2	-1.3e-2	2	508.661	2	NC	1
97		11	max	0	1	.551	3	.034	1	7.256e-3	3	NC	15	NC	2
98			min	-.466	4	-.889	2	-.054	5	-1.206e-2	2	437.972	2	4890.485	5
99		12	max	0	1	.622	3	.11	1	6.669e-3	3	NC	15	NC	3
100			min	-.466	4	-1.068	2	-.062	5	-1.112e-2	2	337.465	2	2455.66	1
101		13	max	0	1	.691	3	.184	1	6.081e-3	3	NC	15	NC	3
102			min	-.466	4	-1.254	2	-.039	5	-1.017e-2	2	272.712	2	1452.542	1
103		14	max	0	1	.731	3	.229	1	5.494e-3	3	9168.402	15	NC	3
104			min	-.466	4	-1.379	2	0	15	-9.233e-3	2	241.599	2	1163.092	1
105		15	max	0	1	.724	3	.231	1	4.907e-3	3	9122.072	15	NC	3
106			min	-.466	4	-1.397	2	.018	12	-8.292e-3	2	237.575	2	1151.631	1
107		16	max	0	1	.659	3	.19	1	4.319e-3	3	NC	15	NC	3
108			min	-.465	4	-1.287	2	.014	12	-7.351e-3	2	263.811	2	1404.147	1
109		17	max	0	1	.537	3	.118	1	3.732e-3	3	NC	15	NC	3
110			min	-.465	4	-1.047	2	.01	12	-6.409e-3	2	347.108	2	2271.201	1
111		18	max	0	1	.368	3	.074	4	3.145e-3	3	NC	5	NC	2
112			min	-.465	4	-.698	2	.003	10	-5.468e-3	2	640.175	2	3572.99	4
113		19	max	0	1	.172	3	.006	3	2.557e-3	3	NC	1	NC	1
114			min	-.465	4	-.286	2	-.003	2	-4.527e-3	2	NC	1	NC	1
115	M16	1	max	0	12	.083	1	.005	3	4.434e-3	3	NC	1	NC	1
116			min	-.153	4	-.055	3	-.002	2	-6.379e-3	1	NC	1	NC	1
117		2	max	0	12	.068	3	.059	1	5.298e-3	3	NC	5	NC	2
118			min	-.153	4	-.23	2	-.044	5	-7.368e-3	1	856.288	2	4601.266	1
119		3	max	0	12	.165	3	.144	1	6.162e-3	3	NC	5	NC	3
120			min	-.153	4	-.477	2	-.053	5	-8.357e-3	1	475.684	2	1853.596	1
121		4	max	0	12	.219	3	.219	1	7.025e-3	3	NC	5	NC	3
122			min	-.153	4	-.62	2	-.038	5	-9.346e-3	1	377.793	2	1217.048	1
123		5	max	0	12	.221	3	.258	1	7.889e-3	3	NC	5	NC	3
124			min	-.153	4	-.642	2	-.01	5	-1.033e-2	1	366.31	2	1030.982	1
125		6	max	0	12	.173	3	.25	1	8.753e-3	3	NC	5	NC	3
126			min	-.153	4	-.546	2	.014	15	-1.132e-2	1	423.139	2	1062.242	1
127		7	max	0	12	.086	3	.198	1	9.617e-3	3	NC	5	NC	3
128			min	-.153	4	-.355	2	.017	12	-1.231e-2	1	608.505	2	1344.074	1
129		8	max	0	12	0	15	.117	1	1.048e-2	3	NC	4	NC	3
130			min	-.153	4	-.12	2	.009	10	-1.33e-2	1	1332.102	2	2290.078	1
131		9	max	0	12	.114	1	.052	4	1.134e-2	3	NC	2	NC	2
132			min	-.153	4	-.111	3	-.002	10	-1.429e-2	1	4672.95	3	5062.896	4
133		10	max	0	1	.201	1	.016	3	1.221e-2	3	NC	4	NC	1
134			min	-.153	4	-.153	3	-.012	2	-1.528e-2	1	2228.435	1	NC	1
135		11	max	0	1	.114	1	.036	1	1.134e-2	3	NC	2	NC	2
136			min	-.153	4	-.111	3	-.035	5	-1.429e-2	1	4672.95	3	7427.815	5
137		12	max	0	1	0	15	.117	1	1.048e-2	3	NC	4	NC	3
138			min	-.152	4	-.12	2	-.036	5	-1.33e-2	1	1332.102	2	2290.078	1
139		13	max	0	1	.086	3	.198	1	9.617e-3	3	NC	5	NC	3
140			min	-.152	4	-.355	2	-.015	5	-1.231e-2	1	608.505	2	1344.074	1
141		14	max	0	1	.173	3	.25	1	8.753e-3	3	NC	5	NC	3
142			min	-.152	4	-.546	2	.011	15	-1.132e-2	1	423.139	2	1062.242	1
143		15	max	0	1	.221	3	.258	1	7.889e-3	3	NC	5	NC	3
144			min	-.152	4	-.642	2	.018	12	-1.033e-2	1	366.31	2	1030.982	1
145		16	max	.001	1	.219	3	.219	1	7.025e-3	3	NC	5	NC	3
146			min	-.152	4	-.62	2	.015	12	-9.346e-3	1	377.793	2	1217.048	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
147		17	max	.001	1	.165	3	.144	1	6.162e-3	3	NC	5	NC	3
148			min	-.152	4	-.477	2	.011	12	-8.357e-3	1	475.684	2	1853.596	1
149		18	max	.001	1	.068	3	.068	4	5.298e-3	3	NC	5	NC	2
150			min	-.152	4	-.23	2	.005	10	-7.368e-3	1	856.288	2	3879.075	4
151		19	max	.002	1	.083	1	.005	3	4.434e-3	3	NC	1	NC	1
152			min	-.152	4	-.055	3	-.002	2	-6.379e-3	1	NC	1	NC	1
153	M2	1	max	.006	1	.006	2	.011	1	1.638e-3	5	NC	1	NC	2
154			min	-.007	3	-.01	3	-.734	4	-3.041e-4	1	NC	1	95.286	4
155		2	max	.006	1	.005	2	.01	1	1.75e-3	5	NC	1	NC	2
156			min	-.006	3	-.01	3	-.675	4	-2.865e-4	1	NC	1	103.682	4
157		3	max	.005	1	.004	2	.009	1	1.862e-3	5	NC	1	NC	2
158			min	-.006	3	-.01	3	-.616	4	-2.69e-4	1	NC	1	113.639	4
159		4	max	.005	1	.003	2	.008	1	1.974e-3	5	NC	1	NC	2
160			min	-.006	3	-.01	3	-.557	4	-2.514e-4	1	NC	1	125.56	4
161		5	max	.005	1	.002	2	.007	1	2.086e-3	5	NC	1	NC	2
162			min	-.005	3	-.009	3	-.5	4	-2.339e-4	1	NC	1	139.994	4
163		6	max	.004	1	.001	2	.006	1	2.198e-3	5	NC	1	NC	1
164			min	-.005	3	-.009	3	-.444	4	-2.163e-4	1	NC	1	157.694	4
165		7	max	.004	1	0	2	.005	1	2.31e-3	5	NC	1	NC	1
166			min	-.005	3	-.009	3	-.389	4	-1.988e-4	1	NC	1	179.732	4
167		8	max	.004	1	0	2	.005	1	2.422e-3	5	NC	1	NC	1
168			min	-.004	3	-.008	3	-.337	4	-1.812e-4	1	NC	1	207.66	4
169		9	max	.003	1	0	15	.004	1	2.534e-3	5	NC	1	NC	1
170			min	-.004	3	-.008	3	-.287	4	-1.637e-4	1	NC	1	243.807	4
171		10	max	.003	1	0	15	.003	1	2.646e-3	4	NC	1	NC	1
172			min	-.003	3	-.007	3	-.24	4	-1.461e-4	1	NC	1	291.792	4
173		11	max	.003	1	0	15	.003	1	2.765e-3	4	NC	1	NC	1
174			min	-.003	3	-.007	3	-.196	4	-1.286e-4	1	NC	1	357.502	4
175		12	max	.002	1	0	15	.002	1	2.883e-3	4	NC	1	NC	1
176			min	-.003	3	-.006	3	-.155	4	-1.11e-4	1	NC	1	451.041	4
177		13	max	.002	1	0	15	.002	1	3.002e-3	4	NC	1	NC	1
178			min	-.002	3	-.005	3	-.118	4	-9.347e-5	1	NC	1	590.99	4
179		14	max	.002	1	0	15	.001	1	3.12e-3	4	NC	1	NC	1
180			min	-.002	3	-.005	3	-.086	4	-7.591e-5	1	NC	1	814.693	4
181		15	max	.001	1	0	15	0	1	3.238e-3	4	NC	1	NC	1
182			min	-.002	3	-.004	3	-.058	4	-5.836e-5	1	NC	1	1206.854	4
183		16	max	.001	1	0	15	0	1	3.357e-3	4	NC	1	NC	1
184			min	-.001	3	-.003	3	-.035	4	-4.081e-5	1	NC	1	1996.289	4
185		17	max	0	1	0	15	0	1	3.475e-3	4	NC	1	NC	1
186			min	0	3	-.002	6	-.017	4	-2.326e-5	1	NC	1	4001.361	4
187		18	max	0	1	0	15	0	1	3.594e-3	4	NC	1	NC	1
188			min	0	3	-.001	6	-.006	4	-5.708e-6	1	NC	1	NC	1
189		19	max	0	1	0	1	0	1	3.712e-3	4	NC	1	NC	1
190			min	0	1	0	1	0	1	5.249e-7	12	NC	1	NC	1
191	M3	1	max	0	1	0	1	0	1	-2.221e-7	12	NC	1	NC	1
192			min	0	1	0	1	0	1	-9.348e-4	4	NC	1	NC	1
193		2	max	0	3	0	15	.017	4	2.414e-5	1	NC	1	NC	1
194			min	0	2	-.002	6	0	12	-1.943e-4	5	NC	1	NC	1
195		3	max	0	3	0	15	.034	4	5.528e-4	4	NC	1	NC	1
196			min	0	2	-.004	6	0	12	2.776e-6	12	NC	1	NC	1
197		4	max	0	3	-.001	15	.048	4	1.297e-3	4	NC	1	NC	1
198			min	0	2	-.006	6	0	12	4.275e-6	12	NC	1	8271.217	5
199		5	max	.001	3	-.002	15	.062	4	2.04e-3	4	NC	1	NC	1
200			min	0	2	-.008	6	0	12	5.774e-6	12	NC	1	7516.001	5
201		6	max	.002	3	-.002	15	.074	4	2.784e-3	4	NC	1	NC	1
202			min	-.001	2	-.009	6	0	12	7.272e-6	12	9762.999	6	7483.345	5
203		7	max	.002	3	-.002	15	.086	4	3.528e-3	4	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
204			min	-.001	2	-.011	6	0	12	8.771e-6	12	8400.372	6	8044.139	5
205		8	max	.002	3	-.003	15	.097	4	4.272e-3	4	NC	2	NC	1
206			min	-.002	2	-.012	6	0	12	1.027e-5	12	7560.313	6	9355.99	5
207		9	max	.003	3	-.003	15	.107	4	5.016e-3	4	NC	3	NC	1
208			min	-.002	2	-.013	6	0	12	1.177e-5	12	7065.844	6	NC	1
209		10	max	.003	3	-.003	15	.117	4	5.76e-3	4	NC	3	NC	1
210			min	-.002	2	-.013	6	0	12	1.327e-5	12	6831.293	6	NC	1
211		11	max	.003	3	-.003	15	.127	4	6.503e-3	4	NC	3	NC	1
212			min	-.002	2	-.013	6	0	12	1.477e-5	12	6822.252	6	NC	1
213		12	max	.003	3	-.003	15	.136	4	7.247e-3	4	NC	3	NC	1
214			min	-.003	2	-.013	6	0	12	1.627e-5	12	7042.395	6	NC	1
215		13	max	.004	3	-.003	15	.147	4	7.991e-3	4	NC	2	NC	1
216			min	-.003	2	-.012	6	0	12	1.776e-5	12	7536.584	6	NC	1
217		14	max	.004	3	-.002	15	.157	4	8.735e-3	4	NC	1	NC	1
218			min	-.003	2	-.011	6	0	12	1.926e-5	12	8413.925	6	NC	1
219		15	max	.004	3	-.002	15	.168	4	9.479e-3	4	NC	1	NC	1
220			min	-.003	2	-.009	6	0	12	2.076e-5	12	9915.438	6	NC	1
221		16	max	.005	3	-.001	15	.18	4	1.022e-2	4	NC	1	NC	1
222			min	-.004	2	-.008	1	0	12	2.226e-5	12	NC	1	NC	1
223		17	max	.005	3	0	15	.194	4	1.097e-2	4	NC	1	NC	1
224			min	-.004	2	-.006	1	0	12	2.376e-5	12	NC	1	NC	1
225		18	max	.005	3	0	15	.209	4	1.171e-2	4	NC	1	NC	1
226			min	-.004	2	-.004	1	0	12	2.526e-5	12	NC	1	NC	1
227		19	max	.006	3	0	5	.225	4	1.245e-2	4	NC	1	NC	2
228			min	-.004	2	-.003	1	0	12	2.676e-5	12	NC	1	9014.597	1
229	M4	1	max	.003	1	.004	2	0	12	1.172e-4	1	NC	1	NC	3
230			min	0	5	-.006	3	-.225	4	-8.021e-5	5	NC	1	110.154	4
231		2	max	.002	1	.004	2	0	12	1.172e-4	1	NC	1	NC	3
232			min	0	5	-.006	3	-.207	4	-8.021e-5	5	NC	1	119.715	4
233		3	max	.002	1	.004	2	0	12	1.172e-4	1	NC	1	NC	3
234			min	0	5	-.005	3	-.189	4	-8.021e-5	5	NC	1	131.097	4
235		4	max	.002	1	.003	2	0	12	1.172e-4	1	NC	1	NC	3
236			min	0	5	-.005	3	-.171	4	-8.021e-5	5	NC	1	144.772	4
237		5	max	.002	1	.003	2	0	12	1.172e-4	1	NC	1	NC	3
238			min	0	5	-.005	3	-.154	4	-8.021e-5	5	NC	1	161.383	4
239		6	max	.002	1	.003	2	0	12	1.172e-4	1	NC	1	NC	3
240			min	0	5	-.004	3	-.136	4	-8.021e-5	5	NC	1	181.821	4
241		7	max	.002	1	.003	2	0	12	1.172e-4	1	NC	1	NC	2
242			min	0	5	-.004	3	-.12	4	-8.021e-5	5	NC	1	207.348	4
243		8	max	.002	1	.002	2	0	12	1.172e-4	1	NC	1	NC	2
244			min	0	5	-.004	3	-.103	4	-8.021e-5	5	NC	1	239.808	4
245		9	max	.001	1	.002	2	0	12	1.172e-4	1	NC	1	NC	2
246			min	0	5	-.003	3	-.088	4	-8.021e-5	5	NC	1	281.975	4
247		10	max	.001	1	.002	2	0	12	1.172e-4	1	NC	1	NC	2
248			min	0	5	-.003	3	-.073	4	-8.021e-5	5	NC	1	338.187	4
249		11	max	.001	1	.002	2	0	12	1.172e-4	1	NC	1	NC	2
250			min	0	5	-.003	3	-.06	4	-8.021e-5	5	NC	1	415.535	4
251		12	max	0	1	.002	2	0	12	1.172e-4	1	NC	1	NC	1
252			min	0	5	-.002	3	-.047	4	-8.021e-5	5	NC	1	526.29	4
253		13	max	0	1	.001	2	0	12	1.172e-4	1	NC	1	NC	1
254			min	0	5	-.002	3	-.036	4	-8.021e-5	5	NC	1	693.22	4
255		14	max	0	1	.001	2	0	12	1.172e-4	1	NC	1	NC	1
256			min	0	5	-.002	3	-.026	4	-8.021e-5	5	NC	1	962.637	4
257		15	max	0	1	0	2	0	12	1.172e-4	1	NC	1	NC	1
258			min	0	5	-.001	3	-.017	4	-8.021e-5	5	NC	1	1441.274	4
259		16	max	0	1	0	2	0	12	1.172e-4	1	NC	1	NC	1
260			min	0	5	0	3	-.01	4	-8.021e-5	5	NC	1	2424.099	4

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
261		17	max	0	1	0	2	0	12	1.172e-4	1	NC	1	NC	1
262			min	0	5	0	3	-.005	4	-8.021e-5	5	NC	1	5004.324	4
263		18	max	0	1	0	2	0	12	1.172e-4	1	NC	1	NC	1
264			min	0	5	0	3	-.002	4	-8.021e-5	5	NC	1	NC	1
265		19	max	0	1	0	1	0	1	1.172e-4	1	NC	1	NC	1
266			min	0	1	0	1	0	1	-8.021e-5	5	NC	1	NC	1
267	M6	1	max	.02	1	.023	2	0	1	1.75e-3	4	NC	3	NC	1
268			min	-.022	3	-.033	3	-.741	4	0	1	2981.261	2	94.366	4
269		2	max	.018	1	.021	2	0	1	1.859e-3	4	NC	3	NC	1
270			min	-.021	3	-.031	3	-.681	4	0	1	3282.744	2	102.682	4
271		3	max	.017	1	.019	2	0	1	1.969e-3	4	NC	3	NC	1
272			min	-.02	3	-.029	3	-.622	4	0	1	3648.618	2	112.545	4
273		4	max	.016	1	.017	2	0	1	2.078e-3	4	NC	3	NC	1
274			min	-.019	3	-.028	3	-.562	4	0	1	4097.703	2	124.354	4
275		5	max	.015	1	.015	2	0	1	2.188e-3	4	NC	1	NC	1
276			min	-.017	3	-.026	3	-.504	4	0	1	4656.485	2	138.652	4
277		6	max	.014	1	.013	2	0	1	2.298e-3	4	NC	1	NC	1
278			min	-.016	3	-.024	3	-.448	4	0	1	5363.194	2	156.188	4
279		7	max	.013	1	.011	2	0	1	2.407e-3	4	NC	1	NC	1
280			min	-.015	3	-.022	3	-.393	4	0	1	6274.677	2	178.021	4
281		8	max	.012	1	.009	2	0	1	2.517e-3	4	NC	1	NC	1
282			min	-.014	3	-.02	3	-.34	4	0	1	7478.52	2	205.691	4
283		9	max	.011	1	.008	2	0	1	2.626e-3	4	NC	1	NC	1
284			min	-.012	3	-.019	3	-.29	4	0	1	9115.577	2	241.505	4
285		10	max	.01	1	.006	2	0	1	2.736e-3	4	NC	1	NC	1
286			min	-.011	3	-.017	3	-.242	4	0	1	NC	1	289.052	4
287		11	max	.009	1	.005	2	0	1	2.846e-3	4	NC	1	NC	1
288			min	-.01	3	-.015	3	-.198	4	0	1	NC	1	354.166	4
289		12	max	.008	1	.003	2	0	1	2.955e-3	4	NC	1	NC	1
290			min	-.009	3	-.013	3	-.157	4	0	1	NC	1	446.865	4
291		13	max	.007	1	.002	2	0	1	3.065e-3	4	NC	1	NC	1
292			min	-.007	3	-.011	3	-.119	4	0	1	NC	1	585.573	4
293		14	max	.005	1	.001	2	0	1	3.174e-3	4	NC	1	NC	1
294			min	-.006	3	-.009	3	-.087	4	0	1	NC	1	807.324	4
295		15	max	.004	1	0	2	0	1	3.284e-3	4	NC	1	NC	1
296			min	-.005	3	-.007	3	-.058	4	0	1	NC	1	1196.139	4
297		16	max	.003	1	0	2	0	1	3.394e-3	4	NC	1	NC	1
298			min	-.004	3	-.006	3	-.035	4	0	1	NC	1	1979.062	4
299		17	max	.002	1	0	2	0	1	3.503e-3	4	NC	1	NC	1
300			min	-.002	3	-.004	3	-.018	4	0	1	NC	1	3968.522	4
301		18	max	.001	1	0	2	0	1	3.613e-3	4	NC	1	NC	1
302			min	-.001	3	-.002	3	-.006	4	0	1	NC	1	NC	1
303		19	max	0	1	0	1	0	1	3.723e-3	4	NC	1	NC	1
304			min	0	1	0	1	0	1	0	1	NC	1	NC	1
305	M7	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
306			min	0	1	0	1	0	1	-9.367e-4	4	NC	1	NC	1
307		2	max	0	3	0	15	.018	4	0	1	NC	1	NC	1
308			min	0	2	-.002	3	0	1	-2.133e-4	4	NC	1	NC	1
309		3	max	.002	3	0	15	.034	4	5.102e-4	4	NC	1	NC	1
310			min	-.002	2	-.005	3	0	1	0	1	NC	1	9572.933	4
311		4	max	.003	3	-.001	15	.048	4	1.234e-3	4	NC	1	NC	1
312			min	-.003	2	-.007	3	0	1	0	1	NC	1	7491.059	4
313		5	max	.004	3	-.002	15	.062	4	1.957e-3	4	NC	1	NC	1
314			min	-.004	2	-.009	3	0	1	0	1	NC	1	6714.828	4
315		6	max	.005	3	-.002	15	.074	4	2.681e-3	4	NC	1	NC	1
316			min	-.005	2	-.01	3	0	1	0	1	9862.226	4	6566.221	4
317		7	max	.006	3	-.003	15	.086	4	3.404e-3	4	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
318			min	-.006	2	-.012	3	0	1	0	1	8479.059	4	6884.544	4
319		8	max	.007	3	-.003	15	.096	4	4.128e-3	4	NC	1	NC	1
320			min	-.007	2	-.013	3	0	1	0	1	7626.16	4	7718.498	4
321		9	max	.008	3	-.003	15	.106	4	4.851e-3	4	NC	1	NC	1
322			min	-.008	2	-.014	3	0	1	0	1	7123.508	4	9338.549	4
323		10	max	.009	3	-.003	15	.116	4	5.575e-3	4	NC	1	NC	1
324			min	-.009	2	-.014	3	0	1	0	1	6883.892	4	NC	1
325		11	max	.01	3	-.003	15	.125	4	6.298e-3	4	NC	1	NC	1
326			min	-.01	2	-.014	3	0	1	0	1	6872.127	4	NC	1
327		12	max	.011	3	-.003	15	.135	4	7.022e-3	4	NC	1	NC	1
328			min	-.011	2	-.014	3	0	1	0	1	7091.564	4	NC	1
329		13	max	.012	3	-.003	15	.144	4	7.745e-3	4	NC	1	NC	1
330			min	-.012	2	-.013	3	0	1	0	1	7587.119	4	NC	1
331		14	max	.013	3	-.003	15	.154	4	8.469e-3	4	NC	1	NC	1
332			min	-.012	2	-.013	3	0	1	0	1	8468.405	4	NC	1
333		15	max	.014	3	-.002	15	.165	4	9.192e-3	4	NC	1	NC	1
334			min	-.013	2	-.011	3	0	1	0	1	9977.777	4	NC	1
335		16	max	.015	3	-.002	15	.176	4	9.916e-3	4	NC	1	NC	1
336			min	-.014	2	-.01	3	0	1	0	1	NC	1	NC	1
337		17	max	.016	3	-.001	15	.188	4	1.064e-2	4	NC	1	NC	1
338			min	-.015	2	-.008	3	0	1	0	1	NC	1	NC	1
339		18	max	.017	3	0	15	.202	4	1.136e-2	4	NC	1	NC	1
340			min	-.016	2	-.007	3	0	1	0	1	NC	1	NC	1
341		19	max	.018	3	0	10	.218	4	1.209e-2	4	NC	1	NC	1
342			min	-.017	2	-.005	3	0	1	0	1	NC	1	NC	1
343	M8	1	max	.006	1	.017	2	0	1	0	1	NC	1	NC	1
344			min	0	3	-.018	3	-.218	4	-1.881e-4	4	NC	1	113.966	4
345		2	max	.006	1	.016	2	0	1	0	1	NC	1	NC	1
346			min	0	3	-.017	3	-.2	4	-1.881e-4	4	NC	1	123.867	4
347		3	max	.006	1	.015	2	0	1	0	1	NC	1	NC	1
348			min	0	3	-.016	3	-.183	4	-1.881e-4	4	NC	1	135.653	4
349		4	max	.005	1	.014	2	0	1	0	1	NC	1	NC	1
350			min	0	3	-.015	3	-.166	4	-1.881e-4	4	NC	1	149.813	4
351		5	max	.005	1	.013	2	0	1	0	1	NC	1	NC	1
352			min	0	3	-.014	3	-.149	4	-1.881e-4	4	NC	1	167.013	4
353		6	max	.005	1	.012	2	0	1	0	1	NC	1	NC	1
354			min	0	3	-.013	3	-.132	4	-1.881e-4	4	NC	1	188.175	4
355		7	max	.004	1	.011	2	0	1	0	1	NC	1	NC	1
356			min	0	3	-.012	3	-.116	4	-1.881e-4	4	NC	1	214.606	4
357		8	max	.004	1	.01	2	0	1	0	1	NC	1	NC	1
358			min	0	3	-.011	3	-.1	4	-1.881e-4	4	NC	1	248.215	4
359		9	max	.004	1	.009	2	0	1	0	1	NC	1	NC	1
360			min	0	3	-.01	3	-.085	4	-1.881e-4	4	NC	1	291.875	4
361		10	max	.003	1	.008	2	0	1	0	1	NC	1	NC	1
362			min	0	3	-.009	3	-.071	4	-1.881e-4	4	NC	1	350.077	4
363		11	max	.003	1	.007	2	0	1	0	1	NC	1	NC	1
364			min	0	3	-.008	3	-.058	4	-1.881e-4	4	NC	1	430.165	4
365		12	max	.002	1	.006	2	0	1	0	1	NC	1	NC	1
366			min	0	3	-.007	3	-.046	4	-1.881e-4	4	NC	1	544.843	4
367		13	max	.002	1	.006	2	0	1	0	1	NC	1	NC	1
368			min	0	3	-.006	3	-.035	4	-1.881e-4	4	NC	1	717.688	4
369		14	max	.002	1	.005	2	0	1	0	1	NC	1	NC	1
370			min	0	3	-.005	3	-.025	4	-1.881e-4	4	NC	1	996.657	4
371		15	max	.001	1	.004	2	0	1	0	1	NC	1	NC	1
372			min	0	3	-.004	3	-.017	4	-1.881e-4	4	NC	1	1492.273	4
373		16	max	.001	1	.003	2	0	1	0	1	NC	1	NC	1
374			min	0	3	-.003	3	-.01	4	-1.881e-4	4	NC	1	2509.989	4

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
375		17	max	0	1	.002	2	0	1	0	1	NC	1	NC	1
376			min	0	3	-.002	3	-.005	4	-1.881e-4	4	NC	1	5181.908	4
377		18	max	0	1	0	2	0	1	0	1	NC	1	NC	1
378			min	0	3	-.001	3	-.001	4	-1.881e-4	4	NC	1	NC	1
379		19	max	0	1	0	1	0	1	0	1	NC	1	NC	1
380			min	0	1	0	1	0	1	-1.881e-4	4	NC	1	NC	1
381	M10	1	max	.006	1	.006	2	0	12	1.768e-3	4	NC	1	NC	2
382			min	-.007	3	-.01	3	-.741	4	1.717e-5	12	NC	1	94.451	4
383		2	max	.006	1	.005	2	0	12	1.875e-3	4	NC	1	NC	2
384			min	-.006	3	-.01	3	-.681	4	1.618e-5	12	NC	1	102.775	4
385		3	max	.005	1	.004	2	0	12	1.983e-3	4	NC	1	NC	2
386			min	-.006	3	-.01	3	-.621	4	1.52e-5	12	NC	1	112.648	4
387		4	max	.005	1	.003	2	0	12	2.091e-3	4	NC	1	NC	2
388			min	-.006	3	-.01	3	-.562	4	1.422e-5	12	NC	1	124.469	4
389		5	max	.005	1	.002	2	0	12	2.198e-3	4	NC	1	NC	2
390			min	-.005	3	-.009	3	-.504	4	1.324e-5	12	NC	1	138.781	4
391		6	max	.004	1	.001	2	0	12	2.306e-3	4	NC	1	NC	1
392			min	-.005	3	-.009	3	-.447	4	1.225e-5	12	NC	1	156.334	4
393		7	max	.004	1	0	2	0	12	2.413e-3	4	NC	1	NC	1
394			min	-.005	3	-.009	3	-.393	4	1.127e-5	12	NC	1	178.19	4
395		8	max	.004	1	0	2	0	12	2.521e-3	4	NC	1	NC	1
396			min	-.004	3	-.008	3	-.34	4	1.029e-5	12	NC	1	205.889	4
397		9	max	.003	1	0	2	0	12	2.629e-3	4	NC	1	NC	1
398			min	-.004	3	-.008	3	-.289	4	9.304e-6	12	NC	1	241.741	4
399		10	max	.003	1	-.001	2	0	12	2.736e-3	4	NC	1	NC	1
400			min	-.003	3	-.007	3	-.242	4	8.321e-6	12	NC	1	289.341	4
401		11	max	.003	1	-.002	15	0	12	2.844e-3	4	NC	1	NC	1
402			min	-.003	3	-.007	3	-.197	4	7.338e-6	12	NC	1	354.529	4
403		12	max	.002	1	-.001	15	0	12	2.951e-3	4	NC	1	NC	1
404			min	-.003	3	-.006	3	-.156	4	6.356e-6	12	NC	1	447.339	4
405		13	max	.002	1	-.001	15	0	12	3.059e-3	4	NC	1	NC	1
406			min	-.002	3	-.005	3	-.119	4	5.373e-6	12	NC	1	586.219	4
407		14	max	.002	1	-.001	15	0	12	3.167e-3	4	NC	1	NC	1
408			min	-.002	3	-.005	4	-.087	4	4.39e-6	12	NC	1	808.264	4
409		15	max	.001	1	-.001	15	0	12	3.274e-3	4	NC	1	NC	1
410			min	-.002	3	-.004	4	-.058	4	3.407e-6	12	NC	1	1197.638	4
411		16	max	.001	1	0	15	0	12	3.382e-3	4	NC	1	NC	1
412			min	-.001	3	-.003	4	-.035	4	2.424e-6	12	NC	1	1981.812	4
413		17	max	0	1	0	15	0	12	3.489e-3	4	NC	1	NC	1
414			min	0	3	-.002	4	-.018	4	1.441e-6	12	NC	1	3974.977	4
415		18	max	0	1	0	15	0	12	3.597e-3	4	NC	1	NC	1
416			min	0	3	-.001	4	-.006	4	4.58e-7	12	NC	1	NC	1
417		19	max	0	1	0	1	0	1	3.705e-3	4	NC	1	NC	1
418			min	0	1	0	1	0	1	-1.184e-5	1	NC	1	NC	1
419	M11	1	max	0	1	0	1	0	1	4.723e-6	1	NC	1	NC	1
420			min	0	1	0	1	0	1	-9.319e-4	4	NC	1	NC	1
421		2	max	0	3	0	15	.017	4	-1.277e-6	12	NC	1	NC	1
422			min	0	2	-.002	4	0	1	-2.059e-4	4	NC	1	NC	1
423		3	max	0	3	0	15	.033	4	5.234e-4	5	NC	1	NC	1
424			min	0	2	-.004	4	0	1	-5.301e-5	1	NC	1	9908.591	4
425		4	max	0	3	-.001	15	.048	4	1.246e-3	4	NC	1	NC	1
426			min	0	2	-.006	4	0	1	-8.188e-5	1	NC	1	7795.399	4
427		5	max	.001	3	-.002	15	.061	4	1.972e-3	4	NC	1	NC	1
428			min	0	2	-.008	4	0	1	-1.107e-4	1	NC	1	7035.043	4
429		6	max	.002	3	-.002	15	.074	4	2.698e-3	4	NC	1	NC	1
430			min	-.001	2	-.01	4	0	1	-1.396e-4	1	9483.7	4	6940.274	4
431		7	max	.002	3	-.003	15	.085	4	3.424e-3	4	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
432			min	-.001	2	-.012	4	0	1	-1.685e-4	1	8178.224	4	7364.625	4
433		8	max	.002	3	-.003	15	.096	4	4.15e-3	4	NC	2	NC	1
434			min	-.002	2	-.013	4	-.001	1	-1.973e-4	1	7373.95	4	8401.255	4
435		9	max	.003	3	-.003	15	.106	4	4.876e-3	4	NC	3	NC	1
436			min	-.002	2	-.014	4	-.002	1	-2.262e-4	1	6902.298	4	NC	1
437		10	max	.003	3	-.003	15	.116	4	5.602e-3	4	NC	3	NC	1
438			min	-.002	2	-.014	4	-.002	1	-2.551e-4	1	6681.848	4	NC	1
439		11	max	.003	3	-.004	15	.125	4	6.328e-3	4	NC	3	NC	1
440			min	-.002	2	-.014	4	-.003	1	-2.84e-4	1	6680.339	4	NC	1
441		12	max	.003	3	-.003	15	.134	4	7.054e-3	4	NC	3	NC	1
442			min	-.003	2	-.014	4	-.003	1	-3.128e-4	1	6902.314	4	NC	1
443		13	max	.004	3	-.003	15	.144	4	7.78e-3	4	NC	2	NC	1
444			min	-.003	2	-.013	4	-.004	1	-3.417e-4	1	7392.459	4	NC	1
445		14	max	.004	3	-.003	15	.154	4	8.506e-3	4	NC	1	NC	1
446			min	-.003	2	-.012	4	-.005	1	-3.706e-4	1	8258.411	4	NC	1
447		15	max	.004	3	-.003	15	.165	4	9.232e-3	4	NC	1	NC	1
448			min	-.003	2	-.01	4	-.006	1	-3.994e-4	1	9737.366	4	NC	1
449		16	max	.005	3	-.002	15	.176	4	9.958e-3	4	NC	1	NC	1
450			min	-.004	2	-.008	4	-.006	1	-4.283e-4	1	NC	1	NC	1
451		17	max	.005	3	-.002	15	.189	4	1.068e-2	4	NC	1	NC	1
452			min	-.004	2	-.006	4	-.008	1	-4.572e-4	1	NC	1	NC	1
453		18	max	.005	3	-.001	15	.203	4	1.141e-2	4	NC	1	NC	1
454			min	-.004	2	-.004	1	-.009	1	-4.86e-4	1	NC	1	NC	1
455		19	max	.006	3	0	10	.219	4	1.214e-2	4	NC	1	NC	2
456			min	-.004	2	-.003	1	-.01	1	-5.149e-4	1	NC	1	9014.597	1
457	M12	1	max	.003	1	.004	2	.01	1	-6.299e-6	12	NC	1	NC	3
458			min	0	3	-.006	3	-.219	4	-1.268e-4	4	NC	1	113.258	4
459		2	max	.002	1	.004	2	.009	1	-6.299e-6	12	NC	1	NC	3
460			min	0	3	-.006	3	-.202	4	-1.268e-4	4	NC	1	123.09	4
461		3	max	.002	1	.004	2	.008	1	-6.299e-6	12	NC	1	NC	3
462			min	0	3	-.005	3	-.184	4	-1.268e-4	4	NC	1	134.796	4
463		4	max	.002	1	.003	2	.008	1	-6.299e-6	12	NC	1	NC	3
464			min	0	3	-.005	3	-.167	4	-1.268e-4	4	NC	1	148.86	4
465		5	max	.002	1	.003	2	.007	1	-6.299e-6	12	NC	1	NC	3
466			min	0	3	-.005	3	-.149	4	-1.268e-4	4	NC	1	165.943	4
467		6	max	.002	1	.003	2	.006	1	-6.299e-6	12	NC	1	NC	3
468			min	0	3	-.004	3	-.133	4	-1.268e-4	4	NC	1	186.961	4
469		7	max	.002	1	.003	2	.005	1	-6.299e-6	12	NC	1	NC	2
470			min	0	3	-.004	3	-.116	4	-1.268e-4	4	NC	1	213.214	4
471		8	max	.002	1	.002	2	.005	1	-6.299e-6	12	NC	1	NC	2
472			min	0	3	-.004	3	-.101	4	-1.268e-4	4	NC	1	246.596	4
473		9	max	.001	1	.002	2	.004	1	-6.299e-6	12	NC	1	NC	2
474			min	0	3	-.003	3	-.086	4	-1.268e-4	4	NC	1	289.961	4
475		10	max	.001	1	.002	2	.003	1	-6.299e-6	12	NC	1	NC	2
476			min	0	3	-.003	3	-.071	4	-1.268e-4	4	NC	1	347.769	4
477		11	max	.001	1	.002	2	.003	1	-6.299e-6	12	NC	1	NC	2
478			min	0	3	-.003	3	-.058	4	-1.268e-4	4	NC	1	427.315	4
479		12	max	0	1	.002	2	.002	1	-6.299e-6	12	NC	1	NC	1
480			min	0	3	-.002	3	-.046	4	-1.268e-4	4	NC	1	541.216	4
481		13	max	0	1	.001	2	.002	1	-6.299e-6	12	NC	1	NC	1
482			min	0	3	-.002	3	-.035	4	-1.268e-4	4	NC	1	712.889	4
483		14	max	0	1	.001	2	.001	1	-6.299e-6	12	NC	1	NC	1
484			min	0	3	-.002	3	-.025	4	-1.268e-4	4	NC	1	989.961	4
485		15	max	0	1	0	2	0	1	-6.299e-6	12	NC	1	NC	1
486			min	0	3	-.001	3	-.017	4	-1.268e-4	4	NC	1	1482.202	4
487		16	max	0	1	0	2	0	1	-6.299e-6	12	NC	1	NC	1
488			min	0	3	0	3	-.01	4	-1.268e-4	4	NC	1	2492.968	4

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
489		17	max	0	1	0	2	0	1	-6.299e-6	12	NC	1	NC	1
490			min	0	3	0	3	-.005	4	-1.268e-4	4	NC	1	5146.574	4
491		18	max	0	1	0	2	0	1	-6.299e-6	12	NC	1	NC	1
492			min	0	3	0	3	-.001	4	-1.268e-4	4	NC	1	NC	1
493		19	max	0	1	0	1	0	1	-6.299e-6	12	NC	1	NC	1
494			min	0	1	0	1	0	1	-1.268e-4	4	NC	1	NC	1
495	M1	1	max	.007	3	.087	2	.787	4	1.624e-2	1	NC	1	NC	1
496			min	-.003	2	-.01	3	0	12	-2.445e-2	3	NC	1	NC	1
497		2	max	.007	3	.041	2	.76	4	9.168e-3	4	NC	3	NC	1
498			min	-.003	2	-.003	3	-.007	1	-1.21e-2	3	2488.914	2	NC	1
499		3	max	.007	3	.011	3	.733	4	1.473e-2	4	NC	5	NC	2
500			min	-.003	2	-.009	2	-.011	1	-2.227e-4	1	1197.309	2	5752.441	5
501		4	max	.007	3	.035	3	.706	4	1.29e-2	4	NC	5	NC	1
502			min	-.003	2	-.065	2	-.01	1	-4.265e-3	3	753.828	2	4128.851	5
503		5	max	.007	3	.066	3	.679	4	1.106e-2	4	NC	15	NC	1
504			min	-.003	2	-.125	2	-.007	1	-8.408e-3	3	542.848	2	3316.72	5
505		6	max	.007	3	.1	3	.65	4	1.296e-2	1	NC	15	NC	1
506			min	-.003	2	-.182	2	-.003	1	-1.255e-2	3	426.826	2	2830.021	5
507		7	max	.007	3	.132	3	.621	4	1.736e-2	1	NC	15	NC	1
508			min	-.003	2	-.234	2	0	12	-1.669e-2	3	358.442	2	2486.831	4
509		8	max	.006	3	.16	3	.591	4	2.175e-2	1	9062.14	15	NC	1
510			min	-.003	2	-.274	2	0	12	-2.084e-2	3	318.039	2	2237.994	4
511		9	max	.006	3	.178	3	.559	4	2.414e-2	1	8465.017	15	NC	1
512			min	-.003	2	-.3	2	0	1	-2.086e-2	3	297.026	2	2086.475	4
513		10	max	.006	3	.184	3	.525	4	2.556e-2	2	8283.288	15	NC	1
514			min	-.003	2	-.309	2	0	12	-1.814e-2	3	290.856	2	2044.529	4
515		11	max	.006	3	.179	3	.488	4	2.769e-2	2	8464.719	15	NC	1
516			min	-.003	2	-.3	2	0	12	-1.542e-2	3	298.001	2	2094.915	4
517		12	max	.006	3	.164	3	.449	4	2.685e-2	2	9061.467	15	NC	1
518			min	-.003	2	-.273	2	-.001	1	-1.277e-2	3	321.034	2	2252.052	4
519		13	max	.006	3	.14	3	.407	4	2.155e-2	2	NC	15	NC	1
520			min	-.003	2	-.23	2	0	1	-1.022e-2	3	365.782	2	2643.336	4
521		14	max	.006	3	.109	3	.361	4	1.625e-2	2	NC	15	NC	1
522			min	-.003	2	-.177	2	0	12	-7.668e-3	3	441.448	1	3447.83	4
523		15	max	.005	3	.074	3	.315	4	1.095e-2	2	NC	15	NC	1
524			min	-.003	2	-.118	2	0	12	-5.117e-3	3	570.425	1	5167.598	4
525		16	max	.005	3	.038	3	.269	4	9.976e-3	4	NC	5	NC	1
526			min	-.003	2	-.059	2	0	12	-2.566e-3	3	808.933	1	9695.445	4
527		17	max	.005	3	.004	3	.226	4	1.115e-2	4	NC	5	NC	1
528			min	-.003	2	-.005	2	0	12	-1.45e-5	3	1317.988	1	NC	1
529		18	max	.005	3	.042	1	.187	4	1.091e-2	2	NC	4	NC	1
530			min	-.003	2	-.027	3	0	12	-4.3e-3	3	2790.946	1	NC	1
531		19	max	.005	3	.083	1	.152	4	2.184e-2	2	NC	1	NC	1
532			min	-.002	2	-.055	3	-.002	1	-8.746e-3	3	NC	1	NC	1
533	M5	1	max	.022	3	.215	2	.786	4	0	1	NC	1	NC	1
534			min	-.015	2	-.012	3	0	1	-4.923e-6	4	NC	1	NC	1
535		2	max	.022	3	.099	2	.766	4	7.574e-3	4	NC	5	NC	1
536			min	-.015	2	.001	3	0	1	0	1	1002.627	2	7879.661	4
537		3	max	.022	3	.034	3	.741	4	1.492e-2	4	NC	15	NC	1
538			min	-.015	2	-.029	2	0	1	0	1	473.487	2	4603.7	4
539		4	max	.022	3	.102	3	.713	4	1.215e-2	4	9409.474	15	NC	1
540			min	-.015	2	-.181	2	0	1	0	1	291.24	2	3552.291	4
541		5	max	.021	3	.195	3	.683	4	9.391e-3	4	6590.455	15	NC	1
542			min	-.014	2	-.345	2	0	1	0	1	205.8	2	3050.387	4
543		6	max	.021	3	.298	3	.652	4	6.627e-3	4	5077.093	15	NC	1
544			min	-.014	2	-.508	2	0	1	0	1	159.541	2	2746.497	4
545		7	max	.02	3	.399	3	.62	4	3.863e-3	4	4202.499	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
546			min	-.014	2	-.654	2	0	1	0	1	132.626	2	2510.376	4
547		8	max	.02	3	.483	3	.59	4	1.1e-3	4	3693.691	15	NC	1
548			min	-.013	2	-.771	2	0	1	0	1	116.891	2	2279.346	4
549		9	max	.019	3	.537	3	.559	4	0	1	3432.657	15	NC	1
550			min	-.013	2	-.846	2	0	1	-3.465e-6	5	108.79	2	2081.891	4
551		10	max	.019	3	.556	3	.525	4	0	1	3354.005	15	NC	1
552			min	-.013	2	-.87	2	0	1	-3.359e-6	5	106.416	2	2057.286	4
553		11	max	.019	3	.542	3	.488	4	0	1	3432.752	15	NC	1
554			min	-.013	2	-.845	2	0	1	-3.253e-6	5	109.158	2	2118.67	4
555		12	max	.018	3	.495	3	.451	4	7.882e-4	4	3693.921	15	NC	1
556			min	-.013	2	-.768	2	0	1	0	1	118.089	2	2210.322	4
557		13	max	.018	3	.42	3	.408	4	2.771e-3	4	4202.983	15	NC	1
558			min	-.012	2	-.644	2	0	1	0	1	135.255	1	2605.054	4
559		14	max	.017	3	.325	3	.36	4	4.753e-3	4	5078.062	15	NC	1
560			min	-.012	2	-.49	2	0	1	0	1	164.988	1	3634.505	4
561		15	max	.017	3	.22	3	.311	4	6.736e-3	4	6592.402	15	NC	1
562			min	-.012	2	-.323	2	0	1	0	1	217.074	1	6603.924	4
563		16	max	.016	3	.112	3	.263	4	8.718e-3	4	9413.589	15	NC	1
564			min	-.012	2	-.16	2	0	1	0	1	315.679	1	NC	1
565		17	max	.016	3	.012	3	.219	4	1.07e-2	4	NC	5	NC	1
566			min	-.012	2	-.016	2	0	1	0	1	531.373	1	NC	1
567		18	max	.016	3	.103	1	.182	4	5.433e-3	4	NC	5	NC	1
568			min	-.012	2	-.075	3	0	1	0	1	1155.302	1	NC	1
569		19	max	.016	3	.201	1	.153	4	0	1	NC	1	NC	1
570			min	-.012	2	-.153	3	0	1	-2.925e-6	4	NC	1	NC	1
571	M9	1	max	.007	3	.087	2	.786	4	2.445e-2	3	NC	1	NC	1
572			min	-.003	2	-.01	3	-.001	1	-1.624e-2	1	NC	1	NC	1
573		2	max	.007	3	.041	2	.765	4	1.21e-2	3	NC	3	NC	1
574			min	-.003	2	-.003	3	0	12	-7.864e-3	1	2488.914	2	8024.991	4
575		3	max	.007	3	.011	3	.74	4	1.489e-2	4	NC	5	NC	2
576			min	-.003	2	-.009	2	0	12	-7.989e-6	10	1197.309	2	4650.868	4
577		4	max	.007	3	.035	3	.712	4	1.167e-2	5	NC	5	NC	1
578			min	-.003	2	-.065	2	0	12	-4.173e-3	1	753.828	2	3557.678	4
579		5	max	.007	3	.066	3	.683	4	8.753e-3	5	NC	15	NC	1
580			min	-.003	2	-.125	2	0	12	-8.568e-3	1	542.848	2	3031.635	4
581		6	max	.007	3	.1	3	.652	4	1.255e-2	3	NC	15	NC	1
582			min	-.003	2	-.182	2	0	12	-1.296e-2	1	426.826	2	2715.74	4
583		7	max	.007	3	.132	3	.621	4	1.669e-2	3	NC	15	NC	1
584			min	-.003	2	-.234	2	0	1	-1.736e-2	1	358.442	2	2480.324	4
585		8	max	.006	3	.16	3	.59	4	2.084e-2	3	9041.312	15	NC	1
586			min	-.003	2	-.274	2	-.001	1	-2.175e-2	1	318.039	2	2263.345	4
587		9	max	.006	3	.178	3	.559	4	2.086e-2	3	8445.83	15	NC	1
588			min	-.003	2	-.3	2	0	12	-2.414e-2	1	297.026	2	2079.626	4
589		10	max	.006	3	.184	3	.525	4	1.814e-2	3	8264.587	15	NC	1
590			min	-.003	2	-.309	2	0	1	-2.556e-2	2	290.856	2	2045.926	4
591		11	max	.006	3	.179	3	.488	4	1.542e-2	3	8445.558	15	NC	1
592			min	-.003	2	-.3	2	0	1	-2.769e-2	2	298.001	2	2104.178	4
593		12	max	.006	3	.164	3	.45	4	1.277e-2	3	9040.802	15	NC	1
594			min	-.003	2	-.273	2	0	12	-2.685e-2	2	321.034	2	2227.35	4
595		13	max	.006	3	.14	3	.407	4	1.022e-2	3	NC	15	NC	1
596			min	-.003	2	-.23	2	0	12	-2.155e-2	2	365.782	2	2646.418	4
597		14	max	.006	3	.109	3	.36	4	7.668e-3	3	NC	15	NC	1
598			min	-.003	2	-.177	2	-.003	1	-1.625e-2	2	441.448	1	3604.36	5
599		15	max	.005	3	.074	3	.311	4	6.337e-3	5	NC	15	NC	1
600			min	-.003	2	-.118	2	-.006	1	-1.095e-2	2	570.425	1	5922.571	5
601		16	max	.005	3	.038	3	.264	4	8.54e-3	5	NC	5	NC	1
602			min	-.003	2	-.059	2	-.009	1	-5.65e-3	2	808.933	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
603		17	max	.005	3	.004	3	.22	4	1.077e-2	4	NC	5	NC	1
604			min	-.003	2	-.005	2	-.01	1	-6.622e-4	1	1317.988	1	NC	1
605		18	max	.005	3	.042	1	.183	4	5.056e-3	5	NC	4	NC	1
606			min	-.003	2	-.027	3	-.007	1	-1.091e-2	2	2790.946	1	NC	1
607		19	max	.005	3	.083	1	.153	4	8.746e-3	3	NC	1	NC	1
608			min	-.002	2	-.055	3	0	12	-2.184e-2	2	NC	1	NC	1

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 4.00 x 0.28

<Figure 1>



<Figure 2>

Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	1723.0	23.0	593.0	593.4
Sum	1723.0	23.0	593.0	593.4

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 1723
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	5.247	10215

$\phi N_{cb} = \phi \, (A_{Nc} / A_{Nco}) \, \Psi_{ed,N} \, \Psi_{c,N} \, \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-4)

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cb} (lb)
220.36	247.75	0.967	1.00	1.000	10215	0.65	5710

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_a = \phi \, (A_{Na} / A_{Na0}) \, \Psi_{ed,Na} \, \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16a)

A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	ϕ	ϕN_a (lb)
109.66	109.66	1.000	1.000	9755	0.55	5365

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in y-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cby} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cby} (lb)
192.89	220.50	0.925	1.000	1.000	6947	0.70	3934

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cbx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbx} (lb)
165.27	278.72	0.878	1.000	1.000	8282	0.70	3018

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
192.89	220.50	1.000	1.000	1.000	6947	0.70	8508

Shear parallel to edge in y-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cby} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cby} (lb)
165.27	278.72	1.000	1.000	1.000	8282	0.70	6875

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cp} = \phi \min|k_{cp}N_a\,;\,k_{cp}N_{cb}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\,\Psi_{p,Na}N_{a0}\,;\,k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ed,N}\,\Psi_{c,N}\,\Psi_{cp,N}N_b|$ (Eq. D-30a)

k_{cp}	A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	109.66	109.66	1.000	1.000	9755	9755

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ	ϕV_{cp} (lb)
220.36	247.75	0.967	1.000	1.000	10215	8785	0.70	12298

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, ϕN_n (lb)	Ratio	Status
Steel	1723	6071	0.28	Pass
Concrete breakout	1723	5710	0.30	Pass
Adhesive	**1723**	**5365**	**0.32**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, ϕV_n (lb)	Ratio	Status
Steel	**593**	**3156**	**0.19**	**Pass (Governs)**
T Concrete breakout y+	593	3934	0.15	Pass
T Concrete breakout x+	23	3018	0.01	Pass
|| Concrete breakout y+	23	8508	0.00	Pass
|| Concrete breakout x+	593	6875	0.09	Pass
Concrete breakout, combined	-	-	0.15	Pass
Pryout	593	12298	0.05	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status
Sec. D.7.1	0.32	0.00	32.1 %	1.0	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

<Figure 1>

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 7.00 x 0.28



<Figure 2>



Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	2344.5	1654.5	0.0	1654.5
2	2344.5	1654.5	0.0	1654.5
Sum	4689.0	3309.0	0.0	3309.0

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 4689
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	6.000	12492

$\phi N_{cbg} = \phi (A_{Nc} / A_{Nco}) \Psi_{ec,N} \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-5)

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cbg} (lb)
378.00	324.00	1.000	0.972	1.00	1.000	12492	0.65	9208

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_{ag} = \phi (A_{Na} / A_{Na0}) \Psi_{ed,Na} \Psi_{g,Na} \Psi_{ec,Na} \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16b)

A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0}(lb)	ϕ	ϕN_{ag} (lb)
158.66	109.66	1.000	1.043	1.000	1.000	9755	0.55	8093

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	12.00	15593

$\phi V_{cbgx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ec,V}\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-22)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ec,V}$	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbgx} (lb)
378.00	648.00	1.000	0.836	1.000	1.000	15593	0.70	5323

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	8.16	8744

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
299.64	299.64	1.000	1.000	1.000	8744	0.70	12241

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cpg} = \phi \min|k_{cp}N_{ag}\,;\, k_{cp}N_{cbg}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\,\Psi_{g,Na}\,\Psi_{ec,Na}\,\Psi_{p,Na}N_{a0}\,;\, k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ec,N}\,\Psi_{ed,N}\,\Psi_{c,N}\,\Psi_{cp,N}N_b|$ (Eq. D-30b)

k_{cp}	A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	158.66	109.66	1.000	1.043	1.000	1.000	9755	14715

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ
378.00	324.00	1.000	0.972	1.000	1.000	12492	14166	0.70

ϕV_{cpg} (lb)
19833

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, ϕN_n (lb)	Ratio	Status
Steel	2345	6071	0.39	Pass
Concrete breakout	4689	9208	0.51	Pass
Adhesive	**4689**	**8093**	**0.58**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, ϕV_n (lb)	Ratio	Status
Steel	1655	3156	0.52	Pass
T Concrete breakout x+	**3309**	**5323**	**0.62**	**Pass (Governs)**
|| Concrete breakout y-	**1655**	**12241**	**0.14**	**Pass (Governs)**
Pryout	3309	19833	0.17	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status

Sec. D.7.3	0.58	0.62	120.1 %	1.2	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.