

Schletter, Inc.		30° Tilt w/o Seismic Design
HCV	Standard PVMax Racking System	
	Representative Calculations - ASCE 7-10	

1. INTRODUCTION

1.1 Project Description

The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. PVMax ground mount system.

1.2 Construction

Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to aluminum struts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

	Maximum		Minimum	
Height =	2000	mm	1900	mm
Width =	1050	mm	970	mm
Dead Load =	3.00	psf	1.75	psf

Modules Per Row =	2
Module Tilt =	30°
Maximum Height Above Grade =	3 ft



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

1.3 Technical Codes

- ASCE 7-10 - Chapter 26-31, Wind Loads
- ASCE 7-10 - Chapter 7, Snow Loads
- ASCE 7-10 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2012, 2015
- Aluminum Design Manual, Eighth Edition, 2005

2. LOAD ACTIONS

2.1 Permanent Loads

g_{MAX} =	3.00	psf	*Self-weight of the PV modules.*
g_{MIN} =	1.75	psf	

2.2 Snow Loads

Ground Snow Load, P_g =	30.00	psf	
Sloped Roof Snow Load, P_s =	16.49	psf	*(ASCE 7-10, Eq. 7.4-1)*
I_s =	1.00		
C_s =	0.73		
C_e =	0.90		
C_t =	1.20		

2.3 Wind Loads

Design Wind Speed, V =	110	mph	Exposure Category = C
Height <	15	ft	Importance Category = II
Peak Velocity Pressure, q_z =	19.00	psf	*Including the gust factor, G=0.85. (ASCE 7-10, Eq. 27.3-1)*

Pressure Coefficients

$Cf+_{TOP}$ =	1.150	*(Pressure)*	*Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0611-1e. Negative forces are applied away from the surface.*
$Cf+_{BOTTOM}$ =	1.850		
$Cf-_{TOP, OUTER PURLIN}$ =	-2.600		
$Cf-_{TOP, INNER PURLIN}$ =	-2.000	*(Suction)*	
$Cf-_{BOTTOM}$ =	-1.100		

2.4 Seismic Loads - N/A

S_S =	0.00	R =	1.25	*ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.*
S_{DS} =	0.00	C_S =	0	
S_1 =	0.00	ρ =	1.3	
S_{D1} =	0.00	Ω =	1.25	
T_a =	0.00	C_d =	1.25	

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.5W
1.2D + 1.0W + 0.5S
0.9D + 1.0W [M]
1.54D + 1.3E + 0.2S [R]
0.56D + 1.3E [R]
1.54D + 1.25E + 0.2S [O]
0.56D + 1.25E [O]

(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S
1.0D + 0.6W
1.0D + 0.75L + 0.45W + 0.75S
0.6D + 0.6W [M]
1.238D + 0.875E [O]
1.1785D + 0.65625E + 0.75S [O]
0.362D + 0.875E [O]

(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)

[M] *Uses the minimum allowable module dead load.*
[R] *Include redundancy factor of 1.3.*
[O] *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location
M13	Top
M14	Mid-Top
M15	Mid-Bottom
M16	Bottom

Girders	Location
M1	Outer
M5	Inner
M9	Outer

Front Struts	Location
M4	Outer
M8	Inner
M12	Outer

Diagonal Struts	Location
M3	Outer
M7	Inner
M11	Outer

Rear Struts	Location
M2	Outer
M6	Inner
M10	Outer

Front Reactions	Location
N7	Outer
N15	Inner
N23	Outer

Rear Reactions	Location
N8	Outer
N16	Inner
N24	Outer

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type =	**S1.5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	120	in
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	25.07	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	23.08	ksi
S_y =	1.33	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	2.16	in^4
I_x =	1.07	in^4
A =	1.25	in^2
g =	1.50	lbs/ft
M_y =	1.741	k-ft
M_z =	0.402	k-ft
$M_{y\ allowable}$ =	2.779	k-ft
$M_{z\ allowable}$ =	1.154	k-ft
Utilization =	97%	



DETAIL VIEW

4.2 Girder Design

Loads from purlins are transferred using an inclined girder, which is connected to a set of aluminum struts. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type =	**BF0**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	104.56	in
$\Phi F_{ty\ AXIAL}$ =	31.09	ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	29.00	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	33.25	ksi
S_y =	1.42	in^3
S_x =	1.41	in^3
E =	10100	ksi
I_y =	2.39	in^4
I_x =	2.22	in^4
A =	1.88	in^2
g =	2.26	lbs/ft
M_y =	-3.100	k-ft
M_z =	0.000	k-ft
P_n =	-0.810	k
$M_{y\ allowable}$ =	3.422	k-ft
$M_{z\ allowable}$ =	3.907	k-ft
$P_{n\ allowable}$ =	58.535	k
Utilization =	92%	



4.3 Front Strut Design

The front aluminum strut connects a portion of the girder to the foundation. Vertical girder forces are then transferred down through the strut into the foundation. The strut is attached with single M12 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	24.80	in
$\Phi F_{ty\ AXIAL}$ =	28.03	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.000	k-ft
M_z =	0.000	k-ft
P_n =	2.818	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	27.532	k
Utilization =	10%	



4.4 Diagonal Strut Design

A diagonal aluminum strut braces the support structure. It connects at a front portion of the girder and transfers horizontal forces to the rear foundation connection. The strut is attached with single M12 bolts at each end. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	98.03	in
$\Phi F_{ty\ AXIAL}$ =	6.11	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.011	k-ft
M_z =	0.000	k-ft
P_n =	2.189	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	6.000	k
Utilization =	37%	



4.5 Rear Strut Design

An aluminum strut connects the rear portion of the girder to the rear foundation connection. Both vertical and horizontal forces are transferred from the girder. The strut is attached with single M12 bolts at each end. See Appendix A.5 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	78.35	in
$\Phi F_{ty\ AXIAL}$ =	8.88	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	-0.010	k-ft
M_z =	0.000	k-ft
P_n =	3.135	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	8.726	k
Utilization =	37%	



5. FOUNDATION DESIGN CALCULATIONS

5.1 Helical Pile Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete foundation design.

Maximum	Front	Rear	
Tensile Load =	87.71	5358.80	k
Compressive Load =	3663.99	4535.75	k
Lateral Load =	24.37	3354.99	k
Moment (Weak Axis) =	0.05	0.01	k

5.2 Design of Ballast Foundations

Ballast foundations are used to secure the racking structure in place. The foundations are checked for potential overturning and sliding. Bearing pressures applied by the racking and ballast foundations are checked against the allowable bearing pressures provided by the IBC table 1806.2 (2012, 2015).



Concrete Properties

Weight of Concrete =	145 pcf
Compressive Strength =	2500 psi
Yield Strength =	60000 psi

Overturning Check

M_O =	145128.6 in-lbs
Resisting Force Required =	2029.77 lbs
S.F. =	1.67
Weight Required =	3382.95 lbs
Minimum Width =	35 in in
Weight Provided =	7559.64 lbs

Sliding

Force =	773.69 lbs
Friction =	0.4
Weight Required =	1934.22 lbs
Resisting Weight =	7559.64 lbs
Additional Weight Required =	0 lbs

Cohesion

Sliding Force =	773.69 lbs
Cohesion =	130 psf
Area =	34.76 ft^2
Resisting =	3779.82 lbs
Additional Weight Required =	0 lbs

Shear Key

Additional Force =	0 lbs
Lateral Bearing Pressure =	200 psf/ft
Required Depth =	0.00 ft
f'_c =	2500 psi
Length =	8 in

Footing Reinforcement

Use fiber reinforcing with (2) #5 rebar.

A minimum 143in long x 35in wide x 18in tall ballast foundation is required to resist overturning.

Use a 143in long x 35in wide x 18in tall ballast foundation to resist sliding. Friction is OK.

Use a 143in long x 35in wide x 18in tall ballast foundation. Cohesion is OK.

Shear key is not required.

Bearing Pressure

	Ballast Width			
	35 in	36 in	37 in	38 in
P_{ftg} = (145 pcf)(11.92 ft)(1.5 ft)(2.92 ft) =	7560 lbs	7776 lbs	7992 lbs	8208 lbs

ASD LC	1.0D + 1.0S				1.0D + 0.6W				1.0D + 0.75L + 0.45W + 0.75S				0.6D + 0.6W			
Width	35 in	36 in	37 in	38 in	35 in	36 in	37 in	38 in	35 in	36 in	37 in	38 in	35 in	36 in	37 in	38 in
F_A	1398 lbs	1398 lbs	1398 lbs	1398 lbs	1133 lbs	1133 lbs	1133 lbs	1133 lbs	1752 lbs	1752 lbs	1752 lbs	1752 lbs	-29 lbs	-29 lbs	-29 lbs	-29 lbs
F_B	1394 lbs	1394 lbs	1394 lbs	1394 lbs	1842 lbs	1842 lbs	1842 lbs	1842 lbs	2283 lbs	2283 lbs	2283 lbs	2283 lbs	-2463 lbs	-2463 lbs	-2463 lbs	-2463 lbs
F_V	207 lbs	207 lbs	207 lbs	207 lbs	1418 lbs	1418 lbs	1418 lbs	1418 lbs	1199 lbs	1199 lbs	1199 lbs	1199 lbs	-1547 lbs	-1547 lbs	-1547 lbs	-1547 lbs
P_{total}	10352 lbs	10568 lbs	10784 lbs	11000 lbs	10535 lbs	10751 lbs	10967 lbs	11183 lbs	11595 lbs	11811 lbs	12027 lbs	12243 lbs	2044 lbs	2173 lbs	2303 lbs	2433 lbs
M	3663 lbs-ft	3663 lbs-ft	3663 lbs-ft	3663 lbs-ft	2767 lbs-ft	2767 lbs-ft	2767 lbs-ft	2767 lbs-ft	4439 lbs-ft	4439 lbs-ft	4439 lbs-ft	4439 lbs-ft	4698 lbs-ft	4698 lbs-ft	4698 lbs-ft	4698 lbs-ft
e	0.35 ft	0.35 ft	0.34 ft	0.33 ft	0.26 ft	0.26 ft	0.25 ft	0.25 ft	0.38 ft	0.38 ft	0.37 ft	0.36 ft	2.30 ft	2.16 ft	2.04 ft	1.93 ft
L/6	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft
f_{min}	244.8 psf	244.0 psf	243.3 psf	242.6 psf	263.0 psf	261.8 psf	260.6 psf	259.4 psf	269.3 psf	267.8 psf	266.5 psf	265.2 psf	0.0 psf	0.0 psf	0.0 psf	1.8 psf
f_{max}	350.9 psf	347.2 psf	343.7 psf	340.4 psf	343.2 psf	339.7 psf	336.4 psf	333.3 psf	397.9 psf	392.9 psf	388.1 psf	383.7 psf	127.6 psf	127.2 psf	127.1 psf	127.1 psf

Maximum Bearing Pressure = 398 psf
Allowable Bearing Pressure = 1500 psf

Use a 143in long x 35in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Weak Side Design

Overturning Check

M_O =	1208.3 ft-lbs
Resisting Force Required =	828.53 lbs
S.F. =	1.67
Weight Required =	1380.88 lbs
Minimum Width =	35 in in
Weight Provided =	7559.64 lbs

A minimum 143in long x 35in wide x 18in tall ballast foundation is required to resist overturning.



Bearing Pressure

ASD LC	1.238D + 0.875E			1.1785D + 0.65625E + 0.75S			0.362D + 0.875E		
Width	35 in			35 in			35 in		
Support	Outer	Inner	Outer	Outer	Inner	Outer	Outer	Inner	Outer
F_Y	288 lbs	720 lbs	288 lbs	851 lbs	2344 lbs	851 lbs	84 lbs	211 lbs	84 lbs
F_V	3 lbs	0 lbs	3 lbs	10 lbs	0 lbs	10 lbs	1 lbs	0 lbs	1 lbs
P_{total}	9647 lbs	7560 lbs	9647 lbs	9760 lbs	7560 lbs	9760 lbs	2821 lbs	7560 lbs	2821 lbs
M	10 lbs-ft	0 lbs-ft	10 lbs-ft	33 lbs-ft	0 lbs-ft	33 lbs-ft	3 lbs-ft	0 lbs-ft	3 lbs-ft
e	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft
L/6	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft
f_{min}	276.9 psf	217.5 psf	276.9 psf	278.9 psf	217.5 psf	278.9 psf	81.0 psf	217.5 psf	81.0 psf
f_{max}	278.2 psf	217.5 psf	278.2 psf	282.8 psf	217.5 psf	282.8 psf	81.4 psf	217.5 psf	81.4 psf

Maximum Bearing Pressure = 283 psf
Allowable Bearing Pressure = 1500 psf

Use a 143in long x 35in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Foundation Requirements: 143in long x 26in wide x 18in tall ballast foundation and fiber reinforcing with (2) #5 rebar.

5.3 Foundation Anchors

Threaded rods are anchored to the the ballast foundations using the Simpson AT-XP epoxy solution. LRFD load results are compared to the allowable strengths of the epoxy solution. Please see the supplementary calculations provided by the Simpson Anchor Designer software.

6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of 80mm mounting clamps. The reliability of calculations is uncertain due to limited standards, therefore the strength of the clamp fasteners has been evaluated by load testing.

Fastening of Modules to Purlins

Maximum Uplifting Force	=	0.540 k
Allowable Uplift	=	1.214 k
Utilization	=	45%



Fastening of Purlins to Girders

Maximum Uplifting Force	=	1.914 k
Allowable Uplift	=	4.357 k
Utilization	=	44%



6.2 Strut Connections

The aluminum struts connect the aluminum girder ends to custom brackets with mounting holes. Single M12 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Front Strut

Maximum Axial Load	=	2.818 k
M12 Bolt Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	38%

Rear Strut

Maximum Axial Load	=	3.599 k
M12 Bolt Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	48%

Diagonal Strut

Maximum Axial Load	=	2.275 k
M12 Bolt Shear Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	31%

Bolt and bearing capacities are accounting for double shear. (ASCE 8-02, Eq. 5.3.4-1)



Struts under compression are shown to demonstrate the load transfer from the girder. Single M12 bolts are located at each end of the strut and are subjected to double shear.

7. SEISMIC DESIGN

7.1 Seismic Drift - N/A

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx}	=	60.93 in
Allowable Story Drift for All Other Structures, Δ	= {	$0.020h_{sx}$
		1.219 in
Max Drift, Δ_{MAX}	=	0.066 in

N/A

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **S1.5**

Strong Axis:		Weak Axis:	
3.4.14		**3.4.14**	
L_b =	120 in	L_b =	120
J =	0.432	J =	0.432
	331.976		211.117
$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$		$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$	
S1 =	0.51461	S1 =	0.51461
$S2 = \left(\frac{C_c}{1.6}\right)^2$		$S2 = \left(\frac{C_c}{1.6}\right)^2$	
S2 =	1701.56	S2 =	1701.56
φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]	φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L=	27.4 ksi	φF_L=	28.6
3.4.16		**3.4.16**	
b/t =	32.195	b/t =	37.0588
$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$		$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$	
S1 =	12.2	S1 =	12.2
$S2 = \frac{k_1 Bp}{1.6Dp}$		$S2 = \frac{k_1 Bp}{1.6Dp}$	
S2 =	46.7	S2 =	46.7
φF_L=	φb[Bp-1.6Dp*b/t]	φF_L=	φb[Bp-1.6Dp*b/t]
φF_L=	25.1 ksi	φF_L=	23.1 ksi
3.4.16.1	Not Used	**3.4.16.1**	
Rb/t =		N/A for Weak Direction	
$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$			
S1 =	1.1		
$S2 = C_t$			
S2 =	141.0		
φF_L=	1.17φyFcy		
φF_L=	38.9 ksi		
3.4.18		**3.4.18**	
h/t =	37.0588	h/t =	32.195
$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$		$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$	
S1 =	36.9	S1 =	36.9
m =	0.65	m =	0.65
C_0 =	40.985	C_0 =	45.5
Cc =	41.015	Cc =	45.5
$S2 = \frac{k_1 Bbr}{mDbr}$		$S2 = \frac{k_1 Bbr}{mDbr}$	
S2 =	77.2	S2 =	77.3
φF_L=	φb[Bbr-mDbr*h/t]	φF_L=	1.3φyFcy
φF_L=	43.2 ksi	φF_L=	43.2 ksi
φF_LSt=	25.1 ksi	φF_LWk=	23.1 ksi
Ix =	897074 mm^4	Iy =	446476 mm^4
	2.155 in^4		1.073 in^4
y =	41.015 mm	x =	45.5 mm
Sx =	1.335 in^3	Sy =	0.599 in^3
M_{max}St =	2.788 k-ft	M_{max}Wk =	1.152 k-ft

Compression

3.4.9

b/t = 32.195
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 25.1 ksi

b/t = 37.0588
S1 = 12.21
S2 = 32.70
φF_L = (φck2*√(BpE))/(1.6b/t)
φF_L = 21.9 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 21.94 ksi
A = 1215.13 mm^2
1.88 in^2
P_{max} = 41.32 kips

A.2 Design of Aluminum Girders - Aluminum Design Manual, 2005 Edition

Girder = **BF0**

Strong Axis:

3.4.14

L_b = 104.56 in
J = 1.08
179.85

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.0 ksi

3.4.16

b/t = 16.2

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 31.6 ksi

Weak Axis:

3.4.14

L_b = 104.56
J = 1.08
190.335

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 28.9

3.4.16

b/t = 7.4

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φyFcy
φF_L = 33.3 ksi

3.4.16.1 Used

Rb/t = 18.1

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= φb[Bt-Dt*√(Rb/t)]

φF_L= 31.1 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 7.4

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 35.2

m = 0.68

C_0 = 41.067

Cc = 43.717

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 73.8

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 29.0 ksi

Ix = 984962 mm^4

2.366 in^4

y = 43.717 mm

Sx = 1.375 in^3

$M_{max}St$ = 3.323 k-ft

3.4.18

h/t = 16.2

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 40

Cc = 40

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 33.3 ksi

Iy = 923544 mm^4

2.219 in^4

x = 40 mm

Sy = 1.409 in^3

$M_{max}Wk$ = 3.904 k-ft

Compression

3.4.9

b/t = 16.2

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 31.6 ksi

b/t = 7.4

S1 = 12.21

S2 = 32.70

φF_L= φyFcy

φF_L= 33.3 ksi

3.4.10

Rb/t = 18.1

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L= φc[Bt-Dt*√(Rb/t)]

φF_L= 31.09 ksi

φF_L= 31.09 ksi

A = 1215.13 mm^2

1.88 in^2

P_{max} = 58.55 kips

A.3 Design of Aluminum Struts (Front) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 24.8 in

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

Weak Axis:

3.4.14

L_b = 24.8

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 0.57371

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

S1* = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

S2* = 1.23671

φcc = 0.87952

φF_L = φcc(Bc-Dc*λ)

φF_L = 28.0279 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 28.03 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 28.85 kips

A.4 Design of Aluminum Struts (Diagonal) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 98.03 in

J = 0.942

152.985

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L = 29.4 ksi

Weak Axis:

3.4.14

L_b = 98.03

J = 0.942

152.985

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L = 29.4

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17 \frac{\theta_y}{\theta_b} Fcy}{1.6Dt} \right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 2.26776

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi} \sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.89749

φF_L= (φccFcy)/(λ²)

φF_L= 6.10803 ksi

3.4.9

b/t = 24.5
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

b/t = 24.5
S1 = 12.21
S2 = 32.70
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 6.11 ksi
A = 663.99 mm^2
1.03 in^2
P_{max} = 6.29 kips

A.5 Design of Aluminum Struts (Rear) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 78.35 in
J = 0.942
122.273

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.8 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

Weak Axis:

3.4.14

L_b = 78.35
J = 0.942
122.273

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.8

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 1.8125

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.83375

φF_L= (φccFcy)/(λ²)

φF_L= 8.88278 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 8.88 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 9.14 kips

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				4		
2	Dead Load, Min	DL		-1				4		
3	Snow Load	SL						4		
4	Wind Load - Pressure	WL						4		
5	Wind Load - Suction	WL						4		
6	Seismic - Lateral	EL								

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-9.843	-9.843	0	0
2	M14	Y	-9.843	-9.843	0	0
3	M15	Y	-9.843	-9.843	0	0
4	M16	Y	-9.843	-9.843	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-5.454	-5.454	0	0
2	M14	Y	-5.454	-5.454	0	0
3	M15	Y	-5.454	-5.454	0	0
4	M16	Y	-5.454	-5.454	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-46.866	-46.866	0	0
2	M14	Y	-46.866	-46.866	0	0
3	M15	Y	-46.866	-46.866	0	0
4	M16	Y	-46.866	-46.866	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	-71.679	-71.679	0	0
2	M14	y	-71.679	-71.679	0	0
3	M15	y	-115.31	-115.31	0	0
4	M16	y	-115.31	-115.31	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	162.058	162.058	0	0
2	M14	y	124.66	124.66	0	0
3	M15	y	68.563	68.563	0	0
4	M16	y	68.563	68.563	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.5W	Yes	Y		1	1.2	3	1.6	4	.5														
2	LRFD 1.2D + 1.0W + 0.5S	Yes	Y		1	1.2	3	.5	4	1														
3	LRFD 0.9D + 1.0W	Yes	Y		2	.9					5	1												
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3												
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3												
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25												
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25												

Load Combinations (Continued)

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
8																										
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																		
10	ASD 1.0D + 0.6W	Yes	Y		1	1			4	.6																
11	ASD 1.0D + 0.75L + 0.45W + 0....	Yes	Y		1	1	3	.75	4	.45																
12	ASD 0.6D + 0.6W	Yes	Y		2	.6					5	.6														
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875														
14	LATERAL - ASD 1.1785D + 0.65...	Yes	Y		1	1.1...	3	.75			6	.656														
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875														

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N8	max	656.403	2	1086.981	2	.909	1	.004	1	0	1	0	1
2		min	-828.811	3	-1274.08	3	.05	15	0	15	0	1	0	1
3	N7	max	.046	9	1108.169	1	-.898	15	-.002	15	0	1	0	1
4		min	-.175	2	11.267	3	-18.743	1	-.036	1	0	1	0	1
5	N15	max	.01	9	2818.457	1	0	1	0	1	0	1	0	1
6		min	-1.92	2	-67.468	3	0	2	0	2	0	1	0	1
7	N16	max	2429.245	2	3489.036	2	0	3	0	3	0	1	0	1
8		min	-2580.761	3	-4122.152	3	0	14	0	11	0	1	0	1
9	N23	max	.046	9	1108.169	1	18.743	1	.036	1	0	1	0	1
10		min	-.175	2	11.267	3	.898	15	.002	15	0	1	0	1
11	N24	max	656.403	2	1086.981	2	-.05	15	0	15	0	1	0	1
12		min	-828.811	3	-1274.08	3	-.909	1	-.004	1	0	1	0	1
13	Totals:	max	3739.78	2	10493.533	1	0	1						
14		min	-4238.44	3	-6715.246	3	0	2						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M13	1	max	108.144	1	415.589	1	-9.83	15	0	3	.304	1	0	1
2			min	5.05	15	-587.688	3	-211.545	1	-.014	2	.014	15	0	3
3		2	max	108.144	1	290.51	1	-7.547	15	0	3	.096	1	.556	3
4			min	5.05	15	-413.649	3	-162.321	1	-.014	2	.005	15	-.392	1
5		3	max	108.144	1	165.431	1	-5.265	15	0	3	0	12	.919	3
6			min	5.05	15	-239.611	3	-113.098	1	-.014	2	-.057	1	-.646	1
7		4	max	108.144	1	40.352	1	-2.983	15	0	3	-.006	12	1.089	3
8			min	5.05	15	-65.572	3	-63.875	1	-.014	2	-.155	1	-.76	1
9		5	max	108.144	1	108.466	3	-.701	15	0	3	-.009	12	1.065	3
10			min	5.05	15	-84.727	1	-14.651	1	-.014	2	-.199	1	-.735	1
11		6	max	108.144	1	282.505	3	34.572	1	0	3	-.009	15	.848	3
12			min	5.05	15	-209.807	1	.857	12	-.014	2	-.188	1	-.572	1
13		7	max	108.144	1	456.543	3	83.796	1	0	3	-.006	15	.437	3
14			min	5.05	15	-334.886	1	3.177	12	-.014	2	-.122	1	-.269	1
15		8	max	108.144	1	630.582	3	133.019	1	0	3	.002	2	.173	1
16			min	5.05	15	-459.965	1	5.496	12	-.014	2	-.004	3	-.167	3
17		9	max	108.144	1	804.62	3	182.243	1	0	3	.174	1	.753	1
18			min	5.05	15	-585.044	1	7.815	12	-.014	2	.005	12	-.964	3
19		10	max	108.144	1	710.123	1	-10.135	12	0	12	.403	1	1.473	1
20			min	5.05	15	-978.659	3	-231.466	1	-.014	2	.015	12	-1.955	3
21		11	max	108.144	1	585.044	1	-7.815	12	.014	2	.174	1	.753	1
22			min	5.05	15	-804.62	3	-182.243	1	0	3	.005	12	-.964	3
23		12	max	108.144	1	459.965	1	-5.496	12	.014	2	.002	2	.173	1
24			min	5.05	15	-630.582	3	-133.019	1	0	3	-.004	3	-.167	3
25		13	max	108.144	1	334.886	1	-3.177	12	.014	2	-.006	15	.437	3
26			min	5.05	15	-456.543	3	-83.796	1	0	3	-.122	1	-.269	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
27		14	max	108.144	1	209.807	1	-.857	12	.014	2	-.009	15	.848	3
28			min	5.05	15	-282.505	3	-34.572	1	0	3	-.188	1	-.572	1
29		15	max	108.144	1	84.727	1	14.651	1	.014	2	-.009	12	1.065	3
30			min	5.05	15	-108.466	3	.701	15	0	3	-.199	1	-.735	1
31		16	max	108.144	1	65.572	3	63.875	1	.014	2	-.006	12	1.089	3
32			min	5.05	15	-40.352	1	2.983	15	0	3	-.155	1	-.76	1
33		17	max	108.144	1	239.611	3	113.098	1	.014	2	0	12	.919	3
34			min	5.05	15	-165.431	1	5.265	15	0	3	-.057	1	-.646	1
35		18	max	108.144	1	413.649	3	162.321	1	.014	2	.096	1	.556	3
36			min	5.05	15	-290.51	1	7.547	15	0	3	.005	15	-.392	1
37		19	max	108.144	1	587.688	3	211.545	1	.014	2	.304	1	0	1
38			min	5.05	15	-415.589	1	9.83	15	0	3	.014	15	0	3
39	M14	1	max	58.625	1	452.254	1	-10.181	15	.01	3	.354	1	0	1
40			min	2.746	15	-467.655	3	-219.112	1	-.012	1	.017	15	0	3
41		2	max	58.625	1	327.175	1	-7.899	15	.01	3	.138	1	.446	3
42			min	2.746	15	-335.17	3	-169.889	1	-.012	1	.006	15	-.433	1
43		3	max	58.625	1	202.095	1	-5.616	15	.01	3	.002	3	.745	3
44			min	2.746	15	-202.685	3	-120.666	1	-.012	1	-.023	1	-.727	1
45		4	max	58.625	1	77.016	1	-3.334	15	.01	3	-.005	12	.896	3
46			min	2.746	15	-70.2	3	-71.442	1	-.012	1	-.13	1	-.882	1
47		5	max	58.625	1	62.286	3	-1.052	15	.01	3	-.008	12	.901	3
48			min	2.746	15	-48.063	1	-22.219	1	-.012	1	-.182	1	-.898	1
49		6	max	58.625	1	194.771	3	27.005	1	.01	3	-.008	15	.758	3
50			min	2.746	15	-173.142	1	.506	12	-.012	1	-.18	1	-.775	1
51		7	max	58.625	1	327.256	3	76.228	1	.01	3	-.006	15	.468	3
52			min	2.746	15	-298.221	1	2.825	12	-.012	1	-.122	1	-.513	1
53		8	max	58.625	1	459.741	3	125.452	1	.01	3	0	10	.031	3
54			min	2.746	15	-423.3	1	5.144	12	-.012	1	-.01	1	-.122	2
55		9	max	58.625	1	592.226	3	174.675	1	.01	3	.157	1	.427	1
56			min	2.746	15	-548.379	1	7.464	12	-.012	1	.004	12	-.554	3
57		10	max	58.625	1	673.459	1	-9.783	12	.01	3	.378	1	1.106	1
58			min	2.746	15	-724.711	3	-223.898	1	-.012	1	.014	12	-1.285	3
59		11	max	58.625	1	548.379	1	-7.464	12	.012	1	.157	1	.427	1
60			min	2.746	15	-592.226	3	-174.675	1	-.01	3	.004	12	-.554	3
61		12	max	58.625	1	423.3	1	-5.144	12	.012	1	0	10	.031	3
62			min	2.746	15	-459.741	3	-125.452	1	-.01	3	-.01	1	-.122	2
63		13	max	58.625	1	298.221	1	-2.825	12	.012	1	-.006	15	.468	3
64			min	2.746	15	-327.256	3	-76.228	1	-.01	3	-.122	1	-.513	1
65		14	max	58.625	1	173.142	1	-.506	12	.012	1	-.008	15	.758	3
66			min	2.746	15	-194.771	3	-27.005	1	-.01	3	-.18	1	-.775	1
67		15	max	58.625	1	48.063	1	22.219	1	.012	1	-.008	12	.901	3
68			min	2.746	15	-62.286	3	1.052	15	-.01	3	-.182	1	-.898	1
69		16	max	58.625	1	70.2	3	71.442	1	.012	1	-.005	12	.896	3
70			min	2.746	15	-77.016	1	3.334	15	-.01	3	-.13	1	-.882	1
71		17	max	58.625	1	202.685	3	120.666	1	.012	1	.002	3	.745	3
72			min	2.746	15	-202.095	1	5.616	15	-.01	3	-.023	1	-.727	1
73		18	max	58.625	1	335.17	3	169.889	1	.012	1	.138	1	.446	3
74			min	2.746	15	-327.175	1	7.899	15	-.01	3	.006	15	-.433	1
75		19	max	58.625	1	467.655	3	219.112	1	.012	1	.354	1	0	1
76			min	2.746	15	-452.254	1	10.181	15	-.01	3	.017	15	0	3
77	M15	1	max	-2.947	15	582.839	2	-10.176	15	.013	2	.354	1	0	2
78			min	-62.9	1	-257.645	3	-219.036	1	-.008	3	.016	15	0	3
79		2	max	-2.947	15	419.066	2	-7.894	15	.013	2	.138	1	.247	3
80			min	-62.9	1	-187.489	3	-169.812	1	-.008	3	.006	15	-.557	2
81		3	max	-2.947	15	255.292	2	-5.611	15	.013	2	.001	3	.417	3
82			min	-62.9	1	-117.334	3	-120.589	1	-.008	3	-.024	1	-.931	2
83		4	max	-2.947	15	91.519	2	-3.329	15	.013	2	-.005	12	.508	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
84			min	-62.9	1	-47.179	3	-71.365	1	-.008	3	-.13	1	-1.124	2
85		5	max	-2.947	15	22.976	3	-1.047	15	.013	2	-.008	12	.521	3
86			min	-62.9	1	-72.254	2	-22.142	1	-.008	3	-.182	1	-1.135	2
87		6	max	-2.947	15	93.131	3	27.082	1	.013	2	-.008	15	.457	3
88			min	-62.9	1	-236.027	2	.574	12	-.008	3	-.18	1	-.963	2
89		7	max	-2.947	15	163.287	3	76.305	1	.013	2	-.006	15	.315	3
90			min	-62.9	1	-399.8	2	2.893	12	-.008	3	-.122	1	-.61	2
91		8	max	-2.947	15	233.442	3	125.528	1	.013	2	0	10	.094	3
92			min	-62.9	1	-563.574	2	5.213	12	-.008	3	-.01	1	-.089	1
93		9	max	-2.947	15	303.597	3	174.752	1	.013	2	.157	1	.642	2
94			min	-62.9	1	-727.347	2	7.532	12	-.008	3	.005	12	-.204	3
95		10	max	-2.947	15	891.12	2	-9.851	12	.013	2	.378	1	1.541	2
96			min	-62.9	1	-373.752	3	-223.975	1	-.008	3	.014	12	-.581	3
97		11	max	-2.947	15	727.347	2	-7.532	12	.008	3	.157	1	.642	2
98			min	-62.9	1	-303.597	3	-174.752	1	-.013	2	.005	12	-.204	3
99		12	max	-2.947	15	563.574	2	-5.213	12	.008	3	0	10	.094	3
100			min	-62.9	1	-233.442	3	-125.528	1	-.013	2	-.01	1	-.089	1
101		13	max	-2.947	15	399.8	2	-2.893	12	.008	3	-.006	15	.315	3
102			min	-62.9	1	-163.287	3	-76.305	1	-.013	2	-.122	1	-.61	2
103		14	max	-2.947	15	236.027	2	-.574	12	.008	3	-.008	15	.457	3
104			min	-62.9	1	-93.131	3	-27.082	1	-.013	2	-.18	1	-.963	2
105		15	max	-2.947	15	72.254	2	22.142	1	.008	3	-.008	12	.521	3
106			min	-62.9	1	-22.976	3	1.047	15	-.013	2	-.182	1	-1.135	2
107		16	max	-2.947	15	47.179	3	71.365	1	.008	3	-.005	12	.508	3
108			min	-62.9	1	-91.519	2	3.329	15	-.013	2	-.13	1	-1.124	2
109		17	max	-2.947	15	117.334	3	120.589	1	.008	3	.001	3	.417	3
110			min	-62.9	1	-255.292	2	5.611	15	-.013	2	-.024	1	-.931	2
111		18	max	-2.947	15	187.489	3	169.812	1	.008	3	.138	1	.247	3
112			min	-62.9	1	-419.066	2	7.894	15	-.013	2	.006	15	-.557	2
113		19	max	-2.947	15	257.645	3	219.036	1	.008	3	.354	1	0	2
114			min	-62.9	1	-582.839	2	10.176	15	-.013	2	.016	15	0	3
115	M16	1	max	-5.698	15	547.361	2	-9.847	15	.011	1	.307	1	0	2
116			min	-121.703	1	-231.126	3	-212.027	1	-.011	3	.014	15	0	3
117		2	max	-5.698	15	383.588	2	-7.565	15	.011	1	.098	1	.218	3
118			min	-121.703	1	-160.971	3	-162.804	1	-.011	3	.005	15	-.517	2
119		3	max	-5.698	15	219.815	2	-5.283	15	.011	1	-.001	12	.358	3
120			min	-121.703	1	-90.816	3	-113.58	1	-.011	3	-.055	1	-.852	2
121		4	max	-5.698	15	56.042	2	-3.001	15	.011	1	-.006	12	.42	3
122			min	-121.703	1	-20.661	3	-64.357	1	-.011	3	-.154	1	-1.006	2
123		5	max	-5.698	15	49.494	3	-.719	15	.011	1	-.009	12	.404	3
124			min	-121.703	1	-107.732	2	-15.133	1	-.011	3	-.198	1	-.977	2
125		6	max	-5.698	15	119.649	3	34.09	1	.011	1	-.009	15	.31	3
126			min	-121.703	1	-271.505	2	1.058	12	-.011	3	-.188	1	-.766	2
127		7	max	-5.698	15	189.805	3	83.314	1	.011	1	-.006	15	.138	3
128			min	-121.703	1	-435.278	2	3.377	12	-.011	3	-.122	1	-.374	2
129		8	max	-5.698	15	259.96	3	132.537	1	.011	1	0	10	.201	2
130			min	-121.703	1	-599.051	2	5.697	12	-.011	3	-.003	3	-.112	3
131		9	max	-5.698	15	330.115	3	181.76	1	.011	1	.172	1	.958	2
132			min	-121.703	1	-762.824	2	8.016	12	-.011	3	.006	12	-.44	3
133		10	max	-5.698	15	926.597	2	-10.335	12	.011	1	.402	1	1.896	2
134			min	-121.703	1	-400.27	3	-230.984	1	-.011	3	.016	12	-.846	3
135		11	max	-5.698	15	762.824	2	-8.016	12	.011	3	.172	1	.958	2
136			min	-121.703	1	-330.115	3	-181.76	1	-.011	1	.006	12	-.44	3
137		12	max	-5.698	15	599.051	2	-5.697	12	.011	3	0	10	.201	2
138			min	-121.703	1	-259.96	3	-132.537	1	-.011	1	-.003	3	-.112	3
139		13	max	-5.698	15	435.278	2	-3.377	12	.011	3	-.006	15	.138	3
140			min	-121.703	1	-189.805	3	-83.314	1	-.011	1	-.122	1	-.374	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
141		14	max	-5.698	15	271.505	2	-1.058	12	.011	3	-.009	15	.31	3
142			min	-121.703	1	-119.649	3	-34.09	1	-.011	1	-.188	1	-.766	2
143		15	max	-5.698	15	107.732	2	15.133	1	.011	3	-.009	12	.404	3
144			min	-121.703	1	-49.494	3	.719	15	-.011	1	-.198	1	-.977	2
145		16	max	-5.698	15	20.661	3	64.357	1	.011	3	-.006	12	.42	3
146			min	-121.703	1	-56.042	2	3.001	15	-.011	1	-.154	1	-1.006	2
147		17	max	-5.698	15	90.816	3	113.58	1	.011	3	-.001	12	.358	3
148			min	-121.703	1	-219.815	2	5.283	15	-.011	1	-.055	1	-.852	2
149		18	max	-5.698	15	160.971	3	162.804	1	.011	3	.098	1	.218	3
150			min	-121.703	1	-383.588	2	7.565	15	-.011	1	.005	15	-.517	2
151		19	max	-5.698	15	231.126	3	212.027	1	.011	3	.307	1	0	2
152			min	-121.703	1	-547.361	2	9.847	15	-.011	1	.014	15	0	3
153	M2	1	max	987.235	1	2.022	4	.605	1	0	5	0	3	0	1
154			min	-1112.805	3	.476	15	.028	15	0	1	0	1	0	1
155		2	max	987.764	1	1.951	4	.605	1	0	5	0	1	0	15
156			min	-1112.408	3	.459	15	.028	15	0	1	0	15	0	4
157		3	max	988.294	1	1.88	4	.605	1	0	5	0	1	0	15
158			min	-1112.011	3	.442	15	.028	15	0	1	0	15	-.001	4
159		4	max	988.823	1	1.809	4	.605	1	0	5	0	1	0	15
160			min	-1111.614	3	.426	15	.028	15	0	1	0	15	-.002	4
161		5	max	989.352	1	1.738	4	.605	1	0	5	0	1	0	15
162			min	-1111.217	3	.409	15	.028	15	0	1	0	15	-.003	4
163		6	max	989.881	1	1.667	4	.605	1	0	5	.001	1	0	15
164			min	-1110.82	3	.392	15	.028	15	0	1	0	15	-.003	4
165		7	max	990.411	1	1.596	4	.605	1	0	5	.001	1	0	15
166			min	-1110.423	3	.375	15	.028	15	0	1	0	15	-.004	4
167		8	max	990.94	1	1.525	4	.605	1	0	5	.002	1	-.001	15
168			min	-1110.026	3	.359	15	.028	15	0	1	0	15	-.004	4
169		9	max	991.469	1	1.454	4	.605	1	0	5	.002	1	-.001	15
170			min	-1109.629	3	.342	15	.028	15	0	1	0	15	-.005	4
171		10	max	991.999	1	1.383	4	.605	1	0	5	.002	1	-.001	15
172			min	-1109.232	3	.325	15	.028	15	0	1	0	15	-.005	4
173		11	max	992.528	1	1.312	4	.605	1	0	5	.002	1	-.001	15
174			min	-1108.835	3	.309	15	.028	15	0	1	0	15	-.006	4
175		12	max	993.057	1	1.241	4	.605	1	0	5	.002	1	-.002	15
176			min	-1108.438	3	.292	15	.028	15	0	1	0	15	-.006	4
177		13	max	993.586	1	1.17	4	.605	1	0	5	.003	1	-.002	15
178			min	-1108.041	3	.275	15	.028	15	0	1	0	15	-.007	4
179		14	max	994.116	1	1.099	4	.605	1	0	5	.003	1	-.002	15
180			min	-1107.644	3	.259	15	.028	15	0	1	0	15	-.007	4
181		15	max	994.645	1	1.028	4	.605	1	0	5	.003	1	-.002	15
182			min	-1107.248	3	.242	15	.028	15	0	1	0	15	-.008	4
183		16	max	995.174	1	.957	4	.605	1	0	5	.003	1	-.002	15
184			min	-1106.851	3	.225	15	.028	15	0	1	0	15	-.008	4
185		17	max	995.704	1	.886	4	.605	1	0	5	.003	1	-.002	15
186			min	-1106.454	3	.207	12	.028	15	0	1	0	15	-.008	4
187		18	max	996.233	1	.815	4	.605	1	0	5	.004	1	-.002	15
188			min	-1106.057	3	.179	12	.028	15	0	1	0	15	-.009	4
189		19	max	996.762	1	.746	2	.605	1	0	5	.004	1	-.002	15
190			min	-1105.66	3	.152	12	.028	15	0	1	0	15	-.009	4
191	M3	1	max	576.657	2	8.874	4	.472	1	0	15	0	1	.009	4
192			min	-734.806	3	2.086	15	.022	15	0	1	0	15	.002	15
193		2	max	576.487	2	8.005	4	.472	1	0	15	0	1	.005	4
194			min	-734.933	3	1.882	15	.022	15	0	1	0	15	.001	12
195		3	max	576.316	2	7.136	4	.472	1	0	15	0	1	.002	2
196			min	-735.061	3	1.678	15	.022	15	0	1	0	15	0	3
197		4	max	576.146	2	6.267	4	.472	1	0	15	.001	1	0	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
198			min	-735.189	3	1.473	15	.022	15	0	1	0	15	-.002	3
199		5	max	575.976	2	5.398	4	.472	1	0	15	.001	1	-.001	15
200			min	-735.317	3	1.269	15	.022	15	0	1	0	15	-.005	4
201		6	max	575.805	2	4.53	4	.472	1	0	15	.002	1	-.002	15
202			min	-735.444	3	1.065	15	.022	15	0	1	0	15	-.007	4
203		7	max	575.635	2	3.661	4	.472	1	0	15	.002	1	-.002	15
204			min	-735.572	3	.861	15	.022	15	0	1	0	15	-.009	4
205		8	max	575.465	2	2.792	4	.472	1	0	15	.002	1	-.002	15
206			min	-735.7	3	.656	15	.022	15	0	1	0	15	-.01	4
207		9	max	575.294	2	1.923	4	.472	1	0	15	.002	1	-.003	15
208			min	-735.828	3	.452	15	.022	15	0	1	0	15	-.011	4
209		10	max	575.124	2	1.054	4	.472	1	0	15	.002	1	-.003	15
210			min	-735.955	3	.248	15	.022	15	0	1	0	15	-.012	4
211		11	max	574.954	2	.271	2	.472	1	0	15	.003	1	-.003	15
212			min	-736.083	3	-.067	3	.022	15	0	1	0	15	-.012	4
213		12	max	574.783	2	-.16	15	.472	1	0	15	.003	1	-.003	15
214			min	-736.211	3	-.684	4	.022	15	0	1	0	15	-.012	4
215		13	max	574.613	2	-.365	15	.472	1	0	15	.003	1	-.003	15
216			min	-736.339	3	-1.553	4	.022	15	0	1	0	15	-.012	4
217		14	max	574.443	2	-.569	15	.472	1	0	15	.003	1	-.003	15
218			min	-736.467	3	-2.422	4	.022	15	0	1	0	15	-.011	4
219		15	max	574.272	2	-.773	15	.472	1	0	15	.004	1	-.002	15
220			min	-736.594	3	-3.29	4	.022	15	0	1	0	15	-.009	4
221		16	max	574.102	2	-.977	15	.472	1	0	15	.004	1	-.002	15
222			min	-736.722	3	-4.159	4	.022	15	0	1	0	15	-.008	4
223		17	max	573.932	2	-1.182	15	.472	1	0	15	.004	1	-.001	15
224			min	-736.85	3	-5.028	4	.022	15	0	1	0	15	-.006	4
225		18	max	573.761	2	-1.386	15	.472	1	0	15	.004	1	0	15
226			min	-736.978	3	-5.897	4	.022	15	0	1	0	15	-.003	4
227		19	max	573.591	2	-1.59	15	.472	1	0	15	.004	1	0	1
228			min	-737.105	3	-6.766	4	.022	15	0	1	0	15	0	1
229	M4	1	max	1105.103	1	0	1	-.899	15	0	1	.004	1	0	1
230			min	8.967	3	0	1	-19.328	1	0	1	0	15	0	1
231		2	max	1105.273	1	0	1	-.899	15	0	1	.001	1	0	1
232			min	9.095	3	0	1	-19.328	1	0	1	0	15	0	1
233		3	max	1105.444	1	0	1	-.899	15	0	1	0	15	0	1
234			min	9.223	3	0	1	-19.328	1	0	1	0	1	0	1
235		4	max	1105.614	1	0	1	-.899	15	0	1	0	15	0	1
236			min	9.35	3	0	1	-19.328	1	0	1	-.003	1	0	1
237		5	max	1105.784	1	0	1	-.899	15	0	1	0	15	0	1
238			min	9.478	3	0	1	-19.328	1	0	1	-.005	1	0	1
239		6	max	1105.955	1	0	1	-.899	15	0	1	0	15	0	1
240			min	9.606	3	0	1	-19.328	1	0	1	-.008	1	0	1
241		7	max	1106.125	1	0	1	-.899	15	0	1	0	15	0	1
242			min	9.734	3	0	1	-19.328	1	0	1	-.01	1	0	1
243		8	max	1106.295	1	0	1	-.899	15	0	1	0	15	0	1
244			min	9.861	3	0	1	-19.328	1	0	1	-.012	1	0	1
245		9	max	1106.466	1	0	1	-.899	15	0	1	0	15	0	1
246			min	9.989	3	0	1	-19.328	1	0	1	-.014	1	0	1
247		10	max	1106.636	1	0	1	-.899	15	0	1	0	15	0	1
248			min	10.117	3	0	1	-19.328	1	0	1	-.016	1	0	1
249		11	max	1106.806	1	0	1	-.899	15	0	1	0	15	0	1
250			min	10.245	3	0	1	-19.328	1	0	1	-.019	1	0	1
251		12	max	1106.977	1	0	1	-.899	15	0	1	0	15	0	1
252			min	10.372	3	0	1	-19.328	1	0	1	-.021	1	0	1
253		13	max	1107.147	1	0	1	-.899	15	0	1	-.001	15	0	1
254			min	10.5	3	0	1	-19.328	1	0	1	-.023	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
255		14	max	1107.317	1	0	1	-.899	15	0	1	-.001	15	0	1
256			min	10.628	3	0	1	-19.328	1	0	1	-.025	1	0	1
257		15	max	1107.488	1	0	1	-.899	15	0	1	-.001	15	0	1
258			min	10.756	3	0	1	-19.328	1	0	1	-.028	1	0	1
259		16	max	1107.658	1	0	1	-.899	15	0	1	-.001	15	0	1
260			min	10.883	3	0	1	-19.328	1	0	1	-.03	1	0	1
261		17	max	1107.828	1	0	1	-.899	15	0	1	-.001	15	0	1
262			min	11.011	3	0	1	-19.328	1	0	1	-.032	1	0	1
263		18	max	1107.999	1	0	1	-.899	15	0	1	-.002	15	0	1
264			min	11.139	3	0	1	-19.328	1	0	1	-.034	1	0	1
265		19	max	1108.169	1	0	1	-.899	15	0	1	-.002	15	0	1
266			min	11.267	3	0	1	-19.328	1	0	1	-.036	1	0	1
267	M6	1	max	3125.705	1	2.173	2	0	1	0	1	0	1	0	1
268			min	-3599.169	3	.352	12	0	1	0	1	0	1	0	1
269		2	max	3126.235	1	2.118	2	0	1	0	1	0	1	0	12
270			min	-3598.772	3	.325	12	0	1	0	1	0	1	0	2
271		3	max	3126.764	1	2.062	2	0	1	0	1	0	1	0	12
272			min	-3598.375	3	.297	12	0	1	0	1	0	1	-.002	2
273		4	max	3127.293	1	2.007	2	0	1	0	1	0	1	0	12
274			min	-3597.978	3	.269	12	0	1	0	1	0	1	-.002	2
275		5	max	3127.822	1	1.951	2	0	1	0	1	0	1	0	12
276			min	-3597.581	3	.242	12	0	1	0	1	0	1	-.003	2
277		6	max	3128.352	1	1.896	2	0	1	0	1	0	1	0	12
278			min	-3597.184	3	.214	12	0	1	0	1	0	1	-.004	2
279		7	max	3128.881	1	1.841	2	0	1	0	1	0	1	0	12
280			min	-3596.787	3	.186	12	0	1	0	1	0	1	-.004	2
281		8	max	3129.41	1	1.785	2	0	1	0	1	0	1	0	12
282			min	-3596.39	3	.159	12	0	1	0	1	0	1	-.005	2
283		9	max	3129.94	1	1.73	2	0	1	0	1	0	1	0	12
284			min	-3595.993	3	.123	3	0	1	0	1	0	1	-.006	2
285		10	max	3130.469	1	1.675	2	0	1	0	1	0	1	0	12
286			min	-3595.596	3	.081	3	0	1	0	1	0	1	-.006	2
287		11	max	3130.998	1	1.619	2	0	1	0	1	0	1	0	12
288			min	-3595.199	3	.04	3	0	1	0	1	0	1	-.007	2
289		12	max	3131.527	1	1.564	2	0	1	0	1	0	1	0	12
290			min	-3594.802	3	-.002	3	0	1	0	1	0	1	-.007	2
291		13	max	3132.057	1	1.509	2	0	1	0	1	0	1	0	12
292			min	-3594.405	3	-.043	3	0	1	0	1	0	1	-.008	2
293		14	max	3132.586	1	1.453	2	0	1	0	1	0	1	0	12
294			min	-3594.008	3	-.085	3	0	1	0	1	0	1	-.008	2
295		15	max	3133.115	1	1.398	2	0	1	0	1	0	1	0	12
296			min	-3593.611	3	-.126	3	0	1	0	1	0	1	-.009	2
297		16	max	3133.645	1	1.343	2	0	1	0	1	0	1	0	3
298			min	-3593.214	3	-.168	3	0	1	0	1	0	1	-.009	2
299		17	max	3134.174	1	1.287	2	0	1	0	1	0	1	0	3
300			min	-3592.817	3	-.209	3	0	1	0	1	0	1	-.01	2
301		18	max	3134.703	1	1.232	2	0	1	0	1	0	1	0	3
302			min	-3592.42	3	-.251	3	0	1	0	1	0	1	-.01	2
303		19	max	3135.232	1	1.177	2	0	1	0	1	0	1	0	3
304			min	-3592.023	3	-.292	3	0	1	0	1	0	1	-.011	2
305	M7	1	max	2188.956	2	8.909	4	0	1	0	1	0	1	.011	2
306			min	-2272.423	3	2.091	15	0	1	0	1	0	1	0	3
307		2	max	2188.786	2	8.04	4	0	1	0	1	0	1	.008	2
308			min	-2272.551	3	1.887	15	0	1	0	1	0	1	-.002	3
309		3	max	2188.615	2	7.171	4	0	1	0	1	0	1	.005	2
310			min	-2272.678	3	1.683	15	0	1	0	1	0	1	-.003	3
311		4	max	2188.445	2	6.302	4	0	1	0	1	0	1	.002	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
312			min	-2272.806	3	1.479	15	0	1	0	1	0	1	-.005	3
313		5	max	2188.275	2	5.433	4	0	1	0	1	0	1	0	2
314			min	-2272.934	3	1.274	15	0	1	0	1	0	1	-.006	3
315		6	max	2188.104	2	4.564	4	0	1	0	1	0	1	-.002	15
316			min	-2273.062	3	1.07	15	0	1	0	1	0	1	-.007	3
317		7	max	2187.934	2	3.695	4	0	1	0	1	0	1	-.002	15
318			min	-2273.189	3	.866	15	0	1	0	1	0	1	-.009	4
319		8	max	2187.764	2	2.826	4	0	1	0	1	0	1	-.002	15
320			min	-2273.317	3	.662	15	0	1	0	1	0	1	-.01	4
321		9	max	2187.593	2	1.957	4	0	1	0	1	0	1	-.003	15
322			min	-2273.445	3	.417	12	0	1	0	1	0	1	-.011	4
323		10	max	2187.423	2	1.277	2	0	1	0	1	0	1	-.003	15
324			min	-2273.573	3	.062	3	0	1	0	1	0	1	-.012	4
325		11	max	2187.253	2	.6	2	0	1	0	1	0	1	-.003	15
326			min	-2273.701	3	-.446	3	0	1	0	1	0	1	-.012	4
327		12	max	2187.082	2	-.078	2	0	1	0	1	0	1	-.003	15
328			min	-2273.828	3	-.954	3	0	1	0	1	0	1	-.012	4
329		13	max	2186.912	2	-.359	15	0	1	0	1	0	1	-.003	15
330			min	-2273.956	3	-1.518	4	0	1	0	1	0	1	-.012	4
331		14	max	2186.742	2	-.564	15	0	1	0	1	0	1	-.003	15
332			min	-2274.084	3	-2.387	4	0	1	0	1	0	1	-.011	4
333		15	max	2186.571	2	-.768	15	0	1	0	1	0	1	-.002	15
334			min	-2274.212	3	-3.256	4	0	1	0	1	0	1	-.009	4
335		16	max	2186.401	2	-.972	15	0	1	0	1	0	1	-.002	15
336			min	-2274.339	3	-4.125	4	0	1	0	1	0	1	-.008	4
337		17	max	2186.231	2	-1.176	15	0	1	0	1	0	1	-.001	15
338			min	-2274.467	3	-4.994	4	0	1	0	1	0	1	-.006	4
339		18	max	2186.06	2	-1.381	15	0	1	0	1	0	1	0	15
340			min	-2274.595	3	-5.863	4	0	1	0	1	0	1	-.003	4
341		19	max	2185.89	2	-1.585	15	0	1	0	1	0	1	0	1
342			min	-2274.723	3	-6.732	4	0	1	0	1	0	1	0	1
343	M8	1	max	2815.391	1	0	1	0	1	0	1	0	1	0	1
344			min	-69.768	3	0	1	0	1	0	1	0	1	0	1
345		2	max	2815.561	1	0	1	0	1	0	1	0	1	0	1
346			min	-69.64	3	0	1	0	1	0	1	0	1	0	1
347		3	max	2815.732	1	0	1	0	1	0	1	0	1	0	1
348			min	-69.512	3	0	1	0	1	0	1	0	1	0	1
349		4	max	2815.902	1	0	1	0	1	0	1	0	1	0	1
350			min	-69.385	3	0	1	0	1	0	1	0	1	0	1
351		5	max	2816.072	1	0	1	0	1	0	1	0	1	0	1
352			min	-69.257	3	0	1	0	1	0	1	0	1	0	1
353		6	max	2816.243	1	0	1	0	1	0	1	0	1	0	1
354			min	-69.129	3	0	1	0	1	0	1	0	1	0	1
355		7	max	2816.413	1	0	1	0	1	0	1	0	1	0	1
356			min	-69.001	3	0	1	0	1	0	1	0	1	0	1
357		8	max	2816.583	1	0	1	0	1	0	1	0	1	0	1
358			min	-68.874	3	0	1	0	1	0	1	0	1	0	1
359		9	max	2816.754	1	0	1	0	1	0	1	0	1	0	1
360			min	-68.746	3	0	1	0	1	0	1	0	1	0	1
361		10	max	2816.924	1	0	1	0	1	0	1	0	1	0	1
362			min	-68.618	3	0	1	0	1	0	1	0	1	0	1
363		11	max	2817.094	1	0	1	0	1	0	1	0	1	0	1
364			min	-68.49	3	0	1	0	1	0	1	0	1	0	1
365		12	max	2817.265	1	0	1	0	1	0	1	0	1	0	1
366			min	-68.363	3	0	1	0	1	0	1	0	1	0	1
367		13	max	2817.435	1	0	1	0	1	0	1	0	1	0	1
368			min	-68.235	3	0	1	0	1	0	1	0	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
369		14	max	2817.605	1	0	1	0	1	0	1	0	1	0	1
370			min	-68.107	3	0	1	0	1	0	1	0	1	0	1
371		15	max	2817.776	1	0	1	0	1	0	1	0	1	0	1
372			min	-67.979	3	0	1	0	1	0	1	0	1	0	1
373		16	max	2817.946	1	0	1	0	1	0	1	0	1	0	1
374			min	-67.851	3	0	1	0	1	0	1	0	1	0	1
375		17	max	2818.117	1	0	1	0	1	0	1	0	1	0	1
376			min	-67.724	3	0	1	0	1	0	1	0	1	0	1
377		18	max	2818.287	1	0	1	0	1	0	1	0	1	0	1
378			min	-67.596	3	0	1	0	1	0	1	0	1	0	1
379		19	max	2818.457	1	0	1	0	1	0	1	0	1	0	1
380			min	-67.468	3	0	1	0	1	0	1	0	1	0	1
381	M10	1	max	987.235	1	2.022	4	-.028	15	0	1	0	1	0	1
382			min	-1112.805	3	.476	15	-.605	1	0	5	0	3	0	1
383		2	max	987.764	1	1.951	4	-.028	15	0	1	0	15	0	15
384			min	-1112.408	3	.459	15	-.605	1	0	5	0	1	0	4
385		3	max	988.294	1	1.88	4	-.028	15	0	1	0	15	0	15
386			min	-1112.011	3	.442	15	-.605	1	0	5	0	1	-.001	4
387		4	max	988.823	1	1.809	4	-.028	15	0	1	0	15	0	15
388			min	-1111.614	3	.426	15	-.605	1	0	5	0	1	-.002	4
389		5	max	989.352	1	1.738	4	-.028	15	0	1	0	15	0	15
390			min	-1111.217	3	.409	15	-.605	1	0	5	0	1	-.003	4
391		6	max	989.881	1	1.667	4	-.028	15	0	1	0	15	0	15
392			min	-1110.82	3	.392	15	-.605	1	0	5	-.001	1	-.003	4
393		7	max	990.411	1	1.596	4	-.028	15	0	1	0	15	0	15
394			min	-1110.423	3	.375	15	-.605	1	0	5	-.001	1	-.004	4
395		8	max	990.94	1	1.525	4	-.028	15	0	1	0	15	-.001	15
396			min	-1110.026	3	.359	15	-.605	1	0	5	-.002	1	-.004	4
397		9	max	991.469	1	1.454	4	-.028	15	0	1	0	15	-.001	15
398			min	-1109.629	3	.342	15	-.605	1	0	5	-.002	1	-.005	4
399		10	max	991.999	1	1.383	4	-.028	15	0	1	0	15	-.001	15
400			min	-1109.232	3	.325	15	-.605	1	0	5	-.002	1	-.005	4
401		11	max	992.528	1	1.312	4	-.028	15	0	1	0	15	-.001	15
402			min	-1108.835	3	.309	15	-.605	1	0	5	-.002	1	-.006	4
403		12	max	993.057	1	1.241	4	-.028	15	0	1	0	15	-.002	15
404			min	-1108.438	3	.292	15	-.605	1	0	5	-.002	1	-.006	4
405		13	max	993.586	1	1.17	4	-.028	15	0	1	0	15	-.002	15
406			min	-1108.041	3	.275	15	-.605	1	0	5	-.003	1	-.007	4
407		14	max	994.116	1	1.099	4	-.028	15	0	1	0	15	-.002	15
408			min	-1107.644	3	.259	15	-.605	1	0	5	-.003	1	-.007	4
409		15	max	994.645	1	1.028	4	-.028	15	0	1	0	15	-.002	15
410			min	-1107.248	3	.242	15	-.605	1	0	5	-.003	1	-.008	4
411		16	max	995.174	1	.957	4	-.028	15	0	1	0	15	-.002	15
412			min	-1106.851	3	.225	15	-.605	1	0	5	-.003	1	-.008	4
413		17	max	995.704	1	.886	4	-.028	15	0	1	0	15	-.002	15
414			min	-1106.454	3	.207	12	-.605	1	0	5	-.003	1	-.008	4
415		18	max	996.233	1	.815	4	-.028	15	0	1	0	15	-.002	15
416			min	-1106.057	3	.179	12	-.605	1	0	5	-.004	1	-.009	4
417		19	max	996.762	1	.746	2	-.028	15	0	1	0	15	-.002	15
418			min	-1105.66	3	.152	12	-.605	1	0	5	-.004	1	-.009	4
419	M11	1	max	576.657	2	8.874	4	-.022	15	0	1	0	15	.009	4
420			min	-734.806	3	2.086	15	-.472	1	0	15	0	1	.002	15
421		2	max	576.487	2	8.005	4	-.022	15	0	1	0	15	.005	4
422			min	-734.933	3	1.882	15	-.472	1	0	15	0	1	.001	12
423		3	max	576.316	2	7.136	4	-.022	15	0	1	0	15	.002	2
424			min	-735.061	3	1.678	15	-.472	1	0	15	0	1	0	3
425		4	max	576.146	2	6.267	4	-.022	15	0	1	0	15	0	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
426			min	-735.189	3	1.473	15	-.472	1	0	15	-.001	1	-.002	3
427		5	max	575.976	2	5.398	4	-.022	15	0	1	0	15	-.001	15
428			min	-735.317	3	1.269	15	-.472	1	0	15	-.001	1	-.005	4
429		6	max	575.805	2	4.53	4	-.022	15	0	1	0	15	-.002	15
430			min	-735.444	3	1.065	15	-.472	1	0	15	-.002	1	-.007	4
431		7	max	575.635	2	3.661	4	-.022	15	0	1	0	15	-.002	15
432			min	-735.572	3	.861	15	-.472	1	0	15	-.002	1	-.009	4
433		8	max	575.465	2	2.792	4	-.022	15	0	1	0	15	-.002	15
434			min	-735.7	3	.656	15	-.472	1	0	15	-.002	1	-.01	4
435		9	max	575.294	2	1.923	4	-.022	15	0	1	0	15	-.003	15
436			min	-735.828	3	.452	15	-.472	1	0	15	-.002	1	-.011	4
437		10	max	575.124	2	1.054	4	-.022	15	0	1	0	15	-.003	15
438			min	-735.955	3	.248	15	-.472	1	0	15	-.002	1	-.012	4
439		11	max	574.954	2	.271	2	-.022	15	0	1	0	15	-.003	15
440			min	-736.083	3	-.067	3	-.472	1	0	15	-.003	1	-.012	4
441		12	max	574.783	2	-.16	15	-.022	15	0	1	0	15	-.003	15
442			min	-736.211	3	-.684	4	-.472	1	0	15	-.003	1	-.012	4
443		13	max	574.613	2	-.365	15	-.022	15	0	1	0	15	-.003	15
444			min	-736.339	3	-1.553	4	-.472	1	0	15	-.003	1	-.012	4
445		14	max	574.443	2	-.569	15	-.022	15	0	1	0	15	-.003	15
446			min	-736.467	3	-2.422	4	-.472	1	0	15	-.003	1	-.011	4
447		15	max	574.272	2	-.773	15	-.022	15	0	1	0	15	-.002	15
448			min	-736.594	3	-3.29	4	-.472	1	0	15	-.004	1	-.009	4
449		16	max	574.102	2	-.977	15	-.022	15	0	1	0	15	-.002	15
450			min	-736.722	3	-4.159	4	-.472	1	0	15	-.004	1	-.008	4
451		17	max	573.932	2	-1.182	15	-.022	15	0	1	0	15	-.001	15
452			min	-736.85	3	-5.028	4	-.472	1	0	15	-.004	1	-.006	4
453		18	max	573.761	2	-1.386	15	-.022	15	0	1	0	15	0	15
454			min	-736.978	3	-5.897	4	-.472	1	0	15	-.004	1	-.003	4
455		19	max	573.591	2	-1.59	15	-.022	15	0	1	0	15	0	1
456			min	-737.105	3	-6.766	4	-.472	1	0	15	-.004	1	0	1
457	M12	1	max	1105.103	1	0	1	19.328	1	0	1	0	15	0	1
458			min	8.967	3	0	1	.899	15	0	1	-.004	1	0	1
459		2	max	1105.273	1	0	1	19.328	1	0	1	0	15	0	1
460			min	9.095	3	0	1	.899	15	0	1	-.001	1	0	1
461		3	max	1105.444	1	0	1	19.328	1	0	1	0	1	0	1
462			min	9.223	3	0	1	.899	15	0	1	0	15	0	1
463		4	max	1105.614	1	0	1	19.328	1	0	1	.003	1	0	1
464			min	9.35	3	0	1	.899	15	0	1	0	15	0	1
465		5	max	1105.784	1	0	1	19.328	1	0	1	.005	1	0	1
466			min	9.478	3	0	1	.899	15	0	1	0	15	0	1
467		6	max	1105.955	1	0	1	19.328	1	0	1	.008	1	0	1
468			min	9.606	3	0	1	.899	15	0	1	0	15	0	1
469		7	max	1106.125	1	0	1	19.328	1	0	1	.01	1	0	1
470			min	9.734	3	0	1	.899	15	0	1	0	15	0	1
471		8	max	1106.295	1	0	1	19.328	1	0	1	.012	1	0	1
472			min	9.861	3	0	1	.899	15	0	1	0	15	0	1
473		9	max	1106.466	1	0	1	19.328	1	0	1	.014	1	0	1
474			min	9.989	3	0	1	.899	15	0	1	0	15	0	1
475		10	max	1106.636	1	0	1	19.328	1	0	1	.016	1	0	1
476			min	10.117	3	0	1	.899	15	0	1	0	15	0	1
477		11	max	1106.806	1	0	1	19.328	1	0	1	.019	1	0	1
478			min	10.245	3	0	1	.899	15	0	1	0	15	0	1
479		12	max	1106.977	1	0	1	19.328	1	0	1	.021	1	0	1
480			min	10.372	3	0	1	.899	15	0	1	0	15	0	1
481		13	max	1107.147	1	0	1	19.328	1	0	1	.023	1	0	1
482			min	10.5	3	0	1	.899	15	0	1	.001	15	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
483		14	max	1107.317	1	0	1	19.328	1	0	1	.025	1	0	1
484			min	10.628	3	0	1	.899	15	0	1	.001	15	0	1
485		15	max	1107.488	1	0	1	19.328	1	0	1	.028	1	0	1
486			min	10.756	3	0	1	.899	15	0	1	.001	15	0	1
487		16	max	1107.658	1	0	1	19.328	1	0	1	.03	1	0	1
488			min	10.883	3	0	1	.899	15	0	1	.001	15	0	1
489		17	max	1107.828	1	0	1	19.328	1	0	1	.032	1	0	1
490			min	11.011	3	0	1	.899	15	0	1	.001	15	0	1
491		18	max	1107.999	1	0	1	19.328	1	0	1	.034	1	0	1
492			min	11.139	3	0	1	.899	15	0	1	.002	15	0	1
493		19	max	1108.169	1	0	1	19.328	1	0	1	.036	1	0	1
494			min	11.267	3	0	1	.899	15	0	1	.002	15	0	1
495	M1	1	max	211.552	1	587.636	3	-5.05	15	0	1	.304	1	0	3
496			min	9.83	15	-413.278	1	-107.925	1	0	3	.014	15	-.014	2
497		2	max	212.395	1	586.542	3	-5.05	15	0	1	.237	1	.243	1
498			min	10.084	15	-414.737	1	-107.925	1	0	3	.011	15	-.365	3
499		3	max	471.337	3	481.346	1	-5.022	15	0	3	.17	1	.491	1
500			min	-289.887	2	-434.008	3	-107.653	1	0	1	.008	15	-.717	3
501		4	max	471.969	3	479.887	1	-5.022	15	0	3	.103	1	.193	1
502			min	-289.044	2	-435.103	3	-107.653	1	0	1	.005	15	-.447	3
503		5	max	472.601	3	478.428	1	-5.022	15	0	3	.036	1	-.005	15
504			min	-288.202	2	-436.197	3	-107.653	1	0	1	.002	15	-.177	3
505		6	max	473.232	3	476.969	1	-5.022	15	0	3	-.001	15	.094	3
506			min	-287.36	2	-437.291	3	-107.653	1	0	1	-.031	1	-.412	2
507		7	max	473.864	3	475.51	1	-5.022	15	0	3	-.005	15	.366	3
508			min	-286.517	2	-438.386	3	-107.653	1	0	1	-.097	1	-.698	2
509		8	max	474.496	3	474.051	1	-5.022	15	0	3	-.008	15	.638	3
510			min	-285.675	2	-439.48	3	-107.653	1	0	1	-.164	1	-.991	1
511		9	max	491.887	3	41.668	2	-7.768	15	0	9	.101	1	.746	3
512			min	-193.969	2	.446	15	-166.343	1	0	3	.005	15	-1.13	1
513		10	max	492.519	3	40.209	2	-7.768	15	0	9	0	15	.727	3
514			min	-193.126	2	.006	15	-166.343	1	0	3	-.002	1	-1.15	2
515		11	max	493.15	3	38.75	2	-7.768	15	0	9	-.005	15	.71	3
516			min	-192.284	2	-1.733	4	-166.343	1	0	3	-.105	1	-1.175	2
517		12	max	510.43	3	288.848	3	-4.822	15	0	2	.161	1	.619	3
518			min	-106.691	10	-544.473	2	-103.534	1	0	3	.007	15	-1.041	2
519		13	max	511.062	3	287.753	3	-4.822	15	0	2	.096	1	.44	3
520			min	-105.989	10	-545.932	2	-103.534	1	0	3	.004	15	-.702	2
521		14	max	511.694	3	286.659	3	-4.822	15	0	2	.032	1	.262	3
522			min	-105.287	10	-547.391	2	-103.534	1	0	3	.002	15	-.376	1
523		15	max	512.325	3	285.565	3	-4.822	15	0	2	-.001	15	.084	3
524			min	-104.585	10	-548.85	2	-103.534	1	0	3	-.032	1	-.052	1
525		16	max	512.957	3	284.47	3	-4.822	15	0	2	-.004	15	.318	2
526			min	-103.883	10	-550.309	2	-103.534	1	0	3	-.096	1	-.093	3
527		17	max	513.589	3	283.376	3	-4.822	15	0	2	-.007	15	.66	2
528			min	-103.181	10	-551.768	2	-103.534	1	0	3	-.161	1	-.269	3
529		18	max	-10.101	15	549.686	2	-5.698	15	0	3	-.011	15	.331	2
530			min	-212.863	1	-230.142	3	-121.909	1	0	2	-.231	1	-.132	3
531		19	max	-9.847	15	548.227	2	-5.698	15	0	3	-.014	15	.011	3
532			min	-212.021	1	-231.237	3	-121.909	1	0	2	-.307	1	-.011	1
533	M5	1	max	462.917	1	1957.171	3	0	1	0	1	0	1	.029	2
534			min	20.271	12	-1408.3	1	0	1	0	1	0	1	0	3
535		2	max	463.759	1	1956.077	3	0	1	0	1	0	1	.902	1
536			min	20.692	12	-1409.759	1	0	1	0	1	0	1	-1.214	3
537		3	max	1495.667	3	1406.958	1	0	1	0	1	0	1	1.746	1
538			min	-1005.433	2	-1362.61	3	0	1	0	1	0	1	-2.391	3
539		4	max	1496.298	3	1405.499	1	0	1	0	1	0	1	.873	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
540			min	-1004.59	2	-1363.704	3	0	1	0	1	0	1	-1.545	3
541		5	max	1496.93	3	1404.04	1	0	1	0	1	0	1	.024	9
542			min	-1003.748	2	-1364.798	3	0	1	0	1	0	1	-.699	3
543		6	max	1497.562	3	1402.581	1	0	1	0	1	0	1	.149	3
544			min	-1002.906	2	-1365.893	3	0	1	0	1	0	1	-.894	2
545		7	max	1498.194	3	1401.122	1	0	1	0	1	0	1	.997	3
546			min	-1002.063	2	-1366.987	3	0	1	0	1	0	1	-1.739	1
547		8	max	1498.826	3	1399.663	1	0	1	0	1	0	1	1.845	3
548			min	-1001.221	2	-1368.081	3	0	1	0	1	0	1	-2.609	1
549		9	max	1528.562	3	139.322	2	0	1	0	1	0	1	2.126	3
550			min	-811.61	2	.445	15	0	1	0	1	0	1	-2.96	1
551		10	max	1529.194	3	137.863	2	0	1	0	1	0	1	2.059	3
552			min	-810.768	2	.005	15	0	1	0	1	0	1	-3.015	2
553		11	max	1529.826	3	136.403	2	0	1	0	1	0	1	1.992	3
554			min	-809.925	2	-1.459	4	0	1	0	1	0	1	-3.1	2
555		12	max	1559.786	3	887.367	3	0	1	0	1	0	1	1.748	3
556			min	-620.332	2	-1627.212	2	0	1	0	1	0	1	-2.772	2
557		13	max	1560.417	3	886.273	3	0	1	0	1	0	1	1.198	3
558			min	-619.49	2	-1628.671	2	0	1	0	1	0	1	-1.761	2
559		14	max	1561.049	3	885.179	3	0	1	0	1	0	1	.648	3
560			min	-618.648	2	-1630.13	2	0	1	0	1	0	1	-.794	1
561		15	max	1561.681	3	884.084	3	0	1	0	1	0	1	.262	2
562			min	-617.805	2	-1631.589	2	0	1	0	1	0	1	0	13
563		16	max	1562.313	3	882.99	3	0	1	0	1	0	1	1.275	2
564			min	-616.963	2	-1633.048	2	0	1	0	1	0	1	-.449	3
565		17	max	1562.945	3	881.896	3	0	1	0	1	0	1	2.289	2
566			min	-616.12	2	-1634.507	2	0	1	0	1	0	1	-.997	3
567		18	max	-21.091	12	1858.889	2	0	1	0	1	0	1	1.173	2
568			min	-462.823	1	-800.047	3	0	1	0	1	0	1	-.519	3
569		19	max	-20.67	12	1857.43	2	0	1	0	1	0	1	.023	1
570			min	-461.98	1	-801.141	3	0	1	0	1	0	1	-.022	3
571	M9	1	max	211.552	1	587.636	3	107.925	1	0	3	-.014	15	0	3
572			min	9.83	15	-413.278	1	5.05	15	0	1	-.304	1	-.014	2
573		2	max	212.395	1	586.542	3	107.925	1	0	3	-.011	15	.243	1
574			min	10.084	15	-414.737	1	5.05	15	0	1	-.237	1	-.365	3
575		3	max	471.337	3	481.346	1	107.653	1	0	1	-.008	15	.491	1
576			min	-289.887	2	-434.008	3	5.022	15	0	3	-.17	1	-.717	3
577		4	max	471.969	3	479.887	1	107.653	1	0	1	-.005	15	.193	1
578			min	-289.044	2	-435.103	3	5.022	15	0	3	-.103	1	-.447	3
579		5	max	472.601	3	478.428	1	107.653	1	0	1	-.002	15	-.005	15
580			min	-288.202	2	-436.197	3	5.022	15	0	3	-.036	1	-.177	3
581		6	max	473.232	3	476.969	1	107.653	1	0	1	.031	1	.094	3
582			min	-287.36	2	-437.291	3	5.022	15	0	3	.001	15	-.412	2
583		7	max	473.864	3	475.51	1	107.653	1	0	1	.097	1	.366	3
584			min	-286.517	2	-438.386	3	5.022	15	0	3	.005	15	-.698	2
585		8	max	474.496	3	474.051	1	107.653	1	0	1	.164	1	.638	3
586			min	-285.675	2	-439.48	3	5.022	15	0	3	.008	15	-.991	1
587		9	max	491.887	3	41.668	2	166.343	1	0	3	-.005	15	.746	3
588			min	-193.969	2	.446	15	7.768	15	0	9	-.101	1	-1.13	1
589		10	max	492.519	3	40.209	2	166.343	1	0	3	.002	1	.727	3
590			min	-193.126	2	.006	15	7.768	15	0	9	0	15	-1.15	2
591		11	max	493.15	3	38.75	2	166.343	1	0	3	.105	1	.71	3
592			min	-192.284	2	-1.733	4	7.768	15	0	9	.005	15	-1.175	2
593		12	max	510.43	3	288.848	3	103.534	1	0	3	-.007	15	.619	3
594			min	-106.691	10	-544.473	2	4.822	15	0	2	-.161	1	-1.041	2
595		13	max	511.062	3	287.753	3	103.534	1	0	3	-.004	15	.44	3
596			min	-105.989	10	-545.932	2	4.822	15	0	2	-.096	1	-.702	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
597		14	max	511.694	3	286.659	3	103.534	1	0	3	-.002	15	.262	3
598			min	-105.287	10	-547.391	2	4.822	15	0	2	-.032	1	-.376	1
599		15	max	512.325	3	285.565	3	103.534	1	0	3	.032	1	.084	3
600			min	-104.585	10	-548.85	2	4.822	15	0	2	.001	15	-.052	1
601		16	max	512.957	3	284.47	3	103.534	1	0	3	.096	1	.318	2
602			min	-103.883	10	-550.309	2	4.822	15	0	2	.004	15	-.093	3
603		17	max	513.589	3	283.376	3	103.534	1	0	3	.161	1	.66	2
604			min	-103.181	10	-551.768	2	4.822	15	0	2	.007	15	-.269	3
605		18	max	-10.101	15	549.686	2	121.909	1	0	2	.231	1	.331	2
606			min	-212.863	1	-230.142	3	5.698	15	0	3	.011	15	-.132	3
607		19	max	-9.847	15	548.227	2	121.909	1	0	2	.307	1	.011	3
608			min	-212.021	1	-231.237	3	5.698	15	0	3	.014	15	-.011	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M13	1	max	.001	1	.168	2	.009	3	1.154e-2	2	NC	1	NC	1
2			min	0	15	-.032	3	-.005	2	-2.238e-3	3	NC	1	NC	1
3		2	max	0	1	.247	3	.052	1	1.294e-2	2	NC	5	NC	2
4			min	0	15	-.01	9	.003	15	-2.222e-3	3	861.292	3	4779.372	1
5		3	max	0	1	.473	3	.122	1	1.434e-2	2	NC	5	NC	3
6			min	0	15	-.139	1	.006	15	-2.207e-3	3	475.83	3	1995.947	1
7		4	max	0	1	.61	3	.181	1	1.575e-2	2	NC	5	NC	3
8			min	0	15	-.211	1	.009	15	-2.192e-3	3	374.043	3	1333.605	1
9		5	max	0	1	.642	3	.211	1	1.715e-2	2	NC	5	NC	3
10			min	0	15	-.208	1	.01	15	-2.177e-3	3	356.185	3	1142.745	1
11		6	max	0	1	.571	3	.203	1	1.855e-2	2	NC	5	NC	5
12			min	0	15	-.135	1	.01	15	-2.162e-3	3	397.861	3	1189.131	1
13		7	max	0	1	.419	3	.159	1	1.995e-2	2	NC	5	NC	5
14			min	0	15	-.016	9	.008	15	-2.146e-3	3	531.946	3	1523.189	1
15		8	max	0	1	.226	3	.092	1	2.135e-2	2	NC	1	NC	3
16			min	0	15	.005	15	.001	10	-2.131e-3	3	930.688	3	2661.529	1
17		9	max	0	1	.296	2	.03	3	2.275e-2	2	NC	4	NC	1
18			min	0	15	.009	15	-.008	10	-2.116e-3	3	1874.406	2	NC	1
19		10	max	0	1	.352	2	.028	3	2.415e-2	2	NC	3	NC	1
20			min	0	1	-.029	3	-.019	2	-2.101e-3	3	1304.804	2	NC	1
21		11	max	0	15	.296	2	.03	3	2.275e-2	2	NC	4	NC	1
22			min	0	1	.009	15	-.008	10	-2.116e-3	3	1874.406	2	NC	1
23		12	max	0	15	.226	3	.092	1	2.135e-2	2	NC	1	NC	3
24			min	0	1	.005	15	.001	10	-2.131e-3	3	930.688	3	2661.529	1
25		13	max	0	15	.419	3	.159	1	1.995e-2	2	NC	5	NC	5
26			min	0	1	-.016	9	.008	15	-2.146e-3	3	531.946	3	1523.189	1
27		14	max	0	15	.571	3	.203	1	1.855e-2	2	NC	5	NC	5
28			min	0	1	-.135	1	.01	15	-2.162e-3	3	397.861	3	1189.131	1
29		15	max	0	15	.642	3	.211	1	1.715e-2	2	NC	5	NC	3
30			min	0	1	-.208	1	.01	15	-2.177e-3	3	356.185	3	1142.745	1
31		16	max	0	15	.61	3	.181	1	1.575e-2	2	NC	5	NC	3
32			min	0	1	-.211	1	.009	15	-2.192e-3	3	374.043	3	1333.605	1
33		17	max	0	15	.473	3	.122	1	1.434e-2	2	NC	5	NC	3
34			min	0	1	-.139	1	.006	15	-2.207e-3	3	475.83	3	1995.947	1
35		18	max	0	15	.247	3	.052	1	1.294e-2	2	NC	5	NC	2
36			min	0	1	-.01	9	.003	15	-2.222e-3	3	861.292	3	4779.372	1
37		19	max	0	15	.168	2	.009	3	1.154e-2	2	NC	1	NC	1
38			min	-.001	1	-.032	3	-.005	2	-2.238e-3	3	NC	1	NC	1
39	M14	1	max	0	1	.308	3	.008	3	6.696e-3	1	NC	1	NC	1
40			min	0	15	-.518	2	-.004	2	-4.668e-3	3	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
41		2	max	0	1	.609	3	.034	1	7.903e-3	1	NC	5	NC	2
42			min	0	15	-.846	1	0	10	-5.616e-3	3	723.801	1	7322.361	1
43		3	max	0	1	.868	3	.095	1	9.11e-3	1	NC	15	NC	3
44			min	0	15	-1.136	1	.005	15	-6.564e-3	3	385.928	1	2563.613	1
45		4	max	0	1	1.055	3	.152	1	1.032e-2	1	9324.703	15	NC	3
46			min	0	15	-1.356	1	.007	15	-7.512e-3	3	285.009	1	1592.049	1
47		5	max	0	1	1.155	3	.185	1	1.152e-2	1	8068.431	15	NC	3
48			min	0	15	-1.491	1	.009	15	-8.46e-3	3	245.651	1	1310.324	1
49		6	max	0	1	1.168	3	.182	1	1.273e-2	1	7732.466	15	NC	3
50			min	0	15	-1.539	1	.009	15	-9.407e-3	3	234.134	1	1328.83	1
51		7	max	0	1	1.109	3	.145	1	1.394e-2	1	7999.146	15	NC	3
52			min	0	15	-1.512	1	.007	15	-1.036e-2	3	240.412	1	1671.074	1
53		8	max	0	1	1.004	3	.085	1	1.515e-2	1	8740.161	15	NC	3
54			min	0	15	-1.436	1	.002	10	-1.13e-2	3	260.204	1	2874.906	1
55		9	max	0	1	.898	3	.026	3	1.635e-2	1	9734.283	15	NC	1
56			min	0	15	-1.351	1	-.007	10	-1.225e-2	3	286.901	1	NC	1
57		10	max	0	1	.847	3	.025	3	1.756e-2	1	NC	15	NC	1
58			min	0	1	-1.311	2	-.017	2	-1.32e-2	3	302.386	1	NC	1
59		11	max	0	15	.898	3	.026	3	1.635e-2	1	9734.283	15	NC	1
60			min	0	1	-1.351	1	-.007	10	-1.225e-2	3	286.901	1	NC	1
61		12	max	0	15	1.004	3	.085	1	1.515e-2	1	8740.161	15	NC	3
62			min	0	1	-1.436	1	.002	10	-1.13e-2	3	260.204	1	2874.906	1
63		13	max	0	15	1.109	3	.145	1	1.394e-2	1	7999.146	15	NC	3
64			min	0	1	-1.512	1	.007	15	-1.036e-2	3	240.412	1	1671.074	1
65		14	max	0	15	1.168	3	.182	1	1.273e-2	1	7732.466	15	NC	3
66			min	0	1	-1.539	1	.009	15	-9.407e-3	3	234.134	1	1328.83	1
67		15	max	0	15	1.155	3	.185	1	1.152e-2	1	8068.431	15	NC	3
68			min	0	1	-1.491	1	.009	15	-8.46e-3	3	245.651	1	1310.324	1
69		16	max	0	15	1.055	3	.152	1	1.032e-2	1	9324.703	15	NC	3
70			min	0	1	-1.356	1	.007	15	-7.512e-3	3	285.009	1	1592.049	1
71		17	max	0	15	.868	3	.095	1	9.11e-3	1	NC	15	NC	3
72			min	0	1	-1.136	1	.005	15	-6.564e-3	3	385.928	1	2563.613	1
73		18	max	0	15	.609	3	.034	1	7.903e-3	1	NC	5	NC	2
74			min	0	1	-.846	1	0	10	-5.616e-3	3	723.801	1	7322.361	1
75		19	max	0	15	.308	3	.008	3	6.696e-3	1	NC	1	NC	1
76			min	0	1	-.518	2	-.004	2	-4.668e-3	3	NC	1	NC	1
77	M15	1	max	0	15	.315	3	.008	3	3.966e-3	3	NC	1	NC	1
78			min	0	1	-.517	2	-.004	2	-6.954e-3	2	NC	1	NC	1
79		2	max	0	15	.518	3	.035	1	4.773e-3	3	NC	5	NC	2
80			min	0	1	-.91	2	.001	10	-8.21e-3	2	610.375	2	7259.781	1
81		3	max	0	15	.698	3	.096	1	5.581e-3	3	NC	15	NC	3
82			min	0	1	-1.25	2	.005	15	-9.467e-3	2	327.262	2	2550.841	1
83		4	max	0	15	.838	3	.153	1	6.388e-3	3	9340.497	15	NC	3
84			min	0	1	-1.501	2	.007	15	-1.072e-2	2	243.961	2	1585.994	1
85		5	max	0	15	.928	3	.185	1	7.195e-3	3	8083.729	15	NC	3
86			min	0	1	-1.642	2	.009	15	-1.198e-2	2	213.229	2	1305.906	1
87		6	max	0	15	.969	3	.183	1	8.002e-3	3	7749.339	15	NC	3
88			min	0	1	-1.675	2	.009	15	-1.324e-2	2	207.314	2	1324.299	1
89		7	max	0	15	.964	3	.146	1	8.809e-3	3	8019.73	15	NC	3
90			min	0	1	-1.614	2	.007	15	-1.449e-2	2	218.802	2	1664.268	1
91		8	max	0	15	.93	3	.086	1	9.616e-3	3	8767.045	15	NC	3
92			min	0	1	-1.495	2	.002	10	-1.575e-2	2	245.446	2	2856.274	1
93		9	max	0	15	.888	3	.025	3	1.042e-2	3	9769.47	15	NC	1
94			min	0	1	-1.37	2	-.006	10	-1.701e-2	2	281.396	2	NC	1
95		10	max	0	1	.865	3	.023	3	1.123e-2	3	NC	15	NC	1
96			min	0	1	-1.309	2	-.016	2	-1.826e-2	2	302.887	2	NC	1
97		11	max	0	1	.888	3	.025	3	1.042e-2	3	9769.47	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
98			min	0	15	-1.37	2	-.006	10	-1.701e-2	2	281.396	2	NC	1
99		12	max	0	1	.93	3	.086	1	9.616e-3	3	8767.045	15	NC	3
100			min	0	15	-1.495	2	.002	10	-1.575e-2	2	245.446	2	2856.274	1
101		13	max	0	1	.964	3	.146	1	8.809e-3	3	8019.73	15	NC	3
102			min	0	15	-1.614	2	.007	15	-1.449e-2	2	218.802	2	1664.268	1
103		14	max	0	1	.969	3	.183	1	8.002e-3	3	7749.339	15	NC	3
104			min	0	15	-1.675	2	.009	15	-1.324e-2	2	207.314	2	1324.299	1
105		15	max	0	1	.928	3	.185	1	7.195e-3	3	8083.729	15	NC	3
106			min	0	15	-1.642	2	.009	15	-1.198e-2	2	213.229	2	1305.906	1
107		16	max	0	1	.838	3	.153	1	6.388e-3	3	9340.497	15	NC	3
108			min	0	15	-1.501	2	.007	15	-1.072e-2	2	243.961	2	1585.994	1
109		17	max	0	1	.698	3	.096	1	5.581e-3	3	NC	15	NC	3
110			min	0	15	-1.25	2	.005	15	-9.467e-3	2	327.262	2	2550.841	1
111		18	max	0	1	.518	3	.035	1	4.773e-3	3	NC	5	NC	2
112			min	0	15	-.91	2	.001	10	-8.21e-3	2	610.375	2	7259.781	1
113		19	max	0	1	.315	3	.008	3	3.966e-3	3	NC	1	NC	1
114			min	0	15	-.517	2	-.004	2	-6.954e-3	2	NC	1	NC	1
115	M16	1	max	0	15	.158	1	.006	3	7.185e-3	3	NC	1	NC	1
116			min	-.001	1	-.106	3	-.004	2	-1.022e-2	1	NC	1	NC	1
117		2	max	0	15	.003	13	.051	1	8.284e-3	3	NC	5	NC	2
118			min	-.001	1	-.088	2	.003	15	-1.133e-2	1	1011.221	2	4844.507	1
119		3	max	0	15	.047	3	.121	1	9.383e-3	3	NC	5	NC	3
120			min	0	1	-.276	2	.006	15	-1.243e-2	1	564.054	2	2010.591	1
121		4	max	0	15	.079	3	.18	1	1.048e-2	3	NC	5	NC	3
122			min	0	1	-.382	2	.009	15	-1.354e-2	1	451.449	2	1338.868	1
123		5	max	0	15	.07	3	.211	1	1.158e-2	3	NC	5	NC	3
124			min	0	1	-.391	2	.01	15	-1.465e-2	1	443.858	2	1144.245	1
125		6	max	0	15	.023	3	.203	1	1.268e-2	3	NC	5	NC	3
126			min	0	1	-.306	2	.01	15	-1.576e-2	1	526.8	2	1187.279	1
127		7	max	0	15	.002	13	.16	1	1.378e-2	3	NC	5	NC	3
128			min	0	1	-.147	2	.008	15	-1.687e-2	1	808.449	2	1513.987	1
129		8	max	0	15	.093	1	.093	1	1.488e-2	3	NC	4	NC	3
130			min	0	1	-.145	3	.004	10	-1.798e-2	1	2329.357	2	2616.615	1
131		9	max	0	15	.252	1	.027	1	1.598e-2	3	NC	4	NC	2
132			min	0	1	-.223	3	-.005	10	-1.909e-2	1	2054.577	3	9468.236	1
133		10	max	0	1	.323	1	.02	3	1.708e-2	3	NC	5	NC	1
134			min	0	1	-.258	3	-.015	2	-2.02e-2	1	1453.863	1	NC	1
135		11	max	0	1	.252	1	.027	1	1.598e-2	3	NC	4	NC	2
136			min	0	15	-.223	3	-.005	10	-1.909e-2	1	2054.577	3	9468.236	1
137		12	max	0	1	.093	1	.093	1	1.488e-2	3	NC	4	NC	3
138			min	0	15	-.145	3	.004	10	-1.798e-2	1	2329.357	2	2616.615	1
139		13	max	0	1	.002	13	.16	1	1.378e-2	3	NC	5	NC	3
140			min	0	15	-.147	2	.008	15	-1.687e-2	1	808.449	2	1513.987	1
141		14	max	0	1	.023	3	.203	1	1.268e-2	3	NC	5	NC	3
142			min	0	15	-.306	2	.01	15	-1.576e-2	1	526.8	2	1187.279	1
143		15	max	0	1	.07	3	.211	1	1.158e-2	3	NC	5	NC	3
144			min	0	15	-.391	2	.01	15	-1.465e-2	1	443.858	2	1144.245	1
145		16	max	0	1	.079	3	.18	1	1.048e-2	3	NC	5	NC	3
146			min	0	15	-.382	2	.009	15	-1.354e-2	1	451.449	2	1338.868	1
147		17	max	0	1	.047	3	.121	1	9.383e-3	3	NC	5	NC	3
148			min	0	15	-.276	2	.006	15	-1.243e-2	1	564.054	2	2010.591	1
149		18	max	.001	1	.003	13	.051	1	8.284e-3	3	NC	5	NC	2
150			min	0	15	-.088	2	.003	15	-1.133e-2	1	1011.221	2	4844.507	1
151		19	max	.001	1	.158	1	.006	3	7.185e-3	3	NC	1	NC	1
152			min	0	15	-.106	3	-.004	2	-1.022e-2	1	NC	1	NC	1
153	M2	1	max	.007	1	.008	2	.014	1	-1.553e-5	15	NC	1	NC	2
154			min	-.008	3	-.014	3	0	15	-3.332e-4	1	9391.226	2	5467.011	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
155		2	max	.007	1	.007	2	.013	1	-1.474e-5	15	NC	1	NC	2
156			min	-.008	3	-.013	3	0	15	-3.163e-4	1	NC	1	5957.901	1
157		3	max	.007	1	.005	2	.012	1	-1.395e-5	15	NC	1	NC	2
158			min	-.007	3	-.013	3	0	15	-2.994e-4	1	NC	1	6541.937	1
159		4	max	.006	1	.004	2	.011	1	-1.317e-5	15	NC	1	NC	2
160			min	-.007	3	-.013	3	0	15	-2.824e-4	1	NC	1	7243.538	1
161		5	max	.006	1	.003	2	.01	1	-1.238e-5	15	NC	1	NC	2
162			min	-.006	3	-.012	3	0	15	-2.655e-4	1	NC	1	8095.927	1
163		6	max	.005	1	.002	2	.008	1	-1.159e-5	15	NC	1	NC	2
164			min	-.006	3	-.012	3	0	15	-2.486e-4	1	NC	1	9145.246	1
165		7	max	.005	1	0	2	.007	1	-1.08e-5	15	NC	1	NC	1
166			min	-.006	3	-.012	3	0	15	-2.317e-4	1	NC	1	NC	1
167		8	max	.005	1	0	2	.006	1	-1.001e-5	15	NC	1	NC	1
168			min	-.005	3	-.011	3	0	15	-2.147e-4	1	NC	1	NC	1
169		9	max	.004	1	-.001	2	.005	1	-9.226e-6	15	NC	1	NC	1
170			min	-.005	3	-.011	3	0	15	-1.978e-4	1	NC	1	NC	1
171		10	max	.004	1	-.002	15	.005	1	-8.438e-6	15	NC	1	NC	1
172			min	-.004	3	-.01	3	0	15	-1.809e-4	1	NC	1	NC	1
173		11	max	.003	1	-.002	15	.004	1	-7.65e-6	15	NC	1	NC	1
174			min	-.004	3	-.009	3	0	15	-1.64e-4	1	NC	1	NC	1
175		12	max	.003	1	-.002	15	.003	1	-6.863e-6	15	NC	1	NC	1
176			min	-.003	3	-.008	3	0	15	-1.47e-4	1	NC	1	NC	1
177		13	max	.002	1	-.002	15	.002	1	-6.075e-6	15	NC	1	NC	1
178			min	-.003	3	-.008	3	0	15	-1.301e-4	1	NC	1	NC	1
179		14	max	.002	1	-.002	15	.002	1	-5.287e-6	15	NC	1	NC	1
180			min	-.002	3	-.007	3	0	15	-1.132e-4	1	NC	1	NC	1
181		15	max	.002	1	-.001	15	.001	1	-4.499e-6	15	NC	1	NC	1
182			min	-.002	3	-.006	4	0	15	-9.628e-5	1	NC	1	NC	1
183		16	max	.001	1	-.001	15	0	1	-3.711e-6	15	NC	1	NC	1
184			min	-.001	3	-.005	4	0	15	-7.935e-5	1	NC	1	NC	1
185		17	max	0	1	0	15	0	1	-2.923e-6	15	NC	1	NC	1
186			min	0	3	-.003	4	0	15	-6.243e-5	1	NC	1	NC	1
187		18	max	0	1	0	15	0	1	-2.135e-6	15	NC	1	NC	1
188			min	0	3	-.002	4	0	15	-4.551e-5	1	NC	1	NC	1
189		19	max	0	1	0	1	0	1	-1.347e-6	15	NC	1	NC	1
190			min	0	1	0	1	0	1	-2.859e-5	1	NC	1	NC	1
191	M3	1	max	0	1	0	1	0	1	5.418e-6	1	NC	1	NC	1
192			min	0	1	0	1	0	1	2.561e-7	15	NC	1	NC	1
193		2	max	0	3	0	15	0	15	4.179e-5	1	NC	1	NC	1
194			min	0	2	-.003	4	0	1	1.947e-6	15	NC	1	NC	1
195		3	max	0	3	-.001	15	0	15	7.816e-5	1	NC	1	NC	1
196			min	0	2	-.006	4	0	1	3.637e-6	15	NC	1	NC	1
197		4	max	.001	3	-.002	15	0	15	1.145e-4	1	NC	1	NC	1
198			min	0	2	-.009	4	0	1	5.328e-6	15	NC	1	NC	1
199		5	max	.002	3	-.003	15	0	15	1.509e-4	1	NC	1	NC	1
200			min	-.001	2	-.012	4	0	1	7.018e-6	15	8382.304	4	NC	1
201		6	max	.002	3	-.004	15	0	15	1.873e-4	1	NC	5	NC	1
202			min	-.002	2	-.015	4	0	1	8.709e-6	15	6802.371	4	NC	1
203		7	max	.002	3	-.004	15	0	15	2.237e-4	1	NC	5	NC	1
204			min	-.002	2	-.018	4	0	1	1.04e-5	15	5850.387	4	NC	1
205		8	max	.003	3	-.005	15	0	1	2.6e-4	1	NC	5	NC	1
206			min	-.002	2	-.02	4	0	12	1.209e-5	15	5263.42	4	NC	1
207		9	max	.003	3	-.005	15	0	1	2.964e-4	1	NC	5	NC	1
208			min	-.003	2	-.021	4	0	12	1.378e-5	15	4917.683	4	NC	1
209		10	max	.004	3	-.005	15	.001	1	3.328e-4	1	NC	5	NC	1
210			min	-.003	2	-.022	4	0	15	1.547e-5	15	4753.226	4	NC	1
211		11	max	.004	3	-.005	15	.002	1	3.691e-4	1	NC	5	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
212			min	-.003	2	-.022	4	0	15	1.716e-5	15	4745.913	4	NC	1
213		12	max	.004	3	-.005	15	.002	1	4.055e-4	1	NC	5	NC	1
214			min	-.003	2	-.021	4	0	15	1.885e-5	15	4898.163	4	NC	1
215		13	max	.005	3	-.005	15	.003	1	4.419e-4	1	NC	5	NC	1
216			min	-.004	2	-.02	4	0	15	2.054e-5	15	5241.08	4	NC	1
217		14	max	.005	3	-.004	15	.004	1	4.783e-4	1	NC	5	NC	1
218			min	-.004	2	-.018	4	0	15	2.223e-5	15	5850.451	4	NC	1
219		15	max	.006	3	-.004	15	.006	1	5.146e-4	1	NC	3	NC	1
220			min	-.004	2	-.015	4	0	15	2.392e-5	15	6893.779	4	NC	1
221		16	max	.006	3	-.003	15	.007	1	5.51e-4	1	NC	1	NC	1
222			min	-.005	2	-.012	4	0	15	2.562e-5	15	8776.38	4	NC	1
223		17	max	.006	3	-.002	15	.009	1	5.874e-4	1	NC	1	NC	1
224			min	-.005	2	-.009	4	0	15	2.731e-5	15	NC	1	NC	1
225		18	max	.007	3	-.001	15	.011	1	6.237e-4	1	NC	1	NC	2
226			min	-.005	2	-.005	1	0	15	2.9e-5	15	NC	1	9281.402	1
227		19	max	.007	3	0	10	.013	1	6.601e-4	1	NC	1	NC	2
228			min	-.006	2	-.002	1	0	15	3.069e-5	15	NC	1	7743.392	1
229	M4	1	max	.003	1	.005	2	0	15	2.337e-4	1	NC	1	NC	3
230			min	0	3	-.007	3	-.013	1	1.09e-5	15	NC	1	1889.337	1
231		2	max	.002	1	.005	2	0	15	2.337e-4	1	NC	1	NC	3
232			min	0	3	-.007	3	-.012	1	1.09e-5	15	NC	1	2050.278	1
233		3	max	.002	1	.005	2	0	15	2.337e-4	1	NC	1	NC	3
234			min	0	3	-.007	3	-.011	1	1.09e-5	15	NC	1	2242.088	1
235		4	max	.002	1	.004	2	0	15	2.337e-4	1	NC	1	NC	3
236			min	0	3	-.006	3	-.01	1	1.09e-5	15	NC	1	2472.74	1
237		5	max	.002	1	.004	2	0	15	2.337e-4	1	NC	1	NC	3
238			min	0	3	-.006	3	-.009	1	1.09e-5	15	NC	1	2753.069	1
239		6	max	.002	1	.004	2	0	15	2.337e-4	1	NC	1	NC	3
240			min	0	3	-.005	3	-.008	1	1.09e-5	15	NC	1	3098.107	1
241		7	max	.002	1	.004	2	0	15	2.337e-4	1	NC	1	NC	3
242			min	0	3	-.005	3	-.007	1	1.09e-5	15	NC	1	3529.188	1
243		8	max	.002	1	.003	2	0	15	2.337e-4	1	NC	1	NC	3
244			min	0	3	-.005	3	-.006	1	1.09e-5	15	NC	1	4077.421	1
245		9	max	.001	1	.003	2	0	15	2.337e-4	1	NC	1	NC	2
246			min	0	3	-.004	3	-.005	1	1.09e-5	15	NC	1	4789.634	1
247		10	max	.001	1	.003	2	0	15	2.337e-4	1	NC	1	NC	2
248			min	0	3	-.004	3	-.004	1	1.09e-5	15	NC	1	5739.009	1
249		11	max	.001	1	.002	2	0	15	2.337e-4	1	NC	1	NC	2
250			min	0	3	-.003	3	-.004	1	1.09e-5	15	NC	1	7045.228	1
251		12	max	.001	1	.002	2	0	15	2.337e-4	1	NC	1	NC	2
252			min	0	3	-.003	3	-.003	1	1.09e-5	15	NC	1	8915.254	1
253		13	max	0	1	.002	2	0	15	2.337e-4	1	NC	1	NC	1
254			min	0	3	-.002	3	-.002	1	1.09e-5	15	NC	1	NC	1
255		14	max	0	1	.001	2	0	15	2.337e-4	1	NC	1	NC	1
256			min	0	3	-.002	3	-.002	1	1.09e-5	15	NC	1	NC	1
257		15	max	0	1	.001	2	0	15	2.337e-4	1	NC	1	NC	1
258			min	0	3	-.002	3	-.001	1	1.09e-5	15	NC	1	NC	1
259		16	max	0	1	0	2	0	15	2.337e-4	1	NC	1	NC	1
260			min	0	3	-.001	3	0	1	1.09e-5	15	NC	1	NC	1
261		17	max	0	1	0	2	0	15	2.337e-4	1	NC	1	NC	1
262			min	0	3	0	3	0	1	1.09e-5	15	NC	1	NC	1
263		18	max	0	1	0	2	0	15	2.337e-4	1	NC	1	NC	1
264			min	0	3	0	3	0	1	1.09e-5	15	NC	1	NC	1
265		19	max	0	1	0	1	0	1	2.337e-4	1	NC	1	NC	1
266			min	0	1	0	1	0	1	1.09e-5	15	NC	1	NC	1
267	M6	1	max	.023	1	.031	2	0	1	0	1	NC	3	NC	1
268			min	-.027	3	-.043	3	0	1	0	1	2474.427	2	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
269		2	max	.022	1	.028	2	0	1	0	1	NC	3	NC	1
270			min	-.025	3	-.041	3	0	1	0	1	2732.751	2	NC	1
271		3	max	.021	1	.025	2	0	1	0	1	NC	3	NC	1
272			min	-.024	3	-.038	3	0	1	0	1	3048.271	2	NC	1
273		4	max	.019	1	.023	2	0	1	0	1	NC	3	NC	1
274			min	-.022	3	-.036	3	0	1	0	1	3438.534	2	NC	1
275		5	max	.018	1	.02	2	0	1	0	1	NC	3	NC	1
276			min	-.021	3	-.034	3	0	1	0	1	3928.631	2	NC	1
277		6	max	.017	1	.017	2	0	1	0	1	NC	3	NC	1
278			min	-.019	3	-.032	3	0	1	0	1	4555.479	2	NC	1
279		7	max	.016	1	.014	2	0	1	0	1	NC	1	NC	1
280			min	-.018	3	-.029	3	0	1	0	1	5375.272	2	NC	1
281		8	max	.014	1	.012	2	0	1	0	1	NC	1	NC	1
282			min	-.016	3	-.027	3	0	1	0	1	6477.121	2	NC	1
283		9	max	.013	1	.01	2	0	1	0	1	NC	1	NC	1
284			min	-.015	3	-.025	3	0	1	0	1	8009.668	2	NC	1
285		10	max	.012	1	.008	2	0	1	0	1	NC	1	NC	1
286			min	-.013	3	-.022	3	0	1	0	1	NC	1	NC	1
287		11	max	.01	1	.006	2	0	1	0	1	NC	1	NC	1
288			min	-.012	3	-.02	3	0	1	0	1	NC	1	NC	1
289		12	max	.009	1	.004	2	0	1	0	1	NC	1	NC	1
290			min	-.01	3	-.018	3	0	1	0	1	NC	1	NC	1
291		13	max	.008	1	.003	2	0	1	0	1	NC	1	NC	1
292			min	-.009	3	-.015	3	0	1	0	1	NC	1	NC	1
293		14	max	.006	1	.001	2	0	1	0	1	NC	1	NC	1
294			min	-.007	3	-.013	3	0	1	0	1	NC	1	NC	1
295		15	max	.005	1	0	2	0	1	0	1	NC	1	NC	1
296			min	-.006	3	-.01	3	0	1	0	1	NC	1	NC	1
297		16	max	.004	1	0	2	0	1	0	1	NC	1	NC	1
298			min	-.004	3	-.008	3	0	1	0	1	NC	1	NC	1
299		17	max	.003	1	0	2	0	1	0	1	NC	1	NC	1
300			min	-.003	3	-.005	3	0	1	0	1	NC	1	NC	1
301		18	max	.001	1	0	2	0	1	0	1	NC	1	NC	1
302			min	-.001	3	-.003	3	0	1	0	1	NC	1	NC	1
303		19	max	0	1	0	1	0	1	0	1	NC	1	NC	1
304			min	0	1	0	1	0	1	0	1	NC	1	NC	1
305	M7	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
306			min	0	1	0	1	0	1	0	1	NC	1	NC	1
307		2	max	.001	3	0	15	0	1	0	1	NC	1	NC	1
308			min	-.001	2	-.003	3	0	1	0	1	NC	1	NC	1
309		3	max	.002	3	-.001	15	0	1	0	1	NC	1	NC	1
310			min	-.002	2	-.007	3	0	1	0	1	NC	1	NC	1
311		4	max	.004	3	-.002	15	0	1	0	1	NC	1	NC	1
312			min	-.004	2	-.01	3	0	1	0	1	NC	1	NC	1
313		5	max	.005	3	-.003	15	0	1	0	1	NC	1	NC	1
314			min	-.005	2	-.013	3	0	1	0	1	8575.994	4	NC	1
315		6	max	.006	3	-.004	15	0	1	0	1	NC	1	NC	1
316			min	-.006	2	-.015	3	0	1	0	1	6945.511	4	NC	1
317		7	max	.007	3	-.004	15	0	1	0	1	NC	2	NC	1
318			min	-.007	2	-.018	4	0	1	0	1	5963.699	4	NC	1
319		8	max	.009	3	-.005	15	0	1	0	1	NC	5	NC	1
320			min	-.008	2	-.02	4	0	1	0	1	5358.107	4	NC	1
321		9	max	.01	3	-.005	15	0	1	0	1	NC	5	NC	1
322			min	-.01	2	-.021	4	0	1	0	1	5000.504	4	NC	1
323		10	max	.011	3	-.005	15	0	1	0	1	NC	5	NC	1
324			min	-.011	2	-.022	4	0	1	0	1	4828.698	4	NC	1
325		11	max	.012	3	-.005	15	0	1	0	1	NC	5	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
326			min	-.012	2	-.022	4	0	1	0	1	4817.415	4	NC	1
327		12	max	.014	3	-.005	15	0	1	0	1	NC	5	NC	1
328			min	-.013	2	-.021	4	0	1	0	1	4968.602	4	NC	1
329		13	max	.015	3	-.005	15	0	1	0	1	NC	5	NC	1
330			min	-.014	2	-.02	4	0	1	0	1	5313.433	4	NC	1
331		14	max	.016	3	-.004	15	0	1	0	1	NC	5	NC	1
332			min	-.015	2	-.018	4	0	1	0	1	5928.415	4	NC	1
333		15	max	.017	3	-.004	15	0	1	0	1	NC	1	NC	1
334			min	-.017	2	-.016	3	0	1	0	1	6982.951	4	NC	1
335		16	max	.019	3	-.003	15	0	1	0	1	NC	1	NC	1
336			min	-.018	2	-.014	3	0	1	0	1	8887.204	4	NC	1
337		17	max	.02	3	-.002	15	0	1	0	1	NC	1	NC	1
338			min	-.019	2	-.011	3	0	1	0	1	NC	1	NC	1
339		18	max	.021	3	-.001	15	0	1	0	1	NC	1	NC	1
340			min	-.02	2	-.008	3	0	1	0	1	NC	1	NC	1
341		19	max	.022	3	0	10	0	1	0	1	NC	1	NC	1
342			min	-.021	2	-.005	3	0	1	0	1	NC	1	NC	1
343	M8	1	max	.007	1	.021	2	0	1	0	1	NC	1	NC	1
344			min	0	3	-.023	3	0	1	0	1	NC	1	NC	1
345		2	max	.006	1	.02	2	0	1	0	1	NC	1	NC	1
346			min	0	3	-.022	3	0	1	0	1	NC	1	NC	1
347		3	max	.006	1	.018	2	0	1	0	1	NC	1	NC	1
348			min	0	3	-.02	3	0	1	0	1	NC	1	NC	1
349		4	max	.006	1	.017	2	0	1	0	1	NC	1	NC	1
350			min	0	3	-.019	3	0	1	0	1	NC	1	NC	1
351		5	max	.005	1	.016	2	0	1	0	1	NC	1	NC	1
352			min	0	3	-.018	3	0	1	0	1	NC	1	NC	1
353		6	max	.005	1	.015	2	0	1	0	1	NC	1	NC	1
354			min	0	3	-.017	3	0	1	0	1	NC	1	NC	1
355		7	max	.004	1	.014	2	0	1	0	1	NC	1	NC	1
356			min	0	3	-.015	3	0	1	0	1	NC	1	NC	1
357		8	max	.004	1	.013	2	0	1	0	1	NC	1	NC	1
358			min	0	3	-.014	3	0	1	0	1	NC	1	NC	1
359		9	max	.004	1	.011	2	0	1	0	1	NC	1	NC	1
360			min	0	3	-.013	3	0	1	0	1	NC	1	NC	1
361		10	max	.003	1	.01	2	0	1	0	1	NC	1	NC	1
362			min	0	3	-.011	3	0	1	0	1	NC	1	NC	1
363		11	max	.003	1	.009	2	0	1	0	1	NC	1	NC	1
364			min	0	3	-.01	3	0	1	0	1	NC	1	NC	1
365		12	max	.003	1	.008	2	0	1	0	1	NC	1	NC	1
366			min	0	3	-.009	3	0	1	0	1	NC	1	NC	1
367		13	max	.002	1	.007	2	0	1	0	1	NC	1	NC	1
368			min	0	3	-.008	3	0	1	0	1	NC	1	NC	1
369		14	max	.002	1	.006	2	0	1	0	1	NC	1	NC	1
370			min	0	3	-.006	3	0	1	0	1	NC	1	NC	1
371		15	max	.001	1	.005	2	0	1	0	1	NC	1	NC	1
372			min	0	3	-.005	3	0	1	0	1	NC	1	NC	1
373		16	max	.001	1	.003	2	0	1	0	1	NC	1	NC	1
374			min	0	3	-.004	3	0	1	0	1	NC	1	NC	1
375		17	max	0	1	.002	2	0	1	0	1	NC	1	NC	1
376			min	0	3	-.003	3	0	1	0	1	NC	1	NC	1
377		18	max	0	1	.001	2	0	1	0	1	NC	1	NC	1
378			min	0	3	-.001	3	0	1	0	1	NC	1	NC	1
379		19	max	0	1	0	1	0	1	0	1	NC	1	NC	1
380			min	0	1	0	1	0	1	0	1	NC	1	NC	1
381	M10	1	max	.007	1	.008	2	0	15	3.332e-4	1	NC	1	NC	2
382			min	-.008	3	-.014	3	-.014	1	1.553e-5	15	9391.226	2	5467.011	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
383		2	max	.007	1	.007	2	0	15	3.163e-4	1	NC	1	NC	2
384			min	-.008	3	-.013	3	-.013	1	1.474e-5	15	NC	1	5957.901	1
385		3	max	.007	1	.005	2	0	15	2.994e-4	1	NC	1	NC	2
386			min	-.007	3	-.013	3	-.012	1	1.395e-5	15	NC	1	6541.937	1
387		4	max	.006	1	.004	2	0	15	2.824e-4	1	NC	1	NC	2
388			min	-.007	3	-.013	3	-.011	1	1.317e-5	15	NC	1	7243.538	1
389		5	max	.006	1	.003	2	0	15	2.655e-4	1	NC	1	NC	2
390			min	-.006	3	-.012	3	-.01	1	1.238e-5	15	NC	1	8095.927	1
391		6	max	.005	1	.002	2	0	15	2.486e-4	1	NC	1	NC	2
392			min	-.006	3	-.012	3	-.008	1	1.159e-5	15	NC	1	9145.246	1
393		7	max	.005	1	0	2	0	15	2.317e-4	1	NC	1	NC	1
394			min	-.006	3	-.012	3	-.007	1	1.08e-5	15	NC	1	NC	1
395		8	max	.005	1	0	2	0	15	2.147e-4	1	NC	1	NC	1
396			min	-.005	3	-.011	3	-.006	1	1.001e-5	15	NC	1	NC	1
397		9	max	.004	1	-.001	2	0	15	1.978e-4	1	NC	1	NC	1
398			min	-.005	3	-.011	3	-.005	1	9.226e-6	15	NC	1	NC	1
399		10	max	.004	1	-.002	15	0	15	1.809e-4	1	NC	1	NC	1
400			min	-.004	3	-.01	3	-.005	1	8.438e-6	15	NC	1	NC	1
401		11	max	.003	1	-.002	15	0	15	1.64e-4	1	NC	1	NC	1
402			min	-.004	3	-.009	3	-.004	1	7.65e-6	15	NC	1	NC	1
403		12	max	.003	1	-.002	15	0	15	1.47e-4	1	NC	1	NC	1
404			min	-.003	3	-.008	3	-.003	1	6.863e-6	15	NC	1	NC	1
405		13	max	.002	1	-.002	15	0	15	1.301e-4	1	NC	1	NC	1
406			min	-.003	3	-.008	3	-.002	1	6.075e-6	15	NC	1	NC	1
407		14	max	.002	1	-.002	15	0	15	1.132e-4	1	NC	1	NC	1
408			min	-.002	3	-.007	3	-.002	1	5.287e-6	15	NC	1	NC	1
409		15	max	.002	1	-.001	15	0	15	9.628e-5	1	NC	1	NC	1
410			min	-.002	3	-.006	4	-.001	1	4.499e-6	15	NC	1	NC	1
411		16	max	.001	1	-.001	15	0	15	7.935e-5	1	NC	1	NC	1
412			min	-.001	3	-.005	4	0	1	3.711e-6	15	NC	1	NC	1
413		17	max	0	1	0	15	0	15	6.243e-5	1	NC	1	NC	1
414			min	0	3	-.003	4	0	1	2.923e-6	15	NC	1	NC	1
415		18	max	0	1	0	15	0	15	4.551e-5	1	NC	1	NC	1
416			min	0	3	-.002	4	0	1	2.135e-6	15	NC	1	NC	1
417		19	max	0	1	0	1	0	1	2.859e-5	1	NC	1	NC	1
418			min	0	1	0	1	0	1	1.347e-6	15	NC	1	NC	1
419	M11	1	max	0	1	0	1	0	1	-2.561e-7	15	NC	1	NC	1
420			min	0	1	0	1	0	1	-5.418e-6	1	NC	1	NC	1
421		2	max	0	3	0	15	0	1	-1.947e-6	15	NC	1	NC	1
422			min	0	2	-.003	4	0	15	-4.179e-5	1	NC	1	NC	1
423		3	max	0	3	-.001	15	0	1	-3.637e-6	15	NC	1	NC	1
424			min	0	2	-.006	4	0	15	-7.816e-5	1	NC	1	NC	1
425		4	max	.001	3	-.002	15	0	1	-5.328e-6	15	NC	1	NC	1
426			min	0	2	-.009	4	0	15	-1.145e-4	1	NC	1	NC	1
427		5	max	.002	3	-.003	15	0	1	-7.018e-6	15	NC	1	NC	1
428			min	-.001	2	-.012	4	0	15	-1.509e-4	1	8382.304	4	NC	1
429		6	max	.002	3	-.004	15	0	1	-8.709e-6	15	NC	5	NC	1
430			min	-.002	2	-.015	4	0	15	-1.873e-4	1	6802.371	4	NC	1
431		7	max	.002	3	-.004	15	0	1	-1.04e-5	15	NC	5	NC	1
432			min	-.002	2	-.018	4	0	15	-2.237e-4	1	5850.387	4	NC	1
433		8	max	.003	3	-.005	15	0	12	-1.209e-5	15	NC	5	NC	1
434			min	-.002	2	-.02	4	0	1	-2.6e-4	1	5263.42	4	NC	1
435		9	max	.003	3	-.005	15	0	12	-1.378e-5	15	NC	5	NC	1
436			min	-.003	2	-.021	4	0	1	-2.964e-4	1	4917.683	4	NC	1
437		10	max	.004	3	-.005	15	0	15	-1.547e-5	15	NC	5	NC	1
438			min	-.003	2	-.022	4	-.001	1	-3.328e-4	1	4753.226	4	NC	1
439		11	max	.004	3	-.005	15	0	15	-1.716e-5	15	NC	5	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
440			min	-.003	2	-.022	4	-.002	1	-3.691e-4	1	4745.913	4	NC	1
441		12	max	.004	3	-.005	15	0	15	-1.885e-5	15	NC	5	NC	1
442			min	-.003	2	-.021	4	-.002	1	-4.055e-4	1	4898.163	4	NC	1
443		13	max	.005	3	-.005	15	0	15	-2.054e-5	15	NC	5	NC	1
444			min	-.004	2	-.02	4	-.003	1	-4.419e-4	1	5241.08	4	NC	1
445		14	max	.005	3	-.004	15	0	15	-2.223e-5	15	NC	5	NC	1
446			min	-.004	2	-.018	4	-.004	1	-4.783e-4	1	5850.451	4	NC	1
447		15	max	.006	3	-.004	15	0	15	-2.392e-5	15	NC	3	NC	1
448			min	-.004	2	-.015	4	-.006	1	-5.146e-4	1	6893.779	4	NC	1
449		16	max	.006	3	-.003	15	0	15	-2.562e-5	15	NC	1	NC	1
450			min	-.005	2	-.012	4	-.007	1	-5.51e-4	1	8776.38	4	NC	1
451		17	max	.006	3	-.002	15	0	15	-2.731e-5	15	NC	1	NC	1
452			min	-.005	2	-.009	4	-.009	1	-5.874e-4	1	NC	1	NC	1
453		18	max	.007	3	-.001	15	0	15	-2.9e-5	15	NC	1	NC	2
454			min	-.005	2	-.005	1	-.011	1	-6.237e-4	1	NC	1	9281.402	1
455		19	max	.007	3	0	10	0	15	-3.069e-5	15	NC	1	NC	2
456			min	-.006	2	-.002	1	-.013	1	-6.601e-4	1	NC	1	7743.392	1
457	M12	1	max	.003	1	.005	2	.013	1	-1.09e-5	15	NC	1	NC	3
458			min	0	3	-.007	3	0	15	-2.337e-4	1	NC	1	1889.337	1
459		2	max	.002	1	.005	2	.012	1	-1.09e-5	15	NC	1	NC	3
460			min	0	3	-.007	3	0	15	-2.337e-4	1	NC	1	2050.278	1
461		3	max	.002	1	.005	2	.011	1	-1.09e-5	15	NC	1	NC	3
462			min	0	3	-.007	3	0	15	-2.337e-4	1	NC	1	2242.088	1
463		4	max	.002	1	.004	2	.01	1	-1.09e-5	15	NC	1	NC	3
464			min	0	3	-.006	3	0	15	-2.337e-4	1	NC	1	2472.74	1
465		5	max	.002	1	.004	2	.009	1	-1.09e-5	15	NC	1	NC	3
466			min	0	3	-.006	3	0	15	-2.337e-4	1	NC	1	2753.069	1
467		6	max	.002	1	.004	2	.008	1	-1.09e-5	15	NC	1	NC	3
468			min	0	3	-.005	3	0	15	-2.337e-4	1	NC	1	3098.107	1
469		7	max	.002	1	.004	2	.007	1	-1.09e-5	15	NC	1	NC	3
470			min	0	3	-.005	3	0	15	-2.337e-4	1	NC	1	3529.188	1
471		8	max	.002	1	.003	2	.006	1	-1.09e-5	15	NC	1	NC	3
472			min	0	3	-.005	3	0	15	-2.337e-4	1	NC	1	4077.421	1
473		9	max	.001	1	.003	2	.005	1	-1.09e-5	15	NC	1	NC	2
474			min	0	3	-.004	3	0	15	-2.337e-4	1	NC	1	4789.634	1
475		10	max	.001	1	.003	2	.004	1	-1.09e-5	15	NC	1	NC	2
476			min	0	3	-.004	3	0	15	-2.337e-4	1	NC	1	5739.009	1
477		11	max	.001	1	.002	2	.004	1	-1.09e-5	15	NC	1	NC	2
478			min	0	3	-.003	3	0	15	-2.337e-4	1	NC	1	7045.228	1
479		12	max	.001	1	.002	2	.003	1	-1.09e-5	15	NC	1	NC	2
480			min	0	3	-.003	3	0	15	-2.337e-4	1	NC	1	8915.254	1
481		13	max	0	1	.002	2	.002	1	-1.09e-5	15	NC	1	NC	1
482			min	0	3	-.002	3	0	15	-2.337e-4	1	NC	1	NC	1
483		14	max	0	1	.001	2	.002	1	-1.09e-5	15	NC	1	NC	1
484			min	0	3	-.002	3	0	15	-2.337e-4	1	NC	1	NC	1
485		15	max	0	1	.001	2	.001	1	-1.09e-5	15	NC	1	NC	1
486			min	0	3	-.002	3	0	15	-2.337e-4	1	NC	1	NC	1
487		16	max	0	1	0	2	0	1	-1.09e-5	15	NC	1	NC	1
488			min	0	3	-.001	3	0	15	-2.337e-4	1	NC	1	NC	1
489		17	max	0	1	0	2	0	1	-1.09e-5	15	NC	1	NC	1
490			min	0	3	0	3	0	15	-2.337e-4	1	NC	1	NC	1
491		18	max	0	1	0	2	0	1	-1.09e-5	15	NC	1	NC	1
492			min	0	3	0	3	0	15	-2.337e-4	1	NC	1	NC	1
493		19	max	0	1	0	1	0	1	-1.09e-5	15	NC	1	NC	1
494			min	0	1	0	1	0	1	-2.337e-4	1	NC	1	NC	1
495	M1	1	max	.009	3	.168	2	.001	1	1.334e-2	1	NC	1	NC	1
496			min	-.005	2	-.032	3	0	15	-2.168e-2	3	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
497		2	max	.009	3	.081	2	0	15	6.418e-3	1	NC	5	NC	1
498			min	-.005	2	-.014	3	-.01	1	-1.076e-2	3	1568.567	2	NC	1
499		3	max	.009	3	.014	3	0	15	-4.601e-6	10	NC	5	NC	2
500			min	-.005	2	-.012	2	-.014	1	-2.995e-4	1	756.929	2	8949.968	1
501		4	max	.009	3	.06	3	0	15	4.471e-3	1	NC	15	NC	2
502			min	-.005	2	-.115	2	-.013	1	-4.388e-3	3	479.151	2	9637.775	1
503		5	max	.009	3	.118	3	0	15	9.241e-3	1	9864.306	15	NC	1
504			min	-.004	2	-.223	2	-.009	1	-8.665e-3	3	346.439	2	NC	1
505		6	max	.009	3	.181	3	0	15	1.401e-2	1	7783.457	15	NC	1
506			min	-.004	2	-.328	2	-.004	1	-1.294e-2	3	273.204	2	NC	1
507		7	max	.008	3	.242	3	0	1	1.878e-2	1	6556.288	15	NC	1
508			min	-.004	2	-.421	2	0	3	-1.722e-2	3	229.93	2	NC	1
509		8	max	.008	3	.292	3	.001	1	2.355e-2	1	5830.806	15	NC	1
510			min	-.004	2	-.496	2	0	15	-2.15e-2	3	204.322	2	NC	1
511		9	max	.008	3	.325	3	0	15	2.603e-2	1	5451.695	15	NC	1
512			min	-.004	2	-.542	2	0	1	-2.178e-2	3	190.973	2	NC	1
513		10	max	.008	3	.337	3	0	1	2.725e-2	2	5335.936	15	NC	1
514			min	-.004	2	-.558	2	0	15	-1.941e-2	3	187.053	2	NC	1
515		11	max	.008	3	.329	3	0	1	2.913e-2	2	5451.455	15	NC	1
516			min	-.004	2	-.542	2	0	15	-1.703e-2	3	191.618	2	NC	1
517		12	max	.007	3	.301	3	0	15	2.804e-2	2	5830.307	15	NC	1
518			min	-.004	2	-.493	2	-.001	1	-1.444e-2	3	206.192	1	NC	1
519		13	max	.007	3	.257	3	0	15	2.252e-2	2	6555.428	15	NC	1
520			min	-.004	2	-.416	2	0	1	-1.155e-2	3	233.787	1	NC	1
521		14	max	.007	3	.2	3	.003	1	1.699e-2	2	7782.018	15	NC	1
522			min	-.004	2	-.319	2	0	15	-8.659e-3	3	280.838	1	NC	1
523		15	max	.007	3	.135	3	.008	1	1.146e-2	2	9861.841	15	NC	1
524			min	-.004	2	-.212	2	0	15	-5.769e-3	3	361.45	1	NC	1
525		16	max	.007	3	.069	3	.012	1	5.959e-3	1	NC	15	NC	1
526			min	-.004	2	-.105	2	0	15	-2.878e-3	3	509.72	1	NC	1
527		17	max	.006	3	.005	3	.013	1	8.473e-4	1	NC	5	NC	2
528			min	-.004	2	-.006	2	0	15	1.174e-5	12	824.041	1	9535.805	1
529		18	max	.006	3	.081	1	.009	1	9.339e-3	2	NC	5	NC	1
530			min	-.004	2	-.053	3	0	15	-3.353e-3	3	1736.687	1	NC	1
531		19	max	.006	3	.158	1	0	15	1.853e-2	2	NC	1	NC	1
532			min	-.004	2	-.106	3	-.001	1	-6.831e-3	3	NC	1	NC	1
533	M5	1	max	.028	3	.352	2	0	1	0	1	NC	1	NC	1
534			min	-.019	2	-.029	3	0	1	0	1	NC	1	NC	1
535		2	max	.028	3	.169	2	0	1	0	1	NC	5	NC	1
536			min	-.02	2	-.009	3	0	1	0	1	746.624	2	NC	1
537		3	max	.028	3	.043	3	0	1	0	1	NC	15	NC	1
538			min	-.02	2	-.037	2	0	1	0	1	350.606	2	NC	1
539		4	max	.028	3	.157	3	0	1	0	1	6861.773	15	NC	1
540			min	-.019	2	-.283	2	0	1	0	1	214.333	2	NC	1
541		5	max	.027	3	.313	3	0	1	0	1	4786.935	15	NC	1
542			min	-.019	2	-.551	2	0	1	0	1	150.594	2	NC	1
543		6	max	.026	3	.488	3	0	1	0	1	3676.468	15	NC	1
544			min	-.018	2	-.817	2	0	1	0	1	116.231	2	NC	1
545		7	max	.026	3	.659	3	0	1	0	1	3036.617	15	NC	1
546			min	-.018	2	-1.059	2	0	1	0	1	96.317	2	NC	1
547		8	max	.025	3	.803	3	0	1	0	1	2665.339	15	NC	1
548			min	-.018	2	-1.252	2	0	1	0	1	84.71	1	NC	1
549		9	max	.025	3	.895	3	0	1	0	1	2474.999	15	NC	1
550			min	-.017	2	-1.375	2	0	1	0	1	78.64	1	NC	1
551		10	max	.024	3	.929	3	0	1	0	1	2417.612	15	NC	1
552			min	-.017	2	-1.417	2	0	1	0	1	76.838	1	NC	1
553		11	max	.023	3	.906	3	0	1	0	1	2475.1	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
554			min	-.017	2	-1.375	2	0	1	0	1	78.786	1	NC	1
555		12	max	.023	3	.827	3	0	1	0	1	2665.584	15	NC	1
556			min	-.016	2	-1.247	2	0	1	0	1	85.192	1	NC	1
557		13	max	.022	3	.7	3	0	1	0	1	3037.129	15	NC	1
558			min	-.016	2	-1.043	2	0	1	0	1	97.807	1	NC	1
559		14	max	.022	3	.541	3	0	1	0	1	3677.486	15	NC	1
560			min	-.016	2	-.791	1	0	1	0	1	119.788	1	NC	1
561		15	max	.021	3	.363	3	0	1	0	1	4788.972	15	NC	1
562			min	-.016	2	-.519	1	0	1	0	1	158.521	1	NC	1
563		16	max	.02	3	.182	3	0	1	0	1	6866.079	15	NC	1
564			min	-.015	2	-.251	1	0	1	0	1	232.359	1	NC	1
565		17	max	.02	3	.014	3	0	1	0	1	NC	15	NC	1
566			min	-.015	2	-.019	2	0	1	0	1	394.731	1	NC	1
567		18	max	.02	3	.169	1	0	1	0	1	NC	5	NC	1
568			min	-.015	2	-.129	3	0	1	0	1	865.733	1	NC	1
569		19	max	.02	3	.323	1	0	1	0	1	NC	1	NC	1
570			min	-.015	2	-.258	3	0	1	0	1	NC	1	NC	1
571	M9	1	max	.009	3	.168	2	0	15	2.168e-2	3	NC	1	NC	1
572			min	-.005	2	-.032	3	-.001	1	-1.334e-2	1	NC	1	NC	1
573		2	max	.009	3	.081	2	.01	1	1.076e-2	3	NC	5	NC	1
574			min	-.005	2	-.014	3	0	15	-6.418e-3	1	1568.567	2	NC	1
575		3	max	.009	3	.014	3	.014	1	2.995e-4	1	NC	5	NC	2
576			min	-.005	2	-.012	2	0	15	4.601e-6	10	756.929	2	8949.968	1
577		4	max	.009	3	.06	3	.013	1	4.388e-3	3	NC	15	NC	2
578			min	-.005	2	-.115	2	0	15	-4.471e-3	1	479.151	2	9637.775	1
579		5	max	.009	3	.118	3	.009	1	8.665e-3	3	9864.306	15	NC	1
580			min	-.004	2	-.223	2	0	15	-9.241e-3	1	346.439	2	NC	1
581		6	max	.009	3	.181	3	.004	1	1.294e-2	3	7783.457	15	NC	1
582			min	-.004	2	-.328	2	0	15	-1.401e-2	1	273.204	2	NC	1
583		7	max	.008	3	.242	3	0	3	1.722e-2	3	6556.288	15	NC	1
584			min	-.004	2	-.421	2	0	1	-1.878e-2	1	229.93	2	NC	1
585		8	max	.008	3	.292	3	0	15	2.15e-2	3	5830.806	15	NC	1
586			min	-.004	2	-.496	2	-.001	1	-2.355e-2	1	204.322	2	NC	1
587		9	max	.008	3	.325	3	0	1	2.178e-2	3	5451.695	15	NC	1
588			min	-.004	2	-.542	2	0	15	-2.603e-2	1	190.973	2	NC	1
589		10	max	.008	3	.337	3	0	15	1.941e-2	3	5335.936	15	NC	1
590			min	-.004	2	-.558	2	0	1	-2.725e-2	2	187.053	2	NC	1
591		11	max	.008	3	.329	3	0	15	1.703e-2	3	5451.455	15	NC	1
592			min	-.004	2	-.542	2	0	1	-2.913e-2	2	191.618	2	NC	1
593		12	max	.007	3	.301	3	.001	1	1.444e-2	3	5830.307	15	NC	1
594			min	-.004	2	-.493	2	0	15	-2.804e-2	2	206.192	1	NC	1
595		13	max	.007	3	.257	3	0	1	1.155e-2	3	6555.428	15	NC	1
596			min	-.004	2	-.416	2	0	15	-2.252e-2	2	233.787	1	NC	1
597		14	max	.007	3	.2	3	0	15	8.659e-3	3	7782.018	15	NC	1
598			min	-.004	2	-.319	2	-.003	1	-1.699e-2	2	280.838	1	NC	1
599		15	max	.007	3	.135	3	0	15	5.769e-3	3	9861.841	15	NC	1
600			min	-.004	2	-.212	2	-.008	1	-1.146e-2	2	361.45	1	NC	1
601		16	max	.007	3	.069	3	0	15	2.878e-3	3	NC	15	NC	1
602			min	-.004	2	-.105	2	-.012	1	-5.959e-3	1	509.72	1	NC	1
603		17	max	.006	3	.005	3	0	15	-1.174e-5	12	NC	5	NC	2
604			min	-.004	2	-.006	2	-.013	1	-8.473e-4	1	824.041	1	9535.805	1
605		18	max	.006	3	.081	1	0	15	3.353e-3	3	NC	5	NC	1
606			min	-.004	2	-.053	3	-.009	1	-9.339e-3	2	1736.687	1	NC	1
607		19	max	.006	3	.158	1	.001	1	6.831e-3	3	NC	1	NC	1
608			min	-.004	2	-.106	3	0	15	-1.853e-2	2	NC	1	NC	1

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 4.00 x 0.28

<Figure 1>



<Figure 2>

Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	1020.0	27.0	565.0	565.6
Sum	1020.0	27.0	565.0	565.6

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 1020
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	5.247	10215

$\phi N_{cb} = \phi (A_{Nc} / A_{Nco}) \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-4)

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cb} (lb)
220.36	247.75	0.967	1.00	1.000	10215	0.65	5710

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_a = \phi (A_{Na} / A_{Na0}) \Psi_{ed,Na} \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16a)

A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	ϕ	ϕN_a (lb)
109.66	109.66	1.000	1.000	9755	0.55	5365

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in y-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cby} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cby} (lb)
192.89	220.50	0.925	1.000	1.000	6947	0.70	3934

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cbx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbx} (lb)
165.27	278.72	0.878	1.000	1.000	8282	0.70	3018

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
192.89	220.50	1.000	1.000	1.000	6947	0.70	8508

Shear parallel to edge in y-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cby} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cby} (lb)
165.27	278.72	1.000	1.000	1.000	8282	0.70	6875

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cp} = \phi \min|k_{cp}N_a\,;\, k_{cp}N_{cb}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\,\Psi_{p,Na}N_{a0}\,;\, k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ed,N}\,\Psi_{c,N}\,\Psi_{cp,N}N_b|$ (Eq. D-30a)

k_{cp}	A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	109.66	109.66	1.000	1.000	9755	9755

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ	ϕV_{cp} (lb)
220.36	247.75	0.967	1.000	1.000	10215	8785	0.70	12298

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, ϕN_n (lb)	Ratio	Status
Steel	1020	6071	0.17	Pass
Concrete breakout	1020	5710	0.18	Pass
Adhesive	**1020**	**5365**	**0.19**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, ϕV_n (lb)	Ratio	Status
Steel	**566**	**3156**	**0.18**	**Pass (Governs)**
T Concrete breakout y+	565	3934	0.14	Pass
T Concrete breakout x+	27	3018	0.01	Pass
|| Concrete breakout y+	27	8508	0.00	Pass
|| Concrete breakout x+	565	6875	0.08	Pass
Concrete breakout, combined	-	-	0.14	Pass
Pryout	566	12298	0.05	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status
Sec. D.7.1	0.19	0.00	19.0 %	1.0	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 7.00 x 0.28

<Figure 1>



<Figure 2>



Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	2495.5	1558.5	0.0	1558.5
2	2495.5	1558.5	0.0	1558.5
Sum	4991.0	3117.0	0.0	3117.0

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 4991
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	6.000	12492

$\phi N_{cbg} = \phi (A_{Nc} / A_{Nco}) \Psi_{ec,N} \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-5)

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cbg} (lb)
378.00	324.00	1.000	0.972	1.00	1.000	12492	0.65	9208

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_{ag} = \phi (A_{Na} / A_{Na0}) \Psi_{ed,Na} \Psi_{g,Na} \Psi_{ec,Na} \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16b)

A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0}(lb)	ϕ	ϕN_{ag} (lb)
158.66	109.66	1.000	1.043	1.000	1.000	9755	0.55	8093

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	12.00	15593

$\phi V_{cbgx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ec,V}\Psi_{ed,V}\Psi_{c,V}\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-22)

A_{Vc} (in²)	A_{Vco} (in²)	$\Psi_{ec,V}$	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbgx} (lb)
378.00	648.00	1.000	0.836	1.000	1.000	15593	0.70	5323

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	8.16	8744

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\Psi_{c,V}\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in²)	A_{Vco} (in²)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
299.64	299.64	1.000	1.000	1.000	8744	0.70	12241

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cpg} = \phi \min|k_{cp}N_{ag}\,;\, k_{cp}N_{cbg}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\Psi_{g,Na}\Psi_{ec,Na}\Psi_{p,Na}N_{a0}\,;\, k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ec,N}\Psi_{ed,N}\Psi_{c,N}\Psi_{cp,N}N_b|$ (Eq. D-30b)

k_{cp}	A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	158.66	109.66	1.000	1.043	1.000	1.000	9755	14715

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ
378.00	324.00	1.000	0.972	1.000	1.000	12492	14166	0.70

ϕV_{cpg} (lb)
19833

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, øN_n (lb)	Ratio	Status
Steel	2496	6071	0.41	Pass
Concrete breakout	4991	9208	0.54	Pass
Adhesive	**4991**	**8093**	**0.62**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, øV_n (lb)	Ratio	Status
Steel	1559	3156	0.49	Pass
T Concrete breakout x+	**3117**	**5323**	**0.59**	**Pass (Governs)**

|| Concrete breakout y-	**1559**	**12241**	**0.13**	**Pass (Governs)**
Pryout	3117	19833	0.16	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status
Sec. D.7.3	0.62	0.59	120.2 %	1.2	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.