

Schletter, Inc.		30° Tilt w/o Seismic Design
HCV	Standard FS Racking System	
	Representative Calculations - ASCE 7-10	

1. INTRODUCTION

1.1 Project Description

The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. FS ground mount system.

1.2 Construction

Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to galvanized steel posts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

	Maximum		Minimum	
Height =	1700	mm	1550	mm
Width =	1050	mm	970	mm
Dead Load =	3.00	psf	1.75	psf

Modules Per Row =	2
Module Tilt =	30°
Maximum Height Above Grade =	3 ft



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

1.3 Technical Codes

- ASCE 7-10 - Chapter 26-31, Wind Loads
- ASCE 7-10 - Chapter 7, Snow Loads
- ASCE 7-10 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2012, 2015
- Aluminum Design Manual, Eighth Edition, 2005

2. LOAD ACTIONS

2.1 Permanent Loads

g_{MAX} =	3.00	psf	*Self-weight of the PV modules.*
g_{MIN} =	1.75	psf	

2.2 Snow Loads

Ground Snow Load, P_g =	30.00	psf	
Sloped Roof Snow Load, P_s =	16.49	psf	*(ASCE 7-10, Eq. 7.4-1)*
I_s =	1.00		
C_s =	0.73		
C_e =	0.90		
C_t =	1.20		

2.3 Wind Loads

Design Wind Speed, V =	150	mph	Exposure Category = C
Height <	15	ft	Importance Category = II

Peak Velocity Pressure, q_z = 35.33 psf *Including the gust factor, G=0.85. (ASCE 7-10, Eq. 27.3-1)*

Pressure Coefficients

$Cf+_{TOP}$ =	1.15	*(Pressure)*	*Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0510-e. Negative forces are applied away from the surface.*
$Cf+_{BOTTOM}$ =	1.85		
$Cf-_{TOP}$ =	-2.3	*(Suction)*	
$Cf-_{BOTTOM}$ =	-1.1		

2.4 Seismic Loads - N/A

S_S =	0.00		R =	1.25	*ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.*
S_{DS} =	0.00		C_S =	0	
S_1 =	0.00		ρ =	1.3	
S_{D1} =	0.00		Ω =	1.25	
T_a =	0.00		C_d =	1.25	

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.5W
1.2D + 1.0W + 0.5S
0.9D + 1.0W [M]
1.54D + 1.3E + 0.2S [R]
0.56D + 1.3E [R]
1.54D + 1.25E + 0.2S [O]
0.56D + 1.25E [O]

(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S
1.0D + 0.6W
1.0D + 0.75L + 0.45W + 0.75S
0.6D + 0.6W [M]
1.238D + 0.875E [O]
1.1785D + 0.65625E + 0.75S [O]
0.362D + 0.875E [O]

(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)

[M] *Uses the minimum allowable module dead load.*
[R] *Include redundancy factor of 1.3.*
[O] *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location
M10	Top
M11	Mid-Top
M12	Mid-Bottom
M13	Bottom

Posts	Location
M2	Outer
M5	Inner
M8	Outer

Girders	Location
M1	Outer
M4	Inner
M7	Outer

Reactions	Location
N9	Outer
N19	Inner
N29	Outer

Struts	Location
M3	Outer
M6	Inner
M9	Outer

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type =	**S1.5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	96	in
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	25.07	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	23.08	ksi
S_y =	1.33	in^3
S_x =	0.6	in^3
E =	10100	ksi
I_y =	2.16	in^4
I_x =	1.07	in^4
A =	1.25	in^2
g =	1.50	lbs/ft
M_y =	1.581	k-ft
M_z =	0.108	k-ft
$M_{y\ allowable}$ =	2.779	k-ft
$M_{z\ allowable}$ =	1.154	k-ft
Utilization =	66%	



DETAIL VIEW

4.2 Girder Design

Loads from purlins are transferred to the posts using an inclined girder, which is connected to the steel post. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type =	**T5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	63.82	in
$\Phi F_{ty\ AXIAL}$ =	30.80	ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	30.46	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	31.56	ksi
S_y =	1.98	in^3
S_x =	1.32	in^3
E =	10100	ksi
I_y =	4.74	in^4
I_x =	1.83	in^4
A =	1.93	in^2
g =	2.32	lbs/ft
M_y =	4.469	k-ft
M_z =	0.000	k-ft
P_n =	0.008	k
$M_{y\ allowable}$ =	5.026	k-ft
$M_{z\ allowable}$ =	3.472	k-ft
$P_{n\ allowable}$ =	59.439	k
Utilization =	89%	



DETAIL VIEW

4.3 Strut Design

The aluminum strut connects a portion of the girder to the galvanized steel post. Girder forces are then transferred down through the strut into the post. The strut is attached with single M10 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	61.00	in
$\Phi F_{ty\ AXIAL}$ =	13.67	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.004	k-ft
M_z =	0.000	k-ft
P_n =	4.446	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	13.425	k
Utilization =	33%	



4.4 Post Design

Galvanized steel posts are a roll formed steel section, that are either ram driven into the ground or placed in a concrete foundation at a defined depth. Embedment depths will be provided on the structural drawings or through a geotechnical testing report. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Post Type =	**FG8**	
Steel Type =	J2340	
F_{ty} =	60	ksi
L_b =	79.31	in
Φ =	0.90	
ΦF_{ty} =	54.00	ksi
S_y =	3.46	in^3
S_x =	1.55	in^3
E =	29000	ksi
I_y =	10.94	in^4
I_x =	4.31	in^4
A =	2.23	in^2
g =	7.59	lbs/ft
M_y =	13.684	k-ft
M_z =	0.000	k-ft
P_r =	-5.349	k
$M_{y\ allowable}$ =	19.207	k-ft
$M_{z\ allowable}$ =	14.389	k-ft
P_c =	32.325	k
Utilization =	84%	



5. FOUNDATION DESIGN CALCULATIONS

5.1 Rammed Post Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete footing design.

Maximum Tensile Load =	6.91	k
Maximum Lateral Load =	3.93	k

5.2 Design of Drilled Shaft Foundations

The galvanized steel post is to be embedded into a cylindrical drilled shaft foundation. For the purpose of design, the post is considered to be fixed to the ground. The applicable lateral force, uplift, and compression resistance checks are seen below.

5.3 Lateral Force Resistance

The equivalent lateral force is applied at the top of the post to determine the required embedment depth. A lateral soil bearing capacity for clay is assumed. Footing is unrestrained at ground level. (IBC, Eq. 18-1)

Lateral Force @ Top of Pole, P =	0.88	k
Height of Pole Above Grade, H =	6.61	ft
Diameter of Pole Footing, B =	2.00	ft
Lateral Soil Bearing Capacity, S =	0.10	ksf/ft
Isolated Pole Factor, F =	2	
First Trial Depth, D =	3.25	ft

$$S_3 = Min\ (D, 12')$$

$$S_1 = Min\left(\frac{D}{3}, 12'\right)$$

$$A = 2.34\ P/S_1 B$$

$$D = \left\{0.5A\left(1+\sqrt{1+\left(\frac{4.36\ H}{A}\right)}\right)\right\}$$



Lateral Bearing @ Bottom =	S_3
Lateral Bearing @ D/3 =	S_1
Required Depth =	D

Non-Constrained

Lateral Force @ Top of Pole, P =	0.88	k
Height of Pole Above Grade, H =	6.61	ft
Diameter of Pole Footing, B =	2.00	ft
Lateral Soil Bearing Capacity, S =	0.20	ksf/ft

1st Trial @ D_1 =	3.25	ft	
Lateral Soil Bearing @ D/3, S_1 =	0.22	ksf	
Lateral Soil Bearing @ D, S_3 =	0.65	ksf	
Constant 2.34P/(S_1B), A =	4.75		
Required Footing Depth, D =	8.69	ft	
2nd Trial @ D_2 =	5.97	ft	
Lateral Soil Bearing @ D/3, S_1 =	0.40	ksf	
Lateral Soil Bearing @ D, S_3 =	1.19	ksf	
Constant 2.34P/(S_1B), A =	2.59		
Required Footing Depth, D =	5.80	ft	
3rd Trial @ D_3 =	5.89	ft	
Lateral Soil Bearing @ D/3, S_1 =	0.39	ksf	
Lateral Soil Bearing @ D, S_3 =	1.18	ksf	
Constant 2.34P/(S_1B), A =	2.62		
Required Footing Depth, D =	5.85	ft	
4th Trial @ D_4 =	5.87	ft	
Lateral Soil Bearing @ D/3, S_1 =	0.39	ksf	
Lateral Soil Bearing @ D, S_3 =	1.17	ksf	
Constant 2.34P/(S_1B), A =	2.63		
Required Footing Depth, D =	5.86	ft	
5th Trial @ D_5 =	5.87	ft	
Lateral Soil Bearing @ D/3, S_1 =	0.39	ksf	
Lateral Soil Bearing @ D, S_3 =	1.17	ksf	
Constant 2.34P/(S_1B), A =	2.63		
Required Footing Depth, D =	6.00	ft	

A 2ft diameter x 6ft deep footing unrestrained at ground level is required for the racking structure.

5.4 Uplifting Force Resistance

Uplifting forces of the racking system are checked against the uplift resistance of the soil. Clay soils are assumed.

Weight of Concrete, g_{con} =	145	pcf
Uplifting Force, N =	3.17	k
Footing Diameter, B =	2.00	ft
Factor of Safety =	2.50	
Cohesion =	208.85	psf
γ_s =	120.43	pcf
α =	0.45	
Required Concrete Weight, g =	2.09	k
Required Concrete Volume, V =	14.38	ft^3
Required Footing Depth, D =	4.75	ft

Iteration	z	dz	Qs	Side
1	0.2	0.2	118.10	6.86
2	0.4	0.2	118.10	6.76
3	0.6	0.2	118.10	6.65
4	0.8	0.2	118.10	6.55
5	1	0.2	118.10	6.44
6	1.2	0.2	118.10	6.34
7	1.4	0.2	118.10	6.24
8	1.6	0.2	118.10	6.13
9	1.8	0.2	118.10	6.03
10	2	0.2	118.10	5.93
11	2.2	0.2	118.10	5.82
12	2.4	0.2	118.10	5.72
13	2.6	0.2	118.10	5.62
14	2.8	0.2	118.10	5.51
15	3	0.2	118.10	5.41
16	3.2	0.2	118.10	5.30
17	3.4	0.2	118.10	5.20
18	3.6	0.2	118.10	5.10
19	3.8	0.2	118.10	4.99
20	4	0.2	118.10	4.89
21	4.2	0.2	118.10	4.79
22	4.4	0.2	118.10	4.68
23	4.6	0.2	118.10	4.58
24	0	0.0	0.00	4.58
25	0	0.0	0.00	4.58
26	0	0.0	0.00	4.58
27	0	0.0	0.00	4.58
28	0	0.0	0.00	4.58
29	0	0.0	0.00	4.58
30	0	0.0	0.00	4.58
31	0	0.0	0.00	4.58
32	0	0.0	0.00	4.58
33	0	0.0	0.00	4.58
34	0	0.0	0.00	4.58
Max	4.6	Sum	1.09	

A 2ft diameter x 4.75ft deep footing unrestrained at ground level is required for the racking structure.



5.5 Compressive Force Resistance

Skin friction of the soil is checked against the compression force from the racking and the weight of the drilled shaft foundation. Skin friction starts at 3ft below grade. Clay soils are again assumed.

Depth Below Grade, D =	6.00	ft
Footing Diameter, B =	2.00	ft
Compressive Force, P =	3.70	k
Footing Area =	3.14	ft^2
Circumference =	6.28	ft
Skin Friction Area =	18.85	ft^2
Concrete Weight =	0.145	kcf

Bearing Pressure

Bearing Area =	3.14	ft^2
Bearing Capacity =	1.5	ksf
Resistance =	4.71	k

Weight of Concrete

Footing Volume	18.85	ft^3
Weight	2.73	k

Skin Friction Resistance

Skin Friction =	0.15	ksf
Resistance =	2.83	k
1/3 Increase for Wind =	1.33	
Total Resistance =	10.05	k
Applied Force =	6.44	k
Utilization =	64%	

A 2ft diameter footing passes at a depth of 6ft.



6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of 40mm mounting clamps. The reliability of calculations is uncertain due to limited standards, therefore the strength of the clamp fasteners has been evaluated by load testing.

Fastening of Modules to Purlins

Maximum Uplifting Force	=	0.765 k
Allowable Uplift	=	1.214 k
Utilization	=	63%



Fastening of Purlins to Girders

Maximum Uplifting Force	=	2.190 k
Allowable Uplift	=	2.180 k
Utilization	=	100%



6.2 Strut Connections

The aluminum struts connect the front end of girder to a center section of the steel post. Single M10 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Maximum Axial Load	=	4.446 k
M10 Bolt Shear Capacity	=	8.894 k
Utilization	=	50%

Bolt capacity is accounting for double shear. (ASCE 8-02, Eq. 5.3.4-1)



A strut under compression is shown to demonstrate the load transfer from the girder. Single M10 bolts are located at each end of the strut and are subjected to double shear.

6.3 Girder to Post Connection

In order to connect the girder to the post, custom extruded sections are assembled to create a post head piece. The reliability of calculations is uncertain due to limited standards, therefore the strength of the head piece has been evaluated by load testing.

Maximum Tensile Load	=	4.622 k
Allowable Load	=	5.649 k
Utilization	=	82%



FRONT VIEW



SIDE VIEW



7. SEISMIC DESIGN

7.1 Seismic Drift - N/A

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx}	=	74.11 in
Allowable Story Drift for All Other Structures, Δ	= {	$0.020h_{sx}$
		1.482 in
Max Drift, Δ_{MAX}	=	0 in
N/A		

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **S1.5**

Strong Axis:		Weak Axis:	
3.4.14		**3.4.14**	
L_b =	96 in	L_b =	96
J =	0.432	J =	0.432
	265.581		168.894
$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$		$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$	
S1 =	0.51461	S1 =	0.51461
$S2 = \left(\frac{C_c}{1.6}\right)^2$		$S2 = \left(\frac{C_c}{1.6}\right)^2$	
S2 =	1701.56	S2 =	1701.56
φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]	φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L=	28.0 ksi	φF_L=	29.1
3.4.16		**3.4.16**	
b/t =	32.195	b/t =	37.0588
$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$		$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$	
S1 =	12.2	S1 =	12.2
$S2 = \frac{k_1 Bp}{1.6Dp}$		$S2 = \frac{k_1 Bp}{1.6Dp}$	
S2 =	46.7	S2 =	46.7
φF_L=	φb[Bp-1.6Dp*b/t]	φF_L=	φb[Bp-1.6Dp*b/t]
φF_L=	25.1 ksi	φF_L=	23.1 ksi
3.4.16.1	Not Used	**3.4.16.1**	
Rb/t =		N/A for Weak Direction	
$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$			
S1 =	1.1		
$S2 = C_t$			
S2 =	141.0		
φF_L=	1.17φyFcy		
φF_L=	38.9 ksi		
3.4.18		**3.4.18**	
h/t =	37.0588	h/t =	32.195
$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$		$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$	
S1 =	36.9	S1 =	36.9
m =	0.65	m =	0.65
C_0 =	40.985	C_0 =	45.5
Cc =	41.015	Cc =	45.5
$S2 = \frac{k_1 Bbr}{mDbr}$		$S2 = \frac{k_1 Bbr}{mDbr}$	
S2 =	77.2	S2 =	77.3
φF_L=	φb[Bbr-mDbr*h/t]	φF_L=	1.3φyFcy
φF_L=	43.2 ksi	φF_L=	43.2 ksi
φF_LSt=	25.1 ksi	φF_LWk=	23.1 ksi
Ix =	897074 mm^4	Iy =	446476 mm^4
	2.155 in^4		1.073 in^4
y =	41.015 mm	x =	45.5 mm
Sx =	1.335 in^3	Sy =	0.599 in^3
M_{max}St =	2.788 k-ft	M_{max}Wk =	1.152 k-ft

Compression

3.4.9

b/t = 32.195
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 25.1 ksi

b/t = 37.0588
S1 = 12.21
S2 = 32.70
φF_L = (φck2*√(BpE))/(1.6b/t)
φF_L = 21.9 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 21.94 ksi
A = 1215.13 mm^2
1.88 in^2
P_{max} = 41.32 kips

A.2 Design of Aluminum Girders - Aluminum Design Manual, 2005 Edition

Girder = **T5**

Strong Axis:

3.4.14

L_b = 63.8189 in
J = 1.98
82.1278

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.5 ksi

3.4.16

b/t = 4.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φyFcy
φF_L = 33.3 ksi

Weak Axis:

3.4.14

L_b = 63.8189
J = 1.98
89.1294

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.3

3.4.16

b/t = 16.3333

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 31.6 ksi

3.4.16.1 Used

Rb/t = 20.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= φb[Bt-Dt*√(Rb/t)]

φF_L= 30.8 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 16.3333

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 37.9

m = 0.63

C_0 = 61.046

Cc = 58.954

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 79.4

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 30.5 ksi

Ix = 1970917 mm^4

4.735 in^4

y = 61.046 mm

Sx = 1.970 in^3

$M_{max}St$ = 5.001 k-ft

3.4.18

h/t = 4.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 35

Cc = 35

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 31.6 ksi

Iy = 763048 mm^4

1.833 in^4

x = 35 mm

Sy = 1.330 in^3

$M_{max}Wk$ = 3.499 k-ft

Compression

3.4.9

b/t = 4.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φyFcy

φF_L= 33.3 ksi

b/t = 16.3333

S1 = 12.21

S2 = 32.70

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 31.6 ksi

3.4.10

Rb/t = 20.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L= φc[Bt-Dt*√(Rb/t)]

φF_L= 30.80 ksi

φF_L= 30.80 ksi

A = 1215.13 mm^2

1.88 in^2

P_{max} = 58.01 kips

A.3 Design of Aluminum Struts - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:	Weak Axis:
3.4.14	**3.4.14**
L_b = 61 in	L_b = 61
J = 0.942	J = 0.942
95.1963	95.1963
$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$	$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$
S1 = 0.51461	S1 = 0.51461
$S2 = \left(\frac{C_c}{1.6}\right)^2$	$S2 = \left(\frac{C_c}{1.6}\right)^2$
S2 = 1701.56	S2 = 1701.56
φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]	φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L= 30.2 ksi	φF_L= 30.2
3.4.16	**3.4.16**
b/t = 24.5	b/t = 24.5
$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$	$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$
S1 = 12.2	S1 = 12.2
$S2 = \frac{k_1 Bp}{1.6Dp}$	$S2 = \frac{k_1 Bp}{1.6Dp}$
S2 = 46.7	S2 = 46.7
φF_L= φb[Bp-1.6Dp*b/t]	φF_L= φb[Bp-1.6Dp*b/t]
φF_L= 28.2 ksi	φF_L= 28.2 ksi
3.4.16.1 Not Used	**3.4.16.1**
Rb/t = 0.0	N/A for Weak Direction
$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$	
S1 = 1.1	
$S2 = C_t$	
S2 = 141.0	
φF_L= 1.17φyFcy	
φF_L= 38.9 ksi	
3.4.18	**3.4.18**
h/t = 24.5	h/t = 24.5
$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$	$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$
S1 = 36.9	S1 = 36.9
m = 0.65	m = 0.65
C_0 = 27.5	C_0 = 27.5
Cc = 27.5	Cc = 27.5
$S2 = \frac{k_1 Bbr}{mDbr}$	$S2 = \frac{k_1 Bbr}{mDbr}$
S2 = 77.3	S2 = 77.3
φF_L= 1.3φyFcy	φF_L= 1.3φyFcy
φF_L= 43.2 ksi	φF_L= 43.2 ksi
φF_LSt= 28.2 ksi	φF_LWk= 28.2 ksi
Ix = 279836 mm^4	Iy = 279836 mm^4
0.672 in^4	0.672 in^4
y = 27.5 mm	x = 27.5 mm
Sx = 0.621 in^3	Sy = 0.621 in^3
M_{max}St = 1.460 k-ft	M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 1.41113

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.77756

φF_L = (φccFcy)/(λ²)

φF_L = 13.6667 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 13.67 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 14.07 kips

A.4 Design of Galvanized Steel Posts

Post Type = **FG8**

Unbraced Length =	79.31	in	
Pr =	-5.35	k	(LRFD Factored Load)
Mr (Strong) =	13.68	k-ft	(LRFD Factored Load)
Mr (Weak) =	0.00	k-ft	(LRFD Factored Load)

Flexural Buckling:

kL/r =	114.11			
4.71√(E/Fy) =	103.55	=>	kL/r	> 4.71√(E/Fy)
Fcr =	19.28	ksi		
Fe =	21.98	ksi		
Pn =	42.988	k		

Torsional/Flexural Torsional Buckling:

Fcr =	14.4957	ksi
Fey =	56.0686	ksi
Fez =	18.5443	ksi
Pn =	32.3254	k

Bending (Strong Axis):

Yielding:

Mn =	21.95	k-ft

Flange Local Buckling:

Mn =	19.207	k-ft

Pr/Pc =	0.1244	<	0.2	
Utilization =	0.84	<	1.0	OK

Bending (Weak Axis):

Yielding:

Mn =	14.65	k-ft

Flange Local Buckling:

Mn =	14.39	k-ft

Pr/Pc =	0.124	<	0.2	
Utilization =	0.00	<	1.0	OK

Combined Forces

Utilization = 84%

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				4		
2	Dead Load, Min	DL		-1				4		
3	Snow Load	SL						4		
4	Wind Load - Pressure	WL						4		
5	Wind Load - Suction	WL						4		
6	Seismic - Lateral	EL								

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-8.366	-8.366	0	0
2	M11	Y	-8.366	-8.366	0	0
3	M12	Y	-8.366	-8.366	0	0
4	M13	Y	-8.366	-8.366	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-4.45	-4.45	0	0
2	M11	Y	-4.45	-4.45	0	0
3	M12	Y	-4.45	-4.45	0	0
4	M13	Y	-4.45	-4.45	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-39.836	-39.836	0	0
2	M11	Y	-39.836	-39.836	0	0
3	M12	Y	-39.836	-39.836	0	0
4	M13	Y	-39.836	-39.836	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	y	-113.295	-113.295	0	0
2	M11	y	-113.295	-113.295	0	0
3	M12	y	-182.257	-182.257	0	0
4	M13	y	-182.257	-182.257	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	y	226.59	226.59	0	0
2	M11	y	226.59	226.59	0	0
3	M12	y	108.369	108.369	0	0
4	M13	y	108.369	108.369	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.5W	Yes	Y		1	1.2	3	1.6	4	.5																
2	LRFD 1.2D + 1.0W + 0.5S	Yes	Y		1	1.2	3	.5	4	1																
3	LRFD 0.9D + 1.0W	Yes	Y		2	.9					5	1														
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3														
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3														
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25														
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25														

Load Combinations (Continued)

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
8																										
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																		
10	ASD 1.0D + 0.6W	Yes	Y		1	1			4	.6																
11	ASD 1.0D + 0.75L + 0.45W + 0....	Yes	Y		1	1	3	.75	4	.45																
12	ASD 0.6D + 0.6W	Yes	Y		2	.6					5	.6														
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875														
14	LATERAL - ASD 1.1785D + 0.65...	Yes	Y		1	1.1...	3	.75			6	.656														
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875														

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N9	max	861.853	2	2199.06	2	170.9	2	.224	2	.005	3	3.855	3
2		min	-1167.544	3	-1720.659	3	-212.797	3	-.318	3	-.012	2	.162	15
3	N19	max	3005.125	2	6095.258	2	0	1	0	3	0	3	7.166	3
4		min	-3024.255	3	-5295.851	3	0	3	0	15	0	15	.242	15
5	N29	max	861.853	2	2199.06	2	212.797	3	.318	3	.012	2	3.855	3
6		min	-1167.544	3	-1720.659	3	-170.9	2	-.224	2	-.005	3	.162	15
7	Totals:	max	4728.832	2	10493.379	2	0	2						
8		min	-5359.344	3	-8737.169	3	0	15						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M1	1	max	0	1	.007	2	0	5	0	1	0	1	0	1
2			min	0	1	0	3	0	1	0	1	0	1	0	1
3		2	max	-.261	15	-.452	15	0	5	0	1	0	15	0	4
4			min	-1.11	4	-1.922	4	0	1	0	1	0	1	0	15
5		3	max	-7.885	15	322.061	3	-4.338	15	.055	3	.182	1	.305	2
6			min	-162.563	1	-698.251	2	-105.286	1	-.196	2	.008	15	-.138	3
7		4	max	-8.146	15	320.937	3	-4.338	15	.055	3	.116	1	.739	2
8			min	-163.428	1	-699.75	2	-105.286	1	-.196	2	.005	15	-.338	3
9		5	max	-8.407	15	319.813	3	-4.338	15	.055	3	.051	1	1.173	2
10			min	-164.293	1	-701.248	2	-105.286	1	-.196	2	.002	10	-.536	3
11		6	max	273.853	3	601.708	2	-2.749	12	.033	2	.076	2	1.131	2
12			min	-878.238	2	-183.814	3	-144.42	1	-.05	3	-.028	3	-.55	3
13		7	max	273.204	3	600.21	2	-2.749	12	.033	2	.007	10	.758	2
14			min	-879.103	2	-184.938	3	-144.42	1	-.05	3	-.03	3	-.436	3
15		8	max	272.555	3	598.711	2	-2.749	12	.033	2	-.005	15	.386	2
16			min	-879.968	2	-186.062	3	-144.42	1	-.05	3	-.114	1	-.321	3
17		9	max	242.673	3	109.677	3	-6.776	15	-.001	15	.07	1	.166	2
18			min	-961.878	2	-65.247	2	-159.78	1	-.135	2	.004	15	-.269	3
19		10	max	242.024	3	108.553	3	-6.776	15	-.001	15	.041	3	.207	2
20			min	-962.743	2	-66.746	2	-159.78	1	-.135	2	-.036	2	-.337	3
21		11	max	241.375	3	107.429	3	-6.776	15	-.001	15	.032	3	.249	2
22			min	-963.608	2	-68.244	2	-159.78	1	-.135	2	-.128	1	-.404	3
23		12	max	207.235	3	840.701	3	91.903	2	.271	3	.107	1	.468	2
24			min	-1108.632	1	-505.224	2	-261.525	3	-.215	2	.005	15	-.757	3
25		13	max	206.586	3	839.577	3	91.903	2	.271	3	.122	1	.782	2
26			min	-1109.497	1	-506.723	2	-261.525	3	-.215	2	-.13	3	-1.279	3
27		14	max	164.891	1	474.542	2	-3.726	15	.185	2	.086	3	1.083	2
28			min	8.669	15	-770.626	3	-76.935	1	-.381	3	-.057	2	-1.777	3
29		15	max	164.026	1	473.044	2	-3.726	15	.185	2	.042	3	.789	2
30			min	8.408	15	-771.75	3	-76.935	1	-.381	3	-.099	1	-1.299	3
31		16	max	163.161	1	471.545	2	-3.726	15	.185	2	-.002	12	.496	2
32			min	8.147	15	-772.874	3	-76.935	1	-.381	3	-.146	1	-.82	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
33		17	max	162.296	1	470.047	2	-3.726	15	.185	2	-.008	15	.204	2
34			min	7.886	15	-773.998	3	-76.935	1	-.381	3	-.194	1	-.34	3
35		18	max	1.11	4	1.923	4	0	1	0	1	0	15	0	4
36			min	.261	15	.452	15	0	5	0	1	0	1	0	15
37		19	max	0	1	.003	2	0	1	0	1	0	1	0	1
38			min	0	1	-.007	3	0	5	0	1	0	1	0	1
39	M4	1	max	0	1	.015	2	0	1	0	1	0	1	0	1
40			min	0	1	-.003	3	0	1	0	1	0	1	0	1
41		2	max	-.261	15	-.452	15	0	1	0	1	0	1	0	4
42			min	-1.11	4	-1.92	4	0	1	0	1	0	1	0	15
43		3	max	10.153	3	1008.758	3	0	1	0	1	0	1	.752	2
44			min	-284.713	1	-1964.65	2	0	1	0	1	0	1	-.391	3
45		4	max	9.504	3	1007.634	3	0	1	0	1	0	1	1.972	2
46			min	-285.578	1	-1966.149	2	0	1	0	1	0	1	-1.017	3
47		5	max	8.855	3	1006.51	3	0	1	0	1	0	1	3.193	2
48			min	-286.443	1	-1967.647	2	0	1	0	1	0	1	-1.642	3
49		6	max	1117.071	3	1832.617	2	0	1	0	1	0	1	3.019	2
50			min	-2436.351	2	-804.187	3	0	1	0	1	0	1	-1.602	3
51		7	max	1116.422	3	1831.119	2	0	1	0	1	0	1	1.882	2
52			min	-2437.216	2	-805.311	3	0	1	0	1	0	1	-1.103	3
53		8	max	1115.773	3	1829.62	2	0	1	0	1	0	1	.746	2
54			min	-2438.082	2	-806.435	3	0	1	0	1	0	1	-.603	3
55		9	max	1130.721	3	253.673	3	0	1	0	1	0	1	.077	1
56			min	-2530.953	2	-215.152	2	0	1	0	1	0	1	-.345	3
57		10	max	1130.072	3	252.549	3	0	1	0	1	0	1	.197	2
58			min	-2531.818	2	-216.651	2	0	1	0	1	0	1	-.502	3
59		11	max	1129.423	3	251.425	3	0	1	0	1	0	1	.332	2
60			min	-2532.683	2	-218.15	2	0	1	0	1	0	1	-.658	3
61		12	max	1152.888	3	2324.68	3	0	1	0	1	0	1	1.014	2
62			min	-2632.987	2	-1613.662	2	0	1	0	1	0	1	-1.644	3
63		13	max	1152.239	3	2323.556	3	0	1	0	1	0	1	2.016	2
64			min	-2633.852	2	-1615.161	2	0	1	0	1	0	1	-3.086	3
65		14	max	287.843	1	1328.033	2	0	1	0	1	0	1	2.979	2
66			min	-8.193	3	-1993.594	3	0	1	0	1	0	1	-4.469	3
67		15	max	286.978	1	1326.535	2	0	1	0	1	0	1	2.155	2
68			min	-8.842	3	-1994.718	3	0	1	0	1	0	1	-3.231	3
69		16	max	286.113	1	1325.036	2	0	1	0	1	0	1	1.332	2
70			min	-9.491	3	-1995.842	3	0	1	0	1	0	1	-1.993	3
71		17	max	285.248	1	1323.538	2	0	1	0	1	0	1	.511	2
72			min	-10.14	3	-1996.966	3	0	1	0	1	0	1	-.754	3
73		18	max	1.11	4	1.924	4	0	1	0	1	0	1	0	4
74			min	.261	15	.452	15	0	1	0	1	0	1	0	15
75		19	max	0	1	.008	2	0	1	0	1	0	1	0	1
76			min	0	1	-.015	3	0	1	0	1	0	1	0	1
77	M7	1	max	0	1	.007	2	0	1	0	1	0	1	0	1
78			min	0	1	0	3	0	5	0	1	0	1	0	1
79		2	max	-.261	15	-.452	15	0	1	0	1	0	1	0	4
80			min	-1.11	4	-1.922	4	0	5	0	1	0	15	0	15
81		3	max	-7.885	15	322.061	3	105.286	1	.196	2	-.008	15	.305	2
82			min	-162.563	1	-698.251	2	4.338	15	-.055	3	-.182	1	-.138	3
83		4	max	-8.146	15	320.937	3	105.286	1	.196	2	-.005	15	.739	2
84			min	-163.428	1	-699.75	2	4.338	15	-.055	3	-.116	1	-.338	3
85		5	max	-8.407	15	319.813	3	105.286	1	.196	2	-.002	10	1.173	2
86			min	-164.293	1	-701.248	2	4.338	15	-.055	3	-.051	1	-.536	3
87		6	max	273.853	3	601.708	2	144.42	1	.05	3	.028	3	1.131	2
88			min	-878.238	2	-183.814	3	2.749	12	-.033	2	-.076	2	-.55	3
89		7	max	273.204	3	600.21	2	144.42	1	.05	3	.03	3	.758	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
90			min	-879.103	2	-184.938	3	2.749	12	-.033	2	-.007	10	-.436	3
91		8	max	272.555	3	598.711	2	144.42	1	.05	3	.114	1	.386	2
92			min	-879.968	2	-186.062	3	2.749	12	-.033	2	.005	15	-.321	3
93		9	max	242.673	3	109.677	3	159.78	1	.135	2	-.004	15	.166	2
94			min	-961.878	2	-65.247	2	6.776	15	.001	15	-.07	1	-.269	3
95		10	max	242.024	3	108.553	3	159.78	1	.135	2	.036	2	.207	2
96			min	-962.743	2	-66.746	2	6.776	15	.001	15	-.041	3	-.337	3
97		11	max	241.375	3	107.429	3	159.78	1	.135	2	.128	1	.249	2
98			min	-963.608	2	-68.244	2	6.776	15	.001	15	-.032	3	-.404	3
99		12	max	207.235	3	840.701	3	261.525	3	.215	2	-.005	15	.468	2
100			min	-1108.632	1	-505.224	2	-91.903	2	-.271	3	-.107	1	-.757	3
101		13	max	206.586	3	839.577	3	261.525	3	.215	2	.13	3	.782	2
102			min	-1109.497	1	-506.723	2	-91.903	2	-.271	3	-.122	1	-1.279	3
103		14	max	164.891	1	474.542	2	76.935	1	.381	3	.057	2	1.083	2
104			min	8.669	15	-770.626	3	3.726	15	-.185	2	-.086	3	-1.777	3
105		15	max	164.026	1	473.044	2	76.935	1	.381	3	.099	1	.789	2
106			min	8.408	15	-771.75	3	3.726	15	-.185	2	-.042	3	-1.299	3
107		16	max	163.161	1	471.545	2	76.935	1	.381	3	.146	1	.496	2
108			min	8.147	15	-772.874	3	3.726	15	-.185	2	.002	12	-.82	3
109		17	max	162.296	1	470.047	2	76.935	1	.381	3	.194	1	.204	2
110			min	7.886	15	-773.998	3	3.726	15	-.185	2	.008	15	-.34	3
111		18	max	1.11	4	1.923	4	0	5	0	1	0	1	0	4
112			min	.261	15	.452	15	0	1	0	1	0	15	0	15
113		19	max	0	1	.003	2	0	5	0	1	0	1	0	1
114			min	0	1	-.007	3	0	1	0	1	0	1	0	1
115	M10	1	max	76.943	1	466.776	2	-7.364	15	.013	2	.225	1	.185	2
116			min	3.726	15	-776.238	3	-160.676	1	-.027	3	.01	15	-.381	3
117		2	max	76.943	1	341.619	2	-5.776	15	.013	2	.097	1	.221	3
118			min	3.726	15	-578.95	3	-127.085	1	-.027	3	.004	15	-.174	2
119		3	max	76.943	1	216.462	2	-4.188	15	.013	2	.031	3	.648	3
120			min	3.726	15	-381.662	3	-93.493	1	-.027	3	-.007	9	-.422	2
121		4	max	76.943	1	91.305	2	-2.6	15	.013	2	.012	3	.9	3
122			min	3.726	15	-184.373	3	-59.902	1	-.027	3	-.069	1	-.559	2
123		5	max	76.943	1	12.915	3	-1.012	15	.013	2	-.003	12	.976	3
124			min	3.726	15	-33.852	2	-26.31	1	-.027	3	-.107	1	-.585	2
125		6	max	76.943	1	210.203	3	7.947	9	.013	2	-.005	15	.877	3
126			min	3.726	15	-159.009	2	-15.348	3	-.027	3	-.116	1	-.499	2
127		7	max	76.943	1	407.491	3	40.873	1	.013	2	-.004	15	.602	3
128			min	3.726	15	-284.166	2	-12.966	3	-.027	3	-.094	1	-.302	2
129		8	max	76.943	1	604.779	3	74.464	1	.013	2	-.001	15	.152	3
130			min	3.726	15	-409.323	2	-10.585	3	-.027	3	-.043	1	0	10
131		9	max	76.943	1	802.068	3	108.056	1	.013	2	.038	1	.426	2
132			min	3.726	15	-534.48	2	-8.203	3	-.027	3	-.051	3	-.473	3
133		10	max	76.943	1	659.637	2	141.648	1	.007	10	.149	1	.956	2
134			min	3.726	15	-999.356	3	-52.207	2	-.027	3	-.057	3	-1.274	3
135		11	max	76.943	1	534.48	2	8.203	3	.027	3	.038	1	.426	2
136			min	3.726	15	-802.068	3	-108.056	1	-.013	2	-.051	3	-.473	3
137		12	max	76.943	1	409.323	2	10.585	3	.027	3	-.001	15	.152	3
138			min	3.726	15	-604.779	3	-74.464	1	-.013	2	-.043	1	0	10
139		13	max	76.943	1	284.166	2	12.966	3	.027	3	-.004	15	.602	3
140			min	3.726	15	-407.491	3	-40.873	1	-.013	2	-.094	1	-.302	2
141		14	max	76.943	1	159.009	2	15.348	3	.027	3	-.005	15	.877	3
142			min	3.726	15	-210.203	3	-7.947	9	-.013	2	-.116	1	-.499	2
143		15	max	76.943	1	33.852	2	26.31	1	.027	3	-.003	12	.976	3
144			min	3.726	15	-12.915	3	1.012	15	-.013	2	-.107	1	-.585	2
145		16	max	76.943	1	184.373	3	59.902	1	.027	3	.012	3	.9	3
146			min	3.726	15	-91.305	2	2.6	15	-.013	2	-.069	1	-.559	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
147		17	max	76.943	1	381.662	3	93.493	1	.027	3	.031	3	.648	3
148			min	3.726	15	-216.462	2	4.188	15	-.013	2	-.007	9	-.422	2
149		18	max	76.943	1	578.95	3	127.085	1	.027	3	.097	1	.221	3
150			min	3.726	15	-341.619	2	5.776	15	-.013	2	.004	15	-.174	2
151		19	max	76.943	1	776.238	3	160.676	1	.027	3	.225	1	.185	2
152			min	3.726	15	-466.776	2	7.364	15	-.013	2	.01	15	-.381	3
153	M11	1	max	183.864	2	433.671	2	-7.694	15	0	15	.262	1	.084	1
154			min	-247.66	3	-734.94	3	-167.581	1	-.004	1	.012	15	-.373	3
155		2	max	183.864	2	308.514	2	-6.106	15	0	15	.128	1	.192	3
156			min	-247.66	3	-537.652	3	-133.989	1	-.004	1	.005	15	-.251	2
157		3	max	183.864	2	183.357	2	-4.518	15	0	15	.052	3	.582	3
158			min	-247.66	3	-340.364	3	-100.398	1	-.004	1	0	15	-.469	2
159		4	max	183.864	2	58.2	2	-2.93	15	0	15	.028	3	.797	3
160			min	-247.66	3	-143.076	3	-66.806	1	-.004	1	-.051	1	-.577	2
161		5	max	183.864	2	54.212	3	-1.342	15	0	15	.006	3	.837	3
162			min	-247.66	3	-66.957	2	-33.215	1	-.004	1	-.095	1	-.573	2
163		6	max	183.864	2	251.501	3	3.344	9	0	15	-.005	15	.701	3
164			min	-247.66	3	-192.114	2	-21.23	3	-.004	1	-.11	1	-.457	2
165		7	max	183.864	2	448.789	3	33.968	1	0	15	-.004	15	.39	3
166			min	-247.66	3	-317.271	2	-18.848	3	-.004	1	-.095	1	-.231	2
167		8	max	183.864	2	646.077	3	67.56	1	0	15	-.002	15	.107	2
168			min	-247.66	3	-442.428	2	-16.467	3	-.004	1	-.049	1	-.097	3
169		9	max	183.864	2	843.365	3	101.151	1	0	15	.027	9	.555	2
170			min	-247.66	3	-567.585	2	-14.085	3	-.004	1	-.061	3	-.759	3
171		10	max	183.864	2	1040.653	3	-6.511	12	0	15	.13	1	1.116	2
172			min	-247.66	3	15.089	15	-134.743	1	-.004	1	-.072	3	-1.596	3
173		11	max	183.864	2	567.585	2	14.085	3	.004	1	.027	9	.555	2
174			min	-247.66	3	-843.365	3	-101.151	1	0	15	-.061	3	-.759	3
175		12	max	183.864	2	442.428	2	16.467	3	.004	1	-.002	15	.107	2
176			min	-247.66	3	-646.077	3	-67.56	1	0	15	-.049	1	-.097	3
177		13	max	183.864	2	317.271	2	18.848	3	.004	1	-.004	15	.39	3
178			min	-247.66	3	-448.789	3	-33.968	1	0	15	-.095	1	-.231	2
179		14	max	183.864	2	192.114	2	21.23	3	.004	1	-.005	15	.701	3
180			min	-247.66	3	-251.501	3	-3.344	9	0	15	-.11	1	-.457	2
181		15	max	183.864	2	66.957	2	33.215	1	.004	1	.006	3	.837	3
182			min	-247.66	3	-54.212	3	1.342	15	0	15	-.095	1	-.573	2
183		16	max	183.864	2	143.076	3	66.806	1	.004	1	.028	3	.797	3
184			min	-247.66	3	-58.2	2	2.93	15	0	15	-.051	1	-.577	2
185		17	max	183.864	2	340.364	3	100.398	1	.004	1	.052	3	.582	3
186			min	-247.66	3	-183.357	2	4.518	15	0	15	0	15	-.469	2
187		18	max	183.864	2	537.652	3	133.989	1	.004	1	.128	1	.192	3
188			min	-247.66	3	-308.514	2	6.106	15	0	15	.005	15	-.251	2
189		19	max	183.864	2	734.94	3	167.581	1	.004	1	.262	1	.084	1
190			min	-247.66	3	-433.671	2	7.694	15	0	15	.012	15	-.373	3
191	M12	1	max	23.246	2	660.874	2	-7.762	15	0	15	.277	1	.169	2
192			min	-22.117	9	-297.277	3	-170.464	1	-.004	1	.012	15	.002	15
193		2	max	23.246	2	474.418	2	-6.174	15	0	15	.14	1	.276	3
194			min	-22.117	9	-205.074	3	-136.872	1	-.004	1	.006	15	-.336	2
195		3	max	23.246	2	287.961	2	-4.586	15	0	15	.039	3	.417	3
196			min	-22.117	9	-112.872	3	-103.281	1	-.004	1	0	15	-.675	2
197		4	max	23.246	2	101.505	2	-2.998	15	0	15	.018	3	.476	3
198			min	-22.117	9	-20.669	3	-69.689	1	-.004	1	-.043	1	-.848	2
199		5	max	23.246	2	71.534	3	-1.41	15	0	15	0	3	.454	3
200			min	-22.117	9	-84.952	2	-36.098	1	-.004	1	-.09	1	-.855	2
201		6	max	23.246	2	163.737	3	2.407	9	0	15	-.005	15	.349	3
202			min	-22.117	9	-271.408	2	-17.31	3	-.004	1	-.108	1	-.697	2
203		7	max	23.246	2	255.94	3	31.085	1	0	15	-.004	15	.163	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
204			min	-22.117	9	-457.865	2	-14.929	3	-.004	1	-.095	1	-.373	2
205		8	max	23.246	2	348.143	3	64.677	1	0	15	-.002	15	.117	2
206			min	-22.117	9	-644.321	2	-12.547	3	-.004	1	-.052	1	-.106	3
207		9	max	23.246	2	440.346	3	98.269	1	0	15	.026	9	.773	2
208			min	-22.117	9	-830.778	2	-10.165	3	-.004	1	-.054	3	-.456	3
209		10	max	23.246	2	1017.235	2	-4.165	12	0	15	.122	1	1.594	2
210			min	-22.117	9	15.132	15	-131.86	1	-.004	1	-.062	3	-.889	3
211		11	max	23.246	2	830.778	2	10.165	3	.004	1	.026	9	.773	2
212			min	-22.117	9	-440.346	3	-98.269	1	0	15	-.054	3	-.456	3
213		12	max	23.246	2	644.321	2	12.547	3	.004	1	-.002	15	.117	2
214			min	-22.117	9	-348.143	3	-64.677	1	0	15	-.052	1	-.106	3
215		13	max	23.246	2	457.865	2	14.929	3	.004	1	-.004	15	.163	3
216			min	-22.117	9	-255.94	3	-31.085	1	0	15	-.095	1	-.373	2
217		14	max	23.246	2	271.408	2	17.31	3	.004	1	-.005	15	.349	3
218			min	-22.117	9	-163.737	3	-2.407	9	0	15	-.108	1	-.697	2
219		15	max	23.246	2	84.952	2	36.098	1	.004	1	0	3	.454	3
220			min	-22.117	9	-71.534	3	1.41	15	0	15	-.09	1	-.855	2
221		16	max	23.246	2	20.669	3	69.689	1	.004	1	.018	3	.476	3
222			min	-22.117	9	-101.505	2	2.998	15	0	15	-.043	1	-.848	2
223		17	max	23.246	2	112.872	3	103.281	1	.004	1	.039	3	.417	3
224			min	-22.117	9	-287.961	2	4.586	15	0	15	0	15	-.675	2
225		18	max	23.246	2	205.074	3	136.872	1	.004	1	.14	1	.276	3
226			min	-22.117	9	-474.418	2	6.174	15	0	15	.006	15	-.336	2
227		19	max	23.246	2	297.277	3	170.464	1	.004	1	.277	1	.169	2
228			min	-22.117	9	-660.874	2	7.762	15	0	15	.012	15	.002	15
229	M13	1	max	-4.338	15	695.763	2	-7.363	15	.008	3	.224	1	.196	2
230			min	-105.213	1	-324.342	3	-160.676	1	-.022	2	.01	15	-.055	3
231		2	max	-4.338	15	509.307	2	-5.775	15	.008	3	.096	1	.193	3
232			min	-105.213	1	-232.139	3	-127.084	1	-.022	2	.004	15	-.34	2
233		3	max	-4.338	15	322.85	2	-4.187	15	.008	3	.031	3	.358	3
234			min	-105.213	1	-139.936	3	-93.493	1	-.022	2	-.007	9	-.709	2
235		4	max	-4.338	15	136.393	2	-2.599	15	.008	3	.013	3	.442	3
236			min	-105.213	1	-47.734	3	-59.901	1	-.022	2	-.07	1	-.914	2
237		5	max	-4.338	15	44.469	3	-1.011	15	.008	3	-.003	12	.443	3
238			min	-105.213	1	-50.063	2	-26.31	1	-.022	2	-.108	1	-.952	2
239		6	max	-4.338	15	136.672	3	7.963	9	.008	3	-.005	15	.362	3
240			min	-105.213	1	-236.52	2	-15.215	3	-.022	2	-.117	1	-.824	2
241		7	max	-4.338	15	228.875	3	40.873	1	.008	3	-.004	15	.2	3
242			min	-105.213	1	-422.976	2	-12.834	3	-.022	2	-.095	1	-.531	2
243		8	max	-4.338	15	321.078	3	74.465	1	.008	3	-.001	15	-.003	15
244			min	-105.213	1	-609.433	2	-10.452	3	-.022	2	-.044	1	-.079	1
245		9	max	-4.338	15	413.281	3	108.057	1	.008	3	.037	1	.552	2
246			min	-105.213	1	-795.889	2	-8.07	3	-.022	2	-.05	3	-.371	3
247		10	max	-4.338	15	982.346	2	-2.849	12	0	15	.148	1	1.342	2
248			min	-105.213	1	14.166	15	-141.648	1	-.022	2	-.056	3	-.779	3
249		11	max	-4.338	15	795.889	2	8.07	3	.022	2	.037	1	.552	2
250			min	-105.213	1	-413.281	3	-108.057	1	-.008	3	-.05	3	-.371	3
251		12	max	-4.338	15	609.433	2	10.452	3	.022	2	-.001	15	-.003	15
252			min	-105.213	1	-321.078	3	-74.465	1	-.008	3	-.044	1	-.079	1
253		13	max	-4.338	15	422.976	2	12.834	3	.022	2	-.004	15	.2	3
254			min	-105.213	1	-228.875	3	-40.873	1	-.008	3	-.095	1	-.531	2
255		14	max	-4.338	15	236.52	2	15.215	3	.022	2	-.005	15	.362	3
256			min	-105.213	1	-136.672	3	-7.963	9	-.008	3	-.117	1	-.824	2
257		15	max	-4.338	15	50.063	2	26.31	1	.022	2	-.003	12	.443	3
258			min	-105.213	1	-44.469	3	1.011	15	-.008	3	-.108	1	-.952	2
259		16	max	-4.338	15	47.734	3	59.901	1	.022	2	.013	3	.442	3
260			min	-105.213	1	-136.393	2	2.599	15	-.008	3	-.07	1	-.914	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
261		17	max	-4.338	15	139.936	3	93.493	1	.022	2	.031	3	.358	3
262			min	-105.213	1	-322.85	2	4.187	15	-.008	3	-.007	9	-.709	2
263		18	max	-4.338	15	232.139	3	127.084	1	.022	2	.096	1	.193	3
264			min	-105.213	1	-509.307	2	5.775	15	-.008	3	.004	15	-.34	2
265		19	max	-4.338	15	324.342	3	160.676	1	.022	2	.224	1	.196	2
266			min	-105.213	1	-695.763	2	7.363	15	-.008	3	.01	15	-.055	3
267	M2	1	max	2199.06	2	1166.85	3	171.023	2	.005	3	.318	3	3.855	3
268			min	-1720.659	3	-861.449	2	-212.661	3	-.012	2	-.224	2	.162	15
269		2	max	2196.223	2	1166.85	3	171.023	2	.005	3	.251	3	3.515	1
270			min	-1722.787	3	-861.449	2	-212.661	3	-.012	2	-.171	2	.16	15
271		3	max	1458.091	2	685.177	1	120.458	2	.001	2	.197	3	3.416	1
272			min	-1447.963	3	30.717	15	-190.31	3	0	3	-.14	2	.153	15
273		4	max	1455.254	2	685.177	1	120.458	2	.001	2	.137	3	3.203	1
274			min	-1450.091	3	30.717	15	-190.31	3	0	3	-.102	2	.144	15
275		5	max	1452.416	2	685.177	1	120.458	2	.001	2	.078	3	2.989	1
276			min	-1452.219	3	30.717	15	-190.31	3	0	3	-.065	1	.134	15
277		6	max	1449.579	2	685.177	1	120.458	2	.001	2	.019	3	2.776	1
278			min	-1454.347	3	30.717	15	-190.31	3	0	3	-.034	1	.124	15
279		7	max	1446.741	2	685.177	1	120.458	2	.001	2	.01	2	2.562	1
280			min	-1456.475	3	30.717	15	-190.31	3	0	3	-.041	3	.115	15
281		8	max	1443.904	2	685.177	1	120.458	2	.001	2	.048	2	2.349	1
282			min	-1458.603	3	30.717	15	-190.31	3	0	3	-.1	3	.105	15
283		9	max	1441.067	2	685.177	1	120.458	2	.001	2	.085	2	2.135	1
284			min	-1460.731	3	30.717	15	-190.31	3	0	3	-.159	3	.096	15
285		10	max	1438.229	2	685.177	1	120.458	2	.001	2	.123	2	1.922	1
286			min	-1462.859	3	30.717	15	-190.31	3	0	3	-.219	3	.086	15
287		11	max	1435.392	2	685.177	1	120.458	2	.001	2	.161	2	1.708	1
288			min	-1464.987	3	30.717	15	-190.31	3	0	3	-.278	3	.077	15
289		12	max	1432.554	2	685.177	1	120.458	2	.001	2	.198	2	1.495	1
290			min	-1467.115	3	30.717	15	-190.31	3	0	3	-.337	3	.067	15
291		13	max	1429.717	2	685.177	1	120.458	2	.001	2	.236	2	1.281	1
292			min	-1469.244	3	30.717	15	-190.31	3	0	3	-.396	3	.057	15
293		14	max	1426.879	2	685.177	1	120.458	2	.001	2	.273	2	1.068	1
294			min	-1471.372	3	30.717	15	-190.31	3	0	3	-.456	3	.048	15
295		15	max	1424.042	2	685.177	1	120.458	2	.001	2	.311	2	.854	1
296			min	-1473.5	3	30.717	15	-190.31	3	0	3	-.515	3	.038	15
297		16	max	1421.204	2	685.177	1	120.458	2	.001	2	.348	2	.641	1
298			min	-1475.628	3	30.717	15	-190.31	3	0	3	-.574	3	.029	15
299		17	max	1418.367	2	685.177	1	120.458	2	.001	2	.386	2	.427	1
300			min	-1477.756	3	30.717	15	-190.31	3	0	3	-.634	3	.019	15
301		18	max	1415.53	2	685.177	1	120.458	2	.001	2	.423	2	.214	1
302			min	-1479.884	3	30.717	15	-190.31	3	0	3	-.693	3	.01	15
303		19	max	1412.692	2	685.177	1	120.458	2	.001	2	.461	2	0	1
304			min	-1482.012	3	30.717	15	-190.31	3	0	3	-.752	3	0	1
305	M5	1	max	6095.258	2	3020.169	3	0	1	0	1	0	1	7.166	3
306			min	-5295.851	3	-3003.557	2	0	1	0	1	0	1	.242	15
307		2	max	6092.421	2	3020.169	3	0	1	0	1	0	1	6.225	3
308			min	-5297.979	3	-3003.557	2	0	1	0	1	0	1	.246	15
309		3	max	3969.168	2	1192.875	1	0	1	0	1	0	1	5.947	1
310			min	-4294.971	3	47.682	15	0	1	0	1	0	1	.238	15
311		4	max	3966.331	2	1192.875	1	0	1	0	1	0	1	5.576	1
312			min	-4297.099	3	47.682	15	0	1	0	1	0	1	.223	15
313		5	max	3963.493	2	1192.875	1	0	1	0	1	0	1	5.204	1
314			min	-4299.227	3	47.682	15	0	1	0	1	0	1	.208	15
315		6	max	3960.656	2	1192.875	1	0	1	0	1	0	1	4.832	1
316			min	-4301.355	3	47.682	15	0	1	0	1	0	1	.193	15
317		7	max	3957.818	2	1192.875	1	0	1	0	1	0	1	4.46	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
318			min	-4303.484	3	47.682	15	0	1	0	1	0	1	.178	15
319		8	max	3954.981	2	1192.875	1	0	1	0	1	0	1	4.089	1
320			min	-4305.612	3	47.682	15	0	1	0	1	0	1	.163	15
321		9	max	3952.144	2	1192.875	1	0	1	0	1	0	1	3.717	1
322			min	-4307.74	3	47.682	15	0	1	0	1	0	1	.149	15
323		10	max	3949.306	2	1192.875	1	0	1	0	1	0	1	3.345	1
324			min	-4309.868	3	47.682	15	0	1	0	1	0	1	.134	15
325		11	max	3946.469	2	1192.875	1	0	1	0	1	0	1	2.974	1
326			min	-4311.996	3	47.682	15	0	1	0	1	0	1	.119	15
327		12	max	3943.631	2	1192.875	1	0	1	0	1	0	1	2.602	1
328			min	-4314.124	3	47.682	15	0	1	0	1	0	1	.104	15
329		13	max	3940.794	2	1192.875	1	0	1	0	1	0	1	2.23	1
330			min	-4316.252	3	47.682	15	0	1	0	1	0	1	.089	15
331		14	max	3937.956	2	1192.875	1	0	1	0	1	0	1	1.859	1
332			min	-4318.38	3	47.682	15	0	1	0	1	0	1	.074	15
333		15	max	3935.119	2	1192.875	1	0	1	0	1	0	1	1.487	1
334			min	-4320.508	3	47.682	15	0	1	0	1	0	1	.059	15
335		16	max	3932.281	2	1192.875	1	0	1	0	1	0	1	1.115	1
336			min	-4322.636	3	47.682	15	0	1	0	1	0	1	.045	15
337		17	max	3929.444	2	1192.875	1	0	1	0	1	0	1	.743	1
338			min	-4324.764	3	47.682	15	0	1	0	1	0	1	.03	15
339		18	max	3926.607	2	1192.875	1	0	1	0	1	0	1	.372	1
340			min	-4326.892	3	47.682	15	0	1	0	1	0	1	.015	15
341		19	max	3923.769	2	1192.875	1	0	1	0	1	0	1	0	1
342			min	-4329.02	3	47.682	15	0	1	0	1	0	1	0	1
343	M8	1	max	2199.06	2	1166.85	3	212.661	3	.012	2	.224	2	3.855	3
344			min	-1720.659	3	-861.449	2	-171.023	2	-.005	3	-.318	3	.162	15
345		2	max	2196.223	2	1166.85	3	212.661	3	.012	2	.171	2	3.515	1
346			min	-1722.787	3	-861.449	2	-171.023	2	-.005	3	-.251	3	.16	15
347		3	max	1458.091	2	685.177	1	190.31	3	0	3	.14	2	3.416	1
348			min	-1447.963	3	30.717	15	-120.458	2	-.001	2	-.197	3	.153	15
349		4	max	1455.254	2	685.177	1	190.31	3	0	3	.102	2	3.203	1
350			min	-1450.091	3	30.717	15	-120.458	2	-.001	2	-.137	3	.144	15
351		5	max	1452.416	2	685.177	1	190.31	3	0	3	.065	1	2.989	1
352			min	-1452.219	3	30.717	15	-120.458	2	-.001	2	-.078	3	.134	15
353		6	max	1449.579	2	685.177	1	190.31	3	0	3	.034	1	2.776	1
354			min	-1454.347	3	30.717	15	-120.458	2	-.001	2	-.019	3	.124	15
355		7	max	1446.741	2	685.177	1	190.31	3	0	3	.041	3	2.562	1
356			min	-1456.475	3	30.717	15	-120.458	2	-.001	2	-.01	2	.115	15
357		8	max	1443.904	2	685.177	1	190.31	3	0	3	.1	3	2.349	1
358			min	-1458.603	3	30.717	15	-120.458	2	-.001	2	-.048	2	.105	15
359		9	max	1441.067	2	685.177	1	190.31	3	0	3	.159	3	2.135	1
360			min	-1460.731	3	30.717	15	-120.458	2	-.001	2	-.085	2	.096	15
361		10	max	1438.229	2	685.177	1	190.31	3	0	3	.219	3	1.922	1
362			min	-1462.859	3	30.717	15	-120.458	2	-.001	2	-.123	2	.086	15
363		11	max	1435.392	2	685.177	1	190.31	3	0	3	.278	3	1.708	1
364			min	-1464.987	3	30.717	15	-120.458	2	-.001	2	-.161	2	.077	15
365		12	max	1432.554	2	685.177	1	190.31	3	0	3	.337	3	1.495	1
366			min	-1467.115	3	30.717	15	-120.458	2	-.001	2	-.198	2	.067	15
367		13	max	1429.717	2	685.177	1	190.31	3	0	3	.396	3	1.281	1
368			min	-1469.244	3	30.717	15	-120.458	2	-.001	2	-.236	2	.057	15
369		14	max	1426.879	2	685.177	1	190.31	3	0	3	.456	3	1.068	1
370			min	-1471.372	3	30.717	15	-120.458	2	-.001	2	-.273	2	.048	15
371		15	max	1424.042	2	685.177	1	190.31	3	0	3	.515	3	.854	1
372			min	-1473.5	3	30.717	15	-120.458	2	-.001	2	-.311	2	.038	15
373		16	max	1421.204	2	685.177	1	190.31	3	0	3	.574	3	.641	1
374			min	-1475.628	3	30.717	15	-120.458	2	-.001	2	-.348	2	.029	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
375		17	max	1418.367	2	685.177	1	190.31	3	0	3	.634	3	.427	1
376			min	-1477.756	3	30.717	15	-120.458	2	-.001	2	-.386	2	.019	15
377		18	max	1415.53	2	685.177	1	190.31	3	0	3	.693	3	.214	1
378			min	-1479.884	3	30.717	15	-120.458	2	-.001	2	-.423	2	.01	15
379		19	max	1412.692	2	685.177	1	190.31	3	0	3	.752	3	0	1
380			min	-1482.012	3	30.717	15	-120.458	2	-.001	2	-.461	2	0	1
381	M3	1	max	1530.741	2	4.384	4	50.213	2	.009	3	.002	3	0	1
382			min	-584.375	3	1.031	15	-22.69	3	-.017	2	-.006	2	0	1
383		2	max	1530.533	2	3.897	4	50.213	2	.009	3	.009	2	0	15
384			min	-584.531	3	.916	15	-22.69	3	-.017	2	-.005	3	-.001	4
385		3	max	1530.325	2	3.41	4	50.213	2	.009	3	.024	2	0	15
386			min	-584.687	3	.802	15	-22.69	3	-.017	2	-.011	3	-.002	4
387		4	max	1530.117	2	2.923	4	50.213	2	.009	3	.038	2	0	15
388			min	-584.843	3	.687	15	-22.69	3	-.017	2	-.018	3	-.003	4
389		5	max	1529.909	2	2.436	4	50.213	2	.009	3	.053	2	0	15
390			min	-584.999	3	.573	15	-22.69	3	-.017	2	-.024	3	-.004	4
391		6	max	1529.701	2	1.949	4	50.213	2	.009	3	.068	2	-.001	15
392			min	-585.155	3	.458	15	-22.69	3	-.017	2	-.031	3	-.005	4
393		7	max	1529.493	2	1.461	4	50.213	2	.009	3	.082	2	-.001	15
394			min	-585.311	3	.344	15	-22.69	3	-.017	2	-.038	3	-.005	4
395		8	max	1529.285	2	.974	4	50.213	2	.009	3	.097	2	-.001	15
396			min	-585.467	3	.229	15	-22.69	3	-.017	2	-.044	3	-.005	4
397		9	max	1529.077	2	.487	4	50.213	2	.009	3	.111	2	-.001	15
398			min	-585.624	3	.115	15	-22.69	3	-.017	2	-.051	3	-.006	4
399		10	max	1528.869	2	0	1	50.213	2	.009	3	.126	2	-.001	15
400			min	-585.78	3	0	1	-22.69	3	-.017	2	-.057	3	-.006	4
401		11	max	1528.66	2	-.115	15	50.213	2	.009	3	.141	2	-.001	15
402			min	-585.936	3	-.487	4	-22.69	3	-.017	2	-.064	3	-.006	4
403		12	max	1528.452	2	-.229	15	50.213	2	.009	3	.155	2	-.001	15
404			min	-586.092	3	-.974	4	-22.69	3	-.017	2	-.071	3	-.005	4
405		13	max	1528.244	2	-.344	15	50.213	2	.009	3	.17	2	-.001	15
406			min	-586.248	3	-1.461	4	-22.69	3	-.017	2	-.077	3	-.005	4
407		14	max	1528.036	2	-.458	15	50.213	2	.009	3	.185	2	-.001	15
408			min	-586.404	3	-1.949	4	-22.69	3	-.017	2	-.084	3	-.005	4
409		15	max	1527.828	2	-.573	15	50.213	2	.009	3	.199	2	0	15
410			min	-586.56	3	-2.436	4	-22.69	3	-.017	2	-.091	3	-.004	4
411		16	max	1527.62	2	-.687	15	50.213	2	.009	3	.214	2	0	15
412			min	-586.716	3	-2.923	4	-22.69	3	-.017	2	-.097	3	-.003	4
413		17	max	1527.412	2	-.802	15	50.213	2	.009	3	.229	2	0	15
414			min	-586.872	3	-3.41	4	-22.69	3	-.017	2	-.104	3	-.002	4
415		18	max	1527.204	2	-.916	15	50.213	2	.009	3	.243	2	0	15
416			min	-587.028	3	-3.897	4	-22.69	3	-.017	2	-.11	3	-.001	4
417		19	max	1526.996	2	-1.031	15	50.213	2	.009	3	.258	2	0	1
418			min	-587.184	3	-4.384	4	-22.69	3	-.017	2	-.117	3	0	1
419	M6	1	max	4445.878	2	4.384	4	0	1	0	1	0	1	0	1
420			min	-2117.768	3	1.031	15	0	1	0	1	0	1	0	1
421		2	max	4445.67	2	3.897	4	0	1	0	1	0	1	0	15
422			min	-2117.924	3	.916	15	0	1	0	1	0	1	-.001	4
423		3	max	4445.462	2	3.41	4	0	1	0	1	0	1	0	15
424			min	-2118.08	3	.802	15	0	1	0	1	0	1	-.002	4
425		4	max	4445.254	2	2.923	4	0	1	0	1	0	1	0	15
426			min	-2118.236	3	.687	15	0	1	0	1	0	1	-.003	4
427		5	max	4445.046	2	2.436	4	0	1	0	1	0	1	0	15
428			min	-2118.392	3	.573	15	0	1	0	1	0	1	-.004	4
429		6	max	4444.837	2	1.949	4	0	1	0	1	0	1	-.001	15
430			min	-2118.548	3	.458	15	0	1	0	1	0	1	-.005	4
431		7	max	4444.629	2	1.461	4	0	1	0	1	0	1	-.001	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
432			min	-2118.704	3	.344	15	0	1	0	1	0	1	-.005	4
433		8	max	4444.421	2	.974	4	0	1	0	1	0	1	-.001	15
434			min	-2118.86	3	.229	15	0	1	0	1	0	1	-.005	4
435		9	max	4444.213	2	.487	4	0	1	0	1	0	1	-.001	15
436			min	-2119.016	3	.115	15	0	1	0	1	0	1	-.006	4
437		10	max	4444.005	2	0	1	0	1	0	1	0	1	-.001	15
438			min	-2119.172	3	0	1	0	1	0	1	0	1	-.006	4
439		11	max	4443.797	2	-.115	15	0	1	0	1	0	1	-.001	15
440			min	-2119.328	3	-.487	4	0	1	0	1	0	1	-.006	4
441		12	max	4443.589	2	-.229	15	0	1	0	1	0	1	-.001	15
442			min	-2119.484	3	-.974	4	0	1	0	1	0	1	-.005	4
443		13	max	4443.381	2	-.344	15	0	1	0	1	0	1	-.001	15
444			min	-2119.64	3	-1.461	4	0	1	0	1	0	1	-.005	4
445		14	max	4443.173	2	-.458	15	0	1	0	1	0	1	-.001	15
446			min	-2119.796	3	-1.949	4	0	1	0	1	0	1	-.005	4
447		15	max	4442.965	2	-.573	15	0	1	0	1	0	1	0	15
448			min	-2119.952	3	-2.436	4	0	1	0	1	0	1	-.004	4
449		16	max	4442.757	2	-.687	15	0	1	0	1	0	1	0	15
450			min	-2120.108	3	-2.923	4	0	1	0	1	0	1	-.003	4
451		17	max	4442.549	2	-.802	15	0	1	0	1	0	1	0	15
452			min	-2120.265	3	-3.41	4	0	1	0	1	0	1	-.002	4
453		18	max	4442.341	2	-.916	15	0	1	0	1	0	1	0	15
454			min	-2120.421	3	-3.897	4	0	1	0	1	0	1	-.001	4
455		19	max	4442.133	2	-1.031	15	0	1	0	1	0	1	0	1
456			min	-2120.577	3	-4.384	4	0	1	0	1	0	1	0	1
457	M9	1	max	1530.741	2	4.384	4	22.69	3	.017	2	.006	2	0	1
458			min	-584.375	3	1.031	15	-50.213	2	-.009	3	-.002	3	0	1
459		2	max	1530.533	2	3.897	4	22.69	3	.017	2	.005	3	0	15
460			min	-584.531	3	.916	15	-50.213	2	-.009	3	-.009	2	-.001	4
461		3	max	1530.325	2	3.41	4	22.69	3	.017	2	.011	3	0	15
462			min	-584.687	3	.802	15	-50.213	2	-.009	3	-.024	2	-.002	4
463		4	max	1530.117	2	2.923	4	22.69	3	.017	2	.018	3	0	15
464			min	-584.843	3	.687	15	-50.213	2	-.009	3	-.038	2	-.003	4
465		5	max	1529.909	2	2.436	4	22.69	3	.017	2	.024	3	0	15
466			min	-584.999	3	.573	15	-50.213	2	-.009	3	-.053	2	-.004	4
467		6	max	1529.701	2	1.949	4	22.69	3	.017	2	.031	3	-.001	15
468			min	-585.155	3	.458	15	-50.213	2	-.009	3	-.068	2	-.005	4
469		7	max	1529.493	2	1.461	4	22.69	3	.017	2	.038	3	-.001	15
470			min	-585.311	3	.344	15	-50.213	2	-.009	3	-.082	2	-.005	4
471		8	max	1529.285	2	.974	4	22.69	3	.017	2	.044	3	-.001	15
472			min	-585.467	3	.229	15	-50.213	2	-.009	3	-.097	2	-.005	4
473		9	max	1529.077	2	.487	4	22.69	3	.017	2	.051	3	-.001	15
474			min	-585.624	3	.115	15	-50.213	2	-.009	3	-.111	2	-.006	4
475		10	max	1528.869	2	0	1	22.69	3	.017	2	.057	3	-.001	15
476			min	-585.78	3	0	1	-50.213	2	-.009	3	-.126	2	-.006	4
477		11	max	1528.66	2	-.115	15	22.69	3	.017	2	.064	3	-.001	15
478			min	-585.936	3	-.487	4	-50.213	2	-.009	3	-.141	2	-.006	4
479		12	max	1528.452	2	-.229	15	22.69	3	.017	2	.071	3	-.001	15
480			min	-586.092	3	-.974	4	-50.213	2	-.009	3	-.155	2	-.005	4
481		13	max	1528.244	2	-.344	15	22.69	3	.017	2	.077	3	-.001	15
482			min	-586.248	3	-1.461	4	-50.213	2	-.009	3	-.17	2	-.005	4
483		14	max	1528.036	2	-.458	15	22.69	3	.017	2	.084	3	-.001	15
484			min	-586.404	3	-1.949	4	-50.213	2	-.009	3	-.185	2	-.005	4
485		15	max	1527.828	2	-.573	15	22.69	3	.017	2	.091	3	0	15
486			min	-586.56	3	-2.436	4	-50.213	2	-.009	3	-.199	2	-.004	4
487		16	max	1527.62	2	-.687	15	22.69	3	.017	2	.097	3	0	15
488			min	-586.716	3	-2.923	4	-50.213	2	-.009	3	-.214	2	-.003	4

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
489		17	max	1527.412	2	-.802	15	22.69	3	.017	2	.104	3	0	15
490			min	-586.872	3	-3.41	4	-50.213	2	-.009	3	-.229	2	-.002	4
491		18	max	1527.204	2	-.916	15	22.69	3	.017	2	.11	3	0	15
492			min	-587.028	3	-3.897	4	-50.213	2	-.009	3	-.243	2	-.001	4
493		19	max	1526.996	2	-1.031	15	22.69	3	.017	2	.117	3	0	1
494			min	-587.184	3	-4.384	4	-50.213	2	-.009	3	-.258	2	0	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M1	1	max	-.009	15	-.015	15	.017	1	7.213e-3	3	NC	3	NC	3
2			min	-.193	1	-.441	1	0	15	-1.849e-2	2	289.698	1	4044.01	1
3		2	max	-.009	15	-.013	15	.005	1	7.213e-3	3	NC	12	NC	2
4			min	-.193	1	-.364	1	0	15	-1.849e-2	2	347.325	1	6374.084	1
5		3	max	-.009	15	-.011	15	0	15	6.784e-3	3	8768.267	15	NC	1
6			min	-.193	1	-.287	1	-.005	1	-1.695e-2	2	433.689	1	NC	1
7		4	max	-.009	15	-.008	15	0	15	6.127e-3	3	NC	15	NC	1
8			min	-.193	1	-.214	1	-.01	1	-1.459e-2	2	569.778	1	NC	1
9		5	max	-.009	15	-.006	15	0	15	5.47e-3	3	NC	10	NC	1
10			min	-.193	1	-.147	1	-.01	1	-1.223e-2	2	792.401	1	NC	1
11		6	max	-.009	15	-.004	15	0	3	5.559e-3	3	NC	15	NC	1
12			min	-.193	1	-.103	3	-.008	1	-1.15e-2	2	1159.175	1	NC	1
13		7	max	-.009	15	-.003	15	.001	3	6.163e-3	3	NC	5	NC	1
14			min	-.192	1	-.097	3	-.004	2	-1.19e-2	2	1519.837	9	NC	1
15		8	max	-.009	15	.003	10	0	3	6.767e-3	3	NC	5	NC	2
16			min	-.192	1	-.084	3	0	2	-1.23e-2	2	1526.12	2	8442.481	1
17		9	max	-.009	15	.022	2	0	15	7.6e-3	3	NC	1	NC	2
18			min	-.192	1	-.067	3	0	3	-1.197e-2	2	1224.728	2	8448.366	1
19		10	max	-.009	15	.042	2	0	2	8.837e-3	3	NC	3	NC	2
20			min	-.192	1	-.047	3	0	3	-1.034e-2	2	1039.436	2	8203.686	1
21		11	max	-.009	15	.062	1	.001	3	1.007e-2	3	NC	5	NC	2
22			min	-.191	1	-.022	3	0	2	-8.709e-3	2	920.61	2	8499.608	1
23		12	max	-.009	15	.084	1	.004	3	8.439e-3	3	NC	4	NC	1
24			min	-.191	1	.003	15	-.003	2	-6.469e-3	2	843.481	2	NC	1
25		13	max	-.009	15	.101	1	.009	3	5.181e-3	3	NC	4	NC	1
26			min	-.19	1	.004	15	-.005	2	-3.883e-3	2	808.003	2	NC	1
27		14	max	-.009	15	.108	3	.008	3	2.095e-3	3	NC	4	NC	2
28			min	-.19	1	.005	15	-.002	2	-1.404e-3	2	827.255	2	7898.01	1
29		15	max	-.009	15	.191	3	.006	1	6.683e-3	3	NC	4	NC	2
30			min	-.19	1	.005	15	0	15	-3.631e-3	2	558.605	3	5960.245	1
31		16	max	-.009	15	.292	3	.008	1	1.127e-2	3	NC	4	NC	2
32			min	-.19	1	.005	10	0	15	-5.858e-3	2	393.636	3	5477.822	1
33		17	max	-.009	15	.403	3	.005	1	1.586e-2	3	NC	4	NC	2
34			min	-.19	1	-.017	10	0	15	-8.084e-3	2	296.276	3	6321.857	1
35		18	max	-.009	15	.52	3	0	15	1.885e-2	3	NC	4	NC	1
36			min	-.19	1	-.049	2	-.005	1	-9.536e-3	2	235.669	3	NC	1
37		19	max	-.009	15	.636	3	0	15	1.885e-2	3	NC	1	NC	1
38			min	-.19	1	-.087	2	-.016	1	-9.536e-3	2	195.684	3	NC	1
39	M4	1	max	-.013	15	.047	3	0	1	0	1	NC	3	NC	1
40			min	-.336	1	-.988	2	0	1	0	1	171.555	1	NC	1
41		2	max	-.013	15	-.011	12	0	1	0	1	5453.195	15	NC	1
42			min	-.336	1	-.79	2	0	1	0	1	218.562	1	NC	1
43		3	max	-.013	15	-.018	15	0	1	0	1	6656.162	15	NC	1
44			min	-.336	1	-.592	2	0	1	0	1	301.378	1	NC	1
45		4	max	-.013	15	-.014	15	0	1	0	1	8460.43	15	NC	1
46			min	-.336	1	-.415	1	0	1	0	1	472.811	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
47		5	max	-.013	15	-.01	15	0	1	0	1	NC	15	NC	1
48			min	-.336	1	-.274	1	0	1	0	1	640.66	3	NC	1
49		6	max	-.013	15	-.007	15	0	1	0	1	NC	15	NC	1
50			min	-.335	1	-.179	3	0	1	0	1	595.179	3	NC	1
51		7	max	-.013	15	-.004	15	0	1	0	1	NC	5	NC	1
52			min	-.335	1	-.172	3	0	1	0	1	525.19	2	NC	1
53		8	max	-.013	15	.002	10	0	1	0	1	NC	5	NC	1
54			min	-.334	1	-.15	3	0	1	0	1	443.42	2	NC	1
55		9	max	-.013	15	.032	2	0	1	0	1	NC	4	NC	1
56			min	-.333	1	-.12	3	0	1	0	1	394.655	2	NC	1
57		10	max	-.013	15	.069	2	0	1	0	1	NC	4	NC	1
58			min	-.332	1	-.085	3	0	1	0	1	355.862	2	NC	1
59		11	max	-.013	15	.109	1	0	1	0	1	NC	4	NC	1
60			min	-.331	1	-.044	3	0	1	0	1	326.167	2	NC	1
61		12	max	-.013	15	.151	1	0	1	0	1	NC	5	NC	1
62			min	-.33	1	.005	12	0	1	0	1	303.908	2	NC	1
63		13	max	-.013	15	.18	1	0	1	0	1	NC	5	NC	1
64			min	-.329	1	.007	15	0	1	0	1	292.966	2	NC	1
65		14	max	-.013	15	.193	3	0	1	0	1	NC	5	NC	1
66			min	-.328	1	.008	15	0	1	0	1	300.517	2	NC	1
67		15	max	-.013	15	.369	3	0	1	0	1	NC	5	NC	1
68			min	-.329	1	.007	15	0	1	0	1	339.904	2	NC	1
69		16	max	-.013	15	.589	3	0	1	0	1	NC	5	NC	1
70			min	-.329	1	-.012	10	0	1	0	1	247.326	3	NC	1
71		17	max	-.013	15	.836	3	0	1	0	1	NC	5	NC	1
72			min	-.329	1	-.095	2	0	1	0	1	169.773	3	NC	1
73		18	max	-.013	15	1.094	3	0	1	0	1	NC	4	NC	1
74			min	-.329	1	-.201	2	0	1	0	1	128.024	3	NC	1
75		19	max	-.013	15	1.35	3	0	1	0	1	NC	1	NC	1
76			min	-.329	1	-.307	2	0	1	0	1	102.81	3	NC	1
77	M7	1	max	-.009	15	-.015	15	0	15	1.849e-2	2	NC	3	NC	3
78			min	-.193	1	-.441	1	-.017	1	-7.213e-3	3	289.698	1	4044.01	1
79		2	max	-.009	15	-.013	15	0	15	1.849e-2	2	NC	12	NC	2
80			min	-.193	1	-.364	1	-.005	1	-7.213e-3	3	347.325	1	6374.084	1
81		3	max	-.009	15	-.011	15	.005	1	1.695e-2	2	8768.267	15	NC	1
82			min	-.193	1	-.287	1	0	15	-6.784e-3	3	433.689	1	NC	1
83		4	max	-.009	15	-.008	15	.01	1	1.459e-2	2	NC	15	NC	1
84			min	-.193	1	-.214	1	0	15	-6.127e-3	3	569.778	1	NC	1
85		5	max	-.009	15	-.006	15	.01	1	1.223e-2	2	NC	10	NC	1
86			min	-.193	1	-.147	1	0	15	-5.47e-3	3	792.401	1	NC	1
87		6	max	-.009	15	-.004	15	.008	1	1.15e-2	2	NC	15	NC	1
88			min	-.193	1	-.103	3	0	3	-5.559e-3	3	1159.175	1	NC	1
89		7	max	-.009	15	-.003	15	.004	2	1.19e-2	2	NC	5	NC	1
90			min	-.192	1	-.097	3	-.001	3	-6.163e-3	3	1519.837	9	NC	1
91		8	max	-.009	15	.003	10	0	2	1.23e-2	2	NC	5	NC	2
92			min	-.192	1	-.084	3	0	3	-6.767e-3	3	1526.12	2	8442.481	1
93		9	max	-.009	15	.022	2	0	3	1.197e-2	2	NC	1	NC	2
94			min	-.192	1	-.067	3	0	15	-7.6e-3	3	1224.728	2	8448.366	1
95		10	max	-.009	15	.042	2	0	3	1.034e-2	2	NC	3	NC	2
96			min	-.192	1	-.047	3	0	2	-8.837e-3	3	1039.436	2	8203.686	1
97		11	max	-.009	15	.062	1	0	2	8.709e-3	2	NC	5	NC	2
98			min	-.191	1	-.022	3	-.001	3	-1.007e-2	3	920.61	2	8499.608	1
99		12	max	-.009	15	.084	1	.003	2	6.469e-3	2	NC	4	NC	1
100			min	-.191	1	.003	15	-.004	3	-8.439e-3	3	843.481	2	NC	1
101		13	max	-.009	15	.101	1	.005	2	3.883e-3	2	NC	4	NC	1
102			min	-.19	1	.004	15	-.009	3	-5.181e-3	3	808.003	2	NC	1
103		14	max	-.009	15	.108	3	.002	2	1.404e-3	2	NC	4	NC	2

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
104			min	-.19	1	.005	15	-.008	3	-2.095e-3	3	827.255	2	7898.01	1
105		15	max	-.009	15	.191	3	0	15	3.631e-3	2	NC	4	NC	2
106			min	-.19	1	.005	15	-.006	1	-6.683e-3	3	558.605	3	5960.245	1
107		16	max	-.009	15	.292	3	0	15	5.858e-3	2	NC	4	NC	2
108			min	-.19	1	.005	10	-.008	1	-1.127e-2	3	393.636	3	5477.822	1
109		17	max	-.009	15	.403	3	0	15	8.084e-3	2	NC	4	NC	2
110			min	-.19	1	-.017	10	-.005	1	-1.586e-2	3	296.276	3	6321.857	1
111		18	max	-.009	15	.52	3	.005	1	9.536e-3	2	NC	4	NC	1
112			min	-.19	1	-.049	2	0	15	-1.885e-2	3	235.669	3	NC	1
113		19	max	-.009	15	.636	3	.016	1	9.536e-3	2	NC	1	NC	1
114			min	-.19	1	-.087	2	0	15	-1.885e-2	3	195.684	3	NC	1
115	M10	1	max	0	1	.479	3	.19	1	1.561e-2	3	NC	1	NC	1
116			min	0	15	-.035	2	.009	15	-5.219e-3	2	NC	1	NC	1
117		2	max	0	1	.685	3	.218	1	1.77e-2	3	NC	4	NC	2
118			min	0	15	-.138	2	.01	15	-6.224e-3	2	931.888	3	6917.149	1
119		3	max	0	1	.878	3	.258	1	1.98e-2	3	NC	5	NC	4
120			min	0	15	-.231	2	.011	15	-7.229e-3	2	481.063	3	2820.207	1
121		4	max	0	1	1.032	3	.299	1	2.19e-2	3	NC	5	NC	5
122			min	0	15	-.298	2	.013	15	-8.234e-3	2	347.524	3	1767.661	1
123		5	max	0	1	1.13	3	.331	1	2.4e-2	3	NC	5	NC	5
124			min	0	15	-.331	2	.014	15	-9.239e-3	2	295.226	3	1363.809	1
125		6	max	0	1	1.167	3	.35	1	2.609e-2	3	NC	5	NC	5
126			min	0	15	-.327	2	.015	15	-1.024e-2	2	279.091	3	1201.917	1
127		7	max	0	1	1.151	3	.355	1	2.819e-2	3	NC	5	NC	5
128			min	0	15	-.293	2	.015	15	-1.125e-2	2	285.93	3	1167.594	1
129		8	max	0	1	1.098	3	.348	1	3.029e-2	3	NC	4	NC	5
130			min	0	15	-.24	2	.014	15	-1.225e-2	2	310.579	3	1218.536	1
131		9	max	0	1	1.036	3	.336	1	3.238e-2	3	NC	4	NC	5
132			min	0	15	-.189	2	.014	15	-1.326e-2	2	345.155	3	1318.87	1
133		10	max	0	1	1.004	3	.329	1	3.448e-2	3	NC	4	NC	5
134			min	0	1	-.164	2	.013	15	-1.426e-2	2	365.771	3	1384.286	1
135		11	max	0	15	1.036	3	.336	1	3.238e-2	3	NC	4	NC	5
136			min	0	1	-.189	2	.014	15	-1.326e-2	2	345.155	3	1318.87	1
137		12	max	0	15	1.098	3	.348	1	3.029e-2	3	NC	4	NC	5
138			min	0	1	-.24	2	.014	15	-1.225e-2	2	310.579	3	1218.536	1
139		13	max	0	15	1.151	3	.355	1	2.819e-2	3	NC	5	NC	5
140			min	0	1	-.293	2	.015	15	-1.125e-2	2	285.93	3	1167.594	1
141		14	max	0	15	1.167	3	.35	1	2.609e-2	3	NC	5	NC	5
142			min	0	1	-.327	2	.015	15	-1.024e-2	2	279.091	3	1201.917	1
143		15	max	0	15	1.13	3	.331	1	2.4e-2	3	NC	5	NC	5
144			min	0	1	-.331	2	.014	15	-9.239e-3	2	295.226	3	1363.809	1
145		16	max	0	15	1.032	3	.299	1	2.19e-2	3	NC	5	NC	5
146			min	0	1	-.298	2	.013	15	-8.234e-3	2	347.524	3	1767.661	1
147		17	max	0	15	.878	3	.258	1	1.98e-2	3	NC	5	NC	4
148			min	0	1	-.231	2	.011	15	-7.229e-3	2	481.063	3	2820.207	1
149		18	max	0	15	.685	3	.218	1	1.77e-2	3	NC	4	NC	2
150			min	0	1	-.138	2	.01	15	-6.224e-3	2	931.888	3	6917.149	1
151		19	max	0	15	.479	3	.19	1	1.561e-2	3	NC	1	NC	1
152			min	0	1	-.035	2	.009	15	-5.219e-3	2	NC	1	NC	1
153	M11	1	max	.001	2	.07	1	.191	1	4.03e-3	3	NC	1	NC	1
154			min	-.002	3	-.011	3	.009	15	1.445e-4	15	NC	1	NC	1
155		2	max	.001	2	.106	3	.211	1	4.318e-3	3	NC	4	NC	2
156			min	-.002	3	-.022	2	.009	15	1.542e-4	15	1637.975	3	9716.42	1
157		3	max	.001	2	.212	3	.247	1	4.607e-3	3	NC	5	NC	3
158			min	-.001	3	-.092	2	.011	15	1.639e-4	15	859.817	3	3433.167	1
159		4	max	0	2	.283	3	.286	1	4.895e-3	3	NC	5	NC	5
160			min	-.001	3	-.133	2	.013	15	1.736e-4	15	653.531	3	2013.213	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
161		5	max	0	2	.304	3	.32	1	5.184e-3	3	NC	5	NC	5
162			min	-.001	3	-.138	2	.014	15	1.834e-4	15	609.132	3	1491.461	1
163		6	max	0	2	.274	3	.341	1	5.472e-3	3	NC	5	NC	5
164			min	0	3	-.108	2	.015	15	1.931e-4	15	673.523	3	1276.485	1
165		7	max	0	2	.201	3	.35	1	5.761e-3	3	NC	4	NC	5
166			min	0	3	-.051	2	.015	15	2.028e-4	15	906.066	3	1210.806	1
167		8	max	0	2	.104	3	.346	1	6.049e-3	3	NC	4	NC	5
168			min	0	3	.002	15	.014	15	2.125e-4	15	1666.266	3	1237.648	1
169		9	max	0	2	.099	1	.337	1	6.338e-3	3	NC	4	NC	5
170			min	0	3	.004	15	.014	15	2.222e-4	15	6646.129	1	1317.049	1
171		10	max	0	1	.124	1	.331	1	6.626e-3	3	NC	3	NC	5
172			min	0	1	-.027	3	.013	15	2.32e-4	15	3549.558	1	1371.807	1
173		11	max	0	3	.099	1	.337	1	6.338e-3	3	NC	4	NC	5
174			min	0	2	.004	15	.014	15	2.222e-4	15	6646.129	1	1317.049	1
175		12	max	0	3	.104	3	.346	1	6.049e-3	3	NC	4	NC	5
176			min	0	2	.002	15	.014	15	2.125e-4	15	1666.266	3	1237.648	1
177		13	max	0	3	.201	3	.35	1	5.761e-3	3	NC	4	NC	5
178			min	0	2	-.051	2	.015	15	2.028e-4	15	906.066	3	1210.806	1
179		14	max	0	3	.274	3	.341	1	5.472e-3	3	NC	5	NC	5
180			min	0	2	-.108	2	.015	15	1.931e-4	15	673.523	3	1276.485	1
181		15	max	.001	3	.304	3	.32	1	5.184e-3	3	NC	5	NC	5
182			min	0	2	-.138	2	.014	15	1.834e-4	15	609.132	3	1491.461	1
183		16	max	.001	3	.283	3	.286	1	4.895e-3	3	NC	5	NC	5
184			min	0	2	-.133	2	.013	15	1.736e-4	15	653.531	3	2013.213	1
185		17	max	.001	3	.212	3	.247	1	4.607e-3	3	NC	5	NC	3
186			min	-.001	2	-.092	2	.011	15	1.639e-4	15	859.817	3	3433.167	1
187		18	max	.002	3	.106	3	.211	1	4.318e-3	3	NC	4	NC	2
188			min	-.001	2	-.022	2	.009	15	1.542e-4	15	1637.975	3	9716.42	1
189		19	max	.002	3	.07	1	.191	1	4.03e-3	3	NC	1	NC	1
190			min	-.001	2	-.011	3	.009	15	1.445e-4	15	NC	1	NC	1
191	M12	1	max	0	2	.014	2	.192	1	3.902e-3	1	NC	1	NC	1
192			min	0	9	-.074	3	.009	15	1.708e-4	15	NC	1	NC	1
193		2	max	0	2	-.001	12	.209	1	4.202e-3	1	NC	4	NC	1
194			min	0	9	-.119	2	.009	15	1.813e-4	15	1442.1	2	NC	1
195		3	max	0	2	.053	3	.243	1	4.503e-3	1	NC	5	NC	4
196			min	0	9	-.232	2	.011	15	1.918e-4	15	780.232	2	3750.798	1
197		4	max	0	2	.082	3	.282	1	4.804e-3	1	NC	5	NC	5
198			min	0	9	-.303	2	.012	15	2.024e-4	15	604.574	2	2125.884	1
199		5	max	0	2	.082	3	.316	1	5.104e-3	1	NC	5	NC	5
200			min	0	9	-.322	2	.014	15	2.129e-4	15	570.102	2	1544.708	1
201		6	max	0	2	.054	3	.339	1	5.405e-3	1	NC	5	NC	5
202			min	0	9	-.289	2	.014	15	2.234e-4	15	633.189	2	1304.297	1
203		7	max	0	2	.004	3	.349	1	5.705e-3	1	NC	5	NC	5
204			min	0	9	-.212	2	.015	15	2.339e-4	15	846.39	2	1223.828	1
205		8	max	0	2	-.003	15	.347	1	6.006e-3	1	NC	3	NC	5
206			min	0	9	-.114	2	.014	15	2.445e-4	15	1500.465	2	1239.245	1
207		9	max	0	2	-.001	15	.339	1	6.307e-3	1	NC	4	NC	5
208			min	0	9	-.108	3	.014	15	2.55e-4	15	5149.527	2	1308.684	1
209		10	max	0	1	.019	2	.333	1	6.607e-3	1	NC	1	NC	5
210			min	0	1	-.131	3	.013	15	2.655e-4	15	3350.244	3	1358.364	1
211		11	max	0	9	-.001	15	.339	1	6.307e-3	1	NC	4	NC	5
212			min	0	2	-.108	3	.014	15	2.55e-4	15	5149.527	2	1308.684	1
213		12	max	0	9	-.003	15	.347	1	6.006e-3	1	NC	3	NC	5
214			min	0	2	-.114	2	.014	15	2.445e-4	15	1500.465	2	1239.245	1
215		13	max	0	9	.004	3	.349	1	5.705e-3	1	NC	5	NC	5
216			min	0	2	-.212	2	.015	15	2.339e-4	15	846.39	2	1223.828	1
217		14	max	0	9	.054	3	.339	1	5.405e-3	1	NC	5	NC	5

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
218			min	0	2	-.289	2	.014	15	2.234e-4	15	633.189	2	1304.297	1
219		15	max	0	9	.082	3	.316	1	5.104e-3	1	NC	5	NC	5
220			min	0	2	-.322	2	.014	15	2.129e-4	15	570.102	2	1544.708	1
221		16	max	0	9	.082	3	.282	1	4.804e-3	1	NC	5	NC	5
222			min	0	2	-.303	2	.012	15	2.024e-4	15	604.574	2	2125.884	1
223		17	max	0	9	.053	3	.243	1	4.503e-3	1	NC	5	NC	4
224			min	0	2	-.232	2	.011	15	1.918e-4	15	780.232	2	3750.798	1
225		18	max	0	9	-.001	12	.209	1	4.202e-3	1	NC	4	NC	1
226			min	0	2	-.119	2	.009	15	1.813e-4	15	1442.1	2	NC	1
227		19	max	0	9	.014	2	.192	1	3.902e-3	1	NC	1	NC	1
228			min	0	2	-.074	3	.009	15	1.708e-4	15	NC	1	NC	1
229	M13	1	max	0	15	-.012	15	.193	1	1.128e-2	2	NC	1	NC	1
230			min	0	1	-.338	1	.009	15	-2.049e-3	3	NC	1	NC	1
231		2	max	0	15	.006	3	.222	1	1.298e-2	2	NC	5	NC	2
232			min	0	1	-.519	2	.01	15	-2.689e-3	3	974.445	2	6698.307	1
233		3	max	0	15	.07	3	.263	1	1.468e-2	2	NC	5	NC	4
234			min	0	1	-.695	2	.012	15	-3.329e-3	3	513.854	2	2751.232	1
235		4	max	0	15	.112	3	.304	1	1.638e-2	2	NC	5	NC	5
236			min	0	1	-.828	2	.013	15	-3.969e-3	3	378.963	2	1729.448	1
237		5	max	0	15	.127	3	.337	1	1.808e-2	2	NC	5	NC	5
238			min	0	1	-.905	2	.015	15	-4.609e-3	3	329.199	2	1335.481	1
239		6	max	0	15	.114	3	.356	1	1.978e-2	2	NC	5	NC	5
240			min	0	1	-.923	2	.015	15	-5.249e-3	3	319.465	2	1176.394	1
241		7	max	0	15	.079	3	.361	1	2.148e-2	2	NC	5	NC	5
242			min	0	1	-.89	2	.015	15	-5.889e-3	3	338.06	2	1140.959	1
243		8	max	0	15	.032	3	.355	1	2.318e-2	2	NC	5	NC	5
244			min	0	1	-.824	2	.015	15	-6.529e-3	3	382.138	2	1187.596	1
245		9	max	0	15	-.011	12	.343	1	2.488e-2	2	NC	5	NC	5
246			min	0	1	-.755	2	.014	15	-7.169e-3	3	443.169	2	1281.333	1
247		10	max	0	1	-.021	15	.336	1	2.658e-2	2	NC	5	NC	5
248			min	0	1	-.721	2	.013	15	-7.809e-3	3	480.566	2	1342.491	1
249		11	max	0	1	-.011	12	.343	1	2.488e-2	2	NC	5	NC	5
250			min	0	15	-.755	2	.014	15	-7.169e-3	3	443.169	2	1281.333	1
251		12	max	0	1	.032	3	.355	1	2.318e-2	2	NC	5	NC	5
252			min	0	15	-.824	2	.015	15	-6.529e-3	3	382.138	2	1187.596	1
253		13	max	0	1	.079	3	.361	1	2.148e-2	2	NC	5	NC	5
254			min	0	15	-.89	2	.015	15	-5.889e-3	3	338.06	2	1140.959	1
255		14	max	0	1	.114	3	.356	1	1.978e-2	2	NC	5	NC	5
256			min	0	15	-.923	2	.015	15	-5.249e-3	3	319.465	2	1176.394	1
257		15	max	0	1	.127	3	.337	1	1.808e-2	2	NC	5	NC	5
258			min	0	15	-.905	2	.015	15	-4.609e-3	3	329.199	2	1335.481	1
259		16	max	0	1	.112	3	.304	1	1.638e-2	2	NC	5	NC	5
260			min	0	15	-.828	2	.013	15	-3.969e-3	3	378.963	2	1729.448	1
261		17	max	0	1	.07	3	.263	1	1.468e-2	2	NC	5	NC	4
262			min	0	15	-.695	2	.012	15	-3.329e-3	3	513.854	2	2751.232	1
263		18	max	0	1	.006	3	.222	1	1.298e-2	2	NC	5	NC	2
264			min	0	15	-.519	2	.01	15	-2.689e-3	3	974.445	2	6698.307	1
265		19	max	0	1	-.012	15	.193	1	1.128e-2	2	NC	1	NC	1
266			min	0	15	-.338	1	.009	15	-2.049e-3	3	NC	1	NC	1
267	M2	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
268			min	0	1	0	1	0	1	0	1	NC	1	NC	1
269		2	max	0	3	0	15	0	3	3.681e-3	2	NC	1	NC	1
270			min	0	2	-.001	3	0	2	-1.699e-3	3	NC	1	NC	1
271		3	max	0	3	0	15	0	3	4.78e-3	2	NC	1	NC	1
272			min	0	2	-.004	3	0	2	-2.17e-3	3	NC	1	NC	1
273		4	max	0	3	0	15	.002	3	4.398e-3	2	NC	2	NC	1
274			min	0	2	-.009	3	-.001	2	-1.939e-3	3	7670.743	3	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
275		5	max	0	3	0	15	.003	3	4.016e-3	2	NC	4	NC	1
276			min	0	2	-.015	3	-.002	2	-1.707e-3	3	4480.475	3	NC	1
277		6	max	0	3	-.001	15	.004	3	3.634e-3	2	NC	4	NC	1
278			min	0	2	-.023	3	-.003	2	-1.475e-3	3	2956.701	3	NC	1
279		7	max	0	3	-.001	15	.005	3	3.252e-3	2	NC	5	NC	1
280			min	0	2	-.032	1	-.003	2	-1.243e-3	3	2098.668	1	8742.379	3
281		8	max	0	3	-.002	15	.006	3	2.87e-3	2	NC	5	NC	1
282			min	0	2	-.043	1	-.004	2	-1.011e-3	3	1570.987	1	7273.669	3
283		9	max	0	3	-.002	15	.007	3	2.488e-3	2	NC	5	NC	1
284			min	0	2	-.055	1	-.005	2	-7.79e-4	3	1227.085	1	6305.258	3
285		10	max	0	3	-.003	15	.008	3	2.106e-3	2	NC	5	NC	1
286			min	0	2	-.068	1	-.006	2	-5.47e-4	3	989.909	1	5664.959	3
287		11	max	0	3	-.004	15	.008	3	1.724e-3	2	NC	5	NC	1
288			min	0	2	-.082	1	-.006	2	-3.151e-4	3	819.33	1	5260.373	3
289		12	max	0	3	-.004	15	.008	3	1.342e-3	2	NC	15	NC	1
290			min	0	2	-.097	1	-.006	2	-8.322e-5	3	692.41	1	5046.767	3
291		13	max	.001	3	-.005	15	.008	3	9.595e-4	2	NC	15	NC	1
292			min	-.001	2	-.113	1	-.006	1	1.381e-6	15	595.33	1	5013.939	3
293		14	max	.001	3	-.006	15	.007	3	5.775e-4	2	NC	15	NC	1
294			min	-.001	2	-.13	1	-.006	1	-8.252e-5	9	519.411	1	5184.483	3
295		15	max	.001	3	-.007	15	.005	3	6.125e-4	3	NC	15	NC	1
296			min	-.001	2	-.147	1	-.006	1	-1.844e-4	9	458.88	1	5644.099	3
297		16	max	.001	3	-.007	15	.003	3	8.444e-4	3	9079.743	15	NC	1
298			min	-.001	2	-.164	1	-.005	1	-4.373e-4	1	409.859	1	6612.072	3
299		17	max	.001	3	-.008	15	0	3	1.076e-3	3	8190.453	15	NC	1
300			min	-.001	2	-.182	1	-.004	1	-7.507e-4	1	369.612	1	8783.835	3
301		18	max	.001	3	-.009	15	0	10	1.308e-3	3	7451.445	15	NC	1
302			min	-.001	2	-.2	1	-.004	3	-1.064e-3	1	336.182	1	NC	1
303		19	max	.002	3	-.01	15	.002	2	1.54e-3	3	6831.26	15	NC	1
304			min	-.002	2	-.218	1	-.008	3	-1.378e-3	1	308.139	1	NC	1
305	M5	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
306			min	0	1	0	1	0	1	0	1	NC	1	NC	1
307		2	max	0	3	0	15	0	1	0	1	NC	1	NC	1
308			min	0	2	-.002	3	0	1	0	1	NC	1	NC	1
309		3	max	0	3	0	15	0	1	0	1	NC	1	NC	1
310			min	0	2	-.008	3	0	1	0	1	8775.658	3	NC	1
311		4	max	0	3	0	15	0	1	0	1	NC	4	NC	1
312			min	0	2	-.016	3	0	1	0	1	4221.056	3	NC	1
313		5	max	.001	3	-.001	15	0	1	0	1	NC	4	NC	1
314			min	-.001	2	-.027	3	0	1	0	1	2489.636	3	NC	1
315		6	max	.001	3	-.002	15	0	1	0	1	NC	5	NC	1
316			min	-.001	2	-.041	3	0	1	0	1	1652.096	3	NC	1
317		7	max	.002	3	-.002	15	0	1	0	1	NC	5	NC	1
318			min	-.002	2	-.057	3	0	1	0	1	1183.533	3	NC	1
319		8	max	.002	3	-.003	15	0	1	0	1	NC	5	NC	1
320			min	-.002	2	-.075	3	0	1	0	1	894.385	3	NC	1
321		9	max	.002	3	-.004	15	0	1	0	1	NC	5	NC	1
322			min	-.002	2	-.096	3	0	1	0	1	703.418	3	NC	1
323		10	max	.002	3	-.005	15	0	1	0	1	NC	15	NC	1
324			min	-.002	2	-.118	3	0	1	0	1	570.422	3	NC	1
325		11	max	.003	3	-.006	15	0	1	0	1	NC	15	NC	1
326			min	-.002	2	-.142	3	0	1	0	1	474.049	3	NC	1
327		12	max	.003	3	-.007	15	0	1	0	1	9922.181	15	NC	1
328			min	-.003	2	-.167	3	0	1	0	1	401.915	3	NC	1
329		13	max	.003	3	-.008	15	0	1	0	1	8532.641	15	NC	1
330			min	-.003	2	-.195	1	0	1	0	1	345.914	1	NC	1
331		14	max	.003	3	-.009	15	0	1	0	1	7445.668	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
332			min	-.003	2	-.223	1	0	1	0	1	301.592	1	NC	1
333		15	max	.004	3	-.01	15	0	1	0	1	6578.812	15	NC	1
334			min	-.003	2	-.253	1	0	1	0	1	266.292	1	NC	1
335		16	max	.004	3	-.011	15	0	1	0	1	5876.654	15	NC	1
336			min	-.004	2	-.283	1	0	1	0	1	237.731	1	NC	1
337		17	max	.004	3	-.013	15	0	1	0	1	5300.061	15	NC	1
338			min	-.004	2	-.314	1	0	1	0	1	214.299	1	NC	1
339		18	max	.004	3	-.014	15	0	1	0	1	4821.061	15	NC	1
340			min	-.004	2	-.345	1	0	1	0	1	194.849	1	NC	1
341		19	max	.005	3	-.015	15	0	1	0	1	4419.192	15	NC	1
342			min	-.004	2	-.377	1	0	1	0	1	178.544	1	NC	1
343	M8	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
344			min	0	1	0	1	0	1	0	1	NC	1	NC	1
345		2	max	0	3	0	15	0	2	1.699e-3	3	NC	1	NC	1
346			min	0	2	-.001	3	0	3	-3.681e-3	2	NC	1	NC	1
347		3	max	0	3	0	15	0	2	2.17e-3	3	NC	1	NC	1
348			min	0	2	-.004	3	0	3	-4.78e-3	2	NC	1	NC	1
349		4	max	0	3	0	15	.001	2	1.939e-3	3	NC	2	NC	1
350			min	0	2	-.009	3	-.002	3	-4.398e-3	2	7670.743	3	NC	1
351		5	max	0	3	0	15	.002	2	1.707e-3	3	NC	4	NC	1
352			min	0	2	-.015	3	-.003	3	-4.016e-3	2	4480.475	3	NC	1
353		6	max	0	3	-.001	15	.003	2	1.475e-3	3	NC	4	NC	1
354			min	0	2	-.023	3	-.004	3	-3.634e-3	2	2956.701	3	NC	1
355		7	max	0	3	-.001	15	.003	2	1.243e-3	3	NC	5	NC	1
356			min	0	2	-.032	1	-.005	3	-3.252e-3	2	2098.668	1	8742.379	3
357		8	max	0	3	-.002	15	.004	2	1.011e-3	3	NC	5	NC	1
358			min	0	2	-.043	1	-.006	3	-2.87e-3	2	1570.987	1	7273.669	3
359		9	max	0	3	-.002	15	.005	2	7.79e-4	3	NC	5	NC	1
360			min	0	2	-.055	1	-.007	3	-2.488e-3	2	1227.085	1	6305.258	3
361		10	max	0	3	-.003	15	.006	2	5.47e-4	3	NC	5	NC	1
362			min	0	2	-.068	1	-.008	3	-2.106e-3	2	989.909	1	5664.959	3
363		11	max	0	3	-.004	15	.006	2	3.151e-4	3	NC	5	NC	1
364			min	0	2	-.082	1	-.008	3	-1.724e-3	2	819.33	1	5260.373	3
365		12	max	0	3	-.004	15	.006	2	8.322e-5	3	NC	15	NC	1
366			min	0	2	-.097	1	-.008	3	-1.342e-3	2	692.41	1	5046.767	3
367		13	max	.001	3	-.005	15	.006	1	-1.381e-6	15	NC	15	NC	1
368			min	-.001	2	-.113	1	-.008	3	-9.595e-4	2	595.33	1	5013.939	3
369		14	max	.001	3	-.006	15	.006	1	8.252e-5	9	NC	15	NC	1
370			min	-.001	2	-.13	1	-.007	3	-5.775e-4	2	519.411	1	5184.483	3
371		15	max	.001	3	-.007	15	.006	1	1.844e-4	9	NC	15	NC	1
372			min	-.001	2	-.147	1	-.005	3	-6.125e-4	3	458.88	1	5644.099	3
373		16	max	.001	3	-.007	15	.005	1	4.373e-4	1	9079.743	15	NC	1
374			min	-.001	2	-.164	1	-.003	3	-8.444e-4	3	409.859	1	6612.072	3
375		17	max	.001	3	-.008	15	.004	1	7.507e-4	1	8190.453	15	NC	1
376			min	-.001	2	-.182	1	0	3	-1.076e-3	3	369.612	1	8783.835	3
377		18	max	.001	3	-.009	15	.004	3	1.064e-3	1	7451.445	15	NC	1
378			min	-.001	2	-.2	1	0	10	-1.308e-3	3	336.182	1	NC	1
379		19	max	.002	3	-.01	15	.008	3	1.378e-3	1	6831.26	15	NC	1
380			min	-.002	2	-.218	1	-.002	2	-1.54e-3	3	308.139	1	NC	1
381	M3	1	max	.002	3	0	15	0	3	2.334e-3	2	NC	1	NC	1
382			min	0	15	0	1	0	2	-9.971e-4	3	NC	1	NC	1
383		2	max	.002	3	0	15	.008	3	2.531e-3	2	NC	1	NC	4
384			min	0	10	-.014	1	-.016	2	-1.104e-3	3	NC	1	3929.593	2
385		3	max	.002	3	-.002	15	.015	3	2.729e-3	2	NC	1	NC	4
386			min	0	2	-.027	1	-.031	2	-1.211e-3	3	NC	1	1976.693	2
387		4	max	.002	3	-.002	15	.022	3	2.927e-3	2	NC	1	NC	4
388			min	0	2	-.041	1	-.046	2	-1.319e-3	3	NC	1	1334.741	2

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
389		5	max	.003	3	-.003	15	.029	3	3.124e-3	2	NC	1	NC	5
390			min	-.001	2	-.054	1	-.06	2	-1.426e-3	3	NC	1	1021.052	2
391		6	max	.003	3	-.004	15	.035	3	3.322e-3	2	NC	1	NC	5
392			min	-.002	2	-.067	1	-.073	2	-1.533e-3	3	NC	1	839.367	2
393		7	max	.003	3	-.004	15	.04	3	3.519e-3	2	NC	1	NC	5
394			min	-.002	2	-.08	1	-.085	2	-1.64e-3	3	NC	1	724.561	2
395		8	max	.003	3	-.005	15	.045	3	3.717e-3	2	NC	1	NC	5
396			min	-.003	2	-.093	1	-.095	2	-1.747e-3	3	NC	1	649.073	2
397		9	max	.003	3	-.006	15	.049	3	3.915e-3	2	NC	1	NC	5
398			min	-.003	2	-.106	1	-.102	2	-1.854e-3	3	NC	1	599.566	2
399		10	max	.004	3	-.006	15	.051	3	4.112e-3	2	NC	1	NC	5
400			min	-.004	2	-.118	1	-.107	2	-1.962e-3	3	NC	1	569.233	2
401		11	max	.004	3	-.007	15	.052	3	4.31e-3	2	NC	1	NC	5
402			min	-.004	2	-.131	1	-.11	2	-2.069e-3	3	NC	1	554.862	2
403		12	max	.004	3	-.007	15	.052	3	4.508e-3	2	NC	1	NC	5
404			min	-.005	2	-.143	1	-.109	2	-2.176e-3	3	NC	1	555.761	2
405		13	max	.004	3	-.008	15	.051	3	4.705e-3	2	NC	1	NC	5
406			min	-.005	2	-.156	1	-.105	2	-2.283e-3	3	NC	1	573.735	2
407		14	max	.004	3	-.008	15	.047	3	4.903e-3	2	NC	1	NC	5
408			min	-.006	2	-.168	1	-.098	2	-2.39e-3	3	NC	1	614.212	2
409		15	max	.005	3	-.009	15	.042	3	5.101e-3	2	NC	1	NC	5
410			min	-.006	2	-.181	1	-.086	2	-2.497e-3	3	NC	1	689.796	2
411		16	max	.005	3	-.009	15	.035	3	5.298e-3	2	NC	1	NC	5
412			min	-.007	2	-.193	1	-.07	2	-2.605e-3	3	NC	1	831.438	2
413		17	max	.005	3	-.009	15	.026	3	5.496e-3	2	NC	1	NC	4
414			min	-.008	2	-.205	1	-.049	2	-2.712e-3	3	NC	1	1133.589	2
415		18	max	.005	3	-.01	15	.015	3	5.693e-3	2	NC	1	NC	4
416			min	-.008	2	-.217	1	-.024	2	-2.819e-3	3	NC	1	2070.728	2
417		19	max	.005	3	-.01	15	.009	1	5.891e-3	2	NC	1	NC	1
418			min	-.009	2	-.229	1	0	15	-2.926e-3	3	NC	1	NC	1
419	M6	1	max	.004	3	0	15	0	1	0	1	NC	1	NC	1
420			min	0	15	-.002	1	0	1	0	1	NC	1	NC	1
421		2	max	.004	3	-.001	15	0	1	0	1	NC	1	NC	1
422			min	0	2	-.024	1	0	1	0	1	NC	1	NC	1
423		3	max	.005	3	-.002	15	0	1	0	1	NC	1	NC	1
424			min	-.002	2	-.047	1	0	1	0	1	NC	1	NC	1
425		4	max	.006	3	-.003	15	0	1	0	1	NC	1	NC	1
426			min	-.004	2	-.07	1	0	1	0	1	NC	1	NC	1
427		5	max	.007	3	-.004	15	0	1	0	1	NC	1	NC	1
428			min	-.005	2	-.093	1	0	1	0	1	NC	1	NC	1
429		6	max	.007	3	-.005	15	0	1	0	1	NC	1	NC	1
430			min	-.007	2	-.116	1	0	1	0	1	NC	1	NC	1
431		7	max	.008	3	-.006	15	0	1	0	1	NC	1	NC	1
432			min	-.008	2	-.138	1	0	1	0	1	NC	1	NC	1
433		8	max	.009	3	-.007	15	0	1	0	1	NC	1	NC	1
434			min	-.01	2	-.161	1	0	1	0	1	NC	1	NC	1
435		9	max	.009	3	-.008	15	0	1	0	1	NC	1	NC	1
436			min	-.011	2	-.184	1	0	1	0	1	NC	1	NC	1
437		10	max	.01	3	-.009	15	0	1	0	1	NC	1	NC	1
438			min	-.013	2	-.206	1	0	1	0	1	NC	1	NC	1
439		11	max	.011	3	-.01	15	0	1	0	1	NC	1	NC	1
440			min	-.014	2	-.228	1	0	1	0	1	NC	1	NC	1
441		12	max	.012	3	-.011	15	0	1	0	1	NC	1	NC	1
442			min	-.016	2	-.25	1	0	1	0	1	NC	1	NC	1
443		13	max	.012	3	-.012	15	0	1	0	1	NC	1	NC	1
444			min	-.017	2	-.273	1	0	1	0	1	NC	1	NC	1
445		14	max	.013	3	-.012	15	0	1	0	1	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
446			min	-.019	2	-.295	1	0	1	0	1	NC	1	NC	1
447		15	max	.014	3	-.013	15	0	1	0	1	NC	1	NC	1
448			min	-.02	2	-.317	1	0	1	0	1	NC	1	NC	1
449		16	max	.014	3	-.014	15	0	1	0	1	NC	1	NC	1
450			min	-.022	2	-.338	1	0	1	0	1	NC	1	NC	1
451		17	max	.015	3	-.015	15	0	1	0	1	NC	1	NC	1
452			min	-.023	2	-.36	1	0	1	0	1	NC	1	NC	1
453		18	max	.016	3	-.015	15	0	1	0	1	NC	1	NC	1
454			min	-.025	2	-.382	1	0	1	0	1	NC	1	NC	1
455		19	max	.017	3	-.016	15	0	1	0	1	NC	1	NC	1
456			min	-.026	2	-.404	1	0	1	0	1	NC	1	NC	1
457	M9	1	max	.002	3	0	15	0	2	9.971e-4	3	NC	1	NC	1
458			min	0	15	0	1	0	3	-2.334e-3	2	NC	1	NC	1
459		2	max	.002	3	0	15	.016	2	1.104e-3	3	NC	1	NC	4
460			min	0	10	-.014	1	-.008	3	-2.531e-3	2	NC	1	3929.593	2
461		3	max	.002	3	-.002	15	.031	2	1.211e-3	3	NC	1	NC	4
462			min	0	2	-.027	1	-.015	3	-2.729e-3	2	NC	1	1976.693	2
463		4	max	.002	3	-.002	15	.046	2	1.319e-3	3	NC	1	NC	4
464			min	0	2	-.041	1	-.022	3	-2.927e-3	2	NC	1	1334.741	2
465		5	max	.003	3	-.003	15	.06	2	1.426e-3	3	NC	1	NC	5
466			min	-.001	2	-.054	1	-.029	3	-3.124e-3	2	NC	1	1021.052	2
467		6	max	.003	3	-.004	15	.073	2	1.533e-3	3	NC	1	NC	5
468			min	-.002	2	-.067	1	-.035	3	-3.322e-3	2	NC	1	839.367	2
469		7	max	.003	3	-.004	15	.085	2	1.64e-3	3	NC	1	NC	5
470			min	-.002	2	-.08	1	-.04	3	-3.519e-3	2	NC	1	724.561	2
471		8	max	.003	3	-.005	15	.095	2	1.747e-3	3	NC	1	NC	5
472			min	-.003	2	-.093	1	-.045	3	-3.717e-3	2	NC	1	649.073	2
473		9	max	.003	3	-.006	15	.102	2	1.854e-3	3	NC	1	NC	5
474			min	-.003	2	-.106	1	-.049	3	-3.915e-3	2	NC	1	599.566	2
475		10	max	.004	3	-.006	15	.107	2	1.962e-3	3	NC	1	NC	5
476			min	-.004	2	-.118	1	-.051	3	-4.112e-3	2	NC	1	569.233	2
477		11	max	.004	3	-.007	15	.11	2	2.069e-3	3	NC	1	NC	5
478			min	-.004	2	-.131	1	-.052	3	-4.31e-3	2	NC	1	554.862	2
479		12	max	.004	3	-.007	15	.109	2	2.176e-3	3	NC	1	NC	5
480			min	-.005	2	-.143	1	-.052	3	-4.508e-3	2	NC	1	555.761	2
481		13	max	.004	3	-.008	15	.105	2	2.283e-3	3	NC	1	NC	5
482			min	-.005	2	-.156	1	-.051	3	-4.705e-3	2	NC	1	573.735	2
483		14	max	.004	3	-.008	15	.098	2	2.39e-3	3	NC	1	NC	5
484			min	-.006	2	-.168	1	-.047	3	-4.903e-3	2	NC	1	614.212	2
485		15	max	.005	3	-.009	15	.086	2	2.497e-3	3	NC	1	NC	5
486			min	-.006	2	-.181	1	-.042	3	-5.101e-3	2	NC	1	689.796	2
487		16	max	.005	3	-.009	15	.07	2	2.605e-3	3	NC	1	NC	5
488			min	-.007	2	-.193	1	-.035	3	-5.298e-3	2	NC	1	831.438	2
489		17	max	.005	3	-.009	15	.049	2	2.712e-3	3	NC	1	NC	4
490			min	-.008	2	-.205	1	-.026	3	-5.496e-3	2	NC	1	1133.589	2
491		18	max	.005	3	-.01	15	.024	2	2.819e-3	3	NC	1	NC	4
492			min	-.008	2	-.217	1	-.015	3	-5.693e-3	2	NC	1	2070.728	2
493		19	max	.005	3	-.01	15	0	15	2.926e-3	3	NC	1	NC	1
494			min	-.009	2	-.229	1	-.009	1	-5.891e-3	2	NC	1	NC	1