

Schletter, Inc.		30° Tilt w/ Seismic Design
HCV	Standard PVMax Racking System	
	Representative Calculations - ASCE 7-10	

1. INTRODUCTION

1.1 Project Description

The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. PVMax ground mount system.

1.2 Construction

Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to aluminum struts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

	Maximum		Minimum	
Height =	2000	mm	1900	mm
Width =	1050	mm	970	mm
Dead Load =	3.00	psf	1.75	psf

Modules Per Row =	2
Module Tilt =	30°
Maximum Height Above Grade =	3 ft

1.3 Technical Codes

- ASCE 7-10 - Chapter 26-31, Wind Loads
- ASCE 7-10 - Chapter 7, Snow Loads
- ASCE 7-10 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2012, 2015
- Aluminum Design Manual, Eighth Edition, 2005



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

2. LOAD ACTIONS

2.1 Permanent Loads

g_{MAX} =	3.00	psf	*Self-weight of the PV modules.*
g_{MIN} =	1.75	psf	

2.2 Snow Loads

Ground Snow Load, P_g =	30.00	psf	
Sloped Roof Snow Load, P_s =	16.49	psf	*(ASCE 7-10, Eq. 7.4-1)*
I_s =	1.00		
C_s =	0.73		
C_e =	0.90		
C_t =	1.20		

2.3 Wind Loads

Design Wind Speed, V =	110	mph	Exposure Category = C
Height <	15	ft	Importance Category = II
Peak Velocity Pressure, q_z =	19.00	psf	*Including the gust factor, G=0.85. (ASCE 7-10, Eq. 27.3-1)*

Pressure Coefficients

$Cf+_{TOP}$ =	1.150	*(Pressure)*	*Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0611-1e. Negative forces are applied away from the surface.*
$Cf+_{BOTTOM}$ =	1.850		
$Cf-_{TOP, OUTER PURLIN}$ =	-2.600		
$Cf-_{TOP, INNER PURLIN}$ =	-2.000	*(Suction)*	
$Cf-_{BOTTOM}$ =	-1.100		

2.4 Seismic Loads

S_S =	2.50	R =	1.25	*ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.*
S_{DS} =	1.67	C_S =	0.8	
S_1 =	1.00	ρ =	1.3	
S_{D1} =	1.00	Ω =	1.25	
T_a =	0.07	C_d =	1.25	

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.5W
1.2D + 1.0W + 0.5S
0.9D + 1.0W [M]
1.54D + 1.3E + 0.2S [R]
0.56D + 1.3E [R]
1.54D + 1.25E + 0.2S [O]
0.56D + 1.25E [O]

(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S
1.0D + 0.6W
1.0D + 0.75L + 0.45W + 0.75S
0.6D + 0.6W [M]
1.238D + 0.875E [O]
1.1785D + 0.65625E + 0.75S [O]
0.362D + 0.875E [O]

(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)

[M] *Uses the minimum allowable module dead load.*
[R] *Include redundancy factor of 1.3.*
[O] *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location
M13	Top
M14	Mid-Top
M15	Mid-Bottom
M16	Bottom

Diagonal Struts	Location
M3	Outer
M7	Inner
M11	Outer

Front Reactions	Location
N7	Outer
N15	Inner
N23	Outer

Girders	Location
M1	Outer
M5	Inner
M9	Outer

Rear Struts	Location
M2	Outer
M6	Inner
M10	Outer

Rear Reactions	Location
N8	Outer
N16	Inner
N24	Outer

Front Struts	Location
M4	Outer
M8	Inner
M12	Outer

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type =	**S1.5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	120	in
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	25.07	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	23.08	ksi
S_y =	1.33	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	2.16	in^4
I_x =	1.07	in^4
A =	1.25	in^2
g =	1.50	lbs/ft
M_y =	1.741	k-ft
M_z =	0.402	k-ft
$M_{y\ allowable}$ =	2.779	k-ft
$M_{z\ allowable}$ =	1.154	k-ft
Utilization =	97%	



DETAIL VIEW

4.2 Girder Design

Loads from purlins are transferred using an inclined girder, which is connected to a set of aluminum struts. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type =	**BF0**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	104.56	in
$\Phi F_{ty\ AXIAL}$ =	31.09	ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	29.00	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	33.25	ksi
S_y =	1.42	in^3
S_x =	1.41	in^3
E =	10100	ksi
I_y =	2.39	in^4
I_x =	2.22	in^4
A =	1.88	in^2
g =	2.26	lbs/ft
M_y =	-3.100	k-ft
M_z =	0.000	k-ft
P_n =	-0.810	k
$M_{y\ allowable}$ =	3.422	k-ft
$M_{z\ allowable}$ =	3.907	k-ft
$P_{n\ allowable}$ =	58.535	k
Utilization =	92%	



4.3 Front Strut Design

The front aluminum strut connects a portion of the girder to the foundation. Vertical girder forces are then transferred down through the strut into the foundation. The strut is attached with single M12 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	24.80	in
$\Phi F_{ty\ AXIAL}$ =	28.03	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.000	k-ft
M_z =	-0.666	k-ft
P_n =	0.163	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	27.532	k
Utilization =	48%	



DETAIL VIEW

4.4 Diagonal Strut Design

A diagonal aluminum strut braces the support structure. It connects at a front portion of the girder and transfers horizontal forces to the rear foundation connection. The strut is attached with single M12 bolts at each end. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	98.03	in
$\Phi F_{ty\ AXIAL}$ =	6.11	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.011	k-ft
M_z =	0.000	k-ft
P_n =	2.189	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	6.000	k
Utilization =	37%	



DETAIL VIEW

4.5 Rear Strut Design

An aluminum strut connects the rear portion of the girder to the rear foundation connection. Both vertical and horizontal forces are transferred from the girder. The strut is attached with single M12 bolts at each end. See Appendix A.5 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	78.35	in
$\Phi F_{ty\ AXIAL}$ =	8.88	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	-0.010	k-ft
M_z =	0.000	k-ft
P_n =	3.135	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	8.726	k
Utilization =	37%	



5. FOUNDATION DESIGN CALCULATIONS

5.1 Helical Pile Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete foundation design.

Maximum	Front	Rear	
Tensile Load =	87.71	5358.80	k
Compressive Load =	3663.99	4535.75	k
Lateral Load =	435.65	3354.99	k
Moment (Weak Axis) =	0.87	0.34	k

5.2 Design of Ballast Foundations

Ballast foundations are used to secure the racking structure in place. The foundations are checked for potential overturning and sliding. Bearing pressures applied by the racking and ballast foundations are checked against the allowable bearing pressures provided by the IBC table 1806.2 (2012, 2015).



Concrete Properties

Weight of Concrete =	145 pcf
Compressive Strength =	2500 psi
Yield Strength =	60000 psi

Overturning Check

M_O =	145128.6 in-lbs
Resisting Force Required =	2029.77 lbs
S.F. =	1.67
Weight Required =	3382.95 lbs
Minimum Width =	35 in in
Weight Provided =	7559.64 lbs

Sliding

Force =	773.69 lbs
Friction =	0.4
Weight Required =	1934.22 lbs
Resisting Weight =	7559.64 lbs
Additional Weight Required =	0 lbs

Cohesion

Sliding Force =	773.69 lbs
Cohesion =	130 psf
Area =	34.76 ft^2
Resisting =	3779.82 lbs
Additional Weight Required =	0 lbs

Shear Key

Additional Force =	0 lbs
Lateral Bearing Pressure =	200 psf/ft
Required Depth =	0.00 ft
f'_c =	2500 psi
Length =	8 in

Footing Reinforcement

Use fiber reinforcing with (2) #5 rebar.

A minimum 143in long x 35in wide x 18in tall ballast foundation is required to resist overturning.

Use a 143in long x 35in wide x 18in tall ballast foundation to resist sliding. Friction is OK.

Use a 143in long x 35in wide x 18in tall ballast foundation. Cohesion is OK.

Shear key is not required.

Bearing Pressure

	Ballast Width			
	35 in	36 in	37 in	38 in
P_{ftg} = (145 pcf)(11.92 ft)(1.5 ft)(2.92 ft) =	7560 lbs	7776 lbs	7992 lbs	8208 lbs

ASD LC	1.0D + 1.0S				1.0D + 0.6W				1.0D + 0.75L + 0.45W + 0.75S				0.6D + 0.6W			
Width	35 in	36 in	37 in	38 in	35 in	36 in	37 in	38 in	35 in	36 in	37 in	38 in	35 in	36 in	37 in	38 in
F_A	1398 lbs	1398 lbs	1398 lbs	1398 lbs	1133 lbs	1133 lbs	1133 lbs	1133 lbs	1752 lbs	1752 lbs	1752 lbs	1752 lbs	-29 lbs	-29 lbs	-29 lbs	-29 lbs
F_B	1394 lbs	1394 lbs	1394 lbs	1394 lbs	1842 lbs	1842 lbs	1842 lbs	1842 lbs	2283 lbs	2283 lbs	2283 lbs	2283 lbs	-2463 lbs	-2463 lbs	-2463 lbs	-2463 lbs
F_V	207 lbs	207 lbs	207 lbs	207 lbs	1418 lbs	1418 lbs	1418 lbs	1418 lbs	1199 lbs	1199 lbs	1199 lbs	1199 lbs	-1547 lbs	-1547 lbs	-1547 lbs	-1547 lbs
P_{total}	10352 lbs	10568 lbs	10784 lbs	11000 lbs	10535 lbs	10751 lbs	10967 lbs	11183 lbs	11595 lbs	11811 lbs	12027 lbs	12243 lbs	2044 lbs	2173 lbs	2303 lbs	2433 lbs
M	3663 lbs-ft	3663 lbs-ft	3663 lbs-ft	3663 lbs-ft	2767 lbs-ft	2767 lbs-ft	2767 lbs-ft	2767 lbs-ft	4439 lbs-ft	4439 lbs-ft	4439 lbs-ft	4439 lbs-ft	4698 lbs-ft	4698 lbs-ft	4698 lbs-ft	4698 lbs-ft
e	0.35 ft	0.35 ft	0.34 ft	0.33 ft	0.26 ft	0.26 ft	0.25 ft	0.25 ft	0.38 ft	0.38 ft	0.37 ft	0.36 ft	2.30 ft	2.16 ft	2.04 ft	1.93 ft
L/6	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft	1.99 ft
f_{min}	244.8 psf	244.0 psf	243.3 psf	242.6 psf	263.0 psf	261.8 psf	260.6 psf	259.4 psf	269.3 psf	267.8 psf	266.5 psf	265.2 psf	0.0 psf	0.0 psf	0.0 psf	1.8 psf
f_{max}	350.9 psf	347.2 psf	343.7 psf	340.4 psf	343.2 psf	339.7 psf	336.4 psf	333.3 psf	397.9 psf	392.9 psf	388.1 psf	383.7 psf	127.6 psf	127.2 psf	127.1 psf	127.1 psf

Maximum Bearing Pressure = 398 psf
Allowable Bearing Pressure = 1500 psf

Use a 143in long x 35in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Seismic Design

Overturning Check

M_O =	2695.9 ft-lbs
Resisting Force Required =	1848.62 lbs
S.F. =	1.67
Weight Required =	3081.03 lbs
Minimum Width =	35 in in
Weight Provided =	7559.64 lbs

A minimum 143in long x 35in wide x 18in tall ballast foundation is required to resist overturning.



Bearing Pressure

ASD LC	1.238D + 0.875E			1.1785D + 0.65625E + 0.75S			0.362D + 0.875E		
Width	35 in			35 in			35 in		
Support	Outer	Inner	Outer	Outer	Inner	Outer	Outer	Inner	Outer
F_Y	350 lbs	720 lbs	226 lbs	899 lbs	2344 lbs	803 lbs	145 lbs	211 lbs	23 lbs
F_V	244 lbs	238 lbs	251 lbs	177 lbs	174 lbs	198 lbs	246 lbs	239 lbs	248 lbs
P_{total}	9708 lbs	10079 lbs	9585 lbs	9808 lbs	11253 lbs	9712 lbs	2882 lbs	2947 lbs	2760 lbs
M	969 lbs-ft	953 lbs-ft	990 lbs-ft	718 lbs-ft	722 lbs-ft	784 lbs-ft	969 lbs-ft	950 lbs-ft	977 lbs-ft
e	0.10 ft	0.09 ft	0.10 ft	0.07 ft	0.06 ft	0.08 ft	0.34 ft	0.32 ft	0.35 ft
L/6	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft
f_{min}	222.0 psf	233.6 psf	217.2 psf	239.7 psf	281.0 psf	233.1 psf	25.5 psf	28.6 psf	21.6 psf
f_{max}	336.7 psf	346.4 psf	334.4 psf	324.7 psf	366.5 psf	325.8 psf	140.3 psf	141.0 psf	137.2 psf

Maximum Bearing Pressure = 366 psf
Allowable Bearing Pressure = 1500 psf

Use a 143in long x 35in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Foundation Requirements: 143in long x 26in wide x 18in tall ballast foundation and fiber reinforcing with (2) #5 rebar.

5.3 Foundation Anchors

Threaded rods are anchored to the the ballast foundations using the Simpson AT-XP epoxy solution. LRFD load results are compared to the allowable strengths of the epoxy solution. Please see the supplementary calculations provided by the Simpson Anchor Designer software.

6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of 80mm mounting clamps. The reliability of calculations is uncertain due to limited standards, therefore the strength of the clamp fasteners has been evaluated by load testing.

Fastening of Modules to Purlins

Maximum Uplifting Force	=	0.540 k
Allowable Uplift	=	1.214 k
Utilization	=	45%



Fastening of Purlins to Girders

Maximum Uplifting Force	=	1.914 k
Allowable Uplift	=	4.357 k
Utilization	=	44%



6.2 Strut Connections

The aluminum struts connect the aluminum girder ends to custom brackets with mounting holes. Single M12 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Front Strut

Maximum Axial Load	=	2.818 k
M12 Bolt Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	38%

Rear Strut

Maximum Axial Load	=	3.599 k
M12 Bolt Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	48%

Diagonal Strut

Maximum Axial Load	=	2.275 k
M12 Bolt Shear Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	31%

Bolt and bearing capacities are accounting for double shear. (ASCE 8-02, Eq. 5.3.4-1)



Struts under compression are shown to demonstrate the load transfer from the girder. Single M12 bolts are located at each end of the strut and are subjected to double shear.

7. SEISMIC DESIGN

7.1 Seismic Drift

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx}	=	60.93 in
Allowable Story Drift for All Other Structures, Δ	= {	$0.020h_{sx}$
		1.219 in
Max Drift, Δ_{MAX}	=	0.996 in

0.996 ≤ 1.219, OK.

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **S1.5**

Strong Axis:		Weak Axis:	
3.4.14		**3.4.14**	
L_b =	120 in	L_b =	120
J =	0.432	J =	0.432
	331.976		211.117
$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$		$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$	
S1 =	0.51461	S1 =	0.51461
$S2 = \left(\frac{C_c}{1.6}\right)^2$		$S2 = \left(\frac{C_c}{1.6}\right)^2$	
S2 =	1701.56	S2 =	1701.56
φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]	φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L=	27.4 ksi	φF_L=	28.6
3.4.16		**3.4.16**	
b/t =	32.195	b/t =	37.0588
$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$		$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$	
S1 =	12.2	S1 =	12.2
$S2 = \frac{k_1 Bp}{1.6Dp}$		$S2 = \frac{k_1 Bp}{1.6Dp}$	
S2 =	46.7	S2 =	46.7
φF_L=	φb[Bp-1.6Dp*b/t]	φF_L=	φb[Bp-1.6Dp*b/t]
φF_L=	25.1 ksi	φF_L=	23.1 ksi
3.4.16.1	Not Used	**3.4.16.1**	
Rb/t =		N/A for Weak Direction	
$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$			
S1 =	1.1		
$S2 = C_t$			
S2 =	141.0		
φF_L=	1.17φyFcy		
φF_L=	38.9 ksi		
3.4.18		**3.4.18**	
h/t =	37.0588	h/t =	32.195
$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$		$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$	
S1 =	36.9	S1 =	36.9
m =	0.65	m =	0.65
C_0 =	40.985	C_0 =	45.5
Cc =	41.015	Cc =	45.5
$S2 = \frac{k_1 Bbr}{mDbr}$		$S2 = \frac{k_1 Bbr}{mDbr}$	
S2 =	77.2	S2 =	77.3
φF_L=	φb[Bbr-mDbr*h/t]	φF_L=	1.3φyFcy
φF_L=	43.2 ksi	φF_L=	43.2 ksi
φF_LSt=	25.1 ksi	φF_LWk=	23.1 ksi
Ix =	897074 mm^4	Iy =	446476 mm^4
	2.155 in^4		1.073 in^4
y =	41.015 mm	x =	45.5 mm
Sx =	1.335 in^3	Sy =	0.599 in^3
M_{max}St =	2.788 k-ft	M_{max}Wk =	1.152 k-ft

Compression

3.4.9

b/t = 32.195
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 25.1 ksi

b/t = 37.0588
S1 = 12.21
S2 = 32.70
φF_L = (φck2*√(BpE))/(1.6b/t)
φF_L = 21.9 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 21.94 ksi
A = 1215.13 mm^2
1.88 in^2
P_{max} = 41.32 kips

A.2 Design of Aluminum Girders - Aluminum Design Manual, 2005 Edition

Girder = **BF0**

Strong Axis:

3.4.14

L_b = 104.56 in
J = 1.08
179.85

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.0 ksi

3.4.16

b/t = 16.2

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 31.6 ksi

Weak Axis:

3.4.14

L_b = 104.56
J = 1.08
190.335

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 28.9

3.4.16

b/t = 7.4

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φyFcy
φF_L = 33.3 ksi

3.4.16.1 Used

Rb/t = 18.1

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= φb[Bt-Dt*√(Rb/t)]

φF_L= 31.1 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 7.4

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 35.2

m = 0.68

C_0 = 41.067

Cc = 43.717

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 73.8

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 29.0 ksi

Ix = 984962 mm^4

2.366 in^4

y = 43.717 mm

Sx = 1.375 in^3

$M_{max}St$ = 3.323 k-ft

3.4.18

h/t = 16.2

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 40

Cc = 40

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 33.3 ksi

Iy = 923544 mm^4

2.219 in^4

x = 40 mm

Sy = 1.409 in^3

$M_{max}Wk$ = 3.904 k-ft

Compression

3.4.9

b/t = 16.2

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 31.6 ksi

b/t = 7.4

S1 = 12.21

S2 = 32.70

φF_L= φyFcy

φF_L= 33.3 ksi

3.4.10

Rb/t = 18.1

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L= φc[Bt-Dt*√(Rb/t)]

φF_L= 31.09 ksi

φF_L= 31.09 ksi

A = 1215.13 mm^2

1.88 in^2

P_{max} = 58.55 kips

A.3 Design of Aluminum Struts (Front) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 24.8 in

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

Weak Axis:

3.4.14

L_b = 24.8

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 0.57371

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

S1* = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

S2* = 1.23671

φcc = 0.87952

φF_L = φcc(Bc-Dc*λ)

φF_L = 28.0279 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 28.03 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 28.85 kips

A.4 Design of Aluminum Struts (Diagonal) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 98.03 in

J = 0.942

152.985

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L = 29.4 ksi

Weak Axis:

3.4.14

L_b = 98.03

J = 0.942

152.985

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L = 29.4

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17 \frac{\theta_y}{\theta_b} Fcy}{1.6Dt} \right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 2.26776

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi} \sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.89749

φF_L= (φccFcy)/(λ²)

φF_L= 6.10803 ksi

3.4.9

b/t = 24.5
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

b/t = 24.5
S1 = 12.21
S2 = 32.70
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 6.11 ksi
A = 663.99 mm^2
1.03 in^2
P_{max} = 6.29 kips

A.5 Design of Aluminum Struts (Rear) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 78.35 in
J = 0.942
122.273

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.8 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

Weak Axis:

3.4.14

L_b = 78.35
J = 0.942
122.273

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.8

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

$M_{max}St$ = 1.460 k-ft

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

$M_{max}Wk$ = 1.460 k-ft

Compression

3.4.7

λ = 1.8125

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.83375

φF_L= (φccFcy)/(λ²)

φF_L= 8.88278 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

$\varphi F_L = \varphi y Fcy$

φF_L = 33.25 ksi

φF_L = 8.88 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 9.14 kips

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				4		
2	Dead Load, Min	DL		-1				4		
3	Snow Load	SL						4		
4	Wind Load - Pressure	WL						4		
5	Wind Load - Suction	WL						4		
6	Seismic - Lateral	EL			.8			8		

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-9.843	-9.843	0	0
2	M14	Y	-9.843	-9.843	0	0
3	M15	Y	-9.843	-9.843	0	0
4	M16	Y	-9.843	-9.843	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-5.454	-5.454	0	0
2	M14	Y	-5.454	-5.454	0	0
3	M15	Y	-5.454	-5.454	0	0
4	M16	Y	-5.454	-5.454	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-46.866	-46.866	0	0
2	M14	Y	-46.866	-46.866	0	0
3	M15	Y	-46.866	-46.866	0	0
4	M16	Y	-46.866	-46.866	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	-71.679	-71.679	0	0
2	M14	y	-71.679	-71.679	0	0
3	M15	y	-115.31	-115.31	0	0
4	M16	y	-115.31	-115.31	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	162.058	162.058	0	0
2	M14	y	124.66	124.66	0	0
3	M15	y	68.563	68.563	0	0
4	M16	y	68.563	68.563	0	0

Member Distributed Loads (BLC 6 : Seismic - Lateral)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Z	7.874	7.874	0	0
2	M14	Z	7.874	7.874	0	0
3	M15	Z	7.874	7.874	0	0
4	M16	Z	7.874	7.874	0	0
5	M13	Z	0	0	0	0
6	M14	Z	0	0	0	0
7	M15	Z	0	0	0	0
8	M16	Z	0	0	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.5W	Yes	Y		1	1.2	3	1.6	4	.5														
2	LRFD 1.2D + 1.0W + 0.5S	Yes	Y		1	1.2	3	.5	4	1														
3	LRFD 0.9D + 1.0W	Yes	Y		2	.9					5	1												
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3												
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3												
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25												
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25												
8																								
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																
10	ASD 1.0D + 0.6W	Yes	Y		1	1			4	.6														
11	ASD 1.0D + 0.75L + 0.45W + 0....	Yes	Y		1	1	3	.75	4	.45														
12	ASD 0.6D + 0.6W	Yes	Y		2	.6					5	.6												
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875												
14	LATERAL - ASD 1.1785D + 0.65...	Yes	Y		1	1.1...	3	.75			6	.656												
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875												

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N8	max	656.403	2	1086.981	2	.909	1	.004	1	0	1	0	1
2		min	-828.811	3	-1274.08	3	-42.055	5	-.258	4	0	1	0	1
3	N7	max	.046	9	1108.169	1	-1.068	12	-.002	12	0	1	0	1
4		min	-.175	2	-56.004	5	-335.112	4	-.666	4	0	1	0	1
5	N15	max	.01	9	2818.457	1	0	1	0	1	0	1	0	1
6		min	-1.92	2	-67.468	3	-313.733	4	-.635	4	0	1	0	1
7	N16	max	2429.245	2	3489.036	2	0	3	0	3	0	1	0	1
8		min	-2580.761	3	-4122.152	3	-41.821	5	-.261	4	0	1	0	1
9	N23	max	.057	14	1108.169	1	18.743	1	.036	1	0	1	0	1
10		min	-.175	2	11.267	3	-321.68	5	-.644	4	0	1	0	1
11	N24	max	656.403	2	1086.981	2	-.064	12	0	12	0	1	0	1
12		min	-828.811	3	-1274.08	3	-42.968	5	-.261	4	0	1	0	1
13	Totals:	max	3739.78	2	10493.533	1	0	1						
14		min	-4238.44	3	-6715.246	3	-1088.44	4						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M13	1	max	108.144	1	415.589	1	-10.74	12	0	3	.304	1	0	4
2			min	6.376	12	-587.688	3	-211.545	1	-.014	2	.018	12	0	3
3		2	max	108.144	1	290.51	1	-8.42	12	0	3	.159	4	.556	3
4			min	6.376	12	-413.649	3	-162.321	1	-.014	2	.007	12	-.392	1
5		3	max	108.144	1	165.431	1	-6.101	12	0	3	.088	5	.919	3
6			min	6.376	12	-239.611	3	-113.098	1	-.014	2	-.057	1	-.646	1
7		4	max	108.144	1	40.352	1	-3.781	12	0	3	.047	5	1.089	3
8			min	6.376	12	-65.572	3	-63.875	1	-.014	2	-.155	1	-.76	1
9		5	max	108.144	1	108.466	3	-1.375	10	0	3	.009	5	1.065	3
10			min	6.376	12	-84.727	1	-36.036	4	-.014	2	-.199	1	-.735	1
11		6	max	108.144	1	282.505	3	34.572	1	0	3	-.009	12	.848	3
12			min	2.71	15	-209.807	1	-28.301	5	-.014	2	-.188	1	-.572	1
13		7	max	108.144	1	456.543	3	83.796	1	0	3	-.007	12	.437	3
14			min	-8.777	5	-334.886	1	-24.771	5	-.014	2	-.122	1	-.269	1
15		8	max	108.144	1	630.582	3	133.019	1	0	3	.002	2	.173	1
16			min	-21.889	5	-459.965	1	-21.241	5	-.014	2	-.082	4	-.167	3
17		9	max	108.144	1	804.62	3	182.243	1	0	3	.174	1	.753	1
18			min	-35.001	5	-585.044	1	-17.711	5	-.014	2	-.101	5	-.964	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
19		10	max	108.144	1	710.123	1	-10.135	12	.004	14	.403	1	1.473	1
20			min	6.376	12	-978.659	3	-231.466	1	-.014	2	.015	12	-1.955	3
21		11	max	108.144	1	585.044	1	-7.815	12	.014	2	.174	1	.753	1
22			min	6.376	12	-804.62	3	-182.243	1	0	3	.005	12	-.964	3
23		12	max	108.144	1	459.965	1	-5.496	12	.014	2	.08	4	.173	1
24			min	6.376	12	-630.582	3	-133.019	1	0	3	-.004	3	-.167	3
25		13	max	108.144	1	334.886	1	-3.177	12	.014	2	.036	5	.437	3
26			min	6.376	12	-456.543	3	-83.796	1	0	3	-.122	1	-.269	1
27		14	max	108.144	1	209.807	1	-.857	12	.014	2	-.002	15	.848	3
28			min	6.376	12	-282.505	3	-41.785	4	0	3	-.188	1	-.572	1
29		15	max	108.144	1	84.727	1	14.651	1	.014	2	-.009	12	1.065	3
30			min	-2.122	5	-108.466	3	-29.662	5	0	3	-.199	1	-.735	1
31		16	max	108.144	1	65.572	3	63.875	1	.014	2	-.006	12	1.089	3
32			min	-15.233	5	-40.352	1	-26.132	5	0	3	-.155	1	-.76	1
33		17	max	108.144	1	239.611	3	113.098	1	.014	2	0	12	.919	3
34			min	-28.345	5	-165.431	1	-22.602	5	0	3	-.111	4	-.646	1
35		18	max	108.144	1	413.649	3	162.321	1	.014	2	.096	1	.556	3
36			min	-41.457	5	-290.51	1	-19.072	5	0	3	-.119	5	-.392	1
37		19	max	108.144	1	587.688	3	211.545	1	.014	2	.304	1	0	1
38			min	-54.568	5	-415.589	1	-15.542	5	0	3	-.138	5	0	3
39	M14	1	max	62.465	4	452.254	1	-11.091	12	.01	3	.354	1	0	4
40			min	3.214	12	-467.655	3	-219.112	1	-.012	1	.02	12	0	3
41		2	max	58.625	1	327.175	1	-8.772	12	.01	3	.234	4	.446	3
42			min	3.214	12	-335.17	3	-169.889	1	-.012	1	.009	12	-.433	1
43		3	max	58.625	1	202.095	1	-6.453	12	.01	3	.133	5	.745	3
44			min	3.214	12	-202.685	3	-120.666	1	-.012	1	-.023	1	-.727	1
45		4	max	58.625	1	77.016	1	-4.133	12	.01	3	.072	5	.896	3
46			min	3.214	12	-70.2	3	-71.442	1	-.012	1	-.13	1	-.882	1
47		5	max	58.625	1	62.286	3	-1.814	12	.01	3	.015	5	.901	3
48			min	-3.498	5	-48.063	1	-55.532	4	-.012	1	-.182	1	-.898	1
49		6	max	58.625	1	194.771	3	27.005	1	.01	3	-.009	12	.758	3
50			min	-16.61	5	-173.142	1	-45.619	5	-.012	1	-.18	1	-.775	1
51		7	max	58.625	1	327.256	3	76.228	1	.01	3	-.007	12	.468	3
52			min	-29.721	5	-298.221	1	-42.089	5	-.012	1	-.122	1	-.513	1
53		8	max	58.625	1	459.741	3	125.452	1	.01	3	0	10	.031	3
54			min	-42.833	5	-423.3	1	-38.558	5	-.012	1	-.137	4	-.122	2
55		9	max	58.625	1	592.226	3	174.675	1	.01	3	.157	1	.427	1
56			min	-55.945	5	-548.379	1	-35.028	5	-.012	1	-.172	5	-.554	3
57		10	max	90.43	4	673.459	1	-9.783	12	.01	3	.378	1	1.106	1
58			min	3.214	12	-724.711	3	-223.898	1	-.012	1	.014	12	-1.285	3
59		11	max	77.319	4	548.379	1	-7.464	12	.012	1	.234	4	.427	1
60			min	3.214	12	-592.226	3	-174.675	1	-.01	3	.004	12	-.554	3
61		12	max	64.207	4	423.3	1	-5.144	12	.012	1	.13	4	.031	3
62			min	3.214	12	-459.741	3	-125.452	1	-.01	3	-.01	1	-.122	2
63		13	max	58.625	1	298.221	1	-2.825	12	.012	1	.068	5	.468	3
64			min	3.214	12	-327.256	3	-76.228	1	-.01	3	-.122	1	-.513	1
65		14	max	58.625	1	173.142	1	-.506	12	.012	1	.011	5	.758	3
66			min	3.214	12	-194.771	3	-56.692	4	-.01	3	-.18	1	-.775	1
67		15	max	58.625	1	48.063	1	22.219	1	.012	1	-.008	12	.901	3
68			min	3.214	12	-62.286	3	-45.895	5	-.01	3	-.182	1	-.898	1
69		16	max	58.625	1	70.2	3	71.442	1	.012	1	-.005	12	.896	3
70			min	-2.043	5	-77.016	1	-42.365	5	-.01	3	-.13	1	-.882	1
71		17	max	58.625	1	202.685	3	120.666	1	.012	1	.002	3	.745	3
72			min	-15.155	5	-202.095	1	-38.834	5	-.01	3	-.144	4	-.727	1
73		18	max	58.625	1	335.17	3	169.889	1	.012	1	.138	1	.446	3
74			min	-28.266	5	-327.175	1	-35.304	5	-.01	3	-.177	5	-.433	1
75		19	max	58.625	1	467.655	3	219.112	1	.012	1	.354	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
76			min	-41.378	5	-452.254	1	-31.774	5	-.01	3	-.214	5	0	3
77	M15	1	max	101.605	5	582.839	2	-11.023	12	.013	2	.424	4	0	2
78			min	-62.9	1	-257.645	3	-219.036	1	-.008	3	.02	12	0	3
79		2	max	88.493	5	419.066	2	-8.704	12	.013	2	.289	4	.247	3
80			min	-62.9	1	-187.489	3	-169.812	1	-.008	3	.009	12	-.557	2
81		3	max	75.382	5	255.292	2	-6.384	12	.013	2	.172	5	.417	3
82			min	-62.9	1	-117.334	3	-120.589	1	-.008	3	-.024	1	-.931	2
83		4	max	62.27	5	91.519	2	-4.065	12	.013	2	.096	5	.508	3
84			min	-62.9	1	-47.179	3	-84.265	4	-.008	3	-.13	1	-1.124	2
85		5	max	49.158	5	22.976	3	-1.746	12	.013	2	.024	5	.521	3
86			min	-62.9	1	-72.254	2	-69.35	4	-.008	3	-.182	1	-1.135	2
87		6	max	36.047	5	93.131	3	27.082	1	.013	2	-.009	12	.457	3
88			min	-62.9	1	-236.027	2	-59.374	5	-.008	3	-.18	1	-.963	2
89		7	max	22.935	5	163.287	3	76.305	1	.013	2	-.007	12	.315	3
90			min	-62.9	1	-399.8	2	-55.843	5	-.008	3	-.138	4	-.61	2
91		8	max	9.823	5	233.442	3	125.528	1	.013	2	0	10	.094	3
92			min	-62.9	1	-563.574	2	-52.313	5	-.008	3	-.174	4	-.089	1
93		9	max	-2.071	15	303.597	3	174.752	1	.013	2	.157	1	.642	2
94			min	-62.9	1	-727.347	2	-48.783	5	-.008	3	-.224	5	-.204	3
95		10	max	-3.773	12	891.12	2	-9.851	12	.013	2	.423	4	1.541	2
96			min	-62.9	1	-373.752	3	-223.975	1	-.008	3	.014	12	-.581	3
97		11	max	-3.773	12	727.347	2	-7.532	12	.008	3	.287	4	.642	2
98			min	-62.9	1	-303.597	3	-174.752	1	-.013	2	.005	12	-.204	3
99		12	max	-3.773	12	563.574	2	-5.213	12	.008	3	.167	4	.094	3
100			min	-62.9	1	-233.442	3	-125.528	1	-.013	2	-.01	1	-.089	1
101		13	max	-3.773	12	399.8	2	-2.893	12	.008	3	.09	5	.315	3
102			min	-62.9	1	-163.287	3	-85.481	4	-.013	2	-.122	1	-.61	2
103		14	max	-3.773	12	236.027	2	-.574	12	.008	3	.018	5	.457	3
104			min	-62.9	1	-93.131	3	-70.566	4	-.013	2	-.18	1	-.963	2
105		15	max	-3.773	12	72.254	2	22.142	1	.008	3	-.008	12	.521	3
106			min	-74.692	4	-22.976	3	-59.656	5	-.013	2	-.182	1	-1.135	2
107		16	max	-3.773	12	47.179	3	71.365	1	.008	3	-.005	12	.508	3
108			min	-87.804	4	-91.519	2	-56.126	5	-.013	2	-.147	4	-1.124	2
109		17	max	-3.773	12	117.334	3	120.589	1	.008	3	.001	3	.417	3
110			min	-100.915	4	-255.292	2	-52.596	5	-.013	2	-.184	4	-.931	2
111		18	max	-3.773	12	187.489	3	169.812	1	.008	3	.138	1	.247	3
112			min	-114.027	4	-419.066	2	-49.066	5	-.013	2	-.232	5	-.557	2
113		19	max	-3.773	12	257.645	3	219.036	1	.008	3	.354	1	0	2
114			min	-127.139	4	-582.839	2	-45.536	5	-.013	2	-.284	5	0	5
115	M16	1	max	96.069	5	547.361	2	-10.539	12	.011	1	.317	4	0	2
116			min	-121.703	1	-231.126	3	-212.027	1	-.011	3	.017	12	0	3
117		2	max	82.957	5	383.588	2	-8.22	12	.011	1	.206	4	.218	3
118			min	-121.703	1	-160.971	3	-162.804	1	-.011	3	.007	12	-.517	2
119		3	max	69.846	5	219.815	2	-5.9	12	.011	1	.122	5	.358	3
120			min	-121.703	1	-90.816	3	-113.58	1	-.011	3	-.055	1	-.852	2
121		4	max	56.734	5	56.042	2	-3.581	12	.011	1	.068	5	.42	3
122			min	-121.703	1	-20.661	3	-64.357	1	-.011	3	-.154	1	-1.006	2
123		5	max	43.622	5	49.494	3	-1.261	12	.011	1	.018	5	.404	3
124			min	-121.703	1	-107.732	2	-47.686	4	-.011	3	-.198	1	-.977	2
125		6	max	30.511	5	119.649	3	34.09	1	.011	1	-.009	12	.31	3
126			min	-121.703	1	-271.505	2	-39.726	5	-.011	3	-.188	1	-.766	2
127		7	max	17.399	5	189.805	3	83.314	1	.011	1	-.007	12	.138	3
128			min	-121.703	1	-435.278	2	-36.196	5	-.011	3	-.122	1	-.374	2
129		8	max	4.287	5	259.96	3	132.537	1	.011	1	0	10	.201	2
130			min	-121.703	1	-599.051	2	-32.665	5	-.011	3	-.112	4	-.112	3
131		9	max	-5.809	15	330.115	3	181.76	1	.011	1	.172	1	.958	2
132			min	-121.703	1	-762.824	2	-29.135	5	-.011	3	-.143	5	-.44	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
133		10	max	-6.821	12	926.597	2	-10.335	12	.011	1	.402	1	1.896	2
134			min	-121.703	1	-400.27	3	-230.984	1	-.011	3	.016	12	-.846	3
135		11	max	-5.497	15	762.824	2	-8.016	12	.011	3	.211	4	.958	2
136			min	-121.703	1	-330.115	3	-181.76	1	-.011	1	.006	12	-.44	3
137		12	max	-6.821	12	599.051	2	-5.697	12	.011	3	.11	4	.201	2
138			min	-121.703	1	-259.96	3	-132.537	1	-.011	1	-.003	3	-.112	3
139		13	max	-6.821	12	435.278	2	-3.377	12	.011	3	.053	5	.138	3
140			min	-121.703	1	-189.805	3	-83.314	1	-.011	1	-.122	1	-.374	2
141		14	max	-6.821	12	271.505	2	-1.058	12	.011	3	.002	5	.31	3
142			min	-121.703	1	-119.649	3	-53.224	4	-.011	1	-.188	1	-.766	2
143		15	max	-6.821	12	107.732	2	15.133	1	.011	3	-.009	12	.404	3
144			min	-121.703	1	-49.494	3	-41.052	5	-.011	1	-.198	1	-.977	2
145		16	max	-6.821	12	20.661	3	64.357	1	.011	3	-.006	12	.42	3
146			min	-121.703	1	-56.042	2	-37.522	5	-.011	1	-.154	1	-1.006	2
147		17	max	-6.821	12	90.816	3	113.58	1	.011	3	-.001	12	.358	3
148			min	-121.703	1	-219.815	2	-33.992	5	-.011	1	-.144	4	-.852	2
149		18	max	-6.821	12	160.971	3	162.804	1	.011	3	.098	1	.218	3
150			min	-129.875	4	-383.588	2	-30.462	5	-.011	1	-.165	5	-.517	2
151		19	max	-6.821	12	231.126	3	212.027	1	.011	3	.307	1	0	2
152			min	-142.987	4	-547.361	2	-26.931	5	-.011	1	-.197	5	0	5
153	M2	1	max	987.235	1	2.056	4	.605	1	0	12	0	3	0	1
154			min	-1112.805	3	.498	15	-37.161	4	0	4	0	1	0	1
155		2	max	987.764	1	1.985	4	.605	1	0	12	0	1	0	15
156			min	-1112.408	3	.481	15	-37.623	4	0	4	-.013	4	0	4
157		3	max	988.294	1	1.914	4	.605	1	0	12	0	1	0	15
158			min	-1112.011	3	.464	15	-38.084	4	0	4	-.027	4	-.001	4
159		4	max	988.823	1	1.843	4	.605	1	0	12	0	1	0	15
160			min	-1111.614	3	.448	15	-38.545	4	0	4	-.041	4	-.002	4
161		5	max	989.352	1	1.772	4	.605	1	0	12	0	1	0	15
162			min	-1111.217	3	.431	15	-39.006	4	0	4	-.055	4	-.003	4
163		6	max	989.881	1	1.701	4	.605	1	0	12	.001	1	0	15
164			min	-1110.82	3	.414	15	-39.467	4	0	4	-.069	4	-.003	4
165		7	max	990.411	1	1.63	4	.605	1	0	12	.001	1	0	15
166			min	-1110.423	3	.398	15	-39.929	4	0	4	-.083	4	-.004	4
167		8	max	990.94	1	1.559	4	.605	1	0	12	.002	1	-.001	15
168			min	-1110.026	3	.381	15	-40.39	4	0	4	-.097	4	-.005	4
169		9	max	991.469	1	1.488	4	.605	1	0	12	.002	1	-.001	15
170			min	-1109.629	3	.364	15	-40.851	4	0	4	-.112	4	-.005	4
171		10	max	991.999	1	1.417	4	.605	1	0	12	.002	1	-.001	15
172			min	-1109.232	3	.348	15	-41.312	4	0	4	-.127	4	-.006	4
173		11	max	992.528	1	1.345	4	.605	1	0	12	.002	1	-.001	15
174			min	-1108.835	3	.331	15	-41.774	4	0	4	-.142	4	-.006	4
175		12	max	993.057	1	1.274	4	.605	1	0	12	.002	1	-.002	15
176			min	-1108.438	3	.314	15	-42.235	4	0	4	-.157	4	-.007	4
177		13	max	993.586	1	1.203	4	.605	1	0	12	.003	1	-.002	15
178			min	-1108.041	3	.297	15	-42.696	4	0	4	-.172	4	-.007	4
179		14	max	994.116	1	1.132	4	.605	1	0	12	.003	1	-.002	15
180			min	-1107.644	3	.281	15	-43.157	4	0	4	-.187	4	-.007	4
181		15	max	994.645	1	1.061	4	.605	1	0	12	.003	1	-.002	15
182			min	-1107.248	3	.262	12	-43.618	4	0	4	-.203	4	-.008	4
183		16	max	995.174	1	.99	4	.605	1	0	12	.003	1	-.002	15
184			min	-1106.851	3	.235	12	-44.08	4	0	4	-.219	4	-.008	4
185		17	max	995.704	1	.919	4	.605	1	0	12	.003	1	-.002	15
186			min	-1106.454	3	.207	12	-44.541	4	0	4	-.234	4	-.009	4
187		18	max	996.233	1	.848	4	.605	1	0	12	.004	1	-.002	15
188			min	-1106.057	3	.179	12	-45.002	4	0	4	-.251	4	-.009	4
189		19	max	996.762	1	.777	4	.605	1	0	12	.004	1	-.002	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
190			min	-1105.66	3	.152	12	-45.463	4	0	4	-.267	4	-.009	4
191	M3	1	max	576.657	2	8.9	4	1.931	4	0	12	0	1	.009	4
192			min	-734.806	3	2.103	15	.026	12	0	4	-.029	4	.002	15
193		2	max	576.487	2	8.031	4	2.536	4	0	12	0	1	.005	4
194			min	-734.933	3	1.899	15	.026	12	0	4	-.028	4	.001	12
195		3	max	576.316	2	7.162	4	3.141	4	0	12	0	1	.002	2
196			min	-735.061	3	1.695	15	.026	12	0	4	-.026	4	0	3
197		4	max	576.146	2	6.293	4	3.746	4	0	12	.001	1	0	15
198			min	-735.189	3	1.49	15	.026	12	0	4	-.025	4	-.002	3
199		5	max	575.976	2	5.424	4	4.351	4	0	12	.001	1	0	15
200			min	-735.317	3	1.286	15	.026	12	0	4	-.023	4	-.004	6
201		6	max	575.805	2	4.555	4	4.956	4	0	12	.002	1	-.002	15
202			min	-735.444	3	1.082	15	.026	12	0	4	-.021	5	-.007	6
203		7	max	575.635	2	3.686	4	5.561	4	0	12	.002	1	-.002	15
204			min	-735.572	3	.878	15	.026	12	0	4	-.018	5	-.009	6
205		8	max	575.465	2	2.818	4	6.166	4	0	12	.002	1	-.002	15
206			min	-735.7	3	.673	15	.026	12	0	4	-.016	5	-.01	6
207		9	max	575.294	2	1.949	4	6.771	4	0	12	.002	1	-.003	15
208			min	-735.828	3	.469	15	.026	12	0	4	-.013	5	-.011	6
209		10	max	575.124	2	1.08	4	7.377	4	0	12	.002	1	-.003	15
210			min	-735.955	3	.265	15	.026	12	0	4	-.009	5	-.012	6
211		11	max	574.954	2	.271	2	7.982	4	0	12	.003	1	-.003	15
212			min	-736.083	3	-.067	3	.026	12	0	4	-.006	5	-.012	6
213		12	max	574.783	2	-.144	15	8.587	4	0	12	.003	1	-.003	15
214			min	-736.211	3	-.659	6	.026	12	0	4	-.002	5	-.012	6
215		13	max	574.613	2	-.348	15	9.192	4	0	12	.003	1	-.003	15
216			min	-736.339	3	-1.528	6	.026	12	0	4	0	12	-.012	6
217		14	max	574.443	2	-.552	15	9.797	4	0	12	.007	4	-.003	15
218			min	-736.467	3	-2.397	6	.026	12	0	4	0	12	-.011	6
219		15	max	574.272	2	-.756	15	10.402	4	0	12	.012	4	-.002	15
220			min	-736.594	3	-3.266	6	.026	12	0	4	0	12	-.009	6
221		16	max	574.102	2	-.961	15	11.007	4	0	12	.017	4	-.002	15
222			min	-736.722	3	-4.135	6	.026	12	0	4	0	12	-.008	6
223		17	max	573.932	2	-1.165	15	11.612	4	0	12	.022	4	-.001	15
224			min	-736.85	3	-5.003	6	.026	12	0	4	0	12	-.006	6
225		18	max	573.761	2	-1.369	15	12.217	4	0	12	.028	4	0	15
226			min	-736.978	3	-5.872	6	.026	12	0	4	0	12	-.003	6
227		19	max	573.591	2	-1.573	15	12.822	4	0	12	.034	4	0	1
228			min	-737.105	3	-6.741	6	.026	12	0	4	0	12	0	1
229	M4	1	max	1105.103	1	0	1	-1.068	12	0	1	.027	4	0	1
230			min	-57.435	5	0	1	-334.056	4	0	1	0	12	0	1
231		2	max	1105.273	1	0	1	-1.068	12	0	1	.001	1	0	1
232			min	-57.356	5	0	1	-334.204	4	0	1	-.011	4	0	1
233		3	max	1105.444	1	0	1	-1.068	12	0	1	0	12	0	1
234			min	-57.276	5	0	1	-334.352	4	0	1	-.05	4	0	1
235		4	max	1105.614	1	0	1	-1.068	12	0	1	0	12	0	1
236			min	-57.197	5	0	1	-334.499	4	0	1	-.088	4	0	1
237		5	max	1105.784	1	0	1	-1.068	12	0	1	0	12	0	1
238			min	-57.117	5	0	1	-334.647	4	0	1	-.126	4	0	1
239		6	max	1105.955	1	0	1	-1.068	12	0	1	0	12	0	1
240			min	-57.038	5	0	1	-334.795	4	0	1	-.165	4	0	1
241		7	max	1106.125	1	0	1	-1.068	12	0	1	0	12	0	1
242			min	-56.958	5	0	1	-334.942	4	0	1	-.203	4	0	1
243		8	max	1106.295	1	0	1	-1.068	12	0	1	0	12	0	1
244			min	-56.879	5	0	1	-335.09	4	0	1	-.242	4	0	1
245		9	max	1106.466	1	0	1	-1.068	12	0	1	0	12	0	1
246			min	-56.799	5	0	1	-335.238	4	0	1	-.28	4	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
247		10	max	1106.636	1	0	1	-1.068	12	0	1	0	12	0	1
248			min	-56.72	5	0	1	-335.385	4	0	1	-.319	4	0	1
249		11	max	1106.806	1	0	1	-1.068	12	0	1	-.001	12	0	1
250			min	-56.64	5	0	1	-335.533	4	0	1	-.357	4	0	1
251		12	max	1106.977	1	0	1	-1.068	12	0	1	-.001	12	0	1
252			min	-56.561	5	0	1	-335.68	4	0	1	-.396	4	0	1
253		13	max	1107.147	1	0	1	-1.068	12	0	1	-.001	12	0	1
254			min	-56.481	5	0	1	-335.828	4	0	1	-.434	4	0	1
255		14	max	1107.317	1	0	1	-1.068	12	0	1	-.001	12	0	1
256			min	-56.402	5	0	1	-335.976	4	0	1	-.473	4	0	1
257		15	max	1107.488	1	0	1	-1.068	12	0	1	-.002	12	0	1
258			min	-56.322	5	0	1	-336.123	4	0	1	-.511	4	0	1
259		16	max	1107.658	1	0	1	-1.068	12	0	1	-.002	12	0	1
260			min	-56.243	5	0	1	-336.271	4	0	1	-.55	4	0	1
261		17	max	1107.828	1	0	1	-1.068	12	0	1	-.002	12	0	1
262			min	-56.163	5	0	1	-336.419	4	0	1	-.589	4	0	1
263		18	max	1107.999	1	0	1	-1.068	12	0	1	-.002	12	0	1
264			min	-56.084	5	0	1	-336.566	4	0	1	-.627	4	0	1
265		19	max	1108.169	1	0	1	-1.068	12	0	1	-.002	12	0	1
266			min	-56.004	5	0	1	-336.714	4	0	1	-.666	4	0	1
267	M6	1	max	3125.705	1	2.173	2	0	1	0	1	0	4	0	1
268			min	-3599.169	3	.352	12	-37.604	4	0	4	0	1	0	1
269		2	max	3126.235	1	2.118	2	0	1	0	1	0	1	0	12
270			min	-3598.772	3	.325	12	-38.065	4	0	4	-.014	4	0	2
271		3	max	3126.764	1	2.062	2	0	1	0	1	0	1	0	12
272			min	-3598.375	3	.297	12	-38.526	4	0	4	-.027	4	-.002	2
273		4	max	3127.293	1	2.007	2	0	1	0	1	0	1	0	12
274			min	-3597.978	3	.269	12	-38.987	4	0	4	-.041	4	-.002	2
275		5	max	3127.822	1	1.951	2	0	1	0	1	0	1	0	12
276			min	-3597.581	3	.242	12	-39.449	4	0	4	-.055	4	-.003	2
277		6	max	3128.352	1	1.896	2	0	1	0	1	0	1	0	12
278			min	-3597.184	3	.214	12	-39.91	4	0	4	-.07	4	-.004	2
279		7	max	3128.881	1	1.841	2	0	1	0	1	0	1	0	12
280			min	-3596.787	3	.186	12	-40.371	4	0	4	-.084	4	-.004	2
281		8	max	3129.41	1	1.785	2	0	1	0	1	0	1	0	12
282			min	-3596.39	3	.159	12	-40.832	4	0	4	-.098	4	-.005	2
283		9	max	3129.94	1	1.73	2	0	1	0	1	0	1	0	12
284			min	-3595.993	3	.123	3	-41.293	4	0	4	-.113	4	-.006	2
285		10	max	3130.469	1	1.675	2	0	1	0	1	0	1	0	12
286			min	-3595.596	3	.081	3	-41.755	4	0	4	-.128	4	-.006	2
287		11	max	3130.998	1	1.619	2	0	1	0	1	0	1	0	12
288			min	-3595.199	3	.04	3	-42.216	4	0	4	-.143	4	-.007	2
289		12	max	3131.527	1	1.564	2	0	1	0	1	0	1	0	12
290			min	-3594.802	3	-.002	3	-42.677	4	0	4	-.158	4	-.007	2
291		13	max	3132.057	1	1.509	2	0	1	0	1	0	1	0	12
292			min	-3594.405	3	-.043	3	-43.138	4	0	4	-.174	4	-.008	2
293		14	max	3132.586	1	1.453	2	0	1	0	1	0	1	0	12
294			min	-3594.008	3	-.085	3	-43.6	4	0	4	-.189	4	-.008	2
295		15	max	3133.115	1	1.398	2	0	1	0	1	0	1	0	12
296			min	-3593.611	3	-.126	3	-44.061	4	0	4	-.205	4	-.009	2
297		16	max	3133.645	1	1.343	2	0	1	0	1	0	1	0	3
298			min	-3593.214	3	-.168	3	-44.522	4	0	4	-.221	4	-.009	2
299		17	max	3134.174	1	1.287	2	0	1	0	1	0	1	0	3
300			min	-3592.817	3	-.209	3	-44.983	4	0	4	-.237	4	-.01	2
301		18	max	3134.703	1	1.232	2	0	1	0	1	0	1	0	3
302			min	-3592.42	3	-.251	3	-45.444	4	0	4	-.253	4	-.01	2
303		19	max	3135.232	1	1.177	2	0	1	0	1	0	1	0	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
304			min	-3592.023	3	-.292	3	-45.906	4	0	4	-.27	4	-.011	2
305	M7	1	max	2188.956	2	8.909	6	1.399	4	0	1	0	1	.011	2
306			min	-2272.423	3	2.091	15	0	1	0	4	-.029	4	0	3
307		2	max	2188.786	2	8.04	6	2.004	4	0	1	0	1	.008	2
308			min	-2272.551	3	1.887	15	0	1	0	4	-.028	4	-.002	3
309		3	max	2188.615	2	7.171	6	2.609	4	0	1	0	1	.005	2
310			min	-2272.678	3	1.683	15	0	1	0	4	-.027	4	-.003	3
311		4	max	2188.445	2	6.302	6	3.215	4	0	1	0	1	.002	2
312			min	-2272.806	3	1.479	15	0	1	0	4	-.026	4	-.005	3
313		5	max	2188.275	2	5.433	6	3.82	4	0	1	0	1	0	2
314			min	-2272.934	3	1.274	15	0	1	0	4	-.024	4	-.006	3
315		6	max	2188.104	2	4.564	6	4.425	4	0	1	0	1	-.002	15
316			min	-2273.062	3	1.07	15	0	1	0	4	-.022	4	-.007	3
317		7	max	2187.934	2	3.695	6	5.03	4	0	1	0	1	-.002	15
318			min	-2273.189	3	.866	15	0	1	0	4	-.02	4	-.009	4
319		8	max	2187.764	2	2.826	6	5.635	4	0	1	0	1	-.002	15
320			min	-2273.317	3	.662	15	0	1	0	4	-.017	4	-.01	4
321		9	max	2187.593	2	1.957	6	6.24	4	0	1	0	1	-.003	15
322			min	-2273.445	3	.417	12	0	1	0	4	-.015	4	-.011	4
323		10	max	2187.423	2	1.277	2	6.845	4	0	1	0	1	-.003	15
324			min	-2273.573	3	.062	3	0	1	0	4	-.011	4	-.012	4
325		11	max	2187.253	2	.6	2	7.45	4	0	1	0	1	-.003	15
326			min	-2273.701	3	-.446	3	0	1	0	4	-.008	4	-.012	4
327		12	max	2187.082	2	-.078	2	8.055	4	0	1	0	1	-.003	15
328			min	-2273.828	3	-.954	3	0	1	0	4	-.004	4	-.012	4
329		13	max	2186.912	2	-.359	15	8.66	4	0	1	0	1	-.003	15
330			min	-2273.956	3	-1.518	4	0	1	0	4	0	4	-.012	4
331		14	max	2186.742	2	-.564	15	9.265	4	0	1	.004	4	-.003	15
332			min	-2274.084	3	-2.387	4	0	1	0	4	0	1	-.011	4
333		15	max	2186.571	2	-.768	15	9.87	4	0	1	.008	4	-.002	15
334			min	-2274.212	3	-3.256	4	0	1	0	4	0	1	-.009	4
335		16	max	2186.401	2	-.972	15	10.475	4	0	1	.013	4	-.002	15
336			min	-2274.339	3	-4.125	4	0	1	0	4	0	1	-.008	4
337		17	max	2186.231	2	-1.176	15	11.08	4	0	1	.018	4	-.001	15
338			min	-2274.467	3	-4.994	4	0	1	0	4	0	1	-.006	4
339		18	max	2186.06	2	-1.381	15	11.686	4	0	1	.023	4	0	15
340			min	-2274.595	3	-5.863	4	0	1	0	4	0	1	-.003	4
341		19	max	2185.89	2	-1.585	15	12.291	4	0	1	.029	4	0	1
342			min	-2274.723	3	-6.732	4	0	1	0	4	0	1	0	1
343	M8	1	max	2815.391	1	0	1	0	1	0	1	.023	4	0	1
344			min	-69.768	3	0	1	-317.409	4	0	1	0	1	0	1
345		2	max	2815.561	1	0	1	0	1	0	1	0	1	0	1
346			min	-69.64	3	0	1	-317.556	4	0	1	-.013	4	0	1
347		3	max	2815.732	1	0	1	0	1	0	1	0	1	0	1
348			min	-69.512	3	0	1	-317.704	4	0	1	-.05	4	0	1
349		4	max	2815.902	1	0	1	0	1	0	1	0	1	0	1
350			min	-69.385	3	0	1	-317.852	4	0	1	-.086	4	0	1
351		5	max	2816.072	1	0	1	0	1	0	1	0	1	0	1
352			min	-69.257	3	0	1	-317.999	4	0	1	-.123	4	0	1
353		6	max	2816.243	1	0	1	0	1	0	1	0	1	0	1
354			min	-69.129	3	0	1	-318.147	4	0	1	-.159	4	0	1
355		7	max	2816.413	1	0	1	0	1	0	1	0	1	0	1
356			min	-69.001	3	0	1	-318.295	4	0	1	-.196	4	0	1
357		8	max	2816.583	1	0	1	0	1	0	1	0	1	0	1
358			min	-68.874	3	0	1	-318.442	4	0	1	-.232	4	0	1
359		9	max	2816.754	1	0	1	0	1	0	1	0	1	0	1
360			min	-68.746	3	0	1	-318.59	4	0	1	-.269	4	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
361		10	max	2816.924	1	0	1	0	1	0	1	0	1	0	1
362			min	-68.618	3	0	1	-318.738	4	0	1	-.305	4	0	1
363		11	max	2817.094	1	0	1	0	1	0	1	0	1	0	1
364			min	-68.49	3	0	1	-318.885	4	0	1	-.342	4	0	1
365		12	max	2817.265	1	0	1	0	1	0	1	0	1	0	1
366			min	-68.363	3	0	1	-319.033	4	0	1	-.379	4	0	1
367		13	max	2817.435	1	0	1	0	1	0	1	0	1	0	1
368			min	-68.235	3	0	1	-319.18	4	0	1	-.415	4	0	1
369		14	max	2817.605	1	0	1	0	1	0	1	0	1	0	1
370			min	-68.107	3	0	1	-319.328	4	0	1	-.452	4	0	1
371		15	max	2817.776	1	0	1	0	1	0	1	0	1	0	1
372			min	-67.979	3	0	1	-319.476	4	0	1	-.489	4	0	1
373		16	max	2817.946	1	0	1	0	1	0	1	0	1	0	1
374			min	-67.851	3	0	1	-319.623	4	0	1	-.525	4	0	1
375		17	max	2818.117	1	0	1	0	1	0	1	0	1	0	1
376			min	-67.724	3	0	1	-319.771	4	0	1	-.562	4	0	1
377		18	max	2818.287	1	0	1	0	1	0	1	0	1	0	1
378			min	-67.596	3	0	1	-319.919	4	0	1	-.599	4	0	1
379		19	max	2818.457	1	0	1	0	1	0	1	0	1	0	1
380			min	-67.468	3	0	1	-320.066	4	0	1	-.635	4	0	1
381	M10	1	max	987.235	1	1.99	6	-.034	12	0	1	0	4	0	1
382			min	-1112.805	3	.453	15	-37.53	4	0	5	0	3	0	1
383		2	max	987.764	1	1.919	6	-.034	12	0	1	0	10	0	15
384			min	-1112.408	3	.437	15	-37.992	4	0	5	-.014	4	0	6
385		3	max	988.294	1	1.848	6	-.034	12	0	1	0	12	0	15
386			min	-1112.011	3	.42	15	-38.453	4	0	5	-.027	4	-.001	6
387		4	max	988.823	1	1.777	6	-.034	12	0	1	0	12	0	15
388			min	-1111.614	3	.403	15	-38.914	4	0	5	-.041	4	-.002	6
389		5	max	989.352	1	1.706	6	-.034	12	0	1	0	12	0	15
390			min	-1111.217	3	.387	15	-39.375	4	0	5	-.055	4	-.003	6
391		6	max	989.881	1	1.634	6	-.034	12	0	1	0	12	0	15
392			min	-1110.82	3	.37	15	-39.836	4	0	5	-.069	4	-.003	6
393		7	max	990.411	1	1.563	6	-.034	12	0	1	0	12	0	15
394			min	-1110.423	3	.353	15	-40.298	4	0	5	-.084	4	-.004	6
395		8	max	990.94	1	1.492	6	-.034	12	0	1	0	12	0	15
396			min	-1110.026	3	.337	15	-40.759	4	0	5	-.098	4	-.004	6
397		9	max	991.469	1	1.421	6	-.034	12	0	1	0	12	-.001	15
398			min	-1109.629	3	.32	15	-41.22	4	0	5	-.113	4	-.005	6
399		10	max	991.999	1	1.35	6	-.034	12	0	1	0	12	-.001	15
400			min	-1109.232	3	.303	15	-41.681	4	0	5	-.128	4	-.005	6
401		11	max	992.528	1	1.279	6	-.034	12	0	1	0	12	-.001	15
402			min	-1108.835	3	.286	15	-42.143	4	0	5	-.143	4	-.006	6
403		12	max	993.057	1	1.208	6	-.034	12	0	1	0	12	-.001	15
404			min	-1108.438	3	.27	15	-42.604	4	0	5	-.158	4	-.006	6
405		13	max	993.586	1	1.137	6	-.034	12	0	1	0	12	-.002	15
406			min	-1108.041	3	.253	15	-43.065	4	0	5	-.173	4	-.007	6
407		14	max	994.116	1	1.066	6	-.034	12	0	1	0	12	-.002	15
408			min	-1107.644	3	.236	15	-43.526	4	0	5	-.189	4	-.007	6
409		15	max	994.645	1	.995	6	-.034	12	0	1	0	12	-.002	15
410			min	-1107.248	3	.22	15	-43.987	4	0	5	-.205	4	-.007	6
411		16	max	995.174	1	.924	6	-.034	12	0	1	0	12	-.002	15
412			min	-1106.851	3	.203	15	-44.449	4	0	5	-.221	4	-.008	6
413		17	max	995.704	1	.857	2	-.034	12	0	1	0	12	-.002	15
414			min	-1106.454	3	.186	15	-44.91	4	0	5	-.237	4	-.008	6
415		18	max	996.233	1	.801	2	-.034	12	0	1	0	12	-.002	15
416			min	-1106.057	3	.17	15	-45.371	4	0	5	-.253	4	-.008	6
417		19	max	996.762	1	.746	2	-.034	12	0	1	0	12	-.002	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
418			min	-1105.66	3	.152	12	-45.832	4	0	5	-.269	4	-.009	6
419	M11	1	max	576.657	2	8.849	6	1.645	5	0	1	0	12	.009	6
420			min	-734.806	3	2.069	15	-.472	1	0	4	-.029	4	.002	15
421		2	max	576.487	2	7.98	6	2.251	5	0	1	0	12	.005	2
422			min	-734.933	3	1.865	15	-.472	1	0	4	-.028	4	.001	15
423		3	max	576.316	2	7.112	6	2.856	5	0	1	0	12	.002	2
424			min	-735.061	3	1.661	15	-.472	1	0	4	-.027	4	0	3
425		4	max	576.146	2	6.243	6	3.461	5	0	1	0	12	0	2
426			min	-735.189	3	1.457	15	-.472	1	0	4	-.025	4	-.002	3
427		5	max	575.976	2	5.374	6	4.066	5	0	1	0	12	-.001	15
428			min	-735.317	3	1.252	15	-.472	1	0	4	-.023	4	-.005	4
429		6	max	575.805	2	4.505	6	4.671	5	0	1	0	12	-.002	15
430			min	-735.444	3	1.048	15	-.472	1	0	4	-.021	4	-.007	4
431		7	max	575.635	2	3.636	6	5.276	5	0	1	0	12	-.002	15
432			min	-735.572	3	.844	15	-.472	1	0	4	-.019	4	-.009	4
433		8	max	575.465	2	2.767	6	5.881	5	0	1	0	12	-.003	15
434			min	-735.7	3	.64	15	-.472	1	0	4	-.016	4	-.01	4
435		9	max	575.294	2	1.898	6	6.486	5	0	1	0	12	-.003	15
436			min	-735.828	3	.435	15	-.472	1	0	4	-.014	4	-.012	4
437		10	max	575.124	2	1.029	6	7.091	5	0	1	0	12	-.003	15
438			min	-735.955	3	.231	15	-.472	1	0	4	-.01	4	-.012	4
439		11	max	574.954	2	.271	2	7.696	5	0	1	0	12	-.003	15
440			min	-736.083	3	-.067	3	-.472	1	0	4	-.007	4	-.012	4
441		12	max	574.783	2	-.177	15	8.301	5	0	1	0	12	-.003	15
442			min	-736.211	3	-.709	4	-.472	1	0	4	-.003	4	-.012	4
443		13	max	574.613	2	-.382	15	8.906	5	0	1	.002	5	-.003	15
444			min	-736.339	3	-1.578	4	-.472	1	0	4	-.003	1	-.012	4
445		14	max	574.443	2	-.586	15	9.511	5	0	1	.006	5	-.003	15
446			min	-736.467	3	-2.447	4	-.472	1	0	4	-.003	1	-.011	4
447		15	max	574.272	2	-.79	15	10.116	5	0	1	.011	5	-.002	15
448			min	-736.594	3	-3.316	4	-.472	1	0	4	-.004	1	-.01	4
449		16	max	574.102	2	-.994	15	10.722	5	0	1	.015	5	-.002	15
450			min	-736.722	3	-4.185	4	-.472	1	0	4	-.004	1	-.008	4
451		17	max	573.932	2	-1.199	15	11.327	5	0	1	.021	5	-.001	15
452			min	-736.85	3	-5.054	4	-.472	1	0	4	-.004	1	-.006	4
453		18	max	573.761	2	-1.403	15	11.932	5	0	1	.026	5	0	15
454			min	-736.978	3	-5.923	4	-.472	1	0	4	-.004	1	-.003	4
455		19	max	573.591	2	-1.607	15	12.537	5	0	1	.032	5	0	1
456			min	-737.105	3	-6.792	4	-.472	1	0	4	-.004	1	0	1
457	M12	1	max	1105.103	1	0	1	19.328	1	0	1	.026	5	0	1
458			min	8.967	3	0	1	-322.21	4	0	1	-.004	1	0	1
459		2	max	1105.273	1	0	1	19.328	1	0	1	0	12	0	1
460			min	9.095	3	0	1	-322.357	4	0	1	-.012	4	0	1
461		3	max	1105.444	1	0	1	19.328	1	0	1	0	1	0	1
462			min	9.223	3	0	1	-322.505	4	0	1	-.049	4	0	1
463		4	max	1105.614	1	0	1	19.328	1	0	1	.003	1	0	1
464			min	9.35	3	0	1	-322.653	4	0	1	-.086	4	0	1
465		5	max	1105.784	1	0	1	19.328	1	0	1	.005	1	0	1
466			min	9.478	3	0	1	-322.8	4	0	1	-.123	4	0	1
467		6	max	1105.955	1	0	1	19.328	1	0	1	.008	1	0	1
468			min	9.606	3	0	1	-322.948	4	0	1	-.16	4	0	1
469		7	max	1106.125	1	0	1	19.328	1	0	1	.01	1	0	1
470			min	9.734	3	0	1	-323.096	4	0	1	-.197	4	0	1
471		8	max	1106.295	1	0	1	19.328	1	0	1	.012	1	0	1
472			min	9.861	3	0	1	-323.243	4	0	1	-.234	4	0	1
473		9	max	1106.466	1	0	1	19.328	1	0	1	.014	1	0	1
474			min	9.989	3	0	1	-323.391	4	0	1	-.271	4	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
475		10	max	1106.636	1	0	1	19.328	1	0	1	.016	1	0	1
476			min	10.117	3	0	1	-323.539	4	0	1	-.309	4	0	1
477		11	max	1106.806	1	0	1	19.328	1	0	1	.019	1	0	1
478			min	10.245	3	0	1	-323.686	4	0	1	-.346	4	0	1
479		12	max	1106.977	1	0	1	19.328	1	0	1	.021	1	0	1
480			min	10.372	3	0	1	-323.834	4	0	1	-.383	4	0	1
481		13	max	1107.147	1	0	1	19.328	1	0	1	.023	1	0	1
482			min	10.5	3	0	1	-323.981	4	0	1	-.42	4	0	1
483		14	max	1107.317	1	0	1	19.328	1	0	1	.025	1	0	1
484			min	10.628	3	0	1	-324.129	4	0	1	-.457	4	0	1
485		15	max	1107.488	1	0	1	19.328	1	0	1	.028	1	0	1
486			min	10.756	3	0	1	-324.277	4	0	1	-.495	4	0	1
487		16	max	1107.658	1	0	1	19.328	1	0	1	.03	1	0	1
488			min	10.883	3	0	1	-324.424	4	0	1	-.532	4	0	1
489		17	max	1107.828	1	0	1	19.328	1	0	1	.032	1	0	1
490			min	11.011	3	0	1	-324.572	4	0	1	-.569	4	0	1
491		18	max	1107.999	1	0	1	19.328	1	0	1	.034	1	0	1
492			min	11.139	3	0	1	-324.72	4	0	1	-.606	4	0	1
493		19	max	1108.169	1	0	1	19.328	1	0	1	.036	1	0	1
494			min	11.267	3	0	1	-324.867	4	0	1	-.644	4	0	1
495	M1	1	max	211.552	1	587.636	3	54.5	5	0	1	.304	1	0	3
496			min	-15.542	5	-413.278	1	-107.925	1	0	3	-.138	5	-.014	2
497		2	max	212.395	1	586.542	3	55.961	5	0	1	.237	1	.243	1
498			min	-15.149	5	-414.737	1	-107.925	1	0	3	-.104	5	-.365	3
499		3	max	471.337	3	481.346	1	21.5	5	0	3	.17	1	.491	1
500			min	-289.887	2	-434.008	3	-107.653	1	0	1	-.069	5	-.717	3
501		4	max	471.969	3	479.887	1	22.96	5	0	3	.103	1	.193	1
502			min	-289.044	2	-435.103	3	-107.653	1	0	1	-.055	5	-.447	3
503		5	max	472.601	3	478.428	1	24.42	5	0	3	.036	1	-.005	15
504			min	-288.202	2	-436.197	3	-107.653	1	0	1	-.041	5	-.177	3
505		6	max	473.232	3	476.969	1	25.88	5	0	3	-.002	12	.094	3
506			min	-287.36	2	-437.291	3	-107.653	1	0	1	-.032	4	-.412	2
507		7	max	473.864	3	475.51	1	27.341	5	0	3	-.006	12	.366	3
508			min	-286.517	2	-438.386	3	-107.653	1	0	1	-.097	1	-.698	2
509		8	max	474.496	3	474.051	1	28.801	5	0	3	.009	5	.638	3
510			min	-285.675	2	-439.48	3	-107.653	1	0	1	-.164	1	-.991	1
511		9	max	491.887	3	41.668	2	71.407	5	0	9	.101	1	.746	3
512			min	-193.969	2	.439	15	-166.343	1	0	3	-.172	5	-1.13	1
513		10	max	492.519	3	40.209	2	72.867	5	0	9	0	12	.727	3
514			min	-193.126	2	-.004	5	-166.343	1	0	3	-.129	4	-1.15	2
515		11	max	493.15	3	38.75	2	74.327	5	0	9	-.006	12	.71	3
516			min	-192.284	2	-1.791	4	-166.343	1	0	3	-.106	4	-1.175	2
517		12	max	510.43	3	288.848	3	186.806	5	0	2	.161	1	.619	3
518			min	-109.299	5	-544.473	2	-103.534	1	0	3	-.291	5	-1.041	2
519		13	max	511.062	3	287.753	3	188.266	5	0	2	.096	1	.44	3
520			min	-108.906	5	-545.932	2	-103.534	1	0	3	-.175	5	-.702	2
521		14	max	511.694	3	286.659	3	189.726	5	0	2	.032	1	.262	3
522			min	-108.513	5	-547.391	2	-103.534	1	0	3	-.058	5	-.376	1
523		15	max	512.325	3	285.565	3	191.186	5	0	2	.061	5	.084	3
524			min	-108.12	5	-548.85	2	-103.534	1	0	3	-.032	1	-.052	1
525		16	max	512.957	3	284.47	3	192.646	5	0	2	.18	5	.318	2
526			min	-107.726	5	-550.309	2	-103.534	1	0	3	-.096	1	-.093	3
527		17	max	513.589	3	283.376	3	194.106	5	0	2	.3	5	.66	2
528			min	-107.333	5	-551.768	2	-103.534	1	0	3	-.161	1	-.269	3
529		18	max	26.537	5	549.686	2	-6.822	12	0	5	.268	5	.331	2
530			min	-212.863	1	-230.142	3	-144.597	4	0	2	-.231	1	-.132	3
531		19	max	26.931	5	548.227	2	-6.822	12	0	5	.197	5	.011	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
532			min	-212.021	1	-231.237	3	-143.137	4	0	2	-.307	1	-.011	1
533	M5	1	max	462.917	1	1957.171	3	111.683	5	0	1	0	1	.029	2
534			min	20.271	12	-1408.3	1	0	1	0	4	-.301	4	0	3
535		2	max	463.759	1	1956.077	3	113.143	5	0	1	0	1	.902	1
536			min	20.692	12	-1409.759	1	0	1	0	4	-.232	4	-1.214	3
537		3	max	1495.667	3	1406.958	1	83.441	4	0	4	0	1	1.746	1
538			min	-1005.433	2	-1362.61	3	0	1	0	1	-.162	4	-2.391	3
539		4	max	1496.298	3	1405.499	1	84.901	4	0	4	0	1	.873	1
540			min	-1004.59	2	-1363.704	3	0	1	0	1	-.109	4	-1.545	3
541		5	max	1496.93	3	1404.04	1	86.361	4	0	4	0	1	.024	9
542			min	-1003.748	2	-1364.798	3	0	1	0	1	-.056	4	-.699	3
543		6	max	1497.562	3	1402.581	1	87.821	4	0	4	0	1	.149	3
544			min	-1002.906	2	-1365.893	3	0	1	0	1	-.002	5	-.894	2
545		7	max	1498.194	3	1401.122	1	89.281	4	0	4	.053	4	.997	3
546			min	-1002.063	2	-1366.987	3	0	1	0	1	0	1	-1.739	1
547		8	max	1498.826	3	1399.663	1	90.741	4	0	4	.109	4	1.845	3
548			min	-1001.221	2	-1368.081	3	0	1	0	1	0	1	-2.609	1
549		9	max	1528.562	3	139.322	2	238.981	4	0	1	0	1	2.126	3
550			min	-811.61	2	.445	15	0	1	0	1	-.262	4	-2.96	1
551		10	max	1529.194	3	137.863	2	240.442	4	0	1	0	1	2.059	3
552			min	-810.768	2	.005	15	0	1	0	1	-.114	4	-3.015	2
553		11	max	1529.826	3	136.403	2	241.902	4	0	1	.036	4	1.992	3
554			min	-809.925	2	-1.458	6	0	1	0	1	0	1	-3.1	2
555		12	max	1559.786	3	887.367	3	265.718	4	0	1	0	1	1.748	3
556			min	-620.332	2	-1627.212	2	0	1	0	4	-.426	4	-2.772	2
557		13	max	1560.417	3	886.273	3	267.178	4	0	1	0	1	1.198	3
558			min	-619.49	2	-1628.671	2	0	1	0	4	-.26	4	-1.761	2
559		14	max	1561.049	3	885.179	3	268.638	4	0	1	0	1	.648	3
560			min	-618.648	2	-1630.13	2	0	1	0	4	-.094	4	-.794	1
561		15	max	1561.681	3	884.084	3	270.098	4	0	1	.073	4	.262	2
562			min	-617.805	2	-1631.589	2	0	1	0	4	0	1	0	13
563		16	max	1562.313	3	882.99	3	271.558	4	0	1	.241	4	1.275	2
564			min	-616.963	2	-1633.048	2	0	1	0	4	0	1	-.449	3
565		17	max	1562.945	3	881.896	3	273.018	4	0	1	.41	4	2.289	2
566			min	-616.12	2	-1634.507	2	0	1	0	4	0	1	-.997	3
567		18	max	-21.091	12	1858.889	2	0	1	0	4	.429	4	1.173	2
568			min	-462.823	1	-800.047	3	-28.098	5	0	1	0	1	-.519	3
569		19	max	-20.67	12	1857.43	2	0	1	0	4	.413	4	.023	1
570			min	-461.98	1	-801.141	3	-26.638	5	0	1	0	1	-.022	3
571	M9	1	max	211.552	1	587.636	3	107.925	1	0	3	-.018	12	0	3
572			min	10.739	12	-413.278	1	6.375	12	0	4	-.304	1	-.014	2
573		2	max	212.395	1	586.542	3	107.925	1	0	3	-.014	12	.243	1
574			min	11.16	12	-414.737	1	6.375	12	0	4	-.237	1	-.365	3
575		3	max	471.337	3	481.346	1	107.653	1	0	1	-.01	12	.491	1
576			min	-289.887	2	-434.008	3	6.342	12	0	3	-.17	1	-.717	3
577		4	max	471.969	3	479.887	1	107.653	1	0	1	-.006	12	.193	1
578			min	-289.044	2	-435.103	3	6.342	12	0	3	-.103	1	-.447	3
579		5	max	472.601	3	478.428	1	107.653	1	0	1	-.002	12	-.005	15
580			min	-288.202	2	-436.197	3	6.342	12	0	3	-.055	4	-.177	3
581		6	max	473.232	3	476.969	1	107.653	1	0	1	.031	1	.094	3
582			min	-287.36	2	-437.291	3	6.342	12	0	3	-.021	5	-.412	2
583		7	max	473.864	3	475.51	1	107.653	1	0	1	.097	1	.366	3
584			min	-286.517	2	-438.386	3	6.342	12	0	3	.003	15	-.698	2
585		8	max	474.496	3	474.051	1	107.653	1	0	1	.164	1	.638	3
586			min	-285.675	2	-439.48	3	6.342	12	0	3	.01	12	-.991	1
587		9	max	491.887	3	41.668	2	166.343	1	0	3	-.006	12	.746	3
588			min	-193.969	2	.454	15	9.549	12	0	9	-.212	4	-1.13	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
589		10	max	492.519	3	40.209	2	166.343	1	0	3	.002	1	.727	3
590			min	-193.126	2	.013	15	9.549	12	0	9	-.127	4	-1.15	2
591		11	max	493.15	3	38.75	2	166.343	1	0	3	.105	1	.71	3
592			min	-192.284	2	-1.676	6	9.549	12	0	9	-.066	5	-1.175	2
593		12	max	510.43	3	288.848	3	229.476	4	0	3	-.009	12	.619	3
594			min	-106.691	10	-544.473	2	5.783	12	0	2	-.357	4	-1.041	2
595		13	max	511.062	3	287.753	3	230.936	4	0	3	-.005	12	.44	3
596			min	-105.989	10	-545.932	2	5.783	12	0	2	-.214	4	-.702	2
597		14	max	511.694	3	286.659	3	232.396	4	0	3	-.002	12	.262	3
598			min	-105.287	10	-547.391	2	5.783	12	0	2	-.07	4	-.376	1
599		15	max	512.325	3	285.565	3	233.857	4	0	3	.074	4	.084	3
600			min	-104.585	10	-548.85	2	5.783	12	0	2	.002	12	-.052	1
601		16	max	512.957	3	284.47	3	235.317	4	0	3	.22	4	.318	2
602			min	-103.883	10	-550.309	2	5.783	12	0	2	.005	12	-.093	3
603		17	max	513.589	3	283.376	3	236.777	4	0	3	.367	4	.66	2
604			min	-103.181	10	-551.768	2	5.783	12	0	2	.009	12	-.269	3
605		18	max	-10.961	12	549.686	2	121.909	1	0	2	.36	4	.331	2
606			min	-212.863	1	-230.142	3	-97.887	5	0	3	.013	12	-.132	3
607		19	max	-10.539	12	548.227	2	121.909	1	0	2	.317	4	.011	3
608			min	-212.021	1	-231.237	3	-96.427	5	0	3	.017	12	-.011	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M13	1	max	.001	1	.168	2	.009	3	1.154e-2	2	NC	1	NC	1
2			min	-1.035	4	-.032	3	-.005	2	-2.238e-3	3	NC	1	NC	1
3		2	max	0	1	.247	3	.052	1	1.294e-2	2	NC	5	NC	2
4			min	-1.035	4	-.01	9	-.031	5	-2.222e-3	3	861.292	3	4779.372	1
5		3	max	0	1	.473	3	.122	1	1.434e-2	2	NC	5	NC	3
6			min	-1.035	4	-.139	1	-.037	5	-2.207e-3	3	475.83	3	1995.947	1
7		4	max	0	1	.61	3	.181	1	1.575e-2	2	NC	5	NC	3
8			min	-1.035	4	-.211	1	-.027	5	-2.192e-3	3	374.043	3	1333.605	1
9		5	max	0	1	.642	3	.211	1	1.715e-2	2	NC	5	NC	3
10			min	-1.035	4	-.208	1	-.007	5	-2.177e-3	3	356.185	3	1142.745	1
11		6	max	0	1	.571	3	.203	1	1.855e-2	2	NC	5	NC	5
12			min	-1.035	4	-.135	1	.009	15	-2.162e-3	3	397.861	3	1189.131	1
13		7	max	0	1	.419	3	.159	1	1.995e-2	2	NC	5	NC	10
14			min	-1.035	4	-.016	9	.011	10	-2.146e-3	3	531.946	3	1523.189	1
15		8	max	0	1	.226	3	.092	1	2.135e-2	2	NC	1	NC	3
16			min	-1.035	4	.005	15	.001	10	-2.131e-3	3	930.688	3	2661.529	1
17		9	max	0	1	.296	2	.038	4	2.275e-2	2	NC	4	NC	1
18			min	-1.035	4	.009	15	-.008	10	-2.116e-3	3	1874.406	2	6252.889	4
19		10	max	0	1	.352	2	.028	3	2.415e-2	2	NC	3	NC	1
20			min	-1.035	4	-.029	3	-.019	2	-2.101e-3	3	1304.804	2	NC	1
21		11	max	0	12	.296	2	.03	3	2.275e-2	2	NC	4	NC	1
22			min	-1.035	4	.009	15	-.024	5	-2.116e-3	3	1874.406	2	NC	1
23		12	max	0	12	.226	3	.092	1	2.135e-2	2	NC	1	NC	3
24			min	-1.035	4	.005	15	-.023	5	-2.131e-3	3	930.688	3	2661.529	1
25		13	max	0	12	.419	3	.159	1	1.995e-2	2	NC	5	NC	5
26			min	-1.035	4	-.016	9	-.007	5	-2.146e-3	3	531.946	3	1523.189	1
27		14	max	0	12	.571	3	.203	1	1.855e-2	2	NC	5	NC	5
28			min	-1.035	4	-.135	1	.01	15	-2.162e-3	3	397.861	3	1189.131	1
29		15	max	0	12	.642	3	.211	1	1.715e-2	2	NC	5	NC	3
30			min	-1.035	4	-.208	1	.02	10	-2.177e-3	3	356.185	3	1142.745	1
31		16	max	0	12	.61	3	.181	1	1.575e-2	2	NC	5	NC	3
32			min	-1.035	4	-.211	1	.017	10	-2.192e-3	3	374.043	3	1333.605	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
33		17	max	0	12	.473	3	.122	1	1.434e-2	2	NC	5	NC	3
34			min	-1.035	4	-.139	1	.011	10	-2.207e-3	3	475.83	3	1995.947	1
35		18	max	0	12	.247	3	.052	4	1.294e-2	2	NC	5	NC	2
36			min	-1.035	4	-.01	9	.003	10	-2.222e-3	3	861.292	3	4527.551	4
37		19	max	0	12	.168	2	.009	3	1.154e-2	2	NC	1	NC	1
38			min	-1.035	4	-.032	3	-.005	2	-2.238e-3	3	NC	1	NC	1
39	M14	1	max	0	1	.308	3	.008	3	6.696e-3	1	NC	1	NC	1
40			min	-.748	4	-.518	2	-.004	2	-4.668e-3	3	NC	1	NC	1
41		2	max	0	1	.609	3	.034	1	7.903e-3	1	NC	5	NC	2
42			min	-.748	4	-.846	1	-.046	5	-5.616e-3	3	723.801	1	5462.987	5
43		3	max	0	1	.868	3	.095	1	9.11e-3	1	NC	15	NC	3
44			min	-.748	4	-1.136	1	-.055	5	-6.564e-3	3	385.928	1	2563.613	1
45		4	max	0	1	1.055	3	.152	1	1.032e-2	1	9324.955	15	NC	3
46			min	-.748	4	-1.356	1	-.038	5	-7.512e-3	3	285.009	1	1592.049	1
47		5	max	0	1	1.155	3	.185	1	1.152e-2	1	8068.611	15	NC	3
48			min	-.748	4	-1.491	1	-.007	5	-8.46e-3	3	245.651	1	1310.324	1
49		6	max	0	1	1.168	3	.182	1	1.273e-2	1	7732.605	15	NC	3
50			min	-.748	4	-1.539	1	.016	10	-9.407e-3	3	234.134	1	1328.83	1
51		7	max	0	1	1.109	3	.145	1	1.394e-2	1	7999.255	15	NC	3
52			min	-.748	4	-1.512	1	.01	10	-1.036e-2	3	240.412	1	1671.074	1
53		8	max	0	1	1.004	3	.088	4	1.515e-2	1	8740.244	15	NC	3
54			min	-.748	4	-1.436	1	.002	10	-1.13e-2	3	260.204	1	2703.512	4
55		9	max	0	1	.898	3	.058	4	1.635e-2	1	9734.342	15	NC	1
56			min	-.748	4	-1.351	1	-.007	10	-1.225e-2	3	286.901	1	4068.488	4
57		10	max	0	1	.847	3	.025	3	1.756e-2	1	NC	15	NC	1
58			min	-.748	4	-1.311	2	-.017	2	-1.32e-2	3	302.386	1	NC	1
59		11	max	0	12	.898	3	.026	3	1.635e-2	1	9734.306	15	NC	1
60			min	-.748	4	-1.351	1	-.045	5	-1.225e-2	3	286.901	1	5580.726	5
61		12	max	0	12	1.004	3	.085	1	1.515e-2	1	8740.14	15	NC	3
62			min	-.748	4	-1.436	1	-.051	5	-1.13e-2	3	260.204	1	2874.906	1
63		13	max	0	12	1.109	3	.145	1	1.394e-2	1	7999.085	15	NC	3
64			min	-.748	4	-1.512	1	-.033	5	-1.036e-2	3	240.412	1	1671.074	1
65		14	max	0	12	1.168	3	.182	1	1.273e-2	1	7732.367	15	NC	3
66			min	-.748	4	-1.539	1	0	15	-9.407e-3	3	234.134	1	1328.83	1
67		15	max	0	12	1.155	3	.185	1	1.152e-2	1	8068.287	15	NC	3
68			min	-.748	4	-1.491	1	.018	10	-8.46e-3	3	245.651	1	1310.324	1
69		16	max	0	12	1.055	3	.152	1	1.032e-2	1	9324.488	15	NC	3
70			min	-.748	4	-1.356	1	.014	10	-7.512e-3	3	285.009	1	1592.049	1
71		17	max	0	12	.868	3	.095	1	9.11e-3	1	NC	15	NC	3
72			min	-.748	4	-1.136	1	.008	10	-6.564e-3	3	385.928	1	2551.469	4
73		18	max	0	12	.609	3	.061	4	7.903e-3	1	NC	5	NC	2
74			min	-.748	4	-.846	1	0	10	-5.616e-3	3	723.801	1	3898.992	4
75		19	max	0	12	.308	3	.008	3	6.696e-3	1	NC	1	NC	1
76			min	-.748	4	-.518	2	-.004	2	-4.668e-3	3	NC	1	NC	1
77	M15	1	max	0	12	.315	3	.008	3	3.966e-3	3	NC	1	NC	1
78			min	-.592	4	-.517	2	-.004	2	-6.954e-3	2	NC	1	NC	1
79		2	max	0	12	.518	3	.035	1	4.773e-3	3	NC	5	NC	2
80			min	-.592	4	-.91	2	-.061	5	-8.21e-3	2	610.375	2	4055.39	5
81		3	max	0	12	.698	3	.096	1	5.581e-3	3	NC	15	NC	3
82			min	-.592	4	-1.25	2	-.074	5	-9.467e-3	2	327.262	2	2550.841	1
83		4	max	0	12	.838	3	.153	1	6.388e-3	3	9340.673	15	NC	3
84			min	-.592	4	-1.501	2	-.054	5	-1.072e-2	2	243.961	2	1585.994	1
85		5	max	0	12	.928	3	.185	1	7.195e-3	3	8083.857	15	NC	3
86			min	-.592	4	-1.642	2	-.014	5	-1.198e-2	2	213.229	2	1305.906	1
87		6	max	0	12	.969	3	.183	1	8.002e-3	3	7749.439	15	NC	3
88			min	-.592	4	-1.675	2	.016	10	-1.324e-2	2	207.314	2	1324.299	1
89		7	max	0	12	.964	3	.146	1	8.809e-3	3	8019.811	15	NC	3

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
90			min	-.592	4	-1.614	2	.011	10	-1.449e-2	2	218.802	2	1664.268	1
91		8	max	0	12	.93	3	.104	4	9.616e-3	3	8767.111	15	NC	3
92			min	-.592	4	-1.495	2	.002	10	-1.575e-2	2	245.446	2	2297.445	4
93		9	max	0	12	.888	3	.071	4	1.042e-2	3	9769.52	15	NC	1
94			min	-.592	4	-1.37	2	-.006	10	-1.701e-2	2	281.396	2	3335.125	4
95		10	max	0	1	.865	3	.023	3	1.123e-2	3	NC	15	NC	1
96			min	-.592	4	-1.309	2	-.016	2	-1.826e-2	2	302.887	2	NC	1
97		11	max	0	1	.888	3	.025	3	1.042e-2	3	9769.489	15	NC	1
98			min	-.592	4	-1.37	2	-.058	5	-1.701e-2	2	281.396	2	4278.464	5
99		12	max	0	1	.93	3	.086	1	9.616e-3	3	8767.032	15	NC	3
100			min	-.592	4	-1.495	2	-.067	5	-1.575e-2	2	245.446	2	2856.274	1
101		13	max	0	1	.964	3	.146	1	8.809e-3	3	8019.689	15	NC	3
102			min	-.592	4	-1.614	2	-.044	5	-1.449e-2	2	218.802	2	1664.268	1
103		14	max	0	1	.969	3	.183	1	8.002e-3	3	7749.272	15	NC	3
104			min	-.592	4	-1.675	2	-.003	5	-1.324e-2	2	207.314	2	1324.299	1
105		15	max	0	1	.928	3	.185	1	7.195e-3	3	8083.632	15	NC	3
106			min	-.592	4	-1.642	2	.017	12	-1.198e-2	2	213.229	2	1305.906	1
107		16	max	0	1	.838	3	.153	1	6.388e-3	3	9340.351	15	NC	3
108			min	-.592	4	-1.501	2	.014	12	-1.072e-2	2	243.961	2	1585.994	1
109		17	max	0	1	.698	3	.113	4	5.581e-3	3	NC	15	NC	3
110			min	-.592	4	-1.25	2	.008	10	-9.467e-3	2	327.262	2	2110.068	4
111		18	max	0	1	.518	3	.076	4	4.773e-3	3	NC	5	NC	2
112			min	-.592	4	-.91	2	.001	10	-8.21e-3	2	610.375	2	3123.155	4
113		19	max	0	1	.315	3	.008	3	3.966e-3	3	NC	1	NC	1
114			min	-.592	4	-.517	2	-.004	2	-6.954e-3	2	NC	1	NC	1
115	M16	1	max	0	12	.158	1	.006	3	7.185e-3	3	NC	1	NC	1
116			min	-.149	4	-.106	3	-.004	2	-1.022e-2	1	NC	1	NC	1
117		2	max	0	12	.003	13	.051	1	8.284e-3	3	NC	5	NC	2
118			min	-.149	4	-.088	2	-.044	5	-1.133e-2	1	1011.221	2	4844.507	1
119		3	max	0	12	.047	3	.121	1	9.383e-3	3	NC	5	NC	3
120			min	-.149	4	-.276	2	-.055	5	-1.243e-2	1	564.054	2	2010.591	1
121		4	max	0	12	.079	3	.18	1	1.048e-2	3	NC	5	NC	3
122			min	-.149	4	-.382	2	-.042	5	-1.354e-2	1	451.449	2	1338.868	1
123		5	max	0	12	.07	3	.211	1	1.158e-2	3	NC	5	NC	3
124			min	-.149	4	-.391	2	-.015	5	-1.465e-2	1	443.858	2	1144.245	1
125		6	max	0	12	.023	3	.203	1	1.268e-2	3	NC	5	NC	3
126			min	-.149	4	-.306	2	.01	15	-1.576e-2	1	526.8	2	1187.279	1
127		7	max	0	12	.002	13	.16	1	1.378e-2	3	NC	5	NC	3
128			min	-.149	4	-.147	2	.013	10	-1.687e-2	1	808.449	2	1513.987	1
129		8	max	0	12	.093	1	.093	1	1.488e-2	3	NC	4	NC	3
130			min	-.149	4	-.145	3	.004	10	-1.798e-2	1	2329.357	2	2616.615	1
131		9	max	0	12	.252	1	.048	4	1.598e-2	3	NC	4	NC	2
132			min	-.149	4	-.223	3	-.005	10	-1.909e-2	1	2054.577	3	4951.718	4
133		10	max	0	1	.323	1	.02	3	1.708e-2	3	NC	5	NC	1
134			min	-.149	4	-.258	3	-.015	2	-2.02e-2	1	1453.863	1	NC	1
135		11	max	0	1	.252	1	.027	1	1.598e-2	3	NC	4	NC	2
136			min	-.149	4	-.223	3	-.034	5	-1.909e-2	1	2054.577	3	7327.546	5
137		12	max	0	1	.093	1	.093	1	1.488e-2	3	NC	4	NC	3
138			min	-.148	4	-.145	3	-.035	5	-1.798e-2	1	2329.357	2	2616.615	1
139		13	max	0	1	.002	13	.16	1	1.378e-2	3	NC	5	NC	3
140			min	-.148	4	-.147	2	-.015	5	-1.687e-2	1	808.449	2	1513.987	1
141		14	max	0	1	.023	3	.203	1	1.268e-2	3	NC	5	NC	3
142			min	-.148	4	-.306	2	.01	15	-1.576e-2	1	526.8	2	1187.279	1
143		15	max	0	1	.07	3	.211	1	1.158e-2	3	NC	5	NC	3
144			min	-.148	4	-.391	2	.018	12	-1.465e-2	1	443.858	2	1144.245	1
145		16	max	0	1	.079	3	.18	1	1.048e-2	3	NC	5	NC	3
146			min	-.148	4	-.382	2	.015	12	-1.354e-2	1	451.449	2	1338.868	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
147		17	max	0	1	.047	3	.121	1	9.383e-3	3	NC	5	NC	3
148			min	-.148	4	-.276	2	.011	12	-1.243e-2	1	564.054	2	2010.591	1
149		18	max	.001	1	.002	13	.065	4	8.284e-3	3	NC	5	NC	2
150			min	-.148	4	-.088	2	.003	10	-1.133e-2	1	1011.221	2	3644.517	4
151		19	max	.001	1	.158	1	.006	3	7.185e-3	3	NC	1	NC	1
152			min	-.148	4	-.106	3	-.004	2	-1.022e-2	1	NC	1	NC	1
153	M2	1	max	.007	1	.008	2	.014	1	2.699e-3	5	NC	1	NC	2
154			min	-.008	3	-.014	3	-.964	4	-3.332e-4	1	9391.226	2	80.364	4
155		2	max	.007	1	.007	2	.013	1	2.762e-3	5	NC	1	NC	2
156			min	-.008	3	-.013	3	-.886	4	-3.163e-4	1	NC	1	87.484	4
157		3	max	.007	1	.005	2	.012	1	2.824e-3	5	NC	1	NC	2
158			min	-.007	3	-.013	3	-.808	4	-2.994e-4	1	NC	1	95.936	4
159		4	max	.006	1	.004	2	.011	1	2.886e-3	5	NC	1	NC	2
160			min	-.007	3	-.013	3	-.731	4	-2.824e-4	1	NC	1	106.065	4
161		5	max	.006	1	.003	2	.01	1	2.948e-3	5	NC	1	NC	2
162			min	-.006	3	-.012	3	-.655	4	-2.655e-4	1	NC	1	118.345	4
163		6	max	.005	1	.002	2	.008	1	3.01e-3	5	NC	1	NC	2
164			min	-.006	3	-.012	3	-.581	4	-2.486e-4	1	NC	1	133.425	4
165		7	max	.005	1	0	2	.007	1	3.072e-3	5	NC	1	NC	1
166			min	-.006	3	-.012	3	-.509	4	-2.317e-4	1	NC	1	152.232	4
167		8	max	.005	1	0	2	.006	1	3.134e-3	5	NC	1	NC	1
168			min	-.005	3	-.011	3	-.44	4	-2.147e-4	1	NC	1	176.113	4
169		9	max	.004	1	0	15	.005	1	3.198e-3	4	NC	1	NC	1
170			min	-.005	3	-.011	3	-.374	4	-1.978e-4	1	NC	1	207.094	4
171		10	max	.004	1	-.001	15	.005	1	3.266e-3	4	NC	1	NC	1
172			min	-.004	3	-.01	3	-.312	4	-1.809e-4	1	NC	1	248.338	4
173		11	max	.003	1	-.001	15	.004	1	3.334e-3	4	NC	1	NC	1
174			min	-.004	3	-.009	3	-.254	4	-1.64e-4	1	NC	1	305.014	4
175		12	max	.003	1	-.001	15	.003	1	3.402e-3	4	NC	1	NC	1
176			min	-.003	3	-.008	3	-.201	4	-1.47e-4	1	NC	1	386.048	4
177		13	max	.002	1	-.001	15	.002	1	3.47e-3	4	NC	1	NC	1
178			min	-.003	3	-.008	3	-.153	4	-1.301e-4	1	NC	1	507.975	4
179		14	max	.002	1	-.001	15	.002	1	3.538e-3	4	NC	1	NC	1
180			min	-.002	3	-.007	3	-.11	4	-1.132e-4	1	NC	1	704.35	4
181		15	max	.002	1	-.001	15	.001	1	3.606e-3	4	NC	1	NC	1
182			min	-.002	3	-.006	3	-.074	4	-9.628e-5	1	NC	1	1052.271	4
183		16	max	.001	1	0	15	0	1	3.674e-3	4	NC	1	NC	1
184			min	-.001	3	-.004	6	-.044	4	-7.935e-5	1	NC	1	1763.875	4
185		17	max	0	1	0	15	0	1	3.742e-3	4	NC	1	NC	1
186			min	0	3	-.003	6	-.021	4	-6.243e-5	1	NC	1	3620.01	4
187		18	max	0	1	0	15	0	1	3.81e-3	4	NC	1	NC	1
188			min	0	3	-.002	6	-.007	4	-4.551e-5	1	NC	1	NC	1
189		19	max	0	1	0	1	0	1	3.878e-3	4	NC	1	NC	1
190			min	0	1	0	1	0	1	-2.859e-5	1	NC	1	NC	1
191	M3	1	max	0	1	0	1	0	1	5.418e-6	1	NC	1	NC	1
192			min	0	1	0	1	0	1	-8.42e-4	4	NC	1	NC	1
193		2	max	0	3	0	15	.021	4	4.179e-5	1	NC	1	NC	1
194			min	0	2	-.003	6	0	1	-2.535e-5	5	NC	1	NC	1
195		3	max	0	3	-.001	15	.04	4	8.114e-4	4	NC	1	NC	1
196			min	0	2	-.006	6	0	1	4.318e-6	12	NC	1	7954.73	5
197		4	max	.001	3	-.002	15	.058	4	1.638e-3	4	NC	1	NC	1
198			min	0	2	-.009	6	0	1	6.301e-6	12	NC	1	6002.957	5
199		5	max	.002	3	-.003	15	.074	4	2.465e-3	4	NC	1	NC	1
200			min	-.001	2	-.012	6	0	1	8.284e-6	12	8520.357	6	5157.93	5
201		6	max	.002	3	-.003	15	.089	4	3.292e-3	4	NC	5	NC	1
202			min	-.002	2	-.015	6	0	1	1.027e-5	12	6904.454	6	4794.105	5
203		7	max	.002	3	-.004	15	.103	4	4.118e-3	4	NC	5	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
204			min	-.002	2	-.017	6	0	1	1.225e-5	12	5931.236	6	4719.521	5
205		8	max	.003	3	-.004	15	.116	4	4.945e-3	4	NC	5	NC	1
206			min	-.002	2	-.019	6	0	12	1.423e-5	12	5331.006	6	4876.016	5
207		9	max	.003	3	-.005	15	.128	4	5.772e-3	4	NC	5	NC	1
208			min	-.003	2	-.021	6	0	12	1.622e-5	12	4976.818	6	5272.409	5
209		10	max	.004	3	-.005	15	.139	4	6.599e-3	4	NC	5	NC	1
210			min	-.003	2	-.021	6	0	12	1.82e-5	12	4807.129	6	5978.494	5
211		11	max	.004	3	-.005	15	.15	4	7.425e-3	4	NC	5	NC	1
212			min	-.003	2	-.021	6	0	12	2.018e-5	12	4796.991	6	7159.244	5
213		12	max	.004	3	-.005	15	.161	4	8.252e-3	4	NC	5	NC	1
214			min	-.003	2	-.021	6	0	12	2.217e-5	12	4948.492	6	9186.08	5
215		13	max	.005	3	-.004	15	.171	4	9.079e-3	4	NC	5	NC	1
216			min	-.004	2	-.019	6	0	12	2.415e-5	12	5292.785	6	NC	1
217		14	max	.005	3	-.004	15	.182	4	9.905e-3	4	NC	5	NC	1
218			min	-.004	2	-.017	6	0	12	2.613e-5	12	5906.173	6	NC	1
219		15	max	.006	3	-.003	15	.193	4	1.073e-2	4	NC	3	NC	1
220			min	-.004	2	-.015	6	0	12	2.812e-5	12	6957.519	6	NC	1
221		16	max	.006	3	-.002	15	.204	4	1.156e-2	4	NC	1	NC	1
222			min	-.005	2	-.012	6	0	12	3.01e-5	12	8855.603	6	NC	1
223		17	max	.006	3	-.002	15	.217	4	1.239e-2	4	NC	1	NC	1
224			min	-.005	2	-.008	1	0	12	3.209e-5	12	NC	1	NC	1
225		18	max	.007	3	0	15	.231	4	1.321e-2	4	NC	1	NC	2
226			min	-.005	2	-.005	1	0	12	3.407e-5	12	NC	1	9281.402	1
227		19	max	.007	3	0	5	.247	4	1.404e-2	4	NC	1	NC	2
228			min	-.006	2	-.002	1	0	12	3.605e-5	12	NC	1	7743.392	1
229	M4	1	max	.003	1	.005	2	0	12	2.337e-4	1	NC	1	NC	3
230			min	0	5	-.007	3	-.247	4	-6.414e-4	5	NC	1	100.619	4
231		2	max	.002	1	.005	2	0	12	2.337e-4	1	NC	1	NC	3
232			min	0	5	-.007	3	-.227	4	-6.414e-4	5	NC	1	109.447	4
233		3	max	.002	1	.005	2	0	12	2.337e-4	1	NC	1	NC	3
234			min	0	5	-.007	3	-.207	4	-6.414e-4	5	NC	1	119.95	4
235		4	max	.002	1	.004	2	0	12	2.337e-4	1	NC	1	NC	3
236			min	0	5	-.006	3	-.187	4	-6.414e-4	5	NC	1	132.565	4
237		5	max	.002	1	.004	2	0	12	2.337e-4	1	NC	1	NC	3
238			min	0	5	-.006	3	-.168	4	-6.414e-4	5	NC	1	147.885	4
239		6	max	.002	1	.004	2	0	12	2.337e-4	1	NC	1	NC	3
240			min	0	5	-.005	3	-.149	4	-6.414e-4	5	NC	1	166.729	4
241		7	max	.002	1	.004	2	0	12	2.337e-4	1	NC	1	NC	3
242			min	0	5	-.005	3	-.13	4	-6.414e-4	5	NC	1	190.265	4
243		8	max	.002	1	.003	2	0	12	2.337e-4	1	NC	1	NC	3
244			min	0	5	-.005	3	-.113	4	-6.414e-4	5	NC	1	220.191	4
245		9	max	.001	1	.003	2	0	12	2.337e-4	1	NC	1	NC	2
246			min	0	5	-.004	3	-.096	4	-6.414e-4	5	NC	1	259.067	4
247		10	max	.001	1	.003	2	0	12	2.337e-4	1	NC	1	NC	2
248			min	0	5	-.004	3	-.08	4	-6.414e-4	5	NC	1	310.894	4
249		11	max	.001	1	.002	2	0	12	2.337e-4	1	NC	1	NC	2
250			min	0	5	-.003	3	-.065	4	-6.414e-4	5	NC	1	382.217	4
251		12	max	.001	1	.002	2	0	12	2.337e-4	1	NC	1	NC	2
252			min	0	5	-.003	3	-.051	4	-6.414e-4	5	NC	1	484.357	4
253		13	max	0	1	.002	2	0	12	2.337e-4	1	NC	1	NC	1
254			min	0	5	-.002	3	-.039	4	-6.414e-4	5	NC	1	638.328	4
255		14	max	0	1	.001	2	0	12	2.337e-4	1	NC	1	NC	1
256			min	0	5	-.002	3	-.028	4	-6.414e-4	5	NC	1	886.881	4
257		15	max	0	1	.001	2	0	12	2.337e-4	1	NC	1	NC	1
258			min	0	5	-.002	3	-.019	4	-6.414e-4	5	NC	1	1328.564	4
259		16	max	0	1	0	2	0	12	2.337e-4	1	NC	1	NC	1
260			min	0	5	-.001	3	-.011	4	-6.414e-4	5	NC	1	2235.791	4

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
261		17	max	0	1	0	2	0	12	2.337e-4	1	NC	1	NC	1
262			min	0	5	0	3	-.005	4	-6.414e-4	5	NC	1	4618.582	4
263		18	max	0	1	0	2	0	12	2.337e-4	1	NC	1	NC	1
264			min	0	5	0	3	-.002	4	-6.414e-4	5	NC	1	NC	1
265		19	max	0	1	0	1	0	1	2.337e-4	1	NC	1	NC	1
266			min	0	1	0	1	0	1	-6.414e-4	5	NC	1	NC	1
267	M6	1	max	.023	1	.031	2	0	1	2.864e-3	4	NC	3	NC	1
268			min	-.027	3	-.043	3	-.975	4	0	1	2474.427	2	79.483	4
269		2	max	.022	1	.028	2	0	1	2.923e-3	4	NC	3	NC	1
270			min	-.025	3	-.041	3	-.896	4	0	1	2732.751	2	86.525	4
271		3	max	.021	1	.025	2	0	1	2.983e-3	4	NC	3	NC	1
272			min	-.024	3	-.038	3	-.817	4	0	1	3048.271	2	94.885	4
273		4	max	.019	1	.023	2	0	1	3.042e-3	4	NC	3	NC	1
274			min	-.022	3	-.036	3	-.739	4	0	1	3438.534	2	104.904	4
275		5	max	.018	1	.02	2	0	1	3.102e-3	4	NC	3	NC	1
276			min	-.021	3	-.034	3	-.662	4	0	1	3928.631	2	117.049	4
277		6	max	.017	1	.017	2	0	1	3.161e-3	4	NC	3	NC	1
278			min	-.019	3	-.032	3	-.587	4	0	1	4555.479	2	131.966	4
279		7	max	.016	1	.014	2	0	1	3.221e-3	4	NC	1	NC	1
280			min	-.018	3	-.029	3	-.515	4	0	1	5375.272	2	150.568	4
281		8	max	.014	1	.012	2	0	1	3.28e-3	4	NC	1	NC	1
282			min	-.016	3	-.027	3	-.445	4	0	1	6477.121	2	174.188	4
283		9	max	.013	1	.01	2	0	1	3.34e-3	4	NC	1	NC	1
284			min	-.015	3	-.025	3	-.378	4	0	1	8009.668	2	204.83	4
285		10	max	.012	1	.008	2	0	1	3.399e-3	4	NC	1	NC	1
286			min	-.013	3	-.022	3	-.315	4	0	1	NC	1	245.624	4
287		11	max	.01	1	.006	2	0	1	3.459e-3	4	NC	1	NC	1
288			min	-.012	3	-.02	3	-.257	4	0	1	NC	1	301.68	4
289		12	max	.009	1	.004	2	0	1	3.518e-3	4	NC	1	NC	1
290			min	-.01	3	-.018	3	-.203	4	0	1	NC	1	381.826	4
291		13	max	.008	1	.003	2	0	1	3.578e-3	4	NC	1	NC	1
292			min	-.009	3	-.015	3	-.154	4	0	1	NC	1	502.412	4
293		14	max	.006	1	.001	2	0	1	3.637e-3	4	NC	1	NC	1
294			min	-.007	3	-.013	3	-.111	4	0	1	NC	1	696.619	4
295		15	max	.005	1	0	2	0	1	3.697e-3	4	NC	1	NC	1
296			min	-.006	3	-.01	3	-.074	4	0	1	NC	1	1040.675	4
297		16	max	.004	1	0	2	0	1	3.756e-3	4	NC	1	NC	1
298			min	-.004	3	-.008	3	-.044	4	0	1	NC	1	1744.301	4
299		17	max	.003	1	0	2	0	1	3.816e-3	4	NC	1	NC	1
300			min	-.003	3	-.005	3	-.022	4	0	1	NC	1	3579.28	4
301		18	max	.001	1	0	2	0	1	3.875e-3	4	NC	1	NC	1
302			min	-.001	3	-.003	3	-.007	4	0	1	NC	1	NC	1
303		19	max	0	1	0	1	0	1	3.935e-3	4	NC	1	NC	1
304			min	0	1	0	1	0	1	0	1	NC	1	NC	1
305	M7	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
306			min	0	1	0	1	0	1	-8.549e-4	4	NC	1	NC	1
307		2	max	.001	3	0	15	.021	4	0	1	NC	1	NC	1
308			min	-.001	2	-.003	3	0	1	-5.615e-5	4	NC	1	NC	1
309		3	max	.002	3	-.001	15	.041	4	7.426e-4	4	NC	1	NC	1
310			min	-.002	2	-.007	3	0	1	0	1	NC	1	7071.216	4
311		4	max	.004	3	-.002	15	.059	4	1.541e-3	4	NC	1	NC	1
312			min	-.004	2	-.01	3	0	1	0	1	NC	1	5282.925	4
313		5	max	.005	3	-.003	15	.075	4	2.34e-3	4	NC	1	NC	1
314			min	-.005	2	-.013	3	0	1	0	1	8575.985	4	4486.358	4
315		6	max	.006	3	-.004	15	.09	4	3.139e-3	4	NC	1	NC	1
316			min	-.006	2	-.015	3	0	1	0	1	6945.504	4	4112.418	4
317		7	max	.007	3	-.004	15	.104	4	3.937e-3	4	NC	2	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
318			min	-.007	2	-.018	4	0	1	0	1	5963.694	4	3981.329	4
319		8	max	.009	3	-.005	15	.117	4	4.736e-3	4	NC	5	NC	1
320			min	-.008	2	-.02	4	0	1	0	1	5358.103	4	4029.738	4
321		9	max	.01	3	-.005	15	.129	4	5.535e-3	4	NC	5	NC	1
322			min	-.01	2	-.021	4	0	1	0	1	5000.5	4	4246.099	4
323		10	max	.011	3	-.005	15	.14	4	6.334e-3	4	NC	5	NC	1
324			min	-.011	2	-.022	4	0	1	0	1	4828.695	4	4655.653	4
325		11	max	.012	3	-.005	15	.15	4	7.132e-3	4	NC	5	NC	1
326			min	-.012	2	-.022	4	0	1	0	1	4817.411	4	5327.218	4
327		12	max	.014	3	-.005	15	.16	4	7.931e-3	4	NC	5	NC	1
328			min	-.013	2	-.021	4	0	1	0	1	4968.599	4	6404.114	4
329		13	max	.015	3	-.005	15	.17	4	8.73e-3	4	NC	5	NC	1
330			min	-.014	2	-.02	4	0	1	0	1	5313.43	4	8188.28	4
331		14	max	.016	3	-.004	15	.179	4	9.528e-3	4	NC	5	NC	1
332			min	-.015	2	-.018	4	0	1	0	1	5928.411	4	NC	1
333		15	max	.017	3	-.004	15	.189	4	1.033e-2	4	NC	1	NC	1
334			min	-.017	2	-.016	3	0	1	0	1	6982.947	4	NC	1
335		16	max	.019	3	-.003	15	.199	4	1.113e-2	4	NC	1	NC	1
336			min	-.018	2	-.014	3	0	1	0	1	8887.199	4	NC	1
337		17	max	.02	3	-.002	15	.21	4	1.192e-2	4	NC	1	NC	1
338			min	-.019	2	-.011	3	0	1	0	1	NC	1	NC	1
339		18	max	.021	3	-.001	15	.222	4	1.272e-2	4	NC	1	NC	1
340			min	-.02	2	-.008	3	0	1	0	1	NC	1	NC	1
341		19	max	.022	3	0	10	.236	4	1.352e-2	4	NC	1	NC	1
342			min	-.021	2	-.005	3	0	1	0	1	NC	1	NC	1
343	M8	1	max	.007	1	.021	2	0	1	0	1	NC	1	NC	1
344			min	0	3	-.023	3	-.236	4	-8.699e-4	4	NC	1	105.252	4
345		2	max	.006	1	.02	2	0	1	0	1	NC	1	NC	1
346			min	0	3	-.022	3	-.217	4	-8.699e-4	4	NC	1	114.505	4
347		3	max	.006	1	.018	2	0	1	0	1	NC	1	NC	1
348			min	0	3	-.02	3	-.198	4	-8.699e-4	4	NC	1	125.514	4
349		4	max	.006	1	.017	2	0	1	0	1	NC	1	NC	1
350			min	0	3	-.019	3	-.179	4	-8.699e-4	4	NC	1	138.736	4
351		5	max	.005	1	.016	2	0	1	0	1	NC	1	NC	1
352			min	0	3	-.018	3	-.16	4	-8.699e-4	4	NC	1	154.79	4
353		6	max	.005	1	.015	2	0	1	0	1	NC	1	NC	1
354			min	0	3	-.017	3	-.142	4	-8.699e-4	4	NC	1	174.538	4
355		7	max	.004	1	.014	2	0	1	0	1	NC	1	NC	1
356			min	0	3	-.015	3	-.125	4	-8.699e-4	4	NC	1	199.201	4
357		8	max	.004	1	.013	2	0	1	0	1	NC	1	NC	1
358			min	0	3	-.014	3	-.108	4	-8.699e-4	4	NC	1	230.561	4
359		9	max	.004	1	.011	2	0	1	0	1	NC	1	NC	1
360			min	0	3	-.013	3	-.091	4	-8.699e-4	4	NC	1	271.3	4
361		10	max	.003	1	.01	2	0	1	0	1	NC	1	NC	1
362			min	0	3	-.011	3	-.076	4	-8.699e-4	4	NC	1	325.611	4
363		11	max	.003	1	.009	2	0	1	0	1	NC	1	NC	1
364			min	0	3	-.01	3	-.062	4	-8.699e-4	4	NC	1	400.354	4
365		12	max	.003	1	.008	2	0	1	0	1	NC	1	NC	1
366			min	0	3	-.009	3	-.049	4	-8.699e-4	4	NC	1	507.394	4
367		13	max	.002	1	.007	2	0	1	0	1	NC	1	NC	1
368			min	0	3	-.008	3	-.037	4	-8.699e-4	4	NC	1	668.757	4
369		14	max	.002	1	.006	2	0	1	0	1	NC	1	NC	1
370			min	0	3	-.006	3	-.027	4	-8.699e-4	4	NC	1	929.253	4
371		15	max	.001	1	.005	2	0	1	0	1	NC	1	NC	1
372			min	0	3	-.005	3	-.018	4	-8.699e-4	4	NC	1	1392.179	4
373		16	max	.001	1	.003	2	0	1	0	1	NC	1	NC	1
374			min	0	3	-.004	3	-.011	4	-8.699e-4	4	NC	1	2343.1	4

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
375		17	max	0	1	.002	2	0	1	0	1	NC	1	NC	1
376			min	0	3	-.003	3	-.005	4	-8.699e-4	4	NC	1	4840.86	4
377		18	max	0	1	.001	2	0	1	0	1	NC	1	NC	1
378			min	0	3	-.001	3	-.002	4	-8.699e-4	4	NC	1	NC	1
379		19	max	0	1	0	1	0	1	0	1	NC	1	NC	1
380			min	0	1	0	1	0	1	-8.699e-4	4	NC	1	NC	1
381	M10	1	max	.007	1	.008	2	0	12	2.857e-3	4	NC	1	NC	2
382			min	-.008	3	-.014	3	-.973	4	2.045e-5	12	9391.226	2	79.65	4
383		2	max	.007	1	.007	2	0	12	2.915e-3	4	NC	1	NC	2
384			min	-.008	3	-.013	3	-.894	4	1.941e-5	12	NC	1	86.707	4
385		3	max	.007	1	.005	2	0	12	2.972e-3	4	NC	1	NC	2
386			min	-.007	3	-.013	3	-.815	4	1.838e-5	12	NC	1	95.084	4
387		4	max	.006	1	.004	2	0	12	3.03e-3	4	NC	1	NC	2
388			min	-.007	3	-.013	3	-.737	4	1.734e-5	12	NC	1	105.126	4
389		5	max	.006	1	.003	2	0	12	3.088e-3	4	NC	1	NC	2
390			min	-.006	3	-.012	3	-.661	4	1.63e-5	12	NC	1	117.298	4
391		6	max	.005	1	.002	2	0	12	3.145e-3	4	NC	1	NC	2
392			min	-.006	3	-.012	3	-.586	4	1.527e-5	12	NC	1	132.248	4
393		7	max	.005	1	0	2	0	12	3.203e-3	4	NC	1	NC	1
394			min	-.006	3	-.012	3	-.514	4	1.423e-5	12	NC	1	150.892	4
395		8	max	.005	1	0	2	0	12	3.261e-3	4	NC	1	NC	1
396			min	-.005	3	-.011	3	-.444	4	1.32e-5	12	NC	1	174.566	4
397		9	max	.004	1	-.001	2	0	12	3.318e-3	4	NC	1	NC	1
398			min	-.005	3	-.011	3	-.377	4	1.216e-5	12	NC	1	205.28	4
399		10	max	.004	1	-.002	2	0	12	3.376e-3	4	NC	1	NC	1
400			min	-.004	3	-.01	3	-.315	4	1.113e-5	12	NC	1	246.17	4
401		11	max	.003	1	-.002	15	0	12	3.433e-3	4	NC	1	NC	1
402			min	-.004	3	-.009	3	-.256	4	1.009e-5	12	NC	1	302.362	4
403		12	max	.003	1	-.002	15	0	12	3.491e-3	4	NC	1	NC	1
404			min	-.003	3	-.008	3	-.202	4	9.057e-6	12	NC	1	382.706	4
405		13	max	.002	1	-.002	15	0	12	3.549e-3	4	NC	1	NC	1
406			min	-.003	3	-.008	4	-.154	4	8.021e-6	12	NC	1	503.602	4
407		14	max	.002	1	-.002	15	0	12	3.606e-3	4	NC	1	NC	1
408			min	-.002	3	-.007	4	-.111	4	6.986e-6	12	NC	1	698.331	4
409		15	max	.002	1	-.002	15	0	12	3.664e-3	4	NC	1	NC	1
410			min	-.002	3	-.006	4	-.074	4	5.95e-6	12	NC	1	1043.366	4
411		16	max	.001	1	-.001	15	0	12	3.722e-3	4	NC	1	NC	1
412			min	-.001	3	-.005	4	-.044	4	4.915e-6	12	NC	1	1749.167	4
413		17	max	0	1	0	15	0	12	3.779e-3	4	NC	1	NC	1
414			min	0	3	-.004	4	-.022	4	3.879e-6	12	NC	1	3590.591	4
415		18	max	0	1	0	15	0	12	3.837e-3	4	NC	1	NC	1
416			min	0	3	-.002	4	-.007	4	2.844e-6	12	NC	1	NC	1
417		19	max	0	1	0	1	0	1	3.895e-3	4	NC	1	NC	1
418			min	0	1	0	1	0	1	1.809e-6	12	NC	1	NC	1
419	M11	1	max	0	1	0	1	0	1	-3.507e-7	12	NC	1	NC	1
420			min	0	1	0	1	0	1	-8.452e-4	4	NC	1	NC	1
421		2	max	0	3	0	15	.021	4	-2.334e-6	12	NC	1	NC	1
422			min	0	2	-.003	4	0	12	-4.179e-5	1	NC	1	NC	1
423		3	max	0	3	-.002	15	.04	4	7.668e-4	5	NC	1	NC	1
424			min	0	2	-.006	4	0	12	-7.816e-5	1	NC	1	7454.887	4
425		4	max	.001	3	-.002	15	.058	4	1.568e-3	4	NC	1	NC	1
426			min	0	2	-.01	4	0	12	-1.145e-4	1	NC	1	5599.909	4
427		5	max	.002	3	-.003	15	.074	4	2.372e-3	4	NC	1	NC	1
428			min	-.001	2	-.013	4	0	12	-1.509e-4	1	8243.393	4	4785.446	4
429		6	max	.002	3	-.004	15	.089	4	3.177e-3	4	NC	5	NC	1
430			min	-.002	2	-.016	4	0	12	-1.873e-4	1	6699.357	4	4418.855	4
431		7	max	.002	3	-.004	15	.103	4	3.981e-3	4	NC	5	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
432			min	-.002	2	-.018	4	0	10	-2.237e-4	1	5768.609	4	4315.447	4
433		8	max	.003	3	-.005	15	.116	4	4.786e-3	4	NC	5	NC	1
434			min	-.002	2	-.02	4	0	1	-2.6e-4	1	5194.924	4	4414.291	4
435		9	max	.003	3	-.005	15	.128	4	5.59e-3	4	NC	5	NC	1
436			min	-.003	2	-.022	4	0	1	-2.964e-4	1	4857.653	4	4712.604	4
437		10	max	.004	3	-.006	15	.139	4	6.394e-3	4	NC	5	NC	1
438			min	-.003	2	-.022	4	-.001	1	-3.328e-4	1	4698.434	4	5254.193	4
439		11	max	.004	3	-.006	15	.149	4	7.199e-3	4	NC	5	NC	1
440			min	-.003	2	-.023	4	-.002	1	-3.691e-4	1	4693.931	4	6146.438	4
441		12	max	.004	3	-.005	15	.159	4	8.003e-3	4	NC	5	NC	1
442			min	-.003	2	-.022	4	-.002	1	-4.055e-4	1	4846.893	4	7619.194	4
443		13	max	.005	3	-.005	15	.169	4	8.808e-3	4	NC	5	NC	1
444			min	-.004	2	-.021	4	-.003	1	-4.419e-4	1	5188.366	4	NC	1
445		14	max	.005	3	-.005	15	.179	4	9.612e-3	4	NC	5	NC	1
446			min	-.004	2	-.019	4	-.004	1	-4.783e-4	1	5793.604	4	NC	1
447		15	max	.006	3	-.004	15	.189	4	1.042e-2	4	NC	3	NC	1
448			min	-.004	2	-.016	4	-.006	1	-5.146e-4	1	6828.716	4	NC	1
449		16	max	.006	3	-.003	15	.2	4	1.122e-2	4	NC	1	NC	1
450			min	-.005	2	-.013	4	-.007	1	-5.51e-4	1	8695.476	4	NC	1
451		17	max	.006	3	-.002	15	.212	4	1.203e-2	4	NC	1	NC	1
452			min	-.005	2	-.01	4	-.009	1	-5.874e-4	1	NC	1	NC	1
453		18	max	.007	3	-.002	15	.224	4	1.283e-2	4	NC	1	NC	2
454			min	-.005	2	-.006	4	-.011	1	-6.237e-4	1	NC	1	9281.402	1
455		19	max	.007	3	0	10	.238	4	1.363e-2	4	NC	1	NC	2
456			min	-.006	2	-.002	1	-.013	1	-6.601e-4	1	NC	1	7743.392	1
457	M12	1	max	.003	1	.005	2	.013	1	-1.321e-5	12	NC	1	NC	3
458			min	0	3	-.007	3	-.238	4	-7.454e-4	4	NC	1	104.017	4
459		2	max	.002	1	.005	2	.012	1	-1.321e-5	12	NC	1	NC	3
460			min	0	3	-.007	3	-.219	4	-7.454e-4	4	NC	1	113.151	4
461		3	max	.002	1	.005	2	.011	1	-1.321e-5	12	NC	1	NC	3
462			min	0	3	-.007	3	-.2	4	-7.454e-4	4	NC	1	124.019	4
463		4	max	.002	1	.004	2	.01	1	-1.321e-5	12	NC	1	NC	3
464			min	0	3	-.006	3	-.181	4	-7.454e-4	4	NC	1	137.072	4
465		5	max	.002	1	.004	2	.009	1	-1.321e-5	12	NC	1	NC	3
466			min	0	3	-.006	3	-.162	4	-7.454e-4	4	NC	1	152.923	4
467		6	max	.002	1	.004	2	.008	1	-1.321e-5	12	NC	1	NC	3
468			min	0	3	-.005	3	-.144	4	-7.454e-4	4	NC	1	172.42	4
469		7	max	.002	1	.004	2	.007	1	-1.321e-5	12	NC	1	NC	3
470			min	0	3	-.005	3	-.126	4	-7.454e-4	4	NC	1	196.77	4
471		8	max	.002	1	.003	2	.006	1	-1.321e-5	12	NC	1	NC	3
472			min	0	3	-.005	3	-.109	4	-7.454e-4	4	NC	1	227.732	4
473		9	max	.001	1	.003	2	.005	1	-1.321e-5	12	NC	1	NC	2
474			min	0	3	-.004	3	-.093	4	-7.454e-4	4	NC	1	267.955	4
475		10	max	.001	1	.003	2	.004	1	-1.321e-5	12	NC	1	NC	2
476			min	0	3	-.004	3	-.077	4	-7.454e-4	4	NC	1	321.577	4
477		11	max	.001	1	.002	2	.004	1	-1.321e-5	12	NC	1	NC	2
478			min	0	3	-.003	3	-.063	4	-7.454e-4	4	NC	1	395.37	4
479		12	max	.001	1	.002	2	.003	1	-1.321e-5	12	NC	1	NC	2
480			min	0	3	-.003	3	-.05	4	-7.454e-4	4	NC	1	501.049	4
481		13	max	0	1	.002	2	.002	1	-1.321e-5	12	NC	1	NC	1
482			min	0	3	-.002	3	-.038	4	-7.454e-4	4	NC	1	660.358	4
483		14	max	0	1	.001	2	.002	1	-1.321e-5	12	NC	1	NC	1
484			min	0	3	-.002	3	-.027	4	-7.454e-4	4	NC	1	917.533	4
485		15	max	0	1	.001	2	.001	1	-1.321e-5	12	NC	1	NC	1
486			min	0	3	-.002	3	-.018	4	-7.454e-4	4	NC	1	1374.545	4
487		16	max	0	1	0	2	0	1	-1.321e-5	12	NC	1	NC	1
488			min	0	3	-.001	3	-.011	4	-7.454e-4	4	NC	1	2313.286	4

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
489		17	max	0	1	0	2	0	1	-1.321e-5	12	NC	1	NC	1
490			min	0	3	0	3	-.005	4	-7.454e-4	4	NC	1	4778.943	4
491		18	max	0	1	0	2	0	1	-1.321e-5	12	NC	1	NC	1
492			min	0	3	0	3	-.002	4	-7.454e-4	4	NC	1	NC	1
493		19	max	0	1	0	1	0	1	-1.321e-5	12	NC	1	NC	1
494			min	0	1	0	1	0	1	-7.454e-4	4	NC	1	NC	1
495	M1	1	max	.009	3	.168	2	1.035	4	1.334e-2	1	NC	1	NC	1
496			min	-.005	2	-.032	3	0	12	-2.168e-2	3	NC	1	NC	1
497		2	max	.009	3	.081	2	1	4	1.033e-2	4	NC	5	NC	1
498			min	-.005	2	-.014	3	-.01	1	-1.076e-2	3	1568.567	2	8154.439	5
499		3	max	.009	3	.014	3	.964	4	1.769e-2	4	NC	5	NC	2
500			min	-.005	2	-.012	2	-.014	1	-2.995e-4	1	756.929	2	4499.566	5
501		4	max	.009	3	.06	3	.926	4	1.536e-2	4	NC	15	NC	2
502			min	-.005	2	-.115	2	-.013	1	-4.388e-3	3	479.151	2	3267.96	5
503		5	max	.009	3	.118	3	.887	4	1.303e-2	4	9888.605	15	NC	1
504			min	-.004	2	-.223	2	-.009	1	-8.665e-3	3	346.439	2	2649.039	5
505		6	max	.009	3	.181	3	.847	4	1.401e-2	1	7801.805	15	NC	1
506			min	-.004	2	-.328	2	-.004	1	-1.294e-2	3	273.204	2	2272.759	5
507		7	max	.008	3	.242	3	.807	4	1.878e-2	1	6571.235	15	NC	1
508			min	-.004	2	-.421	2	0	3	-1.722e-2	3	229.93	2	1998.653	4
509		8	max	.008	3	.292	3	.765	4	2.355e-2	1	5843.791	15	NC	1
510			min	-.004	2	-.496	2	0	12	-2.15e-2	3	204.322	2	1791.765	4
511		9	max	.008	3	.325	3	.722	4	2.603e-2	1	5463.678	15	NC	1
512			min	-.004	2	-.542	2	0	1	-2.178e-2	3	190.973	2	1654.548	4
513		10	max	.008	3	.337	3	.675	4	2.725e-2	2	5347.623	15	NC	1
514			min	-.004	2	-.558	2	0	12	-1.941e-2	3	187.053	2	1613.544	4
515		11	max	.008	3	.329	3	.624	4	2.913e-2	2	5463.429	15	NC	1
516			min	-.004	2	-.542	2	0	12	-1.703e-2	3	191.618	2	1648.407	4
517		12	max	.007	3	.301	3	.569	4	2.804e-2	2	5843.207	15	NC	1
518			min	-.004	2	-.493	2	-.001	1	-1.444e-2	3	206.192	1	1766.253	4
519		13	max	.007	3	.257	3	.508	4	2.252e-2	2	6570.101	15	NC	1
520			min	-.004	2	-.416	2	0	1	-1.155e-2	3	233.787	1	2097.599	4
521		14	max	.007	3	.2	3	.442	4	1.699e-2	2	7799.724	15	NC	1
522			min	-.004	2	-.319	2	0	12	-8.659e-3	3	280.838	1	2833.175	4
523		15	max	.007	3	.135	3	.374	4	1.146e-2	2	9884.782	15	NC	1
524			min	-.004	2	-.212	2	0	12	-5.769e-3	3	361.45	1	4587.604	4
525		16	max	.007	3	.069	3	.309	4	1.079e-2	4	NC	15	NC	1
526			min	-.004	2	-.105	2	0	12	-2.878e-3	3	509.72	1	NC	1
527		17	max	.006	3	.005	3	.248	4	1.208e-2	4	NC	5	NC	2
528			min	-.004	2	-.006	2	0	12	1.174e-5	12	824.041	1	9535.805	1
529		18	max	.006	3	.081	1	.194	4	9.339e-3	2	NC	5	NC	1
530			min	-.004	2	-.053	3	0	12	-3.353e-3	3	1736.687	1	NC	1
531		19	max	.006	3	.158	1	.148	4	1.853e-2	2	NC	1	NC	1
532			min	-.004	2	-.106	3	-.001	1	-6.831e-3	3	NC	1	NC	1
533	M5	1	max	.028	3	.352	2	1.035	4	0	1	NC	1	NC	1
534			min	-.019	2	-.029	3	0	1	-9.747e-6	4	NC	1	NC	1
535		2	max	.028	3	.169	2	1.008	4	9.078e-3	4	NC	5	NC	1
536			min	-.02	2	-.009	3	0	1	0	1	746.624	2	6030.126	4
537		3	max	.028	3	.043	3	.974	4	1.795e-2	4	NC	15	NC	1
538			min	-.02	2	-.037	2	0	1	0	1	350.606	2	3566.54	4
539		4	max	.028	3	.157	3	.935	4	1.462e-2	4	6861.793	15	NC	1
540			min	-.019	2	-.283	2	0	1	0	1	214.333	2	2787.746	4
541		5	max	.027	3	.313	3	.893	4	1.13e-2	4	4786.947	15	NC	1
542			min	-.019	2	-.551	2	0	1	0	1	150.594	2	2422.273	4
543		6	max	.026	3	.488	3	.85	4	7.976e-3	4	3676.477	15	NC	1
544			min	-.018	2	-.817	2	0	1	0	1	116.231	2	2200.009	4
545		7	max	.026	3	.659	3	.806	4	4.652e-3	4	3036.624	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
546			min	-.018	2	-1.059	2	0	1	0	1	96.317	2	2016.93	4
547		8	max	.025	3	.803	3	.764	4	1.328e-3	4	2665.345	15	NC	1
548			min	-.018	2	-1.252	2	0	1	0	1	84.71	1	1822.187	4
549		9	max	.025	3	.895	3	.722	4	0	1	2475.004	15	NC	1
550			min	-.017	2	-1.375	2	0	1	-5.859e-6	5	78.64	1	1648.279	4
551		10	max	.024	3	.929	3	.674	4	0	1	2417.616	15	NC	1
552			min	-.017	2	-1.417	2	0	1	-5.651e-6	5	76.838	1	1626.409	4
553		11	max	.023	3	.906	3	.623	4	0	1	2475.104	15	NC	1
554			min	-.017	2	-1.375	2	0	1	-5.443e-6	5	78.786	1	1672.588	4
555		12	max	.023	3	.827	3	.571	4	8.441e-4	4	2665.589	15	NC	1
556			min	-.016	2	-1.247	2	0	1	0	1	85.192	1	1730.609	4
557		13	max	.022	3	.7	3	.51	4	2.958e-3	4	3037.136	15	NC	1
558			min	-.016	2	-1.043	2	0	1	0	1	97.807	1	2048.764	4
559		14	max	.022	3	.541	3	.441	4	5.072e-3	4	3677.495	15	NC	1
560			min	-.016	2	-.791	1	0	1	0	1	119.788	1	2935.086	4
561		15	max	.021	3	.363	3	.369	4	7.186e-3	4	4788.986	15	NC	1
562			min	-.016	2	-.519	1	0	1	0	1	158.521	1	5797.712	4
563		16	max	.02	3	.182	3	.299	4	9.3e-3	4	6866.103	15	NC	1
564			min	-.015	2	-.251	1	0	1	0	1	232.359	1	NC	1
565		17	max	.02	3	.014	3	.237	4	1.141e-2	4	NC	15	NC	1
566			min	-.015	2	-.019	2	0	1	0	1	394.731	1	NC	1
567		18	max	.02	3	.169	1	.186	4	5.773e-3	4	NC	5	NC	1
568			min	-.015	2	-.129	3	0	1	0	1	865.733	1	NC	1
569		19	max	.02	3	.323	1	.149	4	0	1	NC	1	NC	1
570			min	-.015	2	-.258	3	0	1	-5.737e-6	4	NC	1	NC	1
571	M9	1	max	.009	3	.168	2	1.035	4	2.168e-2	3	NC	1	NC	1
572			min	-.005	2	-.032	3	-.001	1	-1.334e-2	1	NC	1	NC	1
573		2	max	.009	3	.081	2	1.006	4	1.076e-2	3	NC	5	NC	1
574			min	-.005	2	-.014	3	0	12	-6.418e-3	1	1568.567	2	6427.583	4
575		3	max	.009	3	.014	3	.972	4	1.789e-2	4	NC	5	NC	2
576			min	-.005	2	-.012	2	0	12	4.601e-6	10	756.929	2	3737.116	4
577		4	max	.009	3	.06	3	.934	4	1.4e-2	5	NC	15	NC	2
578			min	-.005	2	-.115	2	0	12	-4.471e-3	1	479.151	2	2866.034	4
579		5	max	.009	3	.118	3	.893	4	1.055e-2	5	9840.069	15	NC	1
580			min	-.004	2	-.223	2	0	12	-9.241e-3	1	346.439	2	2445.319	4
581		6	max	.009	3	.181	3	.85	4	1.294e-2	3	7765.156	15	NC	1
582			min	-.004	2	-.328	2	0	12	-1.401e-2	1	273.204	2	2189.304	4
583		7	max	.008	3	.242	3	.807	4	1.722e-2	3	6541.38	15	NC	1
584			min	-.004	2	-.421	2	0	1	-1.878e-2	1	229.93	2	1993.452	4
585		8	max	.008	3	.292	3	.764	4	2.15e-2	3	5817.856	15	NC	1
586			min	-.004	2	-.496	2	-.001	1	-2.355e-2	1	204.322	2	1808.153	4
587		9	max	.008	3	.325	3	.722	4	2.178e-2	3	5439.744	15	NC	1
588			min	-.004	2	-.542	2	0	12	-2.603e-2	1	190.973	2	1648.572	4
589		10	max	.008	3	.337	3	.675	4	1.941e-2	3	5324.28	15	NC	1
590			min	-.004	2	-.558	2	0	1	-2.725e-2	2	187.053	2	1614.715	4
591		11	max	.008	3	.329	3	.623	4	1.703e-2	3	5439.515	15	NC	1
592			min	-.004	2	-.542	2	0	1	-2.913e-2	2	191.618	2	1656.189	4
593		12	max	.007	3	.301	3	.57	4	1.444e-2	3	5817.444	15	NC	1
594			min	-.004	2	-.493	2	0	12	-2.804e-2	2	206.192	1	1750.403	4
595		13	max	.007	3	.257	3	.508	4	1.155e-2	3	6540.795	15	NC	1
596			min	-.004	2	-.416	2	0	12	-2.252e-2	2	233.787	1	2097.986	4
597		14	max	.007	3	.2	3	.44	4	8.659e-3	3	7764.356	15	NC	1
598			min	-.004	2	-.319	2	-.003	1	-1.699e-2	2	280.838	1	2942.447	5
599		15	max	.007	3	.135	3	.369	4	6.832e-3	5	9838.952	15	NC	1
600			min	-.004	2	-.212	2	-.008	1	-1.146e-2	2	361.45	1	5191.418	5
601		16	max	.007	3	.069	3	.301	4	9.198e-3	5	NC	15	NC	1
602			min	-.004	2	-.105	2	-.012	1	-5.959e-3	1	509.72	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
603		17	max	.006	3	.005	3	.239	4	1.159e-2	4	NC	5	NC	2
604			min	-.004	2	-.006	2	-.013	1	-8.473e-4	1	824.041	1	9535.805	1
605		18	max	.006	3	.081	1	.189	4	5.527e-3	5	NC	5	NC	1
606			min	-.004	2	-.053	3	-.009	1	-9.339e-3	2	1736.687	1	NC	1
607		19	max	.006	3	.158	1	.149	4	6.831e-3	3	NC	1	NC	1
608			min	-.004	2	-.106	3	0	12	-1.853e-2	2	NC	1	NC	1

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 4.00 x 0.28

<Figure 1>



<Figure 2>

Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	1020.0	27.0	565.0	565.6
Sum	1020.0	27.0	565.0	565.6

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 1020
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	5.247	10215

$\phi N_{cb} = \phi (A_{Nc} / A_{Nco}) \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-4)

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cb} (lb)
220.36	247.75	0.967	1.00	1.000	10215	0.65	5710

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_a = \phi (A_{Na} / A_{Na0}) \Psi_{ed,Na} \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16a)

A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	ϕ	ϕN_a (lb)
109.66	109.66	1.000	1.000	9755	0.55	5365

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in y-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cby} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cby} (lb)
192.89	220.50	0.925	1.000	1.000	6947	0.70	3934

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cbx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbx} (lb)
165.27	278.72	0.878	1.000	1.000	8282	0.70	3018

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
192.89	220.50	1.000	1.000	1.000	6947	0.70	8508

Shear parallel to edge in y-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cby} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cby} (lb)
165.27	278.72	1.000	1.000	1.000	8282	0.70	6875

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cp} = \phi \min|k_{cp}N_a\,;\, k_{cp}N_{cb}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\,\Psi_{p,Na}N_{a0}\,;\, k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ed,N}\,\Psi_{c,N}\,\Psi_{cp,N}N_b|$ (Eq. D-30a)

k_{cp}	A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	109.66	109.66	1.000	1.000	9755	9755

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ	ϕV_{cp} (lb)
220.36	247.75	0.967	1.000	1.000	10215	8785	0.70	12298

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, ϕN_n (lb)	Ratio	Status
Steel	1020	6071	0.17	Pass
Concrete breakout	1020	5710	0.18	Pass
Adhesive	**1020**	**5365**	**0.19**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, ϕV_n (lb)	Ratio	Status
Steel	**566**	**3156**	**0.18**	**Pass (Governs)**
T Concrete breakout y+	565	3934	0.14	Pass
T Concrete breakout x+	27	3018	0.01	Pass
|| Concrete breakout y+	27	8508	0.00	Pass
|| Concrete breakout x+	565	6875	0.08	Pass
Concrete breakout, combined	-	-	0.14	Pass
Pryout	566	12298	0.05	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status
Sec. D.7.1	0.19	0.00	19.0 %	1.0	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 7.00 x 0.28

<Figure 1>



<Figure 2>



Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	2495.5	1558.5	0.0	1558.5
2	2495.5	1558.5	0.0	1558.5
Sum	4991.0	3117.0	0.0	3117.0

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 4991
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	6.000	12492

$\phi N_{cbg} = \phi (A_{Nc} / A_{Nco}) \Psi_{ec,N} \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-5)

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cbg} (lb)
378.00	324.00	1.000	0.972	1.00	1.000	12492	0.65	9208

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_{ag} = \phi (A_{Na} / A_{Na0}) \Psi_{ed,Na} \Psi_{g,Na} \Psi_{ec,Na} \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16b)

A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0}(lb)	ϕ	ϕN_{ag} (lb)
158.66	109.66	1.000	1.043	1.000	1.000	9755	0.55	8093

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	12.00	15593

$\phi V_{cbgx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ec,V}\Psi_{ed,V}\Psi_{c,V}\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-22)

A_{Vc} (in²)	A_{Vco} (in²)	$\Psi_{ec,V}$	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbgx} (lb)
378.00	648.00	1.000	0.836	1.000	1.000	15593	0.70	5323

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	8.16	8744

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\Psi_{c,V}\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in²)	A_{Vco} (in²)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
299.64	299.64	1.000	1.000	1.000	8744	0.70	12241

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cpg} = \phi \min|k_{cp}N_{ag}\,;\, k_{cp}N_{cbg}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\Psi_{g,Na}\Psi_{ec,Na}\Psi_{p,Na}N_{a0}\,;\, k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ec,N}\Psi_{ed,N}\Psi_{c,N}\Psi_{cp,N}N_b|$ (Eq. D-30b)

k_{cp}	A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	158.66	109.66	1.000	1.043	1.000	1.000	9755	14715

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ
378.00	324.00	1.000	0.972	1.000	1.000	12492	14166	0.70

ϕV_{cpg} (lb)
19833

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, øN_n (lb)	Ratio	Status
Steel	2496	6071	0.41	Pass
Concrete breakout	4991	9208	0.54	Pass
Adhesive	**4991**	**8093**	**0.62**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, øV_n (lb)	Ratio	Status
Steel	1559	3156	0.49	Pass
T Concrete breakout x+	**3117**	**5323**	**0.59**	**Pass (Governs)**

|| Concrete breakout y-	**1559**	**12241**	**0.13**	**Pass (Governs)**
Pryout	3117	19833	0.16	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status
Sec. D.7.3	0.62	0.59	120.2 %	1.2	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.