

Schletter, Inc.		20° Tilt w/ Seismic Design
HCV	Standard PVMax Racking System	
	Representative Calculations - ASCE 7-10	

1. INTRODUCTION

1.1 Project Description

The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. PVMax ground mount system.

1.2 Construction

Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to aluminum struts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

	Maximum		Minimum
Height =	2000 mm	Height =	1900 mm
Width =	1050 mm	Width =	970 mm
Dead Load =	3.00 psf	Dead Load =	1.75 psf

Modules Per Row = 2
Module Tilt = 20°
Maximum Height Above Grade = 3 ft



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

1.3 Technical Codes

- ASCE 7-10 - Chapter 26-31, Wind Loads
- ASCE 7-10 - Chapter 7, Snow Loads
- ASCE 7-10 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2012, 2015
- Aluminum Design Manual, Eight Edition, 2005

2. LOAD ACTIONS

2.1 Permanent Loads

g_{MAX} = 3.00 psf
g_{MIN} = 1.75 psf

Self-weight of the PV modules.

2.2 Snow Loads

Ground Snow Load, P_g =	30.00 psf	
Sloped Roof Snow Load, P_s =	20.62 psf	*(ASCE 7-10, Eq. 7.4-1)*
I_s =	1.00	
C_s =	0.91	
C_e =	0.90	
C_t =	1.20	

2.3 Wind Loads

Design Wind Speed, V = 130 mph — Exposure Category = C
Height < 15 ft — Importance Category = II

Peak Velocity Pressure, q_z = 26.53 psf *Including the gust factor, G=0.85. (ASCE 7-10, Eq. 27.3-1)*

Pressure Coefficients

$Cf+_{TOP}$	=	1.050	*(Pressure)*
$Cf+_{BOTTOM}$	=	1.650	
$Cf-_{TOP,\ OUTER\ PURLIN}$	=	-2.400	
$Cf-_{TOP,\ INNER\ PURLIN}$	=	-1.840	*(Suction)*
$Cf-_{BOTTOM}$	=	-1.000	

Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0611-1e. Negative forces are applied away from the surface.

2.4 Seismic Loads

S_S =	2.50	R =	1.25
S_{DS} =	1.67	C_S =	0.8
S_1 =	1.00	ρ =	1.3
S_{D1} =	1.00	Ω =	1.25
T_a =	0.39	C_d =	1.25

ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.5W
1.2D + 1.0W + 0.5S
0.9D + 1.0W ^{M}
1.54D + 1.3E + 0.2S ^{R}
0.56D + 1.3E ^{R}
1.54D + 1.25E + 0.2S ^{O}
0.56D + 1.25E ^{O}

(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S
1.0D + 0.6W
1.0D + 0.75L + 0.45W + 0.75S
0.6D + 0.6W ^{M}
1.238D + 0.875E ^{O}
1.1785D + 0.65625E + 0.75S ^{O}
0.362D + 0.875E ^{O}

(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)

^{M} *Uses the minimum allowable module dead load.*
^{R} *Include redundancy factor of 1.3.*
^{O} *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location	**Diagonal Struts**	Location	**Front Reactions**	Location
M13	Top	M3	Outer	N7	Outer
M14	Mid-Top	M7	Inner	N15	Inner
M15	Mid-Bottom	M11	Outer	N23	Outer
M16	Bottom				

Girders	Location	**Rear Struts**	Location	**Rear Reactions**	Location
M1	Outer	M2	Outer	N8	Outer
M5	Inner	M6	Inner	N16	Inner
M9	Outer	M10	Outer	N24	Outer

Front Struts	Location
M4	Outer
M8	Inner
M12	Outer

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type =	**S1.5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	102	in
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	25.07	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	23.08	ksi
S_y =	1.33	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	2.16	in^4
I_x =	1.07	in^4
A =	1.25	in^2
g =	1.50	lbs/ft
M_y =	1.705	k-ft
M_z =	0.262	k-ft
$M_{y\ allowable}$ =	2.779	k-ft
$M_{z\ allowable}$ =	1.154	k-ft
Utilization =	84%	



4.2 Girder Design

Loads from purlins are transferred using an inclined girder, which is connected to a set of aluminum struts. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type =	**BF0**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	104.56	in
$\Phi F_{ty\ AXIAL}$ =	31.09	ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	29.00	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	33.25	ksi
S_y =	1.42	in^3
S_x =	1.41	in^3
E =	10100	ksi
I_y =	2.39	in^4
I_x =	2.22	in^4
A =	1.88	in^2
g =	2.26	lbs/ft
M_y =	-3.383	k-ft
M_z =	0.000	k-ft
P_n =	-0.434	k
$M_{y\ allowable}$ =	3.422	k-ft
$M_{z\ allowable}$ =	3.907	k-ft
$P_{n\ allowable}$ =	58.535	k
Utilization =	100%	



4.3 Front Strut Design

The front aluminum strut connects a portion of the girder to the foundation. Vertical girder forces are then transferred down through the strut into the foundation. The strut is attached with single M12 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	24.80	in
$\Phi F_{ty\ AXIAL}$ =	28.03	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.000	k-ft
M_z =	-0.510	k-ft
P_n =	0.626	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	27.532	k
Utilization =	39%	



4.4 Diagonal Strut Design

A diagonal aluminum strut braces the support structure. It connects at a front portion of the girder and transfers horizontal forces to the rear foundation connection. The strut is attached with single M12 bolts at each end. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	98.03	in
$\Phi F_{ty\ AXIAL}$ =	6.11	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.013	k-ft
M_z =	0.000	k-ft
P_n =	1.760	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	6.000	k
Utilization =	30%	



4.5 Rear Strut Design

An aluminum strut connects the rear portion of the girder to the rear foundation connection. Both vertical and horizontal forces are transferred from the girder. The strut is attached with single M12 bolts at each end. See Appendix A.5 for detailed member calculations. Section units are in (mm).

Strut Type =	55x55	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	61.10	in
$\Phi F_{ty\ AXIAL}$ =	13.63	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	-0.011	k-ft
M_z =	0.000	k-ft
P_n =	3.480	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	13.386	k
Utilization =	27%	



5. FOUNDATION DESIGN CALCULATIONS

5.1 Helical Pile Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete foundation design.

Maximum	Front	Rear	
Tensile Load =	993.13	5529.35	k
Compressive Load =	4299.45	4863.00	k
Lateral Load =	337.54	2478.87	k
Moment (Weak Axis) =	0.69	0.38	k

5.2 Design of Ballast Foundations

Ballast foundations are used to secure the racking structure in place. The foundations are checked for potential overturning and sliding. Bearing pressures applied by the racking and ballast foundations are checked against the allowable bearing pressures provided by the IBC table 1806.2 (2012).



Concrete Properties		**Footing Reinforcement**
Weight of Concrete =	145 pcf	*Use fiber reinforcing with (2) #5 rebar.*
Compressive Strength =	2500 psi	
Yield Strength =	60000 psi	
Overturning Check		
M_O =	289537.6 in-lbs	
Resisting Force Required =	3328.02 lbs	*A minimum 174in long x 32in wide x 12in tall ballast foundation is required to resist overturning.*
S.F. =	1.67	
Weight Required =	5546.70 lbs	
Minimum Width =	32 in	
Weight Provided =	5606.67 lbs	
Sliding		
Force =	1143.68 lbs	
Friction =	0.4	*Use a 174in long x 32in wide x 12in tall ballast foundation to resist sliding. Friction is OK.*
Weight Required =	2859.21 lbs	
Resisting Weight =	5606.67 lbs	
Additional Weight Required =	0 lbs	
Cohesion		
Sliding Force =	1143.68 lbs	
Cohesion =	130 psf	
Area =	38.67 ft^2	*Use a 174in long x 32in wide x 12in tall ballast foundation. Cohesion is OK.*
Resisting =	2803.33 lbs	
Additional Weight Required =	0 lbs	
Shear Key		
Additional Force =	0 lbs	
Lateral Bearing Pressure =	200 psf/ft	
Required Depth =	0.00 ft	*Shear key is not required.*
f'_c =	2500 psi	
Length =	8 in	

Bearing Pressure *(Meyerhof, 1953)*

	Ballast Width			
	32 in	33 in	34 in	35 in
P_{ftg} = (145 pcf)(14.5 ft)(1 ft)(2.67 ft) =	5607 lbs	5782 lbs	5957 lbs	6132 lbs

ASD LC	1.0D + 1.0S				1.0D + 0.6W				1.0D + 0.75L + 0.45W + 0.75S				0.6D + 0.6W			
Width	32 in	33 in	34 in	35 in	32 in	33 in	34 in	35 in	32 in	33 in	34 in	35 in	32 in	33 in	34 in	35 in
F_A	1493 lbs	1493 lbs	1493 lbs	1493 lbs	1467 lbs	1467 lbs	1467 lbs	1467 lbs	2098 lbs	2098 lbs	2098 lbs	2098 lbs	-449 lbs	-449 lbs	-449 lbs	-449 lbs
F_B	1604 lbs	1604 lbs	1604 lbs	1604 lbs	1793 lbs	1793 lbs	1793 lbs	1793 lbs	2417 lbs	2417 lbs	2417 lbs	2417 lbs	-2543 lbs	-2543 lbs	-2543 lbs	-2543 lbs
F_V	156 lbs	156 lbs	156 lbs	156 lbs	1020 lbs	1020 lbs	1020 lbs	1020 lbs	871 lbs	871 lbs	871 lbs	871 lbs	-1144 lbs	-1144 lbs	-1144 lbs	-1144 lbs
P_{total}	8704 lbs	8879 lbs	9054 lbs	9230 lbs	8866 lbs	9042 lbs	9217 lbs	9392 lbs	10121 lbs	10296 lbs	10472 lbs	10647 lbs	372 lbs	478 lbs	583 lbs	688 lbs
M	7006 lbs-ft	7006 lbs-ft	7006 lbs-ft	7006 lbs-ft	5651 lbs-ft	5651 lbs-ft	5651 lbs-ft	5651 lbs-ft	8914 lbs-ft	8914 lbs-ft	8914 lbs-ft	8914 lbs-ft	2439 lbs-ft	2439 lbs-ft	2439 lbs-ft	2439 lbs-ft
e	0.80 ft	0.79 ft	0.77 ft	0.76 ft	0.64 ft	0.63 ft	0.61 ft	0.60 ft	0.88 ft	0.87 ft	0.85 ft	0.84 ft	6.55 ft	5.11 ft	4.19 ft	3.55 ft
L'	12.89 ft	12.92 ft	12.95 ft	12.98 ft	13.23 ft	13.25 ft	13.27 ft	13.30 ft	12.74 ft	12.77 ft	12.80 ft	12.83 ft	1.40 ft	4.28 ft	6.13 ft	7.41 ft
A'	34.4 sqft	35.5 sqft	36.7 sqft	37.9 sqft	35.3 sqft	36.4 sqft	37.6 sqft	38.8 sqft	34.0 sqft	35.1 sqft	36.3 sqft	37.4 sqft	3.7 sqft	11.8 sqft	17.4 sqft	21.6 sqft
$f_{meyerhof}$	253.2 psf	249.9 psf	246.7 psf	243.8 psf	251.4 psf	248.1 psf	245.1 psf	242.2 psf	298.0 psf	293.2 psf	288.8 psf	284.6 psf	99.7 psf	40.5 psf	33.6 psf	31.8 psf

Maximum Bearing Pressure = 298 psf
Allowable Bearing Pressure = 1500 psf

Use a 174in long x 32in wide x 12in tall ballast foundation for an acceptable bearing pressure.

Seismic Design

Overturning Check

M_O = 2821.0 ft-lbs
Resisting Force Required = 2115.78 lbs
S.F. = 1.67
Weight Required = 3526.29 lbs
Minimum Width = 32 in in
Weight Provided = 5606.67 lbs

A minimum 174in long x 32in wide x 12in tall ballast foundation is required to resist overturning.



Bearing Pressure *(Meyerhof, 1953)*

ASD LC	1.238D + 0.875E			1.1785D + 0.65625E + 0.75S			0.362D + 0.875E		
Width	32 in			32 in			32 in		
Support	Outer	Inner	Outer	Outer	Inner	Outer	Outer	Inner	Outer
F_Y	281 lbs	628 lbs	213 lbs	911 lbs	2540 lbs	858 lbs	106 lbs	184 lbs	38 lbs
F_V	212 lbs	207 lbs	215 lbs	156 lbs	151 lbs	167 lbs	212 lbs	208 lbs	213 lbs
P_{total}	7222 lbs	7569 lbs	7154 lbs	7518 lbs	9148 lbs	7465 lbs	2135 lbs	2213 lbs	2068 lbs
M	751 lbs-ft	741 lbs-ft	758 lbs-ft	566 lbs-ft	566 lbs-ft	597 lbs-ft	748 lbs-ft	738 lbs-ft	751 lbs-ft
e	0.10 ft	0.10 ft	0.11 ft	0.08 ft	0.06 ft	0.08 ft	0.35 ft	0.33 ft	0.36 ft
B'	2.46 ft	2.47 ft	2.45 ft	2.52 ft	2.54 ft	2.51 ft	1.97 ft	2.00 ft	1.94 ft
A'	35.7 sqft	35.8 sqft	35.6 sqft	36.5 sqft	36.9 sqft	36.3 sqft	28.5 sqft	29.0 sqft	28.1 sqft
$f_{meyerhof}$	202.6 psf	211.3 psf	201.0 psf	206.1 psf	248.1 psf	205.4 psf	74.9 psf	76.3 psf	73.5 psf

Maximum Bearing Pressure = 248 psf
Allowable Bearing Pressure = 1500 psf

Use a 174in long x 32in wide x 12in tall ballast foundation for an acceptable bearing pressure.

Foundation Requirements: 174in long x 32in wide x 12in tall ballast foundation and fiber reinforcing with (2) #5 rebar.

5.3 Foundation Anchors

Threaded rods are anchored to the the ballast foundations using the Simpson AT-XP epoxy solution. LRFD load results are compared to the allowable strengths of the epoxy solution. Please see the supplementary calculations provided by the Simpson Anchor Designer software.

6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of 80mm mounting clamps. The reliability of calculations is uncertain due to limited standards, therefore the strength of the clamp fasteners has been evaluated by load testing.

Fastening of Modules to Purlins		
Maximum Uplifting Force =	0.702	k
Allowable Uplift =	1.214	k
Utilization =	58%	



Fastening of Purlins to Girders		
Maximum Uplifting Force =	2.117	k
Allowable Uplift =	4.357	k
Utilization =	49%	



6.2 Strut Connections

The aluminum struts connect the front end of girder to a center section of the steel post. Single M12 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Front Strut		
Maximum Axial Load =	3.307	k
M12 Bolt Capacity =	12.808	k
Strut Bearing Capacity =	7.421	k
Utilization =	45%	

Rear Strut		
Maximum Axial Load =	3.804	k
M12 Bolt Capacity =	12.808	k
Strut Bearing Capacity =	7.421	k
Utilization =	51%	

Diagonal Strut		
Maximum Axial Load =	1.901	k
M12 Bolt Shear Capacity =	12.808	k
Strut Bearing Capacity =	7.421	k
Utilization =	26%	

Bolt and bearing capacities are accounting for double shear. (ASCE 8-02, Eq. 5.3.4-1)



Struts under compression are shown to demonstrate the load transfer from the girder. Single M12 bolts are located at each end of the strut and are subjected to double shear.

7. SEISMIC DESIGN

7.1 Seismic Drift

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx} =	51.89	in
Allowable Story Drift for All Other Structures, Δ = {	$0.020h_{sx}$	
	1.038	in
Max Drift, Δ_{MAX} =	0.649	in

$0.649 \le 1.038$, OK.

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **S1.5**

Strong Axis:		Weak Axis:	
3.4.14		**3.4.14**	
L_b =	102 in	L_b =	102
J =	0.432	J =	0.432
	282.18		179.449
$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$		$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$	
S1 =	0.51461	S1 =	0.51461
$S2 = \left(\frac{C_c}{1.6}\right)^2$		$S2 = \left(\frac{C_c}{1.6}\right)^2$	
S2 =	1701.56	S2 =	1701.56
φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]	φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L=	27.9 ksi	φF_L=	29.0
3.4.16		**3.4.16**	
b/t =	32.195	b/t =	37.0588
$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$		$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$	
S1 =	12.2	S1 =	12.2
$S2 = \frac{k_1 Bp}{1.6Dp}$		$S2 = \frac{k_1 Bp}{1.6Dp}$	
S2 =	46.7	S2 =	46.7
φF_L=	φb[Bp-1.6Dp*b/t]	φF_L=	φb[Bp-1.6Dp*b/t]
φF_L=	25.1 ksi	φF_L=	23.1 ksi
3.4.16.1	Not Used	**3.4.16.1**	
Rb/t =		N/A for Weak Direction	
$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$			
S1 =	1.1		
$S2 = C_t$			
S2 =	141.0		
φF_L=	1.17φyFcy		
φF_L=	38.9 ksi		
3.4.18		**3.4.18**	
h/t =	37.0588	h/t =	32.195
$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$		$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$	
S1 =	36.9	S1 =	36.9
m =	0.65	m =	0.65
C_0 =	40.985	C_0 =	45.5
Cc =	41.015	Cc =	45.5
$S2 = \frac{k_1 Bbr}{mDbr}$		$S2 = \frac{k_1 Bbr}{mDbr}$	
S2 =	77.2	S2 =	77.3
φF_L=	φb[Bbr-mDbr*h/t]	φF_L=	1.3φyFcy
φF_L=	43.2 ksi	φF_L=	43.2 ksi
$\varphi F_L St$=	25.1 ksi	$\varphi F_L Wk$=	23.1 ksi
Ix =	897074 mm^4	Iy =	446476 mm^4
	2.155 in^4		1.073 in^4
y =	41.015 mm	x =	45.5 mm
Sx =	1.335 in^3	Sy =	0.599 in^3
$M_{max}St$ =	2.788 k-ft	$M_{max}Wk$ =	1.152 k-ft

Compression

3.4.9

b/t = 32.195
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L= φc[Bp-1.6Dp*b/t]
φF_L= 25.1 ksi

b/t = 37.0588
S1 = 12.21
S2 = 32.70
φF_L= (φck2*√(BpE))/(1.6b/t)
φF_L= 21.9 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L= φyFcy
φF_L= 33.25 ksi

φF_L= 21.94 ksi
A = 1215.13 mm^2
1.88 in^2
P_{max} = 41.32 kips

A.2 Design of Aluminum Girders - Aluminum Design Manual, 2005 Edition

Girder = **BF0**

Strong Axis:

3.4.14

L_b = 104.56 in
J = 1.08
179.85

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L= 29.0 ksi

3.4.16

b/t = 16.2

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L= φb[Bp-1.6Dp*b/t]
φF_L= 31.6 ksi

Weak Axis:

3.4.14

L_b = 104.56
J = 1.08
190.335

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L= 28.9

3.4.16

b/t = 7.4

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L= φyFcy
φF_L= 33.3 ksi

3.4.16.1 Used

Rb/t = 18.1

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= φb[Bt-Dt*√(Rb/t)]

φF_L= 31.1 ksi

3.4.18

h/t = 7.4

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 35.2

m = 0.68

C_0 = 41.067

Cc = 43.717

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 73.8

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 29.0 ksi

Ix = 984962 mm^4

2.366 in^4

y = 43.717 mm

Sx = 1.375 in³

M_{max}St = 3.323 k-ft

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 16.2

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 40

Cc = 40

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 33.3 ksi

Iy = 923544 mm^4

2.219 in^4

x = 40 mm

Sy = 1.409 in³

M_{max}Wk = 3.904 k-ft

Compression

3.4.9

b/t = 16.2

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 31.6 ksi

b/t = 7.4

S1 = 12.21

S2 = 32.70

φF_L= φyFcy

φF_L= 33.3 ksi

3.4.10

Rb/t = 18.1

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L= φc[Bt-Dt*√(Rb/t)]

φF_L= 31.09 ksi

φF_L= 31.09 ksi

A = 1215.13 mm^2

1.88 in^2

P_{max} = 58.55 kips

A.3 Design of Aluminum Struts (Front) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 24.8 in

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

Weak Axis:

3.4.14

L_b = 24.8

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 0.57371

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.87952

φF_L= φcc(Bc-Dc*λ)

φF_L= 28.0279 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L= φyFcy

φF_L= 33.25 ksi

φF_L= 28.03 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 28.85 kips

A.4 Design of Aluminum Struts (Diagonal) - Aluminum Design Manual, 2005 Edition

Strut = <u>**55x55**</u>

Strong Axis:

3.4.14

L_b = 98.03 in

J = 0.942

152.985

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 29.4 ksi

Weak Axis:

3.4.14

L_b = 98.03

J = 0.942

152.985

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 29.4

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16 (weak direction)

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt=	28.2 ksi		φF_LWk=	28.2 ksi	
Ix =	279836 mm^4		Iy =	279836 mm^4	
	0.672 in^4			0.672 in^4	
y =	27.5 mm		x =	27.5 mm	
Sx =	0.621 in³		Sy =	0.621 in³	
M_{max}St =	1.460 k-ft		M_{max}Wk =	1.460 k-ft	

Compression

3.4.7

λ = 2.26776

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.89749

φF_L= (φccFcy)/(λ²)

φF_L= 6.10803 ksi

3.4.9

b/t = 24.5
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L= φc[Bp-1.6Dp*b/t]
φF_L= 28.2 ksi

b/t = 24.5
S1 = 12.21
S2 = 32.70
φF_L= φc[Bp-1.6Dp*b/t]
φF_L= 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L= φyFcy
φF_L= 33.25 ksi

φF_L= 6.11 ksi
A = 663.99 mm^2
1.03 in^2
P_{max} = 6.29 kips

A.5 Design of Aluminum Struts (Rear) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 61.10 in
J = 0.942
95.3524

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L= 30.2 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L= φb[Bp-1.6Dp*b/t]
φF_L= 28.2 ksi

Weak Axis:

3.4.14

L_b = 61.1
J = 0.942
95.3524

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L= 30.2

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L= φb[Bp-1.6Dp*b/t]
φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 1.41345

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.77788

φF_L= (φccFcy)/(λ²)

φF_L= 13.6277 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

$\varphi F_L = \varphi yFcy$

$\varphi F_L =$ 33.25 ksi

$\varphi F_L =$ 13.63 ksi

A = 663.99 mm^2

1.03 in^2

$P_{max} =$ 14.03 kips

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				4		
2	Dead Load, Min	DL		-1				4		
3	Snow Load	SL						4		
4	Wind Load - Pressure	WL						4		
5	Wind Load - Suction	WL						4		
6	Seismic - Lateral	EL			.8			8		

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-9.843	-9.843	0	0
2	M14	Y	-9.843	-9.843	0	0
3	M15	Y	-9.843	-9.843	0	0
4	M16	Y	-9.843	-9.843	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-5.454	-5.454	0	0
2	M14	Y	-5.454	-5.454	0	0
3	M15	Y	-5.454	-5.454	0	0
4	M16	Y	-5.454	-5.454	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-63.565	-63.565	0	0
2	M14	Y	-63.565	-63.565	0	0
3	M15	Y	-63.565	-63.565	0	0
4	M16	Y	-63.565	-63.565	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	-91.409	-91.409	0	0
2	M14	y	-91.409	-91.409	0	0
3	M15	y	-143.642	-143.642	0	0
4	M16	y	-143.642	-143.642	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	208.934	208.934	0	0
2	M14	y	160.183	160.183	0	0
3	M15	y	87.056	87.056	0	0
4	M16	y	87.056	87.056	0	0

Member Distributed Loads (BLC 6 : Seismic - Lateral)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Z	7.874	7.874	0	0
2	M14	Z	7.874	7.874	0	0
3	M15	Z	7.874	7.874	0	0
4	M16	Z	7.874	7.874	0	0
5	M13	Z	0	0	0	0
6	M14	Z	0	0	0	0
7	M15	Z	0	0	0	0
8	M16	Z	0	0	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.5W	Yes	Y		1	1.2	3	1.6	4	.5														
2	LRFD 1.2D + 1.0W + 0.5S	Yes	Y		1	1.2	3	.5	4	1														
3	LRFD 0.9D + 1.0W	Yes	Y		2	.9					5	1												
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3												
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3												
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25												
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25												
8																								
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																
10	ASD 1.0D + 0.6W	Yes	Y		1	1			4	.6														
11	ASD 1.0D + 0.75L + 0.45W + 0....	Yes	Y		1	1	3	.75	4	.45														
12	ASD 0.6D + 0.6W	Yes	Y		2	.6					5	.6												
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875												
14	LATERAL - ASD 1.1785D + 0.65...	Yes	Y		1	1.1...	3	.75			6	.656												
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875												

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N8	max	489.067	2	1165.741	1	.832	1	.004	1	0	1	0	1
2		min	-625.503	3	-1336.76	3	-62.627	5	-.291	4	0	1	0	1
3	N7	max	.029	9	1188.865	1	-.576	12	-.001	12	0	1	0	1
4		min	-.174	2	-220.442	3	-259.649	4	-.528	4	0	1	0	1
5	N15	max	0	15	3307.269	1	0	3	0	2	0	1	0	1
6		min	-1.914	2	-763.947	3	-246.886	4	-.51	4	0	1	0	1
7	N16	max	1757.462	2	3740.769	1	0	2	0	1	0	1	0	1
8		min	-1906.822	3	-4253.348	3	-62.527	5	-.294	4	0	1	0	1
9	N23	max	.038	14	1188.865	1	10.819	1	.022	1	0	1	0	1
10		min	-.174	2	-220.442	3	-252.367	4	-.516	4	0	1	0	1
11	N24	max	489.067	2	1165.741	1	-.059	12	0	12	0	1	0	1
12		min	-625.503	3	-1336.76	3	-63.269	5	-.293	4	0	1	0	1
13	Totals:	max	2733.334	2	11757.25	1	0	2						
14		min	-3158.519	3	-8131.699	3	-941.59	4						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M13	1	max	74.834	4	481.002	1	-6.785	12	0	15	.188	1	0	4
2			min	3.908	12	-648.771	3	-158.721	1	-.015	2	.011	12	0	3
3		2	max	67.474	1	335.491	1	-5.436	12	0	15	.099	4	.522	3
4			min	3.908	12	-457.003	3	-121.47	1	-.015	2	.003	10	-.386	1
5		3	max	67.474	1	189.98	1	-4.087	12	0	15	.058	5	.863	3
6			min	3.908	12	-265.234	3	-84.219	1	-.015	2	-.041	1	-.634	1
7		4	max	67.474	1	44.469	1	-2.739	12	0	15	.032	5	1.023	3
8			min	3.908	12	-73.465	3	-46.969	1	-.015	2	-.103	1	-.744	1
9		5	max	67.474	1	118.304	3	-.299	10	0	15	.009	5	1.002	3
10			min	3.908	12	-101.042	1	-26.59	4	-.015	2	-.13	1	-.718	1
11		6	max	67.474	1	310.073	3	27.533	1	0	15	-.005	12	.8	3
12			min	2.895	15	-246.553	1	-21.85	5	-.015	2	-.121	1	-.554	1
13		7	max	67.474	1	501.842	3	64.783	1	0	15	-.005	12	.416	3
14			min	-6.67	5	-392.064	1	-19.798	5	-.015	2	-.078	1	-.252	1
15		8	max	67.474	1	693.61	3	102.034	1	0	15	.003	2	.187	1
16			min	-17.815	5	-537.575	1	-17.745	5	-.015	2	-.052	4	-.148	3
17		9	max	67.474	1	885.379	3	139.285	1	0	15	.115	1	.763	1
18			min	-28.96	5	-683.085	1	-15.693	5	-.015	2	-.066	5	-.894	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
19		10	max	67.474	1	1077.148	3	176.536	1	.005	14	.264	1	1.477	1
20			min	3.908	12	-828.596	1	-105.546	14	-.015	2	.005	12	-1.821	3
21		11	max	67.474	1	683.085	1	-4.004	12	.015	2	.115	1	.763	1
22			min	3.908	12	-885.379	3	-139.285	1	0	15	0	3	-.894	3
23		12	max	67.474	1	537.575	1	-2.655	12	.015	2	.051	4	.187	1
24			min	3.908	12	-693.61	3	-102.034	1	0	15	-.004	3	-.148	3
25		13	max	67.474	1	392.064	1	-1.307	12	.015	2	.024	5	.416	3
26			min	3.908	12	-501.842	3	-64.783	1	0	15	-.078	1	-.252	1
27		14	max	67.474	1	246.553	1	.23	3	.015	2	0	15	.8	3
28			min	1.919	15	-310.073	3	-30.936	4	0	15	-.121	1	-.554	1
29		15	max	67.474	1	101.042	1	9.718	1	.015	2	-.004	12	1.002	3
30			min	-8.211	5	-118.304	3	-22.765	5	0	15	-.13	1	-.718	1
31		16	max	67.474	1	73.465	3	46.969	1	.015	2	-.003	12	1.023	3
32			min	-19.355	5	-44.469	1	-20.713	5	0	15	-.103	1	-.744	1
33		17	max	67.474	1	265.234	3	84.219	1	.015	2	.001	3	.863	3
34			min	-30.5	5	-189.98	1	-18.66	5	0	15	-.072	4	-.634	1
35		18	max	67.474	1	457.003	3	121.47	1	.015	2	.056	1	.522	3
36			min	-41.645	5	-335.491	1	-16.608	5	0	15	-.079	5	-.386	1
37		19	max	67.474	1	648.771	3	158.721	1	.015	2	.188	1	0	1
38			min	-52.79	5	-481.002	1	-14.555	5	0	15	-.093	5	0	3
39	M14	1	max	52.073	4	541.678	1	-7.031	12	.012	3	.225	1	0	1
40			min	2.055	12	-524.14	3	-165.163	1	-.015	1	.013	12	0	3
41		2	max	40.928	4	396.167	1	-5.682	12	.012	3	.151	4	.426	3
42			min	2.055	12	-378.414	3	-127.912	1	-.015	1	.006	10	-.443	1
43		3	max	40.58	1	250.657	1	-4.333	12	.012	3	.089	5	.715	3
44			min	2.055	12	-232.688	3	-90.661	1	-.015	1	-.017	1	-.748	1
45		4	max	40.58	1	105.146	1	-2.985	12	.012	3	.05	5	.866	3
46			min	2.055	12	-86.961	3	-53.411	1	-.015	1	-.085	1	-.916	1
47		5	max	40.58	1	58.765	3	-.905	10	.012	3	.013	5	.879	3
48			min	-.947	5	-40.365	1	-42.527	4	-.015	1	-.118	1	-.947	1
49		6	max	40.58	1	204.491	3	21.091	1	.012	3	-.005	12	.755	3
50			min	-12.091	5	-185.876	1	-36.088	5	-.015	1	-.116	1	-.84	1
51		7	max	40.58	1	350.217	3	58.342	1	.012	3	-.004	12	.493	3
52			min	-23.236	5	-331.387	1	-34.036	5	-.015	1	-.078	1	-.596	1
53		8	max	40.58	1	495.943	3	95.592	1	.012	3	.001	10	.093	3
54			min	-34.381	5	-476.898	1	-31.983	5	-.015	1	-.09	4	-.214	1
55		9	max	40.58	1	641.67	3	132.843	1	.012	3	.103	1	.305	1
56			min	-45.526	5	-622.409	1	-29.93	5	-.015	1	-.116	5	-.444	3
57		10	max	69.264	4	787.396	3	170.094	1	.012	3	.246	1	.962	1
58			min	2.055	12	-767.92	1	-109.547	14	-.015	1	.004	12	-1.119	3
59		11	max	58.119	4	622.409	1	-3.758	12	.015	1	.151	4	.305	1
60			min	2.055	12	-641.67	3	-132.843	1	-.012	3	0	3	-.444	3
61		12	max	46.974	4	476.898	1	-2.409	12	.015	1	.087	4	.093	3
62			min	2.055	12	-495.943	3	-95.592	1	-.012	3	-.005	1	-.214	1
63		13	max	40.58	1	331.387	1	-1.061	12	.015	1	.047	5	.493	3
64			min	2.055	12	-350.217	3	-58.342	1	-.012	3	-.078	1	-.596	1
65		14	max	40.58	1	185.876	1	.601	3	.015	1	.01	5	.755	3
66			min	2.055	12	-204.491	3	-43.493	4	-.012	3	-.116	1	-.84	1
67		15	max	40.58	1	40.365	1	16.16	1	.015	1	-.004	12	.879	3
68			min	2.055	12	-58.765	3	-36.293	5	-.012	3	-.118	1	-.947	1
69		16	max	40.58	1	86.961	3	53.411	1	.015	1	-.002	12	.866	3
70			min	-6.138	5	-105.146	1	-34.24	5	-.012	3	-.085	1	-.916	1
71		17	max	40.58	1	232.688	3	90.661	1	.015	1	.003	3	.715	3
72			min	-17.283	5	-250.657	1	-32.187	5	-.012	3	-.096	4	-.748	1
73		18	max	40.58	1	378.414	3	127.912	1	.015	1	.086	1	.426	3
74			min	-28.428	5	-396.167	1	-30.135	5	-.012	3	-.12	5	-.443	1
75		19	max	40.58	1	524.14	3	165.163	1	.015	1	.225	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
76			min	-39.573	5	-541.678	1	-28.082	5	-.012	3	-.147	5	0	3
77	M15	1	max	84.707	5	641.87	2	-6.942	12	.016	1	.289	4	0	2
78			min	-43.01	1	-291.739	3	-165.134	1	-.01	3	.012	12	0	3
79		2	max	73.562	5	465.917	2	-5.594	12	.016	1	.202	4	.239	3
80			min	-43.01	1	-215.077	3	-127.883	1	-.01	3	.006	12	-.523	2
81		3	max	62.417	5	289.964	2	-4.245	12	.016	1	.126	5	.406	3
82			min	-43.01	1	-138.415	3	-90.633	1	-.01	3	-.017	1	-.88	2
83		4	max	51.272	5	114.371	1	-2.896	12	.016	1	.072	5	.501	3
84			min	-43.01	1	-61.753	3	-67.377	4	-.01	3	-.085	1	-1.071	2
85		5	max	40.127	5	14.909	3	-.945	10	.016	1	.021	5	.523	3
86			min	-43.01	1	-61.942	2	-57.625	4	-.01	3	-.118	1	-1.095	2
87		6	max	28.982	5	91.57	3	21.12	1	.016	1	-.005	12	.473	3
88			min	-43.01	1	-237.895	2	-51.169	5	-.01	3	-.116	1	-.954	2
89		7	max	17.838	5	168.232	3	58.37	1	.016	1	-.004	12	.35	3
90			min	-43.01	1	-413.848	2	-49.117	5	-.01	3	-.093	4	-.648	1
91		8	max	6.693	5	244.894	3	95.621	1	.016	1	.001	10	.155	3
92			min	-43.01	1	-589.801	2	-47.064	5	-.01	3	-.124	4	-.194	1
93		9	max	-2.544	12	321.556	3	132.872	1	.016	1	.103	1	.468	2
94			min	-43.01	1	-765.754	2	-45.012	5	-.01	3	-.164	5	-.113	3
95		10	max	-2.544	12	398.218	3	170.123	1	.016	1	.287	4	1.274	2
96			min	-43.01	1	-941.707	2	-117.227	14	-.005	14	.005	12	-.453	3
97		11	max	-.38	15	765.754	2	-3.846	12	.01	3	.199	4	.468	2
98			min	-43.01	1	-321.556	3	-132.872	1	-.016	1	0	3	-.113	3
99		12	max	-2.544	12	589.801	2	-2.498	12	.01	3	.121	4	.155	3
100			min	-43.01	1	-244.894	3	-95.621	1	-.016	1	-.005	1	-.194	1
101		13	max	-2.544	12	413.848	2	-1.149	12	.01	3	.067	5	.35	3
102			min	-43.01	1	-168.232	3	-68.371	4	-.016	1	-.078	1	-.648	1
103		14	max	-2.544	12	237.895	2	.454	3	.01	3	.015	5	.473	3
104			min	-43.923	4	-91.57	3	-58.62	4	-.016	1	-.116	1	-.954	2
105		15	max	-2.544	12	61.942	2	16.131	1	.01	3	-.004	12	.523	3
106			min	-55.068	4	-14.909	3	-51.374	5	-.016	1	-.118	1	-1.095	2
107		16	max	-2.544	12	61.753	3	53.382	1	.01	3	-.002	12	.501	3
108			min	-66.213	4	-114.371	1	-49.322	5	-.016	1	-.101	4	-1.071	2
109		17	max	-2.544	12	138.415	3	90.633	1	.01	3	.003	3	.406	3
110			min	-77.358	4	-289.964	2	-47.269	5	-.016	1	-.133	4	-.88	2
111		18	max	-2.544	12	215.077	3	127.883	1	.01	3	.086	1	.239	3
112			min	-88.503	4	-465.917	2	-45.217	5	-.016	1	-.171	5	-.523	2
113		19	max	-2.544	12	291.739	3	165.134	1	.01	3	.224	1	0	2
114			min	-99.648	4	-641.87	2	-43.164	5	-.016	1	-.213	5	0	5
115	M16	1	max	80.402	5	586.223	2	-6.509	12	.012	1	.204	4	0	2
116			min	-75.03	1	-250.321	3	-159.211	1	-.012	3	.01	12	0	3
117		2	max	69.257	5	410.27	2	-5.16	12	.012	1	.136	4	.2	3
118			min	-75.03	1	-173.659	3	-121.961	1	-.012	3	.004	10	-.471	2
119		3	max	58.112	5	234.317	2	-3.811	12	.012	1	.085	5	.328	3
120			min	-75.03	1	-96.997	3	-84.71	1	-.012	3	-.04	1	-.775	2
121		4	max	46.968	5	58.364	2	-2.463	12	.012	1	.049	5	.383	3
122			min	-75.03	1	-20.335	3	-47.459	1	-.012	3	-.102	1	-.913	2
123		5	max	35.823	5	56.327	3	-.489	10	.012	1	.015	5	.366	3
124			min	-75.03	1	-117.589	2	-37.377	4	-.012	3	-.129	1	-.885	2
125		6	max	24.678	5	132.988	3	27.042	1	.012	1	-.005	12	.277	3
126			min	-75.03	1	-293.542	2	-32.495	5	-.012	3	-.121	1	-.691	2
127		7	max	13.533	5	209.65	3	64.293	1	.012	1	-.004	12	.115	3
128			min	-75.03	1	-469.495	2	-30.443	5	-.012	3	-.078	1	-.331	2
129		8	max	2.388	5	286.312	3	101.544	1	.012	1	.002	2	.201	1
130			min	-75.03	1	-645.448	2	-28.39	5	-.012	3	-.075	4	-.119	3
131		9	max	-3.936	12	362.974	3	138.794	1	.012	1	.114	1	.888	2
132			min	-75.03	1	-821.401	2	-26.337	5	-.012	3	-.1	5	-.426	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
133		10	max	-3.936	12	439.636	3	176.045	1	.012	1	.262	1	1.747	2
134			min	-75.03	1	-997.354	2	-110.799	14	-.012	3	.006	12	-.805	3
135		11	max	.572	5	821.401	2	-4.28	12	.012	3	.137	4	.888	2
136			min	-75.03	1	-362.974	3	-138.794	1	-.012	1	.001	12	-.426	3
137		12	max	-3.936	12	645.448	2	-2.931	12	.012	3	.075	4	.201	1
138			min	-75.03	1	-286.312	3	-101.544	1	-.012	1	-.003	3	-.119	3
139		13	max	-3.936	12	469.495	2	-1.583	12	.012	3	.037	5	.115	3
140			min	-75.03	1	-209.65	3	-64.293	1	-.012	1	-.078	1	-.331	2
141		14	max	-3.936	12	293.542	2	-.232	3	.012	3	.003	5	.277	3
142			min	-75.03	1	-132.988	3	-41.551	4	-.012	1	-.121	1	-.691	2
143		15	max	-3.936	12	117.589	2	10.209	1	.012	3	-.004	12	.366	3
144			min	-75.03	1	-56.327	3	-33.388	5	-.012	1	-.129	1	-.885	2
145		16	max	-3.936	12	20.335	3	47.459	1	.012	3	-.003	12	.383	3
146			min	-75.03	1	-58.364	2	-31.335	5	-.012	1	-.102	1	-.913	2
147		17	max	-3.936	12	96.997	3	84.71	1	.012	3	0	3	.328	3
148			min	-82.844	4	-234.317	2	-29.282	5	-.012	1	-.098	4	-.775	2
149		18	max	-3.936	12	173.659	3	121.961	1	.012	3	.058	1	.2	3
150			min	-93.989	4	-410.27	2	-27.23	5	-.012	1	-.116	5	-.471	2
151		19	max	-3.936	12	250.321	3	159.211	1	.012	3	.191	1	0	2
152			min	-105.134	4	-586.223	2	-25.177	5	-.012	1	-.14	5	0	5
153	M2	1	max	1119.129	1	2.213	4	.796	1	0	3	0	3	0	1
154			min	-1196.132	3	.544	15	-54.587	4	0	1	0	1	0	1
155		2	max	1119.545	1	2.204	4	.796	1	0	3	0	1	0	15
156			min	-1195.82	3	.542	15	-54.948	4	0	1	-.015	4	0	4
157		3	max	1119.961	1	2.195	4	.796	1	0	3	0	1	0	15
158			min	-1195.508	3	.54	15	-55.308	4	0	1	-.031	4	-.001	4
159		4	max	1120.377	1	2.186	4	.796	1	0	3	0	1	0	15
160			min	-1195.196	3	.538	15	-55.668	4	0	1	-.046	4	-.002	4
161		5	max	1120.793	1	2.178	4	.796	1	0	3	0	1	0	15
162			min	-1194.884	3	.536	15	-56.029	4	0	1	-.062	4	-.002	4
163		6	max	1121.209	1	2.169	4	.796	1	0	3	.001	1	0	15
164			min	-1194.572	3	.534	15	-56.389	4	0	1	-.078	4	-.003	4
165		7	max	1121.625	1	2.16	4	.796	1	0	3	.001	1	0	15
166			min	-1194.26	3	.532	15	-56.75	4	0	1	-.094	4	-.004	4
167		8	max	1122.04	1	2.152	4	.796	1	0	3	.002	1	-.001	15
168			min	-1193.948	3	.529	15	-57.11	4	0	1	-.11	4	-.004	4
169		9	max	1122.456	1	2.143	4	.796	1	0	3	.002	1	-.001	15
170			min	-1193.637	3	.527	15	-57.471	4	0	1	-.126	4	-.005	4
171		10	max	1122.872	1	2.134	4	.796	1	0	3	.002	1	-.001	15
172			min	-1193.325	3	.525	15	-57.831	4	0	1	-.142	4	-.005	4
173		11	max	1123.288	1	2.125	4	.796	1	0	3	.002	1	-.001	15
174			min	-1193.013	3	.523	15	-58.192	4	0	1	-.158	4	-.006	4
175		12	max	1123.704	1	2.117	4	.796	1	0	3	.002	1	-.002	15
176			min	-1192.701	3	.521	15	-58.552	4	0	1	-.174	4	-.007	4
177		13	max	1124.12	1	2.108	4	.796	1	0	3	.003	1	-.002	15
178			min	-1192.389	3	.519	15	-58.913	4	0	1	-.191	4	-.007	4
179		14	max	1124.536	1	2.099	4	.796	1	0	3	.003	1	-.002	15
180			min	-1192.077	3	.517	15	-59.273	4	0	1	-.207	4	-.008	4
181		15	max	1124.952	1	2.091	4	.796	1	0	3	.003	1	-.002	15
182			min	-1191.765	3	.515	15	-59.634	4	0	1	-.224	4	-.008	4
183		16	max	1125.367	1	2.082	4	.796	1	0	3	.003	1	-.002	15
184			min	-1191.453	3	.513	15	-59.994	4	0	1	-.241	4	-.009	4
185		17	max	1125.783	1	2.073	4	.796	1	0	3	.004	1	-.002	15
186			min	-1191.141	3	.511	15	-60.355	4	0	1	-.258	4	-.01	4
187		18	max	1126.199	1	2.064	4	.796	1	0	3	.004	1	-.003	15
188			min	-1190.829	3	.509	15	-60.715	4	0	1	-.275	4	-.01	4
189		19	max	1126.615	1	2.056	4	.796	1	0	3	.004	1	-.003	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
190			min	-1190.517	3	.507	15	-61.076	4	0	1	-.292	4	-.011	4
191	M3	1	max	487.197	2	9.134	4	.188	1	0	3	0	1	.011	4
192			min	-624.065	3	2.161	15	-3.255	5	0	4	-.005	4	.003	15
193		2	max	487.026	2	8.259	4	.188	1	0	3	0	1	.007	4
194			min	-624.193	3	1.956	15	-2.647	5	0	4	-.006	4	.001	12
195		3	max	486.856	2	7.385	4	.188	1	0	3	0	1	.003	2
196			min	-624.321	3	1.75	15	-2.038	5	0	4	-.007	4	0	3
197		4	max	486.685	2	6.51	4	.188	1	0	3	0	1	0	2
198			min	-624.449	3	1.544	15	-1.429	5	0	4	-.008	5	-.002	3
199		5	max	486.515	2	5.636	4	.188	1	0	3	0	1	0	15
200			min	-624.576	3	1.339	15	-.82	5	0	4	-.009	5	-.003	3
201		6	max	486.345	2	4.762	4	.188	1	0	3	0	1	-.001	15
202			min	-624.704	3	1.133	15	-.212	5	0	4	-.009	5	-.006	6
203		7	max	486.174	2	3.887	4	.457	4	0	3	0	1	-.002	15
204			min	-624.832	3	.928	15	.01	12	0	4	-.009	5	-.008	6
205		8	max	486.004	2	3.013	4	1.066	4	0	3	0	1	-.002	15
206			min	-624.96	3	.722	15	.01	12	0	4	-.009	5	-.009	6
207		9	max	485.834	2	2.138	4	1.674	4	0	3	0	1	-.002	15
208			min	-625.087	3	.517	15	.01	12	0	4	-.008	5	-.011	6
209		10	max	485.663	2	1.264	4	2.283	4	0	3	0	1	-.003	15
210			min	-625.215	3	.311	15	.01	12	0	4	-.007	5	-.011	6
211		11	max	485.493	2	.426	2	2.892	4	0	3	0	1	-.003	15
212			min	-625.343	3	.003	3	.01	12	0	4	-.006	5	-.012	6
213		12	max	485.323	2	-.1	15	3.5	4	0	3	.001	1	-.003	15
214			min	-625.471	3	-.508	3	.01	12	0	4	-.004	5	-.012	6
215		13	max	485.152	2	-.306	15	4.109	4	0	3	.001	1	-.003	15
216			min	-625.599	3	-1.361	6	.01	12	0	4	-.003	5	-.011	6
217		14	max	484.982	2	-.511	15	4.718	4	0	3	.001	1	-.002	15
218			min	-625.726	3	-2.235	6	.01	12	0	4	0	5	-.01	6
219		15	max	484.812	2	-.717	15	5.327	4	0	3	.002	4	-.002	15
220			min	-625.854	3	-3.11	6	.01	12	0	4	0	12	-.009	6
221		16	max	484.641	2	-.922	15	5.935	4	0	3	.005	4	-.002	15
222			min	-625.982	3	-3.984	6	.01	12	0	4	0	12	-.008	6
223		17	max	484.471	2	-1.128	15	6.544	4	0	3	.008	4	-.001	15
224			min	-626.11	3	-4.859	6	.01	12	0	4	0	12	-.005	6
225		18	max	484.301	2	-1.333	15	7.153	4	0	3	.011	4	0	15
226			min	-626.237	3	-5.733	6	.01	12	0	4	0	12	-.003	6
227		19	max	484.13	2	-1.539	15	7.761	4	0	3	.015	4	0	1
228			min	-626.365	3	-6.607	6	.01	12	0	4	0	12	0	1
229	M4	1	max	1185.799	1	0	1	-.574	12	0	1	.009	4	0	1
230			min	-222.742	3	0	1	-258.303	4	0	1	0	12	0	1
231		2	max	1185.969	1	0	1	-.574	12	0	1	0	12	0	1
232			min	-222.614	3	0	1	-258.45	4	0	1	-.021	4	0	1
233		3	max	1186.139	1	0	1	-.574	12	0	1	0	12	0	1
234			min	-222.486	3	0	1	-258.598	4	0	1	-.051	4	0	1
235		4	max	1186.31	1	0	1	-.574	12	0	1	0	12	0	1
236			min	-222.358	3	0	1	-258.745	4	0	1	-.08	4	0	1
237		5	max	1186.48	1	0	1	-.574	12	0	1	0	12	0	1
238			min	-222.231	3	0	1	-258.893	4	0	1	-.11	4	0	1
239		6	max	1186.65	1	0	1	-.574	12	0	1	0	12	0	1
240			min	-222.103	3	0	1	-259.041	4	0	1	-.14	4	0	1
241		7	max	1186.821	1	0	1	-.574	12	0	1	0	12	0	1
242			min	-221.975	3	0	1	-259.188	4	0	1	-.17	4	0	1
243		8	max	1186.991	1	0	1	-.574	12	0	1	0	12	0	1
244			min	-221.847	3	0	1	-259.336	4	0	1	-.199	4	0	1
245		9	max	1187.161	1	0	1	-.574	12	0	1	0	12	0	1
246			min	-221.72	3	0	1	-259.484	4	0	1	-.229	4	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
247		10	max	1187.332	1	0	1	-.574	12	0	1	0	12	0	1
248			min	-221.592	3	0	1	-259.631	4	0	1	-.259	4	0	1
249		11	max	1187.502	1	0	1	-.574	12	0	1	0	12	0	1
250			min	-221.464	3	0	1	-259.779	4	0	1	-.289	4	0	1
251		12	max	1187.672	1	0	1	-.574	12	0	1	0	12	0	1
252			min	-221.336	3	0	1	-259.926	4	0	1	-.319	4	0	1
253		13	max	1187.843	1	0	1	-.574	12	0	1	0	12	0	1
254			min	-221.209	3	0	1	-260.074	4	0	1	-.348	4	0	1
255		14	max	1188.013	1	0	1	-.574	12	0	1	0	12	0	1
256			min	-221.081	3	0	1	-260.222	4	0	1	-.378	4	0	1
257		15	max	1188.183	1	0	1	-.574	12	0	1	0	12	0	1
258			min	-220.953	3	0	1	-260.369	4	0	1	-.408	4	0	1
259		16	max	1188.354	1	0	1	-.574	12	0	1	0	12	0	1
260			min	-220.825	3	0	1	-260.517	4	0	1	-.438	4	0	1
261		17	max	1188.524	1	0	1	-.574	12	0	1	0	12	0	1
262			min	-220.698	3	0	1	-260.665	4	0	1	-.468	4	0	1
263		18	max	1188.695	1	0	1	-.574	12	0	1	-.001	12	0	1
264			min	-220.57	3	0	1	-260.812	4	0	1	-.498	4	0	1
265		19	max	1188.865	1	0	1	-.574	12	0	1	-.001	12	0	1
266			min	-220.442	3	0	1	-260.96	4	0	1	-.528	4	0	1
267	M6	1	max	3472.558	1	2.552	2	0	1	0	1	0	4	0	1
268			min	-3803.676	3	.192	3	-55.167	4	0	4	0	1	0	1
269		2	max	3472.974	1	2.545	2	0	1	0	1	0	1	0	3
270			min	-3803.365	3	.187	3	-55.528	4	0	4	-.016	4	0	2
271		3	max	3473.39	1	2.539	2	0	1	0	1	0	1	0	3
272			min	-3803.053	3	.182	3	-55.888	4	0	4	-.031	4	-.001	2
273		4	max	3473.806	1	2.532	2	0	1	0	1	0	1	0	3
274			min	-3802.741	3	.177	3	-56.249	4	0	4	-.047	4	-.002	2
275		5	max	3474.222	1	2.525	2	0	1	0	1	0	1	0	3
276			min	-3802.429	3	.172	3	-56.609	4	0	4	-.063	4	-.003	2
277		6	max	3474.638	1	2.518	2	0	1	0	1	0	1	0	3
278			min	-3802.117	3	.167	3	-56.969	4	0	4	-.079	4	-.004	2
279		7	max	3475.054	1	2.511	2	0	1	0	1	0	1	0	3
280			min	-3801.805	3	.162	3	-57.33	4	0	4	-.095	4	-.004	2
281		8	max	3475.469	1	2.505	2	0	1	0	1	0	1	0	3
282			min	-3801.493	3	.157	3	-57.69	4	0	4	-.111	4	-.005	2
283		9	max	3475.885	1	2.498	2	0	1	0	1	0	1	0	3
284			min	-3801.181	3	.151	3	-58.051	4	0	4	-.127	4	-.006	2
285		10	max	3476.301	1	2.491	2	0	1	0	1	0	1	0	3
286			min	-3800.869	3	.146	3	-58.411	4	0	4	-.143	4	-.006	2
287		11	max	3476.717	1	2.484	2	0	1	0	1	0	1	0	3
288			min	-3800.557	3	.141	3	-58.772	4	0	4	-.16	4	-.007	2
289		12	max	3477.133	1	2.477	2	0	1	0	1	0	1	0	3
290			min	-3800.245	3	.136	3	-59.132	4	0	4	-.176	4	-.008	2
291		13	max	3477.549	1	2.471	2	0	1	0	1	0	1	0	3
292			min	-3799.934	3	.131	3	-59.493	4	0	4	-.193	4	-.008	2
293		14	max	3477.965	1	2.464	2	0	1	0	1	0	1	0	3
294			min	-3799.622	3	.126	3	-59.853	4	0	4	-.21	4	-.009	2
295		15	max	3478.381	1	2.457	2	0	1	0	1	0	1	0	3
296			min	-3799.31	3	.121	3	-60.214	4	0	4	-.226	4	-.01	2
297		16	max	3478.796	1	2.45	2	0	1	0	1	0	1	0	3
298			min	-3798.998	3	.116	3	-60.574	4	0	4	-.243	4	-.011	2
299		17	max	3479.212	1	2.443	2	0	1	0	1	0	1	0	3
300			min	-3798.686	3	.111	3	-60.935	4	0	4	-.26	4	-.011	2
301		18	max	3479.628	1	2.437	2	0	1	0	1	0	1	0	3
302			min	-3798.374	3	.106	3	-61.295	4	0	4	-.278	4	-.012	2
303		19	max	3480.044	1	2.43	2	0	1	0	1	0	1	0	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
304			min	-3798.062	3	.1	3	-61.656	4	0	4	-.295	4	-.013	2
305	M7	1	max	1759.943	2	9.139	6	0	1	0	1	0	1	.013	2
306			min	-1898.363	3	2.144	15	-3.465	5	0	4	-.005	4	0	3
307		2	max	1759.773	2	8.264	6	0	1	0	1	0	1	.009	2
308			min	-1898.491	3	1.939	15	-2.856	5	0	4	-.006	4	-.001	3
309		3	max	1759.603	2	7.39	6	0	1	0	1	0	1	.006	2
310			min	-1898.618	3	1.733	15	-2.248	5	0	4	-.008	4	-.003	3
311		4	max	1759.432	2	6.515	6	0	1	0	1	0	1	.003	2
312			min	-1898.746	3	1.528	15	-1.639	5	0	4	-.009	4	-.005	3
313		5	max	1759.262	2	5.641	6	0	1	0	1	0	1	0	2
314			min	-1898.874	3	1.322	15	-1.03	5	0	4	-.009	4	-.006	3
315		6	max	1759.092	2	4.766	6	0	1	0	1	0	1	-.001	15
316			min	-1899.002	3	1.117	15	-.422	5	0	4	-.01	4	-.007	3
317		7	max	1758.921	2	3.892	6	.201	4	0	1	0	1	-.002	15
318			min	-1899.129	3	.911	15	0	1	0	4	-.01	4	-.008	3
319		8	max	1758.751	2	3.017	6	.81	4	0	1	0	1	-.002	15
320			min	-1899.257	3	.706	15	0	1	0	4	-.009	4	-.009	4
321		9	max	1758.581	2	2.157	2	1.419	4	0	1	0	1	-.002	15
322			min	-1899.385	3	.441	12	0	1	0	4	-.009	4	-.011	4
323		10	max	1758.41	2	1.475	2	2.027	4	0	1	0	1	-.003	15
324			min	-1899.513	3	.087	3	0	1	0	4	-.008	4	-.011	4
325		11	max	1758.24	2	.794	2	2.636	4	0	1	0	1	-.003	15
326			min	-1899.64	3	-.424	3	0	1	0	4	-.007	4	-.012	4
327		12	max	1758.07	2	.112	2	3.245	4	0	1	0	1	-.003	15
328			min	-1899.768	3	-.935	3	0	1	0	4	-.005	4	-.012	4
329		13	max	1757.899	2	-.322	15	3.854	4	0	1	0	1	-.003	15
330			min	-1899.896	3	-1.446	3	0	1	0	4	-.004	4	-.011	4
331		14	max	1757.729	2	-.528	15	4.462	4	0	1	0	1	-.002	15
332			min	-1900.024	3	-2.229	4	0	1	0	4	-.002	4	-.01	4
333		15	max	1757.559	2	-.733	15	5.071	4	0	1	0	5	-.002	15
334			min	-1900.151	3	-3.104	4	0	1	0	4	0	1	-.009	4
335		16	max	1757.388	2	-.939	15	5.68	4	0	1	.003	4	-.002	15
336			min	-1900.279	3	-3.978	4	0	1	0	4	0	1	-.008	4
337		17	max	1757.218	2	-1.144	15	6.288	4	0	1	.006	4	-.001	15
338			min	-1900.407	3	-4.853	4	0	1	0	4	0	1	-.005	4
339		18	max	1757.048	2	-1.35	15	6.897	4	0	1	.009	4	0	15
340			min	-1900.535	3	-5.727	4	0	1	0	4	0	1	-.003	4
341		19	max	1756.877	2	-1.555	15	7.506	4	0	1	.012	4	0	1
342			min	-1900.662	3	-6.601	4	0	1	0	4	0	1	0	1
343	M8	1	max	3304.203	1	0	1	0	1	0	1	.007	4	0	1
344			min	-766.246	3	0	1	-249.034	4	0	1	0	1	0	1
345		2	max	3304.374	1	0	1	0	1	0	1	0	1	0	1
346			min	-766.119	3	0	1	-249.182	4	0	1	-.021	4	0	1
347		3	max	3304.544	1	0	1	0	1	0	1	0	1	0	1
348			min	-765.991	3	0	1	-249.329	4	0	1	-.05	4	0	1
349		4	max	3304.714	1	0	1	0	1	0	1	0	1	0	1
350			min	-765.863	3	0	1	-249.477	4	0	1	-.079	4	0	1
351		5	max	3304.885	1	0	1	0	1	0	1	0	1	0	1
352			min	-765.735	3	0	1	-249.624	4	0	1	-.107	4	0	1
353		6	max	3305.055	1	0	1	0	1	0	1	0	1	0	1
354			min	-765.608	3	0	1	-249.772	4	0	1	-.136	4	0	1
355		7	max	3305.225	1	0	1	0	1	0	1	0	1	0	1
356			min	-765.48	3	0	1	-249.92	4	0	1	-.165	4	0	1
357		8	max	3305.396	1	0	1	0	1	0	1	0	1	0	1
358			min	-765.352	3	0	1	-250.067	4	0	1	-.193	4	0	1
359		9	max	3305.566	1	0	1	0	1	0	1	0	1	0	1
360			min	-765.224	3	0	1	-250.215	4	0	1	-.222	4	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
361		10	max	3305.736	1	0	1	0	1	0	1	0	1	0	1
362			min	-765.096	3	0	1	-250.363	4	0	1	-.251	4	0	1
363		11	max	3305.907	1	0	1	0	1	0	1	0	1	0	1
364			min	-764.969	3	0	1	-250.51	4	0	1	-.279	4	0	1
365		12	max	3306.077	1	0	1	0	1	0	1	0	1	0	1
366			min	-764.841	3	0	1	-250.658	4	0	1	-.308	4	0	1
367		13	max	3306.247	1	0	1	0	1	0	1	0	1	0	1
368			min	-764.713	3	0	1	-250.806	4	0	1	-.337	4	0	1
369		14	max	3306.418	1	0	1	0	1	0	1	0	1	0	1
370			min	-764.585	3	0	1	-250.953	4	0	1	-.366	4	0	1
371		15	max	3306.588	1	0	1	0	1	0	1	0	1	0	1
372			min	-764.458	3	0	1	-251.101	4	0	1	-.395	4	0	1
373		16	max	3306.758	1	0	1	0	1	0	1	0	1	0	1
374			min	-764.33	3	0	1	-251.248	4	0	1	-.424	4	0	1
375		17	max	3306.929	1	0	1	0	1	0	1	0	1	0	1
376			min	-764.202	3	0	1	-251.396	4	0	1	-.452	4	0	1
377		18	max	3307.099	1	0	1	0	1	0	1	0	1	0	1
378			min	-764.074	3	0	1	-251.544	4	0	1	-.481	4	0	1
379		19	max	3307.269	1	0	1	0	1	0	1	0	1	0	1
380			min	-763.947	3	0	1	-251.691	4	0	1	-.51	4	0	1
381	M10	1	max	1119.129	1	2.103	6	-.045	12	0	1	0	4	0	1
382			min	-1196.132	3	.47	15	-55.008	4	0	5	0	3	0	1
383		2	max	1119.545	1	2.094	6	-.045	12	0	1	0	10	0	15
384			min	-1195.82	3	.468	15	-55.369	4	0	5	-.015	4	0	6
385		3	max	1119.961	1	2.085	6	-.045	12	0	1	0	12	0	15
386			min	-1195.508	3	.466	15	-55.729	4	0	5	-.031	4	-.001	6
387		4	max	1120.377	1	2.077	6	-.045	12	0	1	0	12	0	15
388			min	-1195.196	3	.464	15	-56.09	4	0	5	-.047	4	-.002	6
389		5	max	1120.793	1	2.068	6	-.045	12	0	1	0	12	0	15
390			min	-1194.884	3	.462	15	-56.45	4	0	5	-.062	4	-.002	6
391		6	max	1121.209	1	2.059	6	-.045	12	0	1	0	12	0	15
392			min	-1194.572	3	.46	15	-56.811	4	0	5	-.078	4	-.003	6
393		7	max	1121.625	1	2.051	6	-.045	12	0	1	0	12	0	15
394			min	-1194.26	3	.458	15	-57.171	4	0	5	-.094	4	-.003	6
395		8	max	1122.04	1	2.042	6	-.045	12	0	1	0	12	0	15
396			min	-1193.948	3	.456	15	-57.532	4	0	5	-.11	4	-.004	6
397		9	max	1122.456	1	2.033	6	-.045	12	0	1	0	12	-.001	15
398			min	-1193.637	3	.454	15	-57.892	4	0	5	-.127	4	-.005	6
399		10	max	1122.872	1	2.024	6	-.045	12	0	1	0	12	-.001	15
400			min	-1193.325	3	.452	15	-58.253	4	0	5	-.143	4	-.005	6
401		11	max	1123.288	1	2.016	6	-.045	12	0	1	0	12	-.001	15
402			min	-1193.013	3	.45	15	-58.613	4	0	5	-.159	4	-.006	6
403		12	max	1123.704	1	2.007	6	-.045	12	0	1	0	12	-.001	15
404			min	-1192.701	3	.448	15	-58.974	4	0	5	-.176	4	-.006	6
405		13	max	1124.12	1	1.998	6	-.045	12	0	1	0	12	-.002	15
406			min	-1192.389	3	.446	15	-59.334	4	0	5	-.192	4	-.007	6
407		14	max	1124.536	1	1.99	6	-.045	12	0	1	0	12	-.002	15
408			min	-1192.077	3	.444	15	-59.695	4	0	5	-.209	4	-.007	6
409		15	max	1124.952	1	1.981	6	-.045	12	0	1	0	12	-.002	15
410			min	-1191.765	3	.442	15	-60.055	4	0	5	-.226	4	-.008	6
411		16	max	1125.367	1	1.972	6	-.045	12	0	1	0	12	-.002	15
412			min	-1191.453	3	.44	15	-60.416	4	0	5	-.243	4	-.009	6
413		17	max	1125.783	1	1.963	6	-.045	12	0	1	0	12	-.002	15
414			min	-1191.141	3	.437	15	-60.776	4	0	5	-.26	4	-.009	6
415		18	max	1126.199	1	1.955	6	-.045	12	0	1	0	12	-.002	15
416			min	-1190.829	3	.435	15	-61.137	4	0	5	-.277	4	-.01	6
417		19	max	1126.615	1	1.946	6	-.045	12	0	1	0	12	-.002	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
418			min	-1190.517	3	.433	15	-61.497	4	0	5	-.294	4	-.01	6
419	M11	1	max	487.197	2	9.069	6	-.01	12	0	1	0	12	.01	6
420			min	-624.065	3	2.118	15	-3.294	4	0	4	-.005	4	.002	15
421		2	max	487.026	2	8.194	6	-.01	12	0	1	0	12	.006	2
422			min	-624.193	3	1.912	15	-2.686	4	0	4	-.006	4	.001	15
423		3	max	486.856	2	7.32	6	-.01	12	0	1	0	12	.003	2
424			min	-624.321	3	1.706	15	-2.077	4	0	4	-.007	4	0	3
425		4	max	486.685	2	6.446	6	-.01	12	0	1	0	12	0	2
426			min	-624.449	3	1.501	15	-1.468	4	0	4	-.008	4	-.002	3
427		5	max	486.515	2	5.571	6	-.01	12	0	1	0	12	0	15
428			min	-624.576	3	1.295	15	-.859	4	0	4	-.009	4	-.004	4
429		6	max	486.345	2	4.697	6	-.01	12	0	1	0	12	-.002	15
430			min	-624.704	3	1.09	15	-.251	4	0	4	-.009	4	-.006	4
431		7	max	486.174	2	3.822	6	.377	5	0	1	0	12	-.002	15
432			min	-624.832	3	.884	15	-.188	1	0	4	-.009	4	-.008	4
433		8	max	486.004	2	2.948	6	.985	5	0	1	0	12	-.002	15
434			min	-624.96	3	.679	15	-.188	1	0	4	-.009	4	-.01	4
435		9	max	485.834	2	2.073	6	1.594	5	0	1	0	12	-.003	15
436			min	-625.087	3	.473	15	-.188	1	0	4	-.008	4	-.011	4
437		10	max	485.663	2	1.199	6	2.203	5	0	1	0	12	-.003	15
438			min	-625.215	3	.268	15	-.188	1	0	4	-.007	4	-.012	4
439		11	max	485.493	2	.426	2	2.812	5	0	1	0	12	-.003	15
440			min	-625.343	3	.003	3	-.188	1	0	4	-.006	4	-.012	4
441		12	max	485.323	2	-.144	15	3.42	5	0	1	0	12	-.003	15
442			min	-625.471	3	-.551	4	-.188	1	0	4	-.005	4	-.012	4
443		13	max	485.152	2	-.349	15	4.029	5	0	1	0	12	-.003	15
444			min	-625.599	3	-1.426	4	-.188	1	0	4	-.003	4	-.012	4
445		14	max	484.982	2	-.555	15	4.638	5	0	1	0	12	-.003	15
446			min	-625.726	3	-2.3	4	-.188	1	0	4	-.001	1	-.011	4
447		15	max	484.812	2	-.76	15	5.246	5	0	1	.002	5	-.002	15
448			min	-625.854	3	-3.175	4	-.188	1	0	4	-.001	1	-.009	4
449		16	max	484.641	2	-.966	15	5.855	5	0	1	.004	5	-.002	15
450			min	-625.982	3	-4.049	4	-.188	1	0	4	-.001	1	-.008	4
451		17	max	484.471	2	-1.171	15	6.464	5	0	1	.007	5	-.001	15
452			min	-626.11	3	-4.924	4	-.188	1	0	4	-.001	1	-.005	4
453		18	max	484.301	2	-1.377	15	7.072	5	0	1	.01	5	0	15
454			min	-626.237	3	-5.798	4	-.188	1	0	4	-.002	1	-.003	4
455		19	max	484.13	2	-1.582	15	7.681	5	0	1	.014	5	0	1
456			min	-626.365	3	-6.672	4	-.188	1	0	4	-.002	1	0	1
457	M12	1	max	1185.799	1	0	1	11.212	1	0	1	.008	5	0	1
458			min	-222.742	3	0	1	-252.336	4	0	1	0	1	0	1
459		2	max	1185.969	1	0	1	11.212	1	0	1	0	1	0	1
460			min	-222.614	3	0	1	-252.484	4	0	1	-.021	4	0	1
461		3	max	1186.139	1	0	1	11.212	1	0	1	.002	1	0	1
462			min	-222.486	3	0	1	-252.631	4	0	1	-.05	4	0	1
463		4	max	1186.31	1	0	1	11.212	1	0	1	.003	1	0	1
464			min	-222.358	3	0	1	-252.779	4	0	1	-.079	4	0	1
465		5	max	1186.48	1	0	1	11.212	1	0	1	.004	1	0	1
466			min	-222.231	3	0	1	-252.927	4	0	1	-.108	4	0	1
467		6	max	1186.65	1	0	1	11.212	1	0	1	.005	1	0	1
468			min	-222.103	3	0	1	-253.074	4	0	1	-.137	4	0	1
469		7	max	1186.821	1	0	1	11.212	1	0	1	.007	1	0	1
470			min	-221.975	3	0	1	-253.222	4	0	1	-.166	4	0	1
471		8	max	1186.991	1	0	1	11.212	1	0	1	.008	1	0	1
472			min	-221.847	3	0	1	-253.37	4	0	1	-.195	4	0	1
473		9	max	1187.161	1	0	1	11.212	1	0	1	.009	1	0	1
474			min	-221.72	3	0	1	-253.517	4	0	1	-.224	4	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
475		10	max	1187.332	1	0	1	11.212	1	0	1	.011	1	0	1
476			min	-221.592	3	0	1	-253.665	4	0	1	-.253	4	0	1
477		11	max	1187.502	1	0	1	11.212	1	0	1	.012	1	0	1
478			min	-221.464	3	0	1	-253.812	4	0	1	-.282	4	0	1
479		12	max	1187.672	1	0	1	11.212	1	0	1	.013	1	0	1
480			min	-221.336	3	0	1	-253.96	4	0	1	-.312	4	0	1
481		13	max	1187.843	1	0	1	11.212	1	0	1	.014	1	0	1
482			min	-221.209	3	0	1	-254.108	4	0	1	-.341	4	0	1
483		14	max	1188.013	1	0	1	11.212	1	0	1	.016	1	0	1
484			min	-221.081	3	0	1	-254.255	4	0	1	-.37	4	0	1
485		15	max	1188.183	1	0	1	11.212	1	0	1	.017	1	0	1
486			min	-220.953	3	0	1	-254.403	4	0	1	-.399	4	0	1
487		16	max	1188.354	1	0	1	11.212	1	0	1	.018	1	0	1
488			min	-220.825	3	0	1	-254.551	4	0	1	-.428	4	0	1
489		17	max	1188.524	1	0	1	11.212	1	0	1	.02	1	0	1
490			min	-220.698	3	0	1	-254.698	4	0	1	-.458	4	0	1
491		18	max	1188.695	1	0	1	11.212	1	0	1	.021	1	0	1
492			min	-220.57	3	0	1	-254.846	4	0	1	-.487	4	0	1
493		19	max	1188.865	1	0	1	11.212	1	0	1	.022	1	0	1
494			min	-220.442	3	0	1	-254.994	4	0	1	-.516	4	0	1
495	M1	1	max	158.726	1	648.729	3	52.754	5	0	1	.188	1	0	15
496			min	-14.555	5	-478.854	1	-67.373	1	0	3	-.093	5	-.015	2
497		2	max	159.302	1	647.542	3	54.214	5	0	1	.147	1	.283	1
498			min	-14.286	5	-480.437	1	-67.373	1	0	3	-.06	5	-.405	3
499		3	max	402.564	3	570.986	1	2.491	5	0	3	.105	1	.57	1
500			min	-262.698	2	-487.301	3	-66.795	1	0	1	-.027	5	-.794	3
501		4	max	402.996	3	569.403	1	3.951	5	0	3	.063	1	.217	1
502			min	-262.122	2	-488.489	3	-66.795	1	0	1	-.025	5	-.491	3
503		5	max	403.429	3	567.82	1	5.411	5	0	3	.022	1	-.005	15
504			min	-261.546	2	-489.676	3	-66.795	1	0	1	-.022	5	-.188	3
505		6	max	403.861	3	566.236	1	6.872	5	0	3	-.001	12	.117	3
506			min	-260.969	2	-490.863	3	-66.795	1	0	1	-.022	4	-.488	1
507		7	max	404.293	3	564.653	1	8.332	5	0	3	-.003	12	.422	3
508			min	-260.393	2	-492.051	3	-66.795	1	0	1	-.061	1	-.839	1
509		8	max	404.725	3	563.07	1	9.792	5	0	3	-.005	15	.727	3
510			min	-259.817	2	-493.238	3	-66.795	1	0	1	-.103	1	-1.189	1
511		9	max	415.872	3	42.094	2	50.694	5	0	9	.066	1	.849	3
512			min	-195.22	2	.475	15	-107.421	1	0	3	-.134	5	-1.353	1
513		10	max	416.304	3	40.511	2	52.154	5	0	9	0	10	.829	3
514			min	-194.643	2	-.006	5	-107.421	1	0	3	-.103	4	-1.367	1
515		11	max	416.736	3	38.928	2	53.615	5	0	9	-.004	12	.81	3
516			min	-194.067	2	-1.986	4	-107.421	1	0	3	-.083	4	-1.38	1
517		12	max	427.737	3	325.076	3	144.709	5	0	2	.101	1	.708	3
518			min	-129.422	2	-608.819	1	-64.438	1	0	3	-.226	5	-1.22	1
519		13	max	428.169	3	323.889	3	146.169	5	0	2	.061	1	.507	3
520			min	-128.846	2	-610.403	1	-64.438	1	0	3	-.135	5	-.842	1
521		14	max	428.601	3	322.701	3	147.63	5	0	2	.021	1	.306	3
522			min	-128.269	2	-611.986	1	-64.438	1	0	3	-.044	5	-.463	1
523		15	max	429.033	3	321.514	3	149.09	5	0	2	.048	5	.106	3
524			min	-127.693	2	-613.569	1	-64.438	1	0	3	-.019	1	-.082	1
525		16	max	429.466	3	320.326	3	150.55	5	0	2	.141	5	.329	2
526			min	-127.117	2	-615.152	1	-64.438	1	0	3	-.059	1	-.093	3
527		17	max	429.898	3	319.139	3	152.01	5	0	2	.235	5	.708	2
528			min	-126.541	2	-616.735	1	-64.438	1	0	3	-.099	1	-.291	3
529		18	max	24.908	5	588.533	2	-3.937	12	0	5	.196	5	.355	2
530			min	-159.784	1	-249.214	3	-106.626	4	0	2	-.144	1	-.143	3
531		19	max	25.177	5	586.95	2	-3.937	12	0	5	.14	5	.012	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
532			min	-159.207	1	-250.402	3	-105.166	4	0	2	-.191	1	-.012	1
533	M5	1	max	353.061	1	2154.237	3	87.663	5	0	1	0	1	.03	2
534			min	10.706	12	-1647.525	1	0	1	0	4	-.193	4	0	15
535		2	max	353.637	1	2153.049	3	89.123	5	0	1	0	1	1.052	1
536			min	10.994	12	-1649.108	1	0	1	0	4	-.139	4	-1.331	3
537		3	max	1257.208	3	1595.244	1	40.845	4	0	4	0	1	2.04	1
538			min	-868.356	2	-1469.942	3	0	1	0	1	-.084	4	-2.628	3
539		4	max	1257.641	3	1593.661	1	42.305	4	0	4	0	1	1.051	1
540			min	-867.78	2	-1471.13	3	0	1	0	1	-.058	4	-1.715	3
541		5	max	1258.073	3	1592.078	1	43.765	4	0	4	0	1	.062	1
542			min	-867.204	2	-1472.317	3	0	1	0	1	-.031	4	-.802	3
543		6	max	1258.505	3	1590.495	1	45.225	4	0	4	0	1	.113	3
544			min	-866.628	2	-1473.505	3	0	1	0	1	-.004	5	-.925	1
545		7	max	1258.937	3	1588.912	1	46.685	4	0	4	.025	4	1.027	3
546			min	-866.051	2	-1474.692	3	0	1	0	1	0	1	-1.912	1
547		8	max	1259.369	3	1587.329	1	48.145	4	0	4	.054	4	1.943	3
548			min	-865.475	2	-1475.879	3	0	1	0	1	0	1	-2.898	1
549		9	max	1274.784	3	141.51	2	167.374	4	0	1	0	1	2.241	3
550			min	-728.975	2	.479	15	0	1	0	1	-.193	4	-3.29	1
551		10	max	1275.216	3	139.927	2	168.834	4	0	1	0	1	2.165	3
552			min	-728.399	2	.001	15	0	1	0	1	-.089	5	-3.337	1
553		11	max	1275.648	3	138.344	2	170.294	4	0	1	.017	4	2.09	3
554			min	-727.823	2	-1.766	6	0	1	0	1	0	1	-3.383	1
555		12	max	1291.354	3	945.14	3	196.877	4	0	1	0	1	1.83	3
556			min	-591.419	2	-1737.764	1	0	1	0	4	-.317	4	-3.01	1
557		13	max	1291.787	3	943.953	3	198.338	4	0	1	0	1	1.244	3
558			min	-590.843	2	-1739.347	1	0	1	0	4	-.195	4	-1.931	1
559		14	max	1292.219	3	942.766	3	199.798	4	0	1	0	1	.658	3
560			min	-590.267	2	-1740.93	1	0	1	0	4	-.071	4	-.851	1
561		15	max	1292.651	3	941.578	3	201.258	4	0	1	.053	4	.309	2
562			min	-589.691	2	-1742.513	1	0	1	0	4	0	1	0	15
563		16	max	1293.083	3	940.391	3	202.718	4	0	1	.179	4	1.384	2
564			min	-589.114	2	-1744.097	1	0	1	0	4	0	1	-.511	3
565		17	max	1293.515	3	939.204	3	204.178	4	0	1	.305	4	2.46	2
566			min	-588.538	2	-1745.68	1	0	1	0	4	0	1	-1.094	3
567		18	max	-11.545	12	1999.379	2	0	1	0	4	.3	4	1.26	2
568			min	-352.675	1	-878.416	3	-33.148	5	0	1	0	1	-.569	3
569		19	max	-11.256	12	1997.795	2	0	1	0	4	.281	4	.024	1
570			min	-352.099	1	-879.603	3	-31.688	5	0	1	0	1	-.023	3
571	M9	1	max	158.726	1	648.729	3	74.992	4	0	3	-.011	12	0	15
572			min	6.784	12	-478.854	1	3.908	12	0	4	-.188	1	-.015	2
573		2	max	159.302	1	647.542	3	76.452	4	0	3	-.009	12	.283	1
574			min	7.072	12	-480.437	1	3.908	12	0	4	-.147	1	-.405	3
575		3	max	402.564	3	570.986	1	66.795	1	0	1	-.006	12	.57	1
576			min	-262.698	2	-487.301	3	3.861	12	0	3	-.105	1	-.794	3
577		4	max	402.996	3	569.403	1	66.795	1	0	1	-.004	12	.217	1
578			min	-262.122	2	-488.489	3	3.861	12	0	3	-.063	1	-.491	3
579		5	max	403.429	3	567.82	1	66.795	1	0	1	-.001	12	-.005	15
580			min	-261.546	2	-489.676	3	3.861	12	0	3	-.029	4	-.188	3
581		6	max	403.861	3	566.236	1	66.795	1	0	1	.02	1	.117	3
582			min	-260.969	2	-490.863	3	3.861	12	0	3	-.016	5	-.488	1
583		7	max	404.293	3	564.653	1	66.795	1	0	1	.061	1	.422	3
584			min	-260.393	2	-492.051	3	3.861	12	0	3	-.006	5	-.839	1
585		8	max	404.725	3	563.07	1	66.795	1	0	1	.103	1	.727	3
586			min	-259.817	2	-493.238	3	3.861	12	0	3	.002	15	-1.189	1
587		9	max	415.872	3	42.094	2	107.421	1	0	3	-.004	12	.849	3
588			min	-195.22	2	.488	15	5.913	12	0	9	-.156	4	-1.353	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
589		10	max	416.304	3	40.511	2	107.421	1	0	3	.001	1	.829	3
590			min	-194.643	2	.011	15	5.913	12	0	9	-.102	4	-1.367	1
591		11	max	416.736	3	38.928	2	107.421	1	0	3	.068	1	.81	3
592			min	-194.067	2	-1.876	6	5.913	12	0	9	-.062	5	-1.38	1
593		12	max	427.737	3	325.076	3	167.673	4	0	3	-.005	12	.708	3
594			min	-129.422	2	-608.819	1	3.372	12	0	2	-.261	4	-1.22	1
595		13	max	428.169	3	323.889	3	169.133	4	0	3	-.003	12	.507	3
596			min	-128.846	2	-610.403	1	3.372	12	0	2	-.157	4	-.842	1
597		14	max	428.601	3	322.701	3	170.593	4	0	3	-.001	12	.306	3
598			min	-128.269	2	-611.986	1	3.372	12	0	2	-.051	4	-.463	1
599		15	max	429.033	3	321.514	3	172.053	4	0	3	.055	4	.106	3
600			min	-127.693	2	-613.569	1	3.372	12	0	2	0	12	-.082	1
601		16	max	429.466	3	320.326	3	173.513	4	0	3	.162	4	.329	2
602			min	-127.117	2	-615.152	1	3.372	12	0	2	.003	12	-.093	3
603		17	max	429.898	3	319.139	3	174.974	4	0	3	.271	4	.708	2
604			min	-126.541	2	-616.735	1	3.372	12	0	2	.005	12	-.291	3
605		18	max	-6.797	12	588.533	2	75.125	1	0	2	.245	4	.355	2
606			min	-159.784	1	-249.214	3	-82.026	5	0	3	.007	12	-.143	3
607		19	max	-6.509	12	586.95	2	75.125	1	0	2	.204	4	.012	3
608			min	-159.207	1	-250.402	3	-80.565	5	0	3	.01	12	-.012	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M13	1	max	0	1	.202	1	.008	3	1.358e-2	1	NC	1	NC	1
2			min	-.675	4	-.046	3	-.004	2	-2.875e-3	3	NC	1	NC	1
3		2	max	0	1	.146	3	.025	1	1.477e-2	1	NC	5	NC	2
4			min	-.675	4	.004	15	-.014	5	-2.657e-3	3	1064.22	3	8333.689	1
5		3	max	0	1	.302	3	.058	1	1.597e-2	1	NC	5	NC	3
6			min	-.675	4	-.01	9	-.018	5	-2.44e-3	3	587.071	3	3557.639	1
7		4	max	0	1	.398	3	.085	1	1.717e-2	1	NC	5	NC	3
8			min	-.675	4	-.046	1	-.014	5	-2.222e-3	3	460.233	3	2406.43	1
9		5	max	0	1	.422	3	.098	1	1.837e-2	1	NC	5	NC	3
10			min	-.675	4	-.038	1	-.005	5	-2.005e-3	3	436.209	3	2082.429	1
11		6	max	0	1	.377	3	.093	1	1.956e-2	1	NC	5	NC	3
12			min	-.675	4	-.004	9	.002	10	-1.787e-3	3	483.158	3	2191.116	1
13		7	max	0	1	.276	3	.072	1	2.076e-2	1	NC	4	NC	3
14			min	-.675	4	.004	15	0	10	-1.57e-3	3	635.032	3	2857.488	1
15		8	max	0	1	.241	2	.039	1	2.197e-2	2	NC	4	NC	2
16			min	-.675	4	.006	15	-.005	10	-1.352e-3	3	1063.238	3	5227.129	1
17		9	max	0	1	.328	2	.024	3	2.32e-2	2	NC	4	NC	1
18			min	-.675	4	.009	15	-.01	2	-1.135e-3	3	1560.766	2	NC	1
19		10	max	0	1	.37	1	.024	3	2.443e-2	2	NC	5	NC	1
20			min	-.675	4	-.025	3	-.017	2	-9.173e-4	3	1204.962	2	NC	1
21		11	max	0	12	.328	2	.024	3	2.32e-2	2	NC	4	NC	1
22			min	-.675	4	.009	15	-.011	5	-1.135e-3	3	1560.766	2	NC	1
23		12	max	0	12	.241	2	.039	1	2.197e-2	2	NC	4	NC	2
24			min	-.675	4	.006	15	-.011	5	-1.352e-3	3	1063.238	3	5227.129	1
25		13	max	0	12	.276	3	.072	1	2.076e-2	1	NC	4	NC	3
26			min	-.675	4	.003	15	-.004	5	-1.57e-3	3	635.032	3	2857.488	1
27		14	max	0	12	.377	3	.093	1	1.956e-2	1	NC	5	NC	3
28			min	-.675	4	-.004	9	.002	10	-1.787e-3	3	483.158	3	2191.116	1
29		15	max	0	12	.422	3	.098	1	1.837e-2	1	NC	5	NC	3
30			min	-.675	4	-.038	1	.004	10	-2.005e-3	3	436.209	3	2082.429	1
31		16	max	0	12	.398	3	.085	1	1.717e-2	1	NC	5	NC	3
32			min	-.675	4	-.046	1	.003	10	-2.222e-3	3	460.233	3	2406.43	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
33		17	max	0	12	.302	3	.058	1	1.597e-2	1	NC	5	NC	3
34			min	-.675	4	-.01	9	.002	10	-2.44e-3	3	587.071	3	3557.639	1
35		18	max	0	12	.146	3	.025	1	1.477e-2	1	NC	5	NC	2
36			min	-.675	4	.003	15	0	10	-2.657e-3	3	1064.22	3	8305.488	4
37		19	max	0	12	.202	1	.008	3	1.358e-2	1	NC	1	NC	1
38			min	-.675	4	-.046	3	-.004	2	-2.875e-3	3	NC	1	NC	1
39	M14	1	max	0	1	.35	3	.007	3	8.029e-3	1	NC	1	NC	1
40			min	-.515	4	-.617	1	-.004	2	-5.351e-3	3	NC	1	NC	1
41		2	max	0	1	.58	3	.016	1	9.311e-3	1	NC	5	NC	1
42			min	-.515	4	-.895	1	-.022	5	-6.313e-3	3	731.781	1	NC	1
43		3	max	0	1	.78	3	.044	1	1.059e-2	1	NC	5	NC	2
44			min	-.515	4	-1.144	1	-.027	5	-7.275e-3	3	387.091	1	4678.196	1
45		4	max	0	1	.93	3	.07	1	1.187e-2	1	NC	15	NC	3
46			min	-.515	4	-1.34	1	-.019	5	-8.237e-3	3	282.124	1	2924.29	1
47		5	max	0	1	1.021	3	.085	1	1.316e-2	1	9871.353	15	NC	3
48			min	-.515	4	-1.472	1	-.005	5	-9.199e-3	3	238.564	1	2421.492	1
49		6	max	0	1	1.049	3	.083	1	1.444e-2	1	9204.527	15	NC	3
50			min	-.515	4	-1.537	1	.002	10	-1.016e-2	3	221.515	1	2476.05	1
51		7	max	0	1	1.025	3	.065	1	1.572e-2	1	9182.682	15	NC	2
52			min	-.515	4	-1.545	1	0	10	-1.112e-2	3	219.806	1	3161.673	1
53		8	max	0	1	.967	3	.04	4	1.7e-2	1	9594.507	15	NC	2
54			min	-.515	4	-1.51	1	-.004	10	-1.209e-2	3	228.216	1	4950.564	4
55		9	max	0	1	.904	3	.027	4	1.828e-2	1	NC	15	NC	1
56			min	-.515	4	-1.462	1	-.009	2	-1.305e-2	3	241.323	1	7221.694	4
57		10	max	0	1	.872	3	.021	3	1.956e-2	1	NC	15	NC	1
58			min	-.515	4	-1.436	1	-.015	2	-1.401e-2	3	249.026	1	NC	1
59		11	max	0	12	.904	3	.022	3	1.828e-2	1	NC	15	NC	1
60			min	-.515	4	-1.462	1	-.022	5	-1.305e-2	3	241.323	1	NC	1
61		12	max	0	12	.967	3	.037	1	1.7e-2	1	9594.413	15	NC	2
62			min	-.515	4	-1.51	1	-.026	5	-1.209e-2	3	228.216	1	5669.664	1
63		13	max	0	12	1.025	3	.065	1	1.572e-2	1	9182.515	15	NC	2
64			min	-.515	4	-1.545	1	-.017	5	-1.112e-2	3	219.806	1	3161.673	1
65		14	max	0	12	1.049	3	.083	1	1.444e-2	1	9204.278	15	NC	3
66			min	-.515	4	-1.537	1	-.002	5	-1.016e-2	3	221.515	1	2476.05	1
67		15	max	0	12	1.021	3	.085	1	1.316e-2	1	9870.993	15	NC	3
68			min	-.515	4	-1.472	1	.003	10	-9.199e-3	3	238.564	1	2421.492	1
69		16	max	0	12	.93	3	.07	1	1.187e-2	1	NC	15	NC	3
70			min	-.515	4	-1.34	1	.003	10	-8.237e-3	3	282.124	1	2924.29	1
71		17	max	0	12	.78	3	.044	1	1.059e-2	1	NC	5	NC	2
72			min	-.515	4	-1.144	1	0	10	-7.275e-3	3	387.091	1	4678.196	1
73		18	max	0	12	.58	3	.028	4	9.311e-3	1	NC	5	NC	1
74			min	-.515	4	-.895	1	-.001	10	-6.313e-3	3	731.781	1	7014.429	4
75		19	max	0	12	.35	3	.007	3	8.029e-3	1	NC	1	NC	1
76			min	-.515	4	-.617	1	-.004	2	-5.351e-3	3	NC	1	NC	1
77	M15	1	max	0	12	.359	3	.007	3	4.493e-3	3	NC	1	NC	1
78			min	-.421	4	-.616	1	-.004	2	-8.189e-3	1	NC	1	NC	1
79		2	max	0	12	.523	3	.016	1	5.292e-3	3	NC	5	NC	1
80			min	-.421	4	-.919	1	-.032	5	-9.505e-3	1	673.659	1	6710.091	5
81		3	max	0	12	.67	3	.045	1	6.092e-3	3	NC	5	NC	2
82			min	-.421	4	-1.186	1	-.04	5	-1.082e-2	1	357.575	1	4650.381	1
83		4	max	0	12	.789	3	.071	1	6.891e-3	3	NC	15	NC	3
84			min	-.421	4	-1.394	1	-.03	5	-1.214e-2	1	262.094	1	2909.791	1
85		5	max	0	12	.873	3	.085	1	7.691e-3	3	9888.042	15	NC	3
86			min	-.421	4	-1.529	1	-.01	5	-1.345e-2	1	223.439	1	2409.751	1
87		6	max	0	12	.921	3	.084	1	8.491e-3	3	9221.971	15	NC	3
88			min	-.421	4	-1.588	1	.002	10	-1.477e-2	1	209.765	1	2462.503	1
89		7	max	0	12	.936	3	.066	1	9.29e-3	3	9202.489	15	NC	2

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
90			min	-.421	4	-1.582	1	0	10	-1.608e-2	1	211.112	1	3138.337	1
91		8	max	0	12	.926	3	.051	4	1.009e-2	3	9618.175	15	NC	2
92			min	-.421	4	-1.531	1	-.004	10	-1.74e-2	1	222.907	1	3964.96	4
93		9	max	0	12	.905	3	.036	4	1.089e-2	3	NC	15	NC	1
94			min	-.421	4	-1.467	1	-.008	2	-1.872e-2	1	239.636	1	5543.874	4
95		10	max	0	1	.894	3	.02	3	1.169e-2	3	NC	15	NC	1
96			min	-.421	4	-1.434	1	-.014	2	-2.003e-2	1	249.328	1	NC	1
97		11	max	0	1	.905	3	.02	3	1.089e-2	3	NC	15	NC	1
98			min	-.421	4	-1.467	1	-.03	5	-1.872e-2	1	239.636	1	7068.481	5
99		12	max	0	1	.926	3	.037	1	1.009e-2	3	9618.105	15	NC	2
100			min	-.421	4	-1.531	1	-.036	5	-1.74e-2	1	222.907	1	5592.888	1
101		13	max	0	1	.936	3	.066	1	9.29e-3	3	9202.369	15	NC	2
102			min	-.421	4	-1.582	1	-.024	5	-1.608e-2	1	211.112	1	3138.337	1
103		14	max	0	1	.921	3	.084	1	8.491e-3	3	9221.795	15	NC	3
104			min	-.421	4	-1.588	1	-.003	5	-1.477e-2	1	209.765	1	2462.503	1
105		15	max	0	1	.873	3	.085	1	7.691e-3	3	9887.791	15	NC	3
106			min	-.421	4	-1.529	1	.003	10	-1.345e-2	1	223.439	1	2409.751	1
107		16	max	0	1	.789	3	.071	1	6.891e-3	3	NC	15	NC	3
108			min	-.421	4	-1.394	1	.003	10	-1.214e-2	1	262.094	1	2909.791	1
109		17	max	0	1	.67	3	.056	4	6.092e-3	3	NC	5	NC	2
110			min	-.421	4	-1.186	1	.001	10	-1.082e-2	1	357.575	1	3587.998	4
111		18	max	0	1	.523	3	.039	4	5.292e-3	3	NC	5	NC	1
112			min	-.421	4	-.919	1	-.001	10	-9.505e-3	1	673.659	1	5168.117	4
113		19	max	0	1	.359	3	.007	3	4.493e-3	3	NC	1	NC	1
114			min	-.421	4	-.616	1	-.004	2	-8.189e-3	1	NC	1	NC	1
115	M16	1	max	0	12	.194	1	.006	3	8.381e-3	3	NC	1	NC	1
116			min	-.138	4	-.126	3	-.003	2	-1.262e-2	1	NC	1	NC	1
117		2	max	0	12	.053	1	.025	1	9.356e-3	3	NC	5	NC	2
118			min	-.138	4	-.073	3	-.022	5	-1.36e-2	1	1346.722	2	8417.309	1
119		3	max	0	12	.004	13	.058	1	1.033e-2	3	NC	5	NC	3
120			min	-.138	4	-.094	2	-.029	5	-1.459e-2	1	753.795	2	3570.768	1
121		4	max	0	12	0	5	.085	1	1.131e-2	3	NC	5	NC	3
122			min	-.138	4	-.159	2	-.023	5	-1.557e-2	1	607.306	2	2405.546	1
123		5	max	0	12	0	13	.099	1	1.228e-2	3	NC	5	NC	3
124			min	-.138	4	-.161	2	-.01	5	-1.655e-2	1	604.384	2	2073.605	1
125		6	max	0	12	.006	4	.094	1	1.326e-2	3	NC	5	NC	3
126			min	-.138	4	-.101	2	.003	15	-1.753e-2	1	735.183	2	2170.59	1
127		7	max	0	12	.055	1	.073	1	1.423e-2	3	NC	3	NC	3
128			min	-.138	4	-.122	3	.001	10	-1.851e-2	1	1203.566	2	2804.226	1
129		8	max	0	12	.183	1	.041	1	1.521e-2	3	NC	1	NC	2
130			min	-.138	4	-.186	3	-.003	10	-1.949e-2	1	3392.938	3	4999.424	1
131		9	max	0	12	.296	1	.022	4	1.618e-2	3	NC	5	NC	1
132			min	-.138	4	-.24	3	-.006	2	-2.047e-2	1	1778.665	3	8773.554	4
133		10	max	0	1	.347	1	.017	3	1.716e-2	3	NC	5	NC	1
134			min	-.138	4	-.264	3	-.013	2	-2.145e-2	1	1338.07	1	NC	1
135		11	max	0	1	.296	1	.018	3	1.618e-2	3	NC	5	NC	1
136			min	-.138	4	-.24	3	-.017	5	-2.047e-2	1	1778.665	3	NC	1
137		12	max	0	1	.183	1	.041	1	1.521e-2	3	NC	1	NC	2
138			min	-.138	4	-.186	3	-.018	5	-1.949e-2	1	3392.938	3	4999.424	1
139		13	max	0	1	.055	1	.073	1	1.423e-2	3	NC	3	NC	3
140			min	-.138	4	-.122	3	-.008	5	-1.851e-2	1	1203.566	2	2804.226	1
141		14	max	0	1	.006	6	.094	1	1.326e-2	3	NC	5	NC	3
142			min	-.138	4	-.101	2	.004	10	-1.753e-2	1	735.183	2	2170.59	1
143		15	max	0	1	0	13	.099	1	1.228e-2	3	NC	5	NC	3
144			min	-.138	4	-.161	2	.005	10	-1.655e-2	1	604.384	2	2073.605	1
145		16	max	0	1	0	15	.085	1	1.131e-2	3	NC	5	NC	3
146			min	-.138	4	-.159	2	.005	10	-1.557e-2	1	607.306	2	2405.546	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
147		17	max	0	1	.003	13	.058	1	1.033e-2	3	NC	5	NC	3
148			min	-.138	4	-.094	2	.003	10	-1.459e-2	1	753.795	2	3570.768	1
149		18	max	0	1	.053	1	.031	4	9.356e-3	3	NC	5	NC	2
150			min	-.138	4	-.073	3	0	10	-1.36e-2	1	1346.722	2	6380.836	4
151		19	max	0	1	.194	1	.006	3	8.381e-3	3	NC	1	NC	1
152			min	-.138	4	-.126	3	-.003	2	-1.262e-2	1	NC	1	NC	1
153	M2	1	max	.007	1	.007	2	.009	1	2.417e-3	5	NC	1	NC	2
154			min	-.007	3	-.011	3	-.635	4	-1.954e-4	1	9173.939	2	95.351	4
155		2	max	.006	1	.006	2	.008	1	2.422e-3	5	NC	1	NC	2
156			min	-.007	3	-.01	3	-.583	4	-1.83e-4	1	NC	1	103.91	4
157		3	max	.006	1	.005	2	.007	1	2.426e-3	5	NC	1	NC	2
158			min	-.006	3	-.01	3	-.531	4	-1.707e-4	1	NC	1	114.09	4
159		4	max	.005	1	.004	2	.007	1	2.431e-3	5	NC	1	NC	2
160			min	-.006	3	-.01	3	-.479	4	-1.583e-4	1	NC	1	126.32	4
161		5	max	.005	1	.003	2	.006	1	2.435e-3	5	NC	1	NC	1
162			min	-.005	3	-.009	3	-.429	4	-1.46e-4	1	NC	1	141.178	4
163		6	max	.005	1	.002	2	.005	1	2.44e-3	5	NC	1	NC	1
164			min	-.005	3	-.009	3	-.38	4	-1.336e-4	1	NC	1	159.474	4
165		7	max	.004	1	.001	2	.005	1	2.446e-3	4	NC	1	NC	1
166			min	-.005	3	-.009	3	-.332	4	-1.213e-4	1	NC	1	182.356	4
167		8	max	.004	1	0	2	.004	1	2.454e-3	4	NC	1	NC	1
168			min	-.004	3	-.008	3	-.286	4	-1.089e-4	1	NC	1	211.507	4
169		9	max	.004	1	0	2	.003	1	2.461e-3	4	NC	1	NC	1
170			min	-.004	3	-.008	3	-.243	4	-9.654e-5	1	NC	1	249.47	4
171		10	max	.003	1	0	15	.003	1	2.469e-3	4	NC	1	NC	1
172			min	-.003	3	-.007	3	-.202	4	-8.419e-5	1	NC	1	300.239	4
173		11	max	.003	1	0	15	.002	1	2.477e-3	4	NC	1	NC	1
174			min	-.003	3	-.007	3	-.164	4	-7.183e-5	1	NC	1	370.386	4
175		12	max	.003	1	0	15	.002	1	2.484e-3	4	NC	1	NC	1
176			min	-.003	3	-.006	3	-.128	4	-5.948e-5	1	NC	1	471.366	4
177		13	max	.002	1	0	15	.001	1	2.492e-3	4	NC	1	NC	1
178			min	-.002	3	-.005	3	-.097	4	-4.712e-5	1	NC	1	624.637	4
179		14	max	.002	1	0	15	0	1	2.5e-3	4	NC	1	NC	1
180			min	-.002	3	-.005	3	-.069	4	-3.477e-5	1	NC	1	874.389	4
181		15	max	.001	1	0	15	0	1	2.508e-3	4	NC	1	NC	1
182			min	-.002	3	-.004	3	-.046	4	-2.241e-5	1	NC	1	1324.22	4
183		16	max	.001	1	0	15	0	1	2.515e-3	4	NC	1	NC	1
184			min	-.001	3	-.003	3	-.027	4	-1.006e-5	1	NC	1	2267.709	4
185		17	max	0	1	0	15	0	1	2.523e-3	4	NC	1	NC	1
186			min	0	3	-.002	3	-.013	4	-5.402e-7	3	NC	1	4839.095	4
187		18	max	0	1	0	15	0	1	2.531e-3	4	NC	1	NC	1
188			min	0	3	-.001	6	-.003	4	4.181e-7	12	NC	1	NC	1
189		19	max	0	1	0	1	0	1	2.538e-3	4	NC	1	NC	1
190			min	0	1	0	1	0	1	1.154e-6	12	NC	1	NC	1
191	M3	1	max	0	1	0	1	0	1	-3.802e-7	12	NC	1	NC	1
192			min	0	1	0	1	0	1	-4.9e-4	4	NC	1	NC	1
193		2	max	0	3	0	15	.014	4	1.764e-4	4	NC	1	NC	1
194			min	0	2	-.002	6	0	12	8.847e-7	12	NC	1	NC	1
195		3	max	0	3	-.001	15	.028	4	8.428e-4	4	NC	1	NC	1
196			min	0	2	-.005	6	0	12	2.15e-6	12	NC	1	NC	1
197		4	max	.001	3	-.002	15	.041	4	1.509e-3	4	NC	1	NC	1
198			min	0	2	-.008	6	0	12	3.414e-6	12	NC	1	NC	1
199		5	max	.001	3	-.002	15	.054	4	2.176e-3	4	NC	1	NC	1
200			min	-.001	2	-.011	6	0	12	4.679e-6	12	9475.156	6	NC	1
201		6	max	.002	3	-.003	15	.066	4	2.842e-3	4	NC	1	NC	1
202			min	-.001	2	-.014	6	0	12	5.944e-6	12	7588.764	6	9003.683	5
203		7	max	.002	3	-.003	15	.078	4	3.508e-3	4	NC	5	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
204			min	-.002	2	-.016	6	0	12	7.209e-6	12	6458.03	6	8379.088	5
205		8	max	.002	3	-.004	15	.089	4	4.175e-3	4	NC	5	NC	1
206			min	-.002	2	-.018	6	0	12	8.474e-6	12	5760.03	6	8152.618	5
207		9	max	.003	3	-.004	15	.1	4	4.841e-3	4	NC	5	NC	1
208			min	-.002	2	-.019	6	0	12	9.739e-6	12	5343.235	6	8251.013	5
209		10	max	.003	3	-.004	15	.11	4	5.508e-3	4	NC	5	NC	1
210			min	-.002	2	-.02	6	0	12	1.1e-5	12	5133.713	6	8672.753	5
211		11	max	.003	3	-.004	15	.12	4	6.174e-3	4	NC	5	NC	1
212			min	-.003	2	-.02	6	0	12	1.227e-5	12	5100.101	6	9479.782	5
213		12	max	.004	3	-.004	15	.13	4	6.84e-3	4	NC	5	NC	1
214			min	-.003	2	-.02	6	0	12	1.353e-5	12	5241.5	6	NC	1
215		13	max	.004	3	-.004	15	.139	4	7.507e-3	4	NC	5	NC	1
216			min	-.003	2	-.018	6	0	12	1.48e-5	12	5588.608	6	NC	1
217		14	max	.004	3	-.004	15	.149	4	8.173e-3	4	NC	5	NC	1
218			min	-.003	2	-.017	6	0	12	1.606e-5	12	6220.054	6	NC	1
219		15	max	.005	3	-.003	15	.158	4	8.839e-3	4	NC	2	NC	1
220			min	-.004	2	-.014	6	0	12	1.733e-5	12	7311.747	6	NC	1
221		16	max	.005	3	-.002	15	.167	4	9.506e-3	4	NC	1	NC	1
222			min	-.004	2	-.011	6	0	12	1.859e-5	12	9290.973	6	NC	1
223		17	max	.005	3	-.002	15	.177	4	1.017e-2	4	NC	1	NC	1
224			min	-.004	2	-.008	1	0	12	1.986e-5	12	NC	1	NC	1
225		18	max	.006	3	0	15	.187	4	1.084e-2	4	NC	1	NC	1
226			min	-.005	2	-.005	1	0	12	2.112e-5	12	NC	1	NC	1
227		19	max	.006	3	0	5	.198	4	1.151e-2	4	NC	1	NC	1
228			min	-.005	2	-.003	1	0	12	2.239e-5	12	NC	1	NC	1
229	M4	1	max	.003	1	.004	2	0	12	6.991e-5	1	NC	1	NC	3
230			min	0	3	-.006	3	-.198	4	-8.917e-4	5	NC	1	125.469	4
231		2	max	.003	1	.004	2	0	12	6.991e-5	1	NC	1	NC	3
232			min	0	3	-.006	3	-.182	4	-8.917e-4	5	NC	1	136.612	4
233		3	max	.003	1	.004	2	0	12	6.991e-5	1	NC	1	NC	3
234			min	0	3	-.006	3	-.166	4	-8.917e-4	5	NC	1	149.863	4
235		4	max	.002	1	.004	2	0	12	6.991e-5	1	NC	1	NC	2
236			min	0	3	-.005	3	-.15	4	-8.917e-4	5	NC	1	165.772	4
237		5	max	.002	1	.003	2	0	12	6.991e-5	1	NC	1	NC	2
238			min	0	3	-.005	3	-.134	4	-8.917e-4	5	NC	1	185.085	4
239		6	max	.002	1	.003	2	0	12	6.991e-5	1	NC	1	NC	2
240			min	0	3	-.004	3	-.119	4	-8.917e-4	5	NC	1	208.837	4
241		7	max	.002	1	.003	2	0	12	6.991e-5	1	NC	1	NC	2
242			min	0	3	-.004	3	-.104	4	-8.917e-4	5	NC	1	238.498	4
243		8	max	.002	1	.003	2	0	12	6.991e-5	1	NC	1	NC	2
244			min	0	3	-.004	3	-.09	4	-8.917e-4	5	NC	1	276.212	4
245		9	max	.002	1	.002	2	0	12	6.991e-5	1	NC	1	NC	2
246			min	0	3	-.003	3	-.076	4	-8.917e-4	5	NC	1	325.206	4
247		10	max	.001	1	.002	2	0	12	6.991e-5	1	NC	1	NC	2
248			min	0	3	-.003	3	-.064	4	-8.917e-4	5	NC	1	390.526	4
249		11	max	.001	1	.002	2	0	12	6.991e-5	1	NC	1	NC	1
250			min	0	3	-.003	3	-.052	4	-8.917e-4	5	NC	1	480.427	4
251		12	max	.001	1	.002	2	0	12	6.991e-5	1	NC	1	NC	1
252			min	0	3	-.002	3	-.041	4	-8.917e-4	5	NC	1	609.192	4
253		13	max	0	1	.001	2	0	12	6.991e-5	1	NC	1	NC	1
254			min	0	3	-.002	3	-.031	4	-8.917e-4	5	NC	1	803.337	4
255		14	max	0	1	.001	2	0	12	6.991e-5	1	NC	1	NC	1
256			min	0	3	-.002	3	-.022	4	-8.917e-4	5	NC	1	1116.816	4
257		15	max	0	1	0	2	0	12	6.991e-5	1	NC	1	NC	1
258			min	0	3	-.001	3	-.015	4	-8.917e-4	5	NC	1	1674.03	4
259		16	max	0	1	0	2	0	12	6.991e-5	1	NC	1	NC	1
260			min	0	3	-.001	3	-.009	4	-8.917e-4	5	NC	1	2818.976	4

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
261		17	max	0	1	0	2	0	12	6.991e-5	1	NC	1	NC	1
262			min	0	3	0	3	-.004	4	-8.917e-4	5	NC	1	5827.641	4
263		18	max	0	1	0	2	0	12	6.991e-5	1	NC	1	NC	1
264			min	0	3	0	3	-.001	4	-8.917e-4	5	NC	1	NC	1
265		19	max	0	1	0	1	0	1	6.991e-5	1	NC	1	NC	1
266			min	0	1	0	1	0	1	-8.917e-4	5	NC	1	NC	1
267	M6	1	max	.02	1	.024	2	0	1	2.522e-3	4	NC	3	NC	1
268			min	-.022	3	-.033	3	-.642	4	0	1	2532.789	2	94.394	4
269		2	max	.019	1	.022	2	0	1	2.524e-3	4	NC	3	NC	1
270			min	-.021	3	-.031	3	-.589	4	0	1	2775.678	2	102.868	4
271		3	max	.018	1	.02	2	0	1	2.525e-3	4	NC	3	NC	1
272			min	-.02	3	-.03	3	-.536	4	0	1	3067.863	2	112.947	4
273		4	max	.017	1	.018	2	0	1	2.526e-3	4	NC	3	NC	1
274			min	-.018	3	-.028	3	-.484	4	0	1	3423.247	2	125.055	4
275		5	max	.016	1	.016	2	0	1	2.527e-3	4	NC	3	NC	1
276			min	-.017	3	-.026	3	-.433	4	0	1	3861.161	2	139.766	4
277		6	max	.015	1	.014	2	0	1	2.529e-3	4	NC	3	NC	1
278			min	-.016	3	-.024	3	-.384	4	0	1	4409.128	2	157.88	4
279		7	max	.014	1	.012	2	0	1	2.53e-3	4	NC	3	NC	1
280			min	-.015	3	-.022	3	-.335	4	0	1	5107.436	2	180.535	4
281		8	max	.012	1	.01	2	0	1	2.531e-3	4	NC	1	NC	1
282			min	-.014	3	-.021	3	-.289	4	0	1	6017.016	2	209.397	4
283		9	max	.011	1	.008	2	0	1	2.532e-3	4	NC	1	NC	1
284			min	-.012	3	-.019	3	-.245	4	0	1	7233.667	2	246.983	4
285		10	max	.01	1	.007	2	0	1	2.534e-3	4	NC	1	NC	1
286			min	-.011	3	-.017	3	-.204	4	0	1	8915.295	2	297.249	4
287		11	max	.009	1	.005	2	0	1	2.535e-3	4	NC	1	NC	1
288			min	-.01	3	-.015	3	-.165	4	0	1	NC	1	366.702	4
289		12	max	.008	1	.004	2	0	1	2.536e-3	4	NC	1	NC	1
290			min	-.009	3	-.013	3	-.13	4	0	1	NC	1	466.685	4
291		13	max	.007	1	.003	2	0	1	2.537e-3	4	NC	1	NC	1
292			min	-.007	3	-.011	3	-.098	4	0	1	NC	1	618.444	4
293		14	max	.006	1	.002	2	0	1	2.539e-3	4	NC	1	NC	1
294			min	-.006	3	-.01	3	-.07	4	0	1	NC	1	865.736	4
295		15	max	.005	1	.001	2	0	1	2.54e-3	4	NC	1	NC	1
296			min	-.005	3	-.008	3	-.046	4	0	1	NC	1	1311.148	4
297		16	max	.003	1	0	2	0	1	2.541e-3	4	NC	1	NC	1
298			min	-.004	3	-.006	3	-.027	4	0	1	NC	1	2245.403	4
299		17	max	.002	1	0	2	0	1	2.542e-3	4	NC	1	NC	1
300			min	-.002	3	-.004	3	-.013	4	0	1	NC	1	4791.777	4
301		18	max	.001	1	0	2	0	1	2.544e-3	4	NC	1	NC	1
302			min	-.001	3	-.002	3	-.004	4	0	1	NC	1	NC	1
303		19	max	0	1	0	1	0	1	2.545e-3	4	NC	1	NC	1
304			min	0	1	0	1	0	1	0	1	NC	1	NC	1
305	M7	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
306			min	0	1	0	1	0	1	-4.903e-4	4	NC	1	NC	1
307		2	max	.001	3	0	15	.014	4	1.576e-4	4	NC	1	NC	1
308			min	0	2	-.003	3	0	1	0	1	NC	1	NC	1
309		3	max	.002	3	-.001	15	.028	4	8.056e-4	4	NC	1	NC	1
310			min	-.002	2	-.006	3	0	1	0	1	NC	1	NC	1
311		4	max	.003	3	-.002	15	.041	4	1.454e-3	4	NC	1	NC	1
312			min	-.003	2	-.009	3	0	1	0	1	NC	1	NC	1
313		5	max	.004	3	-.003	15	.054	4	2.101e-3	4	NC	1	NC	1
314			min	-.004	2	-.012	3	0	1	0	1	8832.398	3	9053.375	4
315		6	max	.005	3	-.003	15	.066	4	2.749e-3	4	NC	1	NC	1
316			min	-.005	2	-.015	3	0	1	0	1	7409.313	3	7916.439	4
317		7	max	.006	3	-.004	15	.078	4	3.397e-3	4	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
318			min	-.006	2	-.017	3	0	1	0	1	6481.993	4	7306.56	4
319		8	max	.007	3	-.004	15	.089	4	4.045e-3	4	NC	2	NC	1
320			min	-.007	2	-.018	4	0	1	0	1	5779.732	4	7039.257	4
321		9	max	.008	3	-.005	15	.099	4	4.693e-3	4	NC	2	NC	1
322			min	-.008	2	-.02	4	0	1	0	1	5360.238	4	7040.032	4
323		10	max	.009	3	-.005	15	.11	4	5.341e-3	4	NC	5	NC	1
324			min	-.009	2	-.021	4	0	1	0	1	5149.034	4	7293.325	4
325		11	max	.01	3	-.005	15	.119	4	5.989e-3	4	NC	5	NC	1
326			min	-.01	2	-.021	4	0	1	0	1	5114.48	4	7829.768	4
327		12	max	.011	3	-.005	15	.129	4	6.637e-3	4	NC	5	NC	1
328			min	-.011	2	-.02	4	0	1	0	1	5255.553	4	8735.091	4
329		13	max	.012	3	-.004	15	.137	4	7.285e-3	4	NC	5	NC	1
330			min	-.012	2	-.019	4	0	1	0	1	5602.948	4	NC	1
331		14	max	.013	3	-.004	15	.146	4	7.933e-3	4	NC	2	NC	1
332			min	-.012	2	-.017	4	0	1	0	1	6235.421	4	NC	1
333		15	max	.015	3	-.003	15	.155	4	8.581e-3	4	NC	1	NC	1
334			min	-.013	2	-.015	4	0	1	0	1	7329.244	4	NC	1
335		16	max	.016	3	-.003	15	.164	4	9.229e-3	4	NC	1	NC	1
336			min	-.014	2	-.012	4	0	1	0	1	9312.643	4	NC	1
337		17	max	.017	3	-.002	15	.172	4	9.877e-3	4	NC	1	NC	1
338			min	-.015	2	-.01	1	0	1	0	1	NC	1	NC	1
339		18	max	.018	3	-.001	15	.182	4	1.052e-2	4	NC	1	NC	1
340			min	-.016	2	-.008	1	0	1	0	1	NC	1	NC	1
341		19	max	.019	3	0	15	.191	4	1.117e-2	4	NC	1	NC	1
342			min	-.017	2	-.006	1	0	1	0	1	NC	1	NC	1
343	M8	1	max	.008	1	.016	2	0	1	0	1	NC	1	NC	1
344			min	-.002	3	-.019	3	-.191	4	-1.003e-3	4	NC	1	129.735	4
345		2	max	.007	1	.015	2	0	1	0	1	NC	1	NC	1
346			min	-.002	3	-.018	3	-.176	4	-1.003e-3	4	NC	1	141.269	4
347		3	max	.007	1	.014	2	0	1	0	1	NC	1	NC	1
348			min	-.002	3	-.017	3	-.16	4	-1.003e-3	4	NC	1	154.983	4
349		4	max	.007	1	.013	2	0	1	0	1	NC	1	NC	1
350			min	-.002	3	-.016	3	-.145	4	-1.003e-3	4	NC	1	171.448	4
351		5	max	.006	1	.013	2	0	1	0	1	NC	1	NC	1
352			min	-.001	3	-.015	3	-.13	4	-1.003e-3	4	NC	1	191.435	4
353		6	max	.006	1	.012	2	0	1	0	1	NC	1	NC	1
354			min	-.001	3	-.014	3	-.115	4	-1.003e-3	4	NC	1	216.016	4
355		7	max	.005	1	.011	2	0	1	0	1	NC	1	NC	1
356			min	-.001	3	-.013	3	-.101	4	-1.003e-3	4	NC	1	246.712	4
357		8	max	.005	1	.01	2	0	1	0	1	NC	1	NC	1
358			min	-.001	3	-.011	3	-.087	4	-1.003e-3	4	NC	1	285.742	4
359		9	max	.004	1	.009	2	0	1	0	1	NC	1	NC	1
360			min	-.001	3	-.01	3	-.074	4	-1.003e-3	4	NC	1	336.445	4
361		10	max	.004	1	.008	2	0	1	0	1	NC	1	NC	1
362			min	0	3	-.009	3	-.061	4	-1.003e-3	4	NC	1	404.043	4
363		11	max	.004	1	.007	2	0	1	0	1	NC	1	NC	1
364			min	0	3	-.008	3	-.05	4	-1.003e-3	4	NC	1	497.082	4
365		12	max	.003	1	.006	2	0	1	0	1	NC	1	NC	1
366			min	0	3	-.007	3	-.039	4	-1.003e-3	4	NC	1	630.343	4
367		13	max	.003	1	.005	2	0	1	0	1	NC	1	NC	1
368			min	0	3	-.006	3	-.03	4	-1.003e-3	4	NC	1	831.269	4
369		14	max	.002	1	.004	2	0	1	0	1	NC	1	NC	1
370			min	0	3	-.005	3	-.021	4	-1.003e-3	4	NC	1	1155.703	4
371		15	max	.002	1	.004	2	0	1	0	1	NC	1	NC	1
372			min	0	3	-.004	3	-.014	4	-1.003e-3	4	NC	1	1732.403	4
373		16	max	.001	1	.003	2	0	1	0	1	NC	1	NC	1
374			min	0	3	-.003	3	-.009	4	-1.003e-3	4	NC	1	2917.424	4

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
375		17	max	0	1	.002	2	0	1	0	1	NC	1	NC	1
376			min	0	3	-.002	3	-.004	4	-1.003e-3	4	NC	1	6031.524	4
377		18	max	0	1	0	2	0	1	0	1	NC	1	NC	1
378			min	0	3	-.001	3	-.001	4	-1.003e-3	4	NC	1	NC	1
379		19	max	0	1	0	1	0	1	0	1	NC	1	NC	1
380			min	0	1	0	1	0	1	-1.003e-3	4	NC	1	NC	1
381	M10	1	max	.007	1	.007	2	0	12	2.503e-3	4	NC	1	NC	2
382			min	-.007	3	-.011	3	-.64	4	1.209e-5	12	9173.939	2	94.658	4
383		2	max	.006	1	.006	2	0	12	2.504e-3	4	NC	1	NC	2
384			min	-.007	3	-.01	3	-.587	4	1.135e-5	12	NC	1	103.155	4
385		3	max	.006	1	.005	2	0	12	2.506e-3	4	NC	1	NC	2
386			min	-.006	3	-.01	3	-.535	4	1.061e-5	12	NC	1	113.263	4
387		4	max	.005	1	.004	2	0	12	2.507e-3	4	NC	1	NC	2
388			min	-.006	3	-.01	3	-.483	4	9.879e-6	12	NC	1	125.404	4
389		5	max	.005	1	.003	2	0	12	2.508e-3	4	NC	1	NC	1
390			min	-.005	3	-.009	3	-.432	4	9.144e-6	12	NC	1	140.156	4
391		6	max	.005	1	.002	2	0	12	2.509e-3	4	NC	1	NC	1
392			min	-.005	3	-.009	3	-.383	4	8.408e-6	12	NC	1	158.32	4
393		7	max	.004	1	.001	2	0	12	2.51e-3	4	NC	1	NC	1
394			min	-.005	3	-.009	3	-.335	4	7.673e-6	12	NC	1	181.038	4
395		8	max	.004	1	0	2	0	12	2.511e-3	4	NC	1	NC	1
396			min	-.004	3	-.008	3	-.288	4	6.937e-6	12	NC	1	209.981	4
397		9	max	.004	1	0	2	0	12	2.512e-3	4	NC	1	NC	1
398			min	-.004	3	-.008	3	-.245	4	6.201e-6	12	NC	1	247.672	4
399		10	max	.003	1	0	2	0	12	2.513e-3	4	NC	1	NC	1
400			min	-.003	3	-.007	3	-.203	4	5.466e-6	12	NC	1	298.078	4
401		11	max	.003	1	-.001	2	0	12	2.515e-3	4	NC	1	NC	1
402			min	-.003	3	-.007	3	-.165	4	4.73e-6	12	NC	1	367.725	4
403		12	max	.003	1	-.001	2	0	12	2.516e-3	4	NC	1	NC	1
404			min	-.003	3	-.006	3	-.129	4	3.995e-6	12	NC	1	467.988	4
405		13	max	.002	1	-.001	15	0	12	2.517e-3	4	NC	1	NC	1
406			min	-.002	3	-.005	3	-.098	4	3.259e-6	12	NC	1	620.172	4
407		14	max	.002	1	-.001	15	0	12	2.518e-3	4	NC	1	NC	1
408			min	-.002	3	-.005	3	-.07	4	2.524e-6	12	NC	1	868.16	4
409		15	max	.001	1	-.001	15	0	12	2.519e-3	4	NC	1	NC	1
410			min	-.002	3	-.004	4	-.046	4	1.668e-6	10	NC	1	1314.831	4
411		16	max	.001	1	0	15	0	12	2.52e-3	4	NC	1	NC	1
412			min	-.001	3	-.003	4	-.027	4	6.376e-7	10	NC	1	2251.748	4
413		17	max	0	1	0	15	0	12	2.521e-3	4	NC	1	NC	1
414			min	0	3	-.002	4	-.013	4	-2.296e-6	1	NC	1	4805.481	4
415		18	max	0	1	0	15	0	12	2.522e-3	4	NC	1	NC	1
416			min	0	3	-.001	4	-.004	4	-1.465e-5	1	NC	1	NC	1
417		19	max	0	1	0	1	0	1	2.524e-3	4	NC	1	NC	1
418			min	0	1	0	1	0	1	-2.701e-5	1	NC	1	NC	1
419	M11	1	max	0	1	0	1	0	1	8.276e-6	1	NC	1	NC	1
420			min	0	1	0	1	0	1	-4.855e-4	4	NC	1	NC	1
421		2	max	0	3	0	15	.014	4	1.675e-4	4	NC	1	NC	1
422			min	0	2	-.003	4	0	1	-1.691e-5	1	NC	1	NC	1
423		3	max	0	3	-.001	15	.028	4	8.204e-4	4	NC	1	NC	1
424			min	0	2	-.006	4	0	1	-4.21e-5	1	NC	1	NC	1
425		4	max	.001	3	-.002	15	.041	4	1.473e-3	4	NC	1	NC	1
426			min	0	2	-.009	4	0	1	-6.73e-5	1	NC	1	NC	1
427		5	max	.001	3	-.003	15	.053	4	2.126e-3	4	NC	1	NC	1
428			min	-.001	2	-.012	4	0	1	-9.249e-5	1	9035.093	4	9831.19	4
429		6	max	.002	3	-.004	15	.066	4	2.779e-3	4	NC	1	NC	1
430			min	-.001	2	-.014	4	0	1	-1.177e-4	1	7269.882	4	8641.095	4
431		7	max	.002	3	-.004	15	.077	4	3.432e-3	4	NC	5	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
432			min	-.002	2	-.017	4	-.001	1	-1.429e-4	1	6209.561	4	8023.698	4
433		8	max	.002	3	-.005	15	.088	4	4.085e-3	4	NC	5	NC	1
434			min	-.002	2	-.019	4	-.001	1	-1.681e-4	1	5555.074	4	7785.403	4
435		9	max	.003	3	-.005	15	.099	4	4.738e-3	4	NC	5	NC	1
436			min	-.002	2	-.02	4	-.002	1	-1.932e-4	1	5165.876	4	7852.641	4
437		10	max	.003	3	-.005	15	.109	4	5.391e-3	4	NC	5	NC	1
438			min	-.002	2	-.021	4	-.002	1	-2.184e-4	1	4973.535	4	8219.076	4
439		11	max	.003	3	-.005	15	.119	4	6.044e-3	4	NC	5	NC	1
440			min	-.003	2	-.021	4	-.003	1	-2.436e-4	1	4949.489	4	8935.661	4
441		12	max	.004	3	-.005	15	.128	4	6.697e-3	4	NC	5	NC	1
442			min	-.003	2	-.021	4	-.003	1	-2.688e-4	1	5094.062	4	NC	1
443		13	max	.004	3	-.005	15	.137	4	7.35e-3	4	NC	5	NC	1
444			min	-.003	2	-.02	4	-.003	1	-2.94e-4	1	5437.968	4	NC	1
445		14	max	.004	3	-.004	15	.146	4	8.003e-3	4	NC	5	NC	1
446			min	-.003	2	-.018	4	-.004	1	-3.192e-4	1	6058.449	4	NC	1
447		15	max	.005	3	-.004	15	.155	4	8.656e-3	4	NC	2	NC	1
448			min	-.004	2	-.015	4	-.005	1	-3.444e-4	1	7127.572	4	NC	1
449		16	max	.005	3	-.003	15	.164	4	9.309e-3	4	NC	1	NC	1
450			min	-.004	2	-.012	4	-.005	1	-3.696e-4	1	9062.724	4	NC	1
451		17	max	.005	3	-.002	15	.173	4	9.962e-3	4	NC	1	NC	1
452			min	-.004	2	-.009	4	-.006	1	-3.948e-4	1	NC	1	NC	1
453		18	max	.006	3	-.001	15	.183	4	1.061e-2	4	NC	1	NC	1
454			min	-.005	2	-.005	1	-.007	1	-4.2e-4	1	NC	1	NC	1
455		19	max	.006	3	0	10	.193	4	1.127e-2	4	NC	1	NC	1
456			min	-.005	2	-.003	1	-.008	1	-4.452e-4	1	NC	1	NC	1
457	M12	1	max	.003	1	.004	2	.008	1	-3.958e-6	12	NC	1	NC	3
458			min	0	3	-.006	3	-.193	4	-9.266e-4	4	NC	1	128.306	4
459		2	max	.003	1	.004	2	.008	1	-3.958e-6	12	NC	1	NC	3
460			min	0	3	-.006	3	-.178	4	-9.266e-4	4	NC	1	139.704	4
461		3	max	.003	1	.004	2	.007	1	-3.958e-6	12	NC	1	NC	3
462			min	0	3	-.006	3	-.162	4	-9.266e-4	4	NC	1	153.259	4
463		4	max	.002	1	.004	2	.006	1	-3.958e-6	12	NC	1	NC	2
464			min	0	3	-.005	3	-.146	4	-9.266e-4	4	NC	1	169.532	4
465		5	max	.002	1	.003	2	.006	1	-3.958e-6	12	NC	1	NC	2
466			min	0	3	-.005	3	-.131	4	-9.266e-4	4	NC	1	189.286	4
467		6	max	.002	1	.003	2	.005	1	-3.958e-6	12	NC	1	NC	2
468			min	0	3	-.004	3	-.116	4	-9.266e-4	4	NC	1	213.582	4
469		7	max	.002	1	.003	2	.004	1	-3.958e-6	12	NC	1	NC	2
470			min	0	3	-.004	3	-.102	4	-9.266e-4	4	NC	1	243.921	4
471		8	max	.002	1	.003	2	.004	1	-3.958e-6	12	NC	1	NC	2
472			min	0	3	-.004	3	-.088	4	-9.266e-4	4	NC	1	282.498	4
473		9	max	.002	1	.002	2	.003	1	-3.958e-6	12	NC	1	NC	2
474			min	0	3	-.003	3	-.075	4	-9.266e-4	4	NC	1	332.612	4
475		10	max	.001	1	.002	2	.003	1	-3.958e-6	12	NC	1	NC	2
476			min	0	3	-.003	3	-.062	4	-9.266e-4	4	NC	1	399.426	4
477		11	max	.001	1	.002	2	.002	1	-3.958e-6	12	NC	1	NC	1
478			min	0	3	-.003	3	-.05	4	-9.266e-4	4	NC	1	491.383	4
479		12	max	.001	1	.002	2	.002	1	-3.958e-6	12	NC	1	NC	1
480			min	0	3	-.002	3	-.04	4	-9.266e-4	4	NC	1	623.094	4
481		13	max	0	1	.001	2	.001	1	-3.958e-6	12	NC	1	NC	1
482			min	0	3	-.002	3	-.03	4	-9.266e-4	4	NC	1	821.681	4
483		14	max	0	1	.001	2	0	1	-3.958e-6	12	NC	1	NC	1
484			min	0	3	-.002	3	-.022	4	-9.266e-4	4	NC	1	1142.333	4
485		15	max	0	1	0	2	0	1	-3.958e-6	12	NC	1	NC	1
486			min	0	3	-.001	3	-.014	4	-9.266e-4	4	NC	1	1712.303	4
487		16	max	0	1	0	2	0	1	-3.958e-6	12	NC	1	NC	1
488			min	0	3	-.001	3	-.009	4	-9.266e-4	4	NC	1	2883.47	4

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
489		17	max	0	1	0	2	0	1	-3.958e-6	12	NC	1	NC	1
490			min	0	3	0	3	-.004	4	-9.266e-4	4	NC	1	5961.074	4
491		18	max	0	1	0	2	0	1	-3.958e-6	12	NC	1	NC	1
492			min	0	3	0	3	-.001	4	-9.266e-4	4	NC	1	NC	1
493		19	max	0	1	0	1	0	1	-3.958e-6	12	NC	1	NC	1
494			min	0	1	0	1	0	1	-9.266e-4	4	NC	1	NC	1
495	M1	1	max	.008	3	.202	1	.675	4	1.062e-2	1	NC	1	NC	1
496			min	-.004	2	-.046	3	0	12	-1.755e-2	3	NC	1	NC	1
497		2	max	.008	3	.101	1	.656	4	8.799e-3	4	NC	5	NC	1
498			min	-.004	2	-.023	3	-.006	1	-8.71e-3	3	1323.041	1	NC	1
499		3	max	.008	3	.011	3	.635	4	1.545e-2	4	NC	5	NC	1
500			min	-.004	2	-.01	2	-.009	1	-1.853e-4	1	636.84	1	6425.339	5
501		4	max	.008	3	.065	3	.614	4	1.342e-2	4	NC	15	NC	1
502			min	-.004	2	-.133	1	-.008	1	-3.922e-3	3	401.782	1	4543.691	5
503		5	max	.008	3	.132	3	.592	4	1.139e-2	4	9835.497	15	NC	1
504			min	-.004	2	-.262	1	-.006	1	-7.751e-3	3	289.667	1	3583.39	5
505		6	max	.007	3	.205	3	.57	4	1.387e-2	1	7785.506	15	NC	1
506			min	-.004	2	-.388	1	-.003	1	-1.158e-2	3	227.921	1	3000.996	5
507		7	max	.007	3	.274	3	.548	4	1.855e-2	1	6573.898	15	NC	1
508			min	-.004	2	-.5	1	0	3	-1.541e-2	3	191.494	1	2602.28	4
509		8	max	.007	3	.332	3	.524	4	2.324e-2	1	5856.381	15	NC	1
510			min	-.004	2	-.589	1	0	12	-1.924e-2	3	169.96	1	2310.221	4
511		9	max	.007	3	.369	3	.5	4	2.553e-2	1	5480.754	15	NC	1
512			min	-.004	2	-.646	1	0	1	-1.965e-2	3	158.736	1	2122.084	4
513		10	max	.007	3	.384	3	.472	4	2.622e-2	1	5365.908	15	NC	1
514			min	-.004	2	-.664	1	0	10	-1.776e-2	3	155.373	1	2063.86	4
515		11	max	.007	3	.375	3	.44	4	2.691e-2	1	5480.55	15	NC	1
516			min	-.004	2	-.645	1	0	12	-1.588e-2	3	158.967	1	2104.784	4
517		12	max	.006	3	.343	3	.406	4	2.534e-2	1	5855.89	15	NC	1
518			min	-.004	2	-.588	1	0	1	-1.366e-2	3	170.656	1	2251.718	4
519		13	max	.006	3	.292	3	.367	4	2.038e-2	1	6572.933	15	NC	1
520			min	-.003	2	-.497	1	0	1	-1.093e-2	3	193.169	1	2674.441	4
521		14	max	.006	3	.227	3	.324	4	1.542e-2	1	7783.728	15	NC	1
522			min	-.003	2	-.383	1	0	12	-8.199e-3	3	231.46	1	3620.796	4
523		15	max	.006	3	.154	3	.28	4	1.047e-2	1	9832.235	15	NC	1
524			min	-.003	2	-.255	1	0	12	-5.47e-3	3	296.858	1	5897.393	4
525		16	max	.006	3	.078	3	.237	4	9.476e-3	4	NC	15	NC	1
526			min	-.003	2	-.126	1	0	12	-2.74e-3	3	416.685	1	NC	1
527		17	max	.006	3	.004	3	.198	4	1.061e-2	4	NC	5	NC	1
528			min	-.003	2	-.006	2	0	12	-1.103e-5	3	669.861	1	NC	1
529		18	max	.006	3	.099	1	.166	4	6.999e-3	2	NC	5	NC	1
530			min	-.003	2	-.063	3	0	12	-2.389e-3	3	1406.082	1	NC	1
531		19	max	.006	3	.194	1	.138	4	1.394e-2	2	NC	1	NC	1
532			min	-.003	2	-.126	3	0	1	-4.858e-3	3	NC	1	NC	1
533	M5	1	max	.024	3	.37	1	.675	4	0	1	NC	1	NC	1
534			min	-.017	2	-.025	3	0	1	-8.148e-6	4	NC	1	NC	1
535		2	max	.024	3	.186	1	.66	4	7.901e-3	4	NC	5	NC	1
536			min	-.017	2	-.014	3	0	1	0	1	730.741	1	9020.264	4
537		3	max	.024	3	.033	3	.641	4	1.562e-2	4	NC	15	NC	1
538			min	-.017	2	-.029	2	0	1	0	1	338.486	1	5234.473	4
539		4	max	.024	3	.147	3	.62	4	1.273e-2	4	7697.13	15	NC	1
540			min	-.016	2	-.293	1	0	1	0	1	203.266	1	3969.263	4
541		5	max	.023	3	.309	3	.596	4	9.835e-3	4	5353.754	15	NC	1
542			min	-.016	2	-.587	1	0	1	0	1	140.812	1	3333.606	4
543		6	max	.023	3	.492	3	.572	4	6.942e-3	4	4103.225	15	NC	1
544			min	-.016	2	-.882	1	0	1	0	1	107.568	1	2931.806	4
545		7	max	.022	3	.673	3	.547	4	4.05e-3	4	3384.321	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
546			min	-.015	2	-1.152	1	0	1	0	1	88.492	1	2622.042	4
547		8	max	.022	3	.825	3	.524	4	1.157e-3	4	2967.873	15	NC	1
548			min	-.015	2	-1.37	1	0	1	0	1	77.457	1	2340.922	4
549		9	max	.021	3	.923	3	.5	4	1.094e-7	14	2754.637	15	NC	1
550			min	-.015	2	-1.507	1	0	1	-4.261e-6	5	71.816	1	2117.614	4
551		10	max	.021	3	.959	3	.471	4	2.318e-7	14	2690.38	15	NC	1
552			min	-.014	2	-1.553	1	0	1	-4.04e-6	5	70.142	1	2082.876	4
553		11	max	.02	3	.936	3	.44	4	3.543e-7	14	2754.749	15	NC	1
554			min	-.014	2	-1.506	1	0	1	-3.819e-6	5	71.935	1	2134.9	4
555		12	max	.02	3	.854	3	.408	4	7.564e-4	4	2968.138	15	NC	1
556			min	-.014	2	-1.366	1	0	1	0	1	77.852	1	2210.379	4
557		13	max	.019	3	.722	3	.369	4	2.647e-3	4	3384.854	15	NC	1
558			min	-.014	2	-1.143	1	0	1	0	1	89.532	1	2604.618	4
559		14	max	.019	3	.555	3	.324	4	4.538e-3	4	4104.257	15	NC	1
560			min	-.013	2	-.866	1	0	1	0	1	109.944	1	3671.436	4
561		15	max	.018	3	.37	3	.277	4	6.428e-3	4	5355.782	15	NC	1
562			min	-.013	2	-.566	1	0	1	0	1	146.059	1	6875.267	5
563		16	max	.018	3	.184	3	.232	4	8.319e-3	4	7701.373	15	NC	1
564			min	-.013	2	-.272	1	0	1	0	1	215.285	1	NC	1
565		17	max	.017	3	.011	3	.192	4	1.021e-2	4	NC	15	NC	1
566			min	-.013	2	-.016	2	0	1	0	1	368.457	1	NC	1
567		18	max	.017	3	.183	1	.161	4	5.165e-3	4	NC	5	NC	1
568			min	-.013	2	-.135	3	0	1	0	1	812.999	1	NC	1
569		19	max	.017	3	.347	1	.138	4	0	1	NC	1	NC	1
570			min	-.013	2	-.264	3	0	1	-3.919e-6	4	NC	1	NC	1
571	M9	1	max	.008	3	.202	1	.675	4	1.755e-2	3	NC	1	NC	1
572			min	-.004	2	-.046	3	0	1	-1.062e-2	1	NC	1	NC	1
573		2	max	.008	3	.101	1	.659	4	8.71e-3	3	NC	5	NC	1
574			min	-.004	2	-.023	3	0	12	-5.129e-3	1	1323.041	1	9833.923	4
575		3	max	.008	3	.011	3	.639	4	1.556e-2	4	NC	5	NC	1
576			min	-.004	2	-.01	2	0	12	-1.497e-5	10	636.84	1	5582.376	4
577		4	max	.008	3	.065	3	.618	4	1.223e-2	5	NC	15	NC	1
578			min	-.004	2	-.133	1	0	12	-4.5e-3	1	401.782	1	4131.516	4
579		5	max	.008	3	.132	3	.595	4	9.233e-3	5	9798.366	15	NC	1
580			min	-.004	2	-.262	1	0	12	-9.185e-3	1	289.667	1	3392.908	4
581		6	max	.007	3	.205	3	.572	4	1.158e-2	3	7757.228	15	NC	1
582			min	-.004	2	-.388	1	0	12	-1.387e-2	1	227.921	1	2932.839	4
583		7	max	.007	3	.274	3	.548	4	1.541e-2	3	6550.709	15	NC	1
584			min	-.004	2	-.5	1	0	1	-1.855e-2	1	191.494	1	2599.488	4
585		8	max	.007	3	.332	3	.524	4	1.924e-2	3	5836.137	15	NC	1
586			min	-.004	2	-.589	1	0	1	-2.324e-2	1	169.96	1	2325.226	5
587		9	max	.007	3	.369	3	.5	4	1.965e-2	3	5462.013	15	NC	1
588			min	-.004	2	-.646	1	0	12	-2.553e-2	1	158.736	1	2116.237	4
589		10	max	.007	3	.384	3	.472	4	1.776e-2	3	5347.595	15	NC	1
590			min	-.004	2	-.664	1	0	1	-2.622e-2	1	155.373	1	2064.707	4
591		11	max	.007	3	.375	3	.44	4	1.588e-2	3	5461.778	15	NC	1
592			min	-.004	2	-.645	1	0	1	-2.691e-2	1	158.967	1	2111.819	4
593		12	max	.006	3	.343	3	.407	4	1.366e-2	3	5835.691	15	NC	1
594			min	-.004	2	-.588	1	0	12	-2.534e-2	1	170.656	1	2237.251	4
595		13	max	.006	3	.292	3	.367	4	1.093e-2	3	6550.024	15	NC	1
596			min	-.003	2	-.497	1	0	10	-2.038e-2	1	193.169	1	2672.874	4
597		14	max	.006	3	.227	3	.323	4	8.199e-3	3	7756.205	15	NC	1
598			min	-.003	2	-.383	1	-.002	1	-1.542e-2	1	231.46	1	3698.066	5
599		15	max	.006	3	.154	3	.277	4	6.113e-3	5	9796.792	15	NC	1
600			min	-.003	2	-.255	1	-.005	1	-1.047e-2	1	296.858	1	6355.426	5
601		16	max	.006	3	.078	3	.233	4	8.189e-3	5	NC	15	NC	1
602			min	-.003	2	-.126	1	-.008	1	-5.514e-3	1	416.685	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
603		17	max	.006	3	.004	3	.194	4	1.033e-2	4	NC	5	NC	1
604			min	-.003	2	-.006	2	-.008	1	-5.588e-4	1	669.861	1	NC	1
605		18	max	.006	3	.099	1	.162	4	4.99e-3	5	NC	5	NC	1
606			min	-.003	2	-.063	3	-.006	1	-6.999e-3	2	1406.082	1	NC	1
607		19	max	.006	3	.194	1	.138	4	4.858e-3	3	NC	1	NC	1
608			min	-.003	2	-.126	3	0	12	-1.394e-2	2	NC	1	NC	1

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 4.00 x 0.28

<Figure 1>



<Figure 2>

Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	1020.0	27.0	565.0	565.6
Sum	1020.0	27.0	565.0	565.6

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 1020
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	5.247	10215

$\phi N_{cb} = \phi\,(A_{Nc} / A_{Nco})\,\Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-4)

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cb} (lb)
220.36	247.75	0.967	1.00	1.000	10215	0.65	5710

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_a = \phi\,(A_{Na} / A_{Na0})\,\Psi_{ed,Na} \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16a)

A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	ϕ	ϕN_a (lb)
109.66	109.66	1.000	1.000	9755	0.55	5365

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in y-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cby} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cby} (lb)
192.89	220.50	0.925	1.000	1.000	6947	0.70	3934

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cbx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbx} (lb)
165.27	278.72	0.878	1.000	1.000	8282	0.70	3018

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
192.89	220.50	1.000	1.000	1.000	6947	0.70	8508

Shear parallel to edge in y-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cby} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cby} (lb)
165.27	278.72	1.000	1.000	1.000	8282	0.70	6875

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cp} = \phi\,\min|k_{cp}N_a\,;\,k_{cp}N_{cb}| = \phi\,\min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\,\Psi_{p,Na}N_{a0}\,;\,k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ed,N}\,\Psi_{c,N}\,\Psi_{cp,N}N_b|$ (Eq. D-30a)

k_{cp}	A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	109.66	109.66	1.000	1.000	9755	9755

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ	ϕV_{cp} (lb)
220.36	247.75	0.967	1.000	1.000	10215	8785	0.70	12298

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, øN_n (lb)	Ratio	Status
Steel	1020	6071	0.17	Pass
Concrete breakout	1020	5710	0.18	Pass
Adhesive	**1020**	**5365**	**0.19**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, øV_n (lb)	Ratio	Status
Steel	**566**	**3156**	**0.18**	**Pass (Governs)**
T Concrete breakout y+	565	3934	0.14	Pass
T Concrete breakout x+	27	3018	0.01	Pass
|| Concrete breakout y+	27	8508	0.00	Pass
|| Concrete breakout x+	565	6875	0.08	Pass
Concrete breakout, combined	-	-	0.14	Pass
Pryout	566	12298	0.05	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status
Sec. D.7.1	0.19	0.00	19.0 %	1.0	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 7.00 x 0.28

<Figure 1>



<Figure 2>



Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	2732.0	1650.0	0.0	1650.0
2	2732.0	1650.0	0.0	1650.0
Sum	5464.0	3300.0	0.0	3300.0

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 5464
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	6.000	12492

$\phi N_{cbg} = \phi (A_{Nc} / A_{Nco}) \Psi_{ec,N} \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-5)

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cbg} (lb)
408.24	324.00	1.000	1.000	1.00	1.000	12492	0.65	10231

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_{ag} = \phi (A_{Na} / A_{Na0}) \Psi_{ed,Na} \Psi_{g,Na} \Psi_{ec,Na} \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16b)

A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0}(lb)	ϕ	ϕN_{ag} (lb)
158.66	109.66	1.000	1.043	1.000	1.000	9755	0.55	8093

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	12.00	15593

$\phi V_{cbgx} = \phi\ (A_{Vc} / A_{Vco})\ \Psi_{ec,V}\ \Psi_{ed,V}\ \Psi_{c,V}\ \Psi_{h,V} V_{bx}$ (Sec. D.4.1 & Eq. D-22)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ec,V}$	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbgx} (lb)
576.00	648.00	1.000	0.928	1.000	1.000	15593	0.70	9001

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	13.66	18939

$\phi V_{cbx} = \phi\ (2)(A_{Vc} / A_{Vco})\ \Psi_{ed,V}\ \Psi_{c,V}\ \Psi_{h,V} V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
737.64	839.68	1.000	1.000	1.000	18939	0.70	23292

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cpg} = \phi \min|k_{cp}N_{ag}\ ;\ k_{cp}N_{cbg}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\ \Psi_{ed,Na}\ \Psi_{g,Na}\ \Psi_{ec,Na}\ \Psi_{p,Na}N_{a0}\ ;\ k_{cp}(A_{Nc} / A_{Nco})\ \Psi_{ec,N}\ \Psi_{ed,N}\ \Psi_{c,N}\ \Psi_{cp,N}N_b|$ (Eq. D-30b)

k_{cp}	A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	158.66	109.66	1.000	1.043	1.000	1.000	9755	14715

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ
408.24	324.00	1.000	1.000	1.000	1.000	12492	15740	0.70

ϕV_{cpg} (lb)
20601

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, $øN_n$ (lb)	Ratio	Status
Steel	2732	6071	0.45	Pass
Concrete breakout	5464	10231	0.53	Pass
Adhesive	**5464**	**8093**	**0.68**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, $øV_n$ (lb)	Ratio	Status
Steel	**1650**	**3156**	**0.52**	**Pass (Governs)**
T Concrete breakout x+	3300	9001	0.37	Pass

|| Concrete breakout y-	1650	23292	0.07	Pass
Pryout	3300	20601	0.16	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status
Sec. D.7.3	0.68	0.52	119.8 %	1.2	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.