

Schletter, Inc.		25ÁTilt w/o Seismic Design
HCV	Standard PVMax Racking System	
	Representative Calculations - ASCE 7-10	

1. INTRODUCTION

1.1 Project Description

The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. PVMax ground mount system.

1.2 Construction

Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to aluminum struts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

	Maximum		Minimum	
Height =	1700	mm	1550	mm
Width =	1050	mm	970	mm
Dead Load =	3.00	psf	1.75	psf

Modules Per Row =	2
Module Tilt =	25°
Maximum Height Above Grade =	3 ft



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

1.3 Technical Codes

- ASCE 7-10 - Chapter 26-31, Wind Loads
- ASCE 7-10 - Chapter 7, Snow Loads
- ASCE 7-10 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2012, 2015
- Aluminum Design Manual, Eighth Edition, 2005

2. LOAD ACTIONS

2.1 Permanent Loads

g_{MAX} =	3.00	psf	*Self-weight of the PV modules.*
g_{MIN} =	1.75	psf	

2.2 Snow Loads

Ground Snow Load, P_g =	30.00	psf	
Sloped Roof Snow Load, P_s =	18.56	psf	*(ASCE 7-10, Eq. 7.4-1)*
I_s =	1.00		
C_s =	0.82		
C_e =	0.90		
C_t =	1.20		

2.3 Wind Loads

Design Wind Speed, V =	140	mph	Exposure Category = C
Height <	15	ft	Importance Category = II
Peak Velocity Pressure, q_z =	30.77	psf	*Including the gust factor, G=0.85. (ASCE 7-10, Eq. 27.3-1)*

Pressure Coefficients

$Cf+_{TOP}$ =	1.100	*(Pressure)*	*Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0611-1e. Negative forces are applied away from the surface.*
$Cf+_{BOTTOM}$ =	1.700		
$Cf-_{TOP, OUTER PURLIN}$ =	-2.500		
$Cf-_{TOP, INNER PURLIN}$ =	-1.900	*(Suction)*	
$Cf-_{BOTTOM}$ =	-1.000		

2.4 Seismic Loads - N/A

S_S =	0.00	R =	1.25	*ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.*
S_{DS} =	0.00	C_S =	0	
S_1 =	0.00	ρ =	1.3	
S_{D1} =	0.00	Ω =	1.25	
T_a =	0.00	C_d =	1.25	

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.5W
1.2D + 1.0W + 0.5S
0.9D + 1.0W [M]
1.54D + 1.3E + 0.2S [R]
0.56D + 1.3E [R]
1.54D + 1.25E + 0.2S [O]
0.56D + 1.25E [O]

(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S
1.0D + 0.6W
1.0D + 0.75L + 0.45W + 0.75S
0.6D + 0.6W [M]
1.238D + 0.875E [O]
1.1785D + 0.65625E + 0.75S [O]
0.362D + 0.875E [O]

(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)

[M] *Uses the minimum allowable module dead load.*
[R] *Include redundancy factor of 1.3.*
[O] *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location
M13	Top
M14	Mid-Top
M15	Mid-Bottom
M16	Bottom

Girders	Location
M1	Outer
M5	Inner
M9	Outer

Front Struts	Location
M4	Outer
M8	Inner
M12	Outer

Diagonal Struts	Location
M3	Outer
M7	Inner
M11	Outer

Rear Struts	Location
M2	Outer
M6	Inner
M10	Outer

Front Reactions	Location
N7	Outer
N15	Inner
N23	Outer

Rear Reactions	Location
N8	Outer
N16	Inner
N24	Outer

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type =	**S1.5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	120	in
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	25.07	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	23.08	ksi
S_y =	1.33	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	2.16	in^4
I_x =	1.07	in^4
A =	1.25	in^2
g =	1.50	lbs/ft
M_y =	1.944	k-ft
M_z =	0.330	k-ft
$M_{y\ allowable}$ =	2.779	k-ft
$M_{z\ allowable}$ =	1.154	k-ft
Utilization =	99%	



DETAIL VIEW

4.2 Girder Design

Loads from purlins are transferred using an inclined girder, which is connected to a set of aluminum struts. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type =	**BF0**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	88.90	in
$\Phi F_{ty\ AXIAL}$ =	31.09	ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	29.35	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	33.25	ksi
S_y =	1.42	in^3
S_x =	1.41	in^3
E =	10100	ksi
I_y =	2.39	in^4
I_x =	2.22	in^4
A =	1.88	in^2
g =	2.26	lbs/ft
M_y =	-3.288	k-ft
M_z =	0.000	k-ft
P_n =	-0.826	k
$M_{y\ allowable}$ =	3.464	k-ft
$M_{z\ allowable}$ =	3.907	k-ft
$P_{n\ allowable}$ =	58.535	k
Utilization =	96%	



4.3 Front Strut Design

The front aluminum strut connects a portion of the girder to the foundation. Vertical girder forces are then transferred down through the strut into the foundation. The strut is attached with single M12 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	24.80	in
$\Phi F_{ty\ AXIAL}$ =	28.03	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.000	k-ft
M_z =	0.000	k-ft
P_n =	3.178	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	27.532	k
Utilization =	12%	



4.4 Diagonal Strut Design

A diagonal aluminum strut braces the support structure. It connects at a front portion of the girder and transfers horizontal forces to the rear foundation connection. The strut is attached with single M12 bolts at each end. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	86.60	in
$\Phi F_{ty\ AXIAL}$ =	7.50	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.011	k-ft
M_z =	0.000	k-ft
P_n =	2.358	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	7.371	k
Utilization =	33%	



4.5 Rear Strut Design

An aluminum strut connects the rear portion of the girder to the rear foundation connection. Both vertical and horizontal forces are transferred from the girder. The strut is attached with single M12 bolts at each end. See Appendix A.5 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	63.42	in
$\Phi F_{ty\ AXIAL}$ =	12.77	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	-0.011	k-ft
M_z =	0.000	k-ft
P_n =	3.495	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	12.545	k
Utilization =	29%	



5. FOUNDATION DESIGN CALCULATIONS

5.1 Helical Pile Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete foundation design.

Maximum	Front	Rear	
Tensile Load =	748.35	6889.55	k
Compressive Load =	4131.51	5367.43	k
Lateral Load =	13.83	3702.95	k
Moment (Weak Axis) =	0.03	0.01	k

5.2 Design of Ballast Foundations

Ballast foundations are used to secure the racking structure in place. The foundations are checked for potential overturning and sliding. Bearing pressures applied by the racking and ballast foundations are checked against the allowable bearing pressures provided by the IBC table 1806.2 (2012, 2015).



Concrete Properties

Weight of Concrete =	145 pcf
Compressive Strength =	2500 psi
Yield Strength =	60000 psi

Overturning Check

M_O =	167178.6 in-lbs
Resisting Force Required =	2533.01 lbs
S.F. =	1.67
Weight Required =	4221.68 lbs
Minimum Width =	35 in in
Weight Provided =	6978.13 lbs

Sliding

Force =	854.11 lbs
Friction =	0.4
Weight Required =	2135.26 lbs
Resisting Weight =	6978.13 lbs
Additional Weight Required =	0 lbs

Cohesion

Sliding Force =	854.11 lbs
Cohesion =	130 psf
Area =	32.08 ft^2
Resisting =	3489.06 lbs
Additional Weight Required =	0 lbs

Shear Key

Additional Force =	0 lbs
Lateral Bearing Pressure =	200 psf/ft
Required Depth =	0.00 ft
f'_c =	2500 psi
Length =	8 in

Footing Reinforcement

Use fiber reinforcing with (2) #5 rebar.

A minimum 132in long x 35in wide x 18in tall ballast foundation is required to resist overturning.

Use a 132in long x 35in wide x 18in tall ballast foundation to resist sliding. Friction is OK.

Use a 132in long x 35in wide x 18in tall ballast foundation. Cohesion is OK.

Shear key is not required.

Bearing Pressure

	Ballast Width			
	35 in	36 in	37 in	38 in
P_{ftg} = (145 pcf)(11 ft)(1.5 ft)(2.92 ft) =	6978 lbs	7178 lbs	7377 lbs	7576 lbs

ASD LC	1.0D + 1.0S				1.0D + 0.6W				1.0D + 0.75L + 0.45W + 0.75S				0.6D + 0.6W			
Width	35 in	36 in	37 in	38 in	35 in	36 in	37 in	38 in	35 in	36 in	37 in	38 in	35 in	36 in	37 in	38 in
F_A	1386 lbs	1386 lbs	1386 lbs	1386 lbs	1536 lbs	1536 lbs	1536 lbs	1536 lbs	2063 lbs	2063 lbs	2063 lbs	2063 lbs	-335 lbs	-335 lbs	-335 lbs	-335 lbs
F_B	1376 lbs	1376 lbs	1376 lbs	1376 lbs	2212 lbs	2212 lbs	2212 lbs	2212 lbs	2563 lbs	2563 lbs	2563 lbs	2563 lbs	-3171 lbs	-3171 lbs	-3171 lbs	-3171 lbs
F_V	187 lbs	187 lbs	187 lbs	187 lbs	1537 lbs	1537 lbs	1537 lbs	1537 lbs	1277 lbs	1277 lbs	1277 lbs	1277 lbs	-1708 lbs	-1708 lbs	-1708 lbs	-1708 lbs
P_{total}	9740 lbs	9940 lbs	10139 lbs	10338 lbs	10726 lbs	10926 lbs	11125 lbs	11324 lbs	11604 lbs	11804 lbs	12003 lbs	12202 lbs	681 lbs	800 lbs	920 lbs	1040 lbs
M	3679 lbs-ft	3679 lbs-ft	3679 lbs-ft	3679 lbs-ft	4417 lbs-ft	4417 lbs-ft	4417 lbs-ft	4417 lbs-ft	5729 lbs-ft	5729 lbs-ft	5729 lbs-ft	5729 lbs-ft	3455 lbs-ft	3455 lbs-ft	3455 lbs-ft	3455 lbs-ft
e	0.38 ft	0.37 ft	0.36 ft	0.36 ft	0.41 ft	0.40 ft	0.40 ft	0.39 ft	0.49 ft	0.49 ft	0.48 ft	0.47 ft	5.07 ft	4.32 ft	3.76 ft	3.32 ft
L/6	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft
f_{min}	241.0 psf	240.4 psf	239.8 psf	239.2 psf	259.2 psf	258.1 psf	257.0 psf	255.9 psf	264.3 psf	263.0 psf	261.8 psf	260.6 psf	0.0 psf	0.0 psf	0.0 psf	0.0 psf
f_{max}	366.1 psf	362.0 psf	358.1 psf	354.4 psf	409.4 psf	404.1 psf	399.0 psf	394.3 psf	459.1 psf	452.4 psf	446.0 psf	440.0 psf	366.1 psf	150.3 psf	114.0 psf	100.5 psf

Maximum Bearing Pressure = 459 psf
Allowable Bearing Pressure = 1500 psf

Use a 132in long x 35in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Weak Side Design

Overturning Check

M_O =	1144.2 ft-lbs
Resisting Force Required =	784.60 lbs
S.F. =	1.67
Weight Required =	1307.66 lbs
Minimum Width =	35 in in
Weight Provided =	6978.13 lbs

A minimum 132in long x 35in wide x 18in tall ballast foundation is required to resist overturning.



Bearing Pressure

ASD LC	1.238D + 0.875E			1.1785D + 0.65625E + 0.75S			0.362D + 0.875E		
Width	35 in			35 in			35 in		
Support	Outer	Inner	Outer	Outer	Inner	Outer	Outer	Inner	Outer
F_Y	245 lbs	635 lbs	245 lbs	797 lbs	2292 lbs	797 lbs	72 lbs	186 lbs	72 lbs
F_V	1 lbs	0 lbs	1 lbs	5 lbs	0 lbs	5 lbs	0 lbs	0 lbs	0 lbs
P_{total}	8884 lbs	6978 lbs	8884 lbs	9021 lbs	6978 lbs	9021 lbs	2598 lbs	6978 lbs	2598 lbs
M	5 lbs-ft	0 lbs-ft	5 lbs-ft	18 lbs-ft	0 lbs-ft	18 lbs-ft	1 lbs-ft	0 lbs-ft	1 lbs-ft
e	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft
L/6	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft	0.49 ft
f_{min}	276.6 psf	217.5 psf	276.6 psf	280.0 psf	217.5 psf	280.0 psf	80.9 psf	217.5 psf	80.9 psf
f_{max}	277.2 psf	217.5 psf	277.2 psf	282.3 psf	217.5 psf	282.3 psf	81.0 psf	217.5 psf	81.0 psf

Maximum Bearing Pressure = 282 psf
Allowable Bearing Pressure = 1500 psf

Use a 132in long x 35in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Foundation Requirements: 132in long x 35in wide x 18in tall ballast foundation and fiber reinforcing with (2) #5 rebar.

5.3 Foundation Anchors

Threaded rods are anchored to the the ballast foundations using the Simpson AT-XP epoxy solution. LRFD load results are compared to the allowable strengths of the epoxy solution. Please see the supplementary calculations provided by the Simpson Anchor Designer software.

6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of 80mm mounting clamps. The reliability of calculations is uncertain due to limited standards, therefore the strength of the clamp fasteners has been evaluated by load testing.

Fastening of Modules to Purlins

Maximum Uplifting Force	=	0.724 k
Allowable Uplift	=	1.214 k
Utilization	=	60%



Fastening of Purlins to Girders

Maximum Uplifting Force	=	2.582 k
Allowable Uplift	=	4.357 k
Utilization	=	59%



6.2 Strut Connections

The aluminum struts connect the aluminum girder ends to custom brackets with mounting holes. Single M12 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Front Strut

Maximum Axial Load	=	3.178 k
M12 Bolt Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	43%

Rear Strut

Maximum Axial Load	=	4.660 k
M12 Bolt Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	63%

Diagonal Strut

Maximum Axial Load	=	2.462 k
M12 Bolt Shear Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	33%

Bolt and bearing capacities are accounting for double shear. (ASCE 8-02, Eq. 5.3.4-1)



Struts under compression are shown to demonstrate the load transfer from the girder. Single M12 bolts are located at each end of the strut and are subjected to double shear.

7. SEISMIC DESIGN

7.1 Seismic Drift - N/A

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx}	=	46.89 in
Allowable Story Drift for All Other Structures, Δ	= {	$0.020h_{sx}$
		0.938 in
Max Drift, Δ_{MAX}	=	0.05 in

N/A

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **S1.5**

Strong Axis:

3.4.14

L_b = 120 in

J = 0.432

331.976

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 27.4 ksi

3.4.16

b/t = 32.195

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 25.1 ksi

3.4.16.1 Not Used

Rb/t =

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 37.0588

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 40.985

Cc = 41.015

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.2

φF_L= φb[Bbr-mDbr*h/t]

φF_L= 43.2 ksi

$\varphi F_L St$= 25.1 ksi

Ix = 897074 mm^4

2.155 in^4

y = 41.015 mm

Sx = 1.335 in^3

$M_{max}St$ = 2.788 k-ft

Weak Axis:

3.4.14

L_b = 120

J = 0.432

211.117

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 28.6

3.4.16

b/t = 37.0588

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 23.1 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 32.195

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 45.5

Cc = 45.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 23.1 ksi

Iy = 446476 mm^4

1.073 in^4

x = 45.5 mm

Sy = 0.599 in^3

$M_{max}Wk$ = 1.152 k-ft

Compression

3.4.9

b/t = 32.195
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 25.1 ksi

b/t = 37.0588
S1 = 12.21
S2 = 32.70
φF_L = (φck2*√(BpE))/(1.6b/t)
φF_L = 21.9 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 21.94 ksi
A = 1215.13 mm^2
1.88 in^2
P_{max} = 41.32 kips

A.2 Design of Aluminum Girders - Aluminum Design Manual, 2005 Edition

Girder = **BF0**

Strong Axis:

3.4.14

L_b = 88.9 in
J = 1.08
152.913

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.4 ksi

3.4.16

b/t = 16.2

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 31.6 ksi

Weak Axis:

3.4.14

L_b = 88.9
J = 1.08
161.829

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.2

3.4.16

b/t = 7.4

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φyFcy
φF_L = 33.3 ksi

3.4.16.1 Used

Rb/t = 18.1

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= φb[Bt-Dt*√(Rb/t)]

φF_L= 31.1 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 7.4

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 35.2

m = 0.68

C_0 = 41.067

Cc = 43.717

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 73.8

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 29.4 ksi

Ix = 984962 mm^4

2.366 in^4

y = 43.717 mm

Sx = 1.375 in^3

$M_{max}St$ = 3.363 k-ft

3.4.18

h/t = 16.2

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 40

Cc = 40

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 33.3 ksi

Iy = 923544 mm^4

2.219 in^4

x = 40 mm

Sy = 1.409 in^3

$M_{max}Wk$ = 3.904 k-ft

Compression

3.4.9

b/t = 16.2

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 31.6 ksi

b/t = 7.4

S1 = 12.21

S2 = 32.70

φF_L= φyFcy

φF_L= 33.3 ksi

3.4.10

Rb/t = 18.1

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L= φc[Bt-Dt*√(Rb/t)]

φF_L= 31.09 ksi

φF_L= 31.09 ksi

A = 1215.13 mm^2

1.88 in^2

P_{max} = 58.55 kips

A.3 Design of Aluminum Struts (Front) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 24.8 in

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

Weak Axis:

3.4.14

L_b = 24.8

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 0.57371

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

S1* = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

S2* = 1.23671

φcc = 0.87952

φF_L = φcc(Bc-Dc*λ)

φF_L = 28.0279 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 28.03 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 28.85 kips

A.4 Design of Aluminum Struts (Diagonal) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 86.60 in

J = 0.942

135.148

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L = 29.6 ksi

Weak Axis:

3.4.14

L_b = 86.6

J = 0.942

135.148

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L = 29.6

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17 \frac{\theta_y}{\theta_b} Fcy}{1.6Dt} \right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 2.00335

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi} \sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.86047

φF_L= (φccFcy)/(λ²)

φF_L= 7.50396 ksi

3.4.9

b/t = 24.5
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

b/t = 24.5
S1 = 12.21
S2 = 32.70
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 7.50 ksi
A = 663.99 mm^2
1.03 in^2
P_{max} = 7.72 kips

A.5 Design of Aluminum Struts (Rear) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 63.42 in
J = 0.942
98.9729

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.2 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

Weak Axis:

3.4.14

L_b = 63.42
J = 0.942
98.9729

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.2

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 1.46712

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.7854

φF_L= (φccFcy)/(λ²)

φF_L= 12.7711 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 12.77 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 13.14 kips

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				4		
2	Dead Load, Min	DL		-1				4		
3	Snow Load	SL						4		
4	Wind Load - Pressure	WL						4		
5	Wind Load - Suction	WL						4		
6	Seismic - Lateral	EL								

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-8.366	-8.366	0	0
2	M14	Y	-8.366	-8.366	0	0
3	M15	Y	-8.366	-8.366	0	0
4	M16	Y	-8.366	-8.366	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-4.45	-4.45	0	0
2	M14	Y	-4.45	-4.45	0	0
3	M15	Y	-4.45	-4.45	0	0
4	M16	Y	-4.45	-4.45	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-46.9	-46.9	0	0
2	M14	Y	-46.9	-46.9	0	0
3	M15	Y	-46.9	-46.9	0	0
4	M16	Y	-46.9	-46.9	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	-94.402	-94.402	0	0
2	M14	y	-94.402	-94.402	0	0
3	M15	y	-145.893	-145.893	0	0
4	M16	y	-145.893	-145.893	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	214.549	214.549	0	0
2	M14	y	163.057	163.057	0	0
3	M15	y	85.82	85.82	0	0
4	M16	y	85.82	85.82	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.5W	Yes	Y		1	1.2	3	1.6	4	.5														
2	LRFD 1.2D + 1.0W + 0.5S	Yes	Y		1	1.2	3	.5	4	1														
3	LRFD 0.9D + 1.0W	Yes	Y		2	.9					5	1												
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3												
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3												
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25												
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25												

Load Combinations (Continued)

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
8																										
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																		
10	ASD 1.0D + 0.6W	Yes	Y		1	1			4	.6																
11	ASD 1.0D + 0.75L + 0.45W + 0....	Yes	Y		1	1	3	.75	4	.45																
12	ASD 0.6D + 0.6W	Yes	Y		2	.6					5	.6														
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875														
14	LATERAL - ASD 1.1785D + 0.65...	Yes	Y		1	1.1...	3	.75			6	.656														
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875														

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N8	max	719.742	2	1266.148	2	.73	1	.004	1	0	1	0	1
2		min	-896.707	3	-1621.914	3	.035	15	0	15	0	1	0	1
3	N7	max	.037	9	1166.645	1	-.455	15	0	15	0	1	0	1
4		min	-.204	2	-150.177	3	-10.641	1	-.022	1	0	1	0	1
5	N15	max	.028	9	3178.083	1	0	1	0	1	0	1	0	1
6		min	-2.336	2	-575.652	3	0	11	0	11	0	1	0	1
7	N16	max	2625.381	2	4128.793	2	0	10	0	10	0	1	0	1
8		min	-2848.421	3	-5299.651	3	0	1	0	3	0	1	0	1
9	N23	max	.037	9	1166.645	1	10.641	1	.022	1	0	1	0	1
10		min	-.204	2	-150.177	3	.455	15	0	15	0	1	0	1
11	N24	max	719.742	2	1266.148	2	-.035	15	0	15	0	1	0	1
12		min	-896.707	3	-1621.914	3	-.73	1	-.004	1	0	1	0	1
13	Totals:	max	4062.122	2	11678.162	2	0	1						
14		min	-4642.428	3	-9419.486	3	0	11						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M13	1	max	108.095	1	468.192	2	-7.267	15	0	3	.258	1	0	1
2			min	4.483	15	-786.666	3	-176.266	1	-.015	2	.011	15	0	3
3		2	max	108.095	1	327.759	2	-5.59	15	0	3	.085	1	.745	3
4			min	4.483	15	-553.674	3	-135.467	1	-.015	2	.004	15	-.442	2
5		3	max	108.095	1	187.327	2	-3.912	15	0	3	0	3	1.23	3
6			min	4.483	15	-320.683	3	-94.668	1	-.015	2	-.043	1	-.728	2
7		4	max	108.095	1	47.329	1	-2.234	15	0	3	-.004	12	1.457	3
8			min	4.483	15	-87.691	3	-53.869	1	-.015	2	-.126	1	-.858	2
9		5	max	108.095	1	145.3	3	-.556	15	0	3	-.006	12	1.425	3
10			min	4.483	15	-93.538	2	-13.071	1	-.015	2	-.163	1	-.833	2
11		6	max	108.095	1	378.292	3	27.728	1	0	3	-.006	15	1.134	3
12			min	4.483	15	-233.971	2	.396	12	-.015	2	-.155	1	-.652	1
13		7	max	108.095	1	611.283	3	68.527	1	0	3	-.004	15	.585	3
14			min	4.483	15	-374.404	2	2.073	12	-.015	2	-.101	1	-.316	1
15		8	max	108.095	1	844.275	3	109.325	1	0	3	.001	2	.181	2
16			min	4.483	15	-514.836	2	3.751	12	-.015	2	-.004	3	-.224	3
17		9	max	108.095	1	1077.266	3	150.124	1	0	3	.142	1	.831	2
18			min	4.483	15	-655.269	2	5.428	12	-.015	2	.003	12	-1.292	3
19		10	max	108.095	1	795.702	2	-7.106	12	.015	2	.331	1	1.638	2
20			min	4.483	15	-1310.258	3	-190.923	1	0	3	.01	12	-2.618	3
21		11	max	108.095	1	655.269	2	-5.428	12	.015	2	.142	1	.831	2
22			min	4.483	15	-1077.266	3	-150.124	1	0	3	.003	12	-1.292	3
23		12	max	108.095	1	514.836	2	-3.751	12	.015	2	.001	2	.181	2
24			min	4.483	15	-844.275	3	-109.325	1	0	3	-.004	3	-.224	3
25		13	max	108.095	1	374.404	2	-2.073	12	.015	2	-.004	15	.585	3
26			min	4.483	15	-611.283	3	-68.527	1	0	3	-.101	1	-.316	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
27		14	max	108.095	1	233.971	2	-.396	12	.015	2	-.006	15	1.134	3
28			min	4.483	15	-378.292	3	-27.728	1	0	3	-.155	1	-.652	1
29		15	max	108.095	1	93.538	2	13.071	1	.015	2	-.006	12	1.425	3
30			min	4.483	15	-145.3	3	.556	15	0	3	-.163	1	-.833	2
31		16	max	108.095	1	87.691	3	53.869	1	.015	2	-.004	12	1.457	3
32			min	4.483	15	-47.329	1	2.234	15	0	3	-.126	1	-.858	2
33		17	max	108.095	1	320.683	3	94.668	1	.015	2	0	3	1.23	3
34			min	4.483	15	-187.327	2	3.912	15	0	3	-.043	1	-.728	2
35		18	max	108.095	1	553.674	3	135.467	1	.015	2	.085	1	.745	3
36			min	4.483	15	-327.759	2	5.59	15	0	3	.004	15	-.442	2
37		19	max	108.095	1	786.666	3	176.266	1	.015	2	.258	1	0	1
38			min	4.483	15	-468.192	2	7.267	15	0	3	.011	15	0	3
39	M14	1	max	50.19	1	498.518	2	-7.492	15	.01	3	.294	1	0	1
40			min	2.084	15	-610.796	3	-181.731	1	-.012	2	.012	15	0	3
41		2	max	50.19	1	358.085	2	-5.814	15	.01	3	.115	1	.581	3
42			min	2.084	15	-435.018	3	-140.932	1	-.012	2	.005	15	-.476	2
43		3	max	50.19	1	217.653	2	-4.137	15	.01	3	.002	3	.967	3
44			min	2.084	15	-259.239	3	-100.134	1	-.012	2	-.019	1	-.796	2
45		4	max	50.19	1	77.22	2	-2.459	15	.01	3	-.003	12	1.157	3
46			min	2.084	15	-83.461	3	-59.335	1	-.012	2	-.107	1	-.96	2
47		5	max	50.19	1	92.317	3	-.781	15	.01	3	-.006	12	1.152	3
48			min	2.084	15	-64.728	1	-18.536	1	-.012	2	-.151	1	-.967	2
49		6	max	50.19	1	268.095	3	22.262	1	.01	3	-.006	15	.952	3
50			min	2.084	15	-204.666	1	.152	3	-.012	2	-.149	1	-.819	2
51		7	max	50.19	1	443.873	3	63.061	1	.01	3	-.004	15	.556	3
52			min	2.084	15	-344.605	1	1.857	12	-.012	2	-.101	1	-.515	2
53		8	max	50.19	1	619.651	3	103.86	1	.01	3	0	10	0	15
54			min	2.084	15	-484.544	1	3.535	12	-.012	2	-.008	1	-.054	2
55		9	max	50.19	1	795.43	3	144.659	1	.01	3	.13	1	.575	1
56			min	2.084	15	-624.943	2	5.213	12	-.012	2	.002	12	-.821	3
57		10	max	50.19	1	765.376	2	-6.89	12	.012	2	.313	1	1.347	1
58			min	2.084	15	-971.208	3	-185.457	1	-.01	3	.009	12	-1.802	3
59		11	max	50.19	1	624.943	2	-5.213	12	.012	2	.13	1	.575	1
60			min	2.084	15	-795.43	3	-144.659	1	-.01	3	.002	12	-.821	3
61		12	max	50.19	1	484.544	1	-3.535	12	.012	2	0	10	0	15
62			min	2.084	15	-619.651	3	-103.86	1	-.01	3	-.008	1	-.054	2
63		13	max	50.19	1	344.605	1	-1.857	12	.012	2	-.004	15	.556	3
64			min	2.084	15	-443.873	3	-63.061	1	-.01	3	-.101	1	-.515	2
65		14	max	50.19	1	204.666	1	-.152	3	.012	2	-.006	15	.952	3
66			min	2.084	15	-268.095	3	-22.262	1	-.01	3	-.149	1	-.819	2
67		15	max	50.19	1	64.728	1	18.536	1	.012	2	-.006	12	1.152	3
68			min	2.084	15	-92.317	3	.781	15	-.01	3	-.151	1	-.967	2
69		16	max	50.19	1	83.461	3	59.335	1	.012	2	-.003	12	1.157	3
70			min	2.084	15	-77.22	2	2.459	15	-.01	3	-.107	1	-.96	2
71		17	max	50.19	1	259.239	3	100.134	1	.012	2	.002	3	.967	3
72			min	2.084	15	-217.653	2	4.137	15	-.01	3	-.019	1	-.796	2
73		18	max	50.19	1	435.018	3	140.932	1	.012	2	.115	1	.581	3
74			min	2.084	15	-358.085	2	5.814	15	-.01	3	.005	15	-.476	2
75		19	max	50.19	1	610.796	3	181.731	1	.012	2	.294	1	0	1
76			min	2.084	15	-498.518	2	7.492	15	-.01	3	.012	15	0	3
77	M15	1	max	-2.193	15	691.64	2	-7.49	15	.012	2	.294	1	0	2
78			min	-52.731	1	-321.409	3	-181.71	1	-.008	3	.012	15	0	15
79		2	max	-2.193	15	493.995	2	-5.813	15	.012	2	.115	1	.307	3
80			min	-52.731	1	-231.45	3	-140.912	1	-.008	3	.005	15	-.659	2
81		3	max	-2.193	15	296.35	2	-4.135	15	.012	2	.002	3	.514	3
82			min	-52.731	1	-141.491	3	-100.113	1	-.008	3	-.019	1	-1.098	2
83		4	max	-2.193	15	98.705	2	-2.457	15	.012	2	-.003	12	.622	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
84			min	-52.731	1	-51.532	3	-59.314	1	-.008	3	-.108	1	-1.317	2
85		5	max	-2.193	15	38.428	3	-.779	15	.012	2	-.006	12	.629	3
86			min	-52.731	1	-98.939	2	-18.516	1	-.008	3	-.151	1	-1.317	2
87		6	max	-2.193	15	128.387	3	22.283	1	.012	2	-.006	15	.536	3
88			min	-52.731	1	-296.584	2	.237	12	-.008	3	-.149	1	-1.097	2
89		7	max	-2.193	15	218.346	3	63.082	1	.012	2	-.004	15	.344	3
90			min	-52.731	1	-494.229	2	1.914	12	-.008	3	-.101	1	-.658	2
91		8	max	-2.193	15	308.306	3	103.881	1	.012	2	0	10	.051	3
92			min	-52.731	1	-691.874	2	3.592	12	-.008	3	-.008	1	-.013	1
93		9	max	-2.193	15	398.265	3	144.679	1	.012	2	.13	1	.879	2
94			min	-52.731	1	-889.519	2	5.269	12	-.008	3	.003	12	-.342	3
95		10	max	-2.193	15	1087.164	2	-6.947	12	.008	3	.313	1	1.978	2
96			min	-52.731	1	-488.224	3	-185.478	1	-.012	2	.009	12	-.834	3
97		11	max	-2.193	15	889.519	2	-5.269	12	.008	3	.13	1	.879	2
98			min	-52.731	1	-398.265	3	-144.679	1	-.012	2	.003	12	-.342	3
99		12	max	-2.193	15	691.874	2	-3.592	12	.008	3	0	10	.051	3
100			min	-52.731	1	-308.306	3	-103.881	1	-.012	2	-.008	1	-.013	1
101		13	max	-2.193	15	494.229	2	-1.914	12	.008	3	-.004	15	.344	3
102			min	-52.731	1	-218.346	3	-63.082	1	-.012	2	-.101	1	-.658	2
103		14	max	-2.193	15	296.584	2	-.237	12	.008	3	-.006	15	.536	3
104			min	-52.731	1	-128.387	3	-22.283	1	-.012	2	-.149	1	-1.097	2
105		15	max	-2.193	15	98.939	2	18.516	1	.008	3	-.006	12	.629	3
106			min	-52.731	1	-38.428	3	.779	15	-.012	2	-.151	1	-1.317	2
107		16	max	-2.193	15	51.532	3	59.314	1	.008	3	-.003	12	.622	3
108			min	-52.731	1	-98.705	2	2.457	15	-.012	2	-.108	1	-1.317	2
109		17	max	-2.193	15	141.491	3	100.113	1	.008	3	.002	3	.514	3
110			min	-52.731	1	-296.35	2	4.135	15	-.012	2	-.019	1	-1.098	2
111		18	max	-2.193	15	231.45	3	140.912	1	.008	3	.115	1	.307	3
112			min	-52.731	1	-493.995	2	5.813	15	-.012	2	.005	15	-.659	2
113		19	max	-2.193	15	321.409	3	181.71	1	.008	3	.294	1	0	2
114			min	-52.731	1	-691.64	2	7.49	15	-.012	2	.012	15	0	15
115	M16	1	max	-4.794	15	662.33	2	-7.274	15	.011	1	.26	1	0	2
116			min	-115.467	1	-298.665	3	-176.524	1	-.012	3	.011	15	0	3
117		2	max	-4.794	15	464.685	2	-5.597	15	.011	1	.086	1	.282	3
118			min	-115.467	1	-208.706	3	-135.726	1	-.012	3	.004	15	-.626	2
119		3	max	-4.794	15	267.041	2	-3.919	15	.011	1	0	3	.464	3
120			min	-115.467	1	-118.746	3	-94.927	1	-.012	3	-.042	1	-1.033	2
121		4	max	-4.794	15	69.396	2	-2.241	15	.011	1	-.004	12	.546	3
122			min	-115.467	1	-28.787	3	-54.128	1	-.012	3	-.125	1	-1.22	2
123		5	max	-4.794	15	61.172	3	-.563	15	.011	1	-.006	12	.528	3
124			min	-115.467	1	-128.249	2	-13.33	1	-.012	3	-.162	1	-1.187	2
125		6	max	-4.794	15	151.131	3	27.469	1	.011	1	-.006	15	.41	3
126			min	-115.467	1	-325.894	2	.585	12	-.012	3	-.155	1	-.935	2
127		7	max	-4.794	15	241.091	3	68.268	1	.011	1	-.004	15	.192	3
128			min	-115.467	1	-523.539	2	2.263	12	-.012	3	-.101	1	-.463	2
129		8	max	-4.794	15	331.05	3	109.067	1	.011	1	0	10	.229	2
130			min	-115.467	1	-721.184	2	3.94	12	-.012	3	-.003	3	-.126	3
131		9	max	-4.794	15	421.009	3	149.865	1	.011	1	.141	1	1.14	2
132			min	-115.467	1	-918.829	2	5.618	12	-.012	3	.004	12	-.544	3
133		10	max	-4.794	15	1116.474	2	-7.296	12	.012	3	.33	1	2.271	2
134			min	-115.467	1	-510.969	3	-190.664	1	-.011	1	.011	12	-1.062	3
135		11	max	-4.794	15	918.829	2	-5.618	12	.012	3	.141	1	1.14	2
136			min	-115.467	1	-421.009	3	-149.865	1	-.011	1	.004	12	-.544	3
137		12	max	-4.794	15	721.184	2	-3.94	12	.012	3	0	10	.229	2
138			min	-115.467	1	-331.05	3	-109.067	1	-.011	1	-.003	3	-.126	3
139		13	max	-4.794	15	523.539	2	-2.263	12	.012	3	-.004	15	.192	3
140			min	-115.467	1	-241.091	3	-68.268	1	-.011	1	-.101	1	-.463	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
141		14	max	-4.794	15	325.894	2	-.585	12	.012	3	-.006	15	.41	3
142			min	-115.467	1	-151.131	3	-27.469	1	-.011	1	-.155	1	-.935	2
143		15	max	-4.794	15	128.249	2	13.33	1	.012	3	-.006	12	.528	3
144			min	-115.467	1	-61.172	3	.563	15	-.011	1	-.162	1	-1.187	2
145		16	max	-4.794	15	28.787	3	54.128	1	.012	3	-.004	12	.546	3
146			min	-115.467	1	-69.396	2	2.241	15	-.011	1	-.125	1	-1.22	2
147		17	max	-4.794	15	118.746	3	94.927	1	.012	3	0	3	.464	3
148			min	-115.467	1	-267.041	2	3.919	15	-.011	1	-.042	1	-1.033	2
149		18	max	-4.794	15	208.706	3	135.726	1	.012	3	.086	1	.282	3
150			min	-115.467	1	-464.685	2	5.597	15	-.011	1	.004	15	-.626	2
151		19	max	-4.794	15	298.665	3	176.524	1	.012	3	.26	1	0	2
152			min	-115.467	1	-662.33	2	7.274	15	-.011	1	.011	15	0	3
153	M2	1	max	1084.867	2	1.921	4	.697	1	0	5	0	3	0	1
154			min	-1425.854	3	.452	15	.029	15	0	1	0	1	0	1
155		2	max	1085.296	2	1.864	4	.697	1	0	5	0	1	0	15
156			min	-1425.533	3	.439	15	.029	15	0	1	0	15	0	4
157		3	max	1085.724	2	1.807	4	.697	1	0	5	0	1	0	15
158			min	-1425.211	3	.426	15	.029	15	0	1	0	15	-.001	4
159		4	max	1086.153	2	1.751	4	.697	1	0	5	0	1	0	15
160			min	-1424.89	3	.412	15	.029	15	0	1	0	15	-.002	4
161		5	max	1086.581	2	1.694	4	.697	1	0	5	0	1	0	15
162			min	-1424.569	3	.399	15	.029	15	0	1	0	15	-.002	4
163		6	max	1087.01	2	1.637	4	.697	1	0	5	0	1	0	15
164			min	-1424.247	3	.386	15	.029	15	0	1	0	15	-.003	4
165		7	max	1087.438	2	1.58	4	.697	1	0	5	.001	1	0	15
166			min	-1423.926	3	.372	15	.029	15	0	1	0	15	-.003	4
167		8	max	1087.867	2	1.523	4	.697	1	0	5	.001	1	0	15
168			min	-1423.604	3	.359	15	.029	15	0	1	0	15	-.004	4
169		9	max	1088.295	2	1.467	4	.697	1	0	5	.002	1	0	15
170			min	-1423.283	3	.346	15	.029	15	0	1	0	15	-.004	4
171		10	max	1088.724	2	1.41	4	.697	1	0	5	.002	1	-.001	15
172			min	-1422.962	3	.332	15	.029	15	0	1	0	15	-.004	4
173		11	max	1089.152	2	1.353	4	.697	1	0	5	.002	1	-.001	15
174			min	-1422.64	3	.311	12	.029	15	0	1	0	15	-.005	4
175		12	max	1089.581	2	1.296	4	.697	1	0	5	.002	1	-.001	15
176			min	-1422.319	3	.289	12	.029	15	0	1	0	15	-.005	4
177		13	max	1090.009	2	1.24	4	.697	1	0	5	.002	1	-.001	15
178			min	-1421.998	3	.267	12	.029	15	0	1	0	15	-.006	4
179		14	max	1090.438	2	1.187	2	.697	1	0	5	.003	1	-.001	15
180			min	-1421.676	3	.245	12	.029	15	0	1	0	15	-.006	4
181		15	max	1090.866	2	1.143	2	.697	1	0	5	.003	1	-.001	15
182			min	-1421.355	3	.223	12	.029	15	0	1	0	15	-.006	4
183		16	max	1091.295	2	1.098	2	.697	1	0	5	.003	1	-.002	15
184			min	-1421.034	3	.201	12	.029	15	0	1	0	15	-.007	4
185		17	max	1091.723	2	1.054	2	.697	1	0	5	.003	1	-.002	15
186			min	-1420.712	3	.178	12	.029	15	0	1	0	15	-.007	4
187		18	max	1092.152	2	1.01	2	.697	1	0	5	.003	1	-.002	15
188			min	-1420.391	3	.156	12	.029	15	0	1	0	15	-.007	4
189		19	max	1092.58	2	.966	2	.697	1	0	5	.004	1	-.002	15
190			min	-1420.069	3	.134	12	.029	15	0	1	0	15	-.007	4
191	M3	1	max	632.618	2	7.882	4	.161	1	0	5	0	1	.007	4
192			min	-779.363	3	1.853	15	.007	15	0	1	0	15	.002	15
193		2	max	632.447	2	7.115	4	.161	1	0	5	0	1	.005	2
194			min	-779.49	3	1.673	15	.007	15	0	1	0	15	0	12
195		3	max	632.277	2	6.348	4	.161	1	0	5	0	1	.002	2
196			min	-779.618	3	1.493	15	.007	15	0	1	0	15	0	3
197		4	max	632.107	2	5.58	4	.161	1	0	5	0	1	0	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
198			min	-779.746	3	1.312	15	.007	15	0	1	0	15	-.002	3
199		5	max	631.936	2	4.813	4	.161	1	0	5	0	1	0	15
200			min	-779.874	3	1.132	15	.007	15	0	1	0	15	-.003	3
201		6	max	631.766	2	4.046	4	.161	1	0	5	0	1	-.001	15
202			min	-780.002	3	.952	15	.007	15	0	1	0	15	-.005	4
203		7	max	631.596	2	3.279	4	.161	1	0	5	0	1	-.002	15
204			min	-780.129	3	.771	15	.007	15	0	1	0	15	-.007	4
205		8	max	631.425	2	2.511	4	.161	1	0	5	0	1	-.002	15
206			min	-780.257	3	.591	15	.007	15	0	1	0	15	-.008	4
207		9	max	631.255	2	1.744	4	.161	1	0	5	0	1	-.002	15
208			min	-780.385	3	.411	15	.007	15	0	1	0	15	-.009	4
209		10	max	631.085	2	.977	4	.161	1	0	5	0	1	-.002	15
210			min	-780.513	3	.23	15	.007	15	0	1	0	15	-.009	4
211		11	max	630.914	2	.347	2	.161	1	0	5	.001	1	-.002	15
212			min	-780.64	3	-.127	3	.007	15	0	1	0	15	-.01	4
213		12	max	630.744	2	-.13	15	.161	1	0	5	.001	1	-.002	15
214			min	-780.768	3	-.576	3	.007	15	0	1	0	15	-.01	4
215		13	max	630.574	2	-.311	15	.161	1	0	5	.001	1	-.002	15
216			min	-780.896	3	-1.325	4	.007	15	0	1	0	15	-.009	4
217		14	max	630.403	2	-.491	15	.161	1	0	5	.001	1	-.002	15
218			min	-781.024	3	-2.092	4	.007	15	0	1	0	15	-.008	4
219		15	max	630.233	2	-.672	15	.161	1	0	5	.001	1	-.002	15
220			min	-781.151	3	-2.859	4	.007	15	0	1	0	15	-.007	4
221		16	max	630.063	2	-.852	15	.161	1	0	5	.001	1	-.001	15
222			min	-781.279	3	-3.626	4	.007	15	0	1	0	15	-.006	4
223		17	max	629.892	2	-1.032	15	.161	1	0	5	.001	1	-.001	15
224			min	-781.407	3	-4.394	4	.007	15	0	1	0	15	-.004	4
225		18	max	629.722	2	-1.213	15	.161	1	0	5	.002	1	0	15
226			min	-781.535	3	-5.161	4	.007	15	0	1	0	15	-.002	4
227		19	max	629.551	2	-1.393	15	.161	1	0	5	.002	1	0	1
228			min	-781.662	3	-5.928	4	.007	15	0	1	0	15	0	1
229	M4	1	max	1163.579	1	0	1	-.455	15	0	1	.001	1	0	1
230			min	-152.477	3	0	1	-11.016	1	0	1	0	15	0	1
231		2	max	1163.749	1	0	1	-.455	15	0	1	0	3	0	1
232			min	-152.349	3	0	1	-11.016	1	0	1	0	1	0	1
233		3	max	1163.92	1	0	1	-.455	15	0	1	0	15	0	1
234			min	-152.222	3	0	1	-11.016	1	0	1	-.001	1	0	1
235		4	max	1164.09	1	0	1	-.455	15	0	1	0	15	0	1
236			min	-152.094	3	0	1	-11.016	1	0	1	-.003	1	0	1
237		5	max	1164.26	1	0	1	-.455	15	0	1	0	15	0	1
238			min	-151.966	3	0	1	-11.016	1	0	1	-.004	1	0	1
239		6	max	1164.431	1	0	1	-.455	15	0	1	0	15	0	1
240			min	-151.838	3	0	1	-11.016	1	0	1	-.005	1	0	1
241		7	max	1164.601	1	0	1	-.455	15	0	1	0	15	0	1
242			min	-151.71	3	0	1	-11.016	1	0	1	-.006	1	0	1
243		8	max	1164.772	1	0	1	-.455	15	0	1	0	15	0	1
244			min	-151.583	3	0	1	-11.016	1	0	1	-.008	1	0	1
245		9	max	1164.942	1	0	1	-.455	15	0	1	0	15	0	1
246			min	-151.455	3	0	1	-11.016	1	0	1	-.009	1	0	1
247		10	max	1165.112	1	0	1	-.455	15	0	1	0	15	0	1
248			min	-151.327	3	0	1	-11.016	1	0	1	-.01	1	0	1
249		11	max	1165.283	1	0	1	-.455	15	0	1	0	15	0	1
250			min	-151.199	3	0	1	-11.016	1	0	1	-.012	1	0	1
251		12	max	1165.453	1	0	1	-.455	15	0	1	0	15	0	1
252			min	-151.072	3	0	1	-11.016	1	0	1	-.013	1	0	1
253		13	max	1165.623	1	0	1	-.455	15	0	1	0	15	0	1
254			min	-150.944	3	0	1	-11.016	1	0	1	-.014	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
255		14	max	1165.794	1	0	1	-.455	15	0	1	0	15	0	1
256			min	-150.816	3	0	1	-11.016	1	0	1	-.015	1	0	1
257		15	max	1165.964	1	0	1	-.455	15	0	1	0	15	0	1
258			min	-150.688	3	0	1	-11.016	1	0	1	-.017	1	0	1
259		16	max	1166.134	1	0	1	-.455	15	0	1	0	15	0	1
260			min	-150.561	3	0	1	-11.016	1	0	1	-.018	1	0	1
261		17	max	1166.305	1	0	1	-.455	15	0	1	0	15	0	1
262			min	-150.433	3	0	1	-11.016	1	0	1	-.019	1	0	1
263		18	max	1166.475	1	0	1	-.455	15	0	1	0	15	0	1
264			min	-150.305	3	0	1	-11.016	1	0	1	-.02	1	0	1
265		19	max	1166.645	1	0	1	-.455	15	0	1	0	15	0	1
266			min	-150.177	3	0	1	-11.016	1	0	1	-.022	1	0	1
267	M6	1	max	3486.816	2	2.439	2	0	1	0	1	0	1	0	1
268			min	-4660.079	3	-.038	3	0	1	0	1	0	1	0	1
269		2	max	3487.244	2	2.395	2	0	1	0	1	0	1	0	3
270			min	-4659.758	3	-.071	3	0	1	0	1	0	1	0	2
271		3	max	3487.673	2	2.351	2	0	1	0	1	0	1	0	3
272			min	-4659.436	3	-.104	3	0	1	0	1	0	1	-.001	2
273		4	max	3488.101	2	2.306	2	0	1	0	1	0	1	0	3
274			min	-4659.115	3	-.137	3	0	1	0	1	0	1	-.002	2
275		5	max	3488.53	2	2.262	2	0	1	0	1	0	1	0	3
276			min	-4658.794	3	-.17	3	0	1	0	1	0	1	-.003	2
277		6	max	3488.958	2	2.218	2	0	1	0	1	0	1	0	3
278			min	-4658.472	3	-.204	3	0	1	0	1	0	1	-.003	2
279		7	max	3489.387	2	2.174	2	0	1	0	1	0	1	0	3
280			min	-4658.151	3	-.237	3	0	1	0	1	0	1	-.004	2
281		8	max	3489.815	2	2.129	2	0	1	0	1	0	1	0	3
282			min	-4657.83	3	-.27	3	0	1	0	1	0	1	-.005	2
283		9	max	3490.244	2	2.085	2	0	1	0	1	0	1	0	3
284			min	-4657.508	3	-.303	3	0	1	0	1	0	1	-.005	2
285		10	max	3490.672	2	2.041	2	0	1	0	1	0	1	0	3
286			min	-4657.187	3	-.336	3	0	1	0	1	0	1	-.006	2
287		11	max	3491.101	2	1.997	2	0	1	0	1	0	1	0	3
288			min	-4656.866	3	-.37	3	0	1	0	1	0	1	-.006	2
289		12	max	3491.529	2	1.952	2	0	1	0	1	0	1	0	3
290			min	-4656.544	3	-.403	3	0	1	0	1	0	1	-.007	2
291		13	max	3491.958	2	1.908	2	0	1	0	1	0	1	0	3
292			min	-4656.223	3	-.436	3	0	1	0	1	0	1	-.008	2
293		14	max	3492.386	2	1.864	2	0	1	0	1	0	1	0	3
294			min	-4655.901	3	-.469	3	0	1	0	1	0	1	-.008	2
295		15	max	3492.815	2	1.82	2	0	1	0	1	0	1	.001	3
296			min	-4655.58	3	-.502	3	0	1	0	1	0	1	-.009	2
297		16	max	3493.243	2	1.775	2	0	1	0	1	0	1	.001	3
298			min	-4655.259	3	-.535	3	0	1	0	1	0	1	-.009	2
299		17	max	3493.672	2	1.731	2	0	1	0	1	0	1	.001	3
300			min	-4654.937	3	-.569	3	0	1	0	1	0	1	-.01	2
301		18	max	3494.1	2	1.687	2	0	1	0	1	0	1	.002	3
302			min	-4654.616	3	-.602	3	0	1	0	1	0	1	-.01	2
303		19	max	3494.529	2	1.643	2	0	1	0	1	0	1	.002	3
304			min	-4654.295	3	-.635	3	0	1	0	1	0	1	-.011	2
305	M7	1	max	2358.384	2	7.918	4	0	1	0	1	0	1	.011	2
306			min	-2459.976	3	1.858	15	0	1	0	1	0	1	-.002	3
307		2	max	2358.213	2	7.15	4	0	1	0	1	0	1	.008	2
308			min	-2460.104	3	1.678	15	0	1	0	1	0	1	-.003	3
309		3	max	2358.043	2	6.383	4	0	1	0	1	0	1	.005	2
310			min	-2460.232	3	1.498	15	0	1	0	1	0	1	-.005	3
311		4	max	2357.873	2	5.616	4	0	1	0	1	0	1	.003	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
312			min	-2460.36	3	1.317	15	0	1	0	1	0	1	-.006	3
313		5	max	2357.702	2	4.849	4	0	1	0	1	0	1	.001	2
314			min	-2460.487	3	1.137	15	0	1	0	1	0	1	-.007	3
315		6	max	2357.532	2	4.081	4	0	1	0	1	0	1	0	2
316			min	-2460.615	3	.957	15	0	1	0	1	0	1	-.007	3
317		7	max	2357.362	2	3.314	4	0	1	0	1	0	1	-.002	15
318			min	-2460.743	3	.776	15	0	1	0	1	0	1	-.008	3
319		8	max	2357.191	2	2.61	2	0	1	0	1	0	1	-.002	15
320			min	-2460.871	3	.496	12	0	1	0	1	0	1	-.008	3
321		9	max	2357.021	2	2.012	2	0	1	0	1	0	1	-.002	15
322			min	-2460.998	3	.198	12	0	1	0	1	0	1	-.009	4
323		10	max	2356.851	2	1.414	2	0	1	0	1	0	1	-.002	15
324			min	-2461.126	3	-.233	3	0	1	0	1	0	1	-.009	4
325		11	max	2356.68	2	.816	2	0	1	0	1	0	1	-.002	15
326			min	-2461.254	3	-.681	3	0	1	0	1	0	1	-.009	4
327		12	max	2356.51	2	.219	2	0	1	0	1	0	1	-.002	15
328			min	-2461.382	3	-1.13	3	0	1	0	1	0	1	-.009	4
329		13	max	2356.34	2	-.306	15	0	1	0	1	0	1	-.002	15
330			min	-2461.509	3	-1.578	3	0	1	0	1	0	1	-.009	4
331		14	max	2356.169	2	-.486	15	0	1	0	1	0	1	-.002	15
332			min	-2461.637	3	-2.056	4	0	1	0	1	0	1	-.008	4
333		15	max	2355.999	2	-.666	15	0	1	0	1	0	1	-.002	15
334			min	-2461.765	3	-2.824	4	0	1	0	1	0	1	-.007	4
335		16	max	2355.829	2	-.847	15	0	1	0	1	0	1	-.001	15
336			min	-2461.893	3	-3.591	4	0	1	0	1	0	1	-.006	4
337		17	max	2355.658	2	-1.027	15	0	1	0	1	0	1	-.001	15
338			min	-2462.02	3	-4.358	4	0	1	0	1	0	1	-.004	4
339		18	max	2355.488	2	-1.207	15	0	1	0	1	0	1	0	15
340			min	-2462.148	3	-5.125	4	0	1	0	1	0	1	-.002	4
341		19	max	2355.318	2	-1.388	15	0	1	0	1	0	1	0	1
342			min	-2462.276	3	-5.892	4	0	1	0	1	0	1	0	1
343	M8	1	max	3175.017	1	0	1	0	1	0	1	0	1	0	1
344			min	-577.952	3	0	1	0	1	0	1	0	1	0	1
345		2	max	3175.187	1	0	1	0	1	0	1	0	1	0	1
346			min	-577.824	3	0	1	0	1	0	1	0	1	0	1
347		3	max	3175.358	1	0	1	0	1	0	1	0	1	0	1
348			min	-577.697	3	0	1	0	1	0	1	0	1	0	1
349		4	max	3175.528	1	0	1	0	1	0	1	0	1	0	1
350			min	-577.569	3	0	1	0	1	0	1	0	1	0	1
351		5	max	3175.698	1	0	1	0	1	0	1	0	1	0	1
352			min	-577.441	3	0	1	0	1	0	1	0	1	0	1
353		6	max	3175.869	1	0	1	0	1	0	1	0	1	0	1
354			min	-577.313	3	0	1	0	1	0	1	0	1	0	1
355		7	max	3176.039	1	0	1	0	1	0	1	0	1	0	1
356			min	-577.186	3	0	1	0	1	0	1	0	1	0	1
357		8	max	3176.21	1	0	1	0	1	0	1	0	1	0	1
358			min	-577.058	3	0	1	0	1	0	1	0	1	0	1
359		9	max	3176.38	1	0	1	0	1	0	1	0	1	0	1
360			min	-576.93	3	0	1	0	1	0	1	0	1	0	1
361		10	max	3176.55	1	0	1	0	1	0	1	0	1	0	1
362			min	-576.802	3	0	1	0	1	0	1	0	1	0	1
363		11	max	3176.721	1	0	1	0	1	0	1	0	1	0	1
364			min	-576.675	3	0	1	0	1	0	1	0	1	0	1
365		12	max	3176.891	1	0	1	0	1	0	1	0	1	0	1
366			min	-576.547	3	0	1	0	1	0	1	0	1	0	1
367		13	max	3177.061	1	0	1	0	1	0	1	0	1	0	1
368			min	-576.419	3	0	1	0	1	0	1	0	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
369		14	max	3177.232	1	0	1	0	1	0	1	0	1	0	1
370			min	-576.291	3	0	1	0	1	0	1	0	1	0	1
371		15	max	3177.402	1	0	1	0	1	0	1	0	1	0	1
372			min	-576.163	3	0	1	0	1	0	1	0	1	0	1
373		16	max	3177.572	1	0	1	0	1	0	1	0	1	0	1
374			min	-576.036	3	0	1	0	1	0	1	0	1	0	1
375		17	max	3177.743	1	0	1	0	1	0	1	0	1	0	1
376			min	-575.908	3	0	1	0	1	0	1	0	1	0	1
377		18	max	3177.913	1	0	1	0	1	0	1	0	1	0	1
378			min	-575.78	3	0	1	0	1	0	1	0	1	0	1
379		19	max	3178.083	1	0	1	0	1	0	1	0	1	0	1
380			min	-575.652	3	0	1	0	1	0	1	0	1	0	1
381	M10	1	max	1084.867	2	1.921	4	-.029	15	0	1	0	1	0	1
382			min	-1425.854	3	.452	15	-.697	1	0	5	0	3	0	1
383		2	max	1085.296	2	1.864	4	-.029	15	0	1	0	15	0	15
384			min	-1425.533	3	.439	15	-.697	1	0	5	0	1	0	4
385		3	max	1085.724	2	1.807	4	-.029	15	0	1	0	15	0	15
386			min	-1425.211	3	.426	15	-.697	1	0	5	0	1	-.001	4
387		4	max	1086.153	2	1.751	4	-.029	15	0	1	0	15	0	15
388			min	-1424.89	3	.412	15	-.697	1	0	5	0	1	-.002	4
389		5	max	1086.581	2	1.694	4	-.029	15	0	1	0	15	0	15
390			min	-1424.569	3	.399	15	-.697	1	0	5	0	1	-.002	4
391		6	max	1087.01	2	1.637	4	-.029	15	0	1	0	15	0	15
392			min	-1424.247	3	.386	15	-.697	1	0	5	0	1	-.003	4
393		7	max	1087.438	2	1.58	4	-.029	15	0	1	0	15	0	15
394			min	-1423.926	3	.372	15	-.697	1	0	5	-.001	1	-.003	4
395		8	max	1087.867	2	1.523	4	-.029	15	0	1	0	15	0	15
396			min	-1423.604	3	.359	15	-.697	1	0	5	-.001	1	-.004	4
397		9	max	1088.295	2	1.467	4	-.029	15	0	1	0	15	0	15
398			min	-1423.283	3	.346	15	-.697	1	0	5	-.002	1	-.004	4
399		10	max	1088.724	2	1.41	4	-.029	15	0	1	0	15	-.001	15
400			min	-1422.962	3	.332	15	-.697	1	0	5	-.002	1	-.004	4
401		11	max	1089.152	2	1.353	4	-.029	15	0	1	0	15	-.001	15
402			min	-1422.64	3	.311	12	-.697	1	0	5	-.002	1	-.005	4
403		12	max	1089.581	2	1.296	4	-.029	15	0	1	0	15	-.001	15
404			min	-1422.319	3	.289	12	-.697	1	0	5	-.002	1	-.005	4
405		13	max	1090.009	2	1.24	4	-.029	15	0	1	0	15	-.001	15
406			min	-1421.998	3	.267	12	-.697	1	0	5	-.002	1	-.006	4
407		14	max	1090.438	2	1.187	2	-.029	15	0	1	0	15	-.001	15
408			min	-1421.676	3	.245	12	-.697	1	0	5	-.003	1	-.006	4
409		15	max	1090.866	2	1.143	2	-.029	15	0	1	0	15	-.001	15
410			min	-1421.355	3	.223	12	-.697	1	0	5	-.003	1	-.006	4
411		16	max	1091.295	2	1.098	2	-.029	15	0	1	0	15	-.002	15
412			min	-1421.034	3	.201	12	-.697	1	0	5	-.003	1	-.007	4
413		17	max	1091.723	2	1.054	2	-.029	15	0	1	0	15	-.002	15
414			min	-1420.712	3	.178	12	-.697	1	0	5	-.003	1	-.007	4
415		18	max	1092.152	2	1.01	2	-.029	15	0	1	0	15	-.002	15
416			min	-1420.391	3	.156	12	-.697	1	0	5	-.003	1	-.007	4
417		19	max	1092.58	2	.966	2	-.029	15	0	1	0	15	-.002	15
418			min	-1420.069	3	.134	12	-.697	1	0	5	-.004	1	-.007	4
419	M11	1	max	632.618	2	7.882	4	-.007	15	0	1	0	15	.007	4
420			min	-779.363	3	1.853	15	-.161	1	0	5	0	1	.002	15
421		2	max	632.447	2	7.115	4	-.007	15	0	1	0	15	.005	2
422			min	-779.49	3	1.673	15	-.161	1	0	5	0	1	0	12
423		3	max	632.277	2	6.348	4	-.007	15	0	1	0	15	.002	2
424			min	-779.618	3	1.493	15	-.161	1	0	5	0	1	0	3
425		4	max	632.107	2	5.58	4	-.007	15	0	1	0	15	0	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
426			min	-779.746	3	1.312	15	-.161	1	0	5	0	1	-.002	3
427		5	max	631.936	2	4.813	4	-.007	15	0	1	0	15	0	15
428			min	-779.874	3	1.132	15	-.161	1	0	5	0	1	-.003	3
429		6	max	631.766	2	4.046	4	-.007	15	0	1	0	15	-.001	15
430			min	-780.002	3	.952	15	-.161	1	0	5	0	1	-.005	4
431		7	max	631.596	2	3.279	4	-.007	15	0	1	0	15	-.002	15
432			min	-780.129	3	.771	15	-.161	1	0	5	0	1	-.007	4
433		8	max	631.425	2	2.511	4	-.007	15	0	1	0	15	-.002	15
434			min	-780.257	3	.591	15	-.161	1	0	5	0	1	-.008	4
435		9	max	631.255	2	1.744	4	-.007	15	0	1	0	15	-.002	15
436			min	-780.385	3	.411	15	-.161	1	0	5	0	1	-.009	4
437		10	max	631.085	2	.977	4	-.007	15	0	1	0	15	-.002	15
438			min	-780.513	3	.23	15	-.161	1	0	5	0	1	-.009	4
439		11	max	630.914	2	.347	2	-.007	15	0	1	0	15	-.002	15
440			min	-780.64	3	-.127	3	-.161	1	0	5	-.001	1	-.01	4
441		12	max	630.744	2	-.13	15	-.007	15	0	1	0	15	-.002	15
442			min	-780.768	3	-.576	3	-.161	1	0	5	-.001	1	-.01	4
443		13	max	630.574	2	-.311	15	-.007	15	0	1	0	15	-.002	15
444			min	-780.896	3	-1.325	4	-.161	1	0	5	-.001	1	-.009	4
445		14	max	630.403	2	-.491	15	-.007	15	0	1	0	15	-.002	15
446			min	-781.024	3	-2.092	4	-.161	1	0	5	-.001	1	-.008	4
447		15	max	630.233	2	-.672	15	-.007	15	0	1	0	15	-.002	15
448			min	-781.151	3	-2.859	4	-.161	1	0	5	-.001	1	-.007	4
449		16	max	630.063	2	-.852	15	-.007	15	0	1	0	15	-.001	15
450			min	-781.279	3	-3.626	4	-.161	1	0	5	-.001	1	-.006	4
451		17	max	629.892	2	-1.032	15	-.007	15	0	1	0	15	-.001	15
452			min	-781.407	3	-4.394	4	-.161	1	0	5	-.001	1	-.004	4
453		18	max	629.722	2	-1.213	15	-.007	15	0	1	0	15	0	15
454			min	-781.535	3	-5.161	4	-.161	1	0	5	-.002	1	-.002	4
455		19	max	629.551	2	-1.393	15	-.007	15	0	1	0	15	0	1
456			min	-781.662	3	-5.928	4	-.161	1	0	5	-.002	1	0	1
457	M12	1	max	1163.579	1	0	1	11.016	1	0	1	0	15	0	1
458			min	-152.477	3	0	1	.455	15	0	1	-.001	1	0	1
459		2	max	1163.749	1	0	1	11.016	1	0	1	0	1	0	1
460			min	-152.349	3	0	1	.455	15	0	1	0	3	0	1
461		3	max	1163.92	1	0	1	11.016	1	0	1	.001	1	0	1
462			min	-152.222	3	0	1	.455	15	0	1	0	15	0	1
463		4	max	1164.09	1	0	1	11.016	1	0	1	.003	1	0	1
464			min	-152.094	3	0	1	.455	15	0	1	0	15	0	1
465		5	max	1164.26	1	0	1	11.016	1	0	1	.004	1	0	1
466			min	-151.966	3	0	1	.455	15	0	1	0	15	0	1
467		6	max	1164.431	1	0	1	11.016	1	0	1	.005	1	0	1
468			min	-151.838	3	0	1	.455	15	0	1	0	15	0	1
469		7	max	1164.601	1	0	1	11.016	1	0	1	.006	1	0	1
470			min	-151.71	3	0	1	.455	15	0	1	0	15	0	1
471		8	max	1164.772	1	0	1	11.016	1	0	1	.008	1	0	1
472			min	-151.583	3	0	1	.455	15	0	1	0	15	0	1
473		9	max	1164.942	1	0	1	11.016	1	0	1	.009	1	0	1
474			min	-151.455	3	0	1	.455	15	0	1	0	15	0	1
475		10	max	1165.112	1	0	1	11.016	1	0	1	.01	1	0	1
476			min	-151.327	3	0	1	.455	15	0	1	0	15	0	1
477		11	max	1165.283	1	0	1	11.016	1	0	1	.012	1	0	1
478			min	-151.199	3	0	1	.455	15	0	1	0	15	0	1
479		12	max	1165.453	1	0	1	11.016	1	0	1	.013	1	0	1
480			min	-151.072	3	0	1	.455	15	0	1	0	15	0	1
481		13	max	1165.623	1	0	1	11.016	1	0	1	.014	1	0	1
482			min	-150.944	3	0	1	.455	15	0	1	0	15	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
483		14	max	1165.794	1	0	1	11.016	1	0	1	.015	1	0	1
484			min	-150.816	3	0	1	.455	15	0	1	0	15	0	1
485		15	max	1165.964	1	0	1	11.016	1	0	1	.017	1	0	1
486			min	-150.688	3	0	1	.455	15	0	1	0	15	0	1
487		16	max	1166.134	1	0	1	11.016	1	0	1	.018	1	0	1
488			min	-150.561	3	0	1	.455	15	0	1	0	15	0	1
489		17	max	1166.305	1	0	1	11.016	1	0	1	.019	1	0	1
490			min	-150.433	3	0	1	.455	15	0	1	0	15	0	1
491		18	max	1166.475	1	0	1	11.016	1	0	1	.02	1	0	1
492			min	-150.305	3	0	1	.455	15	0	1	0	15	0	1
493		19	max	1166.645	1	0	1	11.016	1	0	1	.022	1	0	1
494			min	-150.177	3	0	1	.455	15	0	1	0	15	0	1
495	M1	1	max	176.272	1	786.637	3	-4.483	15	0	1	.258	1	0	3
496			min	7.267	15	-467.535	2	-107.963	1	0	3	.011	15	-.015	2
497		2	max	176.878	1	785.663	3	-4.483	15	0	1	.201	1	.233	1
498			min	7.45	15	-468.833	2	-107.963	1	0	3	.008	15	-.415	3
499		3	max	480.138	3	551.832	2	-4.454	15	0	3	.144	1	.468	1
500			min	-281.409	2	-565.624	3	-107.497	1	0	2	.006	15	-.813	3
501		4	max	480.592	3	550.533	2	-4.454	15	0	3	.087	1	.19	1
502			min	-280.804	2	-566.597	3	-107.497	1	0	2	.004	15	-.514	3
503		5	max	481.046	3	549.235	2	-4.454	15	0	3	.031	1	-.003	15
504			min	-280.199	2	-567.571	3	-107.497	1	0	2	.001	15	-.215	3
505		6	max	481.5	3	547.937	2	-4.454	15	0	3	-.001	15	.085	3
506			min	-279.593	2	-568.545	3	-107.497	1	0	2	-.026	1	-.403	2
507		7	max	481.954	3	546.639	2	-4.454	15	0	3	-.003	15	.385	3
508			min	-278.988	2	-569.518	3	-107.497	1	0	2	-.083	1	-.691	2
509		8	max	482.408	3	545.341	2	-4.454	15	0	3	-.006	15	.686	3
510			min	-278.383	2	-570.492	3	-107.497	1	0	2	-.14	1	-.98	2
511		9	max	495.291	3	48.62	2	-6.538	15	0	9	.082	1	.802	3
512			min	-204.683	2	.395	15	-157.729	1	0	3	.003	15	-1.121	2
513		10	max	495.745	3	47.322	2	-6.538	15	0	9	0	15	.78	3
514			min	-204.078	2	.004	15	-157.729	1	0	3	-.001	1	-1.147	2
515		11	max	496.199	3	46.023	2	-6.538	15	0	9	-.003	15	.759	3
516			min	-203.473	2	-1.588	4	-157.729	1	0	3	-.084	1	-1.171	2
517		12	max	508.989	3	364.572	3	-4.346	15	0	2	.138	1	.661	3
518			min	-129.746	2	-645.653	2	-105.049	1	0	3	.006	15	-1.038	2
519		13	max	509.443	3	363.599	3	-4.346	15	0	2	.082	1	.469	3
520			min	-129.14	2	-646.952	2	-105.049	1	0	3	.003	15	-.697	2
521		14	max	509.897	3	362.625	3	-4.346	15	0	2	.027	1	.277	3
522			min	-128.535	2	-648.25	2	-105.049	1	0	3	.001	15	-.355	2
523		15	max	510.351	3	361.651	3	-4.346	15	0	2	-.001	15	.086	3
524			min	-127.93	2	-649.548	2	-105.049	1	0	3	-.029	1	-.036	1
525		16	max	510.805	3	360.678	3	-4.346	15	0	2	-.003	15	.33	2
526			min	-127.324	2	-650.846	2	-105.049	1	0	3	-.084	1	-.104	3
527		17	max	511.259	3	359.704	3	-4.346	15	0	2	-.006	15	.674	2
528			min	-126.719	2	-652.145	2	-105.049	1	0	3	-.139	1	-.294	3
529		18	max	-7.457	15	664.198	2	-4.794	15	0	3	-.008	15	.339	2
530			min	-177.124	1	-297.763	3	-115.595	1	0	2	-.199	1	-.145	3
531		19	max	-7.274	15	662.9	2	-4.794	15	0	3	-.011	15	.012	3
532			min	-176.519	1	-298.737	3	-115.595	1	0	2	-.26	1	-.011	1
533	M5	1	max	381.832	1	2620.422	3	0	1	0	1	0	1	.029	2
534			min	14.213	12	-1587.508	2	0	1	0	1	0	1	0	3
535		2	max	382.438	1	2619.449	3	0	1	0	1	0	1	.867	2
536			min	14.515	12	-1588.806	2	0	1	0	1	0	1	-1.383	3
537		3	max	1544.464	3	1672.879	2	0	1	0	1	0	1	1.667	2
538			min	-982.526	2	-1815.467	3	0	1	0	1	0	1	-2.712	3
539		4	max	1544.918	3	1671.581	2	0	1	0	1	0	1	.807	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
540			min	-981.921	2	-1816.441	3	0	1	0	1	0	1	-1.753	3
541		5	max	1545.372	3	1670.283	2	0	1	0	1	0	1	.008	9
542			min	-981.315	2	-1817.414	3	0	1	0	1	0	1	-.795	3
543		6	max	1545.826	3	1668.985	2	0	1	0	1	0	1	.165	3
544			min	-980.71	2	-1818.388	3	0	1	0	1	0	1	-.978	2
545		7	max	1546.28	3	1667.686	2	0	1	0	1	0	1	1.124	3
546			min	-980.105	2	-1819.362	3	0	1	0	1	0	1	-1.859	2
547		8	max	1546.734	3	1666.388	2	0	1	0	1	0	1	2.085	3
548			min	-979.499	2	-1820.335	3	0	1	0	1	0	1	-2.738	2
549		9	max	1567.623	3	162.517	2	0	1	0	1	0	1	2.401	3
550			min	-826.762	2	.392	15	0	1	0	1	0	1	-3.118	2
551		10	max	1568.077	3	161.219	2	0	1	0	1	0	1	2.322	3
552			min	-826.157	2	0	15	0	1	0	1	0	1	-3.203	2
553		11	max	1568.531	3	159.921	2	0	1	0	1	0	1	2.244	3
554			min	-825.552	2	-1.449	4	0	1	0	1	0	1	-3.288	2
555		12	max	1589.607	3	1156.823	3	0	1	0	1	0	1	1.97	3
556			min	-672.87	2	-1995.915	2	0	1	0	1	0	1	-2.942	2
557		13	max	1590.061	3	1155.85	3	0	1	0	1	0	1	1.36	3
558			min	-672.265	2	-1997.214	2	0	1	0	1	0	1	-1.889	2
559		14	max	1590.515	3	1154.876	3	0	1	0	1	0	1	.75	3
560			min	-671.66	2	-1998.512	2	0	1	0	1	0	1	-.834	2
561		15	max	1590.969	3	1153.902	3	0	1	0	1	0	1	.22	2
562			min	-671.054	2	-1999.81	2	0	1	0	1	0	1	-.004	13
563		16	max	1591.423	3	1152.929	3	0	1	0	1	0	1	1.276	2
564			min	-670.449	2	-2001.108	2	0	1	0	1	0	1	-.467	3
565		17	max	1591.877	3	1151.955	3	0	1	0	1	0	1	2.332	2
566			min	-669.843	2	-2002.407	2	0	1	0	1	0	1	-1.076	3
567		18	max	-14.893	12	2237.46	2	0	1	0	1	0	1	1.202	2
568			min	-381.944	1	-1021.381	3	0	1	0	1	0	1	-.563	3
569		19	max	-14.59	12	2236.162	2	0	1	0	1	0	1	.022	1
570			min	-381.339	1	-1022.355	3	0	1	0	1	0	1	-.024	3
571	M9	1	max	176.272	1	786.637	3	107.963	1	0	3	-.011	15	0	3
572			min	7.267	15	-467.535	2	4.483	15	0	1	-.258	1	-.015	2
573		2	max	176.878	1	785.663	3	107.963	1	0	3	-.008	15	.233	1
574			min	7.45	15	-468.833	2	4.483	15	0	1	-.201	1	-.415	3
575		3	max	480.138	3	551.832	2	107.497	1	0	2	-.006	15	.468	1
576			min	-281.409	2	-565.624	3	4.454	15	0	3	-.144	1	-.813	3
577		4	max	480.592	3	550.533	2	107.497	1	0	2	-.004	15	.19	1
578			min	-280.804	2	-566.597	3	4.454	15	0	3	-.087	1	-.514	3
579		5	max	481.046	3	549.235	2	107.497	1	0	2	-.001	15	-.003	15
580			min	-280.199	2	-567.571	3	4.454	15	0	3	-.031	1	-.215	3
581		6	max	481.5	3	547.937	2	107.497	1	0	2	.026	1	.085	3
582			min	-279.593	2	-568.545	3	4.454	15	0	3	.001	15	-.403	2
583		7	max	481.954	3	546.639	2	107.497	1	0	2	.083	1	.385	3
584			min	-278.988	2	-569.518	3	4.454	15	0	3	.003	15	-.691	2
585		8	max	482.408	3	545.341	2	107.497	1	0	2	.14	1	.686	3
586			min	-278.383	2	-570.492	3	4.454	15	0	3	.006	15	-.98	2
587		9	max	495.291	3	48.62	2	157.729	1	0	3	-.003	15	.802	3
588			min	-204.683	2	.395	15	6.538	15	0	9	-.082	1	-1.121	2
589		10	max	495.745	3	47.322	2	157.729	1	0	3	.001	1	.78	3
590			min	-204.078	2	.004	15	6.538	15	0	9	0	15	-1.147	2
591		11	max	496.199	3	46.023	2	157.729	1	0	3	.084	1	.759	3
592			min	-203.473	2	-1.588	4	6.538	15	0	9	.003	15	-1.171	2
593		12	max	508.989	3	364.572	3	105.049	1	0	3	-.006	15	.661	3
594			min	-129.746	2	-645.653	2	4.346	15	0	2	-.138	1	-1.038	2
595		13	max	509.443	3	363.599	3	105.049	1	0	3	-.003	15	.469	3
596			min	-129.14	2	-646.952	2	4.346	15	0	2	-.082	1	-.697	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
597		14	max	509.897	3	362.625	3	105.049	1	0	3	-.001	15	.277	3
598			min	-128.535	2	-648.25	2	4.346	15	0	2	-.027	1	-.355	2
599		15	max	510.351	3	361.651	3	105.049	1	0	3	.029	1	.086	3
600			min	-127.93	2	-649.548	2	4.346	15	0	2	.001	15	-.036	1
601		16	max	510.805	3	360.678	3	105.049	1	0	3	.084	1	.33	2
602			min	-127.324	2	-650.846	2	4.346	15	0	2	.003	15	-.104	3
603		17	max	511.259	3	359.704	3	105.049	1	0	3	.139	1	.674	2
604			min	-126.719	2	-652.145	2	4.346	15	0	2	.006	15	-.294	3
605		18	max	-7.457	15	664.198	2	115.595	1	0	2	.199	1	.339	2
606			min	-177.124	1	-297.763	3	4.794	15	0	3	.008	15	-.145	3
607		19	max	-7.274	15	662.9	2	115.595	1	0	2	.26	1	.012	3
608			min	-176.519	1	-298.737	3	4.794	15	0	3	.011	15	-.011	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M13	1	max	.001	1	.116	2	.008	3	9.575e-3	2	NC	1	NC	1
2			min	0	15	-.017	3	-.004	2	-1.58e-3	3	NC	1	NC	1
3		2	max	0	1	.356	3	.04	1	1.101e-2	2	NC	5	NC	2
4			min	0	15	-.095	1	0	10	-1.611e-3	3	644.069	3	6095.43	1
5		3	max	0	1	.657	3	.097	1	1.245e-2	2	NC	5	NC	3
6			min	0	15	-.253	1	.004	15	-1.641e-3	3	355.858	3	2494.986	1
7		4	max	0	1	.841	3	.146	1	1.389e-2	2	NC	5	NC	3
8			min	0	15	-.342	1	.006	15	-1.672e-3	3	279.787	3	1651.874	1
9		5	max	0	1	.883	3	.171	1	1.532e-2	2	NC	5	NC	3
10			min	0	15	-.347	1	.007	15	-1.703e-3	3	266.514	3	1408.291	1
11		6	max	0	1	.789	3	.165	1	1.676e-2	2	NC	5	NC	3
12			min	0	15	-.273	1	.007	15	-1.733e-3	3	297.871	3	1461.085	1
13		7	max	0	1	.585	3	.129	1	1.82e-2	2	NC	5	NC	3
14			min	0	15	-.136	1	.006	15	-1.764e-3	3	398.735	3	1868.882	1
15		8	max	0	1	.326	3	.074	1	1.963e-2	2	NC	4	NC	2
16			min	0	15	0	15	-.001	10	-1.795e-3	3	699.851	3	3268.93	1
17		9	max	0	1	.206	2	.028	3	2.107e-2	2	NC	4	NC	1
18			min	0	15	.005	15	-.008	10	-1.825e-3	3	2221.795	3	NC	1
19		10	max	0	1	.273	2	.027	3	2.251e-2	2	NC	3	NC	1
20			min	0	1	-.015	3	-.018	2	-1.856e-3	3	1531.034	2	NC	1
21		11	max	0	15	.206	2	.028	3	2.107e-2	2	NC	4	NC	1
22			min	0	1	.005	15	-.008	10	-1.825e-3	3	2221.795	3	NC	1
23		12	max	0	15	.326	3	.074	1	1.963e-2	2	NC	4	NC	2
24			min	0	1	0	15	-.001	10	-1.795e-3	3	699.851	3	3268.93	1
25		13	max	0	15	.585	3	.129	1	1.82e-2	2	NC	5	NC	3
26			min	0	1	-.136	1	.006	15	-1.764e-3	3	398.735	3	1868.882	1
27		14	max	0	15	.789	3	.165	1	1.676e-2	2	NC	5	NC	3
28			min	0	1	-.273	1	.007	15	-1.733e-3	3	297.871	3	1461.085	1
29		15	max	0	15	.883	3	.171	1	1.532e-2	2	NC	5	NC	3
30			min	0	1	-.347	1	.007	15	-1.703e-3	3	266.514	3	1408.291	1
31		16	max	0	15	.841	3	.146	1	1.389e-2	2	NC	5	NC	3
32			min	0	1	-.342	1	.006	15	-1.672e-3	3	279.787	3	1651.874	1
33		17	max	0	15	.657	3	.097	1	1.245e-2	2	NC	5	NC	3
34			min	0	1	-.253	1	.004	15	-1.641e-3	3	355.858	3	2494.986	1
35		18	max	0	15	.356	3	.04	1	1.101e-2	2	NC	5	NC	2
36			min	0	1	-.095	1	0	10	-1.611e-3	3	644.069	3	6095.43	1
37		19	max	0	15	.116	2	.008	3	9.575e-3	2	NC	1	NC	1
38			min	-.001	1	-.017	3	-.004	2	-1.58e-3	3	NC	1	NC	1
39	M14	1	max	0	1	.239	3	.008	3	5.678e-3	2	NC	1	NC	1
40			min	0	15	-.374	2	-.004	2	-4.269e-3	3	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
41		2	max	0	1	.596	3	.028	1	6.807e-3	2	NC	5	NC	2
42			min	0	15	-.706	2	0	10	-5.203e-3	3	671.99	3	8957.589	1
43		3	max	0	1	.898	3	.078	1	7.936e-3	2	NC	5	NC	3
44			min	0	15	-.992	2	.003	15	-6.137e-3	3	364.204	3	3117.282	1
45		4	max	0	1	1.106	3	.125	1	9.066e-3	2	NC	15	NC	3
46			min	0	15	-1.202	2	.005	15	-7.071e-3	3	276.599	3	1931.927	1
47		5	max	0	1	1.203	3	.152	1	1.02e-2	2	NC	15	NC	3
48			min	0	15	-1.319	2	.007	15	-8.006e-3	3	248.8	3	1588.693	1
49		6	max	0	1	1.189	3	.15	1	1.132e-2	2	NC	15	NC	3
50			min	0	15	-1.342	2	.006	15	-8.94e-3	3	247.977	2	1610.826	1
51		7	max	0	1	1.083	3	.12	1	1.245e-2	2	NC	15	NC	3
52			min	0	15	-1.287	2	.005	15	-9.874e-3	3	263.087	2	2026.876	1
53		8	max	0	1	.924	3	.07	1	1.358e-2	2	NC	15	NC	2
54			min	0	15	-1.182	2	-.001	10	-1.081e-2	3	297.213	2	3496.022	1
55		9	max	0	1	.77	3	.025	3	1.471e-2	2	NC	5	NC	1
56			min	0	15	-1.073	2	-.007	10	-1.174e-2	3	343.498	2	NC	1
57		10	max	0	1	.698	3	.024	3	1.584e-2	2	NC	5	NC	1
58			min	0	1	-1.021	2	-.017	2	-1.268e-2	3	371.398	2	NC	1
59		11	max	0	15	.77	3	.025	3	1.471e-2	2	NC	5	NC	1
60			min	0	1	-1.073	2	-.007	10	-1.174e-2	3	343.498	2	NC	1
61		12	max	0	15	.924	3	.07	1	1.358e-2	2	NC	15	NC	2
62			min	0	1	-1.182	2	-.001	10	-1.081e-2	3	297.213	2	3496.022	1
63		13	max	0	15	1.083	3	.12	1	1.245e-2	2	NC	15	NC	3
64			min	0	1	-1.287	2	.005	15	-9.874e-3	3	263.087	2	2026.876	1
65		14	max	0	15	1.189	3	.15	1	1.132e-2	2	NC	15	NC	3
66			min	0	1	-1.342	2	.006	15	-8.94e-3	3	247.977	2	1610.826	1
67		15	max	0	15	1.203	3	.152	1	1.02e-2	2	NC	15	NC	3
68			min	0	1	-1.319	2	.007	15	-8.006e-3	3	248.8	3	1588.693	1
69		16	max	0	15	1.106	3	.125	1	9.066e-3	2	NC	15	NC	3
70			min	0	1	-1.202	2	.005	15	-7.071e-3	3	276.599	3	1931.927	1
71		17	max	0	15	.898	3	.078	1	7.936e-3	2	NC	5	NC	3
72			min	0	1	-.992	2	.003	15	-6.137e-3	3	364.204	3	3117.282	1
73		18	max	0	15	.596	3	.028	1	6.807e-3	2	NC	5	NC	2
74			min	0	1	-.706	2	0	10	-5.203e-3	3	671.99	3	8957.589	1
75		19	max	0	15	.239	3	.008	3	5.678e-3	2	NC	1	NC	1
76			min	0	1	-.374	2	-.004	2	-4.269e-3	3	NC	1	NC	1
77	M15	1	max	0	15	.244	3	.007	3	3.614e-3	3	NC	1	NC	1
78			min	0	1	-.374	2	-.004	2	-5.902e-3	2	NC	1	NC	1
79		2	max	0	15	.465	3	.028	1	4.411e-3	3	NC	5	NC	2
80			min	0	1	-.796	2	0	10	-7.08e-3	2	567.46	2	8913.913	1
81		3	max	0	15	.658	3	.078	1	5.207e-3	3	NC	5	NC	3
82			min	0	1	-1.157	2	.003	15	-8.258e-3	2	306.459	2	3107.989	1
83		4	max	0	15	.8	3	.126	1	6.004e-3	3	NC	15	NC	3
84			min	0	1	-1.411	2	.005	15	-9.437e-3	2	231.306	2	1927.253	1
85		5	max	0	15	.883	3	.153	1	6.8e-3	3	NC	15	NC	3
86			min	0	1	-1.538	2	.007	15	-1.061e-2	2	206.048	2	1585.03	1
87		6	max	0	15	.905	3	.15	1	7.597e-3	3	NC	15	NC	3
88			min	0	1	-1.538	2	.006	15	-1.179e-2	2	206.057	2	1606.748	1
89		7	max	0	15	.875	3	.12	1	8.393e-3	3	NC	15	NC	3
90			min	0	1	-1.432	2	.005	15	-1.297e-2	2	226.637	2	2020.175	1
91		8	max	0	15	.812	3	.07	1	9.19e-3	3	NC	15	NC	2
92			min	0	1	-1.264	2	0	10	-1.415e-2	2	269.504	2	3475.889	1
93		9	max	0	15	.745	3	.023	3	9.986e-3	3	NC	5	NC	1
94			min	0	1	-1.097	2	-.007	10	-1.533e-2	2	331.506	2	NC	1
95		10	max	0	1	.713	3	.022	3	1.078e-2	3	NC	5	NC	1
96			min	0	1	-1.019	2	-.016	2	-1.651e-2	2	371.882	2	NC	1
97		11	max	0	1	.745	3	.023	3	9.986e-3	3	NC	5	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
98			min	0	15	-1.097	2	-.007	10	-1.533e-2	2	331.506	2	NC	1
99		12	max	0	1	.812	3	.07	1	9.19e-3	3	NC	15	NC	2
100			min	0	15	-1.264	2	0	10	-1.415e-2	2	269.504	2	3475.889	1
101		13	max	0	1	.875	3	.12	1	8.393e-3	3	NC	15	NC	3
102			min	0	15	-1.432	2	.005	15	-1.297e-2	2	226.637	2	2020.175	1
103		14	max	0	1	.905	3	.15	1	7.597e-3	3	NC	15	NC	3
104			min	0	15	-1.538	2	.006	15	-1.179e-2	2	206.057	2	1606.748	1
105		15	max	0	1	.883	3	.153	1	6.8e-3	3	NC	15	NC	3
106			min	0	15	-1.538	2	.007	15	-1.061e-2	2	206.048	2	1585.03	1
107		16	max	0	1	.8	3	.126	1	6.004e-3	3	NC	15	NC	3
108			min	0	15	-1.411	2	.005	15	-9.437e-3	2	231.306	2	1927.253	1
109		17	max	0	1	.658	3	.078	1	5.207e-3	3	NC	5	NC	3
110			min	0	15	-1.157	2	.003	15	-8.258e-3	2	306.459	2	3107.989	1
111		18	max	0	1	.465	3	.028	1	4.411e-3	3	NC	5	NC	2
112			min	0	15	-.796	2	0	10	-7.08e-3	2	567.46	2	8913.913	1
113		19	max	0	1	.244	3	.007	3	3.614e-3	3	NC	1	NC	1
114			min	0	15	-.374	2	-.004	2	-5.902e-3	2	NC	1	NC	1
115	M16	1	max	0	15	.104	2	.006	3	6.451e-3	3	NC	1	NC	1
116			min	-.001	1	-.081	3	-.003	2	-8.045e-3	2	NC	1	NC	1
117		2	max	0	15	.041	3	.04	1	7.612e-3	3	NC	5	NC	2
118			min	0	1	-.19	2	.002	10	-9.121e-3	2	815.86	2	6132.8	1
119		3	max	0	15	.136	3	.097	1	8.774e-3	3	NC	5	NC	3
120			min	0	1	-.425	2	.004	15	-1.02e-2	2	453.866	2	2501.215	1
121		4	max	0	15	.186	3	.146	1	9.935e-3	3	NC	5	NC	3
122			min	0	1	-.56	2	.006	15	-1.127e-2	2	361.424	2	1652.505	1
123		5	max	0	15	.184	3	.172	1	1.11e-2	3	NC	5	NC	3
124			min	0	1	-.578	2	.007	15	-1.235e-2	2	352.109	2	1406.182	1
125		6	max	0	15	.13	3	.166	1	1.226e-2	3	NC	5	NC	3
126			min	0	1	-.481	2	.007	15	-1.342e-2	2	410.471	2	1455.438	1
127		7	max	0	15	.037	3	.13	1	1.342e-2	3	NC	5	NC	3
128			min	0	1	-.294	2	.006	15	-1.45e-2	2	602.985	2	1853.971	1
129		8	max	0	15	.008	9	.076	1	1.458e-2	3	NC	3	NC	2
130			min	0	1	-.073	3	0	10	-1.557e-2	2	1430.149	2	3208.378	1
131		9	max	0	15	.154	1	.021	1	1.574e-2	3	NC	4	NC	1
132			min	0	1	-.171	3	-.006	10	-1.665e-2	2	2662.307	3	NC	1
133		10	max	0	1	.235	2	.019	3	1.69e-2	3	NC	4	NC	1
134			min	0	1	-.214	3	-.014	2	-1.772e-2	2	1796.651	3	NC	1
135		11	max	0	1	.154	1	.021	1	1.574e-2	3	NC	4	NC	1
136			min	0	15	-.171	3	-.006	10	-1.665e-2	2	2662.307	3	NC	1
137		12	max	0	1	.008	9	.076	1	1.458e-2	3	NC	3	NC	2
138			min	0	15	-.073	3	0	10	-1.557e-2	2	1430.149	2	3208.378	1
139		13	max	0	1	.037	3	.13	1	1.342e-2	3	NC	5	NC	3
140			min	0	15	-.294	2	.006	15	-1.45e-2	2	602.985	2	1853.971	1
141		14	max	0	1	.13	3	.166	1	1.226e-2	3	NC	5	NC	3
142			min	0	15	-.481	2	.007	15	-1.342e-2	2	410.471	2	1455.438	1
143		15	max	0	1	.184	3	.172	1	1.11e-2	3	NC	5	NC	3
144			min	0	15	-.578	2	.007	15	-1.235e-2	2	352.109	2	1406.182	1
145		16	max	0	1	.186	3	.146	1	9.935e-3	3	NC	5	NC	3
146			min	0	15	-.56	2	.006	15	-1.127e-2	2	361.424	2	1652.505	1
147		17	max	0	1	.136	3	.097	1	8.774e-3	3	NC	5	NC	3
148			min	0	15	-.425	2	.004	15	-1.02e-2	2	453.866	2	2501.215	1
149		18	max	0	1	.041	3	.04	1	7.612e-3	3	NC	5	NC	2
150			min	0	15	-.19	2	.002	10	-9.121e-3	2	815.86	2	6132.8	1
151		19	max	.001	1	.104	2	.006	3	6.451e-3	3	NC	1	NC	1
152			min	0	15	-.081	3	-.003	2	-8.045e-3	2	NC	1	NC	1
153	M2	1	max	.007	2	.007	2	.008	1	-9.517e-6	15	NC	1	NC	2
154			min	-.009	3	-.012	3	0	15	-2.298e-4	1	8911.229	2	7502.077	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
155		2	max	.006	2	.006	2	.008	1	-8.929e-6	15	NC	1	NC	2
156			min	-.008	3	-.011	3	0	15	-2.155e-4	1	NC	1	8183.542	1
157		3	max	.006	2	.005	2	.007	1	-8.342e-6	15	NC	1	NC	2
158			min	-.008	3	-.011	3	0	15	-2.013e-4	1	NC	1	8996	1
159		4	max	.005	2	.004	2	.006	1	-7.754e-6	15	NC	1	NC	2
160			min	-.007	3	-.011	3	0	15	-1.871e-4	1	NC	1	9974.262	1
161		5	max	.005	2	.003	2	.006	1	-7.166e-6	15	NC	1	NC	1
162			min	-.007	3	-.01	3	0	15	-1.729e-4	1	NC	1	NC	1
163		6	max	.005	2	.003	2	.005	1	-6.578e-6	15	NC	1	NC	1
164			min	-.006	3	-.01	3	0	15	-1.587e-4	1	NC	1	NC	1
165		7	max	.004	2	.002	2	.004	1	-5.99e-6	15	NC	1	NC	1
166			min	-.006	3	-.009	3	0	15	-1.445e-4	1	NC	1	NC	1
167		8	max	.004	2	.001	2	.004	1	-5.402e-6	15	NC	1	NC	1
168			min	-.005	3	-.008	3	0	15	-1.303e-4	1	NC	1	NC	1
169		9	max	.004	2	0	2	.003	1	-4.814e-6	15	NC	1	NC	1
170			min	-.005	3	-.008	3	0	15	-1.161e-4	1	NC	1	NC	1
171		10	max	.003	2	0	2	.003	1	-4.227e-6	15	NC	1	NC	1
172			min	-.004	3	-.007	3	0	15	-1.019e-4	1	NC	1	NC	1
173		11	max	.003	2	0	2	.002	1	-3.639e-6	15	NC	1	NC	1
174			min	-.004	3	-.007	3	0	15	-8.772e-5	1	NC	1	NC	1
175		12	max	.003	2	0	2	.002	1	-3.051e-6	15	NC	1	NC	1
176			min	-.003	3	-.006	3	0	15	-7.351e-5	1	NC	1	NC	1
177		13	max	.002	2	0	15	.001	1	-2.463e-6	15	NC	1	NC	1
178			min	-.003	3	-.005	3	0	15	-5.931e-5	1	NC	1	NC	1
179		14	max	.002	2	0	15	0	1	-1.875e-6	15	NC	1	NC	1
180			min	-.002	3	-.005	3	0	15	-4.511e-5	1	NC	1	NC	1
181		15	max	.001	2	0	15	0	1	-1.287e-6	15	NC	1	NC	1
182			min	-.002	3	-.004	3	0	15	-3.09e-5	1	NC	1	NC	1
183		16	max	.001	2	0	15	0	1	-6.995e-7	15	NC	1	NC	1
184			min	-.001	3	-.003	3	0	15	-1.67e-5	1	NC	1	NC	1
185		17	max	0	2	0	15	0	1	-1.117e-7	15	NC	1	NC	1
186			min	0	3	-.002	3	0	15	-2.495e-6	1	NC	1	NC	1
187		18	max	0	2	0	15	0	1	1.171e-5	1	NC	1	NC	1
188			min	0	3	-.001	4	0	15	3.445e-7	12	NC	1	NC	1
189		19	max	0	1	0	1	0	1	2.591e-5	1	NC	1	NC	1
190			min	0	1	0	1	0	1	1.064e-6	15	NC	1	NC	1
191	M3	1	max	0	1	0	1	0	1	-3.537e-7	15	NC	1	NC	1
192			min	0	1	0	1	0	1	-8.603e-6	1	NC	1	NC	1
193		2	max	0	3	0	15	0	1	1.555e-5	1	NC	1	NC	1
194			min	0	2	-.002	4	0	15	6.435e-7	15	NC	1	NC	1
195		3	max	0	3	0	15	0	1	3.97e-5	1	NC	1	NC	1
196			min	0	2	-.004	4	0	15	1.641e-6	15	NC	1	NC	1
197		4	max	.001	3	-.001	15	0	1	6.386e-5	1	NC	1	NC	1
198			min	0	2	-.006	4	0	15	2.638e-6	15	NC	1	NC	1
199		5	max	.002	3	-.002	15	0	1	8.801e-5	1	NC	1	NC	1
200			min	-.001	2	-.007	4	0	15	3.635e-6	15	NC	1	NC	1
201		6	max	.002	3	-.002	15	0	1	1.122e-4	1	NC	1	NC	1
202			min	-.002	2	-.009	4	0	15	4.633e-6	15	NC	1	NC	1
203		7	max	.002	3	-.003	15	.001	1	1.363e-4	1	NC	1	NC	1
204			min	-.002	2	-.011	4	0	15	5.63e-6	15	8606.418	4	NC	1
205		8	max	.003	3	-.003	15	.001	1	1.605e-4	1	NC	1	NC	1
206			min	-.002	2	-.012	4	0	15	6.627e-6	15	7726.846	4	NC	1
207		9	max	.003	3	-.003	15	.002	1	1.846e-4	1	NC	2	NC	1
208			min	-.002	2	-.013	4	0	15	7.625e-6	15	7206.791	4	NC	1
209		10	max	.003	3	-.003	15	.002	1	2.088e-4	1	NC	2	NC	1
210			min	-.003	2	-.013	4	0	15	8.622e-6	15	6955.651	4	NC	1
211		11	max	.004	3	-.003	15	.003	1	2.329e-4	1	NC	2	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
212			min	-.003	2	-.013	4	0	15	9.619e-6	15	6936.43	4	NC	1
213		12	max	.004	3	-.003	15	.003	1	2.571e-4	1	NC	2	NC	1
214			min	-.003	2	-.013	4	0	15	1.062e-5	15	7151.541	4	NC	1
215		13	max	.005	3	-.003	15	.004	1	2.812e-4	1	NC	1	NC	1
216			min	-.004	2	-.012	4	0	15	1.161e-5	15	7645.555	4	NC	1
217		14	max	.005	3	-.003	15	.004	1	3.054e-4	1	NC	1	NC	1
218			min	-.004	2	-.011	4	0	15	1.261e-5	15	8528.309	4	NC	1
219		15	max	.005	3	-.002	15	.005	1	3.295e-4	1	NC	1	NC	1
220			min	-.004	2	-.01	4	0	15	1.361e-5	15	NC	1	NC	1
221		16	max	.006	3	-.002	15	.006	1	3.537e-4	1	NC	1	NC	1
222			min	-.005	2	-.008	4	0	15	1.461e-5	15	NC	1	NC	1
223		17	max	.006	3	-.001	15	.006	1	3.778e-4	1	NC	1	NC	1
224			min	-.005	2	-.006	1	0	15	1.56e-5	15	NC	1	NC	1
225		18	max	.006	3	0	15	.007	1	4.02e-4	1	NC	1	NC	1
226			min	-.005	2	-.004	1	0	15	1.66e-5	15	NC	1	NC	1
227		19	max	.007	3	0	15	.008	1	4.262e-4	1	NC	1	NC	1
228			min	-.005	2	-.003	1	0	15	1.76e-5	15	NC	1	NC	1
229	M4	1	max	.003	1	.005	2	0	15	6.038e-5	1	NC	1	NC	3
230			min	0	3	-.007	3	-.008	1	2.507e-6	15	NC	1	3112.543	1
231		2	max	.003	1	.005	2	0	15	6.038e-5	1	NC	1	NC	3
232			min	0	3	-.007	3	-.007	1	2.507e-6	15	NC	1	3384.073	1
233		3	max	.002	1	.004	2	0	15	6.038e-5	1	NC	1	NC	3
234			min	0	3	-.006	3	-.007	1	2.507e-6	15	NC	1	3707.272	1
235		4	max	.002	1	.004	2	0	15	6.038e-5	1	NC	1	NC	2
236			min	0	3	-.006	3	-.006	1	2.507e-6	15	NC	1	4095.554	1
237		5	max	.002	1	.004	2	0	15	6.038e-5	1	NC	1	NC	2
238			min	0	3	-.005	3	-.005	1	2.507e-6	15	NC	1	4567.151	1
239		6	max	.002	1	.004	2	0	15	6.038e-5	1	NC	1	NC	2
240			min	0	3	-.005	3	-.005	1	2.507e-6	15	NC	1	5147.347	1
241		7	max	.002	1	.003	2	0	15	6.038e-5	1	NC	1	NC	2
242			min	0	3	-.005	3	-.004	1	2.507e-6	15	NC	1	5872.034	1
243		8	max	.002	1	.003	2	0	15	6.038e-5	1	NC	1	NC	2
244			min	0	3	-.004	3	-.004	1	2.507e-6	15	NC	1	6793.554	1
245		9	max	.002	1	.003	2	0	15	6.038e-5	1	NC	1	NC	2
246			min	0	3	-.004	3	-.003	1	2.507e-6	15	NC	1	7990.707	1
247		10	max	.001	1	.003	2	0	15	6.038e-5	1	NC	1	NC	2
248			min	0	3	-.003	3	-.003	1	2.507e-6	15	NC	1	9586.669	1
249		11	max	.001	1	.002	2	0	15	6.038e-5	1	NC	1	NC	1
250			min	0	3	-.003	3	-.002	1	2.507e-6	15	NC	1	NC	1
251		12	max	.001	1	.002	2	0	15	6.038e-5	1	NC	1	NC	1
252			min	0	3	-.003	3	-.002	1	2.507e-6	15	NC	1	NC	1
253		13	max	0	1	.002	2	0	15	6.038e-5	1	NC	1	NC	1
254			min	0	3	-.002	3	-.001	1	2.507e-6	15	NC	1	NC	1
255		14	max	0	1	.001	2	0	15	6.038e-5	1	NC	1	NC	1
256			min	0	3	-.002	3	0	1	2.507e-6	15	NC	1	NC	1
257		15	max	0	1	.001	2	0	15	6.038e-5	1	NC	1	NC	1
258			min	0	3	-.002	3	0	1	2.507e-6	15	NC	1	NC	1
259		16	max	0	1	0	2	0	15	6.038e-5	1	NC	1	NC	1
260			min	0	3	-.001	3	0	1	2.507e-6	15	NC	1	NC	1
261		17	max	0	1	0	2	0	15	6.038e-5	1	NC	1	NC	1
262			min	0	3	0	3	0	1	2.507e-6	15	NC	1	NC	1
263		18	max	0	1	0	2	0	15	6.038e-5	1	NC	1	NC	1
264			min	0	3	0	3	0	1	2.507e-6	15	NC	1	NC	1
265		19	max	0	1	0	1	0	1	6.038e-5	1	NC	1	NC	1
266			min	0	1	0	1	0	1	2.507e-6	15	NC	1	NC	1
267	M6	1	max	.021	2	.027	2	0	1	0	1	NC	4	NC	1
268			min	-.028	3	-.038	3	0	1	0	1	1655.794	3	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
269		2	max	.02	2	.024	2	0	1	0	1	NC	4	NC	1
270			min	-.027	3	-.036	3	0	1	0	1	1756.291	3	NC	1
271		3	max	.019	2	.022	2	0	1	0	1	NC	4	NC	1
272			min	-.025	3	-.034	3	0	1	0	1	1869.756	3	NC	1
273		4	max	.018	2	.02	2	0	1	0	1	NC	4	NC	1
274			min	-.023	3	-.031	3	0	1	0	1	1998.836	3	NC	1
275		5	max	.016	2	.018	2	0	1	0	1	NC	4	NC	1
276			min	-.022	3	-.029	3	0	1	0	1	2146.939	3	NC	1
277		6	max	.015	2	.016	2	0	1	0	1	NC	4	NC	1
278			min	-.02	3	-.027	3	0	1	0	1	2318.52	3	NC	1
279		7	max	.014	2	.014	2	0	1	0	1	NC	1	NC	1
280			min	-.019	3	-.025	3	0	1	0	1	2519.526	3	NC	1
281		8	max	.013	2	.012	2	0	1	0	1	NC	1	NC	1
282			min	-.017	3	-.023	3	0	1	0	1	2758.066	3	NC	1
283		9	max	.012	2	.01	2	0	1	0	1	NC	1	NC	1
284			min	-.016	3	-.021	3	0	1	0	1	3045.499	3	NC	1
285		10	max	.011	2	.008	2	0	1	0	1	NC	1	NC	1
286			min	-.014	3	-.018	3	0	1	0	1	3398.239	3	NC	1
287		11	max	.009	2	.007	2	0	1	0	1	NC	1	NC	1
288			min	-.012	3	-.016	3	0	1	0	1	3840.912	3	NC	1
289		12	max	.008	2	.005	2	0	1	0	1	NC	1	NC	1
290			min	-.011	3	-.014	3	0	1	0	1	4412.229	3	NC	1
291		13	max	.007	2	.004	2	0	1	0	1	NC	1	NC	1
292			min	-.009	3	-.012	3	0	1	0	1	5176.719	3	NC	1
293		14	max	.006	2	.003	2	0	1	0	1	NC	1	NC	1
294			min	-.008	3	-.01	3	0	1	0	1	6250.554	3	NC	1
295		15	max	.005	2	.002	2	0	1	0	1	NC	1	NC	1
296			min	-.006	3	-.008	3	0	1	0	1	7866.103	3	NC	1
297		16	max	.004	2	.001	2	0	1	0	1	NC	1	NC	1
298			min	-.005	3	-.006	3	0	1	0	1	NC	1	NC	1
299		17	max	.002	2	0	2	0	1	0	1	NC	1	NC	1
300			min	-.003	3	-.004	3	0	1	0	1	NC	1	NC	1
301		18	max	.001	2	0	2	0	1	0	1	NC	1	NC	1
302			min	-.002	3	-.002	3	0	1	0	1	NC	1	NC	1
303		19	max	0	1	0	1	0	1	0	1	NC	1	NC	1
304			min	0	1	0	1	0	1	0	1	NC	1	NC	1
305	M7	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
306			min	0	1	0	1	0	1	0	1	NC	1	NC	1
307		2	max	.001	3	0	2	0	1	0	1	NC	1	NC	1
308			min	-.001	2	-.003	3	0	1	0	1	NC	1	NC	1
309		3	max	.002	3	0	2	0	1	0	1	NC	1	NC	1
310			min	-.002	2	-.005	3	0	1	0	1	NC	1	NC	1
311		4	max	.004	3	-.001	15	0	1	0	1	NC	1	NC	1
312			min	-.003	2	-.008	3	0	1	0	1	NC	1	NC	1
313		5	max	.005	3	-.002	15	0	1	0	1	NC	1	NC	1
314			min	-.005	2	-.01	3	0	1	0	1	NC	1	NC	1
315		6	max	.006	3	-.002	15	0	1	0	1	NC	1	NC	1
316			min	-.006	2	-.012	3	0	1	0	1	8748.174	3	NC	1
317		7	max	.007	3	-.003	15	0	1	0	1	NC	1	NC	1
318			min	-.007	2	-.013	3	0	1	0	1	7812.879	3	NC	1
319		8	max	.008	3	-.003	15	0	1	0	1	NC	1	NC	1
320			min	-.008	2	-.014	3	0	1	0	1	7259.297	3	NC	1
321		9	max	.01	3	-.003	15	0	1	0	1	NC	1	NC	1
322			min	-.009	2	-.015	3	0	1	0	1	6973.158	3	NC	1
323		10	max	.011	3	-.003	15	0	1	0	1	NC	1	NC	1
324			min	-.01	2	-.015	3	0	1	0	1	6903.191	3	NC	1
325		11	max	.012	3	-.003	15	0	1	0	1	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
326			min	-.011	2	-.015	3	0	1	0	1	7036.47	3	NC	1
327		12	max	.013	3	-.003	15	0	1	0	1	NC	1	NC	1
328			min	-.013	2	-.015	3	0	1	0	1	7274.835	4	NC	1
329		13	max	.014	3	-.003	15	0	1	0	1	NC	1	NC	1
330			min	-.014	2	-.014	3	0	1	0	1	7771.963	4	NC	1
331		14	max	.015	3	-.003	15	0	1	0	1	NC	1	NC	1
332			min	-.015	2	-.013	3	0	1	0	1	8664.305	4	NC	1
333		15	max	.017	3	-.002	15	0	1	0	1	NC	1	NC	1
334			min	-.016	2	-.012	3	0	1	0	1	NC	1	NC	1
335		16	max	.018	3	-.002	15	0	1	0	1	NC	1	NC	1
336			min	-.017	2	-.01	3	0	1	0	1	NC	1	NC	1
337		17	max	.019	3	-.001	15	0	1	0	1	NC	1	NC	1
338			min	-.018	2	-.009	3	0	1	0	1	NC	1	NC	1
339		18	max	.02	3	0	15	0	1	0	1	NC	1	NC	1
340			min	-.019	2	-.007	3	0	1	0	1	NC	1	NC	1
341		19	max	.021	3	0	15	0	1	0	1	NC	1	NC	1
342			min	-.021	2	-.005	1	0	1	0	1	NC	1	NC	1
343	M8	1	max	.008	1	.019	2	0	1	0	1	NC	1	NC	1
344			min	-.001	3	-.022	3	0	1	0	1	NC	1	NC	1
345		2	max	.007	1	.018	2	0	1	0	1	NC	1	NC	1
346			min	-.001	3	-.021	3	0	1	0	1	NC	1	NC	1
347		3	max	.007	1	.017	2	0	1	0	1	NC	1	NC	1
348			min	-.001	3	-.019	3	0	1	0	1	NC	1	NC	1
349		4	max	.006	1	.016	2	0	1	0	1	NC	1	NC	1
350			min	-.001	3	-.018	3	0	1	0	1	NC	1	NC	1
351		5	max	.006	1	.015	2	0	1	0	1	NC	1	NC	1
352			min	-.001	3	-.017	3	0	1	0	1	NC	1	NC	1
353		6	max	.005	1	.014	2	0	1	0	1	NC	1	NC	1
354			min	0	3	-.016	3	0	1	0	1	NC	1	NC	1
355		7	max	.005	1	.013	2	0	1	0	1	NC	1	NC	1
356			min	0	3	-.015	3	0	1	0	1	NC	1	NC	1
357		8	max	.005	1	.012	2	0	1	0	1	NC	1	NC	1
358			min	0	3	-.013	3	0	1	0	1	NC	1	NC	1
359		9	max	.004	1	.011	2	0	1	0	1	NC	1	NC	1
360			min	0	3	-.012	3	0	1	0	1	NC	1	NC	1
361		10	max	.004	1	.01	2	0	1	0	1	NC	1	NC	1
362			min	0	3	-.011	3	0	1	0	1	NC	1	NC	1
363		11	max	.003	1	.009	2	0	1	0	1	NC	1	NC	1
364			min	0	3	-.01	3	0	1	0	1	NC	1	NC	1
365		12	max	.003	1	.008	2	0	1	0	1	NC	1	NC	1
366			min	0	3	-.009	3	0	1	0	1	NC	1	NC	1
367		13	max	.003	1	.006	2	0	1	0	1	NC	1	NC	1
368			min	0	3	-.007	3	0	1	0	1	NC	1	NC	1
369		14	max	.002	1	.005	2	0	1	0	1	NC	1	NC	1
370			min	0	3	-.006	3	0	1	0	1	NC	1	NC	1
371		15	max	.002	1	.004	2	0	1	0	1	NC	1	NC	1
372			min	0	3	-.005	3	0	1	0	1	NC	1	NC	1
373		16	max	.001	1	.003	2	0	1	0	1	NC	1	NC	1
374			min	0	3	-.004	3	0	1	0	1	NC	1	NC	1
375		17	max	0	1	.002	2	0	1	0	1	NC	1	NC	1
376			min	0	3	-.002	3	0	1	0	1	NC	1	NC	1
377		18	max	0	1	.001	2	0	1	0	1	NC	1	NC	1
378			min	0	3	-.001	3	0	1	0	1	NC	1	NC	1
379		19	max	0	1	0	1	0	1	0	1	NC	1	NC	1
380			min	0	1	0	1	0	1	0	1	NC	1	NC	1
381	M10	1	max	.007	2	.007	2	0	15	2.298e-4	1	NC	1	NC	2
382			min	-.009	3	-.012	3	-.008	1	9.517e-6	15	8911.229	2	7502.077	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
383		2	max	.006	2	.006	2	0	15	2.155e-4	1	NC	1	NC	2
384			min	-.008	3	-.011	3	-.008	1	8.929e-6	15	NC	1	8183.542	1
385		3	max	.006	2	.005	2	0	15	2.013e-4	1	NC	1	NC	2
386			min	-.008	3	-.011	3	-.007	1	8.342e-6	15	NC	1	8996	1
387		4	max	.005	2	.004	2	0	15	1.871e-4	1	NC	1	NC	2
388			min	-.007	3	-.011	3	-.006	1	7.754e-6	15	NC	1	9974.262	1
389		5	max	.005	2	.003	2	0	15	1.729e-4	1	NC	1	NC	1
390			min	-.007	3	-.01	3	-.006	1	7.166e-6	15	NC	1	NC	1
391		6	max	.005	2	.003	2	0	15	1.587e-4	1	NC	1	NC	1
392			min	-.006	3	-.01	3	-.005	1	6.578e-6	15	NC	1	NC	1
393		7	max	.004	2	.002	2	0	15	1.445e-4	1	NC	1	NC	1
394			min	-.006	3	-.009	3	-.004	1	5.99e-6	15	NC	1	NC	1
395		8	max	.004	2	.001	2	0	15	1.303e-4	1	NC	1	NC	1
396			min	-.005	3	-.008	3	-.004	1	5.402e-6	15	NC	1	NC	1
397		9	max	.004	2	0	2	0	15	1.161e-4	1	NC	1	NC	1
398			min	-.005	3	-.008	3	-.003	1	4.814e-6	15	NC	1	NC	1
399		10	max	.003	2	0	2	0	15	1.019e-4	1	NC	1	NC	1
400			min	-.004	3	-.007	3	-.003	1	4.227e-6	15	NC	1	NC	1
401		11	max	.003	2	0	2	0	15	8.772e-5	1	NC	1	NC	1
402			min	-.004	3	-.007	3	-.002	1	3.639e-6	15	NC	1	NC	1
403		12	max	.003	2	0	2	0	15	7.351e-5	1	NC	1	NC	1
404			min	-.003	3	-.006	3	-.002	1	3.051e-6	15	NC	1	NC	1
405		13	max	.002	2	0	15	0	15	5.931e-5	1	NC	1	NC	1
406			min	-.003	3	-.005	3	-.001	1	2.463e-6	15	NC	1	NC	1
407		14	max	.002	2	0	15	0	15	4.511e-5	1	NC	1	NC	1
408			min	-.002	3	-.005	3	0	1	1.875e-6	15	NC	1	NC	1
409		15	max	.001	2	0	15	0	15	3.09e-5	1	NC	1	NC	1
410			min	-.002	3	-.004	3	0	1	1.287e-6	15	NC	1	NC	1
411		16	max	.001	2	0	15	0	15	1.67e-5	1	NC	1	NC	1
412			min	-.001	3	-.003	3	0	1	6.995e-7	15	NC	1	NC	1
413		17	max	0	2	0	15	0	15	2.495e-6	1	NC	1	NC	1
414			min	0	3	-.002	3	0	1	1.117e-7	15	NC	1	NC	1
415		18	max	0	2	0	15	0	15	-3.445e-7	12	NC	1	NC	1
416			min	0	3	-.001	4	0	1	-1.171e-5	1	NC	1	NC	1
417		19	max	0	1	0	1	0	1	-1.064e-6	15	NC	1	NC	1
418			min	0	1	0	1	0	1	-2.591e-5	1	NC	1	NC	1
419	M11	1	max	0	1	0	1	0	1	8.603e-6	1	NC	1	NC	1
420			min	0	1	0	1	0	1	3.537e-7	15	NC	1	NC	1
421		2	max	0	3	0	15	0	15	-6.435e-7	15	NC	1	NC	1
422			min	0	2	-.002	4	0	1	-1.555e-5	1	NC	1	NC	1
423		3	max	0	3	0	15	0	15	-1.641e-6	15	NC	1	NC	1
424			min	0	2	-.004	4	0	1	-3.97e-5	1	NC	1	NC	1
425		4	max	.001	3	-.001	15	0	15	-2.638e-6	15	NC	1	NC	1
426			min	0	2	-.006	4	0	1	-6.386e-5	1	NC	1	NC	1
427		5	max	.002	3	-.002	15	0	15	-3.635e-6	15	NC	1	NC	1
428			min	-.001	2	-.007	4	0	1	-8.801e-5	1	NC	1	NC	1
429		6	max	.002	3	-.002	15	0	15	-4.633e-6	15	NC	1	NC	1
430			min	-.002	2	-.009	4	0	1	-1.122e-4	1	NC	1	NC	1
431		7	max	.002	3	-.003	15	0	15	-5.63e-6	15	NC	1	NC	1
432			min	-.002	2	-.011	4	-.001	1	-1.363e-4	1	8606.418	4	NC	1
433		8	max	.003	3	-.003	15	0	15	-6.627e-6	15	NC	1	NC	1
434			min	-.002	2	-.012	4	-.001	1	-1.605e-4	1	7726.846	4	NC	1
435		9	max	.003	3	-.003	15	0	15	-7.625e-6	15	NC	2	NC	1
436			min	-.002	2	-.013	4	-.002	1	-1.846e-4	1	7206.791	4	NC	1
437		10	max	.003	3	-.003	15	0	15	-8.622e-6	15	NC	2	NC	1
438			min	-.003	2	-.013	4	-.002	1	-2.088e-4	1	6955.651	4	NC	1
439		11	max	.004	3	-.003	15	0	15	-9.619e-6	15	NC	2	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
440			min	-.003	2	-.013	4	-.003	1	-2.329e-4	1	6936.43	4	NC	1
441		12	max	.004	3	-.003	15	0	15	-1.062e-5	15	NC	2	NC	1
442			min	-.003	2	-.013	4	-.003	1	-2.571e-4	1	7151.541	4	NC	1
443		13	max	.005	3	-.003	15	0	15	-1.161e-5	15	NC	1	NC	1
444			min	-.004	2	-.012	4	-.004	1	-2.812e-4	1	7645.555	4	NC	1
445		14	max	.005	3	-.003	15	0	15	-1.261e-5	15	NC	1	NC	1
446			min	-.004	2	-.011	4	-.004	1	-3.054e-4	1	8528.309	4	NC	1
447		15	max	.005	3	-.002	15	0	15	-1.361e-5	15	NC	1	NC	1
448			min	-.004	2	-.01	4	-.005	1	-3.295e-4	1	NC	1	NC	1
449		16	max	.006	3	-.002	15	0	15	-1.461e-5	15	NC	1	NC	1
450			min	-.005	2	-.008	4	-.006	1	-3.537e-4	1	NC	1	NC	1
451		17	max	.006	3	-.001	15	0	15	-1.56e-5	15	NC	1	NC	1
452			min	-.005	2	-.006	1	-.006	1	-3.778e-4	1	NC	1	NC	1
453		18	max	.006	3	0	15	0	15	-1.66e-5	15	NC	1	NC	1
454			min	-.005	2	-.004	1	-.007	1	-4.02e-4	1	NC	1	NC	1
455		19	max	.007	3	0	15	0	15	-1.76e-5	15	NC	1	NC	1
456			min	-.005	2	-.003	1	-.008	1	-4.262e-4	1	NC	1	NC	1
457	M12	1	max	.003	1	.005	2	.008	1	-2.507e-6	15	NC	1	NC	3
458			min	0	3	-.007	3	0	15	-6.038e-5	1	NC	1	3112.543	1
459		2	max	.003	1	.005	2	.007	1	-2.507e-6	15	NC	1	NC	3
460			min	0	3	-.007	3	0	15	-6.038e-5	1	NC	1	3384.073	1
461		3	max	.002	1	.004	2	.007	1	-2.507e-6	15	NC	1	NC	3
462			min	0	3	-.006	3	0	15	-6.038e-5	1	NC	1	3707.272	1
463		4	max	.002	1	.004	2	.006	1	-2.507e-6	15	NC	1	NC	2
464			min	0	3	-.006	3	0	15	-6.038e-5	1	NC	1	4095.554	1
465		5	max	.002	1	.004	2	.005	1	-2.507e-6	15	NC	1	NC	2
466			min	0	3	-.005	3	0	15	-6.038e-5	1	NC	1	4567.151	1
467		6	max	.002	1	.004	2	.005	1	-2.507e-6	15	NC	1	NC	2
468			min	0	3	-.005	3	0	15	-6.038e-5	1	NC	1	5147.347	1
469		7	max	.002	1	.003	2	.004	1	-2.507e-6	15	NC	1	NC	2
470			min	0	3	-.005	3	0	15	-6.038e-5	1	NC	1	5872.034	1
471		8	max	.002	1	.003	2	.004	1	-2.507e-6	15	NC	1	NC	2
472			min	0	3	-.004	3	0	15	-6.038e-5	1	NC	1	6793.554	1
473		9	max	.002	1	.003	2	.003	1	-2.507e-6	15	NC	1	NC	2
474			min	0	3	-.004	3	0	15	-6.038e-5	1	NC	1	7990.707	1
475		10	max	.001	1	.003	2	.003	1	-2.507e-6	15	NC	1	NC	2
476			min	0	3	-.003	3	0	15	-6.038e-5	1	NC	1	9586.669	1
477		11	max	.001	1	.002	2	.002	1	-2.507e-6	15	NC	1	NC	1
478			min	0	3	-.003	3	0	15	-6.038e-5	1	NC	1	NC	1
479		12	max	.001	1	.002	2	.002	1	-2.507e-6	15	NC	1	NC	1
480			min	0	3	-.003	3	0	15	-6.038e-5	1	NC	1	NC	1
481		13	max	0	1	.002	2	.001	1	-2.507e-6	15	NC	1	NC	1
482			min	0	3	-.002	3	0	15	-6.038e-5	1	NC	1	NC	1
483		14	max	0	1	.001	2	0	1	-2.507e-6	15	NC	1	NC	1
484			min	0	3	-.002	3	0	15	-6.038e-5	1	NC	1	NC	1
485		15	max	0	1	.001	2	0	1	-2.507e-6	15	NC	1	NC	1
486			min	0	3	-.002	3	0	15	-6.038e-5	1	NC	1	NC	1
487		16	max	0	1	0	2	0	1	-2.507e-6	15	NC	1	NC	1
488			min	0	3	-.001	3	0	15	-6.038e-5	1	NC	1	NC	1
489		17	max	0	1	0	2	0	1	-2.507e-6	15	NC	1	NC	1
490			min	0	3	0	3	0	15	-6.038e-5	1	NC	1	NC	1
491		18	max	0	1	0	2	0	1	-2.507e-6	15	NC	1	NC	1
492			min	0	3	0	3	0	15	-6.038e-5	1	NC	1	NC	1
493		19	max	0	1	0	1	0	1	-2.507e-6	15	NC	1	NC	1
494			min	0	1	0	1	0	1	-6.038e-5	1	NC	1	NC	1
495	M1	1	max	.008	3	.116	2	.001	1	1.565e-2	1	NC	1	NC	1
496			min	-.004	2	-.017	3	0	15	-2.899e-2	3	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
497		2	max	.008	3	.055	2	0	15	7.611e-3	2	NC	4	NC	1
498			min	-.004	2	-.006	3	-.006	1	-1.434e-2	3	1893.5	2	NC	1
499		3	max	.008	3	.013	3	0	15	2.928e-5	10	NC	5	NC	1
500			min	-.004	2	-.01	2	-.008	1	-1.583e-4	1	911.425	2	NC	1
501		4	max	.008	3	.047	3	0	15	4.733e-3	2	NC	5	NC	1
502			min	-.004	2	-.084	2	-.008	1	-5.225e-3	3	574.313	2	NC	1
503		5	max	.008	3	.091	3	0	15	9.461e-3	2	NC	5	NC	1
504			min	-.004	2	-.162	2	-.005	1	-1.031e-2	3	413.86	2	NC	1
505		6	max	.008	3	.14	3	0	15	1.419e-2	2	NC	15	NC	1
506			min	-.004	2	-.237	2	-.002	1	-1.54e-2	3	325.572	2	NC	1
507		7	max	.008	3	.187	3	0	1	1.892e-2	2	NC	15	NC	1
508			min	-.004	2	-.305	2	0	12	-2.048e-2	3	273.509	2	NC	1
509		8	max	.008	3	.226	3	0	1	2.365e-2	2	9177.069	15	NC	1
510			min	-.004	2	-.358	2	0	15	-2.557e-2	3	242.737	2	NC	1
511		9	max	.008	3	.252	3	0	15	2.687e-2	2	8576.816	15	NC	1
512			min	-.004	2	-.392	2	0	1	-2.561e-2	3	226.728	2	NC	1
513		10	max	.007	3	.261	3	0	1	2.908e-2	2	8393.974	15	NC	1
514			min	-.004	2	-.403	2	0	12	-2.232e-2	3	222.026	2	NC	1
515		11	max	.007	3	.255	3	0	1	3.13e-2	2	8576.53	15	NC	1
516			min	-.004	2	-.392	2	0	15	-1.902e-2	3	227.458	2	NC	1
517		12	max	.007	3	.233	3	0	15	3.025e-2	2	9176.467	15	NC	1
518			min	-.004	2	-.357	2	-.001	1	-1.578e-2	3	244.964	2	NC	1
519		13	max	.007	3	.199	3	0	15	2.426e-2	2	NC	15	NC	1
520			min	-.004	2	-.301	2	0	1	-1.263e-2	3	278.945	2	NC	1
521		14	max	.007	3	.155	3	.002	1	1.827e-2	2	NC	15	NC	1
522			min	-.004	2	-.231	2	0	15	-9.484e-3	3	337.21	2	NC	1
523		15	max	.007	3	.105	3	.005	1	1.229e-2	2	NC	5	NC	1
524			min	-.004	2	-.154	2	0	15	-6.336e-3	3	437.857	2	NC	1
525		16	max	.006	3	.054	3	.007	1	6.299e-3	2	NC	5	NC	1
526			min	-.004	2	-.076	2	0	15	-3.187e-3	3	625.017	2	NC	1
527		17	max	.006	3	.004	3	.008	1	5.603e-4	1	NC	5	NC	1
528			min	-.004	2	-.006	2	0	15	-3.768e-5	3	1026.69	2	NC	1
529		18	max	.006	3	.052	2	.006	1	1.143e-2	2	NC	4	NC	1
530			min	-.004	2	-.04	3	0	15	-4.687e-3	3	2187.499	2	NC	1
531		19	max	.006	3	.104	2	0	15	2.294e-2	2	NC	1	NC	1
532			min	-.003	2	-.081	3	-.001	1	-9.518e-3	3	NC	1	NC	1
533	M5	1	max	.027	3	.273	2	0	1	0	1	NC	1	NC	1
534			min	-.018	2	-.015	3	0	1	0	1	NC	1	NC	1
535		2	max	.027	3	.129	2	0	1	0	1	NC	5	NC	1
536			min	-.018	2	-.001	3	0	1	0	1	802.338	2	NC	1
537		3	max	.027	3	.041	3	0	1	0	1	NC	5	NC	1
538			min	-.018	2	-.033	2	0	1	0	1	378.012	2	NC	1
539		4	max	.026	3	.133	3	0	1	0	1	9975.764	15	NC	1
540			min	-.018	2	-.225	2	0	1	0	1	231.791	2	NC	1
541		5	max	.026	3	.261	3	0	1	0	1	6981.383	15	NC	1
542			min	-.018	2	-.433	2	0	1	0	1	163.382	2	NC	1
543		6	max	.025	3	.404	3	0	1	0	1	5375.232	15	NC	1
544			min	-.017	2	-.639	2	0	1	0	1	126.422	2	NC	1
545		7	max	.025	3	.544	3	0	1	0	1	4447.635	15	NC	1
546			min	-.017	2	-.826	2	0	1	0	1	104.955	2	NC	1
547		8	max	.024	3	.662	3	0	1	0	1	3908.267	15	NC	1
548			min	-.017	2	-.975	2	0	1	0	1	92.421	2	NC	1
549		9	max	.023	3	.737	3	0	1	0	1	3631.66	15	NC	1
550			min	-.016	2	-1.07	2	0	1	0	1	85.974	2	NC	1
551		10	max	.023	3	.765	3	0	1	0	1	3548.326	15	NC	1
552			min	-.016	2	-1.102	2	0	1	0	1	84.085	2	NC	1
553		11	max	.022	3	.746	3	0	1	0	1	3631.764	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
554			min	-.016	2	-1.07	2	0	1	0	1	86.261	2	NC	1
555		12	max	.022	3	.681	3	0	1	0	1	3908.512	15	NC	1
556			min	-.016	2	-.971	2	0	1	0	1	93.358	2	NC	1
557		13	max	.021	3	.578	3	0	1	0	1	4448.138	15	NC	1
558			min	-.015	2	-.814	2	0	1	0	1	107.379	2	NC	1
559		14	max	.021	3	.447	3	0	1	0	1	5376.22	15	NC	1
560			min	-.015	2	-.619	2	0	1	0	1	131.872	2	NC	1
561		15	max	.02	3	.301	3	0	1	0	1	6983.344	15	NC	1
562			min	-.015	2	-.407	2	0	1	0	1	175.218	2	NC	1
563		16	max	.02	3	.153	3	0	1	0	1	9979.876	15	NC	1
564			min	-.015	2	-.2	2	0	1	0	1	258.409	2	NC	1
565		17	max	.019	3	.013	3	0	1	0	1	NC	5	NC	1
566			min	-.014	2	-.018	2	0	1	0	1	443.212	2	NC	1
567		18	max	.019	3	.12	2	0	1	0	1	NC	5	NC	1
568			min	-.014	2	-.106	3	0	1	0	1	978.161	2	NC	1
569		19	max	.019	3	.235	2	0	1	0	1	NC	1	NC	1
570			min	-.014	2	-.214	3	0	1	0	1	NC	1	NC	1
571	M9	1	max	.008	3	.116	2	0	15	2.899e-2	3	NC	1	NC	1
572			min	-.004	2	-.017	3	-.001	1	-1.565e-2	1	NC	1	NC	1
573		2	max	.008	3	.055	2	.006	1	1.434e-2	3	NC	4	NC	1
574			min	-.004	2	-.006	3	0	15	-7.611e-3	2	1893.5	2	NC	1
575		3	max	.008	3	.013	3	.008	1	1.583e-4	1	NC	5	NC	1
576			min	-.004	2	-.01	2	0	15	-2.928e-5	10	911.425	2	NC	1
577		4	max	.008	3	.047	3	.008	1	5.225e-3	3	NC	5	NC	1
578			min	-.004	2	-.084	2	0	15	-4.733e-3	2	574.313	2	NC	1
579		5	max	.008	3	.091	3	.005	1	1.031e-2	3	NC	5	NC	1
580			min	-.004	2	-.162	2	0	15	-9.461e-3	2	413.86	2	NC	1
581		6	max	.008	3	.14	3	.002	1	1.54e-2	3	NC	15	NC	1
582			min	-.004	2	-.237	2	0	15	-1.419e-2	2	325.572	2	NC	1
583		7	max	.008	3	.187	3	0	12	2.048e-2	3	NC	15	NC	1
584			min	-.004	2	-.305	2	0	1	-1.892e-2	2	273.509	2	NC	1
585		8	max	.008	3	.226	3	0	15	2.557e-2	3	9177.069	15	NC	1
586			min	-.004	2	-.358	2	0	1	-2.365e-2	2	242.737	2	NC	1
587		9	max	.008	3	.252	3	0	1	2.561e-2	3	8576.816	15	NC	1
588			min	-.004	2	-.392	2	0	15	-2.687e-2	2	226.728	2	NC	1
589		10	max	.007	3	.261	3	0	12	2.232e-2	3	8393.974	15	NC	1
590			min	-.004	2	-.403	2	0	1	-2.908e-2	2	222.026	2	NC	1
591		11	max	.007	3	.255	3	0	15	1.902e-2	3	8576.53	15	NC	1
592			min	-.004	2	-.392	2	0	1	-3.13e-2	2	227.458	2	NC	1
593		12	max	.007	3	.233	3	.001	1	1.578e-2	3	9176.467	15	NC	1
594			min	-.004	2	-.357	2	0	15	-3.025e-2	2	244.964	2	NC	1
595		13	max	.007	3	.199	3	0	1	1.263e-2	3	NC	15	NC	1
596			min	-.004	2	-.301	2	0	15	-2.426e-2	2	278.945	2	NC	1
597		14	max	.007	3	.155	3	0	15	9.484e-3	3	NC	15	NC	1
598			min	-.004	2	-.231	2	-.002	1	-1.827e-2	2	337.21	2	NC	1
599		15	max	.007	3	.105	3	0	15	6.336e-3	3	NC	5	NC	1
600			min	-.004	2	-.154	2	-.005	1	-1.229e-2	2	437.857	2	NC	1
601		16	max	.006	3	.054	3	0	15	3.187e-3	3	NC	5	NC	1
602			min	-.004	2	-.076	2	-.007	1	-6.299e-3	2	625.017	2	NC	1
603		17	max	.006	3	.004	3	0	15	3.768e-5	3	NC	5	NC	1
604			min	-.004	2	-.006	2	-.008	1	-5.603e-4	1	1026.69	2	NC	1
605		18	max	.006	3	.052	2	0	15	4.687e-3	3	NC	4	NC	1
606			min	-.004	2	-.04	3	-.006	1	-1.143e-2	2	2187.499	2	NC	1
607		19	max	.006	3	.104	2	.001	1	9.518e-3	3	NC	1	NC	1
608			min	-.003	2	-.081	3	0	15	-2.294e-2	2	NC	1	NC	1

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 4.00 x 0.28

<Figure 1>



<Figure 2>

Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	1723.0	23.0	593.0	593.4
Sum	1723.0	23.0	593.0	593.4

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 1723
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	5.247	10215

$\phi N_{cb} = \phi \, (A_{Nc} / A_{Nco}) \, \Psi_{ed,N} \, \Psi_{c,N} \, \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-4)

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cb} (lb)
220.36	247.75	0.967	1.00	1.000	10215	0.65	5710

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_a = \phi \, (A_{Na} / A_{Na0}) \, \Psi_{ed,Na} \, \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16a)

A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	ϕ	ϕN_a (lb)
109.66	109.66	1.000	1.000	9755	0.55	5365

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in y-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cby} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cby} (lb)
192.89	220.50	0.925	1.000	1.000	6947	0.70	3934

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cbx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbx} (lb)
165.27	278.72	0.878	1.000	1.000	8282	0.70	3018

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
192.89	220.50	1.000	1.000	1.000	6947	0.70	8508

Shear parallel to edge in y-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cby} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cby} (lb)
165.27	278.72	1.000	1.000	1.000	8282	0.70	6875

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cp} = \phi \min|k_{cp}N_a\,;\,k_{cp}N_{cb}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\,\Psi_{p,Na}N_{a0}\,;\,k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ed,N}\,\Psi_{c,N}\,\Psi_{cp,N}N_b|$ (Eq. D-30a)

k_{cp}	A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	109.66	109.66	1.000	1.000	9755	9755

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ	ϕV_{cp} (lb)
220.36	247.75	0.967	1.000	1.000	10215	8785	0.70	12298

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, ϕN_n (lb)	Ratio	Status
Steel	1723	6071	0.28	Pass
Concrete breakout	1723	5710	0.30	Pass
Adhesive	**1723**	**5365**	**0.32**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, ϕV_n (lb)	Ratio	Status
Steel	**593**	**3156**	**0.19**	**Pass (Governs)**
T Concrete breakout y+	593	3934	0.15	Pass
T Concrete breakout x+	23	3018	0.01	Pass
|| Concrete breakout y+	23	8508	0.00	Pass
|| Concrete breakout x+	593	6875	0.09	Pass
Concrete breakout, combined	-	-	0.15	Pass
Pryout	593	12298	0.05	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status
Sec. D.7.1	0.32	0.00	32.1 %	1.0	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

<Figure 1>

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 7.00 x 0.28



<Figure 2>



Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	2700.0	1671.0	0.0	1671.0
2	2700.0	1671.0	0.0	1671.0
Sum	5400.0	3342.0	0.0	3342.0

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 5400
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	6.000	12492

$\phi N_{cbg} = \phi (A_{Nc} / A_{Nco}) \Psi_{ec,N} \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-5)

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cbg} (lb)
408.24	324.00	1.000	1.000	1.00	1.000	12492	0.65	10231

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_{ag} = \phi (A_{Na} / A_{Na0}) \Psi_{ed,Na} \Psi_{g,Na} \Psi_{ec,Na} \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16b)

A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0}(lb)	ϕ	ϕN_{ag} (lb)
158.66	109.66	1.000	1.043	1.000	1.000	9755	0.55	8093

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	12.00	15593

$\phi V_{cbgx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ec,V}\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-22)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ec,V}$	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbgx} (lb)
612.00	648.00	1.000	0.944	1.000	1.000	15593	0.70	9735

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	14.66	21056

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
791.64	967.12	1.000	1.000	1.000	21056	0.70	24129

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cpg} = \phi \min|k_{cp}N_{ag}\,;\, k_{cp}N_{cbg}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\,\Psi_{g,Na}\,\Psi_{ec,Na}\,\Psi_{p,Na}N_{a0}\,;\, k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ec,N}\,\Psi_{ed,N}\,\Psi_{c,N}\,\Psi_{cp,N}N_b|$ (Eq. D-30b)

k_{cp}	A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	158.66	109.66	1.000	1.043	1.000	1.000	9755	14715

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ
408.24	324.00	1.000	1.000	1.000	1.000	12492	15740	0.70

ϕV_{cpg} (lb)
20601

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, øN_n (lb)	Ratio	Status
Steel	2700	6071	0.44	Pass
Concrete breakout	5400	10231	0.53	Pass
Adhesive	**5400**	**8093**	**0.67**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, øV_n (lb)	Ratio	Status
Steel	**1671**	**3156**	**0.53**	**Pass (Governs)**
T Concrete breakout x+	3342	9735	0.34	Pass
|| Concrete breakout y-	1671	24129	0.07	Pass
Pryout	3342	20601	0.16	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status

Sec. D.7.3	0.67	0.53	119.7 %	1.2	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.