

Schletter, Inc.		35° Tilt w/o Seismic Design
HCV	Standard FS Racking System	
	Representative Calculations - ASCE 7-10	

1. INTRODUCTION

1.1 Project Description

The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. FS ground mount system.

1.2 Construction

Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to galvanized steel posts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

	Maximum		Minimum
Height =	1700 mm	Height =	1550 mm
Width =	1050 mm	Width =	970 mm
Dead Load =	3.00 psf	Dead Load =	1.75 psf

Modules Per Row =	2
Module Tilt =	35°
Maximum Height Above Grade =	3 ft



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

1.3 Technical Codes

- ASCE 7-10 - Chapter 26-31, Wind Loads
- ASCE 7-10 - Chapter 7, Snow Loads
- ASCE 7-10 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2012, 2015
- Aluminum Design Manual, Eighth Edition, 2005

2. LOAD ACTIONS

2.1 Permanent Loads

g_{MAX} =	3.00 psf	*Self-weight of the PV modules.*
g_{MIN} =	1.75 psf	

2.2 Snow Loads

Ground Snow Load, P_g =	30.00 psf	
Sloped Roof Snow Load, P_s =	14.43 psf	*(ASCE 7-10, Eq. 7.4-1)*
I_s =	1.00	
C_s =	0.64	
C_e =	0.90	
C_t =	1.20	

2.3 Wind Loads

Design Wind Speed, V =	110 mph	Exposure Category = C	
Height <	15 ft	Importance Category = II	
Peak Velocity Pressure, q_z =	19.00 psf	*Including the gust factor, G=0.85. (ASCE 7-10, Eq. 27.3-1)*	

Pressure Coefficients

$Cf+_{TOP}$ =	1.2	*(Pressure)*	*Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0510-e. Negative forces are applied away from the surface.*
$Cf+_{BOTTOM}$ =	2		
$Cf-_{TOP}$ =	-2.4	*(Suction)*	
$Cf-_{BOTTOM}$ =	-1.2		

2.4 Seismic Loads - N/A

S_S =	0.00	R =	1.25	*ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.*
S_{DS} =	0.00	C_S =	0	
S_1 =	0.00	ρ =	1.3	
S_{D1} =	0.00	Ω =	1.25	
T_a =	0.00	C_d =	1.25	

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.5W		
1.2D + 1.0W + 0.5S		
0.9D + 1.0W	M	
1.54D + 1.3E + 0.2S	R	*(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)*
0.56D + 1.3E	R	
1.54D + 1.25E + 0.2S	O	
0.56D + 1.25E	O	

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S		
1.0D + 0.6W		
1.0D + 0.75L + 0.45W + 0.75S		
0.6D + 0.6W	M	*(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)*
1.238D + 0.875E	O	
1.1785D + 0.65625E + 0.75S	O	
0.362D + 0.875E	O	

M *Uses the minimum allowable module dead load.*

R *Include redundancy factor of 1.3.*

O *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location
M10	Top
M11	Mid-Top
M12	Mid-Bottom
M13	Bottom

Posts	Location
M2	Outer
M5	Inner
M8	Outer

Girders	Location
M1	Outer
M4	Inner
M7	Outer

Reactions	Location
N9	Outer
N19	Inner
N29	Outer

Struts	Location
M3	Outer
M6	Inner
M9	Outer

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type =	**S1.5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	144	in
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	25.07	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	23.08	ksi
S_y =	1.33	in^3
S_x =	0.6	in^3
E =	10100	ksi
I_y =	2.16	in^4
I_x =	1.07	in^4
A =	1.25	in^2
g =	1.50	lbs/ft
M_y =	1.782	k-ft
M_z =	0.414	k-ft
$M_{y\ allowable}$ =	2.779	k-ft
$M_{z\ allowable}$ =	1.154	k-ft
Utilization =	100%	



DETAIL VIEW

4.2 Girder Design

Loads from purlins are transferred to the posts using an inclined girder, which is connected to the steel post. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type =	**T5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	63.82	in
$\Phi F_{ty\ AXIAL}$ =	30.80	ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	30.46	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	31.56	ksi
S_y =	1.98	in^3
S_x =	1.32	in^3
E =	10100	ksi
I_y =	4.74	in^4
I_x =	1.83	in^4
A =	1.93	in^2
g =	2.32	lbs/ft
M_y =	3.774	k-ft
M_z =	0.000	k-ft
P_n =	0.019	k
$M_{y\ allowable}$ =	5.026	k-ft
$M_{z\ allowable}$ =	3.472	k-ft
$P_{n\ allowable}$ =	59.439	k
Utilization =	75%	



DETAIL VIEW

4.3 Strut Design

The aluminum strut connects a portion of the girder to the galvanized steel post. Girder forces are then transferred down through the strut into the post. The strut is attached with single M10 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	61.00	in
$\Phi F_{ty\ AXIAL}$ =	13.67	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.000	k-ft
M_z =	0.460	k-ft
P_n =	3.803	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	13.425	k
Utilization =	61%	



4.4 Post Design

Galvanized steel posts are a roll formed steel section, that are either ram driven into the ground or placed in a concrete foundation at a defined depth. Embedment depths will be provided on the structural drawings or through a geotechnical testing report. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Post Type =	**FG8**	
Steel Type =	J2340	
F_{ty} =	60	ksi
L_b =	85.68	in
Φ =	0.90	
ΦF_{ty} =	54.00	ksi
S_y =	3.46	in^3
S_x =	1.55	in^3
E =	29000	ksi
I_y =	10.94	in^4
I_x =	4.31	in^4
A =	2.23	in^2
g =	7.59	lbs/ft
M_y =	16.800	k-ft
M_z =	0.000	k-ft
P_r =	-4.146	k
$M_{y\ allowable}$ =	19.207	k-ft
$M_{z\ allowable}$ =	14.389	k-ft
P_c =	28.060	k
Utilization =	99%	



5. FOUNDATION DESIGN CALCULATIONS

5.1 Rammed Post Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete footing design.

Maximum Tensile Load =	5.36	k
Maximum Lateral Load =	3.88	k

5.2 Design of Drilled Shaft Foundations

The galvanized steel post is to be embedded into a cylindrical drilled shaft foundation. For the purpose of design, the post is considered to be fixed to the ground. The applicable lateral force, uplift, and compression resistance checks are seen below.

5.3 Lateral Force Resistance

The equivalent lateral force is applied at the top of the post to determine the required embedment depth. A lateral soil bearing capacity for clay is assumed. Footing is unrestrained at ground level. (IBC, Eq. 18-1)

Lateral Force @ Top of Pole, P =	1.06	k
Height of Pole Above Grade, H =	7.14	ft
Diameter of Pole Footing, B =	2.00	ft
Lateral Soil Bearing Capacity, S =	0.10	ksf/ft
Isolated Pole Factor, F =	2	
First Trial Depth, D =	3.25	ft
Lateral Bearing @ Bottom =	S_3	
Lateral Bearing @ D/3 =	S_1	
Required Depth =	D	

$$S_3 = Min\ (D, 12')$$

$$S_1 = Min\left(\frac{D}{3}, 12'\right)$$

$$A = 2.34\ P/S_1 B$$

$$D = \left\{0.5A\left(1+\sqrt{1+\left(\frac{4.36\ H}{A}\right)}\right)\right\}$$



Non-Constrained

Lateral Force @ Top of Pole, P =	1.06	k
Height of Pole Above Grade, H =	7.14	ft
Diameter of Pole Footing, B =	2.00	ft
Lateral Soil Bearing Capacity, S =	0.20	ksf/ft

1st Trial @ D_1 =	3.25	ft	
Lateral Soil Bearing @ D/3, S_1 =	0.22	ksf	
Lateral Soil Bearing @ D, S_3 =	0.65	ksf	
Constant 2.34P/(S_1B), A =	5.74		
Required Footing Depth, D =	10.14	ft	
2nd Trial @ D_2 =	6.69	ft	
Lateral Soil Bearing @ D/3, S_1 =	0.45	ksf	
Lateral Soil Bearing @ D, S_3 =	1.34	ksf	
Constant 2.34P/(S_1B), A =	2.78		
Required Footing Depth, D =	6.25	ft	
3rd Trial @ D_3 =	6.47	ft	
Lateral Soil Bearing @ D/3, S_1 =	0.43	ksf	
Lateral Soil Bearing @ D, S_3 =	1.29	ksf	
Constant 2.34P/(S_1B), A =	2.88		
Required Footing Depth, D =	6.39	ft	
4th Trial @ D_4 =	6.43	ft	
Lateral Soil Bearing @ D/3, S_1 =	0.43	ksf	
Lateral Soil Bearing @ D, S_3 =	1.29	ksf	
Constant 2.34P/(S_1B), A =	2.90		
Required Footing Depth, D =	6.42	ft	
5th Trial @ D_5 =	6.42	ft	
Lateral Soil Bearing @ D/3, S_1 =	0.43	ksf	
Lateral Soil Bearing @ D, S_3 =	1.28	ksf	
Constant 2.34P/(S_1B), A =	2.90		
Required Footing Depth, D =	6.50	ft	

A 2ft diameter x 6.5ft deep footing unrestrained at ground level is required for the racking structure.

5.4 Uplifting Force Resistance

Uplifting forces of the racking system are checked against the uplift resistance of the soil. Clay soils are assumed.

Weight of Concrete, g_{con} =	145	pcf
Uplifting Force, N =	2.45	k
Footing Diameter, B =	2.00	ft
Factor of Safety =	2.50	
Cohesion =	208.85	psf
γ_s =	120.43	pcf
α =	0.45	
Required Concrete Weight, g =	1.60	k
Required Concrete Volume, V =	11.02	ft^3
Required Footing Depth, D =	3.75	ft

A 2ft diameter x 3.75ft deep footing unrestrained at ground level is required for the racking structure.



Iteration	z	dz	Qs	Side
1	0.2	0.2	118.10	5.27
2	0.4	0.2	118.10	5.17
3	0.6	0.2	118.10	5.06
4	0.8	0.2	118.10	4.96
5	1	0.2	118.10	4.86
6	1.2	0.2	118.10	4.75
7	1.4	0.2	118.10	4.65
8	1.6	0.2	118.10	4.54
9	1.8	0.2	118.10	4.44
10	2	0.2	118.10	4.34
11	2.2	0.2	118.10	4.23
12	2.4	0.2	118.10	4.13
13	2.6	0.2	118.10	4.03
14	2.8	0.2	118.10	3.92
15	3	0.2	118.10	3.82
16	3.2	0.2	118.10	3.71
17	3.4	0.2	118.10	3.61
18	3.6	0.2	118.10	3.51
19	0	0.0	0.00	3.51
20	0	0.0	0.00	3.51
21	0	0.0	0.00	3.51
22	0	0.0	0.00	3.51
23	0	0.0	0.00	3.51
24	0	0.0	0.00	3.51
25	0	0.0	0.00	3.51
26	0	0.0	0.00	3.51
27	0	0.0	0.00	3.51
28	0	0.0	0.00	3.51
29	0	0.0	0.00	3.51
30	0	0.0	0.00	3.51
31	0	0.0	0.00	3.51
32	0	0.0	0.00	3.51
33	0	0.0	0.00	3.51
34	0	0.0	0.00	3.51
Max	3.6	Sum	0.85	

5.5 Compressive Force Resistance

Skin friction of the soil is checked against the compression force from the racking and the weight of the drilled shaft foundation. Skin friction starts at 3ft below grade. Clay soils are again assumed.

Depth Below Grade, D =	6.50	ft
Footing Diameter, B =	2.00	ft
Compressive Force, P =	3.75	k
Footing Area =	3.14	ft^2
Circumference =	6.28	ft
Skin Friction Area =	21.99	ft^2
Concrete Weight =	0.145	kcf

Bearing Pressure

Bearing Area =	3.14	ft^2
Bearing Capacity =	1.5	ksf
Resistance =	4.71	k

Weight of Concrete

Footing Volume	20.42	ft^3
Weight	2.96	k

Skin Friction Resistance

Skin Friction =	0.15	ksf
Resistance =	3.30	k
1/3 Increase for Wind =	1.33	
Total Resistance =	10.68	k
Applied Force =	6.71	k
Utilization =	63%	

A 2ft diameter footing passes at a depth of 6.5ft.



6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of 40mm mounting clamps. The reliability of calculations is uncertain due to limited standards, therefore the strength of the clamp fasteners has been evaluated by load testing.

Fastening of Modules to Purlins

Maximum Uplifting Force	=	0.423 k
Allowable Uplift	=	1.214 k
Utilization	=	35%



Fastening of Purlins to Girders

Maximum Uplifting Force	=	1.799 k
Allowable Uplift	=	2.180 k
Utilization	=	83%



6.2 Strut Connections

The aluminum struts connect the front end of girder to a center section of the steel post. Single M10 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Maximum Axial Load	=	3.803 k
M10 Bolt Shear Capacity	=	8.894 k
Utilization	=	43%

Bolt capacity is accounting for double shear. (ASCE 8-02, Eq. 5.3.4-1)



A strut under compression is shown to demonstrate the load transfer from the girder. Single M10 bolts are located at each end of the strut and are subjected to double shear.

6.3 Girder to Post Connection

In order to connect the girder to the post, custom extruded sections are assembled to create a post head piece. The reliability of calculations is uncertain due to limited standards, therefore the strength of the head piece has been evaluated by load testing.

Maximum Tensile Load	=	3.830 k
Allowable Load	=	5.649 k
Utilization	=	68%



FRONT VIEW



SIDE VIEW



7. SEISMIC DESIGN

7.1 Seismic Drift - N/A

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx}	=	77.78 in
Allowable Story Drift for All Other Structures, Δ	= {	$0.020h_{sx}$
		1.556 in
Max Drift, Δ_{MAX}	=	0 in
N/A		

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **S1.5**

Strong Axis:		Weak Axis:	
3.4.14		**3.4.14**	
L_b =	144 in	L_b =	144
J =	0.432	J =	0.432
	398.372		253.34
$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$		$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$	
S1 =	0.51461	S1 =	0.51461
$S2 = \left(\frac{C_c}{1.6}\right)^2$		$S2 = \left(\frac{C_c}{1.6}\right)^2$	
S2 =	1701.56	S2 =	1701.56
φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]	φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L=	26.8 ksi	φF_L=	28.2
3.4.16		**3.4.16**	
b/t =	32.195	b/t =	37.0588
$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$		$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$	
S1 =	12.2	S1 =	12.2
$S2 = \frac{k_1 Bp}{1.6Dp}$		$S2 = \frac{k_1 Bp}{1.6Dp}$	
S2 =	46.7	S2 =	46.7
φF_L=	φb[Bp-1.6Dp*b/t]	φF_L=	φb[Bp-1.6Dp*b/t]
φF_L=	25.1 ksi	φF_L=	23.1 ksi
3.4.16.1	Not Used	**3.4.16.1**	
Rb/t =		N/A for Weak Direction	
$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$			
S1 =	1.1		
$S2 = C_t$			
S2 =	141.0		
φF_L=	1.17φyFcy		
φF_L=	38.9 ksi		
3.4.18		**3.4.18**	
h/t =	37.0588	h/t =	32.195
$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$		$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$	
S1 =	36.9	S1 =	36.9
m =	0.65	m =	0.65
C_0 =	40.985	C_0 =	45.5
Cc =	41.015	Cc =	45.5
$S2 = \frac{k_1 Bbr}{mDbr}$		$S2 = \frac{k_1 Bbr}{mDbr}$	
S2 =	77.2	S2 =	77.3
φF_L=	φb[Bbr-mDbr*h/t]	φF_L=	1.3φyFcy
φF_L=	43.2 ksi	φF_L=	43.2 ksi
φF_LSt=	25.1 ksi	φF_LWk=	23.1 ksi
Ix =	897074 mm^4	Iy =	446476 mm^4
	2.155 in^4		1.073 in^4
y =	41.015 mm	x =	45.5 mm
Sx =	1.335 in^3	Sy =	0.599 in^3
M_{max}St =	2.788 k-ft	M_{max}Wk =	1.152 k-ft

Compression

3.4.9

b/t = 32.195
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 25.1 ksi

b/t = 37.0588
S1 = 12.21
S2 = 32.70
φF_L = (φck2*√(BpE))/(1.6b/t)
φF_L = 21.9 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 21.94 ksi
A = 1215.13 mm^2
1.88 in^2
P_{max} = 41.32 kips

A.2 Design of Aluminum Girders - Aluminum Design Manual, 2005 Edition

Girder = **T5**

Strong Axis:

3.4.14

L_b = 63.8189 in
J = 1.98
82.1278

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.5 ksi

3.4.16

b/t = 4.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φyFcy
φF_L = 33.3 ksi

Weak Axis:

3.4.14

L_b = 63.8189
J = 1.98
89.1294

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.3

3.4.16

b/t = 16.3333

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 31.6 ksi

3.4.16.1 Used

Rb/t = 20.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L = φb[Bt-Dt*√(Rb/t)]

φF_L = 30.8 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 16.3333

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 37.9

m = 0.63

C_0 = 61.046

Cc = 58.954

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 79.4

φF_L = 1.3φyFcy

φF_L = 43.2 ksi

$\varphi F_L St$ = 30.5 ksi

Ix = 1970917 mm^4

4.735 in^4

y = 61.046 mm

Sx = 1.970 in^3

$M_{max}St$ = 5.001 k-ft

3.4.18

h/t = 4.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 35

Cc = 35

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L = 1.3φyFcy

φF_L = 43.2 ksi

$\varphi F_L Wk$ = 31.6 ksi

Iy = 763048 mm^4

1.833 in^4

x = 35 mm

Sy = 1.330 in^3

$M_{max}Wk$ = 3.499 k-ft

Compression

3.4.9

b/t = 4.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φyFcy

φF_L = 33.3 ksi

b/t = 16.3333

S1 = 12.21

S2 = 32.70

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 31.6 ksi

3.4.10

Rb/t = 20.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φc[Bt-Dt*√(Rb/t)]

φF_L = 30.80 ksi

φF_L = 30.80 ksi

A = 1215.13 mm^2

1.88 in^2

P_{max} = 58.01 kips

A.3 Design of Aluminum Struts - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 61 in

J = 0.942

95.1963

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 30.2 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

Weak Axis:

3.4.14

L_b = 61

J = 0.942

95.1963

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 30.2

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 1.41113

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.77756

φF_L = (φccFcy)/(λ²)

φF_L = 13.6667 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 13.67 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 14.07 kips

A.4 Design of Galvanized Steel Posts

Post Type = **FG8**

Unbraced Length =	85.68	in	
Pr =	-4.15	k	(LRFD Factored Load)
Mr (Strong) =	16.80	k-ft	(LRFD Factored Load)
Mr (Weak) =	0.00	k-ft	(LRFD Factored Load)

Flexural Buckling:

kL/r =	123.28		
4.71√(E/Fy) =	103.55	=> kL/r	> 4.71√(E/Fy)
Fcr =	16.52	ksi	
Fe =	18.83	ksi	
Pn =	36.831	k	

Torsional/Flexural Torsional Buckling:

Fcr =	12.5831	ksi
Fey =	48.0382	ksi
Fez =	16.1601	ksi
Pn =	28.0602	k

Bending (Strong Axis):

Yielding:

Mn =	21.95	k-ft

Flange Local Buckling:

Mn =	19.207	k-ft

Pr/Pc =	0.1126	<	0.2	
Utilization =	0.99	<	1.0	OK

Bending (Weak Axis):

Yielding:

Mn =	14.65	k-ft

Flange Local Buckling:

Mn =	14.39	k-ft

Pr/Pc =	0.113	<	0.2	
Utilization =	0.00	<	1.0	OK

Combined Forces

Utilization = 99%

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				4		
2	Dead Load, Min	DL		-1				4		
3	Snow Load	SL						4		
4	Wind Load - Pressure	WL						4		
5	Wind Load - Suction	WL						4		
6	Seismic - Lateral	EL								

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-8.366	-8.366	0	0
2	M11	Y	-8.366	-8.366	0	0
3	M12	Y	-8.366	-8.366	0	0
4	M13	Y	-8.366	-8.366	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-4.45	-4.45	0	0
2	M11	Y	-4.45	-4.45	0	0
3	M12	Y	-4.45	-4.45	0	0
4	M13	Y	-4.45	-4.45	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-32.97	-32.97	0	0
2	M11	Y	-32.97	-32.97	0	0
3	M12	Y	-32.97	-32.97	0	0
4	M13	Y	-32.97	-32.97	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	y	-63.577	-63.577	0	0
2	M11	y	-63.577	-63.577	0	0
3	M12	y	-105.961	-105.961	0	0
4	M13	y	-105.961	-105.961	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	y	127.153	127.153	0	0
2	M11	y	127.153	127.153	0	0
3	M12	y	63.577	63.577	0	0
4	M13	y	63.577	63.577	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.5W	Yes	Y		1	1.2	3	1.6	4	.5																
2	LRFD 1.2D + 1.0W + 0.5S	Yes	Y		1	1.2	3	.5	4	1																
3	LRFD 0.9D + 1.0W	Yes	Y		2	.9					5	1														
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3														
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3														
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25														
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25														

Load Combinations (Continued)

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
8																										
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																		
10	ASD 1.0D + 0.6W	Yes	Y		1	1			4	.6																
11	ASD 1.0D + 0.75L + 0.45W + 0....	Yes	Y		1	1	3	.75	4	.45																
12	ASD 0.6D + 0.6W	Yes	Y		2	.6					5	.6														
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875														
14	LATERAL - ASD 1.1785D + 0.65...	Yes	Y		1	1.1...	3	.75			6	.656														
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875														

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N9	max	887.911	2	2120.777	1	308.038	2	.449	2	.02	3	4.556	3
2		min	-1132.49	3	-1331.725	3	-323.122	3	-.532	3	-.04	2	.18	10
3	N19	max	2891.843	2	5600.751	2	0	2	0	1	0	2	9.981	3
4		min	-2986.135	3	-4108.157	3	0	12	0	3	0	3	.036	10
5	N29	max	887.911	2	2120.777	1	323.122	3	.532	3	.04	2	4.556	3
6		min	-1132.49	3	-1331.725	3	-308.038	2	-.449	2	-.02	3	.18	10
7	Totals:	max	4667.664	2	9818.722	1	0	1						
8		min	-5251.115	3	-6771.608	3	0	12						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M1	1	max	0	1	.006	1	0	15	0	1	0	1	0	1
2			min	0	1	0	3	-.002	1	0	1	0	1	0	1
3		2	max	-.299	15	-.428	15	0	15	0	1	0	15	0	4
4			min	-1.274	4	-1.817	4	-.002	1	0	1	0	1	0	15
5		3	max	-12.726	15	273.285	3	-9.616	15	.083	3	.333	1	.267	2
6			min	-220.809	1	-626.448	2	-175.137	1	-.288	2	.019	15	-.113	3
7		4	max	-13.025	15	272.222	3	-9.616	15	.083	3	.224	1	.657	2
8			min	-221.801	1	-627.866	2	-175.137	1	-.288	2	.013	15	-.282	3
9		5	max	-13.325	15	271.159	3	-9.616	15	.083	3	.115	1	1.047	2
10			min	-222.794	1	-629.283	2	-175.137	1	-.288	2	.007	15	-.451	3
11		6	max	141.736	3	559.163	2	10.152	3	.144	2	.116	2	1.001	2
12			min	-612.681	1	-176.192	3	-256.275	1	-.13	3	-.045	3	-.455	3
13		7	max	140.991	3	557.746	2	10.152	3	.144	2	.012	10	.655	2
14			min	-613.674	1	-177.255	3	-256.275	1	-.13	3	-.046	1	-.345	3
15		8	max	140.247	3	556.329	2	10.152	3	.144	2	-.011	15	.309	2
16			min	-614.666	1	-178.318	3	-256.275	1	-.13	3	-.205	1	-.235	3
17		9	max	109.039	3	85.639	3	-12.521	12	-.003	15	.105	1	.109	1
18			min	-842.767	1	-71.313	2	-261.955	1	-.216	2	-.008	10	-.179	3
19		10	max	108.295	3	84.576	3	-12.521	12	-.003	15	.064	3	.15	2
20			min	-843.76	1	-72.731	2	-261.955	1	-.216	2	-.064	2	-.232	3
21		11	max	107.551	3	83.512	3	-12.521	12	-.003	15	.052	3	.195	2
22			min	-844.752	1	-74.148	2	-261.955	1	-.216	2	-.22	1	-.284	3
23		12	max	72.981	3	709.948	3	203.904	2	.456	3	.207	1	.407	2
24			min	-1070.128	1	-491.256	2	-404.839	3	-.416	2	.011	12	-.579	3
25		13	max	72.236	3	708.885	3	203.904	2	.456	3	.259	1	.712	2
26			min	-1071.121	1	-492.673	2	-404.839	3	-.416	2	-.235	3	-1.02	3
27		14	max	223.703	1	441.532	2	10.853	10	.31	2	.192	3	1.006	2
28			min	13.628	15	-625.8	3	-129.012	3	-.51	3	-.154	2	-1.441	3
29		15	max	222.71	1	440.115	2	10.853	10	.31	2	.112	3	.732	2
30			min	13.329	15	-626.863	3	-129.012	3	-.51	3	-.22	1	-1.052	3
31		16	max	221.718	1	438.697	2	10.853	10	.31	2	.032	3	.459	2
32			min	13.03	15	-627.926	3	-129.012	3	-.51	3	-.29	1	-.663	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
33		17	max	220.725	1	437.28	2	10.853	10	.31	2	-.019	15	.188	2
34			min	12.73	15	-628.989	3	-129.012	3	-.51	3	-.36	1	-.273	3
35		18	max	1.274	4	1.819	4	.002	1	0	1	0	15	0	4
36			min	.299	15	.428	15	0	15	0	1	0	1	0	15
37		19	max	0	1	.004	2	.002	1	0	1	0	1	0	1
38			min	0	1	-.007	3	0	15	0	1	0	1	0	1
39	M4	1	max	0	1	.015	1	0	1	0	1	0	1	0	1
40			min	0	1	-.001	3	0	1	0	1	0	1	0	1
41		2	max	-.299	15	-.427	15	0	1	0	1	0	1	0	4
42			min	-1.274	4	-1.815	4	0	1	0	1	0	1	0	15
43		3	max	-12.315	12	867.557	3	0	1	0	1	0	1	.722	2
44			min	-453.558	1	-1850.087	2	0	1	0	1	0	1	-.345	3
45		4	max	-12.811	12	866.494	3	0	1	0	1	0	1	1.871	2
46			min	-454.551	1	-1851.505	2	0	1	0	1	0	1	-.883	3
47		5	max	-13.307	12	865.431	3	0	1	0	1	0	1	3.021	2
48			min	-455.543	1	-1852.922	2	0	1	0	1	0	1	-1.421	3
49		6	max	594.213	3	1681.845	2	0	1	0	1	0	1	2.874	2
50			min	-1605.038	2	-663.166	3	0	1	0	1	0	1	-1.397	3
51		7	max	593.469	3	1680.427	2	0	1	0	1	0	1	1.83	2
52			min	-1606.031	2	-664.229	3	0	1	0	1	0	1	-.985	3
53		8	max	592.725	3	1679.01	2	0	1	0	1	0	1	.788	2
54			min	-1607.023	2	-665.292	3	0	1	0	1	0	1	-.573	3
55		9	max	579.139	3	222.193	3	0	1	0	1	0	1	.172	1
56			min	-2038.453	1	-182.103	1	0	1	0	1	0	1	-.366	3
57		10	max	578.395	3	221.13	3	0	1	0	1	0	1	.286	1
58			min	-2039.445	1	-183.521	1	0	1	0	1	0	1	-.504	3
59		11	max	577.65	3	220.067	3	0	1	0	1	0	1	.4	1
60			min	-2040.438	1	-184.938	1	0	1	0	1	0	1	-.641	3
61		12	max	570.789	3	1907.284	3	0	1	0	1	0	1	.997	1
62			min	-2481.884	1	-1442.433	2	0	1	0	1	0	1	-1.457	3
63		13	max	570.045	3	1906.22	3	0	1	0	1	0	1	1.891	2
64			min	-2482.876	1	-1443.85	2	0	1	0	1	0	1	-2.64	3
65		14	max	456.703	1	1224.642	2	0	1	0	1	0	1	2.751	2
66			min	13.722	12	-1680.088	3	0	1	0	1	0	1	-3.774	3
67		15	max	455.71	1	1223.224	2	0	1	0	1	0	1	1.991	2
68			min	13.226	12	-1681.151	3	0	1	0	1	0	1	-2.731	3
69		16	max	454.718	1	1221.807	2	0	1	0	1	0	1	1.232	2
70			min	12.729	12	-1682.214	3	0	1	0	1	0	1	-1.687	3
71		17	max	453.725	1	1220.389	2	0	1	0	1	0	1	.475	2
72			min	12.233	12	-1683.277	3	0	1	0	1	0	1	-.643	3
73		18	max	1.274	4	1.821	4	0	1	0	1	0	1	0	4
74			min	.299	15	.428	15	0	1	0	1	0	1	0	15
75		19	max	0	1	.011	2	0	1	0	1	0	1	0	1
76			min	0	1	-.017	3	0	1	0	1	0	1	0	1
77	M7	1	max	0	1	.006	1	.002	1	0	1	0	1	0	1
78			min	0	1	0	3	0	15	0	1	0	1	0	1
79		2	max	-.299	15	-.428	15	.002	1	0	1	0	1	0	4
80			min	-1.274	4	-1.817	4	0	15	0	1	0	15	0	15
81		3	max	-12.726	15	273.285	3	175.137	1	.288	2	-.019	15	.267	2
82			min	-220.809	1	-626.448	2	9.616	15	-.083	3	-.333	1	-.113	3
83		4	max	-13.025	15	272.222	3	175.137	1	.288	2	-.013	15	.657	2
84			min	-221.801	1	-627.866	2	9.616	15	-.083	3	-.224	1	-.282	3
85		5	max	-13.325	15	271.159	3	175.137	1	.288	2	-.007	15	1.047	2
86			min	-222.794	1	-629.283	2	9.616	15	-.083	3	-.115	1	-.451	3
87		6	max	141.736	3	559.163	2	256.275	1	.13	3	.045	3	1.001	2
88			min	-612.681	1	-176.192	3	-10.152	3	-.144	2	-.116	2	-.455	3
89		7	max	140.991	3	557.746	2	256.275	1	.13	3	.046	1	.655	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
90			min	-613.674	1	-177.255	3	-10.152	3	-.144	2	-.012	10	-.345	3
91		8	max	140.247	3	556.329	2	256.275	1	.13	3	.205	1	.309	2
92			min	-614.666	1	-178.318	3	-10.152	3	-.144	2	.011	15	-.235	3
93		9	max	109.039	3	85.639	3	261.955	1	.216	2	.008	10	.109	1
94			min	-842.767	1	-71.313	2	12.521	12	.003	15	-.105	1	-.179	3
95		10	max	108.295	3	84.576	3	261.955	1	.216	2	.064	2	.15	2
96			min	-843.76	1	-72.731	2	12.521	12	.003	15	-.064	3	-.232	3
97		11	max	107.551	3	83.512	3	261.955	1	.216	2	.22	1	.195	2
98			min	-844.752	1	-74.148	2	12.521	12	.003	15	-.052	3	-.284	3
99		12	max	72.981	3	709.948	3	404.839	3	.416	2	-.011	12	.407	2
100			min	-1070.128	1	-491.256	2	-203.904	2	-.456	3	-.207	1	-.579	3
101		13	max	72.236	3	708.885	3	404.839	3	.416	2	.235	3	.712	2
102			min	-1071.121	1	-492.673	2	-203.904	2	-.456	3	-.259	1	-1.02	3
103		14	max	223.703	1	441.532	2	129.012	3	.51	3	.154	2	1.006	2
104			min	13.628	15	-625.8	3	-10.853	10	-.31	2	-.192	3	-1.441	3
105		15	max	222.71	1	440.115	2	129.012	3	.51	3	.22	1	.732	2
106			min	13.329	15	-626.863	3	-10.853	10	-.31	2	-.112	3	-1.052	3
107		16	max	221.718	1	438.697	2	129.012	3	.51	3	.29	1	.459	2
108			min	13.03	15	-627.926	3	-10.853	10	-.31	2	-.032	3	-.663	3
109		17	max	220.725	1	437.28	2	129.012	3	.51	3	.36	1	.188	2
110			min	12.73	15	-628.989	3	-10.853	10	-.31	2	.019	15	-.273	3
111		18	max	1.274	4	1.819	4	0	15	0	1	0	1	0	4
112			min	.299	15	.428	15	-.002	1	0	1	0	15	0	15
113		19	max	0	1	.004	2	0	15	0	1	0	1	0	1
114			min	0	1	-.007	3	-.002	1	0	1	0	1	0	1
115	M10	1	max	129.028	3	433.993	2	-12.132	15	.01	2	.405	1	.31	2
116			min	-10.857	10	-631.34	3	-218.844	1	-.019	3	.023	15	-.51	3
117		2	max	129.028	3	318.282	2	-9.399	15	.01	2	.147	1	.223	3
118			min	-10.857	10	-467.655	3	-169.443	1	-.019	3	.008	15	-.199	1
119		3	max	129.028	3	202.572	2	-6.667	15	.01	2	.033	3	.737	3
120			min	-10.857	10	-303.971	3	-120.042	1	-.019	3	-.046	1	-.539	2
121		4	max	129.028	3	86.861	2	-3.934	15	.01	2	.007	3	1.033	3
122			min	-10.857	10	-140.286	3	-70.64	1	-.019	3	-.174	1	-.732	2
123		5	max	129.028	3	23.399	3	-1.202	15	.01	2	-.009	12	1.111	3
124			min	-10.857	10	-32.779	1	-21.239	1	-.019	3	-.235	1	-.771	2
125		6	max	129.028	3	187.083	3	28.162	1	.01	2	-.013	15	.971	3
126			min	-10.857	10	-145.716	1	-9.123	3	-.019	3	-.23	1	-.655	2
127		7	max	129.028	3	350.768	3	77.563	1	.01	2	-.009	15	.612	3
128			min	-10.857	10	-260.27	2	-5.025	3	-.019	3	-.16	1	-.385	2
129		8	max	129.028	3	514.452	3	126.964	1	.01	2	-.001	10	.063	1
130			min	-10.857	10	-375.981	2	-.927	3	-.019	3	-.042	3	.003	15
131		9	max	129.028	3	678.137	3	176.365	1	.01	2	.179	1	.634	1
132			min	-10.857	10	-491.691	2	2.79	12	-.019	3	-.04	3	-.759	3
133		10	max	129.028	3	607.402	2	5.523	12	.019	3	.447	1	1.355	1
134			min	-10.857	10	-841.821	3	-225.766	1	-.01	2	-.033	3	-1.773	3
135		11	max	129.028	3	491.691	2	-2.79	12	.019	3	.179	1	.634	1
136			min	-10.857	10	-678.137	3	-176.365	1	-.01	2	-.04	3	-.759	3
137		12	max	129.028	3	375.981	2	.927	3	.019	3	-.001	10	.063	1
138			min	-10.857	10	-514.452	3	-126.964	1	-.01	2	-.042	3	.003	15
139		13	max	129.028	3	260.27	2	5.025	3	.019	3	-.009	15	.612	3
140			min	-10.857	10	-350.768	3	-77.563	1	-.01	2	-.16	1	-.385	2
141		14	max	129.028	3	145.716	1	9.123	3	.019	3	-.013	15	.971	3
142			min	-10.857	10	-187.083	3	-28.162	1	-.01	2	-.23	1	-.655	2
143		15	max	129.028	3	32.779	1	21.239	1	.019	3	-.009	12	1.111	3
144			min	-10.857	10	-23.399	3	1.202	15	-.01	2	-.235	1	-.771	2
145		16	max	129.028	3	140.286	3	70.64	1	.019	3	.007	3	1.033	3
146			min	-10.857	10	-86.861	2	3.934	15	-.01	2	-.174	1	-.732	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
147		17	max	129.028	3	303.971	3	120.042	1	.019	3	.033	3	.737	3
148			min	-10.857	10	-202.572	2	6.667	15	-.01	2	-.046	1	-.539	2
149		18	max	129.028	3	467.655	3	169.443	1	.019	3	.147	1	.223	3
150			min	-10.857	10	-318.282	2	9.399	15	-.01	2	.008	15	-.199	1
151		19	max	129.028	3	631.34	3	218.844	1	.019	3	.405	1	.31	2
152			min	-10.857	10	-433.993	2	12.132	15	-.01	2	.023	15	-.51	3
153	M11	1	max	344.902	1	414.491	2	-12.486	15	0	10	.452	1	.227	1
154			min	-386.782	3	-627.364	3	-224.703	1	-.005	3	.025	15	-.589	3
155		2	max	344.902	1	298.78	2	-9.753	15	0	10	.185	1	.138	3
156			min	-386.782	3	-463.68	3	-175.302	1	-.005	3	.011	15	-.275	2
157		3	max	344.902	1	183.07	2	-7.021	15	0	10	.051	3	.647	3
158			min	-386.782	3	-299.995	3	-125.901	1	-.005	3	-.015	1	-.597	2
159		4	max	344.902	1	68.904	1	-4.288	15	0	10	.021	3	.938	3
160			min	-386.782	3	-136.311	3	-76.5	1	-.005	3	-.15	1	-.764	2
161		5	max	344.902	1	27.374	3	-1.556	15	0	10	-.004	12	1.011	3
162			min	-386.782	3	-48.351	2	-27.099	1	-.005	3	-.219	1	-.776	2
163		6	max	344.902	1	191.058	3	22.302	1	0	10	-.012	15	.865	3
164			min	-386.782	3	-164.062	2	-12.546	3	-.005	3	-.223	1	-.635	2
165		7	max	344.902	1	354.743	3	71.704	1	0	10	-.009	15	.501	3
166			min	-386.782	3	-279.772	2	-8.448	3	-.005	3	-.16	1	-.339	2
167		8	max	344.902	1	518.427	3	121.105	1	0	10	-.002	10	.111	2
168			min	-386.782	3	-395.483	2	-4.349	3	-.005	3	-.046	3	-.081	3
169		9	max	344.902	1	682.112	3	170.506	1	0	10	.163	1	.716	2
170			min	-386.782	3	-511.193	2	-.251	3	-.005	3	-.049	3	-.881	3
171		10	max	344.902	1	626.904	2	-3.423	12	.005	3	.423	1	1.475	2
172			min	-386.782	3	-845.797	3	-219.907	1	0	11	-.047	3	-1.9	3
173		11	max	344.902	1	511.193	2	.251	3	.005	3	.163	1	.716	2
174			min	-386.782	3	-682.112	3	-170.506	1	0	10	-.049	3	-.881	3
175		12	max	344.902	1	395.483	2	4.349	3	.005	3	-.002	10	.111	2
176			min	-386.782	3	-518.427	3	-121.105	1	0	10	-.046	3	-.081	3
177		13	max	344.902	1	279.772	2	8.448	3	.005	3	-.009	15	.501	3
178			min	-386.782	3	-354.743	3	-71.704	1	0	10	-.16	1	-.339	2
179		14	max	344.902	1	164.062	2	12.546	3	.005	3	-.012	15	.865	3
180			min	-386.782	3	-191.058	3	-22.302	1	0	10	-.223	1	-.635	2
181		15	max	344.902	1	48.351	2	27.099	1	.005	3	-.004	12	1.011	3
182			min	-386.782	3	-27.374	3	1.556	15	0	10	-.219	1	-.776	2
183		16	max	344.902	1	136.311	3	76.5	1	.005	3	.021	3	.938	3
184			min	-386.782	3	-68.904	1	4.288	15	0	10	-.15	1	-.764	2
185		17	max	344.902	1	299.995	3	125.901	1	.005	3	.051	3	.647	3
186			min	-386.782	3	-183.07	2	7.021	15	0	10	-.015	1	-.597	2
187		18	max	344.902	1	463.68	3	175.302	1	.005	3	.185	1	.138	3
188			min	-386.782	3	-298.78	2	9.753	15	0	10	.011	15	-.275	2
189		19	max	344.902	1	627.364	3	224.703	1	.005	3	.452	1	.227	1
190			min	-386.782	3	-414.491	2	12.486	15	0	10	.025	15	-.589	3
191	M12	1	max	55.688	2	625.387	2	-12.561	15	0	15	.471	1	.359	2
192			min	-28.185	3	-265.083	3	-227.104	1	-.004	3	.026	15	.003	12
193		2	max	55.688	2	453.164	2	-9.829	15	0	15	.201	1	.304	3
194			min	-28.185	3	-186.166	3	-177.702	1	-.004	3	.011	15	-.36	2
195		3	max	55.688	2	280.942	2	-7.096	15	0	15	.037	3	.5	3
196			min	-28.185	3	-107.25	3	-128.301	1	-.004	3	-.003	1	-.849	2
197		4	max	55.688	2	108.719	2	-4.364	15	0	15	.01	3	.59	3
198			min	-28.185	3	-28.333	3	-78.9	1	-.004	3	-.141	1	-1.109	2
199		5	max	55.688	2	50.583	3	-1.631	15	0	15	-.008	12	.576	3
200			min	-28.185	3	-63.503	2	-29.499	1	-.004	3	-.213	1	-1.139	2
201		6	max	55.688	2	129.5	3	19.902	1	0	15	-.012	15	.456	3
202			min	-28.185	3	-235.726	2	-9.915	3	-.004	3	-.219	1	-.94	2
203		7	max	55.688	2	208.416	3	69.303	1	0	15	-.009	15	.23	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
204			min	-28.185	3	-407.948	2	-5.817	3	-.004	3	-.16	1	-.511	2
205		8	max	55.688	2	287.333	3	118.704	1	0	15	-.002	15	.148	2
206			min	-28.185	3	-580.171	2	-1.718	3	-.004	3	-.043	3	-.1	3
207		9	max	55.688	2	366.25	3	168.105	1	0	15	.157	1	1.037	2
208			min	-28.185	3	-752.393	2	2.263	12	-.004	3	-.042	3	-.536	3
209		10	max	55.688	2	924.616	2	-4.995	12	.004	3	.414	1	2.155	2
210			min	-28.185	3	-445.166	3	-217.506	1	-.002	1	-.036	3	-1.077	3
211		11	max	55.688	2	752.393	2	-2.263	12	.004	3	.157	1	1.037	2
212			min	-28.185	3	-366.25	3	-168.105	1	0	15	-.042	3	-.536	3
213		12	max	55.688	2	580.171	2	1.718	3	.004	3	-.002	15	.148	2
214			min	-28.185	3	-287.333	3	-118.704	1	0	15	-.043	3	-.1	3
215		13	max	55.688	2	407.948	2	5.817	3	.004	3	-.009	15	.23	3
216			min	-28.185	3	-208.416	3	-69.303	1	0	15	-.16	1	-.511	2
217		14	max	55.688	2	235.726	2	9.915	3	.004	3	-.012	15	.456	3
218			min	-28.185	3	-129.5	3	-19.902	1	0	15	-.219	1	-.94	2
219		15	max	55.688	2	63.503	2	29.499	1	.004	3	-.008	12	.576	3
220			min	-28.185	3	-50.583	3	1.631	15	0	15	-.213	1	-1.139	2
221		16	max	55.688	2	28.333	3	78.9	1	.004	3	.01	3	.59	3
222			min	-28.185	3	-108.719	2	4.364	15	0	15	-.141	1	-1.109	2
223		17	max	55.688	2	107.25	3	128.301	1	.004	3	.037	3	.5	3
224			min	-28.185	3	-280.942	2	7.096	15	0	15	-.003	1	-.849	2
225		18	max	55.688	2	186.166	3	177.702	1	.004	3	.201	1	.304	3
226			min	-28.185	3	-453.164	2	9.829	15	0	15	.011	15	-.36	2
227		19	max	55.688	2	265.083	3	227.104	1	.004	3	.471	1	.359	2
228			min	-28.185	3	-625.387	2	12.561	15	0	15	.026	15	.003	12
229	M13	1	max	-9.615	15	624.191	2	-12.126	15	.003	3	.404	1	.288	2
230			min	-174.943	1	-275.412	3	-218.658	1	-.013	2	.023	15	-.083	3
231		2	max	-9.615	15	451.969	2	-9.394	15	.003	3	.145	1	.231	3
232			min	-174.943	1	-196.495	3	-169.257	1	-.013	2	.008	15	-.429	2
233		3	max	-9.615	15	279.746	2	-6.661	15	.003	3	.031	3	.441	3
234			min	-174.943	1	-117.579	3	-119.856	1	-.013	2	-.048	1	-.917	2
235		4	max	-9.615	15	107.524	2	-3.929	15	.003	3	.006	3	.545	3
236			min	-174.943	1	-38.662	3	-70.455	1	-.013	2	-.175	1	-1.175	2
237		5	max	-9.615	15	40.254	3	-1.196	15	.003	3	-.01	12	.544	3
238			min	-174.943	1	-64.699	2	-21.053	1	-.013	2	-.236	1	-1.204	2
239		6	max	-9.615	15	119.171	3	28.348	1	.003	3	-.013	15	.437	3
240			min	-174.943	1	-236.921	2	-8.844	3	-.013	2	-.231	1	-1.002	2
241		7	max	-9.615	15	198.087	3	77.749	1	.003	3	-.009	15	.226	3
242			min	-174.943	1	-409.144	2	-4.746	3	-.013	2	-.16	1	-.572	2
243		8	max	-9.615	15	277.004	3	127.15	1	.003	3	-.001	10	.089	2
244			min	-174.943	1	-581.366	2	-.648	3	-.013	2	-.041	3	-.091	3
245		9	max	-9.615	15	355.92	3	176.551	1	.003	3	.179	1	.979	2
246			min	-174.943	1	-753.589	2	2.958	12	-.013	2	-.039	3	-.513	3
247		10	max	-9.615	15	925.811	2	-5.69	12	0	15	.447	1	2.098	2
248			min	-174.943	1	-434.837	3	-225.952	1	-.013	2	-.032	3	-1.04	3
249		11	max	-9.615	15	753.589	2	-2.958	12	.013	2	.179	1	.979	2
250			min	-174.943	1	-355.92	3	-176.551	1	-.003	3	-.039	3	-.513	3
251		12	max	-9.615	15	581.366	2	.648	3	.013	2	-.001	10	.089	2
252			min	-174.943	1	-277.004	3	-127.15	1	-.003	3	-.041	3	-.091	3
253		13	max	-9.615	15	409.144	2	4.746	3	.013	2	-.009	15	.226	3
254			min	-174.943	1	-198.087	3	-77.749	1	-.003	3	-.16	1	-.572	2
255		14	max	-9.615	15	236.921	2	8.844	3	.013	2	-.013	15	.437	3
256			min	-174.943	1	-119.171	3	-28.348	1	-.003	3	-.231	1	-1.002	2
257		15	max	-9.615	15	64.699	2	21.053	1	.013	2	-.01	12	.544	3
258			min	-174.943	1	-40.254	3	1.196	15	-.003	3	-.236	1	-1.204	2
259		16	max	-9.615	15	38.662	3	70.455	1	.013	2	.006	3	.545	3
260			min	-174.943	1	-107.524	2	3.929	15	-.003	3	-.175	1	-1.175	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
261		17	max	-9.615	15	117.579	3	119.856	1	.013	2	.031	3	.441	3
262			min	-174.943	1	-279.746	2	6.661	15	-.003	3	-.048	1	-.917	2
263		18	max	-9.615	15	196.495	3	169.257	1	.013	2	.145	1	.231	3
264			min	-174.943	1	-451.969	2	9.394	15	-.003	3	.008	15	-.429	2
265		19	max	-9.615	15	275.412	3	218.658	1	.013	2	.404	1	.288	2
266			min	-174.943	1	-624.191	2	12.126	15	-.003	3	.023	15	-.083	3
267	M2	1	max	2120.777	1	1132.156	3	308.164	2	.02	3	.532	3	4.556	3
268			min	-1331.725	3	-887.893	2	-323.026	3	-.04	2	-.449	2	.18	10
269		2	max	1537.642	1	728.768	3	211.431	2	.002	2	.422	3	4.226	3
270			min	-1074.926	3	35.541	15	-275.965	3	-.001	3	-.342	2	.206	15
271		3	max	1534.535	1	728.768	3	211.431	2	.002	2	.328	3	3.977	3
272			min	-1077.255	3	35.541	15	-275.965	3	-.001	3	-.27	2	.194	15
273		4	max	1531.429	1	728.768	3	211.431	2	.002	2	.234	3	3.729	3
274			min	-1079.585	3	35.541	15	-275.965	3	-.001	3	-.202	1	.182	15
275		5	max	1528.323	1	728.768	3	211.431	2	.002	2	.14	3	3.48	3
276			min	-1081.915	3	35.541	15	-275.965	3	-.001	3	-.136	1	.17	15
277		6	max	1525.217	1	728.768	3	211.431	2	.002	2	.046	3	3.232	3
278			min	-1084.244	3	35.541	15	-275.965	3	-.001	3	-.069	1	.158	15
279		7	max	1522.111	1	728.768	3	211.431	2	.002	2	.018	2	2.983	3
280			min	-1086.574	3	35.541	15	-275.965	3	-.001	3	-.048	3	.145	15
281		8	max	1519.005	1	728.768	3	211.431	2	.002	2	.091	2	2.734	3
282			min	-1088.903	3	35.541	15	-275.965	3	-.001	3	-.142	3	.133	15
283		9	max	1515.899	1	728.768	3	211.431	2	.002	2	.163	2	2.486	3
284			min	-1091.233	3	35.541	15	-275.965	3	-.001	3	-.237	3	.121	15
285		10	max	1512.793	1	728.768	3	211.431	2	.002	2	.235	2	2.237	3
286			min	-1093.562	3	35.541	15	-275.965	3	-.001	3	-.331	3	.109	15
287		11	max	1509.687	1	728.768	3	211.431	2	.002	2	.307	2	1.989	3
288			min	-1095.892	3	35.541	15	-275.965	3	-.001	3	-.425	3	.097	15
289		12	max	1506.581	1	728.768	3	211.431	2	.002	2	.379	2	1.74	3
290			min	-1098.222	3	35.541	15	-275.965	3	-.001	3	-.519	3	.085	15
291		13	max	1503.475	1	728.768	3	211.431	2	.002	2	.451	2	1.492	3
292			min	-1100.551	3	35.541	15	-275.965	3	-.001	3	-.613	3	.073	15
293		14	max	1500.368	1	728.768	3	211.431	2	.002	2	.523	2	1.243	3
294			min	-1102.881	3	35.541	15	-275.965	3	-.001	3	-.707	3	.061	15
295		15	max	1497.262	1	728.768	3	211.431	2	.002	2	.595	2	.994	3
296			min	-1105.21	3	35.541	15	-275.965	3	-.001	3	-.801	3	.048	15
297		16	max	1494.156	1	728.768	3	211.431	2	.002	2	.668	2	.746	3
298			min	-1107.54	3	35.541	15	-275.965	3	-.001	3	-.895	3	.036	15
299		17	max	1491.05	1	728.768	3	211.431	2	.002	2	.74	2	.497	3
300			min	-1109.869	3	35.541	15	-275.965	3	-.001	3	-.99	3	.024	15
301		18	max	1487.944	1	728.768	3	211.431	2	.002	2	.812	2	.249	3
302			min	-1112.199	3	35.541	15	-275.965	3	-.001	3	-1.084	3	.012	15
303		19	max	1484.838	1	728.768	3	211.431	2	.002	2	.884	2	0	1
304			min	-1114.528	3	35.541	15	-275.965	3	-.001	3	-1.178	3	0	1
305	M5	1	max	5600.751	2	2983.802	3	0	1	0	1	0	1	9.981	3
306			min	-4108.157	3	-2892.159	2	0	1	0	1	0	1	.036	10
307		2	max	3885.417	1	1579.444	3	0	1	0	1	0	1	9.159	3
308			min	-3219.233	3	57.983	15	0	1	0	1	0	1	.336	15
309		3	max	3882.311	1	1579.444	3	0	1	0	1	0	1	8.62	3
310			min	-3221.562	3	57.983	15	0	1	0	1	0	1	.316	15
311		4	max	3879.204	1	1579.444	3	0	1	0	1	0	1	8.081	3
312			min	-3223.892	3	57.983	15	0	1	0	1	0	1	.297	15
313		5	max	3876.098	1	1579.444	3	0	1	0	1	0	1	7.543	3
314			min	-3226.221	3	57.983	15	0	1	0	1	0	1	.277	15
315		6	max	3872.992	1	1579.444	3	0	1	0	1	0	1	7.004	3
316			min	-3228.551	3	57.983	15	0	1	0	1	0	1	.257	15
317		7	max	3869.886	1	1579.444	3	0	1	0	1	0	1	6.465	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
318			min	-3230.88	3	57.983	15	0	1	0	1	0	1	.237	15
319		8	max	3866.78	1	1579.444	3	0	1	0	1	0	1	5.926	3
320			min	-3233.21	3	57.983	15	0	1	0	1	0	1	.218	15
321		9	max	3863.674	1	1579.444	3	0	1	0	1	0	1	5.388	3
322			min	-3235.54	3	57.983	15	0	1	0	1	0	1	.198	15
323		10	max	3860.568	1	1579.444	3	0	1	0	1	0	1	4.849	3
324			min	-3237.869	3	57.983	15	0	1	0	1	0	1	.178	15
325		11	max	3857.462	1	1579.444	3	0	1	0	1	0	1	4.31	3
326			min	-3240.199	3	57.983	15	0	1	0	1	0	1	.158	15
327		12	max	3854.356	1	1579.444	3	0	1	0	1	0	1	3.771	3
328			min	-3242.528	3	57.983	15	0	1	0	1	0	1	.138	15
329		13	max	3851.25	1	1579.444	3	0	1	0	1	0	1	3.233	3
330			min	-3244.858	3	57.983	15	0	1	0	1	0	1	.119	15
331		14	max	3848.144	1	1579.444	3	0	1	0	1	0	1	2.694	3
332			min	-3247.187	3	57.983	15	0	1	0	1	0	1	.099	15
333		15	max	3845.037	1	1579.444	3	0	1	0	1	0	1	2.155	3
334			min	-3249.517	3	57.983	15	0	1	0	1	0	1	.079	15
335		16	max	3841.931	1	1579.444	3	0	1	0	1	0	1	1.616	3
336			min	-3251.847	3	57.983	15	0	1	0	1	0	1	.059	15
337		17	max	3838.825	1	1579.444	3	0	1	0	1	0	1	1.078	3
338			min	-3254.176	3	57.983	15	0	1	0	1	0	1	.04	15
339		18	max	3835.719	1	1579.444	3	0	1	0	1	0	1	.539	3
340			min	-3256.506	3	57.983	15	0	1	0	1	0	1	.02	15
341		19	max	3832.613	1	1579.444	3	0	1	0	1	0	1	0	1
342			min	-3258.835	3	57.983	15	0	1	0	1	0	1	0	1
343	M8	1	max	2120.777	1	1132.156	3	323.026	3	.04	2	.449	2	4.556	3
344			min	-1331.725	3	-887.893	2	-308.164	2	-.02	3	-.532	3	.18	10
345		2	max	1537.642	1	728.768	3	275.965	3	.001	3	.342	2	4.226	3
346			min	-1074.926	3	35.541	15	-211.431	2	-.002	2	-.422	3	.206	15
347		3	max	1534.535	1	728.768	3	275.965	3	.001	3	.27	2	3.977	3
348			min	-1077.255	3	35.541	15	-211.431	2	-.002	2	-.328	3	.194	15
349		4	max	1531.429	1	728.768	3	275.965	3	.001	3	.202	1	3.729	3
350			min	-1079.585	3	35.541	15	-211.431	2	-.002	2	-.234	3	.182	15
351		5	max	1528.323	1	728.768	3	275.965	3	.001	3	.136	1	3.48	3
352			min	-1081.915	3	35.541	15	-211.431	2	-.002	2	-.14	3	.17	15
353		6	max	1525.217	1	728.768	3	275.965	3	.001	3	.069	1	3.232	3
354			min	-1084.244	3	35.541	15	-211.431	2	-.002	2	-.046	3	.158	15
355		7	max	1522.111	1	728.768	3	275.965	3	.001	3	.048	3	2.983	3
356			min	-1086.574	3	35.541	15	-211.431	2	-.002	2	-.018	2	.145	15
357		8	max	1519.005	1	728.768	3	275.965	3	.001	3	.142	3	2.734	3
358			min	-1088.903	3	35.541	15	-211.431	2	-.002	2	-.091	2	.133	15
359		9	max	1515.899	1	728.768	3	275.965	3	.001	3	.237	3	2.486	3
360			min	-1091.233	3	35.541	15	-211.431	2	-.002	2	-.163	2	.121	15
361		10	max	1512.793	1	728.768	3	275.965	3	.001	3	.331	3	2.237	3
362			min	-1093.562	3	35.541	15	-211.431	2	-.002	2	-.235	2	.109	15
363		11	max	1509.687	1	728.768	3	275.965	3	.001	3	.425	3	1.989	3
364			min	-1095.892	3	35.541	15	-211.431	2	-.002	2	-.307	2	.097	15
365		12	max	1506.581	1	728.768	3	275.965	3	.001	3	.519	3	1.74	3
366			min	-1098.222	3	35.541	15	-211.431	2	-.002	2	-.379	2	.085	15
367		13	max	1503.475	1	728.768	3	275.965	3	.001	3	.613	3	1.492	3
368			min	-1100.551	3	35.541	15	-211.431	2	-.002	2	-.451	2	.073	15
369		14	max	1500.368	1	728.768	3	275.965	3	.001	3	.707	3	1.243	3
370			min	-1102.881	3	35.541	15	-211.431	2	-.002	2	-.523	2	.061	15
371		15	max	1497.262	1	728.768	3	275.965	3	.001	3	.801	3	.994	3
372			min	-1105.21	3	35.541	15	-211.431	2	-.002	2	-.595	2	.048	15
373		16	max	1494.156	1	728.768	3	275.965	3	.001	3	.895	3	.746	3
374			min	-1107.54	3	35.541	15	-211.431	2	-.002	2	-.668	2	.036	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
375		17	max	1491.05	1	728.768	3	275.965	3	.001	3	.99	3	.497	3
376			min	-1109.869	3	35.541	15	-211.431	2	-.002	2	-.74	2	.024	15
377		18	max	1487.944	1	728.768	3	275.965	3	.001	3	1.084	3	.249	3
378			min	-1112.199	3	35.541	15	-211.431	2	-.002	2	-.812	2	.012	15
379		19	max	1484.838	1	728.768	3	275.965	3	.001	3	1.178	3	0	1
380			min	-1114.528	3	35.541	15	-211.431	2	-.002	2	-.884	2	0	1
381	M3	1	max	1283.787	2	4.147	4	96.29	2	.007	3	.021	3	0	1
382			min	-475.733	3	.975	15	-47.337	3	-.01	2	-.043	2	0	1
383		2	max	1283.549	2	3.686	4	96.29	2	.007	3	.007	3	0	15
384			min	-475.911	3	.866	15	-47.337	3	-.01	2	-.015	2	-.001	4
385		3	max	1283.311	2	3.225	4	96.29	2	.007	3	.013	2	0	15
386			min	-476.09	3	.758	15	-47.337	3	-.01	2	-.006	3	-.002	4
387		4	max	1283.073	2	2.765	4	96.29	2	.007	3	.041	2	0	15
388			min	-476.268	3	.65	15	-47.337	3	-.01	2	-.02	3	-.003	4
389		5	max	1282.835	2	2.304	4	96.29	2	.007	3	.069	2	0	15
390			min	-476.447	3	.542	15	-47.337	3	-.01	2	-.034	3	-.004	4
391		6	max	1282.597	2	1.843	4	96.29	2	.007	3	.097	2	-.001	15
392			min	-476.625	3	.433	15	-47.337	3	-.01	2	-.048	3	-.004	4
393		7	max	1282.359	2	1.382	4	96.29	2	.007	3	.125	2	-.001	15
394			min	-476.804	3	.325	15	-47.337	3	-.01	2	-.061	3	-.005	4
395		8	max	1282.121	2	.922	4	96.29	2	.007	3	.153	2	-.001	15
396			min	-476.982	3	.217	15	-47.337	3	-.01	2	-.075	3	-.005	4
397		9	max	1281.883	2	.461	4	96.29	2	.007	3	.181	2	-.001	15
398			min	-477.161	3	.108	15	-47.337	3	-.01	2	-.089	3	-.005	4
399		10	max	1281.645	2	0	1	96.29	2	.007	3	.209	2	-.001	15
400			min	-477.339	3	0	1	-47.337	3	-.01	2	-.103	3	-.005	4
401		11	max	1281.407	2	-.108	15	96.29	2	.007	3	.237	2	-.001	15
402			min	-477.518	3	-.461	4	-47.337	3	-.01	2	-.116	3	-.005	4
403		12	max	1281.169	2	-.217	15	96.29	2	.007	3	.264	2	-.001	15
404			min	-477.696	3	-.922	4	-47.337	3	-.01	2	-.13	3	-.005	4
405		13	max	1280.931	2	-.325	15	96.29	2	.007	3	.292	2	-.001	15
406			min	-477.875	3	-1.382	4	-47.337	3	-.01	2	-.144	3	-.005	4
407		14	max	1280.693	2	-.433	15	96.29	2	.007	3	.32	2	-.001	15
408			min	-478.053	3	-1.843	4	-47.337	3	-.01	2	-.158	3	-.004	4
409		15	max	1280.455	2	-.542	15	96.29	2	.007	3	.348	2	0	15
410			min	-478.232	3	-2.304	4	-47.337	3	-.01	2	-.171	3	-.004	4
411		16	max	1280.217	2	-.65	15	96.29	2	.007	3	.376	2	0	15
412			min	-478.41	3	-2.765	4	-47.337	3	-.01	2	-.185	3	-.003	4
413		17	max	1279.979	2	-.758	15	96.29	2	.007	3	.404	2	0	15
414			min	-478.589	3	-3.225	4	-47.337	3	-.01	2	-.199	3	-.002	4
415		18	max	1279.741	2	-.866	15	96.29	2	.007	3	.432	2	0	15
416			min	-478.767	3	-3.686	4	-47.337	3	-.01	2	-.213	3	-.001	4
417		19	max	1279.503	2	-.975	15	96.29	2	.007	3	.46	2	0	1
418			min	-478.946	3	-4.147	4	-47.337	3	-.01	2	-.226	3	0	1
419	M6	1	max	3802.618	2	4.147	4	0	1	0	1	0	1	0	1
420			min	-1639.602	3	.975	15	0	1	0	1	0	1	0	1
421		2	max	3802.38	2	3.686	4	0	1	0	1	0	1	0	15
422			min	-1639.78	3	.866	15	0	1	0	1	0	1	-.001	4
423		3	max	3802.142	2	3.225	4	0	1	0	1	0	1	0	15
424			min	-1639.959	3	.758	15	0	1	0	1	0	1	-.002	4
425		4	max	3801.904	2	2.765	4	0	1	0	1	0	1	0	15
426			min	-1640.137	3	.65	15	0	1	0	1	0	1	-.003	4
427		5	max	3801.666	2	2.304	4	0	1	0	1	0	1	0	15
428			min	-1640.316	3	.542	15	0	1	0	1	0	1	-.004	4
429		6	max	3801.428	2	1.843	4	0	1	0	1	0	1	-.001	15
430			min	-1640.494	3	.433	15	0	1	0	1	0	1	-.004	4
431		7	max	3801.19	2	1.382	4	0	1	0	1	0	1	-.001	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
432			min	-1640.673	3	.325	15	0	1	0	1	0	1	-.005	4
433		8	max	3800.952	2	.922	4	0	1	0	1	0	1	-.001	15
434			min	-1640.851	3	.217	15	0	1	0	1	0	1	-.005	4
435		9	max	3800.714	2	.461	4	0	1	0	1	0	1	-.001	15
436			min	-1641.03	3	.108	15	0	1	0	1	0	1	-.005	4
437		10	max	3800.476	2	0	1	0	1	0	1	0	1	-.001	15
438			min	-1641.208	3	0	1	0	1	0	1	0	1	-.005	4
439		11	max	3800.238	2	-.108	15	0	1	0	1	0	1	-.001	15
440			min	-1641.387	3	-.461	4	0	1	0	1	0	1	-.005	4
441		12	max	3800	2	-.217	15	0	1	0	1	0	1	-.001	15
442			min	-1641.565	3	-.922	4	0	1	0	1	0	1	-.005	4
443		13	max	3799.762	2	-.325	15	0	1	0	1	0	1	-.001	15
444			min	-1641.744	3	-1.382	4	0	1	0	1	0	1	-.005	4
445		14	max	3799.524	2	-.433	15	0	1	0	1	0	1	-.001	15
446			min	-1641.922	3	-1.843	4	0	1	0	1	0	1	-.004	4
447		15	max	3799.286	2	-.542	15	0	1	0	1	0	1	0	15
448			min	-1642.101	3	-2.304	4	0	1	0	1	0	1	-.004	4
449		16	max	3799.048	2	-.65	15	0	1	0	1	0	1	0	15
450			min	-1642.279	3	-2.765	4	0	1	0	1	0	1	-.003	4
451		17	max	3798.81	2	-.758	15	0	1	0	1	0	1	0	15
452			min	-1642.458	3	-3.225	4	0	1	0	1	0	1	-.002	4
453		18	max	3798.572	2	-.866	15	0	1	0	1	0	1	0	15
454			min	-1642.636	3	-3.686	4	0	1	0	1	0	1	-.001	4
455		19	max	3798.334	2	-.975	15	0	1	0	1	0	1	0	1
456			min	-1642.815	3	-4.147	4	0	1	0	1	0	1	0	1
457	M9	1	max	1283.787	2	4.147	4	47.337	3	.01	2	.043	2	0	1
458			min	-475.733	3	.975	15	-96.29	2	-.007	3	-.021	3	0	1
459		2	max	1283.549	2	3.686	4	47.337	3	.01	2	.015	2	0	15
460			min	-475.911	3	.866	15	-96.29	2	-.007	3	-.007	3	-.001	4
461		3	max	1283.311	2	3.225	4	47.337	3	.01	2	.006	3	0	15
462			min	-476.09	3	.758	15	-96.29	2	-.007	3	-.013	2	-.002	4
463		4	max	1283.073	2	2.765	4	47.337	3	.01	2	.02	3	0	15
464			min	-476.268	3	.65	15	-96.29	2	-.007	3	-.041	2	-.003	4
465		5	max	1282.835	2	2.304	4	47.337	3	.01	2	.034	3	0	15
466			min	-476.447	3	.542	15	-96.29	2	-.007	3	-.069	2	-.004	4
467		6	max	1282.597	2	1.843	4	47.337	3	.01	2	.048	3	-.001	15
468			min	-476.625	3	.433	15	-96.29	2	-.007	3	-.097	2	-.004	4
469		7	max	1282.359	2	1.382	4	47.337	3	.01	2	.061	3	-.001	15
470			min	-476.804	3	.325	15	-96.29	2	-.007	3	-.125	2	-.005	4
471		8	max	1282.121	2	.922	4	47.337	3	.01	2	.075	3	-.001	15
472			min	-476.982	3	.217	15	-96.29	2	-.007	3	-.153	2	-.005	4
473		9	max	1281.883	2	.461	4	47.337	3	.01	2	.089	3	-.001	15
474			min	-477.161	3	.108	15	-96.29	2	-.007	3	-.181	2	-.005	4
475		10	max	1281.645	2	0	1	47.337	3	.01	2	.103	3	-.001	15
476			min	-477.339	3	0	1	-96.29	2	-.007	3	-.209	2	-.005	4
477		11	max	1281.407	2	-.108	15	47.337	3	.01	2	.116	3	-.001	15
478			min	-477.518	3	-.461	4	-96.29	2	-.007	3	-.237	2	-.005	4
479		12	max	1281.169	2	-.217	15	47.337	3	.01	2	.13	3	-.001	15
480			min	-477.696	3	-.922	4	-96.29	2	-.007	3	-.264	2	-.005	4
481		13	max	1280.931	2	-.325	15	47.337	3	.01	2	.144	3	-.001	15
482			min	-477.875	3	-1.382	4	-96.29	2	-.007	3	-.292	2	-.005	4
483		14	max	1280.693	2	-.433	15	47.337	3	.01	2	.158	3	-.001	15
484			min	-478.053	3	-1.843	4	-96.29	2	-.007	3	-.32	2	-.004	4
485		15	max	1280.455	2	-.542	15	47.337	3	.01	2	.171	3	0	15
486			min	-478.232	3	-2.304	4	-96.29	2	-.007	3	-.348	2	-.004	4
487		16	max	1280.217	2	-.65	15	47.337	3	.01	2	.185	3	0	15
488			min	-478.41	3	-2.765	4	-96.29	2	-.007	3	-.376	2	-.003	4

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
489		17	max	1279.979	2	-.758	15	47.337	3	.01	2	.199	3	0	15
490			min	-478.589	3	-3.225	4	-96.29	2	-.007	3	-.404	2	-.002	4
491		18	max	1279.741	2	-.866	15	47.337	3	.01	2	.213	3	0	15
492			min	-478.767	3	-3.686	4	-96.29	2	-.007	3	-.432	2	-.001	4
493		19	max	1279.503	2	-.975	15	47.337	3	.01	2	.226	3	0	1
494			min	-478.946	3	-4.147	4	-96.29	2	-.007	3	-.46	2	0	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M1	1	max	-.012	15	-.018	15	.033	1	1.18e-2	3	NC	3	NC	3
2			min	-.252	3	-.38	1	.002	15	-2.83e-2	2	324.01	1	2108.665	1
3		2	max	-.012	15	-.015	15	.01	1	1.18e-2	3	NC	3	NC	3
4			min	-.252	3	-.308	1	0	15	-2.83e-2	2	392.567	1	3286.442	1
5		3	max	-.012	15	-.012	15	0	15	1.114e-2	3	NC	3	NC	2
6			min	-.252	3	-.236	1	-.01	1	-2.604e-2	2	498.096	1	6376.727	1
7		4	max	-.012	15	-.009	15	0	15	1.014e-2	3	NC	3	NC	1
8			min	-.252	3	-.166	1	-.019	1	-2.257e-2	2	671.292	1	NC	1
9		5	max	-.012	15	-.006	15	0	12	9.136e-3	3	NC	3	NC	1
10			min	-.252	3	-.104	1	-.019	1	-1.909e-2	2	850.249	9	NC	1
11		6	max	-.012	15	-.002	10	.001	3	9.65e-3	3	NC	11	NC	2
12			min	-.252	3	-.087	3	-.015	1	-1.87e-2	2	1021.493	2	8344.665	1
13		7	max	-.012	15	.009	2	.002	3	1.121e-2	3	NC	15	NC	2
14			min	-.252	3	-.069	3	-.007	1	-2.043e-2	2	866.643	2	5572.324	1
15		8	max	-.012	15	.024	2	.001	3	1.278e-2	3	NC	5	NC	2
16			min	-.252	3	-.045	3	-.002	2	-2.216e-2	2	792.889	2	4411.988	1
17		9	max	-.012	15	.04	1	0	15	1.435e-2	3	NC	1	NC	2
18			min	-.252	3	-.019	3	0	2	-2.232e-2	2	747.355	2	4403.528	1
19		10	max	-.012	15	.065	1	0	3	1.596e-2	3	NC	5	NC	2
20			min	-.252	3	.003	15	0	2	-1.973e-2	2	711.567	2	4347.766	1
21		11	max	-.012	15	.089	1	.003	3	1.757e-2	3	NC	5	NC	2
22			min	-.252	3	.005	15	-.002	2	-1.713e-2	2	686.265	2	4595.05	1
23		12	max	-.012	15	.109	1	.008	3	1.464e-2	3	NC	4	NC	2
24			min	-.252	3	.006	15	-.008	1	-1.3e-2	2	671.293	2	5815.613	1
25		13	max	-.012	15	.125	1	.014	3	9.155e-3	3	NC	4	NC	2
26			min	-.252	3	.008	15	-.009	2	-7.996e-3	2	584.303	3	5771.645	1
27		14	max	-.012	15	.18	3	.011	3	3.925e-3	3	NC	4	NC	2
28			min	-.252	3	.009	15	-.004	2	-3.185e-3	2	466.635	3	4101.929	1
29		15	max	-.012	15	.257	3	.013	1	1.006e-2	3	NC	4	NC	3
30			min	-.252	3	-.005	10	0	15	-6.911e-3	2	367.663	3	3037.885	1
31		16	max	-.012	15	.349	3	.017	1	1.62e-2	3	NC	4	NC	3
32			min	-.252	3	-.026	10	0	15	-1.064e-2	2	293.649	3	2811.361	1
33		17	max	-.012	15	.45	3	.01	1	2.234e-2	3	NC	4	NC	3
34			min	-.252	3	-.058	2	0	12	-1.436e-2	2	240.42	3	3282.245	1
35		18	max	-.012	15	.555	3	0	15	2.634e-2	3	NC	4	NC	2
36			min	-.252	3	-.102	2	-.009	1	-1.679e-2	2	202.427	3	6108.136	1
37		19	max	-.012	15	.659	3	-.002	15	2.634e-2	3	NC	1	NC	1
38			min	-.252	3	-.145	2	-.031	1	-1.679e-2	2	174.83	3	NC	1
39	M4	1	max	-.02	15	-.035	15	0	1	0	1	NC	3	NC	1
40			min	-.544	3	-.85	1	0	1	0	1	193.849	1	NC	1
41		2	max	-.02	15	-.029	15	0	1	0	1	NC	10	NC	1
42			min	-.544	3	-.679	1	0	1	0	1	257.863	1	NC	1
43		3	max	-.02	15	-.022	15	0	1	0	1	5856.822	12	NC	1
44			min	-.544	3	-.507	1	0	1	0	1	385.516	1	NC	1
45		4	max	-.02	15	-.016	15	0	1	0	1	6092.594	15	NC	1
46			min	-.544	3	-.342	1	0	1	0	1	541.932	9	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
47		5	max	-.02	15	-.011	15	0	1	0	1	8180.229	15	NC	1
48			min	-.544	3	-.206	3	0	1	0	1	376.386	2	NC	1
49		6	max	-.02	15	0	10	0	1	0	1	NC	15	NC	1
50			min	-.545	3	-.19	3	0	1	0	1	298.841	2	NC	1
51		7	max	-.02	15	.034	2	0	1	0	1	NC	3	NC	1
52			min	-.545	3	-.154	3	0	1	0	1	268.044	2	NC	1
53		8	max	-.02	15	.06	2	0	1	0	1	NC	5	NC	1
54			min	-.545	3	-.105	3	0	1	0	1	254.697	2	NC	1
55		9	max	-.02	15	.085	1	0	1	0	1	NC	4	NC	1
56			min	-.545	3	-.048	3	0	1	0	1	247.245	2	NC	1
57		10	max	-.02	15	.129	1	0	1	0	1	NC	4	NC	1
58			min	-.545	3	.006	15	0	1	0	1	240.957	2	NC	1
59		11	max	-.02	15	.169	1	0	1	0	1	NC	5	NC	1
60			min	-.546	3	.009	15	0	1	0	1	236.539	2	NC	1
61		12	max	-.02	15	.203	1	0	1	0	1	NC	5	NC	1
62			min	-.546	3	.011	15	0	1	0	1	234.29	2	NC	1
63		13	max	-.02	15	.257	3	0	1	0	1	NC	5	NC	1
64			min	-.546	3	.013	15	0	1	0	1	237.592	2	NC	1
65		14	max	-.02	15	.391	3	0	1	0	1	NC	5	NC	1
66			min	-.546	3	.012	10	0	1	0	1	251.153	3	NC	1
67		15	max	-.02	15	.575	3	0	1	0	1	NC	5	NC	1
68			min	-.546	3	-.03	10	0	1	0	1	186.648	3	NC	1
69		16	max	-.02	15	.797	3	0	1	0	1	NC	5	NC	1
70			min	-.546	3	-.107	2	0	1	0	1	142.537	3	NC	1
71		17	max	-.02	15	1.043	3	0	1	0	1	NC	5	NC	1
72			min	-.546	3	-.223	2	0	1	0	1	113.022	3	NC	1
73		18	max	-.02	15	1.297	3	0	1	0	1	NC	4	NC	1
74			min	-.546	3	-.345	2	0	1	0	1	93.085	3	NC	1
75		19	max	-.02	15	1.55	3	0	1	0	1	NC	1	NC	1
76			min	-.546	3	-.467	2	0	1	0	1	79.153	3	NC	1
77	M7	1	max	-.012	15	-.018	15	-.002	15	2.83e-2	2	NC	3	NC	3
78			min	-.252	3	-.38	1	-.033	1	-1.18e-2	3	324.01	1	2108.665	1
79		2	max	-.012	15	-.015	15	0	15	2.83e-2	2	NC	3	NC	3
80			min	-.252	3	-.308	1	-.01	1	-1.18e-2	3	392.567	1	3286.442	1
81		3	max	-.012	15	-.012	15	.01	1	2.604e-2	2	NC	3	NC	2
82			min	-.252	3	-.236	1	0	15	-1.114e-2	3	498.096	1	6376.727	1
83		4	max	-.012	15	-.009	15	.019	1	2.257e-2	2	NC	3	NC	1
84			min	-.252	3	-.166	1	0	15	-1.014e-2	3	671.292	1	NC	1
85		5	max	-.012	15	-.006	15	.019	1	1.909e-2	2	NC	3	NC	1
86			min	-.252	3	-.104	1	0	12	-9.136e-3	3	850.249	9	NC	1
87		6	max	-.012	15	-.002	10	.015	1	1.87e-2	2	NC	11	NC	2
88			min	-.252	3	-.087	3	-.001	3	-9.65e-3	3	1021.493	2	8344.665	1
89		7	max	-.012	15	.009	2	.007	1	2.043e-2	2	NC	15	NC	2
90			min	-.252	3	-.069	3	-.002	3	-1.121e-2	3	866.643	2	5572.324	1
91		8	max	-.012	15	.024	2	.002	2	2.216e-2	2	NC	5	NC	2
92			min	-.252	3	-.045	3	-.001	3	-1.278e-2	3	792.889	2	4411.988	1
93		9	max	-.012	15	.04	1	0	2	2.232e-2	2	NC	1	NC	2
94			min	-.252	3	-.019	3	0	15	-1.435e-2	3	747.355	2	4403.528	1
95		10	max	-.012	15	.065	1	0	2	1.973e-2	2	NC	5	NC	2
96			min	-.252	3	.003	15	0	3	-1.596e-2	3	711.567	2	4347.766	1
97		11	max	-.012	15	.089	1	.002	2	1.713e-2	2	NC	5	NC	2
98			min	-.252	3	.005	15	-.003	3	-1.757e-2	3	686.265	2	4595.05	1
99		12	max	-.012	15	.109	1	.008	1	1.3e-2	2	NC	4	NC	2
100			min	-.252	3	.006	15	-.008	3	-1.464e-2	3	671.293	2	5815.613	1
101		13	max	-.012	15	.125	1	.009	2	7.996e-3	2	NC	4	NC	2
102			min	-.252	3	.008	15	-.014	3	-9.155e-3	3	584.303	3	5771.645	1
103		14	max	-.012	15	.18	3	.004	2	3.185e-3	2	NC	4	NC	2

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
104			min	-.252	3	.009	15	-.011	3	-3.925e-3	3	466.635	3	4101.929	1
105		15	max	-.012	15	.257	3	0	15	6.911e-3	2	NC	4	NC	3
106			min	-.252	3	-.005	10	-.013	1	-1.006e-2	3	367.663	3	3037.885	1
107		16	max	-.012	15	.349	3	0	15	1.064e-2	2	NC	4	NC	3
108			min	-.252	3	-.026	10	-.017	1	-1.62e-2	3	293.649	3	2811.361	1
109		17	max	-.012	15	.45	3	0	12	1.436e-2	2	NC	4	NC	3
110			min	-.252	3	-.058	2	-.01	1	-2.234e-2	3	240.42	3	3282.245	1
111		18	max	-.012	15	.555	3	.009	1	1.679e-2	2	NC	4	NC	2
112			min	-.252	3	-.102	2	0	15	-2.634e-2	3	202.427	3	6108.136	1
113		19	max	-.012	15	.659	3	.031	1	1.679e-2	2	NC	1	NC	1
114			min	-.252	3	-.145	2	.002	15	-2.634e-2	3	174.83	3	NC	1
115	M10	1	max	.001	3	.518	3	.252	3	1.404e-2	3	NC	1	NC	1
116			min	0	10	-.087	2	.012	15	-5.838e-3	2	NC	1	NC	1
117		2	max	.001	3	.957	3	.282	1	1.626e-2	3	NC	5	NC	3
118			min	0	10	-.364	2	.017	15	-7.006e-3	2	656.765	3	3144.658	1
119		3	max	.001	3	1.366	3	.417	1	1.848e-2	3	NC	5	NC	5
120			min	0	10	-.617	2	.025	15	-8.174e-3	2	339.561	3	1272.915	1
121		4	max	0	3	1.675	3	.54	1	2.07e-2	3	NC	15	NC	15
122			min	0	10	-.795	2	.032	15	-9.342e-3	2	249.06	3	824.507	1
123		5	max	0	3	1.84	3	.615	1	2.293e-2	3	NC	15	NC	15
124			min	0	10	-.871	2	.036	15	-1.051e-2	2	217.965	3	678.14	1
125		6	max	0	3	1.85	3	.625	1	2.515e-2	3	NC	15	NC	15
126			min	0	10	-.841	2	.037	15	-1.168e-2	2	216.207	3	661.973	1
127		7	max	0	3	1.727	3	.572	1	2.737e-2	3	NC	5	NC	15
128			min	0	10	-.72	2	.034	15	-1.285e-2	2	238.336	3	754.47	1
129		8	max	0	3	1.519	3	.525	3	2.959e-2	3	NC	5	NC	5
130			min	0	10	-.546	2	.029	15	-1.401e-2	2	287.753	3	1011.749	1
131		9	max	0	3	1.309	3	.541	3	3.181e-2	3	NC	4	NC	5
132			min	0	10	-.38	2	.023	15	-1.518e-2	2	364.154	3	996.742	3
133		10	max	0	1	1.209	3	.546	3	3.404e-2	3	NC	4	NC	5
134			min	0	1	-.302	2	.02	15	-1.635e-2	2	417.038	3	979.241	3
135		11	max	0	10	1.309	3	.541	3	3.181e-2	3	NC	4	NC	5
136			min	0	3	-.38	2	.023	15	-1.518e-2	2	364.154	3	996.742	3
137		12	max	0	10	1.519	3	.525	3	2.959e-2	3	NC	5	NC	5
138			min	0	3	-.546	2	.029	15	-1.401e-2	2	287.753	3	1011.749	1
139		13	max	0	10	1.727	3	.572	1	2.737e-2	3	NC	5	NC	15
140			min	0	3	-.72	2	.034	15	-1.285e-2	2	238.336	3	754.47	1
141		14	max	0	10	1.85	3	.625	1	2.515e-2	3	NC	15	NC	15
142			min	0	3	-.841	2	.037	15	-1.168e-2	2	216.207	3	661.973	1
143		15	max	0	10	1.84	3	.615	1	2.293e-2	3	NC	15	NC	15
144			min	0	3	-.871	2	.036	15	-1.051e-2	2	217.965	3	678.14	1
145		16	max	0	10	1.675	3	.54	1	2.07e-2	3	NC	15	NC	15
146			min	0	3	-.795	2	.032	15	-9.342e-3	2	249.06	3	824.507	1
147		17	max	0	10	1.366	3	.417	1	1.848e-2	3	NC	5	NC	5
148			min	-.001	3	-.617	2	.025	15	-8.174e-3	2	339.561	3	1272.915	1
149		18	max	0	10	.957	3	.282	1	1.626e-2	3	NC	5	NC	3
150			min	-.001	3	-.364	2	.017	15	-7.006e-3	2	656.765	3	3144.658	1
151		19	max	0	10	.518	3	.252	3	1.404e-2	3	NC	1	NC	1
152			min	-.001	3	-.087	2	.012	15	-5.838e-3	2	NC	1	NC	1
153	M11	1	max	.004	1	.096	1	.252	3	4.77e-3	3	NC	1	NC	1
154			min	-.004	3	.005	15	.012	15	3.528e-5	10	NC	1	NC	1
155		2	max	.003	1	.368	3	.259	1	5.381e-3	3	NC	5	NC	3
156			min	-.004	3	-.209	2	.016	15	1.666e-5	10	919.659	3	4224.66	1
157		3	max	.003	1	.664	3	.382	1	5.992e-3	3	NC	5	NC	5
158			min	-.003	3	-.433	2	.023	15	-1.947e-6	10	472.603	3	1511.99	1
159		4	max	.003	1	.872	3	.501	1	6.602e-3	3	NC	15	NC	5
160			min	-.003	3	-.574	2	.029	15	-2.056e-5	10	352.565	3	929.036	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
161		5	max	.002	1	.949	3	.58	1	7.213e-3	3	NC	15	NC	15
162			min	-.002	3	-.609	2	.034	15	-3.917e-5	10	321.945	3	741.341	1
163		6	max	.002	1	.887	3	.598	1	7.824e-3	3	NC	5	NC	15
164			min	-.002	3	-.537	2	.035	15	-5.778e-5	10	346.061	3	708.731	1
165		7	max	.001	1	.705	3	.554	1	8.434e-3	3	NC	5	NC	15
166			min	-.001	3	-.377	2	.033	15	-7.639e-5	10	442.809	3	794.009	1
167		8	max	0	1	.455	3	.518	3	9.045e-3	3	NC	5	NC	5
168			min	0	3	-.171	2	.028	15	-9.501e-5	10	719.263	3	1046.06	1
169		9	max	0	1	.219	3	.539	3	9.656e-3	3	NC	1	NC	5
170			min	0	3	-.002	10	.023	15	-1.136e-4	10	1751.917	3	1004.411	3
171		10	max	0	1	.182	1	.546	3	1.027e-2	3	NC	4	NC	5
172			min	0	1	.01	15	.02	15	-1.322e-4	10	3368.089	1	980.831	3
173		11	max	0	3	.219	3	.539	3	9.656e-3	3	NC	1	NC	5
174			min	0	1	-.002	10	.023	15	-1.136e-4	10	1751.917	3	1004.411	3
175		12	max	0	3	.455	3	.518	3	9.045e-3	3	NC	5	NC	5
176			min	0	1	-.171	2	.028	15	-9.501e-5	10	719.263	3	1046.06	1
177		13	max	.001	3	.705	3	.554	1	8.434e-3	3	NC	5	NC	15
178			min	-.001	1	-.377	2	.033	15	-7.639e-5	10	442.809	3	794.009	1
179		14	max	.002	3	.887	3	.598	1	7.824e-3	3	NC	5	NC	15
180			min	-.002	1	-.537	2	.035	15	-5.778e-5	10	346.061	3	708.731	1
181		15	max	.002	3	.949	3	.58	1	7.213e-3	3	NC	15	NC	15
182			min	-.002	1	-.609	2	.034	15	-3.917e-5	10	321.945	3	741.341	1
183		16	max	.003	3	.872	3	.501	1	6.602e-3	3	NC	15	NC	5
184			min	-.003	1	-.574	2	.029	15	-2.056e-5	10	352.565	3	929.036	1
185		17	max	.003	3	.664	3	.382	1	5.992e-3	3	NC	5	NC	5
186			min	-.003	1	-.433	2	.023	15	-1.947e-6	10	472.603	3	1511.99	1
187		18	max	.004	3	.368	3	.259	1	5.381e-3	3	NC	5	NC	3
188			min	-.003	1	-.209	2	.016	15	1.666e-5	10	919.659	3	4224.66	1
189		19	max	.004	3	.096	1	.252	3	4.77e-3	3	NC	1	NC	1
190			min	-.004	1	.005	15	.012	15	3.528e-5	10	NC	1	NC	1
191	M12	1	max	0	2	.031	1	.252	3	3.597e-3	3	NC	1	NC	1
192			min	0	3	-.029	3	.012	15	2.254e-4	15	NC	1	NC	1
193		2	max	0	2	.183	3	.269	3	4.055e-3	3	NC	5	NC	2
194			min	0	3	-.348	2	.016	15	2.42e-4	15	760.412	2	4902.355	1
195		3	max	0	2	.354	3	.368	1	4.513e-3	3	NC	5	NC	5
196			min	0	3	-.679	2	.022	15	2.586e-4	15	405.966	2	1635.09	1
197		4	max	0	2	.455	3	.486	1	4.971e-3	3	NC	15	NC	5
198			min	0	3	-.893	2	.029	15	2.752e-4	15	312.029	2	978.455	1
199		5	max	0	2	.474	3	.566	1	5.428e-3	3	NC	15	NC	15
200			min	0	3	-.952	2	.033	15	2.918e-4	15	293.039	2	769.632	1
201		6	max	0	2	.413	3	.587	1	5.886e-3	3	NC	15	NC	15
202			min	0	3	-.854	2	.035	15	3.084e-4	15	325.566	2	728.668	1
203		7	max	0	2	.289	3	.548	1	6.344e-3	3	NC	5	NC	15
204			min	0	3	-.626	2	.033	15	3.25e-4	15	438.653	2	809.812	1
205		8	max	0	2	.134	3	.522	3	6.802e-3	3	NC	5	NC	5
206			min	0	3	-.329	2	.028	15	3.416e-4	15	801.848	2	1057.842	1
207		9	max	0	2	0	15	.54	3	7.26e-3	3	NC	3	NC	5
208			min	0	3	-.055	2	.023	15	3.582e-4	15	3372.736	2	1001.436	3
209		10	max	0	1	.07	2	.545	3	7.718e-3	3	NC	4	NC	5
210			min	0	1	-.069	3	.02	15	3.748e-4	15	7217.768	3	982.464	3
211		11	max	0	3	0	15	.54	3	7.26e-3	3	NC	3	NC	5
212			min	0	2	-.055	2	.023	15	3.582e-4	15	3372.736	2	1001.436	3
213		12	max	0	3	.134	3	.522	3	6.802e-3	3	NC	5	NC	5
214			min	0	2	-.329	2	.028	15	3.416e-4	15	801.848	2	1057.842	1
215		13	max	0	3	.289	3	.548	1	6.344e-3	3	NC	5	NC	15
216			min	0	2	-.626	2	.033	15	3.25e-4	15	438.653	2	809.812	1
217		14	max	0	3	.413	3	.587	1	5.886e-3	3	NC	15	NC	15

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
218			min	0	2	-.854	2	.035	15	3.084e-4	15	325.566	2	728.668	1
219		15	max	0	3	.474	3	.566	1	5.428e-3	3	NC	15	NC	15
220			min	0	2	-.952	2	.033	15	2.918e-4	15	293.039	2	769.632	1
221		16	max	0	3	.455	3	.486	1	4.971e-3	3	NC	15	NC	5
222			min	0	2	-.893	2	.029	15	2.752e-4	15	312.029	2	978.455	1
223		17	max	0	3	.354	3	.368	1	4.513e-3	3	NC	5	NC	5
224			min	0	2	-.679	2	.022	15	2.586e-4	15	405.966	2	1635.09	1
225		18	max	0	3	.183	3	.269	3	4.055e-3	3	NC	5	NC	2
226			min	0	2	-.348	2	.016	15	2.42e-4	15	760.412	2	4902.355	1
227		19	max	0	3	.031	1	.252	3	3.597e-3	3	NC	1	NC	1
228			min	0	2	-.029	3	.012	15	2.254e-4	15	NC	1	NC	1
229	M13	1	max	0	15	-.014	15	.252	3	9.701e-3	1	NC	1	NC	1
230			min	-.002	1	-.283	1	.012	15	5.602e-5	3	NC	1	NC	1
231		2	max	0	15	.079	3	.286	1	1.118e-2	1	NC	5	NC	3
232			min	-.002	1	-.667	1	.018	15	-2.596e-4	3	633.681	2	3092.333	1
233		3	max	0	15	.234	3	.422	1	1.267e-2	1	NC	15	NC	5
234			min	-.002	1	-1.06	2	.025	15	-5.751e-4	3	338.363	2	1258.157	1
235		4	max	0	15	.328	3	.546	1	1.415e-2	1	NC	15	NC	15
236			min	-.001	1	-1.33	2	.032	15	-8.907e-4	3	256.87	2	816.599	1
237		5	max	0	15	.347	3	.622	1	1.563e-2	1	9241.86	15	NC	15
238			min	-.001	1	-1.437	2	.036	15	-1.206e-3	3	234.496	2	672.115	1
239		6	max	0	15	.289	3	.632	1	1.712e-2	1	9425.603	15	NC	15
240			min	0	1	-1.376	2	.037	15	-1.522e-3	3	246.565	2	655.947	1
241		7	max	0	15	.172	3	.579	1	1.86e-2	1	NC	15	NC	15
242			min	0	1	-1.178	2	.034	15	-1.837e-3	3	297.147	2	746.605	1
243		8	max	0	15	.024	3	.523	3	2.008e-2	1	NC	15	NC	5
244			min	0	1	-.926	1	.029	15	-2.153e-3	3	415.928	2	997.895	1
245		9	max	0	15	-.029	15	.539	3	2.157e-2	1	NC	3	NC	5
246			min	0	1	-.716	1	.023	15	-2.469e-3	3	664.774	1	1001.521	3
247		10	max	0	1	-.027	15	.544	3	2.305e-2	1	NC	5	NC	5
248			min	0	1	-.619	1	.02	15	-2.784e-3	3	857.45	1	984.392	3
249		11	max	0	1	-.029	15	.539	3	2.157e-2	1	NC	3	NC	5
250			min	0	15	-.716	1	.023	15	-2.469e-3	3	664.774	1	1001.521	3
251		12	max	0	1	.024	3	.523	3	2.008e-2	1	NC	15	NC	5
252			min	0	15	-.926	1	.029	15	-2.153e-3	3	415.928	2	997.895	1
253		13	max	0	1	.172	3	.579	1	1.86e-2	1	NC	15	NC	15
254			min	0	15	-1.178	2	.034	15	-1.837e-3	3	297.147	2	746.605	1
255		14	max	0	1	.289	3	.632	1	1.712e-2	1	9425.603	15	NC	15
256			min	0	15	-1.376	2	.037	15	-1.522e-3	3	246.565	2	655.947	1
257		15	max	.001	1	.347	3	.622	1	1.563e-2	1	9241.86	15	NC	15
258			min	0	15	-1.437	2	.036	15	-1.206e-3	3	234.496	2	672.115	1
259		16	max	.001	1	.328	3	.546	1	1.415e-2	1	NC	15	NC	15
260			min	0	15	-1.33	2	.032	15	-8.907e-4	3	256.87	2	816.599	1
261		17	max	.002	1	.234	3	.422	1	1.267e-2	1	NC	15	NC	5
262			min	0	15	-1.06	2	.025	15	-5.751e-4	3	338.363	2	1258.157	1
263		18	max	.002	1	.079	3	.286	1	1.118e-2	1	NC	5	NC	3
264			min	0	15	-.667	1	.018	15	-2.596e-4	3	633.681	2	3092.333	1
265		19	max	.002	1	-.014	15	.252	3	9.701e-3	1	NC	1	NC	1
266			min	0	15	-.283	1	.012	15	5.602e-5	3	NC	1	NC	1
267	M2	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
268			min	0	1	0	1	0	1	0	1	NC	1	NC	1
269		2	max	0	3	0	10	0	3	7.712e-3	2	NC	1	NC	1
270			min	0	1	-.002	3	0	2	-3.827e-3	3	NC	1	NC	1
271		3	max	0	3	0	15	.002	3	7.079e-3	2	NC	1	NC	1
272			min	0	1	-.006	3	-.001	2	-3.41e-3	3	NC	1	NC	1
273		4	max	0	3	0	15	.003	3	6.446e-3	2	NC	2	NC	1
274			min	0	1	-.013	3	-.003	2	-2.992e-3	3	5892.118	3	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
275		5	max	0	3	-.001	15	.005	3	5.813e-3	2	NC	2	NC	1
276			min	0	1	-.022	3	-.004	2	-2.575e-3	3	3412.291	3	9412.243	3
277		6	max	0	3	-.002	15	.008	3	5.18e-3	2	NC	5	NC	1
278			min	0	1	-.033	3	-.006	2	-2.157e-3	3	2240.624	3	6869.926	3
279		7	max	0	3	-.002	15	.01	3	4.548e-3	2	NC	5	NC	4
280			min	0	1	-.046	3	-.008	2	-1.74e-3	3	1594.071	3	5379.617	3
281		8	max	0	3	-.003	15	.012	3	3.915e-3	2	NC	5	NC	4
282			min	0	1	-.061	3	-.01	1	-1.322e-3	3	1198.89	3	4441.368	3
283		9	max	0	3	-.004	15	.014	3	3.282e-3	2	NC	5	NC	4
284			min	0	1	-.078	3	-.012	1	-9.046e-4	3	939.49	3	3826.886	3
285		10	max	0	3	-.005	15	.016	3	2.649e-3	2	NC	5	NC	4
286			min	0	1	-.097	3	-.014	1	-4.87e-4	3	759.842	3	3421.144	3
287		11	max	0	3	-.006	15	.017	3	2.017e-3	2	NC	15	NC	4
288			min	0	1	-.117	3	-.015	1	-6.953e-5	3	630.143	3	3163.757	3
289		12	max	0	3	-.007	15	.017	3	1.384e-3	2	NC	15	NC	4
290			min	-.001	1	-.138	3	-.016	1	-5.372e-5	9	533.359	3	3024.793	3
291		13	max	0	3	-.008	15	.017	3	7.655e-4	3	9446.266	15	NC	4
292			min	-.001	1	-.16	3	-.016	1	-2.697e-4	9	459.171	3	2995.671	3
293		14	max	0	3	-.009	15	.015	3	1.183e-3	3	8248.117	15	NC	4
294			min	-.001	1	-.184	3	-.016	1	-5.119e-4	1	401.017	3	3090.361	3
295		15	max	0	3	-.01	15	.013	3	1.601e-3	3	7291.9	15	NC	4
296			min	-.001	1	-.208	3	-.015	1	-1.083e-3	1	354.591	3	3356.604	3
297		16	max	.001	3	-.011	15	.009	3	2.018e-3	3	6516.628	15	NC	4
298			min	-.001	1	-.232	3	-.013	1	-1.653e-3	1	316.938	3	3925.011	3
299		17	max	.001	3	-.013	15	.004	3	2.436e-3	3	5879.544	15	NC	4
300			min	-.002	1	-.258	3	-.01	1	-2.224e-3	1	285.989	3	5205.426	3
301		18	max	.001	3	-.014	15	0	15	2.853e-3	3	5349.958	15	NC	1
302			min	-.002	1	-.283	3	-.007	1	-2.795e-3	1	260.257	3	9270.887	3
303		19	max	.001	3	-.015	15	.004	2	3.271e-3	3	4905.373	15	NC	1
304			min	-.002	1	-.309	3	-.012	3	-3.365e-3	1	238.651	3	NC	1
305	M5	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
306			min	0	1	0	1	0	1	0	1	NC	1	NC	1
307		2	max	0	3	0	10	0	1	0	1	NC	1	NC	1
308			min	0	1	-.003	3	0	1	0	1	NC	1	NC	1
309		3	max	0	3	0	10	0	1	0	1	NC	1	NC	1
310			min	0	1	-.013	3	0	1	0	1	5843.2	3	NC	1
311		4	max	0	3	0	10	0	1	0	1	NC	2	NC	1
312			min	0	1	-.027	3	0	1	0	1	2707.906	3	NC	1
313		5	max	0	3	-.001	10	0	1	0	1	NC	5	NC	1
314			min	-.001	1	-.047	3	0	1	0	1	1570.171	3	NC	1
315		6	max	.001	3	-.002	10	0	1	0	1	NC	5	NC	1
316			min	-.001	1	-.071	3	0	1	0	1	1031.702	3	NC	1
317		7	max	.001	3	-.003	10	0	1	0	1	NC	5	NC	1
318			min	-.002	1	-.1	3	0	1	0	1	734.286	3	NC	1
319		8	max	.001	3	-.005	10	0	1	0	1	NC	10	NC	1
320			min	-.002	1	-.133	3	0	1	0	1	552.398	3	NC	1
321		9	max	.002	3	-.006	10	0	1	0	1	NC	10	NC	1
322			min	-.002	1	-.17	3	0	1	0	1	432.959	3	NC	1
323		10	max	.002	3	-.008	15	0	1	0	1	9606.818	15	NC	1
324			min	-.002	1	-.21	3	0	1	0	1	350.217	3	NC	1
325		11	max	.002	3	-.009	15	0	1	0	1	7962.396	15	NC	1
326			min	-.003	1	-.254	3	0	1	0	1	290.469	3	NC	1
327		12	max	.002	3	-.011	15	0	1	0	1	6736.376	15	NC	1
328			min	-.003	1	-.3	3	0	1	0	1	245.876	3	NC	1
329		13	max	.002	3	-.013	15	0	1	0	1	5797.256	15	NC	1
330			min	-.003	1	-.348	3	0	1	0	1	211.69	3	NC	1
331		14	max	.003	3	-.015	15	0	1	0	1	5061.535	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
332			min	-.003	1	-.399	3	0	1	0	1	184.89	3	NC	1
333		15	max	.003	3	-.016	15	0	1	0	1	4474.447	15	NC	1
334			min	-.003	1	-.451	3	0	1	0	1	163.492	3	NC	1
335		16	max	.003	3	-.018	15	0	1	0	1	3998.504	15	NC	1
336			min	-.004	1	-.504	3	0	1	0	1	146.137	3	NC	1
337		17	max	.003	3	-.02	15	0	1	0	1	3607.432	15	NC	1
338			min	-.004	1	-.559	3	0	1	0	1	131.871	3	NC	1
339		18	max	.004	3	-.022	15	0	1	0	1	3282.372	15	NC	1
340			min	-.004	1	-.614	3	0	1	0	1	120.009	3	NC	1
341		19	max	.004	3	-.024	15	0	1	0	1	3009.505	15	NC	1
342			min	-.004	1	-.67	3	0	1	0	1	110.048	3	NC	1
343	M8	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
344			min	0	1	0	1	0	1	0	1	NC	1	NC	1
345		2	max	0	3	0	10	0	2	3.827e-3	3	NC	1	NC	1
346			min	0	1	-.002	3	0	3	-7.712e-3	2	NC	1	NC	1
347		3	max	0	3	0	15	.001	2	3.41e-3	3	NC	1	NC	1
348			min	0	1	-.006	3	-.002	3	-7.079e-3	2	NC	1	NC	1
349		4	max	0	3	0	15	.003	2	2.992e-3	3	NC	2	NC	1
350			min	0	1	-.013	3	-.003	3	-6.446e-3	2	5892.118	3	NC	1
351		5	max	0	3	-.001	15	.004	2	2.575e-3	3	NC	2	NC	1
352			min	0	1	-.022	3	-.005	3	-5.813e-3	2	3412.291	3	9412.243	3
353		6	max	0	3	-.002	15	.006	2	2.157e-3	3	NC	5	NC	1
354			min	0	1	-.033	3	-.008	3	-5.18e-3	2	2240.624	3	6869.926	3
355		7	max	0	3	-.002	15	.008	2	1.74e-3	3	NC	5	NC	4
356			min	0	1	-.046	3	-.01	3	-4.548e-3	2	1594.071	3	5379.617	3
357		8	max	0	3	-.003	15	.01	1	1.322e-3	3	NC	5	NC	4
358			min	0	1	-.061	3	-.012	3	-3.915e-3	2	1198.89	3	4441.368	3
359		9	max	0	3	-.004	15	.012	1	9.046e-4	3	NC	5	NC	4
360			min	0	1	-.078	3	-.014	3	-3.282e-3	2	939.49	3	3826.886	3
361		10	max	0	3	-.005	15	.014	1	4.87e-4	3	NC	5	NC	4
362			min	0	1	-.097	3	-.016	3	-2.649e-3	2	759.842	3	3421.144	3
363		11	max	0	3	-.006	15	.015	1	6.953e-5	3	NC	15	NC	4
364			min	0	1	-.117	3	-.017	3	-2.017e-3	2	630.143	3	3163.757	3
365		12	max	0	3	-.007	15	.016	1	5.372e-5	9	NC	15	NC	4
366			min	-.001	1	-.138	3	-.017	3	-1.384e-3	2	533.359	3	3024.793	3
367		13	max	0	3	-.008	15	.016	1	2.697e-4	9	9446.266	15	NC	4
368			min	-.001	1	-.16	3	-.017	3	-7.655e-4	3	459.171	3	2995.671	3
369		14	max	0	3	-.009	15	.016	1	5.119e-4	1	8248.117	15	NC	4
370			min	-.001	1	-.184	3	-.015	3	-1.183e-3	3	401.017	3	3090.361	3
371		15	max	0	3	-.01	15	.015	1	1.083e-3	1	7291.9	15	NC	4
372			min	-.001	1	-.208	3	-.013	3	-1.601e-3	3	354.591	3	3356.604	3
373		16	max	.001	3	-.011	15	.013	1	1.653e-3	1	6516.628	15	NC	4
374			min	-.001	1	-.232	3	-.009	3	-2.018e-3	3	316.938	3	3925.011	3
375		17	max	.001	3	-.013	15	.01	1	2.224e-3	1	5879.544	15	NC	4
376			min	-.002	1	-.258	3	-.004	3	-2.436e-3	3	285.989	3	5205.426	3
377		18	max	.001	3	-.014	15	.007	1	2.795e-3	1	5349.958	15	NC	1
378			min	-.002	1	-.283	3	0	15	-2.853e-3	3	260.257	3	9270.887	3
379		19	max	.001	3	-.015	15	.012	3	3.365e-3	1	4905.373	15	NC	1
380			min	-.002	1	-.309	3	-.004	2	-3.271e-3	3	238.651	3	NC	1
381	M3	1	max	0	3	0	15	0	3	4.323e-3	2	NC	1	NC	1
382			min	0	10	0	3	0	2	-2.112e-3	3	NC	1	NC	1
383		2	max	0	3	0	15	.012	3	4.445e-3	2	NC	1	NC	4
384			min	0	2	-.016	3	-.024	2	-2.19e-3	3	NC	1	2565.199	2
385		3	max	0	3	-.002	15	.024	3	4.566e-3	2	NC	1	NC	5
386			min	0	2	-.031	3	-.048	2	-2.268e-3	3	NC	1	1274.142	2
387		4	max	.001	3	-.003	15	.037	3	4.688e-3	2	NC	1	NC	5
388			min	-.001	2	-.046	3	-.072	2	-2.346e-3	3	NC	1	850.734	2

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
389		5	max	.001	3	-.004	15	.048	3	4.81e-3	2	NC	1	NC	5
390			min	-.002	2	-.062	3	-.095	2	-2.424e-3	3	NC	1	644.286	2
391		6	max	.001	3	-.004	15	.059	3	4.931e-3	2	NC	1	NC	5
392			min	-.002	2	-.077	3	-.116	2	-2.502e-3	3	NC	1	524.874	2
393		7	max	.001	3	-.005	15	.069	3	5.053e-3	2	NC	1	NC	5
394			min	-.003	2	-.092	3	-.136	2	-2.58e-3	3	NC	1	449.391	2
395		8	max	.002	3	-.006	15	.077	3	5.175e-3	2	NC	1	NC	5
396			min	-.003	2	-.107	3	-.152	2	-2.658e-3	3	NC	1	399.589	2
397		9	max	.002	3	-.007	15	.084	3	5.297e-3	2	NC	1	NC	15
398			min	-.003	2	-.122	3	-.166	2	-2.736e-3	3	NC	1	366.613	2
399		10	max	.002	3	-.008	15	.089	3	5.418e-3	2	NC	1	NC	15
400			min	-.004	2	-.137	3	-.175	2	-2.814e-3	3	NC	1	345.906	2
401		11	max	.002	3	-.008	15	.092	3	5.54e-3	2	NC	1	NC	15
402			min	-.004	2	-.152	3	-.181	2	-2.892e-3	3	NC	1	335.249	2
403		12	max	.002	3	-.009	15	.093	3	5.662e-3	2	NC	1	NC	15
404			min	-.005	2	-.167	3	-.181	2	-2.97e-3	3	NC	1	334.022	2
405		13	max	.002	3	-.01	15	.09	3	5.783e-3	2	NC	1	NC	15
406			min	-.005	2	-.182	3	-.175	2	-3.048e-3	3	NC	1	343.142	2
407		14	max	.003	3	-.01	15	.085	3	5.905e-3	2	NC	1	NC	15
408			min	-.006	2	-.196	3	-.163	2	-3.126e-3	3	NC	1	365.686	2
409		15	max	.003	3	-.011	15	.076	3	6.027e-3	2	NC	1	NC	5
410			min	-.006	2	-.211	3	-.144	2	-3.204e-3	3	NC	1	408.954	2
411		16	max	.003	3	-.012	15	.063	3	6.148e-3	2	NC	1	NC	5
412			min	-.006	2	-.226	3	-.118	2	-3.282e-3	3	NC	1	490.986	2
413		17	max	.003	3	-.012	15	.046	3	6.27e-3	2	NC	1	NC	5
414			min	-.007	2	-.24	3	-.084	2	-3.36e-3	3	NC	1	666.947	2
415		18	max	.003	3	-.013	15	.026	3	6.392e-3	2	NC	1	NC	5
416			min	-.007	2	-.255	3	-.04	2	-3.438e-3	3	NC	1	1214.102	2
417		19	max	.003	3	-.013	15	.018	1	6.514e-3	2	NC	1	NC	1
418			min	-.008	2	-.269	3	0	3	-3.516e-3	3	NC	1	NC	1
419	M6	1	max	.001	3	0	10	0	1	0	1	NC	1	NC	1
420			min	0	2	0	3	0	1	0	1	NC	1	NC	1
421		2	max	.002	3	-.001	15	0	1	0	1	NC	1	NC	1
422			min	-.002	2	-.033	3	0	1	0	1	NC	1	NC	1
423		3	max	.002	3	-.003	15	0	1	0	1	NC	1	NC	1
424			min	-.003	2	-.066	3	0	1	0	1	NC	1	NC	1
425		4	max	.003	3	-.004	15	0	1	0	1	NC	1	NC	1
426			min	-.004	2	-.098	3	0	1	0	1	NC	1	NC	1
427		5	max	.003	3	-.006	15	0	1	0	1	NC	1	NC	1
428			min	-.005	2	-.131	3	0	1	0	1	NC	1	NC	1
429		6	max	.004	3	-.007	15	0	1	0	1	NC	1	NC	1
430			min	-.007	2	-.163	3	0	1	0	1	NC	1	NC	1
431		7	max	.005	3	-.008	15	0	1	0	1	NC	1	NC	1
432			min	-.008	2	-.196	3	0	1	0	1	NC	1	NC	1
433		8	max	.005	3	-.01	15	0	1	0	1	NC	1	NC	1
434			min	-.009	2	-.228	3	0	1	0	1	NC	1	NC	1
435		9	max	.006	3	-.011	15	0	1	0	1	NC	1	NC	1
436			min	-.01	2	-.261	3	0	1	0	1	NC	1	NC	1
437		10	max	.006	3	-.012	15	0	1	0	1	NC	1	NC	1
438			min	-.012	2	-.293	3	0	1	0	1	NC	1	NC	1
439		11	max	.007	3	-.013	15	0	1	0	1	NC	1	NC	1
440			min	-.013	2	-.325	3	0	1	0	1	NC	1	NC	1
441		12	max	.007	3	-.014	15	0	1	0	1	NC	1	NC	1
442			min	-.014	2	-.357	3	0	1	0	1	NC	1	NC	1
443		13	max	.008	3	-.016	15	0	1	0	1	NC	1	NC	1
444			min	-.016	2	-.389	3	0	1	0	1	NC	1	NC	1
445		14	max	.008	3	-.017	15	0	1	0	1	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
446			min	-.017	2	-.421	3	0	1	0	1	NC	1	NC	1
447		15	max	.009	3	-.018	15	0	1	0	1	NC	1	NC	1
448			min	-.018	2	-.453	3	0	1	0	1	NC	1	NC	1
449		16	max	.009	3	-.019	15	0	1	0	1	NC	1	NC	1
450			min	-.019	2	-.485	3	0	1	0	1	NC	1	NC	1
451		17	max	.01	3	-.02	15	0	1	0	1	NC	1	NC	1
452			min	-.021	2	-.517	3	0	1	0	1	NC	1	NC	1
453		18	max	.011	3	-.021	15	0	1	0	1	NC	1	NC	1
454			min	-.022	2	-.549	3	0	1	0	1	NC	1	NC	1
455		19	max	.011	3	-.022	15	0	1	0	1	NC	1	NC	1
456			min	-.023	2	-.581	3	0	1	0	1	NC	1	NC	1
457	M9	1	max	0	3	0	15	0	2	2.112e-3	3	NC	1	NC	1
458			min	0	10	0	3	0	3	-4.323e-3	2	NC	1	NC	1
459		2	max	0	3	0	15	.024	2	2.19e-3	3	NC	1	NC	4
460			min	0	2	-.016	3	-.012	3	-4.445e-3	2	NC	1	2565.199	2
461		3	max	0	3	-.002	15	.048	2	2.268e-3	3	NC	1	NC	5
462			min	0	2	-.031	3	-.024	3	-4.566e-3	2	NC	1	1274.142	2
463		4	max	.001	3	-.003	15	.072	2	2.346e-3	3	NC	1	NC	5
464			min	-.001	2	-.046	3	-.037	3	-4.688e-3	2	NC	1	850.734	2
465		5	max	.001	3	-.004	15	.095	2	2.424e-3	3	NC	1	NC	5
466			min	-.002	2	-.062	3	-.048	3	-4.81e-3	2	NC	1	644.286	2
467		6	max	.001	3	-.004	15	.116	2	2.502e-3	3	NC	1	NC	5
468			min	-.002	2	-.077	3	-.059	3	-4.931e-3	2	NC	1	524.874	2
469		7	max	.001	3	-.005	15	.136	2	2.58e-3	3	NC	1	NC	5
470			min	-.003	2	-.092	3	-.069	3	-5.053e-3	2	NC	1	449.391	2
471		8	max	.002	3	-.006	15	.152	2	2.658e-3	3	NC	1	NC	5
472			min	-.003	2	-.107	3	-.077	3	-5.175e-3	2	NC	1	399.589	2
473		9	max	.002	3	-.007	15	.166	2	2.736e-3	3	NC	1	NC	15
474			min	-.003	2	-.122	3	-.084	3	-5.297e-3	2	NC	1	366.613	2
475		10	max	.002	3	-.008	15	.175	2	2.814e-3	3	NC	1	NC	15
476			min	-.004	2	-.137	3	-.089	3	-5.418e-3	2	NC	1	345.906	2
477		11	max	.002	3	-.008	15	.181	2	2.892e-3	3	NC	1	NC	15
478			min	-.004	2	-.152	3	-.092	3	-5.54e-3	2	NC	1	335.249	2
479		12	max	.002	3	-.009	15	.181	2	2.97e-3	3	NC	1	NC	15
480			min	-.005	2	-.167	3	-.093	3	-5.662e-3	2	NC	1	334.022	2
481		13	max	.002	3	-.01	15	.175	2	3.048e-3	3	NC	1	NC	15
482			min	-.005	2	-.182	3	-.09	3	-5.783e-3	2	NC	1	343.142	2
483		14	max	.003	3	-.01	15	.163	2	3.126e-3	3	NC	1	NC	15
484			min	-.006	2	-.196	3	-.085	3	-5.905e-3	2	NC	1	365.686	2
485		15	max	.003	3	-.011	15	.144	2	3.204e-3	3	NC	1	NC	5
486			min	-.006	2	-.211	3	-.076	3	-6.027e-3	2	NC	1	408.954	2
487		16	max	.003	3	-.012	15	.118	2	3.282e-3	3	NC	1	NC	5
488			min	-.006	2	-.226	3	-.063	3	-6.148e-3	2	NC	1	490.986	2
489		17	max	.003	3	-.012	15	.084	2	3.36e-3	3	NC	1	NC	5
490			min	-.007	2	-.24	3	-.046	3	-6.27e-3	2	NC	1	666.947	2
491		18	max	.003	3	-.013	15	.04	2	3.438e-3	3	NC	1	NC	5
492			min	-.007	2	-.255	3	-.026	3	-6.392e-3	2	NC	1	1214.102	2
493		19	max	.003	3	-.013	15	0	3	3.516e-3	3	NC	1	NC	1
494			min	-.008	2	-.269	3	-.018	1	-6.514e-3	2	NC	1	NC	1