

Schletter, Inc.		35° Tilt w/o Seismic Design
HCV	Standard FS Racking System	
	Representative Calculations - ASCE 7-10	

1. INTRODUCTION

1.1 Project Description
The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. FS ground mount system.

1.2 Construction
Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to galvanized steel posts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

	Maximum		Minimum
Height =	1700 mm	Height =	1550 mm
Width =	1050 mm	Width =	970 mm
Dead Load =	3.00 psf	Dead Load =	1.75 psf

Modules Per Row = 2
Module Tilt = 35°
Maximum Height Above Grade = 3 ft



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

1.3 Technical Codes
- ASCE 7-10 - Chapter 26-31, Wind Loads
- ASCE 7-10 - Chapter 7, Snow Loads
- ASCE 7-10 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2012, 2015
- Aluminum Design Manual, Eighth Edition, 2005

2. LOAD ACTIONS

2.1 Permanent Loads
g_{MAX} = 3.00 psf
g_{MIN} = 1.75 psf

Self-weight of the PV modules.

2.2 Snow Loads
Ground Snow Load, P_g = 30.00 psf
Sloped Roof Snow Load, P_s = 14.43 psf *(ASCE 7-10, Eq. 7.4-1)*
I_s = 1.00
C_s = 0.64
C_e = 0.90
C_t = 1.20

2.3 Wind Loads
Design Wind Speed, V = 115 mph — Exposure Category = C
Height < 15 ft — Importance Category = II

Peak Velocity Pressure, q_z = 20.76 psf *Including the gust factor, G=0.85. (ASCE 7-10, Eq. 27.3-1)*

Pressure Coefficients

$Cf+_{TOP}$ =	1.2	(Pressure)
$Cf+_{BOTTOM}$ =	2	
$Cf-_{TOP}$ =	-2.4	(Suction)
$Cf-_{BOTTOM}$ =	-1.2	

Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0510-e. Negative forces are applied away from the surface.

2.4 Seismic Loads - N/A

S_S =	0.00	R =	1.25
S_{DS} =	0.00	C_S =	0
S_1 =	0.00	ρ =	1.3
S_{D1} =	0.00	Ω =	1.25
T_a =	0.00	C_d =	1.25

ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.5W
1.2D + 1.0W + 0.5S
0.9D + 1.0W ^{M}
1.54D + 1.3E + 0.2S ^{R}
0.56D + 1.3E ^{R}
1.54D + 1.25E + 0.2S ^{O}
0.56D + 1.25E ^{O}

(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S
1.0D + 0.6W
1.0D + 0.75L + 0.45W + 0.75S
0.6D + 0.6W ^{M}
1.238D + 0.875E ^{O}
1.1785D + 0.65625E + 0.75S ^{O}
0.362D + 0.875E ^{O}

(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)

^{M} *Uses the minimum allowable module dead load.*
^{R} *Include redundancy factor of 1.3.*
^{O} *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location
M10	Top
M11	Mid-Top
M12	Mid-Bottom
M13	Bottom

Posts	Location
M2	Outer
M5	Inner
M8	Outer

Girders	Location
M1	Outer
M4	Inner
M7	Outer

Reactions	Location
N9	Outer
N19	Inner
N29	Outer

Struts	Location
M3	Outer
M6	Inner
M9	Outer

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type =	**S1.5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	132	in
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	25.07	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	23.08	ksi
S_y =	1.33	in^3
S_x =	0.6	in^3
E =	10100	ksi
I_y =	2.16	in^4
I_x =	1.07	in^4
A =	1.25	in^2
g =	1.50	lbs/ft
M_y =	1.578	k-ft
M_z =	0.341	k-ft
$M_{y\ allowable}$ =	2.779	k-ft
$M_{z\ allowable}$ =	1.154	k-ft
Utilization =	86%	



4.2 Girder Design

Loads from purlins are transferred to the posts using an inclined girder, which is connected to the steel post. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type =	**T5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	63.82	in
$\Phi F_{ty\ AXIAL}$ =	30.80	ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	30.46	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	31.56	ksi
S_y =	1.98	in^3
S_x =	1.32	in^3
E =	10100	ksi
I_y =	4.74	in^4
I_x =	1.83	in^4
A =	1.93	in^2
g =	2.32	lbs/ft
M_y =	3.775	k-ft
M_z =	0.000	k-ft
P_n =	0.010	k
$M_{y\ allowable}$ =	5.026	k-ft
$M_{z\ allowable}$ =	3.472	k-ft
$P_{n\ allowable}$ =	59.439	k
Utilization =	75%	



4.3 Strut Design

The aluminum strut connects a portion of the girder to the galvanized steel post. Girder forces are then transferred down through the strut into the post. The strut is attached with single M10 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	61.00	in
$\Phi F_{ty\ AXIAL}$ =	13.67	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.000	k-ft
M_z =	0.393	k-ft
P_n =	3.758	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	13.425	k
Utilization =	56%	



DETAIL VIEW

4.4 Post Design

Galvanized steel posts are a roll formed steel section, that are either ram driven into the ground or placed in a concrete foundation at a defined depth. Embedment depths will be provided on the structural drawings or through a geotechnical testing report. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Post Type =	**FG8**	
Steel Type =	J2340	
F_{ty} =	60	ksi
L_b =	85.68	in
Φ =	0.90	
ΦF_{ty} =	54.00	ksi
S_y =	3.46	in^3
S_x =	1.55	in^3
E =	29000	ksi
I_y =	10.94	in^4
I_x =	4.31	in^4
A =	2.23	in^2
g =	7.59	lbs/ft
M_y =	16.426	k-ft
M_z =	0.000	k-ft
P_r =	-4.201	k
$M_{y\ allowable}$ =	19.207	k-ft
$M_{z\ allowable}$ =	14.389	k-ft
P_c =	28.060	k
Utilization =	97%	



DETAIL VIEW

5. FOUNDATION DESIGN CALCULATIONS

5.1 Rammed Post Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete footing design.

Maximum Tensile Load =	5.42	k
Maximum Lateral Load =	3.87	k

5.2 Design of Drilled Shaft Foundations

The galvanized steel post is to be embedded into a cylindrical drilled shaft foundation. For the purpose of design, the post is considered to be fixed to the ground. The applicable lateral force, uplift, and compression resistance checks are seen below.

5.3 Lateral Force Resistance

The equivalent lateral force is applied at the top of the post to determine the required embedment depth. A lateral soil bearing capacity for clay is assumed. Footing is unrestrained at ground level. (IBC, Eq. 18-1)

Lateral Force @ Top of Pole, P =	1.04	k
Height of Pole Above Grade, H =	7.14	ft
Diameter of Pole Footing, B =	2.00	ft
Lateral Soil Bearing Capacity, S =	0.10	ksf/ft
Isolated Pole Factor, F =	2	
First Trial Depth, D =	3.25	ft

$$S_3 = Min\left(D, 12'\right)$$

$$S_1 = Min\left(\frac{D}{3}, 12'\right)$$

$$A = 2.34\, P/S_1 B$$

$$D = \left\{0.5A\left(1+\sqrt{1+\left(\frac{4.36H}{A}\right)}\right)\right\}$$



Lateral Bearing @ Bottom =	S_3
Lateral Bearing @ D/3 =	S_1
Required Depth =	D

	Non-Constrained	
Lateral Force @ Top of Pole, P =	1.04	k
Height of Pole Above Grade, H =	7.14	ft
Diameter of Pole Footing, B =	2.00	ft
Lateral Soil Bearing Capacity, S =	0.20	ksf/ft

1st Trial @ D_1 =	3.25	ft
Lateral Soil Bearing @ D/3, S_1 =	0.22	ksf
Lateral Soil Bearing @ D, S_3 =	0.65	ksf
Constant $2.34P/(S_1B)$, A =	5.63	
Required Footing Depth, D =	10.00	ft
2nd Trial @ D_2 =	6.63	ft
Lateral Soil Bearing @ D/3, S_1 =	0.44	ksf
Lateral Soil Bearing @ D, S_3 =	1.33	ksf
Constant $2.34P/(S_1B)$, A =	2.76	
Required Footing Depth, D =	6.21	ft
3rd Trial @ D_3 =	6.42	ft
Lateral Soil Bearing @ D/3, S_1 =	0.43	ksf
Lateral Soil Bearing @ D, S_3 =	1.28	ksf
Constant $2.34P/(S_1B)$, A =	2.85	
Required Footing Depth, D =	6.34	ft
4th Trial @ D_4 =	6.38	ft
Lateral Soil Bearing @ D/3, S_1 =	0.43	ksf
Lateral Soil Bearing @ D, S_3 =	1.28	ksf
Constant $2.34P/(S_1B)$, A =	2.87	
Required Footing Depth, D =	6.37	ft
5th Trial @ D_5 =	6.37	ft
Lateral Soil Bearing @ D/3, S_1 =	0.42	ksf
Lateral Soil Bearing @ D, S_3 =	1.27	ksf
Constant $2.34P/(S_1B)$, A =	2.87	
Required Footing Depth, D =	6.50	ft

A 2ft diameter x 6.5ft deep footing unrestrained at ground level is required for the racking structure.

5.4 Uplifting Force Resistance

Uplifting forces of the racking system are checked against the uplift resistance of the soil. Clay soils are assumed.

Weight of Concrete, g_{con} = 145 pcf
Uplifting Force, N = 2.48 k
Footing Diameter, B = 2.00 ft
Factor of Safety = 2.50
Cohesion = 208.85 psf
γ_s = 120.43 pcf
α = 0.45

Required Concrete Weight, g = 1.63 k
Required Concrete Volume, V = 11.24 ft^3
Required Footing Depth, D = 3.75 ft

Iteration	z	dz	Qs	Side
1	0.2	0.2	118.10	5.34
2	0.4	0.2	118.10	5.24
3	0.6	0.2	118.10	5.13
4	0.8	0.2	118.10	5.03
5	1	0.2	118.10	4.93
6	1.2	0.2	118.10	4.82
7	1.4	0.2	118.10	4.72
8	1.6	0.2	118.10	4.62
9	1.8	0.2	118.10	4.51
10	2	0.2	118.10	4.41
11	2.2	0.2	118.10	4.30
12	2.4	0.2	118.10	4.20
13	2.6	0.2	118.10	4.10
14	2.8	0.2	118.10	3.99
15	3	0.2	118.10	3.89
16	3.2	0.2	118.10	3.79
17	3.4	0.2	118.10	3.68
18	3.6	0.2	118.10	3.58
19	0	0.0	0.00	3.58
20	0	0.0	0.00	3.58
21	0	0.0	0.00	3.58
22	0	0.0	0.00	3.58
23	0	0.0	0.00	3.58
24	0	0.0	0.00	3.58
25	0	0.0	0.00	3.58
26	0	0.0	0.00	3.58
27	0	0.0	0.00	3.58
28	0	0.0	0.00	3.58
29	0	0.0	0.00	3.58
30	0	0.0	0.00	3.58
31	0	0.0	0.00	3.58
32	0	0.0	0.00	3.58
33	0	0.0	0.00	3.58
34	0	0.0	0.00	3.58
Max	3.6	Sum	0.85	

A 2ft diameter x 3.75ft deep footing unrestrained at ground level is required for the racking structure.



5.5 Compressive Force Resistance

Skin friction of the soil is checked against the compression force from the racking and the weight of the drilled shaft foundation. Skin friction starts at 3ft below grade. Clay soils are again assumed.

Depth Below Grade, D = 6.50 ft
Footing Diameter, B = 2.00 ft
Compressive Force, P = 3.60 k

Footing Area = 3.14 ft^2
Circumference = 6.28 ft
Skin Friction Area = 21.99 ft^2
Concrete Weight = 0.145 kcf

Bearing Pressure

Bearing Area = 3.14 ft^2
Bearing Capacity = 1.5 ksf
Resistance = 4.71 k

Weight of Concrete

Footing Volume 20.42 ft^3
Weight 2.96 k

Skin Friction Resistance

Skin Friction = 0.15 ksf
Resistance = 3.30 k

1/3 Increase for Wind = 1.33
Total Resistance = 10.68 k
Applied Force = 6.56 k
Utilization = 61%

A 2ft diameter footing passes at a depth of 6.5ft.



6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of 40mm mounting clamps. The reliability of calculations is uncertain due to limited standards, therefore the strength of the clamp fasteners has been evaluated by load testing.

Fastening of Modules to Purlins			Fastening of Purlins to Girders	
Maximum Uplifting Force =	0.464 k		Maximum Uplifting Force =	1.812 k
Allowable Uplift =	1.214 k		Allowable Uplift =	2.180 k
Utilization =	38%		Utilization =	83%





6.2 Strut Connections

The aluminum struts connect the front end of girder to a center section of the steel post. Single M10 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Maximum Axial Load =	3.758 k
M10 Bolt Shear Capacity =	8.894 k
Utilization =	42%

Bolt capacity is accounting for double shear. (ASCE 8-02, Eq. 5.3.4-1)



A strut under compression is shown to demonstrate the load transfer from the girder. Single M10 bolts are located at each end of the strut and are subjected to double shear.

6.3 Girder to Post Connection

In order to connect the girder to the post, custom extruded sections are assembled to create a post head piece. The reliability of calculations is uncertain due to limited standards, therefore the strength of the head piece has been evaluated by load testing.

Maximum Tensile Load =	3.849 k
Allowable Load =	5.649 k
Utilization =	68%



FRONT VIEW



SIDE VIEW



7. SEISMIC DESIGN

7.1 Seismic Drift - N/A

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx} =	77.78 in
Allowable Story Drift for All Other Structures, Δ = {	$0.020h_{sx}$ 1.556 in
Max Drift, Δ_{MAX} =	0 in
N/A	

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **S1.5**

Strong Axis:

3.4.14

L_b = 132 in

J = 0.432

365.174

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 27.1 ksi

3.4.16

b/t = 32.195

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 25.1 ksi

3.4.16.1 Not Used

Rb/t =

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 37.0588

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 40.985

Cc = 41.015

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.2

φF_L= φb[Bbr-mDbr*h/t]

φF_L= 43.2 ksi

$\varphi F_L St$= 25.1 ksi

Ix = 897074 mm^4

2.155 in^4

y = 41.015 mm

Sx = 1.335 in^3

$M_{max}St$ = 2.788 k-ft

Weak Axis:

3.4.14

L_b = 132

J = 0.432

232.229

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 28.4

3.4.16

b/t = 37.0588

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 23.1 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 32.195

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 45.5

Cc = 45.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 23.1 ksi

Iy = 446476 mm^4

1.073 in^4

x = 45.5 mm

Sy = 0.599 in^3

$M_{max}Wk$ = 1.152 k-ft

Compression

3.4.9

b/t = 32.195
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L= φc[Bp-1.6Dp*b/t]
φF_L= 25.1 ksi

b/t = 37.0588
S1 = 12.21
S2 = 32.70
φF_L= (φck2*√(BpE))/(1.6b/t)
φF_L= 21.9 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L= φyFcy
φF_L= 33.25 ksi

φF_L= 21.94 ksi
A = 1215.13 mm^2
1.88 in^2
P_{max} = 41.32 kips

A.2 Design of Aluminum Girders - Aluminum Design Manual, 2005 Edition

Girder = **T5**

Strong Axis:

3.4.14

L_b = 63.8189 in
J = 1.98
82.1278

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L= 30.5 ksi

3.4.16

b/t = 4.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L= φyFcy
φF_L= 33.3 ksi

Weak Axis:

3.4.14

L_b = 63.8189
J = 1.98
89.1294

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L= 30.3

3.4.16

b/t = 16.3333

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L= φb[Bp-1.6Dp*b/t]
φF_L= 31.6 ksi

3.4.16.1 Used

Rb/t = 20.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

$\varphi F_L = \varphi b[Bt-Dt^*\sqrt{(Rb/t)}]$

$\varphi F_L =$ 30.8 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 16.3333

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 37.9

m = 0.63

C_0 = 61.046

Cc = 58.954

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 79.4

$\varphi F_L = 1.3\varphi yFcy$

$\varphi F_L =$ 43.2 ksi

$\varphi F_L St =$ 30.5 ksi

Ix = 1970917 mm^4

4.735 in^4

y = 61.046 mm

Sx = 1.970 in^3

$M_{max}St$ = 5.001 k-ft

3.4.18

h/t = 4.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 35

Cc = 35

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

$\varphi F_L = 1.3\varphi yFcy$

$\varphi F_L =$ 43.2 ksi

$\varphi F_L Wk =$ 31.6 ksi

Iy = 763048 mm^4

1.833 in^4

x = 35 mm

Sy = 1.330 in^3

$M_{max}Wk$ = 3.499 k-ft

Compression

3.4.9

b/t = 4.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

$\varphi F_L = \varphi yFcy$

$\varphi F_L =$ 33.3 ksi

b/t = 16.3333

S1 = 12.21

S2 = 32.70

$\varphi F_L = \varphi c[Bp-1.6Dp^*b/t]$

$\varphi F_L =$ 31.6 ksi

3.4.10

Rb/t = 20.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

$\varphi F_L = \varphi c[Bt-Dt^*\sqrt{(Rb/t)}]$

$\varphi F_L =$ 30.80 ksi

$\varphi F_L =$ 30.80 ksi

A = 1215.13 mm^2

1.88 in^2

P_{max} = 58.01 kips

A.3 Design of Aluminum Struts - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 61 in

J = 0.942

95.1963

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 30.2 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

Weak Axis:

3.4.14

L_b = 61

J = 0.942

95.1963

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 30.2

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

$\lambda =$ 1.41113

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^* =$ 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^* =$ 1.23671

$\varphi cc =$ 0.77756

$\varphi F_L = (\varphi ccFcy)/(\lambda^2)$

$\varphi F_L =$ 13.6667 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

$\varphi F_L = \varphi c[Bp-1.6Dp^*b/t]$

$\varphi F_L =$ 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

$\varphi F_L = \varphi c[Bp-1.6Dp^*b/t]$

$\varphi F_L =$ 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

$\varphi F_L = \varphi yFcy$

$\varphi F_L =$ 33.25 ksi

$\varphi F_L =$ 13.67 ksi

A = 663.99 mm^2

1.03 in^2

$P_{max} =$ 14.07 kips

A.4 Design of Galvanized Steel Posts

Post Type = **FG8**

Unbraced Length =	85.68	in	
Pr =	-4.20	k	(LRFD Factored Load)
Mr (Strong) =	16.43	k-ft	(LRFD Factored Load)
Mr (Weak) =	0.00	k-ft	(LRFD Factored Load)

Flexural Buckling:

kL/r =	123.28	
4.71√(E/Fy) =	103.55 =>	kL/r > 4.71√(E/Fy)
Fcr =	16.52	ksi
Fe =	18.83	ksi
Pn =	36.831	k

Torsional/Flexural Torsional Buckling:

Fcr =	12.5831	ksi
Fey =	48.0382	ksi
Fez =	16.1601	ksi
Pn =	28.0602	k

Bending (Strong Axis):

Yielding:			
Mn =	21.95 k-ft		
Flange Local Buckling:			
Mn =	19.207 k-ft		
Pr/Pc =	0.1141 <	0.2	
Utilization =	0.97 <	1.0	OK

Bending (Weak Axis):

Yielding:			
Mn =	14.65 k-ft		
Flange Local Buckling:			
Mn =	14.39 k-ft		
Pr/Pc =	0.114 <	0.2	
Utilization =	0.00 <	1.0	OK

Combined Forces

Utilization = 97%

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				4		
2	Dead Load, Min	DL		-1				4		
3	Snow Load	SL						4		
4	Wind Load - Pressure	WL						4		
5	Wind Load - Suction	WL						4		
6	Seismic - Lateral	EL								

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-8.366	-8.366	0	0
2	M11	Y	-8.366	-8.366	0	0
3	M12	Y	-8.366	-8.366	0	0
4	M13	Y	-8.366	-8.366	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-4.45	-4.45	0	0
2	M11	Y	-4.45	-4.45	0	0
3	M12	Y	-4.45	-4.45	0	0
4	M13	Y	-4.45	-4.45	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-32.97	-32.97	0	0
2	M11	Y	-32.97	-32.97	0	0
3	M12	Y	-32.97	-32.97	0	0
4	M13	Y	-32.97	-32.97	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	y	-69.488	-69.488	0	0
2	M11	y	-69.488	-69.488	0	0
3	M12	y	-115.813	-115.813	0	0
4	M13	y	-115.813	-115.813	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	y	138.975	138.975	0	0
2	M11	y	138.975	138.975	0	0
3	M12	y	69.488	69.488	0	0
4	M13	y	69.488	69.488	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.5W	Yes	Y		1	1.2	3	1.6	4	.5														
2	LRFD 1.2D + 1.0W + 0.5S	Yes	Y		1	1.2	3	.5	4	1														
3	LRFD 0.9D + 1.0W	Yes	Y		2	.9					5	1												
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3												
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3												
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25												
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25												

Load Combinations (Continued)

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
8																								
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																
10	ASD 1.0D + 0.6W	Yes	Y		1	1			4	.6														
11	ASD 1.0D + 0.75L + 0.45W + 0....	Yes	Y		1	1	3	.75	4	.45														
12	ASD 0.6D + 0.6W	Yes	Y		2	.6					5	.6												
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875												
14	LATERAL - ASD 1.1785D + 0.65..	Yes	Y		1	1.1...	3	.75			6	.656												
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875												

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N9	max	891.548	2	2007.025	1	262.412	2	.383	2	.017	3	4.614	3
2		min	-1141.558	3	-1335.855	3	-286.294	3	-.474	3	-.034	2	.138	10
3	N19	max	2893.412	2	5488.183	2	0	3	0	3	0	3	9.813	3
4		min	-2977.941	3	-4156.966	3	0	2	0	2	0	10	-.044	10
5	N29	max	891.548	2	2007.025	1	286.294	3	.474	3	.034	2	4.614	3
6		min	-1141.558	3	-1335.855	3	-262.412	2	-.383	2	-.017	3	.138	10
7	Totals:	max	4676.509	2	9456.146	2	0	3						
8		min	-5261.056	3	-6828.675	3	0	2						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M1	1	max	0	1	.006	1	0	15	0	1	0	1	0	1
2			min	0	1	0	3	-.002	1	0	1	0	1	0	1
3		2	max	-.299	15	-.428	15	0	15	0	1	0	15	0	4
4			min	-1.274	4	-1.817	4	-.002	1	0	1	0	1	0	15
5		3	max	-11.749	15	274.57	3	-8.127	15	.071	3	.28	1	.265	2
6			min	-203.01	1	-618.63	2	-147.691	1	-.252	2	.016	15	-.114	3
7		4	max	-12.049	15	273.507	3	-8.127	15	.071	3	.189	1	.649	2
8			min	-204.003	1	-620.048	2	-147.691	1	-.252	2	.011	15	-.284	3
9		5	max	-12.348	15	272.444	3	-8.127	15	.071	3	.097	1	1.035	2
10			min	-204.995	1	-621.465	2	-147.691	1	-.252	2	.006	15	-.453	3
11		6	max	140.446	3	549.401	2	1.329	3	.117	2	.099	2	.991	2
12			min	-579.044	1	-174.271	3	-215.129	1	-.111	3	-.038	3	-.459	3
13		7	max	139.702	3	547.984	2	1.329	3	.117	2	.011	10	.65	2
14			min	-580.036	1	-175.334	3	-215.129	1	-.111	3	-.04	1	-.35	3
15		8	max	138.957	3	546.566	2	1.329	3	.117	2	-.009	15	.311	2
16			min	-581.029	1	-176.397	3	-215.129	1	-.111	3	-.173	1	-.241	3
17		9	max	106.373	3	88.222	3	-12.29	15	-.002	15	.093	1	.11	2
18			min	-791.327	1	-69.431	2	-225.019	1	-.185	2	-.007	10	-.187	3
19		10	max	105.629	3	87.159	3	-12.29	15	-.002	15	.056	3	.154	2
20			min	-792.32	1	-70.848	2	-225.019	1	-.185	2	-.054	2	-.241	3
21		11	max	104.884	3	86.096	3	-12.29	15	-.002	15	.042	3	.198	2
22			min	-793.312	1	-72.266	2	-225.019	1	-.185	2	-.187	1	-.295	3
23		12	max	68.852	3	712.932	3	175.113	2	.397	3	.173	1	.404	2
24			min	-1000.988	1	-478.1	2	-367.258	3	-.347	2	.009	15	-.591	3
25		13	max	68.108	3	711.869	3	175.113	2	.397	3	.214	1	.701	2
26			min	-1001.981	1	-479.518	2	-367.258	3	-.347	2	-.205	3	-1.033	3
27		14	max	205.893	1	432.822	2	10.299	10	.27	2	.171	3	.987	2
28			min	12.65	15	-632.074	3	-121.308	3	-.464	3	-.131	2	-1.457	3
29		15	max	204.901	1	431.405	2	10.299	10	.27	2	.096	3	.718	2
30			min	12.351	15	-633.137	3	-121.308	3	-.464	3	-.183	1	-1.064	3
31		16	max	203.908	1	429.987	2	10.299	10	.27	2	.021	3	.451	2
32			min	12.051	15	-634.2	3	-121.308	3	-.464	3	-.243	1	-.671	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
33		17	max	202.916	1	428.57	2	10.299	10	.27	2	-.016	15	.185	2
34			min	11.752	15	-635.263	3	-121.308	3	-.464	3	-.302	1	-.277	3
35		18	max	1.274	4	1.819	4	.002	1	0	1	0	15	0	4
36			min	.299	15	.428	15	0	15	0	1	0	1	0	15
37		19	max	0	1	.004	2	.002	1	0	1	0	1	0	1
38			min	0	1	-.007	3	0	15	0	1	0	1	0	1
39	M4	1	max	0	1	.015	2	0	1	0	1	0	1	0	1
40			min	0	1	-.001	3	0	1	0	1	0	1	0	1
41		2	max	-.299	15	-.427	15	0	1	0	1	0	1	0	4
42			min	-1.274	4	-1.815	4	0	1	0	1	0	1	0	15
43		3	max	-7.102	12	876.666	3	0	1	0	1	0	1	.711	2
44			min	-415.053	1	-1824.722	2	0	1	0	1	0	1	-.348	3
45		4	max	-7.598	12	875.603	3	0	1	0	1	0	1	1.844	2
46			min	-416.045	1	-1826.14	2	0	1	0	1	0	1	-.892	3
47		5	max	-8.094	12	874.54	3	0	1	0	1	0	1	2.977	2
48			min	-417.038	1	-1827.557	2	0	1	0	1	0	1	-1.435	3
49		6	max	611.279	3	1665.997	2	0	1	0	1	0	1	2.83	2
50			min	-1571.371	2	-676.616	3	0	1	0	1	0	1	-1.409	3
51		7	max	610.535	3	1664.579	2	0	1	0	1	0	1	1.796	2
52			min	-1572.363	2	-677.679	3	0	1	0	1	0	1	-.988	3
53		8	max	609.79	3	1663.162	2	0	1	0	1	0	1	.764	2
54			min	-1573.356	2	-678.742	3	0	1	0	1	0	1	-.567	3
55		9	max	605.106	3	218.981	3	0	1	0	1	0	1	.15	1
56			min	-1915.527	1	-175.056	2	0	1	0	1	0	1	-.355	3
57		10	max	604.361	3	217.917	3	0	1	0	1	0	1	.259	1
58			min	-1916.52	1	-176.474	2	0	1	0	1	0	1	-.491	3
59		11	max	603.617	3	216.854	3	0	1	0	1	0	1	.368	1
60			min	-1917.512	1	-177.891	2	0	1	0	1	0	1	-.626	3
61		12	max	605.828	3	1917.62	3	0	1	0	1	0	1	.963	2
62			min	-2320.256	1	-1418.237	2	0	1	0	1	0	1	-1.446	3
63		13	max	605.083	3	1916.557	3	0	1	0	1	0	1	1.844	2
64			min	-2321.248	1	-1419.655	2	0	1	0	1	0	1	-2.635	3
65		14	max	418.22	1	1198.219	2	0	1	0	1	0	1	2.69	2
66			min	8.401	12	-1681.881	3	0	1	0	1	0	1	-3.775	3
67		15	max	417.227	1	1196.801	2	0	1	0	1	0	1	1.946	2
68			min	7.905	12	-1682.944	3	0	1	0	1	0	1	-2.731	3
69		16	max	416.235	1	1195.384	2	0	1	0	1	0	1	1.204	2
70			min	7.408	12	-1684.007	3	0	1	0	1	0	1	-1.686	3
71		17	max	415.242	1	1193.966	2	0	1	0	1	0	1	.463	2
72			min	6.912	12	-1685.07	3	0	1	0	1	0	1	-.641	3
73		18	max	1.274	4	1.821	4	0	1	0	1	0	1	0	4
74			min	.299	15	.428	15	0	1	0	1	0	1	0	15
75		19	max	0	1	.011	2	0	1	0	1	0	1	0	1
76			min	0	1	-.017	3	0	1	0	1	0	1	0	1
77	M7	1	max	0	1	.006	1	.002	1	0	1	0	1	0	1
78			min	0	1	0	3	0	15	0	1	0	1	0	1
79		2	max	-.299	15	-.428	15	.002	1	0	1	0	1	0	4
80			min	-1.274	4	-1.817	4	0	15	0	1	0	15	0	15
81		3	max	-11.749	15	274.57	3	147.691	1	.252	2	-.016	15	.265	2
82			min	-203.01	1	-618.63	2	8.127	15	-.071	3	-.28	1	-.114	3
83		4	max	-12.049	15	273.507	3	147.691	1	.252	2	-.011	15	.649	2
84			min	-204.003	1	-620.048	2	8.127	15	-.071	3	-.189	1	-.284	3
85		5	max	-12.348	15	272.444	3	147.691	1	.252	2	-.006	15	1.035	2
86			min	-204.995	1	-621.465	2	8.127	15	-.071	3	-.097	1	-.453	3
87		6	max	140.446	3	549.401	2	215.129	1	.111	3	.038	3	.991	2
88			min	-579.044	1	-174.271	3	-1.329	3	-.117	2	-.099	2	-.459	3
89		7	max	139.702	3	547.984	2	215.129	1	.111	3	.04	1	.65	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
90			min	-580.036	1	-175.334	3	-1.329	3	-.117	2	-.011	10	-.35	3
91		8	max	138.957	3	546.566	2	215.129	1	.111	3	.173	1	.311	2
92			min	-581.029	1	-176.397	3	-1.329	3	-.117	2	.009	15	-.241	3
93		9	max	106.373	3	88.222	3	225.019	1	.185	2	.007	10	.11	2
94			min	-791.327	1	-69.431	2	12.29	15	.002	15	-.093	1	-.187	3
95		10	max	105.629	3	87.159	3	225.019	1	.185	2	.054	2	.154	2
96			min	-792.32	1	-70.848	2	12.29	15	.002	15	-.056	3	-.241	3
97		11	max	104.884	3	86.096	3	225.019	1	.185	2	.187	1	.198	2
98			min	-793.312	1	-72.266	2	12.29	15	.002	15	-.042	3	-.295	3
99		12	max	68.852	3	712.932	3	367.258	3	.347	2	-.009	15	.404	2
100			min	-1000.988	1	-478.1	2	-175.113	2	-.397	3	-.173	1	-.591	3
101		13	max	68.108	3	711.869	3	367.258	3	.347	2	.205	3	.701	2
102			min	-1001.981	1	-479.518	2	-175.113	2	-.397	3	-.214	1	-1.033	3
103		14	max	205.893	1	432.822	2	121.308	3	.464	3	.131	2	.987	2
104			min	12.65	15	-632.074	3	-10.299	10	-.27	2	-.171	3	-1.457	3
105		15	max	204.901	1	431.405	2	121.308	3	.464	3	.183	1	.718	2
106			min	12.351	15	-633.137	3	-10.299	10	-.27	2	-.096	3	-1.064	3
107		16	max	203.908	1	429.987	2	121.308	3	.464	3	.243	1	.451	2
108			min	12.051	15	-634.2	3	-10.299	10	-.27	2	-.021	3	-.671	3
109		17	max	202.916	1	428.57	2	121.308	3	.464	3	.302	1	.185	2
110			min	11.752	15	-635.263	3	-10.299	10	-.27	2	.016	15	-.277	3
111		18	max	1.274	4	1.819	4	0	15	0	1	0	1	0	4
112			min	.299	15	.428	15	-.002	1	0	1	0	15	0	15
113		19	max	0	1	.004	2	0	15	0	1	0	1	0	1
114			min	0	1	-.007	3	-.002	1	0	1	0	1	0	1
115	M10	1	max	121.322	3	425.314	2	-11.153	15	.011	2	.341	1	.27	2
116			min	-10.302	10	-637.591	3	-201.014	1	-.02	3	.019	15	-.464	3
117		2	max	121.322	3	312.021	2	-8.649	15	.011	2	.123	1	.214	3
118			min	-10.302	10	-473.098	3	-155.73	1	-.02	3	.007	15	-.183	1
119		3	max	121.322	3	198.729	2	-6.144	15	.011	2	.038	3	.692	3
120			min	-10.302	10	-308.605	3	-110.446	1	-.02	3	-.039	1	-.493	2
121		4	max	121.322	3	85.436	2	-3.639	15	.011	2	.011	3	.969	3
122			min	-10.302	10	-144.111	3	-65.161	1	-.02	3	-.147	1	-.667	2
123		5	max	121.322	3	20.382	3	-1.134	15	.011	2	-.007	12	1.044	3
124			min	-10.302	10	-31.491	1	-19.877	1	-.02	3	-.199	1	-.702	2
125		6	max	121.322	3	184.875	3	25.407	1	.011	2	-.011	15	.919	3
126			min	-10.302	10	-141.149	2	-11.98	3	-.02	3	-.195	1	-.599	2
127		7	max	121.322	3	349.368	3	70.692	1	.011	2	-.008	15	.593	3
128			min	-10.302	10	-254.442	2	-8.223	3	-.02	3	-.136	1	-.357	2
129		8	max	121.322	3	513.862	3	115.976	1	.011	2	0	10	.065	3
130			min	-10.302	10	-367.734	2	-4.467	3	-.02	3	-.047	3	.003	15
131		9	max	121.322	3	678.355	3	161.261	1	.011	2	.147	1	.545	1
132			min	-10.302	10	-481.027	2	-.71	3	-.02	3	-.05	3	-.664	3
133		10	max	121.322	3	-19.118	15	206.545	1	.011	2	.372	1	1.199	2
134			min	-10.302	10	-842.848	3	-3.047	3	-.02	3	-.049	3	-1.593	3
135		11	max	121.322	3	481.027	2	.71	3	.02	3	.147	1	.545	1
136			min	-10.302	10	-678.355	3	-161.261	1	-.011	2	-.05	3	-.664	3
137		12	max	121.322	3	367.734	2	4.467	3	.02	3	0	10	.065	3
138			min	-10.302	10	-513.862	3	-115.976	1	-.011	2	-.047	3	.003	15
139		13	max	121.322	3	254.442	2	8.223	3	.02	3	-.008	15	.593	3
140			min	-10.302	10	-349.368	3	-70.692	1	-.011	2	-.136	1	-.357	2
141		14	max	121.322	3	141.149	2	11.98	3	.02	3	-.011	15	.919	3
142			min	-10.302	10	-184.875	3	-25.407	1	-.011	2	-.195	1	-.599	2
143		15	max	121.322	3	31.491	1	19.877	1	.02	3	-.007	12	1.044	3
144			min	-10.302	10	-20.382	3	1.134	15	-.011	2	-.199	1	-.702	2
145		16	max	121.322	3	144.111	3	65.161	1	.02	3	.011	3	.969	3
146			min	-10.302	10	-85.436	2	3.639	15	-.011	2	-.147	1	-.667	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
147		17	max	121.322	3	308.605	3	110.446	1	.02	3	.038	3	.692	3
148			min	-10.302	10	-198.729	2	6.144	15	-.011	2	-.039	1	-.493	2
149		18	max	121.322	3	473.098	3	155.73	1	.02	3	.123	1	.214	3
150			min	-10.302	10	-312.021	2	8.649	15	-.011	2	.007	15	-.183	1
151		19	max	121.322	3	637.591	3	201.014	1	.02	3	.341	1	.27	2
152			min	-10.302	10	-425.314	2	11.153	15	-.011	2	.019	15	-.464	3
153	M11	1	max	289.56	1	403.266	2	-11.511	15	0	10	.385	1	.178	1
154			min	-344.323	3	-627.762	3	-206.938	1	-.005	3	.022	15	-.521	3
155		2	max	289.56	1	289.974	2	-9.007	15	0	10	.16	1	.146	3
156			min	-344.323	3	-463.269	3	-161.653	1	-.005	3	.009	15	-.262	2
157		3	max	289.56	1	176.681	2	-6.502	15	0	10	.056	3	.612	3
158			min	-344.323	3	-298.776	3	-116.369	1	-.005	3	-.013	2	-.547	2
159		4	max	289.56	1	63.389	2	-3.997	15	0	10	.025	3	.876	3
160			min	-344.323	3	-134.282	3	-71.085	1	-.005	3	-.125	1	-.693	2
161		5	max	289.56	1	30.211	3	-1.492	15	0	10	0	3	.94	3
162			min	-344.323	3	-49.904	2	-25.8	1	-.005	3	-.184	1	-.702	2
163		6	max	289.56	1	194.704	3	19.484	1	0	10	-.01	15	.802	3
164			min	-344.323	3	-163.196	2	-15.773	3	-.005	3	-.188	1	-.571	2
165		7	max	289.56	1	359.197	3	64.768	1	0	10	-.008	15	.464	3
166			min	-344.323	3	-276.489	2	-12.017	3	-.005	3	-.137	1	-.303	2
167		8	max	289.56	1	523.691	3	110.053	1	0	10	-.001	10	.104	2
168			min	-344.323	3	-389.781	2	-8.26	3	-.005	3	-.052	3	-.076	3
169		9	max	289.56	1	688.184	3	155.337	1	0	10	.132	1	.65	2
170			min	-344.323	3	-503.074	2	-4.503	3	-.005	3	-.06	3	-.816	3
171		10	max	289.56	1	852.677	3	200.622	1	0	10	.35	1	1.334	2
172			min	-344.323	3	-616.367	2	-.747	3	-.005	3	-.063	3	-1.758	3
173		11	max	289.56	1	503.074	2	4.503	3	.005	3	.132	1	.65	2
174			min	-344.323	3	-688.184	3	-155.337	1	0	10	-.06	3	-.816	3
175		12	max	289.56	1	389.781	2	8.26	3	.005	3	-.001	10	.104	2
176			min	-344.323	3	-523.691	3	-110.053	1	0	10	-.052	3	-.076	3
177		13	max	289.56	1	276.489	2	12.017	3	.005	3	-.008	15	.464	3
178			min	-344.323	3	-359.197	3	-64.768	1	0	10	-.137	1	-.303	2
179		14	max	289.56	1	163.196	2	15.773	3	.005	3	-.01	15	.802	3
180			min	-344.323	3	-194.704	3	-19.484	1	0	10	-.188	1	-.571	2
181		15	max	289.56	1	49.904	2	25.8	1	.005	3	0	3	.94	3
182			min	-344.323	3	-30.211	3	1.492	15	0	10	-.184	1	-.702	2
183		16	max	289.56	1	134.282	3	71.085	1	.005	3	.025	3	.876	3
184			min	-344.323	3	-63.389	2	3.997	15	0	10	-.125	1	-.693	2
185		17	max	289.56	1	298.776	3	116.369	1	.005	3	.056	3	.612	3
186			min	-344.323	3	-176.681	2	6.502	15	0	10	-.013	2	-.547	2
187		18	max	289.56	1	463.269	3	161.653	1	.005	3	.16	1	.146	3
188			min	-344.323	3	-289.974	2	9.007	15	0	10	.009	15	-.262	2
189		19	max	289.56	1	627.762	3	206.938	1	.005	3	.385	1	.178	1
190			min	-344.323	3	-403.266	2	11.511	15	0	10	.022	15	-.521	3
191	M12	1	max	45.584	2	613.744	2	-11.583	15	0	10	.402	1	.302	2
192			min	-27.336	9	-265.74	3	-209.297	1	-.004	3	.022	15	.005	15
193		2	max	45.584	2	443.832	2	-9.078	15	0	10	.174	1	.289	3
194			min	-27.336	9	-186.175	3	-164.013	1	-.004	3	.01	15	-.344	2
195		3	max	45.584	2	273.92	2	-6.573	15	0	10	.043	3	.468	3
196			min	-27.336	9	-106.611	3	-118.728	1	-.004	3	0	10	-.783	2
197		4	max	45.584	2	104.008	2	-4.068	15	0	10	.015	3	.55	3
198			min	-27.336	9	-27.046	3	-73.444	1	-.004	3	-.116	1	-1.014	2
199		5	max	45.584	2	52.519	3	-1.564	15	0	10	-.005	12	.534	3
200			min	-27.336	9	-65.904	2	-28.16	1	-.004	3	-.179	1	-1.037	2
201		6	max	45.584	2	132.083	3	17.125	1	0	10	-.01	15	.421	3
202			min	-27.336	9	-235.816	2	-13.005	3	-.004	3	-.185	1	-.853	2
203		7	max	45.584	2	211.648	3	62.409	1	0	10	-.008	15	.211	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
204			min	-27.336	9	-405.728	2	-9.248	3	-.004	3	-.137	1	-.461	2
205		8	max	45.584	2	291.213	3	107.693	1	0	10	-.002	15	.139	2
206			min	-27.336	9	-575.64	2	-5.492	3	-.004	3	-.048	3	-.096	3
207		9	max	45.584	2	370.778	3	152.978	1	0	10	.127	1	.947	2
208			min	-27.336	9	-745.552	2	-1.735	3	-.004	3	-.053	3	-.5	3
209		10	max	45.584	2	450.342	3	198.262	1	0	10	.341	1	1.962	2
210			min	-27.336	9	-915.464	2	2.022	3	-.004	3	-.053	3	-1.002	3
211		11	max	45.584	2	745.552	2	1.735	3	.004	3	.127	1	.947	2
212			min	-27.336	9	-370.778	3	-152.978	1	0	10	-.053	3	-.5	3
213		12	max	45.584	2	575.64	2	5.492	3	.004	3	-.002	15	.139	2
214			min	-27.336	9	-291.213	3	-107.693	1	0	10	-.048	3	-.096	3
215		13	max	45.584	2	405.728	2	9.248	3	.004	3	-.008	15	.211	3
216			min	-27.336	9	-211.648	3	-62.409	1	0	10	-.137	1	-.461	2
217		14	max	45.584	2	235.816	2	13.005	3	.004	3	-.01	15	.421	3
218			min	-27.336	9	-132.083	3	-17.125	1	0	10	-.185	1	-.853	2
219		15	max	45.584	2	65.904	2	28.16	1	.004	3	-.005	12	.534	3
220			min	-27.336	9	-52.519	3	1.564	15	0	10	-.179	1	-1.037	2
221		16	max	45.584	2	27.046	3	73.444	1	.004	3	.015	3	.55	3
222			min	-27.336	9	-104.008	2	4.068	15	0	10	-.116	1	-1.014	2
223		17	max	45.584	2	106.611	3	118.728	1	.004	3	.043	3	.468	3
224			min	-27.336	9	-273.92	2	6.573	15	0	10	0	10	-.783	2
225		18	max	45.584	2	186.175	3	164.013	1	.004	3	.174	1	.289	3
226			min	-27.336	9	-443.832	2	9.078	15	0	10	.01	15	-.344	2
227		19	max	45.584	2	265.74	3	209.297	1	.004	3	.402	1	.302	2
228			min	-27.336	9	-613.744	2	11.583	15	0	10	.022	15	.005	15
229	M13	1	max	-8.126	15	616.319	2	-11.15	15	.003	3	.34	1	.252	2
230			min	-147.542	1	-276.696	3	-200.893	1	-.014	2	.019	15	-.071	3
231		2	max	-8.126	15	446.407	2	-8.645	15	.003	3	.122	1	.219	3
232			min	-147.542	1	-197.131	3	-155.609	1	-.014	2	.007	15	-.398	2
233		3	max	-8.126	15	276.495	2	-6.14	15	.003	3	.036	3	.411	3
234			min	-147.542	1	-117.566	3	-110.324	1	-.014	2	-.04	1	-.84	2
235		4	max	-8.126	15	106.583	2	-3.636	15	.003	3	.01	3	.506	3
236			min	-147.542	1	-38.001	3	-65.04	1	-.014	2	-.147	1	-1.074	2
237		5	max	-8.126	15	41.563	3	-1.131	15	.003	3	-.008	12	.504	3
238			min	-147.542	1	-63.329	2	-19.756	1	-.014	2	-.199	1	-1.1	2
239		6	max	-8.126	15	121.128	3	25.529	1	.003	3	-.011	15	.405	3
240			min	-147.542	1	-233.241	2	-11.61	3	-.014	2	-.196	1	-.919	2
241		7	max	-8.126	15	200.693	3	70.813	1	.003	3	-.008	15	.208	3
242			min	-147.542	1	-403.153	2	-7.854	3	-.014	2	-.137	1	-.53	2
243		8	max	-8.126	15	280.257	3	116.097	1	.003	3	0	10	.066	2
244			min	-147.542	1	-573.065	2	-4.097	3	-.014	2	-.047	3	-.086	3
245		9	max	-8.126	15	359.822	3	161.382	1	.003	3	.147	1	.871	2
246			min	-147.542	1	-742.977	2	-.34	3	-.014	2	-.049	3	-.477	3
247		10	max	-8.126	15	724.499	1	111.054	11	0	15	.372	1	1.883	2
248			min	-147.542	1	-912.889	2	-206.666	1	-.014	2	-.047	3	-.966	3
249		11	max	-8.126	15	742.977	2	.34	3	.014	2	.147	1	.871	2
250			min	-147.542	1	-359.822	3	-161.382	1	-.003	3	-.049	3	-.477	3
251		12	max	-8.126	15	573.065	2	4.097	3	.014	2	0	10	.066	2
252			min	-147.542	1	-280.257	3	-116.097	1	-.003	3	-.047	3	-.086	3
253		13	max	-8.126	15	403.153	2	7.854	3	.014	2	-.008	15	.208	3
254			min	-147.542	1	-200.693	3	-70.813	1	-.003	3	-.137	1	-.53	2
255		14	max	-8.126	15	233.241	2	11.61	3	.014	2	-.011	15	.405	3
256			min	-147.542	1	-121.128	3	-25.529	1	-.003	3	-.196	1	-.919	2
257		15	max	-8.126	15	63.329	2	19.756	1	.014	2	-.008	12	.504	3
258			min	-147.542	1	-41.563	3	1.131	15	-.003	3	-.199	1	-1.1	2
259		16	max	-8.126	15	38.001	3	65.04	1	.014	2	.01	3	.506	3
260			min	-147.542	1	-106.583	2	3.636	15	-.003	3	-.147	1	-1.074	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
261		17	max	-8.126	15	117.566	3	110.324	1	.014	2	.036	3	.411	3
262			min	-147.542	1	-276.495	2	6.14	15	-.003	3	-.04	1	-.84	2
263		18	max	-8.126	15	197.131	3	155.609	1	.014	2	.122	1	.219	3
264			min	-147.542	1	-446.407	2	8.645	15	-.003	3	.007	15	-.398	2
265		19	max	-8.126	15	276.696	3	200.893	1	.014	2	.34	1	.252	2
266			min	-147.542	1	-616.319	2	11.15	15	-.003	3	.019	15	-.071	3
267	M2	1	max	2007.025	1	1141.219	3	262.517	2	.017	3	.474	3	4.614	3
268			min	-1335.855	3	-891.543	2	-286.208	3	-.034	2	-.383	2	.138	10
269		2	max	1446.907	1	738.303	3	180.007	2	.002	2	.377	3	4.281	3
270			min	-1079.448	3	33.205	15	-246.074	3	-.001	3	-.292	2	.193	15
271		3	max	1443.801	1	738.303	3	180.007	2	.002	2	.293	3	4.029	3
272			min	-1081.777	3	33.205	15	-246.074	3	-.001	3	-.23	2	.181	15
273		4	max	1440.695	1	738.303	3	180.007	2	.002	2	.209	3	3.778	3
274			min	-1084.107	3	33.205	15	-246.074	3	-.001	3	-.169	2	.17	15
275		5	max	1437.589	1	738.303	3	180.007	2	.002	2	.125	3	3.526	3
276			min	-1086.436	3	33.205	15	-246.074	3	-.001	3	-.113	1	.159	15
277		6	max	1434.482	1	738.303	3	180.007	2	.002	2	.041	3	3.274	3
278			min	-1088.766	3	33.205	15	-246.074	3	-.001	3	-.058	1	.147	15
279		7	max	1431.376	1	738.303	3	180.007	2	.002	2	.015	2	3.022	3
280			min	-1091.096	3	33.205	15	-246.074	3	-.001	3	-.043	3	.136	15
281		8	max	1428.27	1	738.303	3	180.007	2	.002	2	.077	2	2.77	3
282			min	-1093.425	3	33.205	15	-246.074	3	-.001	3	-.127	3	.125	15
283		9	max	1425.164	1	738.303	3	180.007	2	.002	2	.138	2	2.518	3
284			min	-1095.755	3	33.205	15	-246.074	3	-.001	3	-.211	3	.113	15
285		10	max	1422.058	1	738.303	3	180.007	2	.002	2	.199	2	2.267	3
286			min	-1098.084	3	33.205	15	-246.074	3	-.001	3	-.295	3	.102	15
287		11	max	1418.952	1	738.303	3	180.007	2	.002	2	.261	2	2.015	3
288			min	-1100.414	3	33.205	15	-246.074	3	-.001	3	-.379	3	.091	15
289		12	max	1415.846	1	738.303	3	180.007	2	.002	2	.322	2	1.763	3
290			min	-1102.743	3	33.205	15	-246.074	3	-.001	3	-.463	3	.079	15
291		13	max	1412.74	1	738.303	3	180.007	2	.002	2	.384	2	1.511	3
292			min	-1105.073	3	33.205	15	-246.074	3	-.001	3	-.546	3	.068	15
293		14	max	1409.634	1	738.303	3	180.007	2	.002	2	.445	2	1.259	3
294			min	-1107.403	3	33.205	15	-246.074	3	-.001	3	-.63	3	.057	15
295		15	max	1406.528	1	738.303	3	180.007	2	.002	2	.506	2	1.007	3
296			min	-1109.732	3	33.205	15	-246.074	3	-.001	3	-.714	3	.045	15
297		16	max	1403.422	1	738.303	3	180.007	2	.002	2	.568	2	.756	3
298			min	-1112.062	3	33.205	15	-246.074	3	-.001	3	-.798	3	.034	15
299		17	max	1400.315	1	738.303	3	180.007	2	.002	2	.629	2	.504	3
300			min	-1114.391	3	33.205	15	-246.074	3	-.001	3	-.882	3	.023	15
301		18	max	1397.209	1	738.303	3	180.007	2	.002	2	.691	2	.252	3
302			min	-1116.721	3	33.205	15	-246.074	3	-.001	3	-.966	3	.011	15
303		19	max	1394.103	1	738.303	3	180.007	2	.002	2	.752	2	0	1
304			min	-1119.05	3	33.205	15	-246.074	3	-.001	3	-1.05	3	0	1
305	M5	1	max	5488.183	2	2975.615	3	0	1	0	1	0	1	9.813	3
306			min	-4156.966	3	-2893.782	2	0	1	0	1	0	1	-.044	10
307		2	max	3666.511	1	1551.353	3	0	1	0	1	0	1	8.996	3
308			min	-3254.624	3	50.512	10	0	1	0	1	0	1	.293	10
309		3	max	3663.405	1	1551.353	3	0	1	0	1	0	1	8.467	3
310			min	-3256.953	3	50.512	10	0	1	0	1	0	1	.276	10
311		4	max	3660.299	1	1551.353	3	0	1	0	1	0	1	7.938	3
312			min	-3259.283	3	50.512	10	0	1	0	1	0	1	.258	10
313		5	max	3657.193	1	1551.353	3	0	1	0	1	0	1	7.409	3
314			min	-3261.612	3	50.512	10	0	1	0	1	0	1	.241	10
315		6	max	3654.087	1	1551.353	3	0	1	0	1	0	1	6.879	3
316			min	-3263.942	3	50.512	10	0	1	0	1	0	1	.224	10
317		7	max	3650.98	1	1551.353	3	0	1	0	1	0	1	6.35	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
318			min	-3266.271	3	50.512	10	0	1	0	1	0	1	.207	10
319		8	max	3647.874	1	1551.353	3	0	1	0	1	0	1	5.821	3
320			min	-3268.601	3	50.512	10	0	1	0	1	0	1	.19	10
321		9	max	3644.768	1	1551.353	3	0	1	0	1	0	1	5.292	3
322			min	-3270.931	3	50.512	10	0	1	0	1	0	1	.172	10
323		10	max	3641.662	1	1551.353	3	0	1	0	1	0	1	4.763	3
324			min	-3273.26	3	50.512	10	0	1	0	1	0	1	.155	10
325		11	max	3638.556	1	1551.353	3	0	1	0	1	0	1	4.233	3
326			min	-3275.59	3	50.512	10	0	1	0	1	0	1	.138	10
327		12	max	3635.45	1	1551.353	3	0	1	0	1	0	1	3.704	3
328			min	-3277.919	3	50.512	10	0	1	0	1	0	1	.121	10
329		13	max	3632.344	1	1551.353	3	0	1	0	1	0	1	3.175	3
330			min	-3280.249	3	50.512	10	0	1	0	1	0	1	.103	10
331		14	max	3629.238	1	1551.353	3	0	1	0	1	0	1	2.646	3
332			min	-3282.578	3	50.512	10	0	1	0	1	0	1	.086	10
333		15	max	3626.132	1	1551.353	3	0	1	0	1	0	1	2.117	3
334			min	-3284.908	3	50.512	10	0	1	0	1	0	1	.069	10
335		16	max	3623.026	1	1551.353	3	0	1	0	1	0	1	1.588	3
336			min	-3287.238	3	50.512	10	0	1	0	1	0	1	.052	10
337		17	max	3619.919	1	1551.353	3	0	1	0	1	0	1	1.058	3
338			min	-3289.567	3	50.512	10	0	1	0	1	0	1	.034	10
339		18	max	3616.813	1	1551.353	3	0	1	0	1	0	1	.529	3
340			min	-3291.897	3	50.512	10	0	1	0	1	0	1	.017	10
341		19	max	3613.707	1	1551.353	3	0	1	0	1	0	1	0	1
342			min	-3294.226	3	50.512	10	0	1	0	1	0	1	0	1
343	M8	1	max	2007.025	1	1141.219	3	286.208	3	.034	2	.383	2	4.614	3
344			min	-1335.855	3	-891.543	2	-262.517	2	-.017	3	-.474	3	.138	10
345		2	max	1446.907	1	738.303	3	246.074	3	.001	3	.292	2	4.281	3
346			min	-1079.448	3	33.205	15	-180.007	2	-.002	2	-.377	3	.193	15
347		3	max	1443.801	1	738.303	3	246.074	3	.001	3	.23	2	4.029	3
348			min	-1081.777	3	33.205	15	-180.007	2	-.002	2	-.293	3	.181	15
349		4	max	1440.695	1	738.303	3	246.074	3	.001	3	.169	2	3.778	3
350			min	-1084.107	3	33.205	15	-180.007	2	-.002	2	-.209	3	.17	15
351		5	max	1437.589	1	738.303	3	246.074	3	.001	3	.113	1	3.526	3
352			min	-1086.436	3	33.205	15	-180.007	2	-.002	2	-.125	3	.159	15
353		6	max	1434.482	1	738.303	3	246.074	3	.001	3	.058	1	3.274	3
354			min	-1088.766	3	33.205	15	-180.007	2	-.002	2	-.041	3	.147	15
355		7	max	1431.376	1	738.303	3	246.074	3	.001	3	.043	3	3.022	3
356			min	-1091.096	3	33.205	15	-180.007	2	-.002	2	-.015	2	.136	15
357		8	max	1428.27	1	738.303	3	246.074	3	.001	3	.127	3	2.77	3
358			min	-1093.425	3	33.205	15	-180.007	2	-.002	2	-.077	2	.125	15
359		9	max	1425.164	1	738.303	3	246.074	3	.001	3	.211	3	2.518	3
360			min	-1095.755	3	33.205	15	-180.007	2	-.002	2	-.138	2	.113	15
361		10	max	1422.058	1	738.303	3	246.074	3	.001	3	.295	3	2.267	3
362			min	-1098.084	3	33.205	15	-180.007	2	-.002	2	-.199	2	.102	15
363		11	max	1418.952	1	738.303	3	246.074	3	.001	3	.379	3	2.015	3
364			min	-1100.414	3	33.205	15	-180.007	2	-.002	2	-.261	2	.091	15
365		12	max	1415.846	1	738.303	3	246.074	3	.001	3	.463	3	1.763	3
366			min	-1102.743	3	33.205	15	-180.007	2	-.002	2	-.322	2	.079	15
367		13	max	1412.74	1	738.303	3	246.074	3	.001	3	.546	3	1.511	3
368			min	-1105.073	3	33.205	15	-180.007	2	-.002	2	-.384	2	.068	15
369		14	max	1409.634	1	738.303	3	246.074	3	.001	3	.63	3	1.259	3
370			min	-1107.403	3	33.205	15	-180.007	2	-.002	2	-.445	2	.057	15
371		15	max	1406.528	1	738.303	3	246.074	3	.001	3	.714	3	1.007	3
372			min	-1109.732	3	33.205	15	-180.007	2	-.002	2	-.506	2	.045	15
373		16	max	1403.422	1	738.303	3	246.074	3	.001	3	.798	3	.756	3
374			min	-1112.062	3	33.205	15	-180.007	2	-.002	2	-.568	2	.034	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
375		17	max	1400.315	1	738.303	3	246.074	3	.001	3	.882	3	.504	3
376			min	-1114.391	3	33.205	15	-180.007	2	-.002	2	-.629	2	.023	15
377		18	max	1397.209	1	738.303	3	246.074	3	.001	3	.966	3	.252	3
378			min	-1116.721	3	33.205	15	-180.007	2	-.002	2	-.691	2	.011	15
379		19	max	1394.103	1	738.303	3	246.074	3	.001	3	1.05	3	0	1
380			min	-1119.05	3	33.205	15	-180.007	2	-.002	2	-.752	2	0	1
381	M3	1	max	1264.86	2	4.147	4	82.145	2	.006	3	.018	3	0	1
382			min	-475.059	3	.975	15	-40.378	3	-.009	2	-.037	2	0	1
383		2	max	1264.622	2	3.686	4	82.145	2	.006	3	.006	3	0	15
384			min	-475.237	3	.866	15	-40.378	3	-.009	2	-.013	2	-.001	4
385		3	max	1264.384	2	3.225	4	82.145	2	.006	3	.011	2	0	15
386			min	-475.416	3	.758	15	-40.378	3	-.009	2	-.006	3	-.002	4
387		4	max	1264.146	2	2.765	4	82.145	2	.006	3	.035	2	0	15
388			min	-475.594	3	.65	15	-40.378	3	-.009	2	-.017	3	-.003	4
389		5	max	1263.908	2	2.304	4	82.145	2	.006	3	.059	2	0	15
390			min	-475.773	3	.542	15	-40.378	3	-.009	2	-.029	3	-.004	4
391		6	max	1263.67	2	1.843	4	82.145	2	.006	3	.083	2	-.001	15
392			min	-475.951	3	.433	15	-40.378	3	-.009	2	-.041	3	-.004	4
393		7	max	1263.432	2	1.382	4	82.145	2	.006	3	.106	2	-.001	15
394			min	-476.13	3	.325	15	-40.378	3	-.009	2	-.052	3	-.005	4
395		8	max	1263.194	2	.922	4	82.145	2	.006	3	.13	2	-.001	15
396			min	-476.308	3	.217	15	-40.378	3	-.009	2	-.064	3	-.005	4
397		9	max	1262.956	2	.461	4	82.145	2	.006	3	.154	2	-.001	15
398			min	-476.487	3	.108	15	-40.378	3	-.009	2	-.076	3	-.005	4
399		10	max	1262.718	2	0	1	82.145	2	.006	3	.178	2	-.001	15
400			min	-476.665	3	0	1	-40.378	3	-.009	2	-.088	3	-.005	4
401		11	max	1262.48	2	-.108	15	82.145	2	.006	3	.202	2	-.001	15
402			min	-476.844	3	-.461	4	-40.378	3	-.009	2	-.099	3	-.005	4
403		12	max	1262.242	2	-.217	15	82.145	2	.006	3	.226	2	-.001	15
404			min	-477.022	3	-.922	4	-40.378	3	-.009	2	-.111	3	-.005	4
405		13	max	1262.004	2	-.325	15	82.145	2	.006	3	.249	2	-.001	15
406			min	-477.201	3	-1.382	4	-40.378	3	-.009	2	-.123	3	-.005	4
407		14	max	1261.765	2	-.433	15	82.145	2	.006	3	.273	2	-.001	15
408			min	-477.379	3	-1.843	4	-40.378	3	-.009	2	-.135	3	-.004	4
409		15	max	1261.527	2	-.542	15	82.145	2	.006	3	.297	2	0	15
410			min	-477.558	3	-2.304	4	-40.378	3	-.009	2	-.146	3	-.004	4
411		16	max	1261.289	2	-.65	15	82.145	2	.006	3	.321	2	0	15
412			min	-477.736	3	-2.765	4	-40.378	3	-.009	2	-.158	3	-.003	4
413		17	max	1261.051	2	-.758	15	82.145	2	.006	3	.345	2	0	15
414			min	-477.915	3	-3.225	4	-40.378	3	-.009	2	-.17	3	-.002	4
415		18	max	1260.813	2	-.866	15	82.145	2	.006	3	.369	2	0	15
416			min	-478.093	3	-3.686	4	-40.378	3	-.009	2	-.181	3	-.001	4
417		19	max	1260.575	2	-.975	15	82.145	2	.006	3	.393	2	0	1
418			min	-478.272	3	-4.147	4	-40.378	3	-.009	2	-.193	3	0	1
419	M6	1	max	3758.296	2	4.147	4	0	1	0	1	0	1	0	1
420			min	-1663.788	3	.975	15	0	1	0	1	0	1	0	1
421		2	max	3758.058	2	3.686	4	0	1	0	1	0	1	0	15
422			min	-1663.966	3	.866	15	0	1	0	1	0	1	-.001	4
423		3	max	3757.82	2	3.225	4	0	1	0	1	0	1	0	15
424			min	-1664.145	3	.758	15	0	1	0	1	0	1	-.002	4
425		4	max	3757.582	2	2.765	4	0	1	0	1	0	1	0	15
426			min	-1664.323	3	.65	15	0	1	0	1	0	1	-.003	4
427		5	max	3757.344	2	2.304	4	0	1	0	1	0	1	0	15
428			min	-1664.502	3	.542	15	0	1	0	1	0	1	-.004	4
429		6	max	3757.106	2	1.843	4	0	1	0	1	0	1	-.001	15
430			min	-1664.68	3	.433	15	0	1	0	1	0	1	-.004	4
431		7	max	3756.868	2	1.382	4	0	1	0	1	0	1	-.001	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
432			min	-1664.859	3	.325	15	0	1	0	1	0	1	-.005	4
433		8	max	3756.63	2	.922	4	0	1	0	1	0	1	-.001	15
434			min	-1665.037	3	.217	15	0	1	0	1	0	1	-.005	4
435		9	max	3756.392	2	.461	4	0	1	0	1	0	1	-.001	15
436			min	-1665.216	3	.108	15	0	1	0	1	0	1	-.005	4
437		10	max	3756.154	2	0	1	0	1	0	1	0	1	-.001	15
438			min	-1665.394	3	0	1	0	1	0	1	0	1	-.005	4
439		11	max	3755.916	2	-.108	15	0	1	0	1	0	1	-.001	15
440			min	-1665.573	3	-.461	4	0	1	0	1	0	1	-.005	4
441		12	max	3755.678	2	-.217	15	0	1	0	1	0	1	-.001	15
442			min	-1665.751	3	-.922	4	0	1	0	1	0	1	-.005	4
443		13	max	3755.44	2	-.325	15	0	1	0	1	0	1	-.001	15
444			min	-1665.93	3	-1.382	4	0	1	0	1	0	1	-.005	4
445		14	max	3755.202	2	-.433	15	0	1	0	1	0	1	-.001	15
446			min	-1666.108	3	-1.843	4	0	1	0	1	0	1	-.004	4
447		15	max	3754.964	2	-.542	15	0	1	0	1	0	1	0	15
448			min	-1666.287	3	-2.304	4	0	1	0	1	0	1	-.004	4
449		16	max	3754.726	2	-.65	15	0	1	0	1	0	1	0	15
450			min	-1666.465	3	-2.765	4	0	1	0	1	0	1	-.003	4
451		17	max	3754.488	2	-.758	15	0	1	0	1	0	1	0	15
452			min	-1666.644	3	-3.225	4	0	1	0	1	0	1	-.002	4
453		18	max	3754.25	2	-.866	15	0	1	0	1	0	1	0	15
454			min	-1666.822	3	-3.686	4	0	1	0	1	0	1	-.001	4
455		19	max	3754.012	2	-.975	15	0	1	0	1	0	1	0	1
456			min	-1667.001	3	-4.147	4	0	1	0	1	0	1	0	1
457	M9	1	max	1264.86	2	4.147	4	40.378	3	.009	2	.037	2	0	1
458			min	-475.059	3	.975	15	-82.145	2	-.006	3	-.018	3	0	1
459		2	max	1264.622	2	3.686	4	40.378	3	.009	2	.013	2	0	15
460			min	-475.237	3	.866	15	-82.145	2	-.006	3	-.006	3	-.001	4
461		3	max	1264.384	2	3.225	4	40.378	3	.009	2	.006	3	0	15
462			min	-475.416	3	.758	15	-82.145	2	-.006	3	-.011	2	-.002	4
463		4	max	1264.146	2	2.765	4	40.378	3	.009	2	.017	3	0	15
464			min	-475.594	3	.65	15	-82.145	2	-.006	3	-.035	2	-.003	4
465		5	max	1263.908	2	2.304	4	40.378	3	.009	2	.029	3	0	15
466			min	-475.773	3	.542	15	-82.145	2	-.006	3	-.059	2	-.004	4
467		6	max	1263.67	2	1.843	4	40.378	3	.009	2	.041	3	-.001	15
468			min	-475.951	3	.433	15	-82.145	2	-.006	3	-.083	2	-.004	4
469		7	max	1263.432	2	1.382	4	40.378	3	.009	2	.052	3	-.001	15
470			min	-476.13	3	.325	15	-82.145	2	-.006	3	-.106	2	-.005	4
471		8	max	1263.194	2	.922	4	40.378	3	.009	2	.064	3	-.001	15
472			min	-476.308	3	.217	15	-82.145	2	-.006	3	-.13	2	-.005	4
473		9	max	1262.956	2	.461	4	40.378	3	.009	2	.076	3	-.001	15
474			min	-476.487	3	.108	15	-82.145	2	-.006	3	-.154	2	-.005	4
475		10	max	1262.718	2	0	1	40.378	3	.009	2	.088	3	-.001	15
476			min	-476.665	3	0	1	-82.145	2	-.006	3	-.178	2	-.005	4
477		11	max	1262.48	2	-.108	15	40.378	3	.009	2	.099	3	-.001	15
478			min	-476.844	3	-.461	4	-82.145	2	-.006	3	-.202	2	-.005	4
479		12	max	1262.242	2	-.217	15	40.378	3	.009	2	.111	3	-.001	15
480			min	-477.022	3	-.922	4	-82.145	2	-.006	3	-.226	2	-.005	4
481		13	max	1262.004	2	-.325	15	40.378	3	.009	2	.123	3	-.001	15
482			min	-477.201	3	-1.382	4	-82.145	2	-.006	3	-.249	2	-.005	4
483		14	max	1261.765	2	-.433	15	40.378	3	.009	2	.135	3	-.001	15
484			min	-477.379	3	-1.843	4	-82.145	2	-.006	3	-.273	2	-.004	4
485		15	max	1261.527	2	-.542	15	40.378	3	.009	2	.146	3	0	15
486			min	-477.558	3	-2.304	4	-82.145	2	-.006	3	-.297	2	-.004	4
487		16	max	1261.289	2	-.65	15	40.378	3	.009	2	.158	3	0	15
488			min	-477.736	3	-2.765	4	-82.145	2	-.006	3	-.321	2	-.003	4

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
489		17	max	1261.051	2	-.758	15	40.378	3	.009	2	.17	3	0	15
490			min	-477.915	3	-3.225	4	-82.145	2	-.006	3	-.345	2	-.002	4
491		18	max	1260.813	2	-.866	15	40.378	3	.009	2	.181	3	0	15
492			min	-478.093	3	-3.686	4	-82.145	2	-.006	3	-.369	2	-.001	4
493		19	max	1260.575	2	-.975	15	40.378	3	.009	2	.193	3	0	1
494			min	-478.272	3	-4.147	4	-82.145	2	-.006	3	-.393	2	0	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M1	1	max	-.012	15	-.017	15	.027	1	1.006e-2	3	NC	3	NC	3
2			min	-.255	3	-.359	1	.001	15	-2.435e-2	2	350.608	1	2516.916	1
3		2	max	-.012	15	-.014	15	.008	1	1.006e-2	3	NC	3	NC	3
4			min	-.255	3	-.291	1	0	15	-2.435e-2	2	427.398	1	3928.168	1
5		3	max	-.012	15	-.011	15	0	15	9.501e-3	3	NC	2	NC	2
6			min	-.255	3	-.222	1	-.008	1	-2.237e-2	2	547.455	1	7645.81	1
7		4	max	-.012	15	-.008	15	0	15	8.649e-3	3	NC	3	NC	1
8			min	-.255	3	-.156	1	-.016	1	-1.934e-2	2	749.355	1	NC	1
9		5	max	-.012	15	-.006	15	0	15	7.797e-3	3	NC	3	NC	1
10			min	-.255	3	-.101	3	-.016	1	-1.632e-2	2	912.85	9	NC	1
11		6	max	-.012	15	-.001	10	0	3	8.24e-3	3	NC	11	NC	2
12			min	-.255	3	-.088	3	-.012	1	-1.591e-2	2	959.434	2	9901.985	1
13		7	max	-.012	15	.011	2	.002	3	9.578e-3	3	NC	15	NC	2
14			min	-.255	3	-.07	3	-.006	1	-1.732e-2	2	825.888	2	6609.848	1
15		8	max	-.012	15	.024	2	.001	3	1.092e-2	3	NC	1	NC	2
16			min	-.255	3	-.046	3	-.002	2	-1.873e-2	2	762.061	2	5238.562	1
17		9	max	-.012	15	.038	1	0	15	1.231e-2	3	NC	5	NC	2
18			min	-.255	3	-.02	3	0	1	-1.883e-2	2	723.086	2	5233.079	1
19		10	max	-.012	15	.062	1	0	2	1.381e-2	3	NC	5	NC	2
20			min	-.255	3	.003	15	0	15	-1.66e-2	2	692.707	2	5151.007	1
21		11	max	-.012	15	.083	1	.002	3	1.53e-2	3	NC	5	NC	2
22			min	-.255	3	.005	15	-.001	2	-1.437e-2	2	671.866	2	5416.555	1
23		12	max	-.012	15	.102	1	.007	3	1.279e-2	3	NC	4	NC	2
24			min	-.255	3	.006	15	-.006	1	-1.09e-2	2	660.692	2	6809.381	1
25		13	max	-.012	15	.123	3	.012	3	8.019e-3	3	NC	4	NC	2
26			min	-.255	3	.007	15	-.008	2	-6.716e-3	2	577.7	3	6738.353	1
27		14	max	-.012	15	.182	3	.01	3	3.473e-3	3	NC	4	NC	2
28			min	-.255	3	.008	15	-.003	2	-2.7e-3	2	460.891	3	4827.034	1
29		15	max	-.012	15	.26	3	.011	1	9.062e-3	3	NC	4	NC	3
30			min	-.255	3	-.007	10	0	15	-5.947e-3	2	362.936	3	3597.22	1
31		16	max	-.012	15	.354	3	.014	1	1.465e-2	3	NC	4	NC	3
32			min	-.256	3	-.028	10	0	15	-9.194e-3	2	289.79	3	3335.469	1
33		17	max	-.012	15	.456	3	.008	1	2.024e-2	3	NC	4	NC	3
34			min	-.256	3	-.064	2	0	12	-1.244e-2	2	237.223	3	3896.212	1
35		18	max	-.012	15	.562	3	0	15	2.388e-2	3	NC	4	NC	2
36			min	-.256	3	-.108	2	-.007	1	-1.456e-2	2	199.713	3	7250.918	1
37		19	max	-.012	15	.668	3	-.001	15	2.388e-2	3	NC	1	NC	1
38			min	-.256	3	-.152	2	-.026	1	-1.456e-2	2	172.471	3	NC	1
39	M4	1	max	-.019	15	-.032	15	0	1	0	1	NC	3	NC	1
40			min	-.535	3	-.794	1	0	1	0	1	214.907	1	NC	1
41		2	max	-.019	15	-.026	15	0	1	0	1	NC	10	NC	1
42			min	-.535	3	-.632	1	0	1	0	1	289.944	1	NC	1
43		3	max	-.019	15	-.02	15	0	1	0	1	5408.266	12	NC	1
44			min	-.535	3	-.471	1	0	1	0	1	446.166	1	NC	1
45		4	max	-.019	15	-.015	15	0	1	0	1	NC	11	NC	1
46			min	-.535	3	-.316	1	0	1	0	1	570.515	2	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
47		5	max	-.019	15	-.01	15	0	1	0	1	NC	1	NC	1
48			min	-.535	3	-.201	3	0	1	0	1	366.148	2	NC	1
49		6	max	-.019	15	.002	10	0	1	0	1	NC	15	NC	1
50			min	-.535	3	-.186	3	0	1	0	1	294.629	2	NC	1
51		7	max	-.019	15	.034	2	0	1	0	1	NC	5	NC	1
52			min	-.535	3	-.151	3	0	1	0	1	266.19	2	NC	1
53		8	max	-.019	15	.058	2	0	1	0	1	NC	5	NC	1
54			min	-.535	3	-.103	3	0	1	0	1	254.2	2	NC	1
55		9	max	-.019	15	.079	1	0	1	0	1	NC	4	NC	1
56			min	-.535	3	-.047	3	0	1	0	1	247.747	2	NC	1
57		10	max	-.019	15	.118	1	0	1	0	1	NC	4	NC	1
58			min	-.536	3	.006	15	0	1	0	1	242.253	2	NC	1
59		11	max	-.019	15	.154	1	0	1	0	1	NC	5	NC	1
60			min	-.536	3	.008	15	0	1	0	1	238.465	2	NC	1
61		12	max	-.018	10	.185	1	0	1	0	1	NC	5	NC	1
62			min	-.536	3	.01	15	0	1	0	1	236.725	2	NC	1
63		13	max	-.018	10	.252	3	0	1	0	1	NC	5	NC	1
64			min	-.536	3	.012	15	0	1	0	1	240.474	2	NC	1
65		14	max	-.018	10	.384	3	0	1	0	1	NC	5	NC	1
66			min	-.537	3	.009	10	0	1	0	1	256.291	2	NC	1
67		15	max	-.018	10	.567	3	0	1	0	1	NC	5	NC	1
68			min	-.537	3	-.033	10	0	1	0	1	191.637	3	NC	1
69		16	max	-.018	10	.787	3	0	1	0	1	NC	5	NC	1
70			min	-.537	3	-.115	2	0	1	0	1	145.7	3	NC	1
71		17	max	-.018	10	1.031	3	0	1	0	1	NC	5	NC	1
72			min	-.537	3	-.229	2	0	1	0	1	115.172	3	NC	1
73		18	max	-.018	10	1.283	3	0	1	0	1	NC	4	NC	1
74			min	-.537	3	-.349	2	0	1	0	1	94.655	3	NC	1
75		19	max	-.018	10	1.535	3	0	1	0	1	NC	1	NC	1
76			min	-.537	3	-.469	2	0	1	0	1	80.37	3	NC	1
77	M7	1	max	-.012	15	-.017	15	-.001	15	2.435e-2	2	NC	3	NC	3
78			min	-.255	3	-.359	1	-.027	1	-1.006e-2	3	350.608	1	2516.916	1
79		2	max	-.012	15	-.014	15	0	15	2.435e-2	2	NC	3	NC	3
80			min	-.255	3	-.291	1	-.008	1	-1.006e-2	3	427.398	1	3928.168	1
81		3	max	-.012	15	-.011	15	.008	1	2.237e-2	2	NC	2	NC	2
82			min	-.255	3	-.222	1	0	15	-9.501e-3	3	547.455	1	7645.81	1
83		4	max	-.012	15	-.008	15	.016	1	1.934e-2	2	NC	3	NC	1
84			min	-.255	3	-.156	1	0	15	-8.649e-3	3	749.355	1	NC	1
85		5	max	-.012	15	-.006	15	.016	1	1.632e-2	2	NC	3	NC	1
86			min	-.255	3	-.101	3	0	15	-7.797e-3	3	912.85	9	NC	1
87		6	max	-.012	15	-.001	10	.012	1	1.591e-2	2	NC	11	NC	2
88			min	-.255	3	-.088	3	0	3	-8.24e-3	3	959.434	2	9901.985	1
89		7	max	-.012	15	.011	2	.006	1	1.732e-2	2	NC	15	NC	2
90			min	-.255	3	-.07	3	-.002	3	-9.578e-3	3	825.888	2	6609.848	1
91		8	max	-.012	15	.024	2	.002	2	1.873e-2	2	NC	1	NC	2
92			min	-.255	3	-.046	3	-.001	3	-1.092e-2	3	762.061	2	5238.562	1
93		9	max	-.012	15	.038	1	0	1	1.883e-2	2	NC	5	NC	2
94			min	-.255	3	-.02	3	0	15	-1.231e-2	3	723.086	2	5233.079	1
95		10	max	-.012	15	.062	1	0	15	1.66e-2	2	NC	5	NC	2
96			min	-.255	3	.003	15	0	2	-1.381e-2	3	692.707	2	5151.007	1
97		11	max	-.012	15	.083	1	.001	2	1.437e-2	2	NC	5	NC	2
98			min	-.255	3	.005	15	-.002	3	-1.53e-2	3	671.866	2	5416.555	1
99		12	max	-.012	15	.102	1	.006	1	1.09e-2	2	NC	4	NC	2
100			min	-.255	3	.006	15	-.007	3	-1.279e-2	3	660.692	2	6809.381	1
101		13	max	-.012	15	.123	3	.008	2	6.716e-3	2	NC	4	NC	2
102			min	-.255	3	.007	15	-.012	3	-8.019e-3	3	577.7	3	6738.353	1
103		14	max	-.012	15	.182	3	.003	2	2.7e-3	2	NC	4	NC	2

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
104			min	-.255	3	.008	15	-.01	3	-3.473e-3	3	460.891	3	4827.034	1
105		15	max	-.012	15	.26	3	0	15	5.947e-3	2	NC	4	NC	3
106			min	-.255	3	-.007	10	-.011	1	-9.062e-3	3	362.936	3	3597.22	1
107		16	max	-.012	15	.354	3	0	15	9.194e-3	2	NC	4	NC	3
108			min	-.256	3	-.028	10	-.014	1	-1.465e-2	3	289.79	3	3335.469	1
109		17	max	-.012	15	.456	3	0	12	1.244e-2	2	NC	4	NC	3
110			min	-.256	3	-.064	2	-.008	1	-2.024e-2	3	237.223	3	3896.212	1
111		18	max	-.012	15	.562	3	.007	1	1.456e-2	2	NC	4	NC	2
112			min	-.256	3	-.108	2	0	15	-2.388e-2	3	199.713	3	7250.918	1
113		19	max	-.012	15	.668	3	.026	1	1.456e-2	2	NC	1	NC	1
114			min	-.256	3	-.152	2	.001	15	-2.388e-2	3	172.471	3	NC	1
115	M10	1	max	.001	3	.525	3	.256	3	1.424e-2	3	NC	1	NC	1
116			min	0	10	-.093	2	.012	15	-5.864e-3	2	NC	1	NC	1
117		2	max	.001	3	.889	3	.274	3	1.641e-2	3	NC	5	NC	3
118			min	0	10	-.312	2	.015	15	-7.002e-3	2	727.063	3	3890.595	1
119		3	max	0	3	1.228	3	.342	1	1.858e-2	3	NC	5	NC	5
120			min	0	10	-.512	2	.021	15	-8.141e-3	2	375.657	3	1588.436	1
121		4	max	0	3	1.488	3	.432	1	2.076e-2	3	NC	5	NC	5
122			min	0	10	-.654	2	.026	15	-9.28e-3	2	274.324	3	1030.078	1
123		5	max	0	3	1.635	3	.488	1	2.293e-2	3	NC	5	NC	15
124			min	0	10	-.719	2	.029	15	-1.042e-2	2	238.031	3	844.625	1
125		6	max	0	3	1.659	3	.498	1	2.511e-2	3	NC	5	NC	15
126			min	0	10	-.702	2	.03	15	-1.156e-2	2	232.804	3	818.241	1
127		7	max	0	3	1.577	3	.484	3	2.728e-2	3	NC	5	NC	5
128			min	0	10	-.616	2	.028	15	-1.27e-2	2	250.963	3	918.797	1
129		8	max	0	3	1.427	3	.513	3	2.945e-2	3	NC	5	NC	5
130			min	0	10	-.488	2	.024	15	-1.384e-2	2	292.801	3	1026.444	3
131		9	max	0	3	1.271	3	.531	3	3.163e-2	3	NC	4	NC	5
132			min	0	10	-.365	2	.02	15	-1.497e-2	2	354.076	3	959.759	3
133		10	max	0	1	1.196	3	.537	3	3.38e-2	3	NC	4	NC	5
134			min	0	1	-.307	2	.018	10	-1.611e-2	2	393.904	3	939.369	3
135		11	max	0	10	1.271	3	.531	3	3.163e-2	3	NC	4	NC	5
136			min	0	3	-.365	2	.02	15	-1.497e-2	2	354.076	3	959.759	3
137		12	max	0	10	1.427	3	.513	3	2.945e-2	3	NC	5	NC	5
138			min	0	3	-.488	2	.024	15	-1.384e-2	2	292.801	3	1026.444	3
139		13	max	0	10	1.577	3	.484	3	2.728e-2	3	NC	5	NC	5
140			min	0	3	-.616	2	.028	15	-1.27e-2	2	250.963	3	918.797	1
141		14	max	0	10	1.659	3	.498	1	2.511e-2	3	NC	5	NC	15
142			min	0	3	-.702	2	.03	15	-1.156e-2	2	232.804	3	818.241	1
143		15	max	0	10	1.635	3	.488	1	2.293e-2	3	NC	5	NC	15
144			min	0	3	-.719	2	.029	15	-1.042e-2	2	238.031	3	844.625	1
145		16	max	0	10	1.488	3	.432	1	2.076e-2	3	NC	5	NC	5
146			min	0	3	-.654	2	.026	15	-9.28e-3	2	274.324	3	1030.078	1
147		17	max	0	10	1.228	3	.342	1	1.858e-2	3	NC	5	NC	5
148			min	0	3	-.512	2	.021	15	-8.141e-3	2	375.657	3	1588.436	1
149		18	max	0	10	.889	3	.274	3	1.641e-2	3	NC	5	NC	3
150			min	-.001	3	-.312	2	.015	15	-7.002e-3	2	727.063	3	3890.595	1
151		19	max	0	10	.525	3	.256	3	1.424e-2	3	NC	1	NC	1
152			min	-.001	3	-.093	2	.012	15	-5.864e-3	2	NC	1	NC	1
153	M11	1	max	.003	1	.09	1	.255	3	4.849e-3	3	NC	1	NC	1
154			min	-.004	3	.005	15	.012	15	-1.596e-5	10	NC	1	NC	1
155		2	max	.003	1	.304	3	.262	3	5.429e-3	3	NC	5	NC	2
156			min	-.003	3	-.15	2	.014	15	-3.453e-5	10	1061.496	3	5316.178	1
157		3	max	.002	1	.537	3	.314	1	6.008e-3	3	NC	5	NC	5
158			min	-.003	3	-.319	2	.019	15	-5.311e-5	10	547.612	3	1907.379	1
159		4	max	.002	1	.7	3	.402	1	6.588e-3	3	NC	5	NC	5
160			min	-.002	3	-.425	2	.024	15	-7.168e-5	10	409.329	3	1169.273	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
161		5	max	.002	1	.761	3	.461	1	7.168e-3	3	NC	5	NC	5
162			min	-.002	3	-.451	2	.027	15	-9.025e-5	10	373.976	3	927.982	1
163		6	max	.001	1	.712	3	.477	1	7.748e-3	3	NC	5	NC	5
164			min	-.002	3	-.394	2	.028	15	-1.088e-4	10	401.542	3	878.746	1
165		7	max	.001	1	.571	3	.473	3	8.327e-3	3	NC	5	NC	5
166			min	-.001	3	-.271	2	.027	15	-1.274e-4	10	511.765	3	968.163	1
167		8	max	0	1	.376	3	.507	3	8.907e-3	3	NC	4	NC	5
168			min	0	3	-.114	2	.024	15	-1.46e-4	10	821.806	3	1049.495	3
169		9	max	0	1	.192	3	.529	3	9.487e-3	3	NC	1	NC	5
170			min	0	3	.006	10	.02	15	-1.645e-4	10	1919.022	3	966.713	3
171		10	max	0	1	.166	1	.536	3	1.007e-2	3	NC	4	NC	5
172			min	0	1	.009	15	.019	15	-1.831e-4	10	3495.567	1	941.051	3
173		11	max	0	3	.192	3	.529	3	9.487e-3	3	NC	1	NC	5
174			min	0	1	.006	10	.02	15	-1.645e-4	10	1919.022	3	966.713	3
175		12	max	0	3	.376	3	.507	3	8.907e-3	3	NC	4	NC	5
176			min	0	1	-.114	2	.024	15	-1.46e-4	10	821.806	3	1049.495	3
177		13	max	.001	3	.571	3	.473	3	8.327e-3	3	NC	5	NC	5
178			min	-.001	1	-.271	2	.027	15	-1.274e-4	10	511.765	3	968.163	1
179		14	max	.002	3	.712	3	.477	1	7.748e-3	3	NC	5	NC	5
180			min	-.001	1	-.394	2	.028	15	-1.088e-4	10	401.542	3	878.746	1
181		15	max	.002	3	.761	3	.461	1	7.168e-3	3	NC	5	NC	5
182			min	-.002	1	-.451	2	.027	15	-9.025e-5	10	373.976	3	927.982	1
183		16	max	.002	3	.7	3	.402	1	6.588e-3	3	NC	5	NC	5
184			min	-.002	1	-.425	2	.024	15	-7.168e-5	10	409.329	3	1169.273	1
185		17	max	.003	3	.537	3	.314	1	6.008e-3	3	NC	5	NC	5
186			min	-.002	1	-.319	2	.019	15	-5.311e-5	10	547.612	3	1907.379	1
187		18	max	.003	3	.304	3	.262	3	5.429e-3	3	NC	5	NC	2
188			min	-.003	1	-.15	2	.014	15	-3.453e-5	10	1061.496	3	5316.178	1
189		19	max	.004	3	.09	1	.255	3	4.849e-3	3	NC	1	NC	1
190			min	-.003	1	.005	15	.012	15	-1.596e-5	10	NC	1	NC	1
191	M12	1	max	0	2	.031	2	.255	3	3.631e-3	3	NC	1	NC	1
192			min	0	9	-.03	3	.012	15	2.108e-4	15	NC	1	NC	1
193		2	max	0	2	.136	3	.271	3	4.07e-3	3	NC	5	NC	2
194			min	0	9	-.261	2	.014	15	2.253e-4	15	905.435	2	6201.378	1
195		3	max	0	2	.268	3	.305	1	4.509e-3	3	NC	5	NC	5
196			min	0	9	-.514	2	.019	15	2.399e-4	15	484.934	2	2068.316	1
197		4	max	0	2	.346	3	.391	1	4.948e-3	3	NC	5	NC	5
198			min	0	9	-.676	2	.024	15	2.544e-4	15	373.675	2	1233.353	1
199		5	max	0	2	.36	3	.451	1	5.388e-3	3	NC	5	NC	5
200			min	0	9	-.72	2	.027	15	2.69e-4	15	351.778	2	964.101	1
201		6	max	0	2	.311	3	.469	1	5.827e-3	3	NC	5	NC	5
202			min	0	9	-.643	2	.028	15	2.835e-4	15	391.939	2	903.523	1
203		7	max	0	2	.213	3	.48	3	6.266e-3	3	NC	5	NC	5
204			min	0	9	-.467	2	.027	15	2.981e-4	15	530.488	2	986.835	1
205		8	max	0	2	.091	3	.51	3	6.705e-3	3	NC	5	NC	5
206			min	0	9	-.239	2	.024	15	3.126e-4	15	980.711	2	1035.979	3
207		9	max	0	2	.002	9	.529	3	7.145e-3	3	NC	3	NC	5
208			min	0	9	-.029	2	.02	15	3.272e-4	15	4453.545	2	964.697	3
209		10	max	0	1	.067	2	.535	3	7.584e-3	3	NC	4	NC	5
210			min	0	1	-.068	3	.019	15	3.417e-4	15	6930.351	3	942.79	3
211		11	max	0	9	.002	9	.529	3	7.145e-3	3	NC	3	NC	5
212			min	0	2	-.029	2	.02	15	3.272e-4	15	4453.545	2	964.697	3
213		12	max	0	9	.091	3	.51	3	6.705e-3	3	NC	5	NC	5
214			min	0	2	-.239	2	.024	15	3.126e-4	15	980.711	2	1035.979	3
215		13	max	0	9	.213	3	.48	3	6.266e-3	3	NC	5	NC	5
216			min	0	2	-.467	2	.027	15	2.981e-4	15	530.488	2	986.835	1
217		14	max	0	9	.311	3	.469	1	5.827e-3	3	NC	5	NC	5

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
218			min	0	2	-.643	2	.028	15	2.835e-4	15	391.939	2	903.523	1
219		15	max	0	9	.36	3	.451	1	5.388e-3	3	NC	5	NC	5
220			min	0	2	-.72	2	.027	15	2.69e-4	15	351.778	2	964.101	1
221		16	max	0	9	.346	3	.391	1	4.948e-3	3	NC	5	NC	5
222			min	0	2	-.676	2	.024	15	2.544e-4	15	373.675	2	1233.353	1
223		17	max	0	9	.268	3	.305	1	4.509e-3	3	NC	5	NC	5
224			min	0	2	-.514	2	.019	15	2.399e-4	15	484.934	2	2068.316	1
225		18	max	0	9	.136	3	.271	3	4.07e-3	3	NC	5	NC	2
226			min	0	2	-.261	2	.014	15	2.253e-4	15	905.435	2	6201.378	1
227		19	max	0	9	.031	2	.255	3	3.631e-3	3	NC	1	NC	1
228			min	0	2	-.03	3	.012	15	2.108e-4	15	NC	1	NC	1
229	M13	1	max	0	15	-.013	15	.255	3	9.223e-3	1	NC	1	NC	1
230			min	-.002	1	-.267	1	.012	15	5.179e-5	3	NC	1	NC	1
231		2	max	0	15	.037	3	.275	3	1.061e-2	1	NC	5	NC	3
232			min	-.001	1	-.562	1	.015	15	-2.851e-4	3	738.132	2	3826.889	1
233		3	max	0	15	.157	3	.346	1	1.199e-2	1	NC	5	NC	5
234			min	-.001	1	-.872	2	.021	15	-6.22e-4	3	393.912	2	1569.603	1
235		4	max	0	15	.23	3	.437	1	1.337e-2	1	NC	15	NC	5
236			min	-.001	1	-1.087	2	.026	15	-9.589e-4	3	298.22	2	1019.619	1
237		5	max	0	15	.243	3	.493	1	1.476e-2	1	NC	15	NC	15
238			min	0	1	-1.177	2	.029	15	-1.296e-3	3	270.751	2	836.413	1
239		6	max	0	15	.198	3	.504	1	1.614e-2	1	NC	15	NC	15
240			min	0	1	-1.138	2	.03	15	-1.633e-3	3	281.899	2	809.833	1
241		7	max	0	15	.105	3	.483	3	1.766e-2	2	NC	15	NC	5
242			min	0	1	-.993	2	.028	15	-1.97e-3	3	333.73	2	907.719	1
243		8	max	0	15	-.011	3	.511	3	1.918e-2	2	NC	5	NC	5
244			min	0	1	-.799	1	.024	15	-2.307e-3	3	451.416	2	1030.624	3
245		9	max	0	15	-.026	15	.529	3	2.069e-2	2	NC	3	NC	5
246			min	0	1	-.647	1	.021	15	-2.643e-3	3	679.49	2	964.89	3
247		10	max	0	1	-.024	15	.535	3	2.221e-2	2	NC	5	NC	5
248			min	0	1	-.576	1	.019	15	-2.98e-3	3	852.852	1	944.841	3
249		11	max	0	1	-.026	15	.529	3	2.069e-2	2	NC	3	NC	5
250			min	0	15	-.647	1	.021	15	-2.643e-3	3	679.49	2	964.89	3
251		12	max	0	1	-.011	3	.511	3	1.918e-2	2	NC	5	NC	5
252			min	0	15	-.799	1	.024	15	-2.307e-3	3	451.416	2	1030.624	3
253		13	max	0	1	.105	3	.483	3	1.766e-2	2	NC	15	NC	5
254			min	0	15	-.993	2	.028	15	-1.97e-3	3	333.73	2	907.719	1
255		14	max	0	1	.198	3	.504	1	1.614e-2	1	NC	15	NC	15
256			min	0	15	-1.138	2	.03	15	-1.633e-3	3	281.899	2	809.833	1
257		15	max	0	1	.243	3	.493	1	1.476e-2	1	NC	15	NC	15
258			min	0	15	-1.177	2	.029	15	-1.296e-3	3	270.751	2	836.413	1
259		16	max	.001	1	.23	3	.437	1	1.337e-2	1	NC	15	NC	5
260			min	0	15	-1.087	2	.026	15	-9.589e-4	3	298.22	2	1019.619	1
261		17	max	.001	1	.157	3	.346	1	1.199e-2	1	NC	5	NC	5
262			min	0	15	-.872	2	.021	15	-6.22e-4	3	393.912	2	1569.603	1
263		18	max	.001	1	.037	3	.275	3	1.061e-2	1	NC	5	NC	3
264			min	0	15	-.562	1	.015	15	-2.851e-4	3	738.132	2	3826.889	1
265		19	max	.002	1	-.013	15	.255	3	9.223e-3	1	NC	1	NC	1
266			min	0	15	-.267	1	.012	15	5.179e-5	3	NC	1	NC	1
267	M2	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
268			min	0	1	0	1	0	1	0	1	NC	1	NC	1
269		2	max	0	3	0	10	0	3	6.581e-3	2	NC	1	NC	1
270			min	0	1	-.002	3	0	2	-3.271e-3	3	NC	1	NC	1
271		3	max	0	3	0	10	.001	3	6.043e-3	2	NC	1	NC	1
272			min	0	1	-.006	3	-.001	2	-2.91e-3	3	NC	1	NC	1
273		4	max	0	3	0	15	.003	3	5.504e-3	2	NC	2	NC	1
274			min	0	1	-.013	3	-.002	2	-2.549e-3	3	5816.556	3	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
275		5	max	0	3	0	15	.005	3	4.966e-3	2	NC	2	NC	1
276			min	0	1	-.022	3	-.004	2	-2.188e-3	3	3368.434	3	NC	1
277		6	max	0	3	-.001	15	.007	3	4.427e-3	2	NC	2	NC	1
278			min	0	1	-.033	3	-.005	2	-1.826e-3	3	2211.792	3	7712.118	3
279		7	max	0	3	-.002	15	.009	3	3.888e-3	2	NC	5	NC	1
280			min	0	1	-.047	3	-.007	2	-1.465e-3	3	1573.544	3	6038.309	3
281		8	max	0	3	-.003	15	.011	3	3.35e-3	2	NC	5	NC	4
282			min	0	1	-.062	3	-.009	2	-1.104e-3	3	1183.444	3	4984.673	3
283		9	max	0	3	-.004	15	.013	3	2.811e-3	2	NC	5	NC	4
284			min	0	1	-.079	3	-.01	2	-7.433e-4	3	927.383	3	4294.677	3
285		10	max	0	3	-.004	15	.014	3	2.273e-3	2	NC	5	NC	4
286			min	0	1	-.098	3	-.011	2	-3.823e-4	3	750.047	3	3839.089	3
287		11	max	0	3	-.005	15	.015	3	1.734e-3	2	NC	10	NC	4
288			min	0	1	-.118	3	-.012	1	-2.122e-5	3	622.019	3	3550.067	3
289		12	max	0	3	-.006	15	.015	3	1.196e-3	2	NC	15	NC	4
290			min	-.001	1	-.14	3	-.013	1	-5.446e-5	9	526.481	3	3393.983	3
291		13	max	0	3	-.007	15	.015	3	7.009e-4	3	NC	15	NC	4
292			min	-.001	1	-.163	3	-.014	1	-2.273e-4	9	453.249	3	3361.177	3
293		14	max	0	3	-.008	15	.014	3	1.062e-3	3	8828.485	15	NC	4
294			min	-.001	1	-.186	3	-.013	1	-4.113e-4	1	395.845	3	3467.306	3
295		15	max	0	3	-.009	15	.012	3	1.423e-3	3	7804.988	15	NC	4
296			min	-.001	1	-.211	3	-.013	1	-8.84e-4	1	350.017	3	3765.915	3
297		16	max	.001	3	-.011	15	.008	3	1.784e-3	3	6975.168	15	NC	4
298			min	-.001	1	-.236	3	-.011	1	-1.357e-3	1	312.85	3	4403.522	3
299		17	max	.001	3	-.012	15	.003	3	2.145e-3	3	6293.259	15	NC	4
300			min	-.001	1	-.261	3	-.009	1	-1.83e-3	1	282.3	3	5839.906	3
301		18	max	.001	3	-.013	15	0	15	2.506e-3	3	5726.41	15	NC	1
302			min	-.002	1	-.287	3	-.006	1	-2.302e-3	1	256.9	3	NC	1
303		19	max	.001	3	-.014	15	.003	2	2.867e-3	3	5250.543	15	NC	1
304			min	-.002	1	-.313	3	-.01	3	-2.775e-3	1	235.572	3	NC	1
305	M5	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
306			min	0	1	0	1	0	1	0	1	NC	1	NC	1
307		2	max	0	3	0	10	0	1	0	1	NC	1	NC	1
308			min	0	2	-.003	3	0	1	0	1	NC	1	NC	1
309		3	max	0	3	0	10	0	1	0	1	NC	1	NC	1
310			min	0	1	-.012	3	0	1	0	1	5945.444	3	NC	1
311		4	max	0	3	0	10	0	1	0	1	NC	2	NC	1
312			min	0	1	-.027	3	0	1	0	1	2756	3	NC	1
313		5	max	0	3	-.001	10	0	1	0	1	NC	2	NC	1
314			min	0	1	-.046	3	0	1	0	1	1598.228	3	NC	1
315		6	max	.001	3	-.002	10	0	1	0	1	NC	5	NC	1
316			min	-.001	1	-.07	3	0	1	0	1	1050.196	3	NC	1
317		7	max	.001	3	-.003	10	0	1	0	1	NC	5	NC	1
318			min	-.001	1	-.099	3	0	1	0	1	747.475	3	NC	1
319		8	max	.001	3	-.004	10	0	1	0	1	NC	5	NC	1
320			min	-.002	1	-.131	3	0	1	0	1	562.332	3	NC	1
321		9	max	.002	3	-.005	10	0	1	0	1	NC	10	NC	1
322			min	-.002	1	-.167	3	0	1	0	1	440.752	3	NC	1
323		10	max	.002	3	-.006	10	0	1	0	1	NC	10	NC	1
324			min	-.002	1	-.207	3	0	1	0	1	356.526	3	NC	1
325		11	max	.002	3	-.007	10	0	1	0	1	NC	10	NC	1
326			min	-.002	1	-.249	3	0	1	0	1	295.704	3	NC	1
327		12	max	.002	3	-.009	10	0	1	0	1	8495.557	10	NC	1
328			min	-.003	1	-.294	3	0	1	0	1	250.309	3	NC	1
329		13	max	.003	3	-.01	10	0	1	0	1	7257.429	10	NC	1
330			min	-.003	1	-.342	3	0	1	0	1	215.507	3	NC	1
331		14	max	.003	3	-.012	10	0	1	0	1	6298.639	10	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
332			min	-.003	1	-.391	3	0	1	0	1	188.225	3	NC	1
333		15	max	.003	3	-.013	10	0	1	0	1	5540.802	10	NC	1
334			min	-.003	1	-.443	3	0	1	0	1	166.442	3	NC	1
335		16	max	.003	3	-.015	10	0	1	0	1	4931.308	10	NC	1
336			min	-.004	1	-.495	3	0	1	0	1	148.774	3	NC	1
337		17	max	.003	3	-.017	10	0	1	0	1	4433.867	10	NC	1
338			min	-.004	1	-.549	3	0	1	0	1	134.251	3	NC	1
339		18	max	.004	3	-.018	10	0	1	0	1	4022.786	10	NC	1
340			min	-.004	1	-.603	3	0	1	0	1	122.175	3	NC	1
341		19	max	.004	3	-.02	10	0	1	0	1	3679.45	10	NC	1
342			min	-.004	1	-.658	3	0	1	0	1	112.035	3	NC	1
343	M8	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
344			min	0	1	0	1	0	1	0	1	NC	1	NC	1
345		2	max	0	3	0	10	0	2	3.271e-3	3	NC	1	NC	1
346			min	0	1	-.002	3	0	3	-6.581e-3	2	NC	1	NC	1
347		3	max	0	3	0	10	.001	2	2.91e-3	3	NC	1	NC	1
348			min	0	1	-.006	3	-.001	3	-6.043e-3	2	NC	1	NC	1
349		4	max	0	3	0	15	.002	2	2.549e-3	3	NC	2	NC	1
350			min	0	1	-.013	3	-.003	3	-5.504e-3	2	5816.556	3	NC	1
351		5	max	0	3	0	15	.004	2	2.188e-3	3	NC	2	NC	1
352			min	0	1	-.022	3	-.005	3	-4.966e-3	2	3368.434	3	NC	1
353		6	max	0	3	-.001	15	.005	2	1.826e-3	3	NC	2	NC	1
354			min	0	1	-.033	3	-.007	3	-4.427e-3	2	2211.792	3	7712.118	3
355		7	max	0	3	-.002	15	.007	2	1.465e-3	3	NC	5	NC	1
356			min	0	1	-.047	3	-.009	3	-3.888e-3	2	1573.544	3	6038.309	3
357		8	max	0	3	-.003	15	.009	2	1.104e-3	3	NC	5	NC	4
358			min	0	1	-.062	3	-.011	3	-3.35e-3	2	1183.444	3	4984.673	3
359		9	max	0	3	-.004	15	.01	2	7.433e-4	3	NC	5	NC	4
360			min	0	1	-.079	3	-.013	3	-2.811e-3	2	927.383	3	4294.677	3
361		10	max	0	3	-.004	15	.011	2	3.823e-4	3	NC	5	NC	4
362			min	0	1	-.098	3	-.014	3	-2.273e-3	2	750.047	3	3839.089	3
363		11	max	0	3	-.005	15	.012	1	2.122e-5	3	NC	10	NC	4
364			min	0	1	-.118	3	-.015	3	-1.734e-3	2	622.019	3	3550.067	3
365		12	max	0	3	-.006	15	.013	1	5.446e-5	9	NC	15	NC	4
366			min	-.001	1	-.14	3	-.015	3	-1.196e-3	2	526.481	3	3393.983	3
367		13	max	0	3	-.007	15	.014	1	2.273e-4	9	NC	15	NC	4
368			min	-.001	1	-.163	3	-.015	3	-7.009e-4	3	453.249	3	3361.177	3
369		14	max	0	3	-.008	15	.013	1	4.113e-4	1	8828.485	15	NC	4
370			min	-.001	1	-.186	3	-.014	3	-1.062e-3	3	395.845	3	3467.306	3
371		15	max	0	3	-.009	15	.013	1	8.84e-4	1	7804.988	15	NC	4
372			min	-.001	1	-.211	3	-.012	3	-1.423e-3	3	350.017	3	3765.915	3
373		16	max	.001	3	-.011	15	.011	1	1.357e-3	1	6975.168	15	NC	4
374			min	-.001	1	-.236	3	-.008	3	-1.784e-3	3	312.85	3	4403.522	3
375		17	max	.001	3	-.012	15	.009	1	1.83e-3	1	6293.259	15	NC	4
376			min	-.001	1	-.261	3	-.003	3	-2.145e-3	3	282.3	3	5839.906	3
377		18	max	.001	3	-.013	15	.006	1	2.302e-3	1	5726.41	15	NC	1
378			min	-.002	1	-.287	3	0	15	-2.506e-3	3	256.9	3	NC	1
379		19	max	.001	3	-.014	15	.01	3	2.775e-3	1	5250.543	15	NC	1
380			min	-.002	1	-.313	3	-.003	2	-2.867e-3	3	235.572	3	NC	1
381	M3	1	max	0	3	0	10	0	3	3.689e-3	2	NC	1	NC	1
382			min	0	10	0	3	0	2	-1.803e-3	3	NC	1	NC	1
383		2	max	0	3	0	15	.01	3	3.793e-3	2	NC	1	NC	4
384			min	0	2	-.016	3	-.02	2	-1.871e-3	3	NC	1	3007.005	2
385		3	max	0	3	-.002	15	.021	3	3.897e-3	2	NC	1	NC	4
386			min	0	2	-.031	3	-.041	2	-1.939e-3	3	NC	1	1493.585	2
387		4	max	.001	3	-.003	15	.031	3	4.001e-3	2	NC	1	NC	5
388			min	-.001	2	-.047	3	-.061	2	-2.007e-3	3	NC	1	997.252	2

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
389		5	max	.001	3	-.003	15	.041	3	4.105e-3	2	NC	1	NC	5
390			min	-.002	2	-.062	3	-.081	2	-2.076e-3	3	NC	1	755.248	2
391		6	max	.001	3	-.004	15	.051	3	4.209e-3	2	NC	1	NC	5
392			min	-.002	2	-.078	3	-.099	2	-2.144e-3	3	NC	1	615.268	2
393		7	max	.001	3	-.005	15	.059	3	4.312e-3	2	NC	1	NC	5
394			min	-.003	2	-.093	3	-.116	2	-2.212e-3	3	NC	1	526.785	2
395		8	max	.002	3	-.006	15	.066	3	4.416e-3	2	NC	1	NC	5
396			min	-.003	2	-.108	3	-.13	2	-2.28e-3	3	NC	1	468.405	2
397		9	max	.002	3	-.007	15	.072	3	4.52e-3	2	NC	1	NC	5
398			min	-.003	2	-.124	3	-.142	2	-2.349e-3	3	NC	1	429.75	2
399		10	max	.002	3	-.007	15	.077	3	4.624e-3	2	NC	1	NC	5
400			min	-.004	2	-.139	3	-.15	2	-2.417e-3	3	NC	1	405.477	2
401		11	max	.002	3	-.008	15	.079	3	4.728e-3	2	NC	1	NC	5
402			min	-.004	2	-.154	3	-.154	2	-2.485e-3	3	NC	1	392.984	2
403		12	max	.002	3	-.009	15	.079	3	4.832e-3	2	NC	1	NC	5
404			min	-.005	2	-.169	3	-.154	2	-2.554e-3	3	NC	1	391.546	2
405		13	max	.002	3	-.009	15	.077	3	4.936e-3	2	NC	1	NC	5
406			min	-.005	2	-.184	3	-.149	2	-2.622e-3	3	NC	1	402.236	2
407		14	max	.003	3	-.01	15	.073	3	5.04e-3	2	NC	1	NC	5
408			min	-.006	2	-.199	3	-.139	2	-2.69e-3	3	NC	1	428.662	2
409		15	max	.003	3	-.01	15	.065	3	5.144e-3	2	NC	1	NC	5
410			min	-.006	2	-.214	3	-.123	2	-2.758e-3	3	NC	1	479.38	2
411		16	max	.003	3	-.011	15	.054	3	5.248e-3	2	NC	1	NC	5
412			min	-.006	2	-.229	3	-.101	2	-2.827e-3	3	NC	1	575.539	2
413		17	max	.003	3	-.012	15	.04	3	5.351e-3	2	NC	1	NC	5
414			min	-.007	2	-.243	3	-.071	2	-2.895e-3	3	NC	1	781.801	2
415		18	max	.003	3	-.012	15	.022	3	5.455e-3	2	NC	1	NC	4
416			min	-.007	2	-.258	3	-.035	2	-2.963e-3	3	NC	1	1423.181	2
417		19	max	.003	3	-.013	15	.015	1	5.559e-3	2	NC	1	NC	1
418			min	-.008	2	-.273	3	0	12	-3.032e-3	3	NC	1	NC	1
419	M6	1	max	.001	3	0	10	0	1	0	1	NC	1	NC	1
420			min	0	2	0	3	0	1	0	1	NC	1	NC	1
421		2	max	.002	3	-.001	15	0	1	0	1	NC	1	NC	1
422			min	-.002	2	-.033	3	0	1	0	1	NC	1	NC	1
423		3	max	.002	3	-.003	15	0	1	0	1	NC	1	NC	1
424			min	-.003	2	-.065	3	0	1	0	1	NC	1	NC	1
425		4	max	.003	3	-.004	15	0	1	0	1	NC	1	NC	1
426			min	-.004	2	-.097	3	0	1	0	1	NC	1	NC	1
427		5	max	.003	3	-.005	15	0	1	0	1	NC	1	NC	1
428			min	-.005	2	-.129	3	0	1	0	1	NC	1	NC	1
429		6	max	.004	3	-.006	15	0	1	0	1	NC	1	NC	1
430			min	-.007	2	-.161	3	0	1	0	1	NC	1	NC	1
431		7	max	.005	3	-.008	15	0	1	0	1	NC	1	NC	1
432			min	-.008	2	-.192	3	0	1	0	1	NC	1	NC	1
433		8	max	.005	3	-.009	15	0	1	0	1	NC	1	NC	1
434			min	-.009	2	-.224	3	0	1	0	1	NC	1	NC	1
435		9	max	.006	3	-.01	15	0	1	0	1	NC	1	NC	1
436			min	-.01	2	-.256	3	0	1	0	1	NC	1	NC	1
437		10	max	.006	3	-.011	15	0	1	0	1	NC	1	NC	1
438			min	-.012	2	-.288	3	0	1	0	1	NC	1	NC	1
439		11	max	.007	3	-.012	15	0	1	0	1	NC	1	NC	1
440			min	-.013	2	-.319	3	0	1	0	1	NC	1	NC	1
441		12	max	.007	3	-.013	15	0	1	0	1	NC	1	NC	1
442			min	-.014	2	-.351	3	0	1	0	1	NC	1	NC	1
443		13	max	.008	3	-.014	15	0	1	0	1	NC	1	NC	1
444			min	-.015	2	-.382	3	0	1	0	1	NC	1	NC	1
445		14	max	.008	3	-.015	15	0	1	0	1	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
446			min	-.017	2	-.414	3	0	1	0	1	NC	1	NC	1
447		15	max	.009	3	-.016	15	0	1	0	1	NC	1	NC	1
448			min	-.018	2	-.445	3	0	1	0	1	NC	1	NC	1
449		16	max	.01	3	-.017	15	0	1	0	1	NC	1	NC	1
450			min	-.019	2	-.476	3	0	1	0	1	NC	1	NC	1
451		17	max	.01	3	-.018	15	0	1	0	1	NC	1	NC	1
452			min	-.02	2	-.507	3	0	1	0	1	NC	1	NC	1
453		18	max	.011	3	-.019	15	0	1	0	1	NC	1	NC	1
454			min	-.022	2	-.539	3	0	1	0	1	NC	1	NC	1
455		19	max	.011	3	-.02	15	0	1	0	1	NC	1	NC	1
456			min	-.023	2	-.57	3	0	1	0	1	NC	1	NC	1
457	M9	1	max	0	3	0	10	0	2	1.803e-3	3	NC	1	NC	1
458			min	0	10	0	3	0	3	-3.689e-3	2	NC	1	NC	1
459		2	max	0	3	0	15	.02	2	1.871e-3	3	NC	1	NC	4
460			min	0	2	-.016	3	-.01	3	-3.793e-3	2	NC	1	3007.005	2
461		3	max	0	3	-.002	15	.041	2	1.939e-3	3	NC	1	NC	4
462			min	0	2	-.031	3	-.021	3	-3.897e-3	2	NC	1	1493.585	2
463		4	max	.001	3	-.003	15	.061	2	2.007e-3	3	NC	1	NC	5
464			min	-.001	2	-.047	3	-.031	3	-4.001e-3	2	NC	1	997.252	2
465		5	max	.001	3	-.003	15	.081	2	2.076e-3	3	NC	1	NC	5
466			min	-.002	2	-.062	3	-.041	3	-4.105e-3	2	NC	1	755.248	2
467		6	max	.001	3	-.004	15	.099	2	2.144e-3	3	NC	1	NC	5
468			min	-.002	2	-.078	3	-.051	3	-4.209e-3	2	NC	1	615.268	2
469		7	max	.001	3	-.005	15	.116	2	2.212e-3	3	NC	1	NC	5
470			min	-.003	2	-.093	3	-.059	3	-4.312e-3	2	NC	1	526.785	2
471		8	max	.002	3	-.006	15	.13	2	2.28e-3	3	NC	1	NC	5
472			min	-.003	2	-.108	3	-.066	3	-4.416e-3	2	NC	1	468.405	2
473		9	max	.002	3	-.007	15	.142	2	2.349e-3	3	NC	1	NC	5
474			min	-.003	2	-.124	3	-.072	3	-4.52e-3	2	NC	1	429.75	2
475		10	max	.002	3	-.007	15	.15	2	2.417e-3	3	NC	1	NC	5
476			min	-.004	2	-.139	3	-.077	3	-4.624e-3	2	NC	1	405.477	2
477		11	max	.002	3	-.008	15	.154	2	2.485e-3	3	NC	1	NC	5
478			min	-.004	2	-.154	3	-.079	3	-4.728e-3	2	NC	1	392.984	2
479		12	max	.002	3	-.009	15	.154	2	2.554e-3	3	NC	1	NC	5
480			min	-.005	2	-.169	3	-.079	3	-4.832e-3	2	NC	1	391.546	2
481		13	max	.002	3	-.009	15	.149	2	2.622e-3	3	NC	1	NC	5
482			min	-.005	2	-.184	3	-.077	3	-4.936e-3	2	NC	1	402.236	2
483		14	max	.003	3	-.01	15	.139	2	2.69e-3	3	NC	1	NC	5
484			min	-.006	2	-.199	3	-.073	3	-5.04e-3	2	NC	1	428.662	2
485		15	max	.003	3	-.01	15	.123	2	2.758e-3	3	NC	1	NC	5
486			min	-.006	2	-.214	3	-.065	3	-5.144e-3	2	NC	1	479.38	2
487		16	max	.003	3	-.011	15	.101	2	2.827e-3	3	NC	1	NC	5
488			min	-.006	2	-.229	3	-.054	3	-5.248e-3	2	NC	1	575.539	2
489		17	max	.003	3	-.012	15	.071	2	2.895e-3	3	NC	1	NC	5
490			min	-.007	2	-.243	3	-.04	3	-5.351e-3	2	NC	1	781.801	2
491		18	max	.003	3	-.012	15	.035	2	2.963e-3	3	NC	1	NC	4
492			min	-.007	2	-.258	3	-.022	3	-5.455e-3	2	NC	1	1423.181	2
493		19	max	.003	3	-.013	15	0	12	3.032e-3	3	NC	1	NC	1
494			min	-.008	2	-.273	3	-.015	1	-5.559e-3	2	NC	1	NC	1