

Schletter, Inc.		20° Tilt w/o Seismic Design
HCV	Standard FS Racking System	
	Representative Calculations - ASCE 7-10	

1. INTRODUCTION

1.1 Project Description

The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. FS ground mount system.

1.2 Construction

Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to galvanized steel posts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

	Maximum		Minimum
Height =	2000 mm	Height =	1900 mm
Width =	1050 mm	Width =	970 mm
Dead Load =	3.00 psf	Dead Load =	1.75 psf

Modules Per Row =	2
Module Tilt =	20°
Maximum Height Above Grade =	3 ft



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

1.3 Technical Codes

- ASCE 7-10 - Chapter 26-31, Wind Loads
- ASCE 7-10 - Chapter 7, Snow Loads
- ASCE 7-10 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2012, 2015
- Aluminum Design Manual, Eighth Edition, 2005

2. LOAD ACTIONS

2.1 Permanent Loads

g_{MAX} =	3.00 psf	*Self-weight of the PV modules.*
g_{MIN} =	1.75 psf	

2.2 Snow Loads

Ground Snow Load, P_g =	30.00 psf	
Sloped Roof Snow Load, P_s =	20.62 psf	*(ASCE 7-10, Eq. 7.4-1)*
I_s =	1.00	
C_s =	0.91	
C_e =	0.90	
C_t =	1.20	

2.3 Wind Loads

Design Wind Speed, V =	115 mph	Exposure Category = C	
Height <	15 ft	Importance Category = II	
Peak Velocity Pressure, q_z =	20.76 psf	*Including the gust factor, G=0.85. (ASCE 7-10, Eq. 27.3-1)*	

Pressure Coefficients

$Cf+_{TOP}$ =	1.05	*(Pressure)*	*Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0510-e. Negative forces are applied away from the surface.*
$Cf+_{BOTTOM}$ =	1.65		
$Cf-_{TOP}$ =	-2.12	*(Suction)*	
$Cf-_{BOTTOM}$ =	-1		

2.4 Seismic Loads - N/A

S_S =	0.00	R =	1.25	*ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.*
S_{DS} =	0.00	C_S =	0	
S_1 =	0.00	ρ =	1.3	
S_{D1} =	0.00	Ω =	1.25	
T_a =	0.00	C_d =	1.25	

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.5W
1.2D + 1.0W + 0.5S
0.9D + 1.0W [M]
1.54D + 1.3E + 0.2S [R]
0.56D + 1.3E [R]
1.54D + 1.25E + 0.2S [O]
0.56D + 1.25E [O]

(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S
1.0D + 0.6W
1.0D + 0.75L + 0.45W + 0.75S
0.6D + 0.6W [M]
1.238D + 0.875E [O]
1.1785D + 0.65625E + 0.75S [O]
0.362D + 0.875E [O]

(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)

[M] *Uses the minimum allowable module dead load.*
[R] *Include redundancy factor of 1.3.*
[O] *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location
M10	Top
M11	Mid-Top
M12	Mid-Bottom
M13	Bottom

Posts	Location
M2	Outer
M5	Inner
M8	Outer

Girders	Location
M1	Outer
M4	Inner
M7	Outer

Reactions	Location
N9	Outer
N19	Inner
N29	Outer

Struts	Location
M3	Outer
M6	Inner
M9	Outer

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type =	**S1.5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	96	in
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	25.07	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	23.08	ksi
S_y =	1.33	in^3
S_x =	0.6	in^3
E =	10100	ksi
I_y =	2.16	in^4
I_x =	1.07	in^4
A =	1.25	in^2
g =	1.50	lbs/ft
M_y =	0.946	k-ft
M_z =	0.152	k-ft
$M_{y\ allowable}$ =	2.779	k-ft
$M_{z\ allowable}$ =	1.154	k-ft
Utilization =	47%	



DETAIL VIEW

4.2 Girder Design

Loads from purlins are transferred to the posts using an inclined girder, which is connected to the steel post. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type =	**T5**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	81.77	in
$\Phi F_{ty\ AXIAL}$ =	30.80	ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$ =	30.06	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$ =	31.56	ksi
S_y =	1.98	in^3
S_x =	1.32	in^3
E =	10100	ksi
I_y =	4.74	in^4
I_x =	1.83	in^4
A =	1.93	in^2
g =	2.32	lbs/ft
M_y =	3.097	k-ft
M_z =	0.000	k-ft
P_n =	6.436	k
$M_{y\ allowable}$ =	4.960	k-ft
$M_{z\ allowable}$ =	3.472	k-ft
$P_{n\ allowable}$ =	59.439	k
Utilization =	73%	



DETAIL VIEW

4.3 Strut Design

The aluminum strut connects a portion of the girder to the galvanized steel post. Girder forces are then transferred down through the strut into the post. The strut is attached with single M10 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	74.80	in
$\Phi F_{ty\ AXIAL}$ =	9.61	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.008	k-ft
M_z =	0.000	k-ft
P_n =	6.460	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	9.441	k
Utilization =	69%	



4.4 Post Design

Galvanized steel posts are a roll formed steel section, that are either ram driven into the ground or placed in a concrete foundation at a defined depth. Embedment depths will be provided on the structural drawings or through a geotechnical testing report. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Post Type =	**FG8**	
Steel Type =	J2340	
F_{ty} =	60	ksi
L_b =	72.67	in
Φ =	0.90	
ΦF_{ty} =	54.00	ksi
S_y =	3.46	in^3
S_x =	1.55	in^3
E =	29000	ksi
I_y =	10.94	in^4
I_x =	4.31	in^4
A =	2.23	in^2
g =	7.59	lbs/ft
M_y =	15.822	k-ft
M_z =	0.000	k-ft
P_r =	5.739	k
$M_{y\ allowable}$ =	19.207	k-ft
$M_{z\ allowable}$ =	14.389	k-ft
P_c =	38.013	k
Utilization =	100%	



5. FOUNDATION DESIGN CALCULATIONS

5.1 Rammed Post Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete footing design.

Maximum Tensile Load =	4.46	k
Maximum Lateral Load =	2.11	k

5.2 Design of Drilled Shaft Foundations

The galvanized steel post is to be embedded into a cylindrical drilled shaft foundation. For the purpose of design, the post is considered to be fixed to the ground. The applicable lateral force, uplift, and compression resistance checks are seen below.

5.3 Lateral Force Resistance

The equivalent lateral force is applied at the top of the post to determine the required embedment depth. A lateral soil bearing capacity for clay is assumed. Footing is unrestrained at ground level. (IBC, Eq. 18-1)

Lateral Force @ Top of Pole, P =	1.65	k
Height of Pole Above Grade, H =	5.06	ft
Diameter of Pole Footing, B =	2.00	ft
Lateral Soil Bearing Capacity, S =	0.10	ksf/ft
Isolated Pole Factor, F =	2	
First Trial Depth, D =	3.25	ft
Lateral Bearing @ Bottom =	S_3	
Lateral Bearing @ D/3 =	S_1	
Required Depth =	D	

$$S_3 = Min\ (D, 12')$$

$$S_1 = Min\left(\frac{D}{3}, 12'\right)$$

$$A = 2.34\ P/S_1 B$$

$$D = \left\{0.5A\left(1+\sqrt{1+\left(\frac{4.36\ H}{A}\right)}\right)\right\}$$



Non-Constrained

Lateral Force @ Top of Pole, P =	1.65	k
Height of Pole Above Grade, H =	5.06	ft
Diameter of Pole Footing, B =	2.00	ft
Lateral Soil Bearing Capacity, S =	0.20	ksf/ft

1st Trial @ D_1 =	3.25	ft	
Lateral Soil Bearing @ D/3, S_1 =	0.22	ksf	
Lateral Soil Bearing @ D, S_3 =	0.65	ksf	
Constant 2.34P/(S_1B), A =	8.90		
Required Footing Depth, D =	12.75	ft	
2nd Trial @ D_2 =	8.00	ft	
Lateral Soil Bearing @ D/3, S_1 =	0.53	ksf	
Lateral Soil Bearing @ D, S_3 =	1.60	ksf	
Constant 2.34P/(S_1B), A =	3.62		
Required Footing Depth, D =	6.63	ft	
3rd Trial @ D_3 =	7.31	ft	
Lateral Soil Bearing @ D/3, S_1 =	0.49	ksf	
Lateral Soil Bearing @ D, S_3 =	1.46	ksf	
Constant 2.34P/(S_1B), A =	3.96		
Required Footing Depth, D =	7.05	ft	
4th Trial @ D_4 =	7.18	ft	
Lateral Soil Bearing @ D/3, S_1 =	0.48	ksf	
Lateral Soil Bearing @ D, S_3 =	1.44	ksf	
Constant 2.34P/(S_1B), A =	4.03		
Required Footing Depth, D =	7.14	ft	
5th Trial @ D_5 =	7.16	ft	
Lateral Soil Bearing @ D/3, S_1 =	0.48	ksf	
Lateral Soil Bearing @ D, S_3 =	1.43	ksf	
Constant 2.34P/(S_1B), A =	4.04		
Required Footing Depth, D =	7.25	ft	

A 2ft diameter x 7.25ft deep footing unrestrained at ground level is required for the racking structure.

5.4 Uplifting Force Resistance

Uplifting forces of the racking system are checked against the uplift resistance of the soil. Clay soils are assumed.

Weight of Concrete, g_{con} =	145	pcf
Uplifting Force, N =	2.04	k
Footing Diameter, B =	2.00	ft
Factor of Safety =	2.50	
Cohesion =	208.85	psf
γ_s =	120.43	pcf
α =	0.45	
Required Concrete Weight, g =	1.33	k
Required Concrete Volume, V =	9.18	ft^3
Required Footing Depth, D =	3.00	ft

Iteration	z	dz	Qs	Side
1	0.2	0.2	118.10	4.38
2	0.4	0.2	118.10	4.27
3	0.6	0.2	118.10	4.17
4	0.8	0.2	118.10	4.06
5	1	0.2	118.10	3.96
6	1.2	0.2	118.10	3.86
7	1.4	0.2	118.10	3.75
8	1.6	0.2	118.10	3.65
9	1.8	0.2	118.10	3.55
10	2	0.2	118.10	3.44
11	2.2	0.2	118.10	3.34
12	2.4	0.2	118.10	3.23
13	2.6	0.2	118.10	3.13
14	2.8	0.2	118.10	3.03
15	3	0.2	118.10	2.92
16	0	0.0	0.00	2.92
17	0	0.0	0.00	2.92
18	0	0.0	0.00	2.92
19	0	0.0	0.00	2.92
20	0	0.0	0.00	2.92
21	0	0.0	0.00	2.92
22	0	0.0	0.00	2.92
23	0	0.0	0.00	2.92
24	0	0.0	0.00	2.92
25	0	0.0	0.00	2.92
26	0	0.0	0.00	2.92
27	0	0.0	0.00	2.92
28	0	0.0	0.00	2.92
29	0	0.0	0.00	2.92
30	0	0.0	0.00	2.92
31	0	0.0	0.00	2.92
32	0	0.0	0.00	2.92
33	0	0.0	0.00	2.92
34	0	0.0	0.00	2.92
Max	3	Sum	0.71	

A 2ft diameter x 3ft deep footing unrestrained at ground level is required for the racking structure.



5.5 Compressive Force Resistance

Skin friction of the soil is checked against the compression force from the racking and the weight of the drilled shaft foundation. Skin friction starts at 3ft below grade. Clay soils are again assumed.

Depth Below Grade, D =	7.25	ft
Footing Diameter, B =	2.00	ft
Compressive Force, P =	3.60	k
Footing Area =	3.14	ft^2
Circumference =	6.28	ft
Skin Friction Area =	26.70	ft^2
Concrete Weight =	0.145	kcf

Bearing Pressure

Bearing Area =	3.14	ft^2
Bearing Capacity =	1.5	ksf
Resistance =	4.71	k

Weight of Concrete

Footing Volume	22.78	ft^3
Weight	3.30	k

Skin Friction Resistance

Skin Friction =	0.15	ksf
Resistance =	4.01	k
1/3 Increase for Wind =	1.33	
Total Resistance =	11.62	k
Applied Force =	6.91	k
Utilization =	59%	

A 2ft diameter footing passes at a depth of 7.25ft.



6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of 40mm mounting clamps. The reliability of calculations is uncertain due to limited standards, therefore the strength of the clamp fasteners has been evaluated by load testing.

Fastening of Modules to Purlins

Maximum Uplifting Force	=	0.480 k
Allowable Uplift	=	1.214 k
Utilization	=	40%



Fastening of Purlins to Girders

Maximum Uplifting Force	=	1.347 k
Allowable Uplift	=	2.180 k
Utilization	=	62%



6.2 Strut Connections

The aluminum struts connect the front end of girder to a center section of the steel post. Single M10 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Maximum Axial Load	=	6.460 k
M10 Bolt Shear Capacity	=	8.894 k
Utilization	=	73%

Bolt capacity is accounting for double shear. (ASCE 8-02, Eq. 5.3.4-1)



A strut under compression is shown to demonstrate the load transfer from the girder. Single M10 bolts are located at each end of the strut and are subjected to double shear.

6.3 Girder to Post Connection

In order to connect the girder to the post, custom extruded sections are assembled to create a post head piece. The reliability of calculations is uncertain due to limited standards, therefore the strength of the head piece has been evaluated by load testing.

Maximum Tensile Load	=	2.814 k
Allowable Load	=	5.649 k
Utilization	=	50%



FRONT VIEW



SIDE VIEW



7. SEISMIC DESIGN

7.1 Seismic Drift - N/A

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx}	=	69.36 in
Allowable Story Drift for All Other Structures, Δ	= {	$0.020h_{sx}$
		1.387 in
Max Drift, Δ_{MAX}	=	0 in
N/A		

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **S1.5**

Strong Axis:		Weak Axis:	
3.4.14		**3.4.14**	
L_b =	96 in	L_b =	96
J =	0.432	J =	0.432
	265.581		168.894
$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$		$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$	
S1 =	0.51461	S1 =	0.51461
$S2 = \left(\frac{C_c}{1.6}\right)^2$		$S2 = \left(\frac{C_c}{1.6}\right)^2$	
S2 =	1701.56	S2 =	1701.56
φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]	φF_L=	φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L=	28.0 ksi	φF_L=	29.1
3.4.16		**3.4.16**	
b/t =	32.195	b/t =	37.0588
$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$		$S1 = \frac{Bp - \frac{\theta_y}{\theta_b}Fcy}{1.6Dp}$	
S1 =	12.2	S1 =	12.2
$S2 = \frac{k_1 Bp}{1.6Dp}$		$S2 = \frac{k_1 Bp}{1.6Dp}$	
S2 =	46.7	S2 =	46.7
φF_L=	φb[Bp-1.6Dp*b/t]	φF_L=	φb[Bp-1.6Dp*b/t]
φF_L=	25.1 ksi	φF_L=	23.1 ksi
3.4.16.1	Not Used	**3.4.16.1**	
Rb/t =		N/A for Weak Direction	
$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$			
S1 =	1.1		
$S2 = C_t$			
S2 =	141.0		
φF_L=	1.17φyFcy		
φF_L=	38.9 ksi		
3.4.18		**3.4.18**	
h/t =	37.0588	h/t =	32.195
$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$		$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$	
S1 =	36.9	S1 =	36.9
m =	0.65	m =	0.65
C_0 =	40.985	C_0 =	45.5
Cc =	41.015	Cc =	45.5
$S2 = \frac{k_1 Bbr}{mDbr}$		$S2 = \frac{k_1 Bbr}{mDbr}$	
S2 =	77.2	S2 =	77.3
φF_L=	φb[Bbr-mDbr*h/t]	φF_L=	1.3φyFcy
φF_L=	43.2 ksi	φF_L=	43.2 ksi
φF_LSt=	25.1 ksi	φF_LWk=	23.1 ksi
Ix =	897074 mm^4	Iy =	446476 mm^4
	2.155 in^4		1.073 in^4
y =	41.015 mm	x =	45.5 mm
Sx =	1.335 in^3	Sy =	0.599 in^3
M_{max}St =	2.788 k-ft	M_{max}Wk =	1.152 k-ft

Compression

3.4.9

b/t = 32.195
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 25.1 ksi

b/t = 37.0588
S1 = 12.21
S2 = 32.70
φF_L = (φck2*√(BpE))/(1.6b/t)
φF_L = 21.9 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 21.94 ksi
A = 1215.13 mm^2
1.88 in^2
P_{max} = 41.32 kips

A.2 Design of Aluminum Girders - Aluminum Design Manual, 2005 Edition

Girder = **T5**

Strong Axis:

3.4.14

L_b = 81.7717 in
J = 1.98
105.231

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.1 ksi

3.4.16

b/t = 4.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φyFcy
φF_L = 33.3 ksi

Weak Axis:

3.4.14

L_b = 81.7717
J = 1.98
114.202

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.9

3.4.16

b/t = 16.3333

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 31.6 ksi

3.4.16.1 Used

Rb/t = 20.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L = φb[Bt-Dt*√(Rb/t)]

φF_L = 30.8 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 16.3333

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 37.9

m = 0.63

C_0 = 61.046

Cc = 58.954

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 79.4

φF_L = 1.3φyFcy

φF_L = 43.2 ksi

3.4.18

h/t = 4.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 35

Cc = 35

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L = 1.3φyFcy

φF_L = 43.2 ksi

$\varphi F_L St$ = 30.1 ksi

Ix = 1970917 mm^4

4.735 in^4

y = 61.046 mm

Sx = 1.970 in^3

$M_{max}St$ = 4.935 k-ft

$\varphi F_L Wk$ = 31.6 ksi

Iy = 763048 mm^4

1.833 in^4

x = 35 mm

Sy = 1.330 in^3

$M_{max}Wk$ = 3.499 k-ft

Compression

3.4.9

b/t = 4.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φyFcy

φF_L = 33.3 ksi

b/t = 16.3333

S1 = 12.21

S2 = 32.70

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 31.6 ksi

3.4.10

Rb/t = 20.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φc[Bt-Dt*√(Rb/t)]

φF_L = 30.80 ksi

φF_L = 30.80 ksi

A = 1215.13 mm^2

1.88 in^2

P_{max} = 58.01 kips

A.3 Design of Aluminum Struts - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 74.8031 in

J = 0.942

116.737

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 29.9 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LSt= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

M_{max}St = 1.460 k-ft

Weak Axis:

3.4.14

L_b = 74.8031

J = 0.942

116.737

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 29.9

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

M_{max}Wk = 1.460 k-ft

Compression

3.4.7

λ = 1.73045

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.82226

$\varphi F_L = (\varphi ccFcy)/(\lambda^2)$

φF_L = 9.61085 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 9.61 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 9.89 kips

A.4 Design of Galvanized Steel Posts

Post Type = **FG8**

Unbraced Length =	72.67	in	
Pr =	5.74	k	(LRFD Factored Load)
Mr (Strong) =	15.82	k-ft	(LRFD Factored Load)
Mr (Weak) =	0.00	k-ft	(LRFD Factored Load)

Flexural Buckling:

kL/r =	104.56		
4.71√(E/Fy) =	103.55	=> kL/r >	4.71√(E/Fy)
Fcr =	22.96	ksi	
Fe =	26.18	ksi	
Pn =	51.204	k	

Torsional/Flexural Torsional Buckling:

Fcr =	17.0464	ksi
Fey =	66.785	ksi
Fez =	21.7259	ksi
Pn =	38.0134	k

Bending (Strong Axis):

Yielding:

Mn =	21.95	k-ft

Flange Local Buckling:

Mn =	19.207	k-ft

Pr/Pc =	0.1678	<	0.2	
Utilization =	1.00	<	1.0	OK

Bending (Weak Axis):

Yielding:

Mn =	14.65	k-ft

Flange Local Buckling:

Mn =	14.39	k-ft

Pr/Pc =	0.168	<	0.2	
Utilization =	0.00	<	1.0	OK

Combined Forces

Utilization =	100%

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				4		
2	Dead Load, Min	DL		-1				4		
3	Snow Load	SL						4		
4	Wind Load - Pressure	WL						4		
5	Wind Load - Suction	WL						4		
6	Seismic - Lateral	EL								

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-9.843	-9.843	0	0
2	M11	Y	-9.843	-9.843	0	0
3	M12	Y	-9.843	-9.843	0	0
4	M13	Y	-9.843	-9.843	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-5.454	-5.454	0	0
2	M11	Y	-5.454	-5.454	0	0
3	M12	Y	-5.454	-5.454	0	0
4	M13	Y	-5.454	-5.454	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	Y	-63.565	-63.565	0	0
2	M11	Y	-63.565	-63.565	0	0
3	M12	Y	-63.565	-63.565	0	0
4	M13	Y	-63.565	-63.565	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	y	-71.531	-71.531	0	0
2	M11	y	-71.531	-71.531	0	0
3	M12	y	-112.406	-112.406	0	0
4	M13	y	-112.406	-112.406	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M10	y	144.425	144.425	0	0
2	M11	y	144.425	144.425	0	0
3	M12	y	68.125	68.125	0	0
4	M13	y	68.125	68.125	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.5W	Yes	Y		1	1.2	3	1.6	4	.5																
2	LRFD 1.2D + 1.0W + 0.5S	Yes	Y		1	1.2	3	.5	4	1																
3	LRFD 0.9D + 1.0W	Yes	Y		2	.9					5	1														
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3														
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3														
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25														
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25														

Load Combinations (Continued)

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
8																										
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																		
10	ASD 1.0D + 0.6W	Yes	Y		1	1			4	.6																
11	ASD 1.0D + 0.75L + 0.45W + 0....	Yes	Y		1	1	3	.75	4	.45																
12	ASD 0.6D + 0.6W	Yes	Y		2	.6					5	.6														
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875														
14	LATERAL - ASD 1.1785D + 0.65...	Yes	Y		1	1.1...	3	.75			6	.656														
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875														

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N9	max	221.276	2	2311.78	1	149.881	1	.23	1	0	3	8.571	1
2		min	-445.411	3	-1179.081	3	-105.631	3	-.116	3	-.002	1	-.451	3
3	N19	max	1570.574	2	5788.008	1	0	15	0	3	0	3	13.911	1
4		min	-1435.462	3	-3433.282	3	0	1	0	11	0	1	-.469	3
5	N29	max	221.276	2	2311.78	1	105.631	3	.116	3	.002	1	8.571	1
6		min	-445.411	3	-1179.081	3	-149.881	1	-.23	1	0	3	-.451	3
7	Totals:	max	2013.125	2	10411.568	1	0	2						
8		min	-2326.284	3	-5791.444	3	0	3						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M1	1	max	0	1	.003	1	0	3	0	1	0	1	0	1
2			min	0	1	0	3	0	1	0	1	0	1	0	1
3		2	max	.868	3	216.851	3	15.414	3	.047	3	.296	1	.232	1
4			min	-199.273	1	-616.634	1	-144.865	1	-.192	1	-.021	3	-.081	3
5		3	max	.398	3	215.562	3	15.414	3	.047	3	.201	1	.638	1
6			min	-199.899	1	-618.353	1	-144.865	1	-.192	1	-.011	3	-.223	3
7		4	max	-.071	3	214.272	3	15.414	3	.047	3	.106	1	1.044	1
8			min	-200.525	1	-620.072	1	-144.865	1	-.192	1	0	3	-.364	3
9		5	max	818.367	3	570.166	1	24.654	3	0	3	.145	1	1.232	1
10			min	-2685.653	1	-187.322	3	-172.223	1	-.05	1	-.033	3	-.43	3
11		6	max	817.898	3	568.447	1	24.654	3	0	3	.033	2	.859	1
12			min	-2686.279	1	-188.611	3	-172.223	1	-.05	1	-.017	3	-.307	3
13		7	max	817.429	3	566.728	1	24.654	3	0	3	0	12	.486	1
14			min	-2686.905	1	-189.9	3	-172.223	1	-.05	1	-.081	1	-.183	3
15		8	max	816.959	3	565.009	1	24.654	3	0	3	.015	3	.115	1
16			min	-2687.53	1	-191.19	3	-172.223	1	-.05	1	-.194	1	-.058	3
17		9	max	819.602	3	18.186	1	40.923	3	-.003	15	.108	1	.002	3
18			min	-2902.878	1	-4.539	3	-226.817	1	-.15	2	0	12	-.057	1
19		10	max	819.133	3	16.467	1	40.923	3	-.003	15	.028	3	.005	3
20			min	-2903.504	1	-5.828	3	-226.817	1	-.15	2	-.041	1	-.068	1
21		11	max	818.664	3	14.747	1	40.923	3	-.003	15	.055	3	.009	3
22			min	-2904.13	1	-7.118	3	-226.817	1	-.15	2	-.19	1	-.078	1
23		12	max	818.118	3	444.737	3	5.121	10	.153	3	.134	1	.077	1
24			min	-3113.358	1	-447.962	1	-77.42	3	-.235	1	.004	15	-.135	3
25		13	max	817.649	3	443.448	3	5.121	10	.153	3	.12	1	.372	1
26			min	-3113.984	1	-449.681	1	-77.42	3	-.235	1	-.026	3	-.426	3
27		14	max	817.179	3	442.158	3	5.121	10	.153	3	.105	1	.667	1
28			min	-3114.609	1	-451.4	1	-77.42	3	-.235	1	-.076	3	-.717	3
29		15	max	816.71	3	440.869	3	5.121	10	.153	3	.091	1	.964	1
30			min	-3115.235	1	-453.119	1	-77.42	3	-.235	1	-.127	3	-1.007	3
31		16	max	200.904	1	445.999	1	19.276	3	.117	1	.004	3	.733	1
32			min	-1.645	3	-458.242	3	-142.935	1	-.194	3	-.121	1	-.768	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
33		17	max	200.278	1	444.28	1	19.276	3	.117	1	.017	3	.441	1
34			min	-2.114	3	-459.531	3	-142.935	1	-.194	3	-.214	1	-.467	3
35		18	max	199.652	1	442.561	1	19.276	3	.117	1	.03	3	.15	1
36			min	-2.583	3	-460.82	3	-142.935	1	-.194	3	-.308	1	-.165	3
37		19	max	0	1	0	5	0	1	0	1	0	1	0	1
38			min	0	1	0	1	0	3	0	1	0	1	0	1
39	M4	1	max	0	1	.006	1	0	1	0	1	0	1	0	1
40			min	0	1	-.001	3	0	1	0	1	0	1	0	1
41		2	max	6.779	10	557.901	3	0	1	0	1	0	1	.412	1
42			min	-234.402	1	-1388.269	1	0	1	0	1	0	1	-.17	3
43		3	max	6.258	10	556.612	3	0	1	0	1	0	1	1.324	1
44			min	-235.028	1	-1389.988	1	0	1	0	1	0	1	-.536	3
45		4	max	5.736	10	555.322	3	0	1	0	1	0	1	2.236	1
46			min	-235.653	1	-1391.707	1	0	1	0	1	0	1	-.901	3
47		5	max	2308.708	3	1418.752	1	0	1	0	1	0	1	2.633	1
48			min	-6118.113	1	-587.95	3	0	1	0	1	0	1	-1.055	3
49		6	max	2308.239	3	1417.033	1	0	1	0	1	0	1	1.703	1
50			min	-6118.739	1	-589.239	3	0	1	0	1	0	1	-.669	3
51		7	max	2307.769	3	1415.314	1	0	1	0	1	0	1	.774	1
52			min	-6119.364	1	-590.529	3	0	1	0	1	0	1	-.282	3
53		8	max	2307.3	3	1413.595	1	0	1	0	1	0	1	.106	3
54			min	-6119.99	1	-591.818	3	0	1	0	1	0	1	-.154	1
55		9	max	2266.334	3	26.281	3	0	1	0	1	0	1	.292	3
56			min	-6322.243	1	-128.642	1	0	1	0	1	0	1	-.589	1
57		10	max	2265.865	3	24.992	3	0	1	0	1	0	1	.275	3
58			min	-6322.868	1	-130.361	1	0	1	0	1	0	1	-.504	1
59		11	max	2265.396	3	23.702	3	0	1	0	1	0	1	.259	3
60			min	-6323.494	1	-132.081	1	0	1	0	1	0	1	-.418	1
61		12	max	2230.808	3	1326.781	3	0	1	0	1	0	1	.075	1
62			min	-6537.986	1	-1519.855	1	0	1	0	1	0	1	-.161	3
63		13	max	2230.339	3	1325.491	3	0	1	0	1	0	1	1.073	1
64			min	-6538.612	1	-1521.574	1	0	1	0	1	0	1	-1.031	3
65		14	max	2229.87	3	1324.202	3	0	1	0	1	0	1	2.072	1
66			min	-6539.238	1	-1523.293	1	0	1	0	1	0	1	-1.9	3
67		15	max	2229.401	3	1322.913	3	0	1	0	1	0	1	3.072	1
68			min	-6539.863	1	-1525.012	1	0	1	0	1	0	1	-2.769	3
69		16	max	234.895	1	1424.717	1	0	1	0	1	0	1	2.34	1
70			min	-6.292	10	-1288.95	3	0	1	0	1	0	1	-2.103	3
71		17	max	234.27	1	1422.998	1	0	1	0	1	0	1	1.405	1
72			min	-6.814	10	-1290.239	3	0	1	0	1	0	1	-1.257	3
73		18	max	233.644	1	1421.278	1	0	1	0	1	0	1	.472	1
74			min	-7.335	10	-1291.529	3	0	1	0	1	0	1	-.41	3
75		19	max	0	1	0	5	0	1	0	1	0	1	0	1
76			min	0	1	-.001	3	0	1	0	1	0	1	0	1
77	M7	1	max	0	1	.003	1	0	1	0	1	0	1	0	1
78			min	0	1	0	3	0	3	0	1	0	1	0	1
79		2	max	.868	3	216.851	3	144.865	1	.192	1	.021	3	.232	1
80			min	-199.273	1	-616.634	1	-15.414	3	-.047	3	-.296	1	-.081	3
81		3	max	.398	3	215.562	3	144.865	1	.192	1	.011	3	.638	1
82			min	-199.899	1	-618.353	1	-15.414	3	-.047	3	-.201	1	-.223	3
83		4	max	-.071	3	214.272	3	144.865	1	.192	1	0	3	1.044	1
84			min	-200.525	1	-620.072	1	-15.414	3	-.047	3	-.106	1	-.364	3
85		5	max	818.367	3	570.166	1	172.223	1	.05	1	.033	3	1.232	1
86			min	-2685.653	1	-187.322	3	-24.654	3	0	3	-.145	1	-.43	3
87		6	max	817.898	3	568.447	1	172.223	1	.05	1	.017	3	.859	1
88			min	-2686.279	1	-188.611	3	-24.654	3	0	3	-.033	2	-.307	3
89		7	max	817.429	3	566.728	1	172.223	1	.05	1	.081	1	.486	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
90			min	-2686.905	1	-189.9	3	-24.654	3	0	3	0	12	-.183	3
91		8	max	816.959	3	565.009	1	172.223	1	.05	1	.194	1	.115	1
92			min	-2687.53	1	-191.19	3	-24.654	3	0	3	-.015	3	-.058	3
93		9	max	819.602	3	18.186	1	226.817	1	.15	2	0	12	.002	3
94			min	-2902.878	1	-4.539	3	-40.923	3	.003	15	-.108	1	-.057	1
95		10	max	819.133	3	16.467	1	226.817	1	.15	2	.041	1	.005	3
96			min	-2903.504	1	-5.828	3	-40.923	3	.003	15	-.028	3	-.068	1
97		11	max	818.664	3	14.747	1	226.817	1	.15	2	.19	1	.009	3
98			min	-2904.13	1	-7.118	3	-40.923	3	.003	15	-.055	3	-.078	1
99		12	max	818.118	3	444.737	3	77.42	3	.235	1	-.004	15	.077	1
100			min	-3113.358	1	-447.962	1	-5.121	10	-.153	3	-.134	1	-.135	3
101		13	max	817.649	3	443.448	3	77.42	3	.235	1	.026	3	.372	1
102			min	-3113.984	1	-449.681	1	-5.121	10	-.153	3	-.12	1	-.426	3
103		14	max	817.179	3	442.158	3	77.42	3	.235	1	.076	3	.667	1
104			min	-3114.609	1	-451.4	1	-5.121	10	-.153	3	-.105	1	-.717	3
105		15	max	816.71	3	440.869	3	77.42	3	.235	1	.127	3	.964	1
106			min	-3115.235	1	-453.119	1	-5.121	10	-.153	3	-.091	1	-1.007	3
107		16	max	200.904	1	445.999	1	142.935	1	.194	3	.121	1	.733	1
108			min	-1.645	3	-458.242	3	-19.276	3	-.117	1	-.004	3	-.768	3
109		17	max	200.278	1	444.28	1	142.935	1	.194	3	.214	1	.441	1
110			min	-2.114	3	-459.531	3	-19.276	3	-.117	1	-.017	3	-.467	3
111		18	max	199.652	1	442.561	1	142.935	1	.194	3	.308	1	.15	1
112			min	-2.583	3	-460.82	3	-19.276	3	-.117	1	-.03	3	-.165	3
113		19	max	0	1	0	5	0	3	0	1	0	1	0	1
114			min	0	1	0	1	0	1	0	1	0	1	0	1
115	M10	1	max	142.959	1	442.042	1	3.038	3	.002	1	.356	1	.117	1
116			min	-19.277	3	-462.091	3	-199.616	1	-.011	3	-.036	3	-.194	3
117		2	max	142.959	1	313.925	1	4.942	3	.002	1	.194	1	.162	3
118			min	-19.277	3	-338.944	3	-164.557	1	-.011	3	-.033	3	-.219	1
119		3	max	142.959	1	185.809	1	6.846	3	.002	1	.071	2	.409	3
120			min	-19.277	3	-215.797	3	-129.497	1	-.011	3	-.027	3	-.441	1
121		4	max	142.959	1	57.692	1	8.75	3	.002	1	.014	10	.546	3
122			min	-19.277	3	-92.651	3	-94.438	1	-.011	3	-.036	1	-.549	1
123		5	max	142.959	1	30.496	3	10.654	3	.002	1	-.004	15	.573	3
124			min	-19.277	3	-70.425	1	-59.378	1	-.011	3	-.104	1	-.543	1
125		6	max	142.959	1	153.643	3	12.558	3	.002	1	-.001	12	.492	3
126			min	-19.277	3	-198.542	1	-32.326	2	-.011	3	-.142	1	-.424	1
127		7	max	142.959	1	276.789	3	16.469	9	.002	1	.01	3	.3	3
128			min	-19.277	3	-326.658	1	-18.524	2	-.011	3	-.148	1	-.19	1
129		8	max	142.959	1	399.936	3	45.8	1	.002	1	.024	3	.157	1
130			min	-19.277	3	-454.775	1	-10.892	10	-.011	3	-.122	1	0	3
131		9	max	142.959	1	523.083	3	80.86	1	.002	1	.04	3	.618	1
132			min	-19.277	3	-582.892	1	-7.442	10	-.011	3	-.101	2	-.411	3
133		10	max	142.959	1	711.009	1	3.992	10	.002	1	.057	3	1.193	1
134			min	-19.277	3	-646.229	3	-115.919	1	-.011	3	-.087	2	-.93	3
135		11	max	142.959	1	582.892	1	7.442	10	.011	3	.04	3	.618	1
136			min	-19.277	3	-523.083	3	-80.86	1	-.002	1	-.101	2	-.411	3
137		12	max	142.959	1	454.775	1	10.892	10	.011	3	.024	3	.157	1
138			min	-19.277	3	-399.936	3	-45.8	1	-.002	1	-.122	1	0	3
139		13	max	142.959	1	326.658	1	18.524	2	.011	3	.01	3	.3	3
140			min	-19.277	3	-276.789	3	-16.469	9	-.002	1	-.148	1	-.19	1
141		14	max	142.959	1	198.542	1	32.326	2	.011	3	-.001	12	.492	3
142			min	-19.277	3	-153.643	3	-12.558	3	-.002	1	-.142	1	-.424	1
143		15	max	142.959	1	70.425	1	59.378	1	.011	3	-.004	15	.573	3
144			min	-19.277	3	-30.496	3	-10.654	3	-.002	1	-.104	1	-.543	1
145		16	max	142.959	1	92.651	3	94.438	1	.011	3	.014	10	.546	3
146			min	-19.277	3	-57.692	1	-8.75	3	-.002	1	-.036	1	-.549	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
147		17	max	142.959	1	215.797	3	129.497	1	.011	3	.071	2	.409	3
148			min	-19.277	3	-185.809	1	-6.846	3	-.002	1	-.027	3	-.441	1
149		18	max	142.959	1	338.944	3	164.557	1	.011	3	.194	1	.162	3
150			min	-19.277	3	-313.925	1	-4.942	3	-.002	1	-.033	3	-.219	1
151		19	max	142.959	1	462.091	3	199.616	1	.011	3	.356	1	.117	1
152			min	-19.277	3	-442.042	1	-3.038	3	-.002	1	-.036	3	-.194	3
153	M11	1	max	204.169	1	461.728	1	-.169	3	.005	3	.408	1	.089	1
154			min	-118.149	3	-454.016	3	-209.455	1	-.018	1	-.019	3	-.188	3
155		2	max	204.169	1	333.611	1	1.735	3	.005	3	.237	1	.161	3
156			min	-118.149	3	-330.87	3	-174.396	1	-.018	1	-.018	3	-.264	1
157		3	max	204.169	1	205.494	1	3.639	3	.005	3	.098	1	.4	3
158			min	-118.149	3	-207.723	3	-139.336	1	-.018	1	-.016	3	-.504	1
159		4	max	204.169	1	77.378	1	5.543	3	.005	3	.025	2	.53	3
160			min	-118.149	3	-84.576	3	-104.277	1	-.018	1	-.019	9	-.63	1
161		5	max	204.169	1	38.57	3	7.447	3	.005	3	-.003	10	.551	3
162			min	-118.149	3	-50.739	1	-69.217	1	-.018	1	-.088	1	-.641	1
163		6	max	204.169	1	161.717	3	9.351	3	.005	3	.002	3	.462	3
164			min	-118.149	3	-178.856	1	-37.813	2	-.018	1	-.134	1	-.539	1
165		7	max	204.169	1	284.864	3	11.255	3	.005	3	.011	3	.263	3
166			min	-118.149	3	-306.973	1	-24.011	2	-.018	1	-.149	1	-.323	1
167		8	max	204.169	1	408.01	3	35.961	1	.005	3	.022	3	.006	1
168			min	-118.149	3	-435.09	1	-12.931	10	-.018	1	-.132	1	-.045	3
169		9	max	204.169	1	531.157	3	71.021	1	.005	3	.034	3	.45	1
170			min	-118.149	3	-563.206	1	-9.481	10	-.018	1	-.112	2	-.462	3
171		10	max	204.169	1	691.323	1	6.032	10	.018	1	.048	3	1.008	1
172			min	-118.149	3	-654.304	3	-106.08	1	-.005	3	-.103	2	-.989	3
173		11	max	204.169	1	563.206	1	9.481	10	.018	1	.034	3	.45	1
174			min	-118.149	3	-531.157	3	-71.021	1	-.005	3	-.112	2	-.462	3
175		12	max	204.169	1	435.09	1	12.931	10	.018	1	.022	3	.006	1
176			min	-118.149	3	-408.01	3	-35.961	1	-.005	3	-.132	1	-.045	3
177		13	max	204.169	1	306.973	1	24.011	2	.018	1	.011	3	.263	3
178			min	-118.149	3	-284.864	3	-11.255	3	-.005	3	-.149	1	-.323	1
179		14	max	204.169	1	178.856	1	37.813	2	.018	1	.002	3	.462	3
180			min	-118.149	3	-161.717	3	-9.351	3	-.005	3	-.134	1	-.539	1
181		15	max	204.169	1	50.739	1	69.217	1	.018	1	-.003	10	.551	3
182			min	-118.149	3	-38.57	3	-7.447	3	-.005	3	-.088	1	-.641	1
183		16	max	204.169	1	84.576	3	104.277	1	.018	1	.025	2	.53	3
184			min	-118.149	3	-77.378	1	-5.543	3	-.005	3	-.019	9	-.63	1
185		17	max	204.169	1	207.723	3	139.336	1	.018	1	.098	1	.4	3
186			min	-118.149	3	-205.494	1	-3.639	3	-.005	3	-.016	3	-.504	1
187		18	max	204.169	1	330.87	3	174.396	1	.018	1	.237	1	.161	3
188			min	-118.149	3	-333.611	1	-1.735	3	-.005	3	-.018	3	-.264	1
189		19	max	204.169	1	454.016	3	209.455	1	.018	1	.408	1	.089	1
190			min	-118.149	3	-461.728	1	.169	3	-.005	3	-.019	3	-.188	3
191	M12	1	max	16.381	3	544.306	1	3.126	3	.003	3	.434	1	.103	2
192			min	-52.544	1	-188.392	3	-214.5	1	-.014	1	-.036	3	.002	15
193		2	max	16.381	3	398.023	1	5.029	3	.003	3	.259	1	.178	3
194			min	-52.544	1	-133.067	3	-179.441	1	-.014	1	-.032	3	-.324	1
195		3	max	16.381	3	251.739	1	6.933	3	.003	3	.115	1	.272	3
196			min	-52.544	1	-77.743	3	-144.381	1	-.014	1	-.027	3	-.612	1
197		4	max	16.381	3	105.456	1	8.837	3	.003	3	.036	2	.316	3
198			min	-52.544	1	-22.419	3	-109.322	1	-.014	1	-.02	3	-.771	1
199		5	max	16.381	3	32.906	3	10.741	3	.003	3	0	10	.312	3
200			min	-52.544	1	-40.828	1	-74.262	1	-.014	1	-.08	1	-.8	1
201		6	max	16.381	3	88.23	3	12.645	3	.003	3	0	3	.258	3
202			min	-52.544	1	-187.111	1	-41.992	2	-.014	1	-.13	1	-.698	1
203		7	max	16.381	3	143.555	3	14.549	3	.003	3	.011	3	.155	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
204			min	-52.544	1	-333.395	1	-28.19	2	-.014	1	-.149	1	-.467	1
205		8	max	16.381	3	198.879	3	31.155	9	.003	3	.025	3	.003	3
206			min	-52.544	1	-479.678	1	-14.931	10	-.014	1	-.137	1	-.106	1
207		9	max	16.381	3	254.204	3	65.976	1	.003	3	.04	3	.386	1
208			min	-52.544	1	-625.961	1	-11.482	10	-.014	1	-.12	2	-.199	3
209		10	max	16.381	3	772.245	1	8.032	10	.014	1	.058	3	1.007	1
210			min	-52.544	1	-309.528	3	-101.035	1	-.003	3	-.115	2	-.449	3
211		11	max	16.381	3	625.961	1	11.482	10	.014	1	.04	3	.386	1
212			min	-52.544	1	-254.204	3	-65.976	1	-.003	3	-.12	2	-.199	3
213		12	max	16.381	3	479.678	1	14.931	10	.014	1	.025	3	.003	3
214			min	-52.544	1	-198.879	3	-31.155	9	-.003	3	-.137	1	-.106	1
215		13	max	16.381	3	333.395	1	28.19	2	.014	1	.011	3	.155	3
216			min	-52.544	1	-143.555	3	-14.549	3	-.003	3	-.149	1	-.467	1
217		14	max	16.381	3	187.111	1	41.992	2	.014	1	0	3	.258	3
218			min	-52.544	1	-88.23	3	-12.645	3	-.003	3	-.13	1	-.698	1
219		15	max	16.381	3	40.828	1	74.262	1	.014	1	0	10	.312	3
220			min	-52.544	1	-32.906	3	-10.741	3	-.003	3	-.08	1	-.8	1
221		16	max	16.381	3	22.419	3	109.322	1	.014	1	.036	2	.316	3
222			min	-52.544	1	-105.456	1	-8.837	3	-.003	3	-.02	3	-.771	1
223		17	max	16.381	3	77.743	3	144.381	1	.014	1	.115	1	.272	3
224			min	-52.544	1	-251.739	1	-6.933	3	-.003	3	-.027	3	-.612	1
225		18	max	16.381	3	133.067	3	179.441	1	.014	1	.259	1	.178	3
226			min	-52.544	1	-398.023	1	-5.029	3	-.003	3	-.032	3	-.324	1
227		19	max	16.381	3	188.392	3	214.5	1	.014	1	.434	1	.103	2
228			min	-52.544	1	-544.306	1	-3.126	3	-.003	3	-.036	3	.002	15
229	M13	1	max	15.414	3	617.136	1	1.35	3	.008	3	.345	1	.192	1
230			min	-144.702	1	-218.188	3	-198.029	1	-.026	1	-.026	3	-.047	3
231		2	max	15.414	3	470.852	1	3.254	3	.008	3	.184	1	.122	3
232			min	-144.702	1	-162.863	3	-162.97	1	-.026	1	-.024	3	-.292	1
233		3	max	15.414	3	324.569	1	5.157	3	.008	3	.065	2	.242	3
234			min	-144.702	1	-107.539	3	-127.91	1	-.026	1	-.02	3	-.645	1
235		4	max	15.414	3	178.285	1	7.061	3	.008	3	.012	10	.313	3
236			min	-144.702	1	-52.215	3	-92.851	1	-.026	1	-.043	1	-.869	1
237		5	max	15.414	3	32.002	1	8.965	3	.008	3	-.004	15	.335	3
238			min	-144.702	1	.872	15	-57.791	1	-.026	1	-.11	1	-.962	1
239		6	max	15.414	3	58.434	3	10.869	3	.008	3	.001	3	.308	3
240			min	-144.702	1	-114.282	1	-31.333	2	-.026	1	-.146	1	-.926	1
241		7	max	15.414	3	113.759	3	17.358	9	.008	3	.012	3	.231	3
242			min	-144.702	1	-260.565	1	-17.531	2	-.026	1	-.15	1	-.759	1
243		8	max	15.414	3	169.083	3	47.387	1	.008	3	.024	3	.106	3
244			min	-144.702	1	-406.849	1	-10.478	10	-.026	1	-.124	1	-.462	1
245		9	max	15.414	3	224.408	3	82.447	1	.008	3	.038	3	.012	10
246			min	-144.702	1	-553.132	1	-7.028	10	-.026	1	-.102	2	-.069	3
247		10	max	15.414	3	279.732	3	117.506	1	.026	1	.055	9	.536	2
248			min	-144.702	1	-699.416	1	-3.578	10	-.008	3	-.087	2	-.293	3
249		11	max	15.414	3	553.132	1	7.028	10	.026	1	.038	3	.012	10
250			min	-144.702	1	-224.408	3	-82.447	1	-.008	3	-.102	2	-.069	3
251		12	max	15.414	3	406.849	1	10.478	10	.026	1	.024	3	.106	3
252			min	-144.702	1	-169.083	3	-47.387	1	-.008	3	-.124	1	-.462	1
253		13	max	15.414	3	260.565	1	17.531	2	.026	1	.012	3	.231	3
254			min	-144.702	1	-113.759	3	-17.358	9	-.008	3	-.15	1	-.759	1
255		14	max	15.414	3	114.282	1	31.333	2	.026	1	.001	3	.308	3
256			min	-144.702	1	-58.434	3	-10.869	3	-.008	3	-.146	1	-.926	1
257		15	max	15.414	3	-.872	15	57.791	1	.026	1	-.004	15	.335	3
258			min	-144.702	1	-32.002	1	-8.965	3	-.008	3	-.11	1	-.962	1
259		16	max	15.414	3	52.215	3	92.851	1	.026	1	.012	10	.313	3
260			min	-144.702	1	-178.285	1	-7.061	3	-.008	3	-.043	1	-.869	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
261		17	max	15.414	3	107.539	3	127.91	1	.026	1	.065	2	.242	3
262			min	-144.702	1	-324.569	1	-5.157	3	-.008	3	-.02	3	-.645	1
263		18	max	15.414	3	162.863	3	162.97	1	.026	1	.184	1	.122	3
264			min	-144.702	1	-470.852	1	-3.254	3	-.008	3	-.024	3	-.292	1
265		19	max	15.414	3	218.188	3	198.029	1	.026	1	.345	1	.192	1
266			min	-144.702	1	-617.136	1	-1.35	3	-.008	3	-.026	3	-.047	3
267	M2	1	max	2311.78	1	445.812	3	150.24	1	0	3	.116	3	8.571	1
268			min	-1179.081	3	-215.257	2	-105.565	3	-.002	1	-.23	1	-.451	3
269		2	max	2309.223	1	445.812	3	150.24	1	0	3	.086	3	8.55	1
270			min	-1180.999	3	-215.257	2	-105.565	3	-.002	1	-.187	1	-.576	3
271		3	max	2306.665	1	445.812	3	150.24	1	0	3	.056	3	8.529	1
272			min	-1182.917	3	-215.257	2	-105.565	3	-.002	1	-.145	1	-.701	3
273		4	max	2304.108	1	445.812	3	150.24	1	0	3	.027	3	8.509	1
274			min	-1184.835	3	-215.257	2	-105.565	3	-.002	1	-.103	1	-.826	3
275		5	max	2301.55	1	445.812	3	150.24	1	0	3	-.002	12	8.488	1
276			min	-1186.753	3	-215.257	2	-105.565	3	-.002	1	-.061	1	-.952	3
277		6	max	2298.993	1	445.812	3	150.24	1	0	3	.004	10	8.467	1
278			min	-1188.671	3	-215.257	2	-105.565	3	-.002	1	-.033	3	-1.077	3
279		7	max	2296.435	1	445.812	3	150.24	1	0	3	.035	2	8.447	1
280			min	-1190.59	3	-215.257	2	-105.565	3	-.002	1	-.062	3	-1.202	3
281		8	max	2293.878	1	445.812	3	150.24	1	0	3	.069	2	8.426	1
282			min	-1192.508	3	-215.257	2	-105.565	3	-.002	1	-.092	3	-1.327	3
283		9	max	2042.532	1	2819.664	1	120.447	1	.002	1	.037	2	7.919	1
284			min	-1103.589	3	-460.056	3	-96.784	3	0	3	-.097	3	-1.292	3
285		10	max	2039.974	1	2819.664	1	120.447	1	.002	1	.07	1	7.127	1
286			min	-1105.507	3	-460.056	3	-96.784	3	0	3	-.125	3	-1.163	3
287		11	max	2037.417	1	2819.664	1	120.447	1	.002	1	.103	1	6.335	1
288			min	-1107.425	3	-460.056	3	-96.784	3	0	3	-.152	3	-1.034	3
289		12	max	2034.859	1	2819.664	1	120.447	1	.002	1	.137	1	5.544	1
290			min	-1109.343	3	-460.056	3	-96.784	3	0	3	-.179	3	-.904	3
291		13	max	2032.302	1	2819.664	1	120.447	1	.002	1	.171	1	4.752	1
292			min	-1111.261	3	-460.056	3	-96.784	3	0	3	-.206	3	-.775	3
293		14	max	2029.744	1	2819.664	1	120.447	1	.002	1	.205	1	3.96	1
294			min	-1113.179	3	-460.056	3	-96.784	3	0	3	-.233	3	-.646	3
295		15	max	2027.187	1	2819.664	1	120.447	1	.002	1	.239	1	3.168	1
296			min	-1115.097	3	-460.056	3	-96.784	3	0	3	-.26	3	-.517	3
297		16	max	2024.629	1	2819.664	1	120.447	1	.002	1	.273	1	2.376	1
298			min	-1117.016	3	-460.056	3	-96.784	3	0	3	-.288	3	-.388	3
299		17	max	2022.072	1	2819.664	1	120.447	1	.002	1	.306	1	1.584	1
300			min	-1118.934	3	-460.056	3	-96.784	3	0	3	-.315	3	-.258	3
301		18	max	2019.514	1	2819.664	1	120.447	1	.002	1	.34	1	.792	1
302			min	-1120.852	3	-460.056	3	-96.784	3	0	3	-.342	3	-.129	3
303		19	max	2016.957	1	2819.664	1	120.447	1	.002	1	.374	1	0	1
304			min	-1122.77	3	-460.056	3	-96.784	3	0	3	-.369	3	0	1
305	M5	1	max	5788.008	1	1437.624	3	0	1	0	1	0	1	13.911	1
306			min	-3433.282	3	-1544.181	2	0	1	0	1	0	1	-.469	3
307		2	max	5785.45	1	1437.624	3	0	1	0	1	0	1	14.219	1
308			min	-3435.2	3	-1544.181	2	0	1	0	1	0	1	-.873	3
309		3	max	5782.893	1	1437.624	3	0	1	0	1	0	1	14.526	1
310			min	-3437.118	3	-1544.181	2	0	1	0	1	0	1	-1.277	3
311		4	max	5780.335	1	1437.624	3	0	1	0	1	0	1	14.834	1
312			min	-3439.036	3	-1544.181	2	0	1	0	1	0	1	-1.681	3
313		5	max	5777.778	1	1437.624	3	0	1	0	1	0	1	15.142	1
314			min	-3440.954	3	-1544.181	2	0	1	0	1	0	1	-2.084	3
315		6	max	5775.22	1	1437.624	3	0	1	0	1	0	1	15.45	1
316			min	-3442.872	3	-1544.181	2	0	1	0	1	0	1	-2.488	3
317		7	max	5772.663	1	1437.624	3	0	1	0	1	0	1	15.758	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
318			min	-3444.79	3	-1544.181	2	0	1	0	1	0	1	-2.892	3
319		8	max	5770.105	1	1437.624	3	0	1	0	1	0	1	16.066	1
320			min	-3446.709	3	-1544.181	2	0	1	0	1	0	1	-3.296	3
321		9	max	5258.31	1	5419.246	1	0	1	0	1	0	1	15.221	1
322			min	-3175.041	3	-1153.956	3	0	1	0	1	0	1	-3.241	3
323		10	max	5255.753	1	5419.246	1	0	1	0	1	0	1	13.699	1
324			min	-3176.959	3	-1153.956	3	0	1	0	1	0	1	-2.917	3
325		11	max	5253.196	1	5419.246	1	0	1	0	1	0	1	12.176	1
326			min	-3178.877	3	-1153.956	3	0	1	0	1	0	1	-2.593	3
327		12	max	5250.638	1	5419.246	1	0	1	0	1	0	1	10.654	1
328			min	-3180.795	3	-1153.956	3	0	1	0	1	0	1	-2.269	3
329		13	max	5248.081	1	5419.246	1	0	1	0	1	0	1	9.132	1
330			min	-3182.713	3	-1153.956	3	0	1	0	1	0	1	-1.945	3
331		14	max	5245.523	1	5419.246	1	0	1	0	1	0	1	7.61	1
332			min	-3184.632	3	-1153.956	3	0	1	0	1	0	1	-1.621	3
333		15	max	5242.966	1	5419.246	1	0	1	0	1	0	1	6.088	1
334			min	-3186.55	3	-1153.956	3	0	1	0	1	0	1	-1.296	3
335		16	max	5240.408	1	5419.246	1	0	1	0	1	0	1	4.566	1
336			min	-3188.468	3	-1153.956	3	0	1	0	1	0	1	-.972	3
337		17	max	5237.851	1	5419.246	1	0	1	0	1	0	1	3.044	1
338			min	-3190.386	3	-1153.956	3	0	1	0	1	0	1	-.648	3
339		18	max	5235.293	1	5419.246	1	0	1	0	1	0	1	1.522	1
340			min	-3192.304	3	-1153.956	3	0	1	0	1	0	1	-.324	3
341		19	max	5232.736	1	5419.246	1	0	1	0	1	0	1	0	1
342			min	-3194.222	3	-1153.956	3	0	1	0	1	0	1	0	1
343	M8	1	max	2311.78	1	445.812	3	105.565	3	.002	1	.23	1	8.571	1
344			min	-1179.081	3	-215.257	2	-150.24	1	0	3	-.116	3	-.451	3
345		2	max	2309.223	1	445.812	3	105.565	3	.002	1	.187	1	8.55	1
346			min	-1180.999	3	-215.257	2	-150.24	1	0	3	-.086	3	-.576	3
347		3	max	2306.665	1	445.812	3	105.565	3	.002	1	.145	1	8.529	1
348			min	-1182.917	3	-215.257	2	-150.24	1	0	3	-.056	3	-.701	3
349		4	max	2304.108	1	445.812	3	105.565	3	.002	1	.103	1	8.509	1
350			min	-1184.835	3	-215.257	2	-150.24	1	0	3	-.027	3	-.826	3
351		5	max	2301.55	1	445.812	3	105.565	3	.002	1	.061	1	8.488	1
352			min	-1186.753	3	-215.257	2	-150.24	1	0	3	.002	12	-.952	3
353		6	max	2298.993	1	445.812	3	105.565	3	.002	1	.033	3	8.467	1
354			min	-1188.671	3	-215.257	2	-150.24	1	0	3	-.004	10	-1.077	3
355		7	max	2296.435	1	445.812	3	105.565	3	.002	1	.062	3	8.447	1
356			min	-1190.59	3	-215.257	2	-150.24	1	0	3	-.035	2	-1.202	3
357		8	max	2293.878	1	445.812	3	105.565	3	.002	1	.092	3	8.426	1
358			min	-1192.508	3	-215.257	2	-150.24	1	0	3	-.069	2	-1.327	3
359		9	max	2042.532	1	2819.664	1	96.784	3	0	3	.097	3	7.919	1
360			min	-1103.589	3	-460.056	3	-120.447	1	-.002	1	-.037	2	-1.292	3
361		10	max	2039.974	1	2819.664	1	96.784	3	0	3	.125	3	7.127	1
362			min	-1105.507	3	-460.056	3	-120.447	1	-.002	1	-.07	1	-1.163	3
363		11	max	2037.417	1	2819.664	1	96.784	3	0	3	.152	3	6.335	1
364			min	-1107.425	3	-460.056	3	-120.447	1	-.002	1	-.103	1	-1.034	3
365		12	max	2034.859	1	2819.664	1	96.784	3	0	3	.179	3	5.544	1
366			min	-1109.343	3	-460.056	3	-120.447	1	-.002	1	-.137	1	-.904	3
367		13	max	2032.302	1	2819.664	1	96.784	3	0	3	.206	3	4.752	1
368			min	-1111.261	3	-460.056	3	-120.447	1	-.002	1	-.171	1	-.775	3
369		14	max	2029.744	1	2819.664	1	96.784	3	0	3	.233	3	3.96	1
370			min	-1113.179	3	-460.056	3	-120.447	1	-.002	1	-.205	1	-.646	3
371		15	max	2027.187	1	2819.664	1	96.784	3	0	3	.26	3	3.168	1
372			min	-1115.097	3	-460.056	3	-120.447	1	-.002	1	-.239	1	-.517	3
373		16	max	2024.629	1	2819.664	1	96.784	3	0	3	.288	3	2.376	1
374			min	-1117.016	3	-460.056	3	-120.447	1	-.002	1	-.273	1	-.388	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
375		17	max	2022.072	1	2819.664	1	96.784	3	0	3	.315	3	1.584	1
376			min	-1118.934	3	-460.056	3	-120.447	1	-.002	1	-.306	1	-.258	3
377		18	max	2019.514	1	2819.664	1	96.784	3	0	3	.342	3	.792	1
378			min	-1120.852	3	-460.056	3	-120.447	1	-.002	1	-.34	1	-.129	3
379		19	max	2016.957	1	2819.664	1	96.784	3	0	3	.369	3	0	1
380			min	-1122.77	3	-460.056	3	-120.447	1	-.002	1	-.374	1	0	1
381	M3	1	max	2742.169	1	6.095	4	28.5	1	.023	3	.003	1	0	1
382			min	-911.666	3	1.433	15	-9.211	3	-.067	1	0	3	0	1
383		2	max	2742.115	1	5.418	4	28.5	1	.023	3	.013	1	0	15
384			min	-911.707	3	1.274	15	-9.211	3	-.067	1	-.004	3	-.002	4
385		3	max	2742.061	1	4.741	4	28.5	1	.023	3	.023	1	0	15
386			min	-911.747	3	1.114	15	-9.211	3	-.067	1	-.008	3	-.004	4
387		4	max	2742.007	1	4.064	4	28.5	1	.023	3	.034	1	-.001	15
388			min	-911.788	3	.955	15	-9.211	3	-.067	1	-.011	3	-.005	4
389		5	max	2741.953	1	3.386	4	28.5	1	.023	3	.044	1	-.002	15
390			min	-911.828	3	.796	15	-9.211	3	-.067	1	-.014	3	-.007	4
391		6	max	2741.899	1	2.709	4	28.5	1	.023	3	.054	1	-.002	15
392			min	-911.869	3	.637	15	-9.211	3	-.067	1	-.017	3	-.008	4
393		7	max	2741.845	1	2.032	4	28.5	1	.023	3	.064	1	-.002	15
394			min	-911.909	3	.478	15	-9.211	3	-.067	1	-.021	3	-.009	4
395		8	max	2741.791	1	1.355	4	28.5	1	.023	3	.074	1	-.002	15
396			min	-911.95	3	.318	15	-9.211	3	-.067	1	-.024	3	-.009	4
397		9	max	2741.737	1	.677	4	28.5	1	.023	3	.085	1	-.002	15
398			min	-911.99	3	.159	15	-9.211	3	-.067	1	-.027	3	-.01	4
399		10	max	2741.683	1	0	1	28.5	1	.023	3	.095	1	-.002	15
400			min	-912.031	3	0	1	-9.211	3	-.067	1	-.031	3	-.01	4
401		11	max	2741.629	1	-.159	15	28.5	1	.023	3	.105	1	-.002	15
402			min	-912.071	3	-.677	4	-9.211	3	-.067	1	-.034	3	-.01	4
403		12	max	2741.575	1	-.318	15	28.5	1	.023	3	.115	1	-.002	15
404			min	-912.112	3	-1.355	4	-9.211	3	-.067	1	-.037	3	-.009	4
405		13	max	2741.521	1	-.478	15	28.5	1	.023	3	.125	1	-.002	15
406			min	-912.152	3	-2.032	4	-9.211	3	-.067	1	-.04	3	-.009	4
407		14	max	2741.467	1	-.637	15	28.5	1	.023	3	.136	1	-.002	15
408			min	-912.193	3	-2.709	4	-9.211	3	-.067	1	-.044	3	-.008	4
409		15	max	2741.413	1	-.796	15	28.5	1	.023	3	.146	1	-.002	15
410			min	-912.233	3	-3.386	4	-9.211	3	-.067	1	-.047	3	-.007	4
411		16	max	2741.359	1	-.955	15	28.5	1	.023	3	.156	1	-.001	15
412			min	-912.274	3	-4.064	4	-9.211	3	-.067	1	-.05	3	-.005	4
413		17	max	2741.305	1	-1.114	15	28.5	1	.023	3	.166	1	0	15
414			min	-912.314	3	-4.741	4	-9.211	3	-.067	1	-.054	3	-.004	4
415		18	max	2741.251	1	-1.274	15	28.5	1	.023	3	.176	1	0	15
416			min	-912.355	3	-5.418	4	-9.211	3	-.067	1	-.057	3	-.002	4
417		19	max	2741.197	1	-1.433	15	28.5	1	.023	3	.186	1	0	1
418			min	-912.395	3	-6.095	4	-9.211	3	-.067	1	-.06	3	0	1
419	M6	1	max	6459.574	1	6.095	4	0	1	0	1	0	1	0	1
420			min	-2614.714	3	1.433	15	0	1	0	1	0	1	0	1
421		2	max	6459.52	1	5.418	4	0	1	0	1	0	1	0	15
422			min	-2614.755	3	1.274	15	0	1	0	1	0	1	-.002	4
423		3	max	6459.466	1	4.741	4	0	1	0	1	0	1	0	15
424			min	-2614.795	3	1.114	15	0	1	0	1	0	1	-.004	4
425		4	max	6459.412	1	4.064	4	0	1	0	1	0	1	-.001	15
426			min	-2614.836	3	.955	15	0	1	0	1	0	1	-.005	4
427		5	max	6459.358	1	3.386	4	0	1	0	1	0	1	-.002	15
428			min	-2614.876	3	.796	15	0	1	0	1	0	1	-.007	4
429		6	max	6459.304	1	2.709	4	0	1	0	1	0	1	-.002	15
430			min	-2614.917	3	.637	15	0	1	0	1	0	1	-.008	4
431		7	max	6459.25	1	2.032	4	0	1	0	1	0	1	-.002	15

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
432			min	-2614.957	3	.478	15	0	1	0	1	0	1	-.009	4
433		8	max	6459.196	1	1.355	4	0	1	0	1	0	1	-.002	15
434			min	-2614.998	3	.318	15	0	1	0	1	0	1	-.009	4
435		9	max	6459.142	1	.677	4	0	1	0	1	0	1	-.002	15
436			min	-2615.038	3	.159	15	0	1	0	1	0	1	-.01	4
437		10	max	6459.088	1	0	1	0	1	0	1	0	1	-.002	15
438			min	-2615.079	3	0	1	0	1	0	1	0	1	-.01	4
439		11	max	6459.034	1	-.159	15	0	1	0	1	0	1	-.002	15
440			min	-2615.119	3	-.677	4	0	1	0	1	0	1	-.01	4
441		12	max	6458.98	1	-.318	15	0	1	0	1	0	1	-.002	15
442			min	-2615.16	3	-1.355	4	0	1	0	1	0	1	-.009	4
443		13	max	6458.926	1	-.478	15	0	1	0	1	0	1	-.002	15
444			min	-2615.2	3	-2.032	4	0	1	0	1	0	1	-.009	4
445		14	max	6458.872	1	-.637	15	0	1	0	1	0	1	-.002	15
446			min	-2615.241	3	-2.709	4	0	1	0	1	0	1	-.008	4
447		15	max	6458.818	1	-.796	15	0	1	0	1	0	1	-.002	15
448			min	-2615.281	3	-3.386	4	0	1	0	1	0	1	-.007	4
449		16	max	6458.764	1	-.955	15	0	1	0	1	0	1	-.001	15
450			min	-2615.322	3	-4.064	4	0	1	0	1	0	1	-.005	4
451		17	max	6458.71	1	-1.114	15	0	1	0	1	0	1	0	15
452			min	-2615.362	3	-4.741	4	0	1	0	1	0	1	-.004	4
453		18	max	6458.656	1	-1.274	15	0	1	0	1	0	1	0	15
454			min	-2615.403	3	-5.418	4	0	1	0	1	0	1	-.002	4
455		19	max	6458.602	1	-1.433	15	0	1	0	1	0	1	0	1
456			min	-2615.443	3	-6.095	4	0	1	0	1	0	1	0	1
457	M9	1	max	2742.169	1	6.095	4	9.211	3	.067	1	0	3	0	1
458			min	-911.666	3	1.433	15	-28.5	1	-.023	3	-.003	1	0	1
459		2	max	2742.115	1	5.418	4	9.211	3	.067	1	.004	3	0	15
460			min	-911.707	3	1.274	15	-28.5	1	-.023	3	-.013	1	-.002	4
461		3	max	2742.061	1	4.741	4	9.211	3	.067	1	.008	3	0	15
462			min	-911.747	3	1.114	15	-28.5	1	-.023	3	-.023	1	-.004	4
463		4	max	2742.007	1	4.064	4	9.211	3	.067	1	.011	3	-.001	15
464			min	-911.788	3	.955	15	-28.5	1	-.023	3	-.034	1	-.005	4
465		5	max	2741.953	1	3.386	4	9.211	3	.067	1	.014	3	-.002	15
466			min	-911.828	3	.796	15	-28.5	1	-.023	3	-.044	1	-.007	4
467		6	max	2741.899	1	2.709	4	9.211	3	.067	1	.017	3	-.002	15
468			min	-911.869	3	.637	15	-28.5	1	-.023	3	-.054	1	-.008	4
469		7	max	2741.845	1	2.032	4	9.211	3	.067	1	.021	3	-.002	15
470			min	-911.909	3	.478	15	-28.5	1	-.023	3	-.064	1	-.009	4
471		8	max	2741.791	1	1.355	4	9.211	3	.067	1	.024	3	-.002	15
472			min	-911.95	3	.318	15	-28.5	1	-.023	3	-.074	1	-.009	4
473		9	max	2741.737	1	.677	4	9.211	3	.067	1	.027	3	-.002	15
474			min	-911.99	3	.159	15	-28.5	1	-.023	3	-.085	1	-.01	4
475		10	max	2741.683	1	0	1	9.211	3	.067	1	.031	3	-.002	15
476			min	-912.031	3	0	1	-28.5	1	-.023	3	-.095	1	-.01	4
477		11	max	2741.629	1	-.159	15	9.211	3	.067	1	.034	3	-.002	15
478			min	-912.071	3	-.677	4	-28.5	1	-.023	3	-.105	1	-.01	4
479		12	max	2741.575	1	-.318	15	9.211	3	.067	1	.037	3	-.002	15
480			min	-912.112	3	-1.355	4	-28.5	1	-.023	3	-.115	1	-.009	4
481		13	max	2741.521	1	-.478	15	9.211	3	.067	1	.04	3	-.002	15
482			min	-912.152	3	-2.032	4	-28.5	1	-.023	3	-.125	1	-.009	4
483		14	max	2741.467	1	-.637	15	9.211	3	.067	1	.044	3	-.002	15
484			min	-912.193	3	-2.709	4	-28.5	1	-.023	3	-.136	1	-.008	4
485		15	max	2741.413	1	-.796	15	9.211	3	.067	1	.047	3	-.002	15
486			min	-912.233	3	-3.386	4	-28.5	1	-.023	3	-.146	1	-.007	4
487		16	max	2741.359	1	-.955	15	9.211	3	.067	1	.05	3	-.001	15
488			min	-912.274	3	-4.064	4	-28.5	1	-.023	3	-.156	1	-.005	4

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
489		17	max	2741.305	1	-1.114	15	9.211	3	.067	1	.054	3	0	15
490			min	-912.314	3	-4.741	4	-28.5	1	-.023	3	-.166	1	-.004	4
491		18	max	2741.251	1	-1.274	15	9.211	3	.067	1	.057	3	0	15
492			min	-912.355	3	-5.418	4	-28.5	1	-.023	3	-.176	1	-.002	4
493		19	max	2741.197	1	-1.433	15	9.211	3	.067	1	.06	3	0	1
494			min	-912.395	3	-6.095	4	-28.5	1	-.023	3	-.186	1	0	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M1	1	max	.062	3	.264	3	.012	1	8.56e-3	3	2552.017	15	NC	1
2			min	-.507	1	-1.459	1	-.001	3	-2.758e-2	1	76.414	1	NC	1
3		2	max	.062	3	.223	3	0	3	8.254e-3	3	2787.525	15	NC	2
4			min	-.507	1	-1.29	1	-.008	1	-2.633e-2	1	84.063	1	7360.348	1
5		3	max	.062	3	.184	3	.002	3	7.655e-3	3	3486.841	12	NC	3
6			min	-.507	1	-1.124	1	-.019	1	-2.389e-2	1	93.207	1	5010.831	1
7		4	max	.062	3	.147	3	.002	3	7.056e-3	3	7309.662	12	NC	3
8			min	-.507	1	-.969	1	-.021	1	-2.145e-2	1	103.829	1	4847.427	1
9		5	max	.062	3	.117	3	.003	3	6.624e-3	3	NC	3	NC	3
10			min	-.507	1	-.83	1	-.019	1	-1.951e-2	1	115.608	1	5513.508	1
11		6	max	.062	3	.093	3	.002	3	6.619e-3	3	NC	12	NC	2
12			min	-.505	1	-.71	1	-.012	1	-1.887e-2	1	128.135	1	7947.583	1
13		7	max	.061	3	.074	3	.001	3	6.614e-3	3	6051.518	12	NC	1
14			min	-.504	1	-.603	1	-.004	1	-1.823e-2	1	141.797	1	NC	1
15		8	max	.061	3	.058	3	0	1	6.609e-3	3	5003.483	15	NC	1
16			min	-.503	1	-.504	1	0	10	-1.758e-2	1	157.394	1	NC	1
17		9	max	.061	3	.043	3	0	10	6.834e-3	3	5586.384	15	NC	1
18			min	-.502	1	-.407	1	0	3	-1.632e-2	1	176.486	1	NC	1
19		10	max	.06	3	.027	3	.001	1	7.278e-3	3	6337.471	15	NC	1
20			min	-.501	1	-.308	1	0	3	-1.446e-2	1	201.157	1	NC	1
21		11	max	.06	3	.012	3	.001	1	7.721e-3	3	7341.741	15	NC	1
22			min	-.5	1	-.209	1	0	3	-1.261e-2	1	234.254	1	NC	1
23		12	max	.06	3	-.003	12	.003	3	7.003e-3	3	8755.538	15	NC	1
24			min	-.499	1	-.108	1	-.005	1	-1.021e-2	1	281.127	1	NC	1
25		13	max	.059	3	0	15	.006	3	5.052e-3	3	NC	15	NC	1
26			min	-.497	1	-.018	3	-.007	1	-7.217e-3	1	350.576	1	NC	1
27		14	max	.059	3	.086	1	.009	3	3.102e-3	3	NC	15	NC	1
28			min	-.496	1	-.025	3	-.005	1	-4.227e-3	1	456.965	1	NC	1
29		15	max	.059	3	.17	1	.009	3	1.151e-3	3	NC	5	NC	1
30			min	-.495	1	-.021	3	-.001	2	-1.238e-3	1	626.136	1	NC	1
31		16	max	.059	3	.239	1	.009	1	3.155e-3	3	NC	5	NC	2
32			min	-.495	1	-.002	3	0	15	-2.26e-3	1	901.376	1	9265.37	1
33		17	max	.059	3	.297	1	.012	1	5.623e-3	3	NC	5	NC	2
34			min	-.495	1	.009	15	0	15	-3.752e-3	1	1423.641	1	7273.807	1
35		18	max	.059	3	.348	1	.006	1	8.091e-3	3	NC	4	NC	2
36			min	-.495	1	.011	15	0	15	-5.245e-3	1	2910.694	1	9406.51	1
37		19	max	.059	3	.396	1	0	12	9.349e-3	3	NC	1	NC	1
38			min	-.495	1	.013	15	-.01	1	-6.006e-3	1	NC	1	NC	1
39	M4	1	max	.141	3	.592	3	0	1	0	1	1577.438	15	NC	1
40			min	-.918	1	-2.713	1	0	1	0	1	43.284	1	NC	1
41		2	max	.141	3	.506	3	0	1	0	1	1735.86	15	NC	1
42			min	-.918	1	-2.399	1	0	1	0	1	47.877	1	NC	1
43		3	max	.141	3	.422	3	0	1	0	1	1925.9	15	NC	1
44			min	-.917	1	-2.091	1	0	1	0	1	53.44	1	NC	1
45		4	max	.141	3	.347	3	0	1	0	1	3698.592	12	NC	1
46			min	-.917	1	-1.803	1	0	1	0	1	59.941	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
47		5	max	.141	3	.285	3	0	1	0	1	NC	3	NC	1
48			min	-.917	1	-1.551	1	0	1	0	1	67.101	1	NC	1
49		6	max	.14	3	.241	3	0	1	0	1	5891.582	12	NC	1
50			min	-.914	1	-1.34	1	0	1	0	1	74.555	1	NC	1
51		7	max	.139	3	.206	3	0	1	0	1	3205.482	12	NC	1
52			min	-.912	1	-1.155	1	0	1	0	1	82.585	1	NC	1
53		8	max	.138	3	.176	3	0	1	0	1	3246.358	15	NC	1
54			min	-.909	1	-.982	1	0	1	0	1	91.835	1	NC	1
55		9	max	.137	3	.144	3	0	1	0	1	3659.142	15	NC	1
56			min	-.907	1	-.806	1	0	1	0	1	103.641	1	NC	1
57		10	max	.136	3	.108	3	0	1	0	1	4224.323	15	NC	1
58			min	-.904	1	-.621	1	0	1	0	1	119.893	1	NC	1
59		11	max	.135	3	.067	3	0	1	0	1	5034.371	15	NC	1
60			min	-.902	1	-.428	1	0	1	0	1	143.31	1	NC	1
61		12	max	.134	3	.021	3	0	1	0	1	6282.948	15	NC	1
62			min	-.899	1	-.227	1	0	1	0	1	179.673	1	NC	1
63		13	max	.133	3	0	15	0	1	0	1	8347.561	15	NC	1
64			min	-.896	1	-.031	2	0	1	0	1	240.442	1	NC	1
65		14	max	.133	3	.155	1	0	1	0	1	NC	15	NC	1
66			min	-.894	1	-.049	3	0	1	0	1	348.502	1	NC	1
67		15	max	.132	3	.305	1	0	1	0	1	NC	5	NC	1
68			min	-.891	1	-.047	3	0	1	0	1	442.32	3	NC	1
69		16	max	.132	3	.409	1	0	1	0	1	NC	5	NC	1
70			min	-.891	1	-.003	3	0	1	0	1	513.236	3	NC	1
71		17	max	.132	3	.477	1	0	1	0	1	NC	5	NC	1
72			min	-.891	1	.014	15	0	1	0	1	712.024	3	NC	1
73		18	max	.132	3	.523	1	0	1	0	1	NC	4	NC	1
74			min	-.891	1	.015	15	0	1	0	1	1382.651	3	NC	1
75		19	max	.132	3	.561	1	0	1	0	1	NC	1	NC	1
76			min	-.891	1	.016	15	0	1	0	1	NC	1	NC	1
77	M7	1	max	.062	3	.264	3	.001	3	2.758e-2	1	2552.017	15	NC	1
78			min	-.507	1	-1.459	1	-.012	1	-8.56e-3	3	76.414	1	NC	1
79		2	max	.062	3	.223	3	.008	1	2.633e-2	1	2787.525	15	NC	2
80			min	-.507	1	-1.29	1	0	3	-8.254e-3	3	84.063	1	7360.348	1
81		3	max	.062	3	.184	3	.019	1	2.389e-2	1	3486.841	12	NC	3
82			min	-.507	1	-1.124	1	-.002	3	-7.655e-3	3	93.207	1	5010.831	1
83		4	max	.062	3	.147	3	.021	1	2.145e-2	1	7309.662	12	NC	3
84			min	-.507	1	-.969	1	-.002	3	-7.056e-3	3	103.829	1	4847.427	1
85		5	max	.062	3	.117	3	.019	1	1.951e-2	1	NC	3	NC	3
86			min	-.507	1	-.83	1	-.003	3	-6.624e-3	3	115.608	1	5513.508	1
87		6	max	.062	3	.093	3	.012	1	1.887e-2	1	NC	12	NC	2
88			min	-.505	1	-.71	1	-.002	3	-6.619e-3	3	128.135	1	7947.583	1
89		7	max	.061	3	.074	3	.004	1	1.823e-2	1	6051.518	12	NC	1
90			min	-.504	1	-.603	1	-.001	3	-6.614e-3	3	141.797	1	NC	1
91		8	max	.061	3	.058	3	0	10	1.758e-2	1	5003.483	15	NC	1
92			min	-.503	1	-.504	1	0	1	-6.609e-3	3	157.394	1	NC	1
93		9	max	.061	3	.043	3	0	3	1.632e-2	1	5586.384	15	NC	1
94			min	-.502	1	-.407	1	0	10	-6.834e-3	3	176.486	1	NC	1
95		10	max	.06	3	.027	3	0	3	1.446e-2	1	6337.471	15	NC	1
96			min	-.501	1	-.308	1	-.001	1	-7.278e-3	3	201.157	1	NC	1
97		11	max	.06	3	.012	3	0	3	1.261e-2	1	7341.741	15	NC	1
98			min	-.5	1	-.209	1	-.001	1	-7.721e-3	3	234.254	1	NC	1
99		12	max	.06	3	-.003	12	.005	1	1.021e-2	1	8755.538	15	NC	1
100			min	-.499	1	-.108	1	-.003	3	-7.003e-3	3	281.127	1	NC	1
101		13	max	.059	3	0	15	.007	1	7.217e-3	1	NC	15	NC	1
102			min	-.497	1	-.018	3	-.006	3	-5.052e-3	3	350.576	1	NC	1
103		14	max	.059	3	.086	1	.005	1	4.227e-3	1	NC	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
104			min	-.496	1	-.025	3	-.009	3	-3.102e-3	3	456.965	1	NC	1
105		15	max	.059	3	.17	1	.001	2	1.238e-3	1	NC	5	NC	1
106			min	-.495	1	-.021	3	-.009	3	-1.151e-3	3	626.136	1	NC	1
107		16	max	.059	3	.239	1	0	15	2.26e-3	1	NC	5	NC	2
108			min	-.495	1	-.002	3	-.009	1	-3.155e-3	3	901.376	1	9265.37	1
109		17	max	.059	3	.297	1	0	15	3.752e-3	1	NC	5	NC	2
110			min	-.495	1	.009	15	-.012	1	-5.623e-3	3	1423.641	1	7273.807	1
111		18	max	.059	3	.348	1	0	15	5.245e-3	1	NC	4	NC	2
112			min	-.495	1	.011	15	-.006	1	-8.091e-3	3	2910.694	1	9406.51	1
113		19	max	.059	3	.396	1	.01	1	6.006e-3	1	NC	1	NC	1
114			min	-.495	1	.013	15	0	12	-9.349e-3	3	NC	1	NC	1
115	M10	1	max	.001	1	.372	1	.495	1	6.202e-3	1	NC	1	NC	1
116			min	0	3	.012	15	-.059	3	2.089e-4	15	NC	1	NC	1
117		2	max	0	1	.309	1	.539	1	6.068e-3	1	NC	4	NC	3
118			min	0	3	.01	15	-.059	3	2.03e-4	15	1889.969	3	4409.596	1
119		3	max	0	1	.282	3	.607	1	6.896e-3	3	NC	5	NC	3
120			min	0	3	.009	15	-.064	3	1.971e-4	15	991.817	3	1716.147	1
121		4	max	0	1	.349	3	.684	1	7.762e-3	3	NC	5	NC	3
122			min	0	3	.008	15	-.073	3	1.912e-4	15	736.969	3	1018.318	1
123		5	max	0	1	.382	3	.756	1	8.628e-3	3	NC	5	NC	5
124			min	0	3	.008	15	-.084	3	1.853e-4	15	653.46	3	735.615	1
125		6	max	0	1	.38	3	.816	1	9.495e-3	3	NC	5	NC	5
126			min	0	3	.009	15	-.096	3	1.795e-4	15	658.132	3	598.793	1
127		7	max	0	1	.359	1	.858	1	1.036e-2	3	NC	1	NC	5
128			min	0	3	.011	15	-.109	3	1.736e-4	15	740.17	3	529.251	1
129		8	max	0	1	.44	1	.882	1	1.123e-2	3	NC	4	NC	5
130			min	0	3	.013	15	-.12	3	1.677e-4	15	919.493	3	496.585	1
131		9	max	0	1	.511	1	.89	1	1.209e-2	3	NC	5	NC	5
132			min	0	3	.015	15	-.128	3	1.618e-4	15	1208.872	3	485.58	1
133		10	max	0	1	.542	1	.891	1	1.296e-2	3	NC	5	NC	5
134			min	0	1	.016	15	-.132	3	1.559e-4	15	1130.824	1	484.657	1
135		11	max	0	3	.511	1	.89	1	1.209e-2	3	NC	5	NC	5
136			min	0	1	.015	15	-.128	3	1.618e-4	15	1208.872	3	485.58	1
137		12	max	0	3	.44	1	.882	1	1.123e-2	3	NC	4	NC	5
138			min	0	1	.013	15	-.12	3	1.677e-4	15	919.493	3	496.585	1
139		13	max	0	3	.359	1	.858	1	1.036e-2	3	NC	1	NC	5
140			min	0	1	.011	15	-.109	3	1.736e-4	15	740.17	3	529.251	1
141		14	max	0	3	.38	3	.816	1	9.495e-3	3	NC	5	NC	5
142			min	0	1	.009	15	-.096	3	1.795e-4	15	658.132	3	598.793	1
143		15	max	0	3	.382	3	.756	1	8.628e-3	3	NC	5	NC	5
144			min	0	1	.008	15	-.084	3	1.853e-4	15	653.46	3	735.615	1
145		16	max	0	3	.349	3	.684	1	7.762e-3	3	NC	5	NC	3
146			min	0	1	.008	15	-.073	3	1.912e-4	15	736.969	3	1018.318	1
147		17	max	0	3	.282	3	.607	1	6.896e-3	3	NC	5	NC	3
148			min	0	1	.009	15	-.064	3	1.971e-4	15	991.817	3	1716.147	1
149		18	max	0	3	.309	1	.539	1	6.068e-3	1	NC	4	NC	3
150			min	0	1	.01	15	-.059	3	2.03e-4	15	1889.969	3	4409.596	1
151		19	max	0	3	.372	1	.495	1	6.202e-3	1	NC	1	NC	1
152			min	-.001	1	.012	15	-.059	3	2.089e-4	15	NC	1	NC	1
153	M11	1	max	.002	1	.004	3	.499	1	1.28e-2	1	NC	1	NC	1
154			min	0	3	-.157	1	-.06	3	-1.989e-3	3	NC	1	NC	1
155		2	max	.001	1	.09	3	.532	1	1.42e-2	1	NC	5	NC	3
156			min	0	3	-.28	1	-.065	3	-2.402e-3	3	1562.575	1	5853.801	1
157		3	max	.001	1	.167	3	.595	1	1.559e-2	1	NC	5	NC	3
158			min	0	3	-.387	1	-.072	3	-2.815e-3	3	835.611	1	2004.448	1
159		4	max	.001	1	.22	3	.671	1	1.698e-2	1	NC	5	NC	5
160			min	0	3	-.463	1	-.082	3	-3.228e-3	3	628.128	1	1120.21	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
161		5	max	0	1	.239	3	.745	1	1.838e-2	1	NC	5	NC	5
162			min	0	3	-.5	1	-.092	3	-3.641e-3	3	560.279	1	780.529	1
163		6	max	0	1	.225	3	.809	1	1.977e-2	1	NC	5	NC	5
164			min	0	3	-.497	1	-.104	3	-4.054e-3	3	564.576	1	619.666	1
165		7	max	0	1	.183	3	.856	1	2.117e-2	1	NC	5	NC	5
166			min	0	3	-.461	1	-.115	3	-4.467e-3	3	631.073	1	537.545	1
167		8	max	0	1	.125	3	.885	1	2.256e-2	1	NC	5	NC	5
168			min	0	3	-.406	1	-.125	3	-4.88e-3	3	771.949	1	497.24	1
169		9	max	0	1	.069	3	.898	1	2.396e-2	1	NC	5	NC	5
170			min	0	3	-.351	1	-.132	3	-5.293e-3	3	988.726	1	481.489	1
171		10	max	0	1	.044	3	.9	1	2.535e-2	1	NC	5	NC	5
172			min	0	1	-.326	1	-.135	3	-5.706e-3	3	1139.683	1	478.724	1
173		11	max	0	3	.069	3	.898	1	2.396e-2	1	NC	5	NC	5
174			min	0	1	-.351	1	-.132	3	-5.293e-3	3	988.726	1	481.489	1
175		12	max	0	3	.125	3	.885	1	2.256e-2	1	NC	5	NC	5
176			min	0	1	-.406	1	-.125	3	-4.88e-3	3	771.949	1	497.24	1
177		13	max	0	3	.183	3	.856	1	2.117e-2	1	NC	5	NC	5
178			min	0	1	-.461	1	-.115	3	-4.467e-3	3	631.073	1	537.545	1
179		14	max	0	3	.225	3	.809	1	1.977e-2	1	NC	5	NC	5
180			min	0	1	-.497	1	-.104	3	-4.054e-3	3	564.576	1	619.666	1
181		15	max	0	3	.239	3	.745	1	1.838e-2	1	NC	5	NC	5
182			min	0	1	-.5	1	-.092	3	-3.641e-3	3	560.279	1	780.529	1
183		16	max	0	3	.22	3	.671	1	1.698e-2	1	NC	5	NC	5
184			min	-.001	1	-.463	1	-.082	3	-3.228e-3	3	628.128	1	1120.21	1
185		17	max	0	3	.167	3	.595	1	1.559e-2	1	NC	5	NC	3
186			min	-.001	1	-.387	1	-.072	3	-2.815e-3	3	835.611	1	2004.448	1
187		18	max	0	3	.09	3	.532	1	1.42e-2	1	NC	5	NC	3
188			min	-.001	1	-.28	1	-.065	3	-2.402e-3	3	1562.575	1	5853.801	1
189		19	max	0	3	.004	3	.499	1	1.28e-2	1	NC	1	NC	1
190			min	-.002	1	-.157	1	-.06	3	-1.989e-3	3	NC	1	NC	1
191	M12	1	max	0	3	.051	3	.503	1	1.24e-2	1	NC	1	NC	1
192			min	0	1	-.457	1	-.061	3	-1.957e-3	3	NC	1	NC	1
193		2	max	0	3	.118	3	.53	1	1.35e-2	1	NC	5	NC	2
194			min	0	1	-.639	1	-.062	3	-2.191e-3	3	1053.402	1	6946.727	1
195		3	max	0	3	.175	3	.591	1	1.461e-2	1	NC	5	NC	3
196			min	0	1	-.802	1	-.068	3	-2.426e-3	3	556.636	1	2177.097	1
197		4	max	0	3	.215	3	.666	1	1.572e-2	1	NC	5	NC	3
198			min	0	1	-.927	1	-.077	3	-2.66e-3	3	408.615	1	1174.141	1
199		5	max	0	3	.235	3	.742	1	1.682e-2	1	NC	15	NC	5
200			min	0	1	-1.004	1	-.088	3	-2.895e-3	3	350.898	1	801.897	1
201		6	max	0	3	.236	3	.808	1	1.793e-2	1	NC	15	NC	5
202			min	0	1	-1.032	1	-.101	3	-3.13e-3	3	333.92	1	628.196	1
203		7	max	0	3	.221	3	.859	1	1.904e-2	1	NC	15	NC	5
204			min	0	1	-1.017	1	-.114	3	-3.364e-3	3	343.044	1	539.653	1
205		8	max	0	3	.197	3	.89	1	2.014e-2	1	NC	15	NC	5
206			min	0	1	-.973	1	-.126	3	-3.599e-3	3	372.242	1	495.552	1
207		9	max	0	3	.173	3	.905	1	2.125e-2	1	NC	5	NC	5
208			min	0	1	-.923	1	-.134	3	-3.833e-3	3	412.071	1	477.464	1
209		10	max	0	1	.161	3	.908	1	2.236e-2	1	NC	5	NC	5
210			min	0	1	-.898	1	-.138	3	-4.068e-3	3	435.428	1	473.791	1
211		11	max	0	1	.173	3	.905	1	2.125e-2	1	NC	5	NC	5
212			min	0	3	-.923	1	-.134	3	-3.833e-3	3	412.071	1	477.464	1
213		12	max	0	1	.197	3	.89	1	2.014e-2	1	NC	15	NC	5
214			min	0	3	-.973	1	-.126	3	-3.599e-3	3	372.242	1	495.552	1
215		13	max	0	1	.221	3	.859	1	1.904e-2	1	NC	15	NC	5
216			min	0	3	-1.017	1	-.114	3	-3.364e-3	3	343.044	1	539.653	1
217		14	max	0	1	.236	3	.808	1	1.793e-2	1	NC	15	NC	5

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
218			min	0	3	-1.032	1	-.101	3	-3.13e-3	3	333.92	1	628.196	1
219		15	max	0	1	.235	3	.742	1	1.682e-2	1	NC	15	NC	5
220			min	0	3	-1.004	1	-.088	3	-2.895e-3	3	350.898	1	801.897	1
221		16	max	0	1	.215	3	.666	1	1.572e-2	1	NC	5	NC	3
222			min	0	3	-.927	1	-.077	3	-2.66e-3	3	408.615	1	1174.141	1
223		17	max	0	1	.175	3	.591	1	1.461e-2	1	NC	5	NC	3
224			min	0	3	-.802	1	-.068	3	-2.426e-3	3	556.636	1	2177.097	1
225		18	max	0	1	.118	3	.53	1	1.35e-2	1	NC	5	NC	2
226			min	0	3	-.639	1	-.062	3	-2.191e-3	3	1053.402	1	6946.727	1
227		19	max	0	1	.051	3	.503	1	1.24e-2	1	NC	1	NC	1
228			min	0	3	-.457	1	-.061	3	-1.957e-3	3	NC	1	NC	1
229	M13	1	max	0	3	.244	3	.507	1	2.141e-2	1	NC	1	NC	1
230			min	-.001	1	-1.376	1	-.062	3	-5.175e-3	3	NC	1	NC	1
231		2	max	0	3	.335	3	.556	1	2.346e-2	1	NC	5	NC	3
232			min	0	1	-1.671	1	-.066	3	-5.814e-3	3	651.572	1	3962.842	1
233		3	max	0	3	.418	3	.628	1	2.551e-2	1	NC	15	NC	3
234			min	0	1	-1.948	1	-.073	3	-6.454e-3	3	335.819	1	1593.991	1
235		4	max	0	3	.487	3	.707	1	2.755e-2	1	9803.787	15	NC	5
236			min	0	1	-2.185	1	-.083	3	-7.093e-3	3	237.322	1	961.348	1
237		5	max	0	3	.536	3	.781	1	2.96e-2	1	7974.767	15	NC	5
238			min	0	1	-2.368	1	-.095	3	-7.732e-3	3	193.445	1	701.01	1
239		6	max	0	3	.564	3	.842	1	3.164e-2	1	7071.9	15	NC	5
240			min	0	1	-2.492	1	-.107	3	-8.372e-3	3	171.983	1	573.939	1
241		7	max	0	3	.573	3	.884	1	3.369e-2	1	6654.515	15	NC	5
242			min	0	1	-2.559	1	-.119	3	-9.011e-3	3	162.314	1	509.108	1
243		8	max	0	3	.568	3	.908	1	3.574e-2	1	6525.541	15	NC	5
244			min	0	1	-2.578	1	-.13	3	-9.65e-3	3	159.668	1	478.674	1
245		9	max	0	3	.557	3	.917	1	3.778e-2	1	6555.151	15	NC	5
246			min	0	1	-2.57	1	-.138	3	-1.029e-2	3	160.834	1	468.513	1
247		10	max	0	1	.55	3	.918	1	3.983e-2	1	6603.709	15	NC	5
248			min	0	1	-2.559	1	-.141	3	-1.093e-2	3	162.229	1	467.725	1
249		11	max	0	1	.557	3	.917	1	3.778e-2	1	6555.151	15	NC	5
250			min	0	3	-2.57	1	-.138	3	-1.029e-2	3	160.834	1	468.513	1
251		12	max	0	1	.568	3	.908	1	3.574e-2	1	6525.541	15	NC	5
252			min	0	3	-2.578	1	-.13	3	-9.65e-3	3	159.668	1	478.674	1
253		13	max	0	1	.573	3	.884	1	3.369e-2	1	6654.515	15	NC	5
254			min	0	3	-2.559	1	-.119	3	-9.011e-3	3	162.314	1	509.108	1
255		14	max	0	1	.564	3	.842	1	3.164e-2	1	7071.9	15	NC	5
256			min	0	3	-2.492	1	-.107	3	-8.372e-3	3	171.983	1	573.939	1
257		15	max	0	1	.536	3	.781	1	2.96e-2	1	7974.767	15	NC	5
258			min	0	3	-2.368	1	-.095	3	-7.732e-3	3	193.445	1	701.01	1
259		16	max	0	1	.487	3	.707	1	2.755e-2	1	9803.787	15	NC	5
260			min	0	3	-2.185	1	-.083	3	-7.093e-3	3	237.322	1	961.348	1
261		17	max	0	1	.418	3	.628	1	2.551e-2	1	NC	15	NC	3
262			min	0	3	-1.948	1	-.073	3	-6.454e-3	3	335.819	1	1593.991	1
263		18	max	0	1	.335	3	.556	1	2.346e-2	1	NC	5	NC	3
264			min	0	3	-1.671	1	-.066	3	-5.814e-3	3	651.572	1	3962.842	1
265		19	max	.001	1	.244	3	.507	1	2.141e-2	1	NC	1	NC	1
266			min	0	3	-1.376	1	-.062	3	-5.175e-3	3	NC	1	NC	1
267	M2	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
268			min	0	1	0	1	0	1	0	1	NC	1	NC	1
269		2	max	0	3	0	3	0	3	5.527e-4	1	NC	1	NC	1
270			min	0	1	-.002	1	0	1	-1.853e-4	3	NC	1	NC	1
271		3	max	0	3	0	3	0	3	1.105e-3	1	NC	2	NC	1
272			min	0	1	-.007	1	0	1	-3.706e-4	3	8224.782	1	NC	1
273		4	max	0	3	0	3	0	3	1.658e-3	1	NC	3	NC	1
274			min	0	1	-.017	1	0	1	-5.559e-4	3	3662.571	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
275		5	max	0	3	.002	3	0	3	2.211e-3	1	NC	3	NC	1
276			min	0	1	-.029	1	-.002	1	-7.412e-4	3	2063.034	1	NC	1
277		6	max	0	3	.003	3	0	3	2.763e-3	1	NC	3	NC	1
278			min	0	1	-.046	1	-.002	1	-9.265e-4	3	1321.819	1	NC	1
279		7	max	0	3	.005	3	.001	3	3.316e-3	1	NC	3	NC	1
280			min	0	1	-.066	1	-.003	1	-1.112e-3	3	918.818	1	NC	1
281		8	max	0	3	.007	3	.001	3	3.869e-3	1	NC	5	NC	1
282			min	0	1	-.09	1	-.004	1	-1.297e-3	3	675.686	1	NC	1
283		9	max	0	3	.01	3	.001	3	3.752e-3	1	NC	5	NC	1
284			min	0	1	-.117	1	-.004	1	-1.244e-3	3	516.812	1	NC	1
285		10	max	0	3	.014	3	.001	3	3.241e-3	1	NC	15	NC	1
286			min	-.001	1	-.149	1	-.005	1	-1.051e-3	3	408.473	1	NC	1
287		11	max	0	3	.018	3	.001	3	2.731e-3	1	NC	15	NC	1
288			min	-.001	1	-.183	1	-.005	1	-8.58e-4	3	332.021	1	NC	1
289		12	max	0	3	.023	3	0	3	2.22e-3	1	8965.103	15	NC	1
290			min	-.001	1	-.22	1	-.006	1	-6.65e-4	3	276.21	1	NC	1
291		13	max	0	3	.027	3	0	3	1.71e-3	1	7614.434	15	NC	1
292			min	-.001	1	-.259	1	-.006	1	-4.72e-4	3	234.288	1	NC	1
293		14	max	0	3	.033	3	0	15	1.235e-3	2	6573.391	15	NC	1
294			min	-.001	1	-.3	1	-.006	1	-2.789e-4	3	202.03	1	NC	1
295		15	max	0	3	.038	3	0	15	7.952e-4	2	5754.729	15	NC	1
296			min	-.002	1	-.343	1	-.006	1	-8.588e-5	3	176.702	1	NC	1
297		16	max	0	3	.044	3	0	15	3.553e-4	2	5099.757	15	NC	1
298			min	-.002	1	-.388	1	-.005	1	-1.519e-7	4	156.464	1	NC	1
299		17	max	0	3	.05	3	0	15	3.002e-4	3	4568.075	15	NC	1
300			min	-.002	1	-.433	1	-.005	1	-3.318e-4	1	140.056	1	NC	1
301		18	max	.001	3	.056	3	0	10	4.932e-4	3	4131.008	15	NC	1
302			min	-.002	1	-.479	1	-.006	3	-8.423e-4	1	126.582	1	9374.894	3
303		19	max	.001	3	.062	3	0	10	6.863e-4	3	3767.882	15	NC	1
304			min	-.002	1	-.526	1	-.009	3	-1.353e-3	1	115.398	1	6883.25	3
305	M5	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
306			min	0	1	0	1	0	1	0	1	NC	1	NC	1
307		2	max	0	3	0	12	0	1	0	1	NC	1	NC	1
308			min	0	1	-.003	1	0	1	0	1	NC	1	NC	1
309		3	max	0	3	0	3	0	1	0	1	NC	3	NC	1
310			min	0	1	-.012	1	0	1	0	1	5124.699	1	NC	1
311		4	max	0	3	.001	3	0	1	0	1	NC	3	NC	1
312			min	0	1	-.027	1	0	1	0	1	2242.735	1	NC	1
313		5	max	0	3	.003	3	0	1	0	1	NC	3	NC	1
314			min	-.001	1	-.049	1	0	1	0	1	1247.409	1	NC	1
315		6	max	0	3	.005	3	0	1	0	1	NC	3	NC	1
316			min	-.002	1	-.077	1	0	1	0	1	790.709	1	NC	1
317		7	max	.001	3	.009	3	0	1	0	1	NC	5	NC	1
318			min	-.002	1	-.111	1	0	1	0	1	544.303	1	NC	1
319		8	max	.001	3	.013	3	0	1	0	1	NC	15	NC	1
320			min	-.002	1	-.153	1	0	1	0	1	396.62	1	NC	1
321		9	max	.001	3	.02	3	0	1	0	1	NC	15	NC	1
322			min	-.002	1	-.202	1	0	1	0	1	300.494	1	NC	1
323		10	max	.002	3	.028	3	0	1	0	1	8221.397	15	NC	1
324			min	-.003	1	-.258	1	0	1	0	1	235.441	1	NC	1
325		11	max	.002	3	.037	3	0	1	0	1	6655.949	15	NC	1
326			min	-.003	1	-.319	1	0	1	0	1	189.973	1	NC	1
327		12	max	.002	3	.047	3	0	1	0	1	5518.508	15	NC	1
328			min	-.003	1	-.386	1	0	1	0	1	157.067	1	NC	1
329		13	max	.002	3	.059	3	0	1	0	1	4667.669	15	NC	1
330			min	-.003	1	-.458	1	0	1	0	1	132.539	1	NC	1
331		14	max	.002	3	.071	3	0	1	0	1	4015.387	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
332			min	-.004	1	-.533	1	0	1	0	1	113.793	1	NC	1
333		15	max	.002	3	.084	3	0	1	0	1	3504.867	15	NC	1
334			min	-.004	1	-.612	1	0	1	0	1	99.161	1	NC	1
335		16	max	.003	3	.097	3	0	1	0	1	3098.135	15	NC	1
336			min	-.004	1	-.693	1	0	1	0	1	87.53	1	NC	1
337		17	max	.003	3	.111	3	0	1	0	1	2769.198	15	NC	1
338			min	-.005	1	-.776	1	0	1	0	1	78.144	1	NC	1
339		18	max	.003	3	.125	3	0	1	0	1	2499.705	15	NC	1
340			min	-.005	1	-.861	1	0	1	0	1	70.469	1	NC	1
341		19	max	.003	3	.139	3	0	1	0	1	2276.487	15	NC	1
342			min	-.005	1	-.946	1	0	1	0	1	64.122	1	NC	1
343	M8	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
344			min	0	1	0	1	0	1	0	1	NC	1	NC	1
345		2	max	0	3	0	3	0	1	1.853e-4	3	NC	1	NC	1
346			min	0	1	-.002	1	0	3	-5.527e-4	1	NC	1	NC	1
347		3	max	0	3	0	3	0	1	3.706e-4	3	NC	2	NC	1
348			min	0	1	-.007	1	0	3	-1.105e-3	1	8224.782	1	NC	1
349		4	max	0	3	0	3	0	1	5.559e-4	3	NC	3	NC	1
350			min	0	1	-.017	1	0	3	-1.658e-3	1	3662.571	1	NC	1
351		5	max	0	3	.002	3	.002	1	7.412e-4	3	NC	3	NC	1
352			min	0	1	-.029	1	0	3	-2.211e-3	1	2063.034	1	NC	1
353		6	max	0	3	.003	3	.002	1	9.265e-4	3	NC	3	NC	1
354			min	0	1	-.046	1	0	3	-2.763e-3	1	1321.819	1	NC	1
355		7	max	0	3	.005	3	.003	1	1.112e-3	3	NC	3	NC	1
356			min	0	1	-.066	1	-.001	3	-3.316e-3	1	918.818	1	NC	1
357		8	max	0	3	.007	3	.004	1	1.297e-3	3	NC	5	NC	1
358			min	0	1	-.09	1	-.001	3	-3.869e-3	1	675.686	1	NC	1
359		9	max	0	3	.01	3	.004	1	1.244e-3	3	NC	5	NC	1
360			min	0	1	-.117	1	-.001	3	-3.752e-3	1	516.812	1	NC	1
361		10	max	0	3	.014	3	.005	1	1.051e-3	3	NC	15	NC	1
362			min	-.001	1	-.149	1	-.001	3	-3.241e-3	1	408.473	1	NC	1
363		11	max	0	3	.018	3	.005	1	8.58e-4	3	NC	15	NC	1
364			min	-.001	1	-.183	1	-.001	3	-2.731e-3	1	332.021	1	NC	1
365		12	max	0	3	.023	3	.006	1	6.65e-4	3	8965.103	15	NC	1
366			min	-.001	1	-.22	1	0	3	-2.22e-3	1	276.21	1	NC	1
367		13	max	0	3	.027	3	.006	1	4.72e-4	3	7614.434	15	NC	1
368			min	-.001	1	-.259	1	0	3	-1.71e-3	1	234.288	1	NC	1
369		14	max	0	3	.033	3	.006	1	2.789e-4	3	6573.391	15	NC	1
370			min	-.001	1	-.3	1	0	15	-1.235e-3	2	202.03	1	NC	1
371		15	max	0	3	.038	3	.006	1	8.588e-5	3	5754.729	15	NC	1
372			min	-.002	1	-.343	1	0	15	-7.952e-4	2	176.702	1	NC	1
373		16	max	0	3	.044	3	.005	1	1.519e-7	4	5099.757	15	NC	1
374			min	-.002	1	-.388	1	0	15	-3.553e-4	2	156.464	1	NC	1
375		17	max	0	3	.05	3	.005	1	3.318e-4	1	4568.075	15	NC	1
376			min	-.002	1	-.433	1	0	15	-3.002e-4	3	140.056	1	NC	1
377		18	max	.001	3	.056	3	.006	3	8.423e-4	1	4131.008	15	NC	1
378			min	-.002	1	-.479	1	0	10	-4.932e-4	3	126.582	1	9374.894	3
379		19	max	.001	3	.062	3	.009	3	1.353e-3	1	3767.882	15	NC	1
380			min	-.002	1	-.526	1	0	10	-6.863e-4	3	115.398	1	6883.25	3
381	M3	1	max	.099	1	.001	3	.001	3	2.749e-4	2	NC	1	NC	1
382			min	-.008	3	-.011	1	-.004	1	-1.238e-4	3	NC	1	NC	1
383		2	max	.098	1	.008	3	.007	3	1.202e-3	1	NC	1	NC	3
384			min	-.008	3	-.067	1	-.021	1	-4.5e-4	3	NC	1	4131.22	1
385		3	max	.097	1	.014	3	.013	3	2.165e-3	1	NC	1	NC	4
386			min	-.008	3	-.124	1	-.038	1	-7.762e-4	3	5881.547	3	2089.641	1
387		4	max	.095	1	.021	3	.018	3	3.129e-3	1	NC	1	NC	5
388			min	-.007	3	-.18	1	-.054	1	-1.102e-3	3	3902.66	3	1418.078	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
389		5	max	.094	1	.028	3	.023	3	4.092e-3	1	NC	1	NC	5
390			min	-.007	3	-.236	1	-.07	1	-1.429e-3	3	2908.794	3	1089.74	1
391		6	max	.093	1	.035	3	.028	3	5.055e-3	1	NC	1	NC	5
392			min	-.006	3	-.292	1	-.083	1	-1.755e-3	3	2309.469	3	899.551	1
393		7	max	.092	1	.042	3	.032	3	6.019e-3	1	NC	1	NC	5
394			min	-.006	3	-.348	1	-.095	1	-2.081e-3	3	1907.855	3	779.465	1
395		8	max	.091	1	.049	3	.035	3	6.982e-3	1	NC	5	NC	5
396			min	-.006	3	-.404	1	-.105	1	-2.407e-3	3	1619.589	3	700.697	1
397		9	max	.09	1	.056	3	.038	3	7.945e-3	1	NC	5	NC	5
398			min	-.005	3	-.459	1	-.112	1	-2.734e-3	3	1402.478	3	649.338	1
399		10	max	.089	1	.064	3	.04	3	8.909e-3	1	NC	5	NC	5
400			min	-.005	3	-.514	1	-.117	1	-3.06e-3	3	1233.063	3	618.325	1
401		11	max	.088	1	.072	3	.04	3	9.872e-3	1	NC	5	NC	5
402			min	-.005	3	-.569	1	-.119	1	-3.386e-3	3	1097.256	3	604.383	1
403		12	max	.086	1	.08	3	.04	3	1.084e-2	1	NC	5	NC	5
404			min	-.004	3	-.624	1	-.117	1	-3.712e-3	3	986.075	3	606.921	1
405		13	max	.085	1	.088	3	.038	3	1.18e-2	1	NC	1	NC	5
406			min	-.004	3	-.678	1	-.111	1	-4.039e-3	3	893.519	3	628.055	1
407		14	max	.084	1	.096	3	.035	3	1.276e-2	1	NC	1	NC	5
408			min	-.003	3	-.732	1	-.102	1	-4.365e-3	3	815.42	3	673.875	1
409		15	max	.083	1	.104	3	.031	3	1.373e-2	1	NC	1	NC	5
410			min	-.003	3	-.786	1	-.087	1	-4.691e-3	3	748.79	3	758.393	1
411		16	max	.082	1	.113	3	.025	3	1.469e-2	1	NC	1	NC	5
412			min	-.003	3	-.84	1	-.069	1	-5.017e-3	3	691.43	3	915.928	1
413		17	max	.081	1	.122	3	.018	3	1.565e-2	1	NC	1	NC	5
414			min	-.002	3	-.894	1	-.045	1	-5.343e-3	3	641.681	3	1251.105	1
415		18	max	.08	1	.13	3	.008	3	1.662e-2	1	NC	1	NC	4
416			min	-.002	3	-.947	1	-.018	2	-5.67e-3	3	598.27	3	2289.401	1
417		19	max	.079	1	.139	3	.02	1	1.758e-2	1	NC	1	NC	1
418			min	-.002	3	-1.001	1	-.003	3	-5.996e-3	3	560.204	3	NC	1
419	M6	1	max	.169	1	.003	3	0	1	0	1	NC	1	NC	1
420			min	-.015	3	-.02	1	0	1	0	1	NC	1	NC	1
421		2	max	.166	1	.02	3	0	1	0	1	NC	1	NC	1
422			min	-.014	3	-.123	1	0	1	0	1	4498.019	3	NC	1
423		3	max	.164	1	.037	3	0	1	0	1	NC	1	NC	1
424			min	-.013	3	-.226	1	0	1	0	1	2246.473	3	NC	1
425		4	max	.161	1	.055	3	0	1	0	1	NC	1	NC	1
426			min	-.012	3	-.33	1	0	1	0	1	1494.96	3	NC	1
427		5	max	.158	1	.072	3	0	1	0	1	NC	1	NC	1
428			min	-.011	3	-.433	1	0	1	0	1	1118.539	3	NC	1
429		6	max	.156	1	.089	3	0	1	0	1	NC	1	NC	1
430			min	-.01	3	-.536	1	0	1	0	1	892.222	3	NC	1
431		7	max	.153	1	.107	3	0	1	0	1	NC	1	NC	1
432			min	-.009	3	-.639	1	0	1	0	1	741.012	3	NC	1
433		8	max	.15	1	.125	3	0	1	0	1	NC	5	NC	1
434			min	-.008	3	-.741	1	0	1	0	1	632.768	3	NC	1
435		9	max	.148	1	.143	3	0	1	0	1	NC	5	NC	1
436			min	-.007	3	-.843	1	0	1	0	1	551.42	3	NC	1
437		10	max	.145	1	.161	3	0	1	0	1	NC	5	NC	1
438			min	-.006	3	-.946	1	0	1	0	1	488.037	3	NC	1
439		11	max	.142	1	.18	3	0	1	0	1	NC	5	NC	1
440			min	-.005	3	-1.047	1	0	1	0	1	437.262	3	NC	1
441		12	max	.14	1	.198	3	0	1	0	1	NC	5	NC	1
442			min	-.004	3	-1.149	1	0	1	0	1	395.683	3	NC	1
443		13	max	.137	1	.217	3	0	1	0	1	NC	1	NC	1
444			min	-.002	3	-1.25	1	0	1	0	1	361.026	3	NC	1
445		14	max	.134	1	.236	3	0	1	0	1	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
446			min	-.001	3	-1.351	1	0	1	0	1	331.715	3	NC	1
447		15	max	.132	1	.255	3	0	1	0	1	NC	1	NC	1
448			min	0	3	-1.452	1	0	1	0	1	306.624	3	NC	1
449		16	max	.129	1	.274	3	0	1	0	1	NC	1	NC	1
450			min	0	3	-1.553	1	0	1	0	1	284.927	3	NC	1
451		17	max	.126	1	.293	3	0	1	0	1	NC	1	NC	1
452			min	.001	12	-1.654	1	0	1	0	1	266.003	3	NC	1
453		18	max	.124	1	.313	3	0	1	0	1	NC	1	NC	1
454			min	.002	12	-1.754	1	0	1	0	1	249.377	3	NC	1
455		19	max	.121	1	.332	3	0	1	0	1	NC	1	NC	1
456			min	.003	12	-1.855	1	0	1	0	1	234.679	3	NC	1
457	M9	1	max	.099	1	.001	3	.004	1	1.238e-4	3	NC	1	NC	1
458			min	-.008	3	-.011	1	-.001	3	-2.749e-4	2	NC	1	NC	1
459		2	max	.098	1	.008	3	.021	1	4.5e-4	3	NC	1	NC	3
460			min	-.008	3	-.067	1	-.007	3	-1.202e-3	1	NC	1	4131.22	1
461		3	max	.097	1	.014	3	.038	1	7.762e-4	3	NC	1	NC	4
462			min	-.008	3	-.124	1	-.013	3	-2.165e-3	1	5881.547	3	2089.641	1
463		4	max	.095	1	.021	3	.054	1	1.102e-3	3	NC	1	NC	5
464			min	-.007	3	-.18	1	-.018	3	-3.129e-3	1	3902.66	3	1418.078	1
465		5	max	.094	1	.028	3	.07	1	1.429e-3	3	NC	1	NC	5
466			min	-.007	3	-.236	1	-.023	3	-4.092e-3	1	2908.794	3	1089.74	1
467		6	max	.093	1	.035	3	.083	1	1.755e-3	3	NC	1	NC	5
468			min	-.006	3	-.292	1	-.028	3	-5.055e-3	1	2309.469	3	899.551	1
469		7	max	.092	1	.042	3	.095	1	2.081e-3	3	NC	1	NC	5
470			min	-.006	3	-.348	1	-.032	3	-6.019e-3	1	1907.855	3	779.465	1
471		8	max	.091	1	.049	3	.105	1	2.407e-3	3	NC	5	NC	5
472			min	-.006	3	-.404	1	-.035	3	-6.982e-3	1	1619.589	3	700.697	1
473		9	max	.09	1	.056	3	.112	1	2.734e-3	3	NC	5	NC	5
474			min	-.005	3	-.459	1	-.038	3	-7.945e-3	1	1402.478	3	649.338	1
475		10	max	.089	1	.064	3	.117	1	3.06e-3	3	NC	5	NC	5
476			min	-.005	3	-.514	1	-.04	3	-8.909e-3	1	1233.063	3	618.325	1
477		11	max	.088	1	.072	3	.119	1	3.386e-3	3	NC	5	NC	5
478			min	-.005	3	-.569	1	-.04	3	-9.872e-3	1	1097.256	3	604.383	1
479		12	max	.086	1	.08	3	.117	1	3.712e-3	3	NC	5	NC	5
480			min	-.004	3	-.624	1	-.04	3	-1.084e-2	1	986.075	3	606.921	1
481		13	max	.085	1	.088	3	.111	1	4.039e-3	3	NC	1	NC	5
482			min	-.004	3	-.678	1	-.038	3	-1.18e-2	1	893.519	3	628.055	1
483		14	max	.084	1	.096	3	.102	1	4.365e-3	3	NC	1	NC	5
484			min	-.003	3	-.732	1	-.035	3	-1.276e-2	1	815.42	3	673.875	1
485		15	max	.083	1	.104	3	.087	1	4.691e-3	3	NC	1	NC	5
486			min	-.003	3	-.786	1	-.031	3	-1.373e-2	1	748.79	3	758.393	1
487		16	max	.082	1	.113	3	.069	1	5.017e-3	3	NC	1	NC	5
488			min	-.003	3	-.84	1	-.025	3	-1.469e-2	1	691.43	3	915.928	1
489		17	max	.081	1	.122	3	.045	1	5.343e-3	3	NC	1	NC	5
490			min	-.002	3	-.894	1	-.018	3	-1.565e-2	1	641.681	3	1251.105	1
491		18	max	.08	1	.13	3	.018	2	5.67e-3	3	NC	1	NC	4
492			min	-.002	3	-.947	1	-.008	3	-1.662e-2	1	598.27	3	2289.401	1
493		19	max	.079	1	.139	3	.003	3	5.996e-3	3	NC	1	NC	1
494			min	-.002	3	-1.001	1	-.02	1	-1.758e-2	1	560.204	3	NC	1