

Schletter, Inc.		15ÁTilt w/o Seismic Design
HCV	Standard PVMax Racking System	
	Representative Calculations - ASCE 7-10	

1. INTRODUCTION

1.1 Project Description

The following sections will cover the determination of forces and structural design calculations for the Schletter, Inc. PVMax ground mount system.

1.2 Construction

Photovoltaic modules are attached to aluminum purlins using clamp fasteners. Purlins are clamped to inclined aluminum girders, which are then connected to aluminum struts. Each support structure is equally spaced.

PV modules are required to meet the following specifications:

Maximum			Minimum		
Height =	1700	mm	Height =	1550	mm
Width =	1050	mm	Width =	970	mm
Dead Load =	3.00	psf	Dead Load =	1.75	psf

Modules Per Row =	2
Module Tilt =	15°
Maximum Height Above Grade =	3 ft

1.3 Technical Codes

- ASCE 7-10 - Chapter 26-31, Wind Loads
- ASCE 7-10 - Chapter 7, Snow Loads
- ASCE 7-10 - Chapter 2, Combination of Loads
- International Building Code, IBC, 2012, 2015
- Aluminum Design Manual, Eighth Edition, 2005



Typical loading conditions of the module dead loads, snow loads, and wind loads are shown on the left.

2. LOAD ACTIONS

2.1 Permanent Loads

g_{MAX} =	3.00	psf	*Self-weight of the PV modules.*
g_{MIN} =	1.75	psf	

2.2 Snow Loads

Ground Snow Load, P_g =	30.00	psf	
Sloped Roof Snow Load, P_s =	22.68	psf	*(ASCE 7-10, Eq. 7.4-1)*
I_s =	1.00		
C_s =	1.00		
C_e =	0.90		
C_t =	1.20		

2.3 Wind Loads

Design Wind Speed, V =	150	mph	Exposure Category = C
Height <	15	ft	Importance Category = II
Peak Velocity Pressure, q_z =	35.33	psf	*Including the gust factor, G=0.85. (ASCE 7-10, Eq. 27.3-1)*

Pressure Coefficients

$Cf+_{TOP}$ =	1.000		*(Pressure)*
$Cf+_{BOTTOM}$ =	1.600		
$Cf-_{TOP, OUTER PURLIN}$ =	-2.300		
$Cf-_{TOP, INNER PURLIN}$ =	-1.780	*(Suction)*	
$Cf-_{BOTTOM}$ =	-1.000		

Provided pressure coefficients are the result of wind tunnel testing done by Ruscheweyh Consult. Coefficients are located in test report # 1127/0611-1e. Negative forces are applied away from the surface.

2.4 Seismic Loads - N/A

S_S =	0.00	R =	1.25
S_{DS} =	0.00	C_S =	0
S_1 =	0.00	ρ =	1.3
S_{D1} =	0.00	Ω =	1.25
T_a =	0.00	C_d =	1.25

ASCE 7, Section 12.8.1.3: A maximum S_s of 1.5 may be used to calculate the base shear, C_s, of structures under five stories and with a period, T, of 0.5 or less. Therefore, a S_{ds} of 1.0 was used to calculate C_s.

2.5 Combination of Loads

ASCE 7 requires that all structures be checked by specified combinations of loads. Applicable load combinations are provided below.

Strength Design, LRFD

Component stresses are checked using the following LRFD load combinations:

1.2D + 1.6S + 0.5W	
1.2D + 1.0W + 0.5S	
0.9D + 1.0W [M]	
1.54D + 1.3E + 0.2S [R]	*(ASCE 7, Eq 2.3.2-1 through 2.3.2-7) & (ASCE 7, Section 12.4.3.2)*
0.56D + 1.3E [R]	
1.54D + 1.25E + 0.2S [O]	
0.56D + 1.25E [O]	

Allowable Stress Design, ASD

Member deflection checks and foundation designs are done according to the following ASD load combinations:

1.0D + 1.0S	
1.0D + 0.6W	
1.0D + 0.75L + 0.45W + 0.75S	
0.6D + 0.6W [M]	*(ASCE 7, Eq 2.4.1-1 through 2.4.1-8) & (ASCE 7, Section 12.4.3.2)*
1.238D + 0.875E [O]	
1.1785D + 0.65625E + 0.75S [O]	
0.362D + 0.875E [O]	

[M] *Uses the minimum allowable module dead load.*

[R] *Include redundancy factor of 1.3.*

[O] *Includes overstrength factor of 1.25. Used to check seismic drift.*

3. STRUCTURAL ANALYSIS

3.1 RISA Results

Appendix B.1 contains outputs from the structural analysis software package, RISA. These outputs are used to accurately determine resultant member and reaction forces from the loads seen throughout Section 2.

3.2 RISA Components

A member and node list has been provided below to correlate the RISA components with the design calculations in Section 4. Items of significance have been listed.

Purlins	Location
M13	Top
M14	Mid-Top
M15	Mid-Bottom
M16	Bottom

Diagonal Struts	Location
M3	Outer
M7	Inner
M11	Outer

Front Reactions	Location
N7	Outer
N15	Inner
N23	Outer

Girders	Location
M1	Outer
M5	Inner
M9	Outer

Rear Struts	Location
M2	Outer
M6	Inner
M10	Outer

Rear Reactions	Location
N8	Outer
N16	Inner
N24	Outer

Front Struts	Location
M4	Outer
M8	Inner
M12	Outer

4. MEMBER DESIGN CALCULATIONS

4.1 Purlin Design

Aluminum purlins are used to transfer loads to the support structure. Purlins are designed as continous beams with cantilevers. These are considered beams with internal hinges that can be joined with splices at 25% of the support respective span. See Appendix A.1 for detailed member calculations. Section units are in (mm).

Purlin Type	=	**S1.5**	
Aluminum Type	=	6105-T5	
F_{ty}	=	35	ksi
L_b	=	111	in
$\Phi F_{ty\ STRONG\text{-}AXIS}$	=	25.07	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$	=	23.08	ksi
S_y	=	1.33	in^3
S_x	=	0.60	in^3
E	=	10100	ksi
I_y	=	2.16	in^4
I_x	=	1.07	in^4
A	=	1.25	in^2
g	=	1.50	lbs/ft
M_y	=	2.036	k-ft
M_z	=	0.219	k-ft
$M_{y\ allowable}$	=	2.779	k-ft
$M_{z\ allowable}$	=	1.154	k-ft
Utilization	=	92%	



4.2 Girder Design

Loads from purlins are transferred using an inclined girder, which is connected to a set of aluminum struts. Loads on the girder result from the support reactions of the purlins. See Appendix A.2 for detailed member calculations. Section units are in (mm).

Girder Type	=	**BF0**	
Aluminum Type	=	6105-T5	
F_{ty}	=	35	ksi
L_b	=	88.90	in
$\Phi F_{ty\ AXIAL}$	=	31.09	ksi
$\Phi F_{ty\ STRONG\text{-}AXIS}$	=	29.35	ksi
$\Phi F_{ty\ WEAK\text{-}AXIS}$	=	33.25	ksi
S_y	=	1.42	in^3
S_x	=	1.41	in^3
E	=	10100	ksi
I_y	=	2.39	in^4
I_x	=	2.22	in^4
A	=	1.88	in^2
g	=	2.26	lbs/ft
M_y	=	-3.367	k-ft
M_z	=	0.000	k-ft
P_n	=	-0.555	k
$M_{y\ allowable}$	=	3.464	k-ft
$M_{z\ allowable}$	=	3.907	k-ft
$P_{n\ allowable}$	=	58.535	k
Utilization	=	98%	



4.3 Front Strut Design

The front aluminum strut connects a portion of the girder to the foundation. Vertical girder forces are then transferred down through the strut into the foundation. The strut is attached with single M12 bolts at each end. See Appendix A.3 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	24.80	in
$\Phi F_{ty\ AXIAL}$ =	28.03	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.000	k-ft
M_z =	0.000	k-ft
P_n =	3.840	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	27.532	k
Utilization =	14%	



DETAIL VIEW

4.4 Diagonal Strut Design

A diagonal aluminum strut braces the support structure. It connects at a front portion of the girder and transfers horizontal forces to the rear foundation connection. The strut is attached with single M12 bolts at each end. See Appendix A.4 for detailed member calculations. Section units are in (mm).

Strut Type =	**55x55**	
Aluminum Type =	6105-T5	
F_{ty} =	35	ksi
L_b =	86.60	in
$\Phi F_{ty\ AXIAL}$ =	7.50	ksi
$\Phi F_{ty\ BENDING}$ =	28.22	ksi
S_y =	0.60	in^3
S_x =	0.60	in^3
E =	10100	ksi
I_y =	0.67	in^4
I_x =	0.67	in^4
A =	0.98	in^2
g =	1.18	lbs/ft
M_y =	0.011	k-ft
M_z =	0.000	k-ft
P_n =	1.526	k
$M_{y\ allowable}$ =	1.408	k-ft
$M_{z\ allowable}$ =	1.408	k-ft
$P_{n\ allowable}$ =	7.371	k
Utilization =	21%	



DETAIL VIEW

4.5 Rear Strut Design

An aluminum strut connects the rear portion of the girder to the rear foundation connection. Both vertical and horizontal forces are transferred from the girder. The strut is attached with single M12 bolts at each end. See Appendix A.5 for detailed member calculations. Section units are in (mm).

Strut Type	=	**55x55**	
Aluminum Type	=	6105-T5	
F_{ty}	=	35	ksi
L_b	=	48.30	in
$\Phi F_{ty\ AXIAL}$	=	18.93	ksi
$\Phi F_{ty\ BENDING}$	=	28.22	ksi
S_y	=	0.60	in^3
S_x	=	0.60	in^3
E	=	10100	ksi
I_y	=	0.67	in^4
I_x	=	0.67	in^4
A	=	0.98	in^2
g	=	1.18	lbs/ft
M_y	=	-0.010	k-ft
M_z	=	0.000	k-ft
P_n	=	3.740	k
$M_{y\ allowable}$	=	1.408	k-ft
$M_{z\ allowable}$	=	1.408	k-ft
$P_{n\ allowable}$	=	18.592	k
Utilization	=	21%	



5. FOUNDATION DESIGN CALCULATIONS

5.1 Helical Pile Foundations

The following LRFD loads include a safety factor of 1.3, and are to be used in conjunction with a Schletter, Inc. Geotechnical Investigation Report. The forces below should fall within the guidelines provided in the Geotechnical Investigation Report. If a Geotechnical Investigation Report is not present, please proceed to Section 5.2 for a concrete foundation design.

Maximum		Front	Rear	
Tensile Load	=	1887.60	6354.48	k
Compressive Load	=	4992.44	5173.80	k
Lateral Load	=	8.47	2280.41	k
Moment (Weak Axis)	=	0.02	0.01	k

5.2 Design of Ballast Foundations

Ballast foundations are used to secure the racking structure in place. The foundations are checked for potential overturning and sliding. Bearing pressures applied by the racking and ballast foundations are checked against the allowable bearing pressures provided by the IBC table 1806.2 (2012, 2015).



Concrete Properties		
Weight of Concrete =	145	pcf
Compressive Strength =	2500	psi
Yield Strength =	60000	psi
Overturning Check		
M_O =	152497.6	in-lbs
Resisting Force Required =	2310.57	lbs
S.F. =	1.67	
Weight Required =	3850.95	lbs
Minimum Width =	34 in	in
Weight Provided =	6778.75	lbs
Sliding		
Force =	526.05	lbs
Friction =	0.4	
Weight Required =	1315.12	lbs
Resisting Weight =	6778.75	lbs
Additional Weight Required =	0	lbs
Cohesion		
Sliding Force =	526.05	lbs
Cohesion =	130	psf
Area =	31.17	ft^2
Resisting =	3389.38	lbs
Additional Weight Required =	0	lbs
Shear Key		
Additional Force =	0	lbs
Lateral Bearing Pressure =	200	psf/ft
Required Depth =	0.00	ft
f'_c =	2500	psi
Length =	8	in

Footing Reinforcement

Use fiber reinforcing with (2) #5 rebar.

A minimum 132in long x 34in wide x 18in tall ballast foundation is required to resist overturning.

Use a 132in long x 34in wide x 18in tall ballast foundation to resist sliding. Friction is OK.

Use a 132in long x 34in wide x 18in tall ballast foundation. Cohesion is OK.

Shear key is not required.

Bearing Pressure

	Ballast Width			
	34 in	35 in	36 in	37 in
P_{ftg} = (145 pcf)(11 ft)(1.5 ft)(2.83 ft) =	6779 lbs	6978 lbs	7178 lbs	7377 lbs

ASD LC	1.0D + 1.0S				1.0D + 0.6W				1.0D + 0.75L + 0.45W + 0.75S				0.6D + 0.6W			
Width	34 in	35 in	36 in	37 in	34 in	35 in	36 in	37 in	34 in	35 in	36 in	37 in	34 in	35 in	36 in	37 in
F_A	1594 lbs	1594 lbs	1594 lbs	1594 lbs	1903 lbs	1903 lbs	1903 lbs	1903 lbs	2503 lbs	2503 lbs	2503 lbs	2503 lbs	-862 lbs	-862 lbs	-862 lbs	-862 lbs
F_B	1649 lbs	1649 lbs	1649 lbs	1649 lbs	1972 lbs	1972 lbs	1972 lbs	1972 lbs	2593 lbs	2593 lbs	2593 lbs	2593 lbs	-2924 lbs	-2924 lbs	-2924 lbs	-2924 lbs
F_V	138 lbs	138 lbs	138 lbs	138 lbs	925 lbs	925 lbs	925 lbs	925 lbs	788 lbs	788 lbs	788 lbs	788 lbs	-1052 lbs	-1052 lbs	-1052 lbs	-1052 lbs
P_{total}	10021 lbs	10220 lbs	10420 lbs	10619 lbs	10654 lbs	10853 lbs	11052 lbs	11252 lbs	11875 lbs	12074 lbs	12273 lbs	12473 lbs	281 lbs	401 lbs	521 lbs	640 lbs
M	3873 lbs-ft	3873 lbs-ft	3873 lbs-ft	3873 lbs-ft	5755 lbs-ft	5755 lbs-ft	5755 lbs-ft	5755 lbs-ft	6931 lbs-ft	6931 lbs-ft	6931 lbs-ft	6931 lbs-ft	1437 lbs-ft	1437 lbs-ft	1437 lbs-ft	1437 lbs-ft
e	0.39 ft	0.38 ft	0.37 ft	0.36 ft	0.54 ft	0.53 ft	0.52 ft	0.51 ft	0.58 ft	0.57 ft	0.56 ft	0.56 ft	5.11 ft	3.58 ft	2.76 ft	2.24 ft
L/6	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft	1.83 ft
f_{min}	253.8 psf	252.7 psf	251.7 psf	250.8 psf	241.1 psf	240.4 psf	239.8 psf	239.2 psf	259.7 psf	258.5 psf	257.4 psf	256.3 psf	0.0 psf	0.0 psf	0.0 psf	0.0 psf
f_{max}	389.3 psf	384.4 psf	379.8 psf	375.4 psf	442.5 psf	436.1 psf	430.0 psf	424.3 psf	502.3 psf	494.2 psf	486.5 psf	479.2 psf	169.4 psf	47.8 psf	42.2 psf	42.5 psf

Maximum Bearing Pressure = 502 psf
Allowable Bearing Pressure = 1500 psf

Use a 132in long x 34in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Weak Side Design

Overturning Check

M_O =	1228.7	ft-lbs
Resisting Force Required =	867.34	lbs
S.F. =	1.67	
Weight Required =	1445.57	lbs
Minimum Width =	34 in	in
Weight Provided =	6778.75	lbs

A minimum 132in long x 34in wide x 18in tall ballast foundation is required to resist overturning.



Bearing Pressure

ASD LC	1.238D + 0.875E			1.1785D + 0.65625E + 0.75S			0.362D + 0.875E		
Width	34 in			34 in			34 in		
Support	Outer	Inner	Outer	Outer	Inner	Outer	Outer	Inner	Outer
F_Y	224 lbs	599 lbs	224 lbs	874 lbs	2639 lbs	874 lbs	65 lbs	175 lbs	65 lbs
F_V	1 lbs	0 lbs	1 lbs	3 lbs	0 lbs	3 lbs	0 lbs	0 lbs	0 lbs
P_{total}	8616 lbs	6779 lbs	8616 lbs	8863 lbs	6779 lbs	8863 lbs	2519 lbs	6779 lbs	2519 lbs
M	3 lbs-ft	0 lbs-ft	3 lbs-ft	10 lbs-ft	0 lbs-ft	10 lbs-ft	0 lbs-ft	0 lbs-ft	0 lbs-ft
e	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft	0.00 ft
L/6	0.47 ft	0.47 ft	0.47 ft	0.47 ft	0.47 ft	0.47 ft	0.47 ft	0.47 ft	0.47 ft
f_{min}	276.2 psf	217.5 psf	276.2 psf	283.7 psf	217.5 psf	283.7 psf	80.8 psf	217.5 psf	80.8 psf
f_{max}	276.6 psf	217.5 psf	276.6 psf	285.0 psf	217.5 psf	285.0 psf	80.9 psf	217.5 psf	80.9 psf

Maximum Bearing Pressure = 285 psf
Allowable Bearing Pressure = 1500 psf

Use a 132in long x 34in wide x 18in tall ballast foundation for an acceptable bearing pressure.

Foundation Requirements: 132in long x 34in wide x 18in tall ballast foundation and fiber reinforcing with (2) #5 rebar.

5.3 Foundation Anchors

Threaded rods are anchored to the the ballast foundations using the Simpson AT-XP epoxy solution. LRFD load results are compared to the allowable strengths of the epoxy solution. Please see the supplementary calculations provided by the Simpson Anchor Designer software.

6. DESIGN OF JOINTS AND CONNECTIONS

6.1 Anchorage of Modules to Purlins and Connection of Purlins to Girders

Modules are secured to the purlins with Schletter, Inc. Rapid2+ mounting clamps. Purlins are secured to the girders with the use of 80mm mounting clamps. The reliability of calculations is uncertain due to limited standards, therefore the strength of the clamp fasteners has been evaluated by load testing.

Fastening of Modules to Purlins

Maximum Uplifting Force	=	0.765 k
Allowable Uplift	=	1.214 k
Utilization	=	63%



Fastening of Purlins to Girders

Maximum Uplifting Force	=	2.522 k
Allowable Uplift	=	4.357 k
Utilization	=	58%



6.2 Strut Connections

The aluminum struts connect the aluminum girder ends to custom brackets with mounting holes. Single M12 bolts are used to attach each end of the strut to the girder and post. ASTM A193/A193M-86 equivalent stainless steel bolts are used.

Front Strut

Maximum Axial Load	=	3.840 k
M12 Bolt Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	52%

Rear Strut

Maximum Axial Load	=	4.449 k
M12 Bolt Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	60%

Diagonal Strut

Maximum Axial Load	=	1.655 k
M12 Bolt Shear Capacity	=	12.808 k
Strut Bearing Capacity	=	7.421 k
Utilization	=	22%

Bolt and bearing capacities are accounting for double shear. (ASCE 8-02, Eq. 5.3.4-1)



Struts under compression are shown to demonstrate the load transfer from the girder. Single M12 bolts are located at each end of the strut and are subjected to double shear.

7. SEISMIC DESIGN

7.1 Seismic Drift - N/A

The racking structure has been analyzed under seismic loading. The allowable story drift of the structure must fall within the limits provided by (ASCE 7, Table 12.12-1).

Mean Height, h_{sx}	=	36.30 in
Allowable Story Drift for All Other Structures, Δ	= {	$0.020h_{sx}$
		0.726 in
Max Drift, Δ_{MAX}	=	0.025 in

N/A

The racking structure's reaction to seismic loads is shown to the right. The deflections have been magnified to provide a clear portrayal of potential story drift.



APPENDIX A

A.1 Design of Aluminum Purlins - Aluminum Design Manual, 2005 Edition

Purlin = **S1.5**

Strong Axis:

3.4.14

L_b = 111 in

J = 0.432

307.078

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 27.6 ksi

3.4.16

b/t = 32.195

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 25.1 ksi

3.4.16.1 Not Used

Rb/t =

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 37.0588

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 40.985

Cc = 41.015

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.2

φF_L= φb[Bbr-mDbr*h/t]

φF_L= 43.2 ksi

φF_LSt= 25.1 ksi

Ix = 897074 mm^4

2.155 in^4

y = 41.015 mm

Sx = 1.335 in^3

M_{max}St = 2.788 k-ft

Weak Axis:

3.4.14

L_b = 111

J = 0.432

195.283

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 28.8

3.4.16

b/t = 37.0588

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 23.1 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 32.195

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 45.5

Cc = 45.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

φF_LWk= 23.1 ksi

Iy = 446476 mm^4

1.073 in^4

x = 45.5 mm

Sy = 0.599 in^3

M_{max}Wk = 1.152 k-ft

Compression

3.4.9

b/t = 32.195
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 25.1 ksi

b/t = 37.0588
S1 = 12.21
S2 = 32.70
φF_L = (φck2*√(BpE))/(1.6b/t)
φF_L = 21.9 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 21.94 ksi
A = 1215.13 mm^2
1.88 in^2
P_{max} = 41.32 kips

A.2 Design of Aluminum Girders - Aluminum Design Manual, 2005 Edition

Girder = **BF0**

Strong Axis:

3.4.14

L_b = 88.9 in
J = 1.08
152.913

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.4 ksi

3.4.16

b/t = 16.2

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 31.6 ksi

Weak Axis:

3.4.14

L_b = 88.9
J = 1.08
161.829

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 29.2

3.4.16

b/t = 7.4

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φyFcy
φF_L = 33.3 ksi

3.4.16.1 Used

Rb/t = 18.1

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L = φb[Bt-Dt*√(Rb/t)]

φF_L = 31.1 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 7.4

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 35.2

m = 0.68

C_0 = 41.067

Cc = 43.717

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 73.8

φF_L = 1.3φyFcy

φF_L = 43.2 ksi

$\varphi F_L St$ = 29.4 ksi

Ix = 984962 mm^4

2.366 in^4

y = 43.717 mm

Sx = 1.375 in^3

$M_{max}St$ = 3.363 k-ft

3.4.18

h/t = 16.2

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 40

Cc = 40

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L = 1.3φyFcy

φF_L = 43.2 ksi

$\varphi F_L Wk$ = 33.3 ksi

Iy = 923544 mm^4

2.219 in^4

x = 40 mm

Sy = 1.409 in^3

$M_{max}Wk$ = 3.904 k-ft

Compression

3.4.9

b/t = 16.2

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 31.6 ksi

b/t = 7.4

S1 = 12.21

S2 = 32.70

φF_L = φyFcy

φF_L = 33.3 ksi

3.4.10

Rb/t = 18.1

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φc[Bt-Dt*√(Rb/t)]

φF_L = 31.09 ksi

φF_L = 31.09 ksi

A = 1215.13 mm^2

1.88 in^2

P_{max} = 58.55 kips

A.3 Design of Aluminum Struts (Front) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 24.8 in

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

$M_{max}St$ = 1.460 k-ft

Weak Axis:

3.4.14

L_b = 24.8

J = 0.942

38.7028

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L= φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L= 31.4

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

$M_{max}Wk$ = 1.460 k-ft

Compression

3.4.7

λ = 0.57371

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

S1* = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

S2* = 1.23671

φcc = 0.87952

φF_L = φcc(Bc-Dc*λ)

φF_L = 28.0279 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L = φc[Bp-1.6Dp*b/t]

φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b}Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 28.03 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 28.85 kips

A.4 Design of Aluminum Struts (Diagonal) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 86.60 in

J = 0.942

135.148

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L = 29.6 ksi

Weak Axis:

3.4.14

L_b = 86.6

J = 0.942

135.148

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b}Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56

φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]

φF_L = 29.6

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b} Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

$M_{max}St$ = 1.460 k-ft

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7

φF_L= φb[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b} 1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

$M_{max}Wk$ = 1.460 k-ft

Compression

3.4.7

λ = 2.00335

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.86047

φF_L= (φccFcy)/(λ²)

φF_L= 7.50396 ksi

3.4.9

b/t = 24.5
S1 = 12.21 (See 3.4.16 above for formula)
S2 = 32.70 (See 3.4.16 above for formula)
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

b/t = 24.5
S1 = 12.21
S2 = 32.70
φF_L = φc[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87
S2 = 131.3
φF_L = φyFcy
φF_L = 33.25 ksi

φF_L = 7.50 ksi
A = 663.99 mm^2
1.03 in^2
P_{max} = 7.72 kips

A.5 Design of Aluminum Struts (Rear) - Aluminum Design Manual, 2005 Edition

Strut = **55x55**

Strong Axis:

3.4.14

L_b = 48.30 in
J = 0.942
75.3767

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.6 ksi

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

Weak Axis:

3.4.14

L_b = 48.3
J = 0.942
75.3767

$$S1 = \left(\frac{Bc - \frac{\theta_y}{\theta_b} Fcy}{1.6Dc}\right)^2$$

S1 = 0.51461

$$S2 = \left(\frac{C_c}{1.6}\right)^2$$

S2 = 1701.56
φF_L = φb[Bc-1.6Dc*√((LbSc)/(Cb*√(IyJ)/2))]
φF_L = 30.6

3.4.16

b/t = 24.5

$$S1 = \frac{Bp - \frac{\theta_y}{\theta_b} Fcy}{1.6Dp}$$

S1 = 12.2

$$S2 = \frac{k_1 Bp}{1.6Dp}$$

S2 = 46.7
φF_L = φb[Bp-1.6Dp*b/t]
φF_L = 28.2 ksi

3.4.16.1 Not Used

Rb/t = 0.0

$$S1 = \left(\frac{Bt - 1.17\frac{\theta_y}{\theta_b}Fcy}{1.6Dt}\right)^2$$

S1 = 1.1

$$S2 = C_t$$

S2 = 141.0

φF_L= 1.17φyFcy

φF_L= 38.9 ksi

3.4.16.1

N/A for Weak Direction

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L St$= 28.2 ksi

Ix = 279836 mm^4

0.672 in^4

y = 27.5 mm

Sx = 0.621 in^3

$M_{max}St$ = 1.460 k-ft

3.4.18

h/t = 24.5

$$S1 = \frac{Bbr - \frac{\theta_y}{\theta_b}1.3Fcy}{mDbr}$$

S1 = 36.9

m = 0.65

C_0 = 27.5

Cc = 27.5

$$S2 = \frac{k_1 Bbr}{mDbr}$$

S2 = 77.3

φF_L= 1.3φyFcy

φF_L= 43.2 ksi

$\varphi F_L Wk$= 28.2 ksi

Iy = 279836 mm^4

0.672 in^4

x = 27.5 mm

Sy = 0.621 in^3

$M_{max}Wk$ = 1.460 k-ft

Compression

3.4.7

λ = 1.11734

r = 0.81 in

$$S1^* = \frac{Bc - Fcy}{1.6Dc^*}$$

$S1^*$ = 0.33515

$$S2^* = \frac{Cc}{\pi}\sqrt{Fcy/E}$$

$S2^*$ = 1.23671

φcc = 0.76536

φF_L= φcc(Bc-Dc*λ)

φF_L= 18.9268 ksi

3.4.9

b/t = 24.5

S1 = 12.21 (See 3.4.16 above for formula)

S2 = 32.70 (See 3.4.16 above for formula)

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

b/t = 24.5

S1 = 12.21

S2 = 32.70

φF_L= φc[Bp-1.6Dp*b/t]

φF_L= 28.2 ksi

3.4.10

Rb/t = 0.0

$$S1 = \left(\frac{Bt - \frac{\theta_y}{\theta_b} Fcy}{Dt}\right)^2$$

S1 = 6.87

S2 = 131.3

φF_L = φyFcy

φF_L = 33.25 ksi

φF_L = 18.93 ksi

A = 663.99 mm^2

1.03 in^2

P_{max} = 19.48 kips

APPENDIX B

B.1

The following pages will contain the results from RISA. Please refer back to Section 2 for load information and Section 4-5 for member and foundation design.

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distribut...	Area(Me...	Surface(...
1	Dead Load, Max	DL		-1				4		
2	Dead Load, Min	DL		-1				4		
3	Snow Load	SL						4		
4	Wind Load - Pressure	WL						4		
5	Wind Load - Suction	WL						4		
6	Seismic - Lateral	EL								

Member Distributed Loads (BLC 1 : Dead Load, Max)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-8.366	-8.366	0	0
2	M14	Y	-8.366	-8.366	0	0
3	M15	Y	-8.366	-8.366	0	0
4	M16	Y	-8.366	-8.366	0	0

Member Distributed Loads (BLC 2 : Dead Load, Min)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-4.45	-4.45	0	0
2	M14	Y	-4.45	-4.45	0	0
3	M15	Y	-4.45	-4.45	0	0
4	M16	Y	-4.45	-4.45	0	0

Member Distributed Loads (BLC 3 : Snow Load)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	Y	-61.093	-61.093	0	0
2	M14	Y	-61.093	-61.093	0	0
3	M15	Y	-61.093	-61.093	0	0
4	M16	Y	-61.093	-61.093	0	0

Member Distributed Loads (BLC 4 : Wind Load - Pressure)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	-98.517	-98.517	0	0
2	M14	y	-98.517	-98.517	0	0
3	M15	y	-157.628	-157.628	0	0
4	M16	y	-157.628	-157.628	0	0

Member Distributed Loads (BLC 5 : Wind Load - Suction)

	Member Label	Direction	Start Magnitude[lb/ft,F]	End Magnitude[lb/ft,F]	Start Location[ft,%]	End Location[ft,%]
1	M13	y	226.59	226.59	0	0
2	M14	y	175.361	175.361	0	0
3	M15	y	98.517	98.517	0	0
4	M16	y	98.517	98.517	0	0

Load Combinations

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
1	LRFD 1.2D + 1.6S + 0.5W	Yes	Y		1	1.2	3	1.6	4	.5														
2	LRFD 1.2D + 1.0W + 0.5S	Yes	Y		1	1.2	3	.5	4	1														
3	LRFD 0.9D + 1.0W	Yes	Y		2	.9					5	1												
4	LATERAL - LRFD 1.54D + 1.3E ...	Yes	Y		1	1.54	3	.2			6	1.3												
5	LATERAL - LRFD 0.56D + 1.3E	Yes	Y		1	.56					6	1.3												
6	LATERAL - LRFD 1.54D + 1.25...	Yes	Y		1	1.54	3	.2			6	1.25												
7	LATERAL - LRFD 0.56D + 1.25E	Yes	Y		1	.56					6	1.25												

Load Combinations (Continued)

	Description	S...	P...	S...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...	B...	Fa...
8																										
9	ASD 1.0D + 1.0S	Yes	Y		1	1	3	1																		
10	ASD 1.0D + 0.6W	Yes	Y		1	1			4	.6																
11	ASD 1.0D + 0.75L + 0.45W + 0....	Yes	Y		1	1	3	.75	4	.45																
12	ASD 0.6D + 0.6W	Yes	Y		2	.6					5	.6														
13	LATERAL - ASD 1.238D + 0.875E	Yes	Y		1	1.2...					6	.875														
14	LATERAL - ASD 1.1785D + 0.65...	Yes	Y		1	1.1...	3	.75			6	.656														
15	LATERAL - ASD 0.362D + 0.875E	Yes	Y		1	.362					6	.875														

Envelope Joint Reactions

	Joint		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N8	max	430.833	2	1203.386	1	.9	1	.004	1	0	1	0	1
2		min	-556.446	3	-1500.871	3	.034	15	0	15	0	1	0	1
3	N7	max	.028	9	1299.137	1	-.222	15	0	15	0	1	0	1
4		min	-.14	2	-430.868	3	-6.515	1	-.014	1	0	1	0	1
5	N15	max	.022	9	3840.336	1	0	10	0	2	0	1	0	1
6		min	-1.712	2	-1451.997	3	0	12	0	12	0	1	0	1
7	N16	max	1593.248	2	3979.848	1	0	11	0	11	0	1	0	1
8		min	-1754.158	3	-4888.062	3	0	12	0	1	0	1	0	1
9	N23	max	.028	9	1299.137	1	6.515	1	.014	1	0	1	0	1
10		min	-.14	2	-430.868	3	.222	15	0	15	0	1	0	1
11	N24	max	430.833	2	1203.386	1	-.034	15	0	15	0	1	0	1
12		min	-556.446	3	-1500.871	3	-.9	1	-.004	1	0	1	0	1
13	Totals:	max	2452.923	2	12825.231	1	0	11						
14		min	-2868.031	3	-10203.536	3	0	12						

Envelope Member Section Forces

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
1	M13	1	max	70.944	1	530.81	1	-4.106	15	0	3	.168	1	0	1
2			min	2.335	15	-767.795	3	-125.583	1	-.016	2	.006	15	0	3
3		2	max	70.944	1	371.383	1	-3.155	15	0	3	.054	1	.672	3
4			min	2.335	15	-540.23	3	-96.43	1	-.016	2	.002	15	-.464	1
5		3	max	70.944	1	211.956	1	-2.205	15	0	3	0	3	1.11	3
6			min	2.335	15	-312.666	3	-67.277	1	-.016	2	-.03	1	-.763	1
7		4	max	70.944	1	52.529	1	-1.254	15	0	3	-.002	12	1.315	3
8			min	2.335	15	-85.102	3	-38.124	1	-.016	2	-.084	1	-.899	1
9		5	max	70.944	1	142.462	3	-.304	15	0	3	-.003	12	1.285	3
10			min	2.335	15	-106.897	1	-8.972	1	-.016	2	-.108	1	-.871	1
11		6	max	70.944	1	370.027	3	20.181	1	0	3	-.003	15	1.022	3
12			min	2.335	15	-266.324	1	-.022	3	-.016	2	-.102	1	-.68	1
13		7	max	70.944	1	597.591	3	49.334	1	0	3	-.002	15	.525	3
14			min	2.335	15	-425.751	1	1.001	12	-.016	2	-.067	1	-.324	1
15		8	max	70.944	1	825.155	3	78.487	1	0	3	.001	2	.196	1
16			min	2.335	15	-585.178	1	1.951	12	-.016	2	-.003	3	-.206	3
17		9	max	70.944	1	1052.719	3	107.64	1	0	3	.095	1	.879	1
18			min	2.335	15	-744.604	1	2.902	12	-.016	2	0	12	-1.171	3
19		10	max	70.944	1	1280.284	3	136.793	1	0	3	.22	1	1.726	1
20			min	2.335	15	-904.031	1	3.852	12	-.016	2	.004	12	-2.37	3
21		11	max	70.944	1	744.604	1	-2.902	12	.016	2	.095	1	.879	1
22			min	2.335	15	-1052.719	3	-107.64	1	0	3	0	12	-1.171	3
23		12	max	70.944	1	585.178	1	-1.951	12	.016	2	.001	2	.196	1
24			min	2.335	15	-825.155	3	-78.487	1	0	3	-.003	3	-.206	3
25		13	max	70.944	1	425.751	1	-1.001	12	.016	2	-.002	15	.525	3
26			min	2.335	15	-597.591	3	-49.334	1	0	3	-.067	1	-.324	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
27		14	max	70.944	1	266.324	1	.022	3	.016	2	-.003	15	1.022	3
28			min	2.335	15	-370.027	3	-20.181	1	0	3	-.102	1	-.68	1
29		15	max	70.944	1	106.897	1	8.972	1	.016	2	-.003	12	1.285	3
30			min	2.335	15	-142.462	3	.304	15	0	3	-.108	1	-.871	1
31		16	max	70.944	1	85.102	3	38.124	1	.016	2	-.002	12	1.315	3
32			min	2.335	15	-52.529	1	1.254	15	0	3	-.084	1	-.899	1
33		17	max	70.944	1	312.666	3	67.277	1	.016	2	0	3	1.11	3
34			min	2.335	15	-211.956	1	2.205	15	0	3	-.03	1	-.763	1
35		18	max	70.944	1	540.23	3	96.43	1	.016	2	.054	1	.672	3
36			min	2.335	15	-371.383	1	3.155	15	0	3	.002	15	-.464	1
37		19	max	70.944	1	767.795	3	125.583	1	.016	2	.168	1	0	1
38			min	2.335	15	-530.81	1	4.106	15	0	3	.006	15	0	3
39	M14	1	max	34.698	1	569.461	1	-4.241	15	.01	3	.194	1	0	1
40			min	1.143	15	-611.948	3	-129.726	1	-.013	1	.006	15	0	3
41		2	max	34.698	1	410.034	1	-3.29	15	.01	3	.075	1	.539	3
42			min	1.143	15	-437.036	3	-100.573	1	-.013	1	.003	15	-.503	1
43		3	max	34.698	1	250.607	1	-2.34	15	.01	3	.002	3	.898	3
44			min	1.143	15	-262.124	3	-71.421	1	-.013	1	-.013	1	-.843	1
45		4	max	34.698	1	91.18	1	-1.389	15	.01	3	-.001	12	1.078	3
46			min	1.143	15	-87.212	3	-42.268	1	-.013	1	-.071	1	-1.018	1
47		5	max	34.698	1	87.701	3	-.439	15	.01	3	-.003	12	1.078	3
48			min	1.143	15	-68.246	1	-13.115	1	-.013	1	-.1	1	-1.03	1
49		6	max	34.698	1	262.613	3	16.038	1	.01	3	-.003	15	.898	3
50			min	1.143	15	-227.673	1	-.219	3	-.013	1	-.098	1	-.878	1
51		7	max	34.698	1	437.525	3	45.191	1	.01	3	-.002	15	.538	3
52			min	1.143	15	-387.1	1	.869	12	-.013	1	-.067	1	-.562	1
53		8	max	34.698	1	612.437	3	74.344	1	.01	3	0	10	-.001	15
54			min	1.143	15	-546.527	1	1.819	12	-.013	1	-.005	1	-.094	2
55		9	max	34.698	1	787.349	3	103.497	1	.01	3	.086	1	.561	1
56			min	1.143	15	-705.954	1	2.77	12	-.013	1	0	3	-.721	3
57		10	max	34.698	1	962.262	3	132.65	1	.01	3	.207	1	1.369	1
58			min	1.143	15	-865.38	1	3.72	12	-.013	1	.004	12	-1.62	3
59		11	max	34.698	1	705.954	1	-2.77	12	.013	1	.086	1	.561	1
60			min	1.143	15	-787.349	3	-103.497	1	-.01	3	0	3	-.721	3
61		12	max	34.698	1	546.527	1	-1.819	12	.013	1	0	10	-.001	15
62			min	1.143	15	-612.437	3	-74.344	1	-.01	3	-.005	1	-.094	2
63		13	max	34.698	1	387.1	1	-.869	12	.013	1	-.002	15	.538	3
64			min	1.143	15	-437.525	3	-45.191	1	-.01	3	-.067	1	-.562	1
65		14	max	34.698	1	227.673	1	.219	3	.013	1	-.003	15	.898	3
66			min	1.143	15	-262.613	3	-16.038	1	-.01	3	-.098	1	-.878	1
67		15	max	34.698	1	68.246	1	13.115	1	.013	1	-.003	12	1.078	3
68			min	1.143	15	-87.701	3	.439	15	-.01	3	-.1	1	-1.03	1
69		16	max	34.698	1	87.212	3	42.268	1	.013	1	-.001	12	1.078	3
70			min	1.143	15	-91.18	1	1.389	15	-.01	3	-.071	1	-1.018	1
71		17	max	34.698	1	262.124	3	71.421	1	.013	1	.002	3	.898	3
72			min	1.143	15	-250.607	1	2.34	15	-.01	3	-.013	1	-.843	1
73		18	max	34.698	1	437.036	3	100.573	1	.013	1	.075	1	.539	3
74			min	1.143	15	-410.034	1	3.29	15	-.01	3	.003	15	-.503	1
75		19	max	34.698	1	611.948	3	129.726	1	.013	1	.194	1	0	1
76			min	1.143	15	-569.461	1	4.241	15	-.01	3	.006	15	0	3
77	M15	1	max	-1.197	15	719.856	2	-4.24	15	.013	1	.194	1	0	2
78			min	-36.253	1	-345.747	3	-129.72	1	-.009	3	.006	15	0	3
79		2	max	-1.197	15	515.766	2	-3.289	15	.013	1	.075	1	.306	3
80			min	-36.253	1	-249.814	3	-100.567	1	-.009	3	.002	15	-.635	2
81		3	max	-1.197	15	311.676	2	-2.339	15	.013	1	.002	3	.514	3
82			min	-36.253	1	-153.88	3	-71.414	1	-.009	3	-.013	1	-1.06	2
83		4	max	-1.197	15	107.585	2	-1.389	15	.013	1	-.001	12	.622	3

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
84			min	-36.253	1	-57.946	3	-42.261	1	-.009	3	-.071	1	-1.276	2
85		5	max	-1.197	15	37.987	3	-.438	15	.013	1	-.003	12	.633	3
86			min	-36.253	1	-96.505	2	-13.108	1	-.009	3	-.1	1	-1.281	2
87		6	max	-1.197	15	133.921	3	16.044	1	.013	1	-.003	15	.544	3
88			min	-36.253	1	-300.596	2	-.143	3	-.009	3	-.098	1	-1.077	2
89		7	max	-1.197	15	229.855	3	45.197	1	.013	1	-.002	15	.357	3
90			min	-36.253	1	-504.686	2	.915	12	-.009	3	-.067	1	-.663	2
91		8	max	-1.197	15	325.788	3	74.35	1	.013	1	0	10	.072	3
92			min	-36.253	1	-708.777	2	1.865	12	-.009	3	-.005	1	-.055	1
93		9	max	-1.197	15	421.722	3	103.503	1	.013	1	.086	1	.793	2
94			min	-36.253	1	-912.867	2	2.816	12	-.009	3	0	12	-.312	3
95		10	max	-1.197	15	517.656	3	132.656	1	.013	1	.207	1	1.837	2
96			min	-36.253	1	-1116.957	2	3.766	12	-.009	3	.004	12	-.795	3
97		11	max	-1.197	15	912.867	2	-2.816	12	.009	3	.086	1	.793	2
98			min	-36.253	1	-421.722	3	-103.503	1	-.013	1	0	12	-.312	3
99		12	max	-1.197	15	708.777	2	-1.865	12	.009	3	0	10	.072	3
100			min	-36.253	1	-325.788	3	-74.35	1	-.013	1	-.005	1	-.055	1
101		13	max	-1.197	15	504.686	2	-.915	12	.009	3	-.002	15	.357	3
102			min	-36.253	1	-229.855	3	-45.197	1	-.013	1	-.067	1	-.663	2
103		14	max	-1.197	15	300.596	2	.143	3	.009	3	-.003	15	.544	3
104			min	-36.253	1	-133.921	3	-16.044	1	-.013	1	-.098	1	-1.077	2
105		15	max	-1.197	15	96.505	2	13.108	1	.009	3	-.003	12	.633	3
106			min	-36.253	1	-37.987	3	.438	15	-.013	1	-.1	1	-1.281	2
107		16	max	-1.197	15	57.946	3	42.261	1	.009	3	-.001	12	.622	3
108			min	-36.253	1	-107.585	2	1.389	15	-.013	1	-.071	1	-1.276	2
109		17	max	-1.197	15	153.88	3	71.414	1	.009	3	.002	3	.514	3
110			min	-36.253	1	-311.676	2	2.339	15	-.013	1	-.013	1	-1.06	2
111		18	max	-1.197	15	249.814	3	100.567	1	.009	3	.075	1	.306	3
112			min	-36.253	1	-515.766	2	3.289	15	-.013	1	.002	15	-.635	2
113		19	max	-1.197	15	345.747	3	129.72	1	.009	3	.194	1	0	2
114			min	-36.253	1	-719.856	2	4.24	15	-.013	1	.006	15	0	3
115	M16	1	max	-2.47	15	682.899	2	-4.11	15	.013	1	.169	1	0	2
116			min	-75.004	1	-317.811	3	-125.794	1	-.012	3	.006	15	0	3
117		2	max	-2.47	15	478.809	2	-3.16	15	.013	1	.055	1	.277	3
118			min	-75.004	1	-221.877	3	-96.641	1	-.012	3	.002	15	-.597	2
119		3	max	-2.47	15	274.719	2	-2.209	15	.013	1	0	3	.456	3
120			min	-75.004	1	-125.943	3	-67.488	1	-.012	3	-.029	1	-.984	2
121		4	max	-2.47	15	70.628	2	-1.259	15	.013	1	-.002	12	.536	3
122			min	-75.004	1	-30.01	3	-38.335	1	-.012	3	-.084	1	-1.162	2
123		5	max	-2.47	15	65.924	3	-.308	15	.013	1	-.003	12	.518	3
124			min	-75.004	1	-133.462	2	-9.182	1	-.012	3	-.108	1	-1.129	2
125		6	max	-2.47	15	161.858	3	19.971	1	.013	1	-.003	15	.401	3
126			min	-75.004	1	-337.553	2	.206	12	-.012	3	-.102	1	-.887	2
127		7	max	-2.47	15	257.791	3	49.124	1	.013	1	-.002	15	.185	3
128			min	-75.004	1	-541.643	2	1.156	12	-.012	3	-.067	1	-.436	2
129		8	max	-2.47	15	353.725	3	78.276	1	.013	1	0	10	.226	2
130			min	-75.004	1	-745.734	2	2.107	12	-.012	3	-.002	3	-.129	3
131		9	max	-2.47	15	449.659	3	107.429	1	.013	1	.094	1	1.097	2
132			min	-75.004	1	-949.824	2	3.057	12	-.012	3	.001	12	-.542	3
133		10	max	-2.47	15	545.593	3	136.582	1	.013	1	.219	1	2.178	2
134			min	-75.004	1	-1153.914	2	4.007	12	-.012	3	.005	12	-1.053	3
135		11	max	-2.47	15	949.824	2	-3.057	12	.012	3	.094	1	1.097	2
136			min	-75.004	1	-449.659	3	-107.429	1	-.013	1	.001	12	-.542	3
137		12	max	-2.47	15	745.734	2	-2.107	12	.012	3	0	10	.226	2
138			min	-75.004	1	-353.725	3	-78.276	1	-.013	1	-.002	3	-.129	3
139		13	max	-2.47	15	541.643	2	-1.156	12	.012	3	-.002	15	.185	3
140			min	-75.004	1	-257.791	3	-49.124	1	-.013	1	-.067	1	-.436	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
141		14	max	-2.47	15	337.553	2	-.206	12	.012	3	-.003	15	.401	3
142			min	-75.004	1	-161.858	3	-19.971	1	-.013	1	-.102	1	-.887	2
143		15	max	-2.47	15	133.462	2	9.182	1	.012	3	-.003	12	.518	3
144			min	-75.004	1	-65.924	3	.308	15	-.013	1	-.108	1	-1.129	2
145		16	max	-2.47	15	30.01	3	38.335	1	.012	3	-.002	12	.536	3
146			min	-75.004	1	-70.628	2	1.259	15	-.013	1	-.084	1	-1.162	2
147		17	max	-2.47	15	125.943	3	67.488	1	.012	3	0	3	.456	3
148			min	-75.004	1	-274.719	2	2.209	15	-.013	1	-.029	1	-.984	2
149		18	max	-2.47	15	221.877	3	96.641	1	.012	3	.055	1	.277	3
150			min	-75.004	1	-478.809	2	3.16	15	-.013	1	.002	15	-.597	2
151		19	max	-2.47	15	317.811	3	125.794	1	.012	3	.169	1	0	2
152			min	-75.004	1	-682.899	2	4.11	15	-.013	1	.006	15	0	3
153	M2	1	max	1167.571	1	2.281	4	1.012	1	0	3	0	3	0	1
154			min	-1367.164	3	.537	15	.033	15	0	1	0	1	0	1
155		2	max	1167.9	1	2.266	4	1.012	1	0	3	0	1	0	15
156			min	-1366.918	3	.534	15	.033	15	0	1	0	15	0	4
157		3	max	1168.228	1	2.251	4	1.012	1	0	3	0	1	0	15
158			min	-1366.671	3	.53	15	.033	15	0	1	0	15	-.001	4
159		4	max	1168.556	1	2.236	4	1.012	1	0	3	0	1	0	15
160			min	-1366.425	3	.527	15	.033	15	0	1	0	15	-.002	4
161		5	max	1168.885	1	2.22	4	1.012	1	0	3	0	1	0	15
162			min	-1366.179	3	.523	15	.033	15	0	1	0	15	-.002	4
163		6	max	1169.213	1	2.205	4	1.012	1	0	3	.001	1	0	15
164			min	-1365.932	3	.519	15	.033	15	0	1	0	15	-.002	4
165		7	max	1169.542	1	2.19	4	1.012	1	0	3	.001	1	0	15
166			min	-1365.686	3	.516	15	.033	15	0	1	0	15	-.003	4
167		8	max	1169.87	1	2.174	4	1.012	1	0	3	.002	1	0	15
168			min	-1365.44	3	.512	15	.033	15	0	1	0	15	-.003	4
169		9	max	1170.199	1	2.159	4	1.012	1	0	3	.002	1	0	15
170			min	-1365.193	3	.509	15	.033	15	0	1	0	15	-.004	4
171		10	max	1170.527	1	2.144	4	1.012	1	0	3	.002	1	-.001	15
172			min	-1364.947	3	.505	15	.033	15	0	1	0	15	-.004	4
173		11	max	1170.855	1	2.129	4	1.012	1	0	3	.002	1	-.001	15
174			min	-1364.701	3	.501	15	.033	15	0	1	0	15	-.005	4
175		12	max	1171.184	1	2.113	4	1.012	1	0	3	.002	1	-.001	15
176			min	-1364.454	3	.498	15	.033	15	0	1	0	15	-.005	4
177		13	max	1171.512	1	2.098	4	1.012	1	0	3	.003	1	-.001	15
178			min	-1364.208	3	.494	15	.033	15	0	1	0	15	-.006	4
179		14	max	1171.841	1	2.083	4	1.012	1	0	3	.003	1	-.001	15
180			min	-1363.962	3	.491	15	.033	15	0	1	0	15	-.006	4
181		15	max	1172.169	1	2.068	4	1.012	1	0	3	.003	1	-.002	15
182			min	-1363.715	3	.487	15	.033	15	0	1	0	15	-.007	4
183		16	max	1172.498	1	2.052	4	1.012	1	0	3	.003	1	-.002	15
184			min	-1363.469	3	.484	15	.033	15	0	1	0	15	-.007	4
185		17	max	1172.826	1	2.037	4	1.012	1	0	3	.004	1	-.002	15
186			min	-1363.223	3	.48	15	.033	15	0	1	0	15	-.008	4
187		18	max	1173.155	1	2.022	4	1.012	1	0	3	.004	1	-.002	15
188			min	-1362.976	3	.476	15	.033	15	0	1	0	15	-.008	4
189		19	max	1173.483	1	2.007	4	1.012	1	0	3	.004	1	-.002	15
190			min	-1362.73	3	.473	15	.033	15	0	1	0	15	-.009	4
191	M3	1	max	406.878	2	8.078	4	.017	1	0	3	0	1	.009	4
192			min	-526.338	3	1.899	15	0	15	0	1	0	15	.002	15
193		2	max	406.708	2	7.306	4	.017	1	0	3	0	1	.005	2
194			min	-526.466	3	1.718	15	0	15	0	1	0	15	.001	12
195		3	max	406.538	2	6.533	4	.017	1	0	3	0	1	.003	2
196			min	-526.593	3	1.536	15	0	15	0	1	0	15	0	3
197		4	max	406.367	2	5.761	4	.017	1	0	3	0	1	0	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
198			min	-526.721	3	1.355	15	0	15	0	1	0	15	-.002	3
199		5	max	406.197	2	4.989	4	.017	1	0	3	0	1	0	15
200			min	-526.849	3	1.173	15	0	15	0	1	0	15	-.003	3
201		6	max	406.027	2	4.216	4	.017	1	0	3	0	1	-.001	15
202			min	-526.977	3	.992	15	0	15	0	1	0	15	-.004	4
203		7	max	405.856	2	3.444	4	.017	1	0	3	0	1	-.001	15
204			min	-527.104	3	.81	15	0	15	0	1	0	15	-.006	4
205		8	max	405.686	2	2.671	4	.017	1	0	3	0	1	-.002	15
206			min	-527.232	3	.629	15	0	15	0	1	0	15	-.007	4
207		9	max	405.516	2	1.899	4	.017	1	0	3	0	1	-.002	15
208			min	-527.36	3	.447	15	0	15	0	1	0	15	-.008	4
209		10	max	405.345	2	1.126	4	.017	1	0	3	0	1	-.002	15
210			min	-527.488	3	.265	15	0	15	0	1	0	15	-.009	4
211		11	max	405.175	2	.446	2	.017	1	0	3	0	1	-.002	15
212			min	-527.615	3	-.026	3	0	15	0	1	0	15	-.009	4
213		12	max	405.005	2	-.098	15	.017	1	0	3	0	1	-.002	15
214			min	-527.743	3	-.478	3	0	15	0	1	0	15	-.009	4
215		13	max	404.834	2	-.279	15	.017	1	0	3	0	1	-.002	15
216			min	-527.871	3	-1.191	4	0	15	0	1	0	15	-.009	4
217		14	max	404.664	2	-.461	15	.017	1	0	3	0	1	-.002	15
218			min	-527.999	3	-1.963	4	0	15	0	1	0	15	-.008	4
219		15	max	404.494	2	-.642	15	.017	1	0	3	0	1	-.002	15
220			min	-528.126	3	-2.736	4	0	15	0	1	0	15	-.007	4
221		16	max	404.323	2	-.824	15	.017	1	0	3	0	1	-.001	15
222			min	-528.254	3	-3.508	4	0	15	0	1	0	15	-.006	4
223		17	max	404.153	2	-1.006	15	.017	1	0	3	0	1	-.001	15
224			min	-528.382	3	-4.281	4	0	15	0	1	0	15	-.004	4
225		18	max	403.983	2	-1.187	15	.017	1	0	3	0	1	0	15
226			min	-528.51	3	-5.053	4	0	15	0	1	0	15	-.002	4
227		19	max	403.812	2	-1.369	15	.017	1	0	3	0	1	0	1
228			min	-528.637	3	-5.825	4	0	15	0	1	0	15	0	1
229	M4	1	max	1296.071	1	0	1	-.223	15	0	1	0	1	0	1
230			min	-433.167	3	0	1	-6.788	1	0	1	0	10	0	1
231		2	max	1296.241	1	0	1	-.223	15	0	1	0	15	0	1
232			min	-433.039	3	0	1	-6.788	1	0	1	0	1	0	1
233		3	max	1296.412	1	0	1	-.223	15	0	1	0	15	0	1
234			min	-432.912	3	0	1	-6.788	1	0	1	-.001	1	0	1
235		4	max	1296.582	1	0	1	-.223	15	0	1	0	15	0	1
236			min	-432.784	3	0	1	-6.788	1	0	1	-.002	1	0	1
237		5	max	1296.752	1	0	1	-.223	15	0	1	0	15	0	1
238			min	-432.656	3	0	1	-6.788	1	0	1	-.003	1	0	1
239		6	max	1296.923	1	0	1	-.223	15	0	1	0	15	0	1
240			min	-432.528	3	0	1	-6.788	1	0	1	-.004	1	0	1
241		7	max	1297.093	1	0	1	-.223	15	0	1	0	15	0	1
242			min	-432.401	3	0	1	-6.788	1	0	1	-.005	1	0	1
243		8	max	1297.263	1	0	1	-.223	15	0	1	0	15	0	1
244			min	-432.273	3	0	1	-6.788	1	0	1	-.005	1	0	1
245		9	max	1297.434	1	0	1	-.223	15	0	1	0	15	0	1
246			min	-432.145	3	0	1	-6.788	1	0	1	-.006	1	0	1
247		10	max	1297.604	1	0	1	-.223	15	0	1	0	15	0	1
248			min	-432.017	3	0	1	-6.788	1	0	1	-.007	1	0	1
249		11	max	1297.775	1	0	1	-.223	15	0	1	0	15	0	1
250			min	-431.89	3	0	1	-6.788	1	0	1	-.008	1	0	1
251		12	max	1297.945	1	0	1	-.223	15	0	1	0	15	0	1
252			min	-431.762	3	0	1	-6.788	1	0	1	-.008	1	0	1
253		13	max	1298.115	1	0	1	-.223	15	0	1	0	15	0	1
254			min	-431.634	3	0	1	-6.788	1	0	1	-.009	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
255		14	max	1298.286	1	0	1	-.223	15	0	1	0	15	0	1
256			min	-431.506	3	0	1	-6.788	1	0	1	-.01	1	0	1
257		15	max	1298.456	1	0	1	-.223	15	0	1	0	15	0	1
258			min	-431.379	3	0	1	-6.788	1	0	1	-.011	1	0	1
259		16	max	1298.626	1	0	1	-.223	15	0	1	0	15	0	1
260			min	-431.251	3	0	1	-6.788	1	0	1	-.012	1	0	1
261		17	max	1298.797	1	0	1	-.223	15	0	1	0	15	0	1
262			min	-431.123	3	0	1	-6.788	1	0	1	-.012	1	0	1
263		18	max	1298.967	1	0	1	-.223	15	0	1	0	15	0	1
264			min	-430.995	3	0	1	-6.788	1	0	1	-.013	1	0	1
265		19	max	1299.137	1	0	1	-.223	15	0	1	0	15	0	1
266			min	-430.868	3	0	1	-6.788	1	0	1	-.014	1	0	1
267	M6	1	max	3734.218	1	2.939	2	0	1	0	1	0	1	0	1
268			min	-4449.348	3	-.085	3	0	1	0	1	0	1	0	1
269		2	max	3734.547	1	2.928	2	0	1	0	1	0	1	0	3
270			min	-4449.102	3	-.094	3	0	1	0	1	0	1	0	2
271		3	max	3734.875	1	2.916	2	0	1	0	1	0	1	0	3
272			min	-4448.856	3	-.103	3	0	1	0	1	0	1	-.001	2
273		4	max	3735.204	1	2.904	2	0	1	0	1	0	1	0	3
274			min	-4448.609	3	-.112	3	0	1	0	1	0	1	-.002	2
275		5	max	3735.532	1	2.892	2	0	1	0	1	0	1	0	3
276			min	-4448.363	3	-.12	3	0	1	0	1	0	1	-.003	2
277		6	max	3735.86	1	2.88	2	0	1	0	1	0	1	0	3
278			min	-4448.117	3	-.129	3	0	1	0	1	0	1	-.003	2
279		7	max	3736.189	1	2.868	2	0	1	0	1	0	1	0	3
280			min	-4447.87	3	-.138	3	0	1	0	1	0	1	-.004	2
281		8	max	3736.517	1	2.856	2	0	1	0	1	0	1	0	3
282			min	-4447.624	3	-.147	3	0	1	0	1	0	1	-.004	2
283		9	max	3736.846	1	2.844	2	0	1	0	1	0	1	0	3
284			min	-4447.378	3	-.156	3	0	1	0	1	0	1	-.005	2
285		10	max	3737.174	1	2.832	2	0	1	0	1	0	1	0	3
286			min	-4447.132	3	-.165	3	0	1	0	1	0	1	-.006	2
287		11	max	3737.503	1	2.821	2	0	1	0	1	0	1	0	3
288			min	-4446.885	3	-.174	3	0	1	0	1	0	1	-.006	2
289		12	max	3737.831	1	2.809	2	0	1	0	1	0	1	0	3
290			min	-4446.639	3	-.183	3	0	1	0	1	0	1	-.007	2
291		13	max	3738.159	1	2.797	2	0	1	0	1	0	1	0	3
292			min	-4446.393	3	-.192	3	0	1	0	1	0	1	-.008	2
293		14	max	3738.488	1	2.785	2	0	1	0	1	0	1	0	3
294			min	-4446.146	3	-.201	3	0	1	0	1	0	1	-.008	2
295		15	max	3738.816	1	2.773	2	0	1	0	1	0	1	0	3
296			min	-4445.9	3	-.21	3	0	1	0	1	0	1	-.009	2
297		16	max	3739.145	1	2.761	2	0	1	0	1	0	1	0	3
298			min	-4445.654	3	-.219	3	0	1	0	1	0	1	-.009	2
299		17	max	3739.473	1	2.749	2	0	1	0	1	0	1	0	3
300			min	-4445.407	3	-.228	3	0	1	0	1	0	1	-.01	2
301		18	max	3739.802	1	2.737	2	0	1	0	1	0	1	0	3
302			min	-4445.161	3	-.236	3	0	1	0	1	0	1	-.011	2
303		19	max	3740.13	1	2.725	2	0	1	0	1	0	1	0	3
304			min	-4444.915	3	-.245	3	0	1	0	1	0	1	-.011	2
305	M7	1	max	1526.181	2	8.115	4	0	1	0	1	0	1	.011	2
306			min	-1652.367	3	1.904	15	0	1	0	1	0	1	0	3
307		2	max	1526.01	2	7.342	4	0	1	0	1	0	1	.009	2
308			min	-1652.495	3	1.723	15	0	1	0	1	0	1	-.002	3
309		3	max	1525.84	2	6.57	4	0	1	0	1	0	1	.006	2
310			min	-1652.623	3	1.541	15	0	1	0	1	0	1	-.004	3
311		4	max	1525.67	2	5.798	4	0	1	0	1	0	1	.004	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
312			min	-1652.75	3	1.36	15	0	1	0	1	0	1	-.005	3
313		5	max	1525.499	2	5.025	4	0	1	0	1	0	1	.002	2
314			min	-1652.878	3	1.178	15	0	1	0	1	0	1	-.006	3
315		6	max	1525.329	2	4.253	4	0	1	0	1	0	1	0	2
316			min	-1653.006	3	.996	15	0	1	0	1	0	1	-.007	3
317		7	max	1525.159	2	3.48	4	0	1	0	1	0	1	-.001	15
318			min	-1653.134	3	.815	15	0	1	0	1	0	1	-.007	3
319		8	max	1524.988	2	2.708	4	0	1	0	1	0	1	-.002	15
320			min	-1653.262	3	.594	12	0	1	0	1	0	1	-.008	3
321		9	max	1524.818	2	2.09	2	0	1	0	1	0	1	-.002	15
322			min	-1653.389	3	.293	12	0	1	0	1	0	1	-.008	4
323		10	max	1524.648	2	1.488	2	0	1	0	1	0	1	-.002	15
324			min	-1653.517	3	-.087	3	0	1	0	1	0	1	-.009	4
325		11	max	1524.477	2	.886	2	0	1	0	1	0	1	-.002	15
326			min	-1653.645	3	-.538	3	0	1	0	1	0	1	-.009	4
327		12	max	1524.307	2	.284	2	0	1	0	1	0	1	-.002	15
328			min	-1653.773	3	-.99	3	0	1	0	1	0	1	-.009	4
329		13	max	1524.137	2	-.275	15	0	1	0	1	0	1	-.002	15
330			min	-1653.9	3	-1.441	3	0	1	0	1	0	1	-.009	4
331		14	max	1523.966	2	-.456	15	0	1	0	1	0	1	-.002	15
332			min	-1654.028	3	-1.927	4	0	1	0	1	0	1	-.008	4
333		15	max	1523.796	2	-.638	15	0	1	0	1	0	1	-.002	15
334			min	-1654.156	3	-2.699	4	0	1	0	1	0	1	-.007	4
335		16	max	1523.626	2	-.819	15	0	1	0	1	0	1	-.001	15
336			min	-1654.284	3	-3.472	4	0	1	0	1	0	1	-.006	4
337		17	max	1523.455	2	-1.001	15	0	1	0	1	0	1	0	15
338			min	-1654.411	3	-4.244	4	0	1	0	1	0	1	-.004	4
339		18	max	1523.285	2	-1.182	15	0	1	0	1	0	1	0	15
340			min	-1654.539	3	-5.016	4	0	1	0	1	0	1	-.002	4
341		19	max	1523.115	2	-1.364	15	0	1	0	1	0	1	0	1
342			min	-1654.667	3	-5.789	4	0	1	0	1	0	1	0	1
343	M8	1	max	3837.269	1	0	1	0	1	0	1	0	1	0	1
344			min	-1454.297	3	0	1	0	1	0	1	0	1	0	1
345		2	max	3837.44	1	0	1	0	1	0	1	0	1	0	1
346			min	-1454.169	3	0	1	0	1	0	1	0	1	0	1
347		3	max	3837.61	1	0	1	0	1	0	1	0	1	0	1
348			min	-1454.041	3	0	1	0	1	0	1	0	1	0	1
349		4	max	3837.78	1	0	1	0	1	0	1	0	1	0	1
350			min	-1453.914	3	0	1	0	1	0	1	0	1	0	1
351		5	max	3837.951	1	0	1	0	1	0	1	0	1	0	1
352			min	-1453.786	3	0	1	0	1	0	1	0	1	0	1
353		6	max	3838.121	1	0	1	0	1	0	1	0	1	0	1
354			min	-1453.658	3	0	1	0	1	0	1	0	1	0	1
355		7	max	3838.291	1	0	1	0	1	0	1	0	1	0	1
356			min	-1453.53	3	0	1	0	1	0	1	0	1	0	1
357		8	max	3838.462	1	0	1	0	1	0	1	0	1	0	1
358			min	-1453.403	3	0	1	0	1	0	1	0	1	0	1
359		9	max	3838.632	1	0	1	0	1	0	1	0	1	0	1
360			min	-1453.275	3	0	1	0	1	0	1	0	1	0	1
361		10	max	3838.802	1	0	1	0	1	0	1	0	1	0	1
362			min	-1453.147	3	0	1	0	1	0	1	0	1	0	1
363		11	max	3838.973	1	0	1	0	1	0	1	0	1	0	1
364			min	-1453.019	3	0	1	0	1	0	1	0	1	0	1
365		12	max	3839.143	1	0	1	0	1	0	1	0	1	0	1
366			min	-1452.892	3	0	1	0	1	0	1	0	1	0	1
367		13	max	3839.314	1	0	1	0	1	0	1	0	1	0	1
368			min	-1452.764	3	0	1	0	1	0	1	0	1	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
369		14	max	3839.484	1	0	1	0	1	0	1	0	1	0	1
370			min	-1452.636	3	0	1	0	1	0	1	0	1	0	1
371		15	max	3839.654	1	0	1	0	1	0	1	0	1	0	1
372			min	-1452.508	3	0	1	0	1	0	1	0	1	0	1
373		16	max	3839.825	1	0	1	0	1	0	1	0	1	0	1
374			min	-1452.38	3	0	1	0	1	0	1	0	1	0	1
375		17	max	3839.995	1	0	1	0	1	0	1	0	1	0	1
376			min	-1452.253	3	0	1	0	1	0	1	0	1	0	1
377		18	max	3840.165	1	0	1	0	1	0	1	0	1	0	1
378			min	-1452.125	3	0	1	0	1	0	1	0	1	0	1
379		19	max	3840.336	1	0	1	0	1	0	1	0	1	0	1
380			min	-1451.997	3	0	1	0	1	0	1	0	1	0	1
381	M10	1	max	1167.571	1	2.281	4	-.033	15	0	1	0	1	0	1
382			min	-1367.164	3	.537	15	-1.012	1	0	3	0	3	0	1
383		2	max	1167.9	1	2.266	4	-.033	15	0	1	0	15	0	15
384			min	-1366.918	3	.534	15	-1.012	1	0	3	0	1	0	4
385		3	max	1168.228	1	2.251	4	-.033	15	0	1	0	15	0	15
386			min	-1366.671	3	.53	15	-1.012	1	0	3	0	1	-.001	4
387		4	max	1168.556	1	2.236	4	-.033	15	0	1	0	15	0	15
388			min	-1366.425	3	.527	15	-1.012	1	0	3	0	1	-.002	4
389		5	max	1168.885	1	2.22	4	-.033	15	0	1	0	15	0	15
390			min	-1366.179	3	.523	15	-1.012	1	0	3	0	1	-.002	4
391		6	max	1169.213	1	2.205	4	-.033	15	0	1	0	15	0	15
392			min	-1365.932	3	.519	15	-1.012	1	0	3	-.001	1	-.002	4
393		7	max	1169.542	1	2.19	4	-.033	15	0	1	0	15	0	15
394			min	-1365.686	3	.516	15	-1.012	1	0	3	-.001	1	-.003	4
395		8	max	1169.87	1	2.174	4	-.033	15	0	1	0	15	0	15
396			min	-1365.44	3	.512	15	-1.012	1	0	3	-.002	1	-.003	4
397		9	max	1170.199	1	2.159	4	-.033	15	0	1	0	15	0	15
398			min	-1365.193	3	.509	15	-1.012	1	0	3	-.002	1	-.004	4
399		10	max	1170.527	1	2.144	4	-.033	15	0	1	0	15	-.001	15
400			min	-1364.947	3	.505	15	-1.012	1	0	3	-.002	1	-.004	4
401		11	max	1170.855	1	2.129	4	-.033	15	0	1	0	15	-.001	15
402			min	-1364.701	3	.501	15	-1.012	1	0	3	-.002	1	-.005	4
403		12	max	1171.184	1	2.113	4	-.033	15	0	1	0	15	-.001	15
404			min	-1364.454	3	.498	15	-1.012	1	0	3	-.002	1	-.005	4
405		13	max	1171.512	1	2.098	4	-.033	15	0	1	0	15	-.001	15
406			min	-1364.208	3	.494	15	-1.012	1	0	3	-.003	1	-.006	4
407		14	max	1171.841	1	2.083	4	-.033	15	0	1	0	15	-.001	15
408			min	-1363.962	3	.491	15	-1.012	1	0	3	-.003	1	-.006	4
409		15	max	1172.169	1	2.068	4	-.033	15	0	1	0	15	-.002	15
410			min	-1363.715	3	.487	15	-1.012	1	0	3	-.003	1	-.007	4
411		16	max	1172.498	1	2.052	4	-.033	15	0	1	0	15	-.002	15
412			min	-1363.469	3	.484	15	-1.012	1	0	3	-.003	1	-.007	4
413		17	max	1172.826	1	2.037	4	-.033	15	0	1	0	15	-.002	15
414			min	-1363.223	3	.48	15	-1.012	1	0	3	-.004	1	-.008	4
415		18	max	1173.155	1	2.022	4	-.033	15	0	1	0	15	-.002	15
416			min	-1362.976	3	.476	15	-1.012	1	0	3	-.004	1	-.008	4
417		19	max	1173.483	1	2.007	4	-.033	15	0	1	0	15	-.002	15
418			min	-1362.73	3	.473	15	-1.012	1	0	3	-.004	1	-.009	4
419	M11	1	max	406.878	2	8.078	4	0	15	0	1	0	15	.009	4
420			min	-526.338	3	1.899	15	-.017	1	0	3	0	1	.002	15
421		2	max	406.708	2	7.306	4	0	15	0	1	0	15	.005	2
422			min	-526.466	3	1.718	15	-.017	1	0	3	0	1	.001	12
423		3	max	406.538	2	6.533	4	0	15	0	1	0	15	.003	2
424			min	-526.593	3	1.536	15	-.017	1	0	3	0	1	0	3
425		4	max	406.367	2	5.761	4	0	15	0	1	0	15	0	2

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
426			min	-526.721	3	1.355	15	-.017	1	0	3	0	1	-.002	3
427		5	max	406.197	2	4.989	4	0	15	0	1	0	15	0	15
428			min	-526.849	3	1.173	15	-.017	1	0	3	0	1	-.003	3
429		6	max	406.027	2	4.216	4	0	15	0	1	0	15	-.001	15
430			min	-526.977	3	.992	15	-.017	1	0	3	0	1	-.004	4
431		7	max	405.856	2	3.444	4	0	15	0	1	0	15	-.001	15
432			min	-527.104	3	.81	15	-.017	1	0	3	0	1	-.006	4
433		8	max	405.686	2	2.671	4	0	15	0	1	0	15	-.002	15
434			min	-527.232	3	.629	15	-.017	1	0	3	0	1	-.007	4
435		9	max	405.516	2	1.899	4	0	15	0	1	0	15	-.002	15
436			min	-527.36	3	.447	15	-.017	1	0	3	0	1	-.008	4
437		10	max	405.345	2	1.126	4	0	15	0	1	0	15	-.002	15
438			min	-527.488	3	.265	15	-.017	1	0	3	0	1	-.009	4
439		11	max	405.175	2	.446	2	0	15	0	1	0	15	-.002	15
440			min	-527.615	3	-.026	3	-.017	1	0	3	0	1	-.009	4
441		12	max	405.005	2	-.098	15	0	15	0	1	0	15	-.002	15
442			min	-527.743	3	-.478	3	-.017	1	0	3	0	1	-.009	4
443		13	max	404.834	2	-.279	15	0	15	0	1	0	15	-.002	15
444			min	-527.871	3	-1.191	4	-.017	1	0	3	0	1	-.009	4
445		14	max	404.664	2	-.461	15	0	15	0	1	0	15	-.002	15
446			min	-527.999	3	-1.963	4	-.017	1	0	3	0	1	-.008	4
447		15	max	404.494	2	-.642	15	0	15	0	1	0	15	-.002	15
448			min	-528.126	3	-2.736	4	-.017	1	0	3	0	1	-.007	4
449		16	max	404.323	2	-.824	15	0	15	0	1	0	15	-.001	15
450			min	-528.254	3	-3.508	4	-.017	1	0	3	0	1	-.006	4
451		17	max	404.153	2	-1.006	15	0	15	0	1	0	15	-.001	15
452			min	-528.382	3	-4.281	4	-.017	1	0	3	0	1	-.004	4
453		18	max	403.983	2	-1.187	15	0	15	0	1	0	15	0	15
454			min	-528.51	3	-5.053	4	-.017	1	0	3	0	1	-.002	4
455		19	max	403.812	2	-1.369	15	0	15	0	1	0	15	0	1
456			min	-528.637	3	-5.825	4	-.017	1	0	3	0	1	0	1
457	M12	1	max	1296.071	1	0	1	6.788	1	0	1	0	10	0	1
458			min	-433.167	3	0	1	.223	15	0	1	0	1	0	1
459		2	max	1296.241	1	0	1	6.788	1	0	1	0	1	0	1
460			min	-433.039	3	0	1	.223	15	0	1	0	15	0	1
461		3	max	1296.412	1	0	1	6.788	1	0	1	.001	1	0	1
462			min	-432.912	3	0	1	.223	15	0	1	0	15	0	1
463		4	max	1296.582	1	0	1	6.788	1	0	1	.002	1	0	1
464			min	-432.784	3	0	1	.223	15	0	1	0	15	0	1
465		5	max	1296.752	1	0	1	6.788	1	0	1	.003	1	0	1
466			min	-432.656	3	0	1	.223	15	0	1	0	15	0	1
467		6	max	1296.923	1	0	1	6.788	1	0	1	.004	1	0	1
468			min	-432.528	3	0	1	.223	15	0	1	0	15	0	1
469		7	max	1297.093	1	0	1	6.788	1	0	1	.005	1	0	1
470			min	-432.401	3	0	1	.223	15	0	1	0	15	0	1
471		8	max	1297.263	1	0	1	6.788	1	0	1	.005	1	0	1
472			min	-432.273	3	0	1	.223	15	0	1	0	15	0	1
473		9	max	1297.434	1	0	1	6.788	1	0	1	.006	1	0	1
474			min	-432.145	3	0	1	.223	15	0	1	0	15	0	1
475		10	max	1297.604	1	0	1	6.788	1	0	1	.007	1	0	1
476			min	-432.017	3	0	1	.223	15	0	1	0	15	0	1
477		11	max	1297.775	1	0	1	6.788	1	0	1	.008	1	0	1
478			min	-431.89	3	0	1	.223	15	0	1	0	15	0	1
479		12	max	1297.945	1	0	1	6.788	1	0	1	.008	1	0	1
480			min	-431.762	3	0	1	.223	15	0	1	0	15	0	1
481		13	max	1298.115	1	0	1	6.788	1	0	1	.009	1	0	1
482			min	-431.634	3	0	1	.223	15	0	1	0	15	0	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
483		14	max	1298.286	1	0	1	6.788	1	0	1	.01	1	0	1
484			min	-431.506	3	0	1	.223	15	0	1	0	15	0	1
485		15	max	1298.456	1	0	1	6.788	1	0	1	.011	1	0	1
486			min	-431.379	3	0	1	.223	15	0	1	0	15	0	1
487		16	max	1298.626	1	0	1	6.788	1	0	1	.012	1	0	1
488			min	-431.251	3	0	1	.223	15	0	1	0	15	0	1
489		17	max	1298.797	1	0	1	6.788	1	0	1	.012	1	0	1
490			min	-431.123	3	0	1	.223	15	0	1	0	15	0	1
491		18	max	1298.967	1	0	1	6.788	1	0	1	.013	1	0	1
492			min	-430.995	3	0	1	.223	15	0	1	0	15	0	1
493		19	max	1299.137	1	0	1	6.788	1	0	1	.014	1	0	1
494			min	-430.868	3	0	1	.223	15	0	1	0	15	0	1
495	M1	1	max	125.586	1	767.773	3	-2.335	15	0	1	.168	1	0	3
496			min	4.106	15	-529.605	1	-70.883	1	0	3	.006	15	-.016	2
497		2	max	125.957	1	766.736	3	-2.335	15	0	1	.131	1	.265	1
498			min	4.217	15	-530.989	1	-70.883	1	0	3	.004	15	-.404	3
499		3	max	314.212	3	603.235	1	-2.302	15	0	3	.094	1	.532	1
500			min	-190.909	2	-568.848	3	-70.043	1	0	1	.003	15	-.792	3
501		4	max	314.49	3	601.851	1	-2.302	15	0	3	.057	1	.214	1
502			min	-190.538	2	-569.885	3	-70.043	1	0	1	.002	15	-.492	3
503		5	max	314.768	3	600.467	1	-2.302	15	0	3	.02	1	-.004	15
504			min	-190.168	2	-570.923	3	-70.043	1	0	1	0	15	-.191	3
505		6	max	315.046	3	599.084	1	-2.302	15	0	3	0	15	.111	3
506			min	-189.797	2	-571.961	3	-70.043	1	0	1	-.017	1	-.427	2
507		7	max	315.324	3	597.7	1	-2.302	15	0	3	-.002	15	.413	3
508			min	-189.426	2	-572.998	3	-70.043	1	0	1	-.054	1	-.736	1
509		8	max	315.602	3	596.317	1	-2.302	15	0	3	-.003	15	.715	3
510			min	-189.055	2	-574.036	3	-70.043	1	0	1	-.091	1	-1.051	1
511		9	max	323.227	3	51.317	2	-3.445	15	0	9	.055	1	.834	3
512			min	-139.073	2	.42	15	-104.764	1	0	3	.002	15	-1.198	1
513		10	max	323.505	3	49.933	2	-3.445	15	0	9	0	15	.814	3
514			min	-138.702	2	.002	15	-104.764	1	0	3	0	1	-1.212	1
515		11	max	323.783	3	48.549	2	-3.445	15	0	9	-.002	15	.794	3
516			min	-138.331	2	-1.72	4	-104.764	1	0	3	-.056	1	-1.226	2
517		12	max	331.332	3	384.146	3	-2.248	15	0	2	.09	1	.693	3
518			min	-88.32	2	-671.786	2	-68.532	1	0	3	.003	15	-1.087	2
519		13	max	331.61	3	383.108	3	-2.248	15	0	2	.054	1	.49	3
520			min	-87.949	2	-673.17	2	-68.532	1	0	3	.002	15	-.739	1
521		14	max	331.888	3	382.071	3	-2.248	15	0	2	.018	1	.288	3
522			min	-87.578	2	-674.554	2	-68.532	1	0	3	0	15	-.394	1
523		15	max	332.166	3	381.033	3	-2.248	15	0	2	0	15	.087	3
524			min	-87.207	2	-675.937	2	-68.532	1	0	3	-.018	1	-.049	1
525		16	max	332.444	3	379.995	3	-2.248	15	0	2	-.002	15	.337	2
526			min	-86.837	2	-677.321	2	-68.532	1	0	3	-.054	1	-.114	3
527		17	max	332.722	3	378.958	3	-2.248	15	0	2	-.003	15	.695	2
528			min	-86.466	2	-678.704	2	-68.532	1	0	3	-.091	1	-.314	3
529		18	max	-4.222	15	684.694	2	-2.47	15	0	3	-.004	15	.349	2
530			min	-126.162	1	-316.817	3	-75.063	1	0	2	-.13	1	-.155	3
531		19	max	-4.11	15	683.31	2	-2.47	15	0	3	-.006	15	.012	3
532			min	-125.791	1	-317.854	3	-75.063	1	0	2	-.169	1	-.013	1
533	M5	1	max	273.579	1	2560.505	3	0	1	0	1	0	1	.032	2
534			min	7.704	12	-1801.315	1	0	1	0	1	0	1	-.001	3
535		2	max	273.95	1	2559.468	3	0	1	0	1	0	1	.981	1
536			min	7.89	12	-1802.699	1	0	1	0	1	0	1	-1.352	3
537		3	max	1005.123	3	1812.646	1	0	1	0	1	0	1	1.889	1
538			min	-661.981	2	-1798.261	3	0	1	0	1	0	1	-2.65	3
539		4	max	1005.401	3	1811.262	1	0	1	0	1	0	1	.933	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
540			min	-661.61	2	-1799.299	3	0	1	0	1	0	1	-1.701	3
541		5	max	1005.679	3	1809.879	1	0	1	0	1	0	1	.019	9
542			min	-661.239	2	-1800.337	3	0	1	0	1	0	1	-.751	3
543		6	max	1005.957	3	1808.495	1	0	1	0	1	0	1	.199	3
544			min	-660.868	2	-1801.374	3	0	1	0	1	0	1	-.998	2
545		7	max	1006.235	3	1807.111	1	0	1	0	1	0	1	1.15	3
546			min	-660.498	2	-1802.412	3	0	1	0	1	0	1	-1.931	1
547		8	max	1006.513	3	1805.728	1	0	1	0	1	0	1	2.101	3
548			min	-660.127	2	-1803.45	3	0	1	0	1	0	1	-2.884	1
549		9	max	1017.757	3	172.013	2	0	1	0	1	0	1	2.416	3
550			min	-556.006	2	.417	15	0	1	0	1	0	1	-3.267	1
551		10	max	1018.035	3	170.63	2	0	1	0	1	0	1	2.343	3
552			min	-555.636	2	0	15	0	1	0	1	0	1	-3.314	1
553		11	max	1018.313	3	169.246	2	0	1	0	1	0	1	2.271	3
554			min	-555.265	2	-1.628	4	0	1	0	1	0	1	-3.367	2
555		12	max	1029.708	3	1193.046	3	0	1	0	1	0	1	1.994	3
556			min	-451.202	2	-2052.465	2	0	1	0	1	0	1	-3.015	2
557		13	max	1029.986	3	1192.009	3	0	1	0	1	0	1	1.364	3
558			min	-450.831	2	-2053.849	2	0	1	0	1	0	1	-1.949	1
559		14	max	1030.264	3	1190.971	3	0	1	0	1	0	1	.736	3
560			min	-450.46	2	-2055.232	2	0	1	0	1	0	1	-.9	1
561		15	max	1030.542	3	1189.933	3	0	1	0	1	0	1	.238	2
562			min	-450.089	2	-2056.616	2	0	1	0	1	0	1	-.003	13
563		16	max	1030.82	3	1188.895	3	0	1	0	1	0	1	1.323	2
564			min	-449.719	2	-2058	2	0	1	0	1	0	1	-.52	3
565		17	max	1031.098	3	1187.858	3	0	1	0	1	0	1	2.41	2
566			min	-449.348	2	-2059.383	2	0	1	0	1	0	1	-1.147	3
567		18	max	-8.2	12	2311.425	2	0	1	0	1	0	1	1.242	2
568			min	-273.54	1	-1090.372	3	0	1	0	1	0	1	-.6	3
569		19	max	-8.014	12	2310.042	2	0	1	0	1	0	1	.026	1
570			min	-273.169	1	-1091.41	3	0	1	0	1	0	1	-.024	3
571	M9	1	max	125.586	1	767.773	3	70.883	1	0	3	-.006	15	0	3
572			min	4.106	15	-529.605	1	2.335	15	0	1	-.168	1	-.016	2
573		2	max	125.957	1	766.736	3	70.883	1	0	3	-.004	15	.265	1
574			min	4.217	15	-530.989	1	2.335	15	0	1	-.131	1	-.404	3
575		3	max	314.212	3	603.235	1	70.043	1	0	1	-.003	15	.532	1
576			min	-190.909	2	-568.848	3	2.302	15	0	3	-.094	1	-.792	3
577		4	max	314.49	3	601.851	1	70.043	1	0	1	-.002	15	.214	1
578			min	-190.538	2	-569.885	3	2.302	15	0	3	-.057	1	-.492	3
579		5	max	314.768	3	600.467	1	70.043	1	0	1	0	15	-.004	15
580			min	-190.168	2	-570.923	3	2.302	15	0	3	-.02	1	-.191	3
581		6	max	315.046	3	599.084	1	70.043	1	0	1	.017	1	.111	3
582			min	-189.797	2	-571.961	3	2.302	15	0	3	0	15	-.427	2
583		7	max	315.324	3	597.7	1	70.043	1	0	1	.054	1	.413	3
584			min	-189.426	2	-572.998	3	2.302	15	0	3	.002	15	-.736	1
585		8	max	315.602	3	596.317	1	70.043	1	0	1	.091	1	.715	3
586			min	-189.055	2	-574.036	3	2.302	15	0	3	.003	15	-1.051	1
587		9	max	323.227	3	51.317	2	104.764	1	0	3	-.002	15	.834	3
588			min	-139.073	2	.42	15	3.445	15	0	9	-.055	1	-1.198	1
589		10	max	323.505	3	49.933	2	104.764	1	0	3	0	1	.814	3
590			min	-138.702	2	.002	15	3.445	15	0	9	0	15	-1.212	1
591		11	max	323.783	3	48.549	2	104.764	1	0	3	.056	1	.794	3
592			min	-138.331	2	-1.72	4	3.445	15	0	9	.002	15	-1.226	2
593		12	max	331.332	3	384.146	3	68.532	1	0	3	-.003	15	.693	3
594			min	-88.32	2	-671.786	2	2.248	15	0	2	-.09	1	-1.087	2
595		13	max	331.61	3	383.108	3	68.532	1	0	3	-.002	15	.49	3
596			min	-87.949	2	-673.17	2	2.248	15	0	2	-.054	1	-.739	1

Envelope Member Section Forces (Continued)

	Member	Sec		Axial[lb]	LC	y Shear[lb]	LC	z Shear[lb]	LC	Torque[k-ft]	LC	y-y Mome...	LC	z-z Mome...	LC
597		14	max	331.888	3	382.071	3	68.532	1	0	3	0	15	.288	3
598			min	-87.578	2	-674.554	2	2.248	15	0	2	-.018	1	-.394	1
599		15	max	332.166	3	381.033	3	68.532	1	0	3	.018	1	.087	3
600			min	-87.207	2	-675.937	2	2.248	15	0	2	0	15	-.049	1
601		16	max	332.444	3	379.995	3	68.532	1	0	3	.054	1	.337	2
602			min	-86.837	2	-677.321	2	2.248	15	0	2	.002	15	-.114	3
603		17	max	332.722	3	378.958	3	68.532	1	0	3	.091	1	.695	2
604			min	-86.466	2	-678.704	2	2.248	15	0	2	.003	15	-.314	3
605		18	max	-4.222	15	684.694	2	75.063	1	0	2	.13	1	.349	2
606			min	-126.162	1	-316.817	3	2.47	15	0	3	.004	15	-.155	3
607		19	max	-4.11	15	683.31	2	75.063	1	0	2	.169	1	.012	3
608			min	-125.791	1	-317.854	3	2.47	15	0	3	.006	15	-.013	1

Envelope Member Section Deflections

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
1	M13	1	max	0	1	.127	2	.006	3	1.021e-2	2	NC	1	NC	1
2			min	0	15	-.029	3	-.003	2	-2.243e-3	3	NC	1	NC	1
3		2	max	0	1	.257	3	.024	1	1.163e-2	2	NC	5	NC	2
4			min	0	15	-.051	1	0	10	-2.305e-3	3	776.078	3	9736.598	1
5		3	max	0	1	.488	3	.056	1	1.306e-2	2	NC	5	NC	2
6			min	0	15	-.189	1	.002	15	-2.366e-3	3	429.071	3	4024.268	1
7		4	max	0	1	.628	3	.084	1	1.449e-2	2	NC	5	NC	3
8			min	0	15	-.265	1	.003	15	-2.428e-3	3	337.75	3	2677.131	1
9		5	max	0	1	.659	3	.098	1	1.591e-2	2	NC	5	NC	3
10			min	0	15	-.266	1	.003	15	-2.49e-3	3	322.394	3	2289.712	1
11		6	max	0	1	.584	3	.094	1	1.734e-2	2	NC	5	NC	3
12			min	0	15	-.195	1	.003	15	-2.552e-3	3	361.685	3	2382.448	1
13		7	max	0	1	.426	3	.074	1	1.877e-2	2	NC	5	NC	3
14			min	0	15	-.068	1	.001	10	-2.614e-3	3	487.965	3	3058.993	1
15		8	max	0	1	.224	3	.042	1	2.019e-2	2	NC	2	NC	2
16			min	0	15	.002	15	-.002	10	-2.676e-3	3	874.87	3	5395.329	1
17		9	max	0	1	.235	2	.018	3	2.162e-2	2	NC	4	NC	1
18			min	0	15	.005	15	-.006	10	-2.737e-3	3	2049.063	2	NC	1
19		10	max	0	1	.29	2	.017	3	2.305e-2	2	NC	3	NC	1
20			min	0	1	-.04	3	-.011	2	-2.799e-3	3	1361.355	2	NC	1
21		11	max	0	15	.235	2	.018	3	2.162e-2	2	NC	4	NC	1
22			min	0	1	.005	15	-.006	10	-2.737e-3	3	2049.063	2	NC	1
23		12	max	0	15	.224	3	.042	1	2.019e-2	2	NC	2	NC	2
24			min	0	1	.002	15	-.002	10	-2.676e-3	3	874.87	3	5395.329	1
25		13	max	0	15	.426	3	.074	1	1.877e-2	2	NC	5	NC	3
26			min	0	1	-.068	1	.001	10	-2.614e-3	3	487.965	3	3058.993	1
27		14	max	0	15	.584	3	.094	1	1.734e-2	2	NC	5	NC	3
28			min	0	1	-.195	1	.003	15	-2.552e-3	3	361.685	3	2382.448	1
29		15	max	0	15	.659	3	.098	1	1.591e-2	2	NC	5	NC	3
30			min	0	1	-.266	1	.003	15	-2.49e-3	3	322.394	3	2289.712	1
31		16	max	0	15	.628	3	.084	1	1.449e-2	2	NC	5	NC	3
32			min	0	1	-.265	1	.003	15	-2.428e-3	3	337.75	3	2677.131	1
33		17	max	0	15	.488	3	.056	1	1.306e-2	2	NC	5	NC	2
34			min	0	1	-.189	1	.002	15	-2.366e-3	3	429.071	3	4024.268	1
35		18	max	0	15	.257	3	.024	1	1.163e-2	2	NC	5	NC	2
36			min	0	1	-.051	1	0	10	-2.305e-3	3	776.078	3	9736.598	1
37		19	max	0	15	.127	2	.006	3	1.021e-2	2	NC	1	NC	1
38			min	0	1	-.029	3	-.003	2	-2.243e-3	3	NC	1	NC	1
39	M14	1	max	0	1	.248	3	.005	3	6.057e-3	1	NC	1	NC	1
40			min	0	15	-.394	1	-.002	2	-4.442e-3	3	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
41		2	max	0	1	.544	3	.016	1	7.223e-3	1	NC	5	NC	1
42			min	0	15	-.704	1	0	10	-5.37e-3	3	715.773	1	NC	1
43		3	max	0	1	.795	3	.045	1	8.389e-3	1	NC	5	NC	2
44			min	0	15	-.973	1	.002	15	-6.297e-3	3	383.248	1	5080.22	1
45		4	max	0	1	.973	3	.071	1	9.555e-3	1	NC	15	NC	3
46			min	0	15	-1.173	1	.002	15	-7.225e-3	3	285.032	1	3154.941	1
47		5	max	0	1	1.062	3	.087	1	1.072e-2	1	NC	15	NC	3
48			min	0	15	-1.288	1	.003	15	-8.152e-3	3	248.259	1	2598.259	1
49		6	max	0	1	1.061	3	.085	1	1.189e-2	1	NC	15	NC	3
50			min	0	15	-1.319	1	.003	15	-9.08e-3	3	240.161	1	2638.669	1
51		7	max	0	1	.987	3	.068	1	1.305e-2	1	NC	15	NC	2
52			min	0	15	-1.276	1	.001	10	-1.001e-2	3	251.682	1	3328.67	1
53		8	max	0	1	.869	3	.04	1	1.422e-2	1	NC	15	NC	2
54			min	0	15	-1.188	1	-.002	10	-1.094e-2	3	279.682	1	5778.022	1
55		9	max	0	1	.752	3	.016	3	1.538e-2	1	NC	15	NC	1
56			min	0	15	-1.094	1	-.005	10	-1.186e-2	3	317.287	1	NC	1
57		10	max	0	1	.696	3	.016	3	1.655e-2	1	NC	5	NC	1
58			min	0	1	-1.048	1	-.01	2	-1.279e-2	3	339.559	1	NC	1
59		11	max	0	15	.752	3	.016	3	1.538e-2	1	NC	15	NC	1
60			min	0	1	-1.094	1	-.005	10	-1.186e-2	3	317.287	1	NC	1
61		12	max	0	15	.869	3	.04	1	1.422e-2	1	NC	15	NC	2
62			min	0	1	-1.188	1	-.002	10	-1.094e-2	3	279.682	1	5778.022	1
63		13	max	0	15	.987	3	.068	1	1.305e-2	1	NC	15	NC	2
64			min	0	1	-1.276	1	.001	10	-1.001e-2	3	251.682	1	3328.67	1
65		14	max	0	15	1.061	3	.085	1	1.189e-2	1	NC	15	NC	3
66			min	0	1	-1.319	1	.003	15	-9.08e-3	3	240.161	1	2638.669	1
67		15	max	0	15	1.062	3	.087	1	1.072e-2	1	NC	15	NC	3
68			min	0	1	-1.288	1	.003	15	-8.152e-3	3	248.259	1	2598.259	1
69		16	max	0	15	.973	3	.071	1	9.555e-3	1	NC	15	NC	3
70			min	0	1	-1.173	1	.002	15	-7.225e-3	3	285.032	1	3154.941	1
71		17	max	0	15	.795	3	.045	1	8.389e-3	1	NC	5	NC	2
72			min	0	1	-.973	1	.002	15	-6.297e-3	3	383.248	1	5080.22	1
73		18	max	0	15	.544	3	.016	1	7.223e-3	1	NC	5	NC	1
74			min	0	1	-.704	1	0	10	-5.37e-3	3	715.773	1	NC	1
75		19	max	0	15	.248	3	.005	3	6.057e-3	1	NC	1	NC	1
76			min	0	1	-.394	1	-.002	2	-4.442e-3	3	NC	1	NC	1
77	M15	1	max	0	15	.254	3	.005	3	3.778e-3	3	NC	1	NC	1
78			min	0	1	-.394	1	-.002	2	-6.179e-3	1	NC	1	NC	1
79		2	max	0	15	.451	3	.016	1	4.567e-3	3	NC	5	NC	1
80			min	0	1	-.755	2	0	10	-7.373e-3	1	607.786	2	NC	1
81		3	max	0	15	.623	3	.045	1	5.356e-3	3	NC	5	NC	2
82			min	0	1	-1.069	2	.002	15	-8.567e-3	1	327.067	2	5063.914	1
83		4	max	0	15	.753	3	.072	1	6.145e-3	3	NC	15	NC	3
84			min	0	1	-1.295	2	.002	15	-9.761e-3	1	245.343	2	3146.343	1
85		5	max	0	15	.832	3	.087	1	6.934e-3	3	NC	15	NC	3
86			min	0	1	-1.416	2	.003	15	-1.095e-2	1	216.483	2	2591.197	1
87		6	max	0	15	.858	3	.085	1	7.723e-3	3	NC	15	NC	3
88			min	0	1	-1.43	2	.003	15	-1.215e-2	1	213.425	2	2630.429	1
89		7	max	0	15	.839	3	.068	1	8.512e-3	3	NC	15	NC	2
90			min	0	1	-1.356	2	.001	10	-1.334e-2	1	229.806	2	3314.482	1
91		8	max	0	15	.791	3	.04	1	9.301e-3	3	NC	15	NC	2
92			min	0	1	-1.228	2	-.002	10	-1.454e-2	1	264.999	2	5733.293	1
93		9	max	0	15	.738	3	.015	3	1.009e-2	3	NC	15	NC	1
94			min	0	1	-1.104	1	-.005	10	-1.573e-2	1	312.623	1	NC	1
95		10	max	0	1	.711	3	.015	3	1.088e-2	3	NC	5	NC	1
96			min	0	1	-1.047	1	-.009	2	-1.692e-2	1	339.845	1	NC	1
97		11	max	0	1	.738	3	.015	3	1.009e-2	3	NC	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
98			min	0	15	-1.104	1	-.005	10	-1.573e-2	1	312.623	1	NC	1
99		12	max	0	1	.791	3	.04	1	9.301e-3	3	NC	15	NC	2
100			min	0	15	-1.228	2	-.002	10	-1.454e-2	1	264.999	2	5733.293	1
101		13	max	0	1	.839	3	.068	1	8.512e-3	3	NC	15	NC	2
102			min	0	15	-1.356	2	.001	10	-1.334e-2	1	229.806	2	3314.482	1
103		14	max	0	1	.858	3	.085	1	7.723e-3	3	NC	15	NC	3
104			min	0	15	-1.43	2	.003	15	-1.215e-2	1	213.425	2	2630.429	1
105		15	max	0	1	.832	3	.087	1	6.934e-3	3	NC	15	NC	3
106			min	0	15	-1.416	2	.003	15	-1.095e-2	1	216.483	2	2591.197	1
107		16	max	0	1	.753	3	.072	1	6.145e-3	3	NC	15	NC	3
108			min	0	15	-1.295	2	.002	15	-9.761e-3	1	245.343	2	3146.343	1
109		17	max	0	1	.623	3	.045	1	5.356e-3	3	NC	5	NC	2
110			min	0	15	-1.069	2	.002	15	-8.567e-3	1	327.067	2	5063.914	1
111		18	max	0	1	.451	3	.016	1	4.567e-3	3	NC	5	NC	1
112			min	0	15	-.755	2	0	10	-7.373e-3	1	607.786	2	NC	1
113		19	max	0	1	.254	3	.005	3	3.778e-3	3	NC	1	NC	1
114			min	0	15	-.394	1	-.002	2	-6.179e-3	1	NC	1	NC	1
115	M16	1	max	0	15	.118	1	.004	3	6.688e-3	3	NC	1	NC	1
116			min	0	1	-.085	3	-.002	2	-9.079e-3	1	NC	1	NC	1
117		2	max	0	15	.015	3	.024	1	7.77e-3	3	NC	5	NC	2
118			min	0	1	-.126	2	0	10	-1.024e-2	1	937.73	2	9781.414	1
119		3	max	0	15	.093	3	.056	1	8.851e-3	3	NC	5	NC	2
120			min	0	1	-.314	2	.002	15	-1.14e-2	1	522.466	2	4028.647	1
121		4	max	0	15	.133	3	.084	1	9.933e-3	3	NC	5	NC	3
122			min	0	1	-.421	2	.003	15	-1.256e-2	1	417.263	2	2674.002	1
123		5	max	0	15	.129	3	.098	1	1.101e-2	3	NC	5	NC	3
124			min	0	1	-.432	2	.003	15	-1.372e-2	1	408.647	2	2281.944	1
125		6	max	0	15	.082	3	.095	1	1.21e-2	3	NC	5	NC	3
126			min	0	1	-.35	2	.003	15	-1.488e-2	1	481.281	2	2367.142	1
127		7	max	0	15	.003	12	.074	1	1.318e-2	3	NC	5	NC	3
128			min	0	1	-.196	2	.002	10	-1.604e-2	1	724.622	2	3022.422	1
129		8	max	0	15	.031	1	.043	1	1.426e-2	3	NC	3	NC	2
130			min	0	1	-.092	3	0	10	-1.72e-2	1	1906.866	2	5252.324	1
131		9	max	0	15	.19	1	.013	3	1.534e-2	3	NC	4	NC	1
132			min	0	1	-.175	3	-.004	10	-1.837e-2	1	2449.959	3	NC	1
133		10	max	0	1	.261	1	.013	3	1.642e-2	3	NC	5	NC	1
134			min	0	1	-.212	3	-.009	2	-1.953e-2	1	1552.304	1	NC	1
135		11	max	0	1	.19	1	.013	3	1.534e-2	3	NC	4	NC	1
136			min	0	15	-.175	3	-.004	10	-1.837e-2	1	2449.959	3	NC	1
137		12	max	0	1	.031	1	.043	1	1.426e-2	3	NC	3	NC	2
138			min	0	15	-.092	3	0	10	-1.72e-2	1	1906.866	2	5252.324	1
139		13	max	0	1	.003	12	.074	1	1.318e-2	3	NC	5	NC	3
140			min	0	15	-.196	2	.002	10	-1.604e-2	1	724.622	2	3022.422	1
141		14	max	0	1	.082	3	.095	1	1.21e-2	3	NC	5	NC	3
142			min	0	15	-.35	2	.003	15	-1.488e-2	1	481.281	2	2367.142	1
143		15	max	0	1	.129	3	.098	1	1.101e-2	3	NC	5	NC	3
144			min	0	15	-.432	2	.003	15	-1.372e-2	1	408.647	2	2281.944	1
145		16	max	0	1	.133	3	.084	1	9.933e-3	3	NC	5	NC	3
146			min	0	15	-.421	2	.003	15	-1.256e-2	1	417.263	2	2674.002	1
147		17	max	0	1	.093	3	.056	1	8.851e-3	3	NC	5	NC	2
148			min	0	15	-.314	2	.002	15	-1.14e-2	1	522.466	2	4028.647	1
149		18	max	0	1	.015	3	.024	1	7.77e-3	3	NC	5	NC	2
150			min	0	15	-.126	2	0	10	-1.024e-2	1	937.73	2	9781.414	1
151		19	max	0	1	.118	1	.004	3	6.688e-3	3	NC	1	NC	1
152			min	0	15	-.085	3	-.002	2	-9.079e-3	1	NC	1	NC	1
153	M2	1	max	.005	1	.004	2	.005	1	-4.52e-6	15	NC	1	NC	2
154			min	-.006	3	-.007	3	0	15	-1.376e-4	1	NC	1	8777.198	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
155		2	max	.005	1	.003	2	.005	1	-4.189e-6	15	NC	1	NC	2
156			min	-.006	3	-.007	3	0	15	-1.275e-4	1	NC	1	9571.622	1
157		3	max	.005	1	.003	2	.005	1	-3.858e-6	15	NC	1	NC	1
158			min	-.006	3	-.007	3	0	15	-1.174e-4	1	NC	1	NC	1
159		4	max	.004	1	.002	2	.004	1	-3.527e-6	15	NC	1	NC	1
160			min	-.005	3	-.006	3	0	15	-1.073e-4	1	NC	1	NC	1
161		5	max	.004	1	.002	2	.004	1	-3.197e-6	15	NC	1	NC	1
162			min	-.005	3	-.006	3	0	15	-9.724e-5	1	NC	1	NC	1
163		6	max	.004	1	.001	2	.003	1	-2.866e-6	15	NC	1	NC	1
164			min	-.005	3	-.006	3	0	15	-8.715e-5	1	NC	1	NC	1
165		7	max	.004	1	0	2	.003	1	-2.535e-6	15	NC	1	NC	1
166			min	-.004	3	-.005	3	0	15	-7.706e-5	1	NC	1	NC	1
167		8	max	.003	1	0	2	.002	1	-2.204e-6	15	NC	1	NC	1
168			min	-.004	3	-.005	3	0	15	-6.698e-5	1	NC	1	NC	1
169		9	max	.003	1	0	2	.002	1	-1.873e-6	15	NC	1	NC	1
170			min	-.003	3	-.005	3	0	15	-5.689e-5	1	NC	1	NC	1
171		10	max	.003	1	0	2	.002	1	-1.542e-6	15	NC	1	NC	1
172			min	-.003	3	-.004	3	0	15	-4.68e-5	1	NC	1	NC	1
173		11	max	.002	1	0	2	.001	1	-1.211e-6	15	NC	1	NC	1
174			min	-.003	3	-.004	3	0	15	-3.672e-5	1	NC	1	NC	1
175		12	max	.002	1	0	15	.001	1	-8.801e-7	15	NC	1	NC	1
176			min	-.002	3	-.004	3	0	15	-2.663e-5	1	NC	1	NC	1
177		13	max	.002	1	0	15	0	1	-5.492e-7	15	NC	1	NC	1
178			min	-.002	3	-.003	3	0	15	-1.654e-5	1	NC	1	NC	1
179		14	max	.001	1	0	15	0	1	-2.183e-7	15	NC	1	NC	1
180			min	-.002	3	-.003	3	0	15	-6.458e-6	1	NC	1	NC	1
181		15	max	.001	1	0	15	0	1	3.629e-6	1	NC	1	NC	1
182			min	-.001	3	-.002	3	0	15	-3.171e-7	3	NC	1	NC	1
183		16	max	0	1	0	15	0	1	1.372e-5	1	NC	1	NC	1
184			min	-.001	3	-.002	3	0	15	3.126e-7	12	NC	1	NC	1
185		17	max	0	1	0	15	0	1	2.38e-5	1	NC	1	NC	1
186			min	0	3	-.001	3	0	15	7.745e-7	15	NC	1	NC	1
187		18	max	0	1	0	15	0	1	3.389e-5	1	NC	1	NC	1
188			min	0	3	0	4	0	15	1.105e-6	15	NC	1	NC	1
189		19	max	0	1	0	1	0	1	4.398e-5	1	NC	1	NC	1
190			min	0	1	0	1	0	1	1.436e-6	15	NC	1	NC	1
191	M3	1	max	0	1	0	1	0	1	-4.471e-7	15	NC	1	NC	1
192			min	0	1	0	1	0	1	-1.368e-5	1	NC	1	NC	1
193		2	max	0	3	0	15	0	1	3.725e-6	1	NC	1	NC	1
194			min	0	2	-.001	4	0	15	1.227e-7	15	NC	1	NC	1
195		3	max	0	3	0	15	0	1	2.113e-5	1	NC	1	NC	1
196			min	0	2	-.003	4	0	15	6.924e-7	15	NC	1	NC	1
197		4	max	0	3	-.001	15	0	1	3.853e-5	1	NC	1	NC	1
198			min	0	2	-.005	4	0	15	1.262e-6	15	NC	1	NC	1
199		5	max	.001	3	-.002	15	0	1	5.594e-5	1	NC	1	NC	1
200			min	0	2	-.007	4	0	15	1.832e-6	15	NC	1	NC	1
201		6	max	.001	3	-.002	15	.001	1	7.334e-5	1	NC	1	NC	1
202			min	0	2	-.009	4	0	15	2.402e-6	15	NC	1	NC	1
203		7	max	.002	3	-.002	15	.001	1	9.075e-5	1	NC	1	NC	1
204			min	-.001	2	-.01	4	0	15	2.971e-6	15	9289.431	4	NC	1
205		8	max	.002	3	-.003	15	.002	1	1.082e-4	1	NC	1	NC	1
206			min	-.001	2	-.011	4	0	15	3.541e-6	15	8280.337	4	NC	1
207		9	max	.002	3	-.003	15	.002	1	1.256e-4	1	NC	1	NC	1
208			min	-.002	2	-.012	4	0	15	4.111e-6	15	7677.314	4	NC	1
209		10	max	.002	3	-.003	15	.002	1	1.43e-4	1	NC	2	NC	1
210			min	-.002	2	-.013	4	0	15	4.681e-6	15	7373.192	4	NC	1
211		11	max	.003	3	-.003	15	.003	1	1.604e-4	1	NC	2	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
212			min	-.002	2	-.013	4	0	15	5.251e-6	15	7322.368	4	NC	1
213		12	max	.003	3	-.003	15	.003	1	1.778e-4	1	NC	1	NC	1
214			min	-.002	2	-.013	4	0	15	5.82e-6	15	7523.187	4	NC	1
215		13	max	.003	3	-.003	15	.003	1	1.952e-4	1	NC	1	NC	1
216			min	-.002	2	-.012	4	0	15	6.39e-6	15	8019.446	4	NC	1
217		14	max	.003	3	-.002	15	.003	1	2.126e-4	1	NC	1	NC	1
218			min	-.003	2	-.011	4	0	15	6.96e-6	15	8923.752	4	NC	1
219		15	max	.004	3	-.002	15	.004	1	2.3e-4	1	NC	1	NC	1
220			min	-.003	2	-.009	4	0	15	7.53e-6	15	NC	1	NC	1
221		16	max	.004	3	-.002	15	.004	1	2.474e-4	1	NC	1	NC	1
222			min	-.003	2	-.008	1	0	15	8.099e-6	15	NC	1	NC	1
223		17	max	.004	3	-.001	15	.004	1	2.648e-4	1	NC	1	NC	1
224			min	-.003	2	-.006	1	0	15	8.669e-6	15	NC	1	NC	1
225		18	max	.004	3	0	15	.005	1	2.822e-4	1	NC	1	NC	1
226			min	-.003	2	-.005	1	0	15	9.239e-6	15	NC	1	NC	1
227		19	max	.005	3	0	15	.005	1	2.996e-4	1	NC	1	NC	1
228			min	-.004	2	-.003	1	0	15	9.809e-6	15	NC	1	NC	1
229	M4	1	max	.003	1	.003	2	0	15	-1.432e-7	12	NC	1	NC	2
230			min	-.001	3	-.005	3	-.005	1	-8.018e-6	1	NC	1	4743.156	1
231		2	max	.003	1	.003	2	0	15	-1.432e-7	12	NC	1	NC	2
232			min	0	3	-.004	3	-.005	1	-8.018e-6	1	NC	1	5166.083	1
233		3	max	.003	1	.003	2	0	15	-1.432e-7	12	NC	1	NC	2
234			min	0	3	-.004	3	-.004	1	-8.018e-6	1	NC	1	5668.978	1
235		4	max	.003	1	.002	2	0	15	-1.432e-7	12	NC	1	NC	2
236			min	0	3	-.004	3	-.004	1	-8.018e-6	1	NC	1	6272.697	1
237		5	max	.002	1	.002	2	0	15	-1.432e-7	12	NC	1	NC	2
238			min	0	3	-.004	3	-.004	1	-8.018e-6	1	NC	1	7005.58	1
239		6	max	.002	1	.002	2	0	15	-1.432e-7	12	NC	1	NC	2
240			min	0	3	-.003	3	-.003	1	-8.018e-6	1	NC	1	7906.931	1
241		7	max	.002	1	.002	2	0	15	-1.432e-7	12	NC	1	NC	2
242			min	0	3	-.003	3	-.003	1	-8.018e-6	1	NC	1	9032.543	1
243		8	max	.002	1	.002	2	0	15	-1.432e-7	12	NC	1	NC	1
244			min	0	3	-.003	3	-.002	1	-8.018e-6	1	NC	1	NC	1
245		9	max	.002	1	.002	2	0	15	-1.432e-7	12	NC	1	NC	1
246			min	0	3	-.003	3	-.002	1	-8.018e-6	1	NC	1	NC	1
247		10	max	.002	1	.001	2	0	15	-1.432e-7	12	NC	1	NC	1
248			min	0	3	-.002	3	-.002	1	-8.018e-6	1	NC	1	NC	1
249		11	max	.001	1	.001	2	0	15	-1.432e-7	12	NC	1	NC	1
250			min	0	3	-.002	3	-.001	1	-8.018e-6	1	NC	1	NC	1
251		12	max	.001	1	.001	2	0	15	-1.432e-7	12	NC	1	NC	1
252			min	0	3	-.002	3	-.001	1	-8.018e-6	1	NC	1	NC	1
253		13	max	.001	1	0	2	0	15	-1.432e-7	12	NC	1	NC	1
254			min	0	3	-.002	3	0	1	-8.018e-6	1	NC	1	NC	1
255		14	max	0	1	0	2	0	15	-1.432e-7	12	NC	1	NC	1
256			min	0	3	-.001	3	0	1	-8.018e-6	1	NC	1	NC	1
257		15	max	0	1	0	2	0	15	-1.432e-7	12	NC	1	NC	1
258			min	0	3	-.001	3	0	1	-8.018e-6	1	NC	1	NC	1
259		16	max	0	1	0	2	0	15	-1.432e-7	12	NC	1	NC	1
260			min	0	3	0	3	0	1	-8.018e-6	1	NC	1	NC	1
261		17	max	0	1	0	2	0	15	-1.432e-7	12	NC	1	NC	1
262			min	0	3	0	3	0	1	-8.018e-6	1	NC	1	NC	1
263		18	max	0	1	0	2	0	15	-1.432e-7	12	NC	1	NC	1
264			min	0	3	0	3	0	1	-8.018e-6	1	NC	1	NC	1
265		19	max	0	1	0	1	0	1	-1.432e-7	12	NC	1	NC	1
266			min	0	1	0	1	0	1	-8.018e-6	1	NC	1	NC	1
267	M6	1	max	.017	1	.015	2	0	1	0	1	NC	4	NC	1
268			min	-.02	3	-.023	3	0	1	0	1	2115.888	3	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
269		2	max	.016	1	.014	2	0	1	0	1	NC	4	NC	1
270			min	-.019	3	-.021	3	0	1	0	1	2242.314	3	NC	1
271		3	max	.015	1	.013	2	0	1	0	1	NC	4	NC	1
272			min	-.018	3	-.02	3	0	1	0	1	2384.779	3	NC	1
273		4	max	.014	1	.011	2	0	1	0	1	NC	4	NC	1
274			min	-.017	3	-.019	3	0	1	0	1	2546.505	3	NC	1
275		5	max	.013	1	.01	2	0	1	0	1	NC	4	NC	1
276			min	-.016	3	-.018	3	0	1	0	1	2731.634	3	NC	1
277		6	max	.012	1	.009	2	0	1	0	1	NC	1	NC	1
278			min	-.015	3	-.016	3	0	1	0	1	2945.583	3	NC	1
279		7	max	.011	1	.008	2	0	1	0	1	NC	1	NC	1
280			min	-.014	3	-.015	3	0	1	0	1	3195.576	3	NC	1
281		8	max	.011	1	.007	2	0	1	0	1	NC	1	NC	1
282			min	-.013	3	-.014	3	0	1	0	1	3491.465	3	NC	1
283		9	max	.01	1	.006	2	0	1	0	1	NC	1	NC	1
284			min	-.011	3	-.012	3	0	1	0	1	3847.042	3	NC	1
285		10	max	.009	1	.005	2	0	1	0	1	NC	1	NC	1
286			min	-.01	3	-.011	3	0	1	0	1	4282.229	3	NC	1
287		11	max	.008	1	.004	2	0	1	0	1	NC	1	NC	1
288			min	-.009	3	-.01	3	0	1	0	1	4826.912	3	NC	1
289		12	max	.007	1	.003	2	0	1	0	1	NC	1	NC	1
290			min	-.008	3	-.009	3	0	1	0	1	5528.054	3	NC	1
291		13	max	.006	1	.002	2	0	1	0	1	NC	1	NC	1
292			min	-.007	3	-.007	3	0	1	0	1	6463.93	3	NC	1
293		14	max	.005	1	.002	2	0	1	0	1	NC	1	NC	1
294			min	-.006	3	-.006	3	0	1	0	1	7775.434	3	NC	1
295		15	max	.004	1	.001	2	0	1	0	1	NC	1	NC	1
296			min	-.005	3	-.005	3	0	1	0	1	9744.36	3	NC	1
297		16	max	.003	1	0	2	0	1	0	1	NC	1	NC	1
298			min	-.003	3	-.004	3	0	1	0	1	NC	1	NC	1
299		17	max	.002	1	0	2	0	1	0	1	NC	1	NC	1
300			min	-.002	3	-.002	3	0	1	0	1	NC	1	NC	1
301		18	max	0	1	0	2	0	1	0	1	NC	1	NC	1
302			min	-.001	3	-.001	3	0	1	0	1	NC	1	NC	1
303		19	max	0	1	0	1	0	1	0	1	NC	1	NC	1
304			min	0	1	0	1	0	1	0	1	NC	1	NC	1
305	M7	1	max	0	1	0	1	0	1	0	1	NC	1	NC	1
306			min	0	1	0	1	0	1	0	1	NC	1	NC	1
307		2	max	0	3	0	2	0	1	0	1	NC	1	NC	1
308			min	0	2	-.002	3	0	1	0	1	NC	1	NC	1
309		3	max	.002	3	0	15	0	1	0	1	NC	1	NC	1
310			min	-.001	2	-.004	3	0	1	0	1	NC	1	NC	1
311		4	max	.002	3	-.001	15	0	1	0	1	NC	1	NC	1
312			min	-.002	2	-.006	3	0	1	0	1	NC	1	NC	1
313		5	max	.003	3	-.002	15	0	1	0	1	NC	1	NC	1
314			min	-.003	2	-.008	3	0	1	0	1	NC	1	NC	1
315		6	max	.004	3	-.002	15	0	1	0	1	NC	1	NC	1
316			min	-.004	2	-.01	3	0	1	0	1	9425.887	3	NC	1
317		7	max	.005	3	-.002	15	0	1	0	1	NC	1	NC	1
318			min	-.004	2	-.011	3	0	1	0	1	8382.943	3	NC	1
319		8	max	.006	3	-.003	15	0	1	0	1	NC	1	NC	1
320			min	-.005	2	-.012	3	0	1	0	1	7760.237	3	NC	1
321		9	max	.006	3	-.003	15	0	1	0	1	NC	1	NC	1
322			min	-.006	2	-.012	3	0	1	0	1	7430.059	3	NC	1
323		10	max	.007	3	-.003	15	0	1	0	1	NC	1	NC	1
324			min	-.007	2	-.013	4	0	1	0	1	7334.341	3	NC	1
325		11	max	.008	3	-.003	15	0	1	0	1	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
326			min	-.007	2	-.013	4	0	1	0	1	7456.996	3	NC	1
327		12	max	.009	3	-.003	15	0	1	0	1	NC	1	NC	1
328			min	-.008	2	-.013	4	0	1	0	1	7665.247	4	NC	1
329		13	max	.01	3	-.003	15	0	1	0	1	NC	1	NC	1
330			min	-.009	2	-.012	4	0	1	0	1	8164.229	4	NC	1
331		14	max	.01	3	-.003	15	0	1	0	1	NC	1	NC	1
332			min	-.01	2	-.011	1	0	1	0	1	9078.751	4	NC	1
333		15	max	.011	3	-.002	15	0	1	0	1	NC	1	NC	1
334			min	-.01	2	-.011	1	0	1	0	1	NC	1	NC	1
335		16	max	.012	3	-.002	15	0	1	0	1	NC	1	NC	1
336			min	-.011	2	-.01	1	0	1	0	1	NC	1	NC	1
337		17	max	.013	3	-.001	15	0	1	0	1	NC	1	NC	1
338			min	-.012	2	-.009	1	0	1	0	1	NC	1	NC	1
339		18	max	.014	3	0	15	0	1	0	1	NC	1	NC	1
340			min	-.013	2	-.008	1	0	1	0	1	NC	1	NC	1
341		19	max	.014	3	0	15	0	1	0	1	NC	1	NC	1
342			min	-.013	2	-.007	1	0	1	0	1	NC	1	NC	1
343	M8	1	max	.009	1	.011	2	0	1	0	1	NC	1	NC	1
344			min	-.003	3	-.014	3	0	1	0	1	NC	1	NC	1
345		2	max	.009	1	.011	2	0	1	0	1	NC	1	NC	1
346			min	-.003	3	-.013	3	0	1	0	1	NC	1	NC	1
347		3	max	.008	1	.01	2	0	1	0	1	NC	1	NC	1
348			min	-.003	3	-.013	3	0	1	0	1	NC	1	NC	1
349		4	max	.008	1	.009	2	0	1	0	1	NC	1	NC	1
350			min	-.003	3	-.012	3	0	1	0	1	NC	1	NC	1
351		5	max	.007	1	.009	2	0	1	0	1	NC	1	NC	1
352			min	-.003	3	-.011	3	0	1	0	1	NC	1	NC	1
353		6	max	.007	1	.008	2	0	1	0	1	NC	1	NC	1
354			min	-.003	3	-.01	3	0	1	0	1	NC	1	NC	1
355		7	max	.006	1	.008	2	0	1	0	1	NC	1	NC	1
356			min	-.002	3	-.009	3	0	1	0	1	NC	1	NC	1
357		8	max	.006	1	.007	2	0	1	0	1	NC	1	NC	1
358			min	-.002	3	-.009	3	0	1	0	1	NC	1	NC	1
359		9	max	.005	1	.006	2	0	1	0	1	NC	1	NC	1
360			min	-.002	3	-.008	3	0	1	0	1	NC	1	NC	1
361		10	max	.005	1	.006	2	0	1	0	1	NC	1	NC	1
362			min	-.002	3	-.007	3	0	1	0	1	NC	1	NC	1
363		11	max	.004	1	.005	2	0	1	0	1	NC	1	NC	1
364			min	-.002	3	-.006	3	0	1	0	1	NC	1	NC	1
365		12	max	.004	1	.004	2	0	1	0	1	NC	1	NC	1
366			min	-.001	3	-.005	3	0	1	0	1	NC	1	NC	1
367		13	max	.003	1	.004	2	0	1	0	1	NC	1	NC	1
368			min	-.001	3	-.005	3	0	1	0	1	NC	1	NC	1
369		14	max	.003	1	.003	2	0	1	0	1	NC	1	NC	1
370			min	0	3	-.004	3	0	1	0	1	NC	1	NC	1
371		15	max	.002	1	.003	2	0	1	0	1	NC	1	NC	1
372			min	0	3	-.003	3	0	1	0	1	NC	1	NC	1
373		16	max	.002	1	.002	2	0	1	0	1	NC	1	NC	1
374			min	0	3	-.002	3	0	1	0	1	NC	1	NC	1
375		17	max	.001	1	.001	2	0	1	0	1	NC	1	NC	1
376			min	0	3	-.002	3	0	1	0	1	NC	1	NC	1
377		18	max	0	1	0	2	0	1	0	1	NC	1	NC	1
378			min	0	3	0	3	0	1	0	1	NC	1	NC	1
379		19	max	0	1	0	1	0	1	0	1	NC	1	NC	1
380			min	0	1	0	1	0	1	0	1	NC	1	NC	1
381	M10	1	max	.005	1	.004	2	0	15	1.376e-4	1	NC	1	NC	2
382			min	-.006	3	-.007	3	-.005	1	4.52e-6	15	NC	1	8777.198	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
383		2	max	.005	1	.003	2	0	15	1.275e-4	1	NC	1	NC	2
384			min	-.006	3	-.007	3	-.005	1	4.189e-6	15	NC	1	9571.622	1
385		3	max	.005	1	.003	2	0	15	1.174e-4	1	NC	1	NC	1
386			min	-.006	3	-.007	3	-.005	1	3.858e-6	15	NC	1	NC	1
387		4	max	.004	1	.002	2	0	15	1.073e-4	1	NC	1	NC	1
388			min	-.005	3	-.006	3	-.004	1	3.527e-6	15	NC	1	NC	1
389		5	max	.004	1	.002	2	0	15	9.724e-5	1	NC	1	NC	1
390			min	-.005	3	-.006	3	-.004	1	3.197e-6	15	NC	1	NC	1
391		6	max	.004	1	.001	2	0	15	8.715e-5	1	NC	1	NC	1
392			min	-.005	3	-.006	3	-.003	1	2.866e-6	15	NC	1	NC	1
393		7	max	.004	1	0	2	0	15	7.706e-5	1	NC	1	NC	1
394			min	-.004	3	-.005	3	-.003	1	2.535e-6	15	NC	1	NC	1
395		8	max	.003	1	0	2	0	15	6.698e-5	1	NC	1	NC	1
396			min	-.004	3	-.005	3	-.002	1	2.204e-6	15	NC	1	NC	1
397		9	max	.003	1	0	2	0	15	5.689e-5	1	NC	1	NC	1
398			min	-.003	3	-.005	3	-.002	1	1.873e-6	15	NC	1	NC	1
399		10	max	.003	1	0	2	0	15	4.68e-5	1	NC	1	NC	1
400			min	-.003	3	-.004	3	-.002	1	1.542e-6	15	NC	1	NC	1
401		11	max	.002	1	0	2	0	15	3.672e-5	1	NC	1	NC	1
402			min	-.003	3	-.004	3	-.001	1	1.211e-6	15	NC	1	NC	1
403		12	max	.002	1	0	15	0	15	2.663e-5	1	NC	1	NC	1
404			min	-.002	3	-.004	3	-.001	1	8.801e-7	15	NC	1	NC	1
405		13	max	.002	1	0	15	0	15	1.654e-5	1	NC	1	NC	1
406			min	-.002	3	-.003	3	0	1	5.492e-7	15	NC	1	NC	1
407		14	max	.001	1	0	15	0	15	6.458e-6	1	NC	1	NC	1
408			min	-.002	3	-.003	3	0	1	2.183e-7	15	NC	1	NC	1
409		15	max	.001	1	0	15	0	15	3.171e-7	3	NC	1	NC	1
410			min	-.001	3	-.002	3	0	1	-3.629e-6	1	NC	1	NC	1
411		16	max	0	1	0	15	0	15	-3.126e-7	12	NC	1	NC	1
412			min	-.001	3	-.002	3	0	1	-1.372e-5	1	NC	1	NC	1
413		17	max	0	1	0	15	0	15	-7.745e-7	15	NC	1	NC	1
414			min	0	3	-.001	3	0	1	-2.38e-5	1	NC	1	NC	1
415		18	max	0	1	0	15	0	15	-1.105e-6	15	NC	1	NC	1
416			min	0	3	0	4	0	1	-3.389e-5	1	NC	1	NC	1
417		19	max	0	1	0	1	0	1	-1.436e-6	15	NC	1	NC	1
418			min	0	1	0	1	0	1	-4.398e-5	1	NC	1	NC	1
419	M11	1	max	0	1	0	1	0	1	1.368e-5	1	NC	1	NC	1
420			min	0	1	0	1	0	1	4.471e-7	15	NC	1	NC	1
421		2	max	0	3	0	15	0	15	-1.227e-7	15	NC	1	NC	1
422			min	0	2	-.001	4	0	1	-3.725e-6	1	NC	1	NC	1
423		3	max	0	3	0	15	0	15	-6.924e-7	15	NC	1	NC	1
424			min	0	2	-.003	4	0	1	-2.113e-5	1	NC	1	NC	1
425		4	max	0	3	-.001	15	0	15	-1.262e-6	15	NC	1	NC	1
426			min	0	2	-.005	4	0	1	-3.853e-5	1	NC	1	NC	1
427		5	max	.001	3	-.002	15	0	15	-1.832e-6	15	NC	1	NC	1
428			min	0	2	-.007	4	0	1	-5.594e-5	1	NC	1	NC	1
429		6	max	.001	3	-.002	15	0	15	-2.402e-6	15	NC	1	NC	1
430			min	0	2	-.009	4	-.001	1	-7.334e-5	1	NC	1	NC	1
431		7	max	.002	3	-.002	15	0	15	-2.971e-6	15	NC	1	NC	1
432			min	-.001	2	-.01	4	-.001	1	-9.075e-5	1	9289.431	4	NC	1
433		8	max	.002	3	-.003	15	0	15	-3.541e-6	15	NC	1	NC	1
434			min	-.001	2	-.011	4	-.002	1	-1.082e-4	1	8280.337	4	NC	1
435		9	max	.002	3	-.003	15	0	15	-4.111e-6	15	NC	1	NC	1
436			min	-.002	2	-.012	4	-.002	1	-1.256e-4	1	7677.314	4	NC	1
437		10	max	.002	3	-.003	15	0	15	-4.681e-6	15	NC	2	NC	1
438			min	-.002	2	-.013	4	-.002	1	-1.43e-4	1	7373.192	4	NC	1
439		11	max	.003	3	-.003	15	0	15	-5.251e-6	15	NC	2	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
440			min	-.002	2	-.013	4	-.003	1	-1.604e-4	1	7322.368	4	NC	1
441		12	max	.003	3	-.003	15	0	15	-5.82e-6	15	NC	1	NC	1
442			min	-.002	2	-.013	4	-.003	1	-1.778e-4	1	7523.187	4	NC	1
443		13	max	.003	3	-.003	15	0	15	-6.39e-6	15	NC	1	NC	1
444			min	-.002	2	-.012	4	-.003	1	-1.952e-4	1	8019.446	4	NC	1
445		14	max	.003	3	-.002	15	0	15	-6.96e-6	15	NC	1	NC	1
446			min	-.003	2	-.011	4	-.003	1	-2.126e-4	1	8923.752	4	NC	1
447		15	max	.004	3	-.002	15	0	15	-7.53e-6	15	NC	1	NC	1
448			min	-.003	2	-.009	4	-.004	1	-2.3e-4	1	NC	1	NC	1
449		16	max	.004	3	-.002	15	0	15	-8.099e-6	15	NC	1	NC	1
450			min	-.003	2	-.008	1	-.004	1	-2.474e-4	1	NC	1	NC	1
451		17	max	.004	3	-.001	15	0	15	-8.669e-6	15	NC	1	NC	1
452			min	-.003	2	-.006	1	-.004	1	-2.648e-4	1	NC	1	NC	1
453		18	max	.004	3	0	15	0	15	-9.239e-6	15	NC	1	NC	1
454			min	-.003	2	-.005	1	-.005	1	-2.822e-4	1	NC	1	NC	1
455		19	max	.005	3	0	15	0	15	-9.809e-6	15	NC	1	NC	1
456			min	-.004	2	-.003	1	-.005	1	-2.996e-4	1	NC	1	NC	1
457	M12	1	max	.003	1	.003	2	.005	1	8.018e-6	1	NC	1	NC	2
458			min	-.001	3	-.005	3	0	15	1.432e-7	12	NC	1	4743.156	1
459		2	max	.003	1	.003	2	.005	1	8.018e-6	1	NC	1	NC	2
460			min	0	3	-.004	3	0	15	1.432e-7	12	NC	1	5166.083	1
461		3	max	.003	1	.003	2	.004	1	8.018e-6	1	NC	1	NC	2
462			min	0	3	-.004	3	0	15	1.432e-7	12	NC	1	5668.978	1
463		4	max	.003	1	.002	2	.004	1	8.018e-6	1	NC	1	NC	2
464			min	0	3	-.004	3	0	15	1.432e-7	12	NC	1	6272.697	1
465		5	max	.002	1	.002	2	.004	1	8.018e-6	1	NC	1	NC	2
466			min	0	3	-.004	3	0	15	1.432e-7	12	NC	1	7005.58	1
467		6	max	.002	1	.002	2	.003	1	8.018e-6	1	NC	1	NC	2
468			min	0	3	-.003	3	0	15	1.432e-7	12	NC	1	7906.931	1
469		7	max	.002	1	.002	2	.003	1	8.018e-6	1	NC	1	NC	2
470			min	0	3	-.003	3	0	15	1.432e-7	12	NC	1	9032.543	1
471		8	max	.002	1	.002	2	.002	1	8.018e-6	1	NC	1	NC	1
472			min	0	3	-.003	3	0	15	1.432e-7	12	NC	1	NC	1
473		9	max	.002	1	.002	2	.002	1	8.018e-6	1	NC	1	NC	1
474			min	0	3	-.003	3	0	15	1.432e-7	12	NC	1	NC	1
475		10	max	.002	1	.001	2	.002	1	8.018e-6	1	NC	1	NC	1
476			min	0	3	-.002	3	0	15	1.432e-7	12	NC	1	NC	1
477		11	max	.001	1	.001	2	.001	1	8.018e-6	1	NC	1	NC	1
478			min	0	3	-.002	3	0	15	1.432e-7	12	NC	1	NC	1
479		12	max	.001	1	.001	2	.001	1	8.018e-6	1	NC	1	NC	1
480			min	0	3	-.002	3	0	15	1.432e-7	12	NC	1	NC	1
481		13	max	.001	1	0	2	0	1	8.018e-6	1	NC	1	NC	1
482			min	0	3	-.002	3	0	15	1.432e-7	12	NC	1	NC	1
483		14	max	0	1	0	2	0	1	8.018e-6	1	NC	1	NC	1
484			min	0	3	-.001	3	0	15	1.432e-7	12	NC	1	NC	1
485		15	max	0	1	0	2	0	1	8.018e-6	1	NC	1	NC	1
486			min	0	3	-.001	3	0	15	1.432e-7	12	NC	1	NC	1
487		16	max	0	1	0	2	0	1	8.018e-6	1	NC	1	NC	1
488			min	0	3	0	3	0	15	1.432e-7	12	NC	1	NC	1
489		17	max	0	1	0	2	0	1	8.018e-6	1	NC	1	NC	1
490			min	0	3	0	3	0	15	1.432e-7	12	NC	1	NC	1
491		18	max	0	1	0	2	0	1	8.018e-6	1	NC	1	NC	1
492			min	0	3	0	3	0	15	1.432e-7	12	NC	1	NC	1
493		19	max	0	1	0	1	0	1	8.018e-6	1	NC	1	NC	1
494			min	0	1	0	1	0	1	1.432e-7	12	NC	1	NC	1
495	M1	1	max	.006	3	.127	2	0	1	1.486e-2	1	NC	1	NC	1
496			min	-.003	2	-.029	3	0	15	-2.408e-2	3	NC	1	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
497		2	max	.006	3	.062	2	0	15	7.245e-3	1	NC	4	NC	1
498			min	-.003	2	-.015	3	-.004	1	-1.191e-2	3	1781.638	2	NC	1
499		3	max	.006	3	.008	3	0	15	3.501e-5	10	NC	5	NC	1
500			min	-.003	2	-.007	2	-.005	1	-1.193e-4	3	859.051	2	NC	1
501		4	max	.005	3	.046	3	0	15	4.707e-3	1	NC	5	NC	1
502			min	-.003	2	-.086	2	-.005	1	-4.667e-3	3	542.619	2	NC	1
503		5	max	.005	3	.094	3	0	15	9.501e-3	1	NC	15	NC	1
504			min	-.003	2	-.167	2	-.004	1	-9.215e-3	3	391.82	2	NC	1
505		6	max	.005	3	.145	3	0	15	1.429e-2	1	NC	15	NC	1
506			min	-.002	2	-.248	1	-.001	1	-1.376e-2	3	307.862	1	NC	1
507		7	max	.005	3	.194	3	0	1	1.909e-2	1	NC	15	NC	1
508			min	-.002	2	-.32	1	0	12	-1.831e-2	3	258.014	1	NC	1
509		8	max	.005	3	.235	3	0	1	2.388e-2	1	9013.212	15	NC	1
510			min	-.002	2	-.377	1	0	15	-2.286e-2	3	228.604	1	NC	1
511		9	max	.005	3	.262	3	0	15	2.64e-2	1	8427.364	15	NC	1
512			min	-.002	2	-.413	1	0	1	-2.312e-2	3	213.32	1	NC	1
513		10	max	.005	3	.272	3	0	1	2.741e-2	1	8248.81	15	NC	1
514			min	-.002	2	-.425	1	0	15	-2.053e-2	3	208.759	1	NC	1
515		11	max	.005	3	.265	3	0	1	2.922e-2	2	8427.171	15	NC	1
516			min	-.002	2	-.413	1	0	15	-1.795e-2	3	213.663	1	NC	1
517		12	max	.005	3	.243	3	0	15	2.82e-2	2	9012.802	15	NC	1
518			min	-.002	2	-.376	1	0	1	-1.519e-2	3	229.656	1	NC	1
519		13	max	.005	3	.206	3	0	15	2.261e-2	2	NC	15	NC	1
520			min	-.002	2	-.317	1	0	1	-1.216e-2	3	260.589	1	NC	1
521		14	max	.004	3	.16	3	.001	1	1.702e-2	2	NC	15	NC	1
522			min	-.002	2	-.244	1	0	15	-9.131e-3	3	313.37	1	NC	1
523		15	max	.004	3	.108	3	.003	1	1.143e-2	2	NC	15	NC	1
524			min	-.002	2	-.163	1	0	15	-6.104e-3	3	403.933	1	NC	1
525		16	max	.004	3	.055	3	.005	1	5.832e-3	2	NC	5	NC	1
526			min	-.002	2	-.081	1	0	15	-3.077e-3	3	570.913	1	NC	1
527		17	max	.004	3	.003	3	.005	1	4.173e-4	1	NC	5	NC	1
528			min	-.002	2	-.005	2	0	15	-4.932e-5	3	926.314	1	NC	1
529		18	max	.004	3	.06	1	.004	1	9.932e-3	2	NC	4	NC	1
530			min	-.002	2	-.042	3	0	15	-4.186e-3	3	1955.565	1	NC	1
531		19	max	.004	3	.118	1	0	15	1.998e-2	2	NC	1	NC	1
532			min	-.002	2	-.085	3	0	1	-8.49e-3	3	NC	1	NC	1
533	M5	1	max	.017	3	.29	2	0	1	0	1	NC	1	NC	1
534			min	-.011	2	-.04	3	0	1	0	1	NC	1	NC	1
535		2	max	.017	3	.142	2	0	1	0	1	NC	5	NC	1
536			min	-.011	2	-.02	3	0	1	0	1	786.654	2	NC	1
537		3	max	.017	3	.027	3	0	1	0	1	NC	5	NC	1
538			min	-.011	2	-.023	2	0	1	0	1	370.51	2	NC	1
539		4	max	.017	3	.123	3	0	1	0	1	NC	15	NC	1
540			min	-.011	2	-.22	2	0	1	0	1	227.109	2	NC	1
541		5	max	.017	3	.254	3	0	1	0	1	7140.441	15	NC	1
542			min	-.011	2	-.434	1	0	1	0	1	160.037	2	NC	1
543		6	max	.016	3	.4	3	0	1	0	1	5494.434	15	NC	1
544			min	-.011	2	-.649	1	0	1	0	1	123.358	1	NC	1
545		7	max	.016	3	.541	3	0	1	0	1	4544.47	15	NC	1
546			min	-.01	2	-.844	1	0	1	0	1	101.952	1	NC	1
547		8	max	.016	3	.66	3	0	1	0	1	3992.378	15	NC	1
548			min	-.01	2	-1	1	0	1	0	1	89.508	1	NC	1
549		9	max	.015	3	.736	3	0	1	0	1	3709.35	15	NC	1
550			min	-.01	2	-1.099	1	0	1	0	1	83.132	1	NC	1
551		10	max	.015	3	.764	3	0	1	0	1	3624.083	15	NC	1
552			min	-.01	2	-1.132	1	0	1	0	1	81.24	1	NC	1
553		11	max	.015	3	.745	3	0	1	0	1	3709.425	15	NC	1

Envelope Member Section Deflections (Continued)

	Member	Sec		x [in]	LC	y [in]	LC	z [in]	LC	x Rotate [r...	LC	(n) L/y Ratio	LC	(n) L/z Ratio	LC
554			min	-.01	2	-1.099	1	0	1	0	1	83.274	1	NC	1
555		12	max	.014	3	.68	3	0	1	0	1	3992.554	15	NC	1
556			min	-.009	2	-.998	1	0	1	0	1	89.976	1	NC	1
557		13	max	.014	3	.576	3	0	1	0	1	4544.826	15	NC	1
558			min	-.009	2	-.837	1	0	1	0	1	103.17	1	NC	1
559		14	max	.014	3	.444	3	0	1	0	1	5495.126	15	NC	1
560			min	-.009	2	-.638	1	0	1	0	1	126.106	1	NC	1
561		15	max	.013	3	.297	3	0	1	0	1	7141.802	15	NC	1
562			min	-.009	2	-.42	1	0	1	0	1	166.409	1	NC	1
563		16	max	.013	3	.148	3	0	1	0	1	NC	15	NC	1
564			min	-.009	2	-.205	1	0	1	0	1	243.018	1	NC	1
565		17	max	.013	3	.01	3	0	1	0	1	NC	5	NC	1
566			min	-.009	2	-.015	2	0	1	0	1	411.348	1	NC	1
567		18	max	.013	3	.135	1	0	1	0	1	NC	5	NC	1
568			min	-.009	2	-.107	3	0	1	0	1	898.332	1	NC	1
569		19	max	.013	3	.261	1	0	1	0	1	NC	1	NC	1
570			min	-.009	2	-.212	3	0	1	0	1	NC	1	NC	1
571	M9	1	max	.006	3	.127	2	0	15	2.408e-2	3	NC	1	NC	1
572			min	-.003	2	-.029	3	0	1	-1.486e-2	1	NC	1	NC	1
573		2	max	.006	3	.062	2	.004	1	1.191e-2	3	NC	4	NC	1
574			min	-.003	2	-.015	3	0	15	-7.245e-3	1	1781.638	2	NC	1
575		3	max	.006	3	.008	3	.005	1	1.193e-4	3	NC	5	NC	1
576			min	-.003	2	-.007	2	0	15	-3.501e-5	10	859.051	2	NC	1
577		4	max	.005	3	.046	3	.005	1	4.667e-3	3	NC	5	NC	1
578			min	-.003	2	-.086	2	0	15	-4.707e-3	1	542.619	2	NC	1
579		5	max	.005	3	.094	3	.004	1	9.215e-3	3	NC	15	NC	1
580			min	-.003	2	-.167	2	0	15	-9.501e-3	1	391.82	2	NC	1
581		6	max	.005	3	.145	3	.001	1	1.376e-2	3	NC	15	NC	1
582			min	-.002	2	-.248	1	0	15	-1.429e-2	1	307.862	1	NC	1
583		7	max	.005	3	.194	3	0	12	1.831e-2	3	NC	15	NC	1
584			min	-.002	2	-.32	1	0	1	-1.909e-2	1	258.014	1	NC	1
585		8	max	.005	3	.235	3	0	15	2.286e-2	3	9013.212	15	NC	1
586			min	-.002	2	-.377	1	0	1	-2.388e-2	1	228.604	1	NC	1
587		9	max	.005	3	.262	3	0	1	2.312e-2	3	8427.364	15	NC	1
588			min	-.002	2	-.413	1	0	15	-2.64e-2	1	213.32	1	NC	1
589		10	max	.005	3	.272	3	0	15	2.053e-2	3	8248.81	15	NC	1
590			min	-.002	2	-.425	1	0	1	-2.741e-2	1	208.759	1	NC	1
591		11	max	.005	3	.265	3	0	15	1.795e-2	3	8427.171	15	NC	1
592			min	-.002	2	-.413	1	0	1	-2.922e-2	2	213.663	1	NC	1
593		12	max	.005	3	.243	3	0	1	1.519e-2	3	9012.802	15	NC	1
594			min	-.002	2	-.376	1	0	15	-2.82e-2	2	229.656	1	NC	1
595		13	max	.005	3	.206	3	0	1	1.216e-2	3	NC	15	NC	1
596			min	-.002	2	-.317	1	0	15	-2.261e-2	2	260.589	1	NC	1
597		14	max	.004	3	.16	3	0	15	9.131e-3	3	NC	15	NC	1
598			min	-.002	2	-.244	1	-.001	1	-1.702e-2	2	313.37	1	NC	1
599		15	max	.004	3	.108	3	0	15	6.104e-3	3	NC	15	NC	1
600			min	-.002	2	-.163	1	-.003	1	-1.143e-2	2	403.933	1	NC	1
601		16	max	.004	3	.055	3	0	15	3.077e-3	3	NC	5	NC	1
602			min	-.002	2	-.081	1	-.005	1	-5.832e-3	2	570.913	1	NC	1
603		17	max	.004	3	.003	3	0	15	4.932e-5	3	NC	5	NC	1
604			min	-.002	2	-.005	2	-.005	1	-4.173e-4	1	926.314	1	NC	1
605		18	max	.004	3	.06	1	0	15	4.186e-3	3	NC	4	NC	1
606			min	-.002	2	-.042	3	-.004	1	-9.932e-3	2	1955.565	1	NC	1
607		19	max	.004	3	.118	1	0	1	8.49e-3	3	NC	1	NC	1
608			min	-.002	2	-.085	3	0	15	-1.998e-2	2	NC	1	NC	1

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 4.00 x 0.28

<Figure 1>



<Figure 2>

Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	1723.0	23.0	593.0	593.4
Sum	1723.0	23.0	593.0	593.4

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 1723
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	5.247	10215

$\phi N_{cb} = \phi \, (A_{Nc} / A_{Nco}) \, \Psi_{ed,N} \, \Psi_{c,N} \, \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-4)

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cb} (lb)
220.36	247.75	0.967	1.00	1.000	10215	0.65	5710

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_a = \phi \, (A_{Na} / A_{Na0}) \, \Psi_{ed,Na} \, \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16a)

A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	ϕ	ϕN_a (lb)
109.66	109.66	1.000	1.000	9755	0.55	5365

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in y-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cby} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cby} (lb)
192.89	220.50	0.925	1.000	1.000	6947	0.70	3934

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cbx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbx} (lb)
165.27	278.72	0.878	1.000	1.000	8282	0.70	3018

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	7.00	6947

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
192.89	220.50	1.000	1.000	1.000	6947	0.70	8508

Shear parallel to edge in y-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	7.87	8282

$\phi V_{cby} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cby} (lb)
165.27	278.72	1.000	1.000	1.000	8282	0.70	6875

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cp} = \phi \min|k_{cp}N_a\,;\,k_{cp}N_{cb}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\,\Psi_{p,Na}N_{a0}\,;\,k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ed,N}\,\Psi_{c,N}\,\Psi_{cp,N}N_b|$ (Eq. D-30a)

k_{cp}	A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	109.66	109.66	1.000	1.000	9755	9755

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ	ϕV_{cp} (lb)
220.36	247.75	0.967	1.000	1.000	10215	8785	0.70	12298

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, ϕN_n (lb)	Ratio	Status
Steel	1723	6071	0.28	Pass
Concrete breakout	1723	5710	0.30	Pass
Adhesive	**1723**	**5365**	**0.32**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, ϕV_n (lb)	Ratio	Status
Steel	**593**	**3156**	**0.19**	**Pass (Governs)**
T Concrete breakout y+	593	3934	0.15	Pass
T Concrete breakout x+	23	3018	0.01	Pass
|| Concrete breakout y+	23	8508	0.00	Pass
|| Concrete breakout x+	593	6875	0.09	Pass
Concrete breakout, combined	-	-	0.15	Pass
Pryout	593	12298	0.05	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status
Sec. D.7.1	0.32	0.00	32.1 %	1.0	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.

1.Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General
Design method:ACI 318-05
Units: Imperial units

Anchor Information:
Anchor type: Bonded anchor
Material: A193 Grade B8/B8M (304/316SS)
Diameter (inch): 0.500
Effective Embedment depth, h_{ef} (inch): 6.000
Code report: IAPMO UES ER-263
Anchor category: -
Anchor ductility: Yes
h_{min} (inch): 8.50
c_{ac} (inch): 9.67
C_{min} (inch): 1.75
S_{min} (inch): 3.00

Load and Geometry
Load factor source: ACI 318 Section 9.2
Load combination: not set
Seismic design: No
Anchors subjected to sustained tension: No
Apply entire shear load at front row: No
Anchors only resisting wind and/or seismic loads: No

<Figure 1>

Base Material
Concrete: Normal-weight
Concrete thickness, h (inch): 18.00
State: Cracked
Compressive strength, f'_c (psi): 2500
$\Psi_{c,V}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental reinforcement: Not applicable
Reinforcement provided at corners: No
Do not evaluate concrete breakout in tension: No
Do not evaluate concrete breakout in shear: No
Hole condition: Dry concrete
Inspection: Periodic
Temperature range, Short/Long: 110/75°F
Ignore 6do requirement: Not applicable
Build-up grout pad: No

Base Plate
Length x Width x Thickness (inch): 4.00 x 7.00 x 0.28



<Figure 2>



Recommended Anchor
Anchor Name: AT-XP® - AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS)
Code Report: IAPMO UES ER-263

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2+(V_{uay})^2}$ (lb)
1	2700.0	1671.0	0.0	1671.0
2	2700.0	1671.0	0.0	1671.0
Sum	5400.0	3342.0	0.0	3342.0

Maximum concrete compression strain (‰): 0.00
Maximum concrete compression stress (psi): 0
Resultant tension force (lb): 5400
Resultant compression force (lb): 0
Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 0.00
Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension(Sec. D.5.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
8095	0.75	6071

5. Concrete Breakout Strength of Anchor in Tension (Sec. D.5.2)

$N_b = k_c \lambda \sqrt{f'_c} h_{ef}^{1.5}$ (Eq. D-7)

k_c	λ	f'_c (psi)	h_{ef} (in)	N_b (lb)
17.0	1.00	2500	6.000	12492

$\phi N_{cbg} = \phi (A_{Nc} / A_{Nco}) \Psi_{ec,N} \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b$ (Sec. D.4.1 & Eq. D-5)

A_{Nc} (in²)	A_{Nco} (in²)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cbg} (lb)
408.24	324.00	1.000	1.000	1.00	1.000	12492	0.65	10231

6. Adhesive Strength of Anchor in Tension (AC308 Sec. 3.3)

$\tau_{k,cr} = \tau_{k,cr} f_{short\text{-}term} K_{sat}$

$\tau_{k,cr}$ (psi)	$f_{short\text{-}term}$	K_{sat}	$\tau_{k,cr}$ (psi)
1035	1.00	1.00	1035

$N_{a0} = \tau_{k,cr} \pi d_a h_{ef}$ (Eq. D-16f)

$\tau_{k,cr}$ (psi)	d_a (in)	h_{ef} (in)	N_{a0} (lb)
1035	0.50	6.000	9755

$\phi N_{ag} = \phi (A_{Na} / A_{Na0}) \Psi_{ed,Na} \Psi_{g,Na} \Psi_{ec,Na} \Psi_{p,Na} N_{a0}$ (Sec. D.4.1 & Eq. D-16b)

A_{Na} (in²)	A_{Na0} (in²)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0}(lb)	ϕ	ϕN_{ag} (lb)
158.66	109.66	1.000	1.043	1.000	1.000	9755	0.55	8093

8. Steel Strength of Anchor in Shear (Sec. D.6.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
4855	1.0	0.65	3156

9. Concrete Breakout Strength of Anchor in Shear (Sec. D.6.2)

Shear perpendicular to edge in x-direction:

$V_{bx} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
4.00	0.50	1.00	2500	12.00	15593

$\phi V_{cbgx} = \phi\,(A_{Vc} / A_{Vco})\,\Psi_{ec,V}\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{bx}$ (Sec. D.4.1 & Eq. D-22)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ec,V}$	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbgx} (lb)
612.00	648.00	1.000	0.944	1.000	1.000	15593	0.70	9735

Shear parallel to edge in x-direction:

$V_{by} = 7(l_e / d_a)^{0.2}\sqrt{d_a}\lambda\sqrt{f'_c}c_{a1}^{1.5}$ (Eq. D-24)

l_e (in)	d_a (in)	λ	f'_c (psi)	c_{a1} (in)	V_{by} (lb)
4.00	0.50	1.00	2500	14.66	21056

$\phi V_{cbx} = \phi\,(2)(A_{Vc} / A_{Vco})\,\Psi_{ed,V}\,\Psi_{c,V}\,\Psi_{h,V}V_{by}$ (Sec. D.4.1, D.6.2.1(c) & Eq. D-21)

A_{Vc} (in^2)	A_{Vco} (in^2)	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{by} (lb)	ϕ	ϕV_{cbx} (lb)
791.64	967.12	1.000	1.000	1.000	21056	0.70	24129

10. Concrete Pryout Strength of Anchor in Shear (Sec. D.6.3)

$\phi V_{cpg} = \phi \min|k_{cp}N_{ag}\,;\, k_{cp}N_{cbg}| = \phi \min|k_{cp}(A_{Na} / A_{Na0})\,\Psi_{ed,Na}\,\Psi_{g,Na}\,\Psi_{ec,Na}\,\Psi_{p,Na}N_{a0}\,;\, k_{cp}(A_{Nc} / A_{Nco})\,\Psi_{ec,N}\,\Psi_{ed,N}\,\Psi_{c,N}\,\Psi_{cp,N}N_b|$ (Eq. D-30b)

k_{cp}	A_{Na} (in^2)	A_{Na0} (in^2)	$\Psi_{ed,Na}$	$\Psi_{g,Na}$	$\Psi_{ec,Na}$	$\Psi_{p,Na}$	N_{a0} (lb)	N_a (lb)
2.0	158.66	109.66	1.000	1.043	1.000	1.000	9755	14715

A_{Nc} (in^2)	A_{Nco} (in^2)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	N_{cb} (lb)	ϕ
408.24	324.00	1.000	1.000	1.000	1.000	12492	15740	0.70

ϕV_{cpg} (lb)
20601

11. Results

Interaction of Tensile and Shear Forces (Sec. D.7)

Tension	Factored Load, N_{ua} (lb)	Design Strength, øN_n (lb)	Ratio	Status
Steel	2700	6071	0.44	Pass
Concrete breakout	5400	10231	0.53	Pass
Adhesive	**5400**	**8093**	**0.67**	**Pass (Governs)**

Shear	Factored Load, V_{ua} (lb)	Design Strength, øV_n (lb)	Ratio	Status
Steel	**1671**	**3156**	**0.53**	**Pass (Governs)**
T Concrete breakout x+	3342	9735	0.34	Pass
|| Concrete breakout y-	1671	24129	0.07	Pass
Pryout	3342	20601	0.16	Pass

Interaction check	$N_{ua}/\phi N_n$	$V_{ua}/\phi V_n$	Combined Ratio	Permissible	Status

Sec. D.7.3	0.67	0.53	119.7 %	1.2	Pass

AT-XP w/ 1/2"Ø A193 Gr. B8/B8M (304/316SS) with hef = 6.000 inch meets the selected design criteria.

12. Warnings

- This temperature range is currently outside the scope of ACI 318-11 and ACI 355.4, and is provided for historical purposes.

- Designer must exercise own judgement to determine if this design is suitable.

- Refer to manufacturer's product literature for hole cleaning and installation instructions.