

GAYK

Hydraulic ram used for pile/pier driving

- Finely-tuned, intuitive controls
- Up to 13 – 18 feet tall for powerful ramming
- Rubber tracked for accurate and straight installations
- Operation by walking alongside the ram
- Engineered for easy maintenance
- Drilling options and customized heads available
- Auto-levelling option

The fully hydraulic GAYK ram features a track machine with center pounding for more efficient and accurate installations. Even difficult terrain conditions (gravel or stones) are possible; in case of bedrock, the GAYK can be equipped with a drilling unit. It is possible to ram posts on slopes up to 20° (on north-south slopes).

To ensure consistent ramming depth, the GAYK is equipped with an electric cut-off that disengages the rammer and chain feed automatically when the preset ramming depth is reached. This, along with standing operation and intuitive controls, makes the ram easy to operate while saving valuable installation time.

Schletter offers sales and rentals of the GAYK ram and on-site training upon request. For more information, visit www.schletter.us or call 888-608-0234.

Find videos of the GAYK in action at schletter.us/GAYK.html

Buy Online through Schletter Secure

Purchase spare parts online as well as the three GAYK models available. Visit secure.schletter.us, create an account, and access GAYK equipment as well as a variety of other Schletter offerings.



Schletter is the exclusive distributor for the GAYK™ ram in North and South America



Technical Data

The GAYK is available in three models; the HRE 3000, 4000, and 6000.



GAYK HRE 3000

GAYK HRE 3000

Transport length	16.4 ft
Transport width	6.56 ft
Transport height	8.2 ft
Weight with hammer	8,069 lbs
Max. length of posts to be rammed	13 ft
Number of impacts	670 – 1450 1/min
Weight of hammer	300 lbs
Power	48.3 hp



GAYK HRE 4000

GAYK HRE 4000

Transport length	16.4 ft
Transport width	6.56 ft
Transport height	8.2 ft
Weight with hammer	8,378 lbs
Max. length of posts to be rammed	13 ft
Number of impacts	530 – 1150 1/min
Weight of hammer	397 lbs
Power	48.3 hp



GAYK HRE 6000

GAYK HRE 6000

Transport length	21 ft
Transport width	6.89 ft
Transport height	8.2 ft
Weight with hammer	15,430 kbs
Max. length of posts to be rammed	19.6 ft
Number of impacts	530 – 1050 1/min
Weight of hammer	417 lbs
Power	48.3 hp

**Only available for lease under special circumstances as determined by Schletter Geotechnical staff.*

Schletter stands behind the quality, durability, and functionality of its products and services its customers with professionalism. For United States, visit www.schletter.us or call **888-608-0234** or for Canada, please visit www.schletter.ca or call **519-946-3800** to speak to a Schletter representative for more information.



SCHLETTER GMBH (Headquarters)

Gewerbegebiet an der B15
Alustraße 1
83527 Kirchdorf / Haag i.OB
DEUTSCHLAND

**SCHLETTER (Shanghai)
Solar Technology Co., Ltd**

677 Beihe Gong Road
Jiading, Shanghai
201807 PR CHINA

SCHLETTER Inc.

1001 Commerce Center Drive
Shelby, North Carolina 28150
USA

(888) 608 - 0234
info.us@schletter-group.com
www.schletter.us