

Multi-threading and Thread Synchronization

Luca Arrotta and Riccardo Presotto

EWLab – Università degli studi di Milano

Professor: Claudio Bettini

Copyright

Some slides for this course are partly adapted from the ones distributed by the publisher of the reference book for this course (Distributed Systems: Principles and Paradigms, A. S. Tanenbaum, M. Van Steen, Prentice Hall, 2007).

All the other slides are from the teacher of this course. All the material is subject to copyright and cannot be redistributed without consent of the copyright holder. The same holds for audio and video-recordings of the classes of this course.

Lesson Outline

- Client-Server Paradigm
- Iterative Servers
- Multi-threaded Servers
- Thread Synchronization - Synchronized

Client-Server Paradigm

- **Client-Server paradigm:** a Client asks a specific service to a Server
- **Socket:** endpoint of a bidirectional communication between two processes across the network

Client-Server Paradigm

Client

- creates a socket specifying the server address and the service port number
- Communication through the *established socket*


Server

- creates a *listening socket* specifying the service port number
- Once an input connection is received, it creates an *established socket*
- Communication through the *established sockets* of the server and the client


Iterative Servers

- **Iterative Servers** can handle one request at time

Iterative Servers



Iterative Servers



An Iterative Server in Java

UpperCaseServer

- The client read a line from the user (*stream inFromUser*) and sends it to the server via socket (*stream outToServer*)
- The server reads the line from the socket
- The server makes the line upper case and sends it back to the client
- The client read the converted line from the server (*stream inFromServer*) e prints it

An Iterative Server in Java – Client

```
1  import java.io.*;
2  import java.net.*;
3
4  class TCPClient {
5      public static void main(String argv[]) throws Exception {
6          String sentence;
7          String modifiedSentence;
8
9          // input stream initialization (from user keyboard)
10         BufferedReader inFromUser =
11             new BufferedReader(new InputStreamReader(System.in));
12
13         /* client socket initialization
14            localhost: server address
15            6789: server service port number */
16         Socket clientSocket = new Socket("localhost", 6789);
17
18         // output stream towards socket initialization
19         DataOutputStream outToServer =
20             new DataOutputStream(clientSocket.getOutputStream());
```



An Iterative Server in Java – Client

```
22      // input stream from socket initialization
23      BufferedReader inFromServer =
24          new BufferedReader(
25              new InputStreamReader(clientSocket.getInputStream()));
26
27      // read a line from the user
28      sentence = inFromUser.readLine();
29
30      // send the line to the server
31      outToServer.writeBytes(sentence + '\n');
32
33      // read the response from the server
34      modifiedSentence = inFromServer.readLine();
35      System.out.println("FROM SERVER: " + modifiedSentence);
36      clientSocket.close();
37  }
38 }
```

An Iterative Server in Java – Server

```
49 import java.io.*;
50 import java.net.*;
51
52 class TCPServer {
53     public static void main(String argv[]) throws Exception {
54         String clientSentence;
55         String capitalizedSentence;
56
57         // create a "listening socket" on the specified port
58         ServerSocket welcomeSocket = new ServerSocket(6789);
59
60         while(true) {
61             /* accept is a blocking call
62              once a new connection arrived, it creates
63              a new "established socket" */
64             Socket connectionSocket = welcomeSocket.accept();
```

An Iterative Server in Java – Server

```
66      // input stream from the socket initialization
67      BufferedReader inFromClient =
68          new BufferedReader(
69              new InputStreamReader(connectionSocket.getInputStream()));
70
71      // output stream to the socket initialization
72      DataOutputStream outToClient =
73          new DataOutputStream(connectionSocket.getOutputStream());
74
75      // read a line (that terminates with \n) from the client
76      clientSentence = inFromClient.readLine();
77      capitalizedSentence = clientSentence.toUpperCase() + '\n';
78
79      // send the response to the client
80      outToClient.writeBytes(capitalizedSentence);
81  }
82  }
83 }
```

An Iterative Server in Java – Issue

```
// read a line (that terminates with \n) from the client
clientSentence = inFromClient.readLine();

// wait for 10 seconds
Thread.sleep(10000);

capitalizedSentence = clientSentence.toUpperCase() + '\n';

// send the response to the client
outToClient.writeBytes(capitalizedSentence);
```

- What's the problem here?
- How to solve it?

Threads

- Threads are different execution sequences within the same process
- Threads share the same memory space
- Threads are scheduled as processes
- Useful for concurrent applications:
 - asynchronous events
 - Overlapping between I/O and computation
 - ...

Threads in Java – First Solution

Thread Inheriting

- Thread creation:
 - We extend the *Thread* class by defining a constructor that takes as arguments the references to the data structure the thread will access to
 - We redefine the *run()* method so that the thread can executes its task
- Thread invocation:
 - We create an instance of the thread
 - We call the *start()* method

Threads in Java – Second Solution

Implementing Runnable

- Thread creation:
 - We implement the *Runnable* interface by defining a constructor that takes as arguments the references to the data structure the thread will access to
 - We implement the *run()* method so that the thread can executes its task
- Thread invocation:
 - We create an instance of a *Thread* object, passing to its constructor an instance of the class that implements *Runnable*
 - We call the *start()* method

Threads in Java – Solutions Comparison

Thread Inheriting

Thread creation

```
public class MyThread extends Thread{  
    ...  
    public void run(){  
    ...  
}
```

Thread invocation

```
MyThread thread = new MyThread();  
thread.start();
```

Implementing Runnable

Thread creation

```
public class RunnableThread implements Runnable{  
    ...  
    public void run(){  
    ...  
}
```

Thread invocation

```
Thread thread = new Thread(new RunnableThread());  
thread.start();
```

Threads in Java


- Once the execution of a thread started, we have two executions in two different points of the code
 1. `run()` within the thread
 2. the point after the `start()` call
- The *father* thread can have a reference to the object related to the *son* thread
- We can use this reference to handle the threads in different ways
- After that the `run()` method ends, also the thread ends its execution

Concurrent Servers

- Different clients can *concurrently* send different requests to the port the server is listening on
- In iterative servers, the requests are queued and the server will *sequentially* accept and handle each request
- Solution: the server can simultaneously handle multiple connections through threads. It runs a different thread for each connection with a client

Multi-threaded Server

Dispatcher-Worker Model



Multi-threaded Server in Java - Dispatcher

```
30  import java.io.*;
31  import java.net.*;
32
33  class TCPServer {
34      public static void main(String argv[]) throws Exception {
35          ServerSocket welcomeSocket = new ServerSocket(6789);
36
37          while(true) {
38              Socket connectionSocket = welcomeSocket.accept();
39
40              // thread creation passing the established socket as arg
41              TCPThread theThread =
42                  new TCPThread(connectionSocket);
43
44              // start of the thread
45              theThread.start();
46          }
47      }
48  }
```



Multi-threaded Server in Java - Worker

```
55  import java.io.*;
56  import java.net.*;
57
58  public class TCPServerThread extends Thread {
59      private Socket connectionSocket = null;
60      private BufferedReader inFromClient;
61      private DataOutputStream outToClient;
62
63      // the constructor argument is an established socket
64      public TCPServerThread(Socket s) {
65          connectionSocket = s;
66          try {
67              inFromClient =
68                  new BufferedReader(
69                      new InputStreamReader(connectionSocket.getInputStream()));
70              outToClient =
71                  new DataOutputStream(connectionSocket.getOutputStream());
72          } catch (IOException e) {
73              e.printStackTrace();
74          }
75      }

```

Multi-threaded Server in Java - Worker

```
77     public void run() {  
78         String clientSentence;  
79         String capitalizedSentence;  
80         try {  
81             clientSentence = inFromClient.readLine();  
82             capitalizedSentence = clientSentence.toUpperCase() + '\n';  
83             outToClient.writeBytes(capitalizedSentence);  
84             connectionSocket.close();  
85         } catch (IOException e) {  
86             e.printStackTrace();  
87         }  
88     }  
89 }
```


Exercise – A Service for Sums

- Client:

- Reads address and port number of the server service from command line
- Reads two numbers from standard input and sends them to the server
- Receives and prints the response from the server

- Server:

- Reads the port number of the service from command line
- Prints address and port number of the connecting clients
- Receives two integers from each client, computes the sum and sends back the response with the result
- You have to handle the possible exceptions
- Develop both an iterative and a multi-threaded version of the server

Concurrent Programming

- A *concurrent program* is a set of instructions that could be executed simultaneously
- It is different from a *distributed system* in which several processes work in parallel, by communicating through a specific protocol
 - A concurrent program could run on a single processor (pseudo-parallelism)
- We will develop Java programs with different threads that work simultaneously
- The thread execution is non-deterministic and depends on the threads scheduling

Concurrent Programming - Issues

- The threads share the memory space of the process they belong to
- The data exchange is very efficient but subject to some issues
 - **Thread Interference**
 - **Memory Inconsistency**
- The Thread Synchronization is necessary to overcome these issues!

Thread Interference

```
1  class Counter {  
2      private int c = 0;  
3  
4      public void increment() {  
5          int newValue = c + 1;  
6          c = newValue;  
7      }  
8  
9      public void decrement() {  
10         int newValue = c - 1;  
11         c = newValue;  
12     }  
13 }
```

- Threads A and B execute simultaneously operations on the *Counter* object
- A invokes *increment()* and B invokes *decrement()*
- Remember that the execution order is non-deterministic!
- What could happen?

Thread Interference

```
1  class Counter {  
2      private int c = 0;  
3  
4      public void increment() {  
5          int newValue = c + 1;  
6          c = newValue;  
7      }  
8  
9      public void decrement() {  
10         int newValue = c - 1;  
11         c = newValue;  
12     }  
13 }
```

- c is equal to 0
- Possible execution order
 - A: $newValue = c + 1 = 1$;
 - B: $newValue = c - 1 = -1$;
 - A: $c = newValue = 1$;
 - B: $c = newValue = -1$;
- The result of the execution of A is being lost!

Memory Inconsistency

```
1  class Store {  
2      private int c = 10;  
3  
4      // return true if can sell  
5      public boolean sell() {  
6          if(c>0) {  
7              c--;  
8              return true;  
9          }  
10         return false;  
11     }  
12 }
```

- After some invocations, c is equal to 1
- Execution order:
 - A: *if* ($c > 0$)
 - B: *if* ($c > 0$)
 - A: $c--$; *return true*;
 - B: $c--$; *return true*;
- We've sold twice the last object!

Synchronized Access

- Every object instance has associated an *intrinsic lock*, that is also called *monitor*
- If a method is declared *synchronized*, before the execution of the method, the intrinsic lock must be acquired
- The *synchronized* methods grant that a single thread at a time can access to the object
- Example of declaration:
public synchronized int methodName(int param) {...}

Call of a Synchronized Method

- When a thread executes a synchronized method on an object *obj*, this is what atomically happens:
 - It is checked the value of the intrinsic lock associated with *obj*
 - If it is “available”:
 - The value of the intrinsic lock is changed to “not available”
 - The method is executed
 - Once the method ends, the value of the intrinsic lock is changed to “available”
 - If “not available”:
 - Wait until the intrinsic lock is “available”

Synchronization Example

- Let's consider a class *MyCollection* that stores a collection of objects
- A thread wants to order this collection
- Another thread wants to obtain the smallest element of the collection
- Why synchronization is required?
- How to synchronize?

Synchronization Example

```
class MyCollection {  
    synchronized void sortItems() {  
        // Sorting implementation  
    }  
  
    synchronized Object getSmallest() {  
        // Complicated code to get the minimum  
    }  
}
```

- Note that the attributes can't be declared *synchronized*
- The access to the data structures that must be synchronized can occur only through methods

Counter Class Correction

```
56  class Counter {  
57      private int c = 0;  
58  
59      public synchronized void increment(){  
60          int newValue = c + 1;  
61          c = newValue;  
62      }  
63  
64      public synchronized void decrement(){  
65          int newValue = c - 1;  
66          c = newValue;  
67      }  
68  }
```

- A invokes *increment()* and B invokes *decrement()*
- The only possible execution order:
 - A: $newValue = c + 1 = 1$;
 - A: $c = newValue = 1$;
 - B: $newValue = c - 1 = 0$;
 - B: $c = newValue = 0$;

Synchronized Statement

- Another way to write synchronized code concerns the use of *synchronized* statements

```
synchronized(objVar) {  
    // do stuff  
}
```

- The *objVar* to specify is the object that contains the intrinsic lock we want to use
- *objVar* typically is also the object on which we want to grant atomicity
- To synchronize primitive types (*int*, *float*, ...) we can create “dummy” objects which are used only for their lock

Synchronized Statement

Why these two codes have the same behavior?

```
public synchronized void methodA(){  
    // do stuff  
}
```

```
public void methodB() {  
    synchronized(this) {  
        // do stuff  
    }  
}
```

Synchronized Statement

- Why should we use a synchronized statement?
 - To avoid excessive synchronization
 - To achieve a finer synchronization
- In the following example, we consider two private fields *c1* and *c2* of the same class. *c1* and *c2* are **not** correlated

Synchronized Statement

```
public class FineGrainedSynchronization {  
    private Long c1 = 0;  
    private Long c2 = 0;  
    private Object lock1 = new Object();  
    private Object lock2 = new Object();  
  
    public void inc1() {  
        synchronized(lock1) {  
            c1++;  
        }  
    }  
  
    public void inc2() {  
        synchronized(lock2) {  
            c2++;  
        }  
    }  
}
```

Synchronized and Static Methods

- Also a static method can be defined *synchronized*

```
class Foo{  
    synchronized static void foo(){  
        // do stuff  
    }  
}
```

- The acquired lock is not related to the object instance, but to the class. This is equivalent to:

```
class Foo{  
    static void foo(){  
        synchronized(Foo.class){  
            // do stuff  
        }  
}
```




Deadlock

```
147 public class Model {
148     private View myView;
149
150     public synchronized void updateModel(Object someArg) {
151         doSomething(someArg);
152         myView.somethingChanged();
153     }
154
155     public synchronized Object getSomething() {
156         return someMethod();
157     }
158 }
159
160
161 public class View {
162     private Model underlyingModel;
163
164     public synchronized void somethingChanged() {
165         doSomething();
166     }
167
168     public synchronized void updateView() {
169         Object o = myModel.getSomething();
170     }
171 }
```

Some Observations

- The intrinsic lock associated with an object *obj* is used by all the *synchronized* methods and by the *synchronized* statements that specify *obj* as parameter
- It is **not** granted that the execution order of the waiting threads on a lock is equal to the order in which the threads have requested the lock
- The use of *synchronized* grants two properties:
 - **Mutual Exclusion**: only one thread at a time can obtain a specific lock
 - **Visibility**: the changes applied to the shared data before the lock is released must be visible to the threads that will acquire the lock later
- **Remember** to synchronize every time you have more threads that read and write the same data!

Visibility



- For optimization purposes, a thread can copy variables from the main memory to a CPU cache
- In a multi-cores setting, every thread can copy the variables in a different cache
- Without synchronization, we don't have guarantees about the update of a variable value

Volatile

- *volatile* is a keyword we can assign to *variables* (*volatile int x;*)
- It is a “light” version of *synchronized*
- It grants the **visibility**, but not the **mutual exclusion**
- The threads will automatically see the updated value of the *volatile* variables
 - The atomicity is granted only for direct reading and writing
- It must be used carefully: in a *volatile* variable we can write only values which are independent from any other state of the program (the variable itself included)
 - *x++* on a *volatile* variable is not thread-safe! Why?

Volatile

```
class Worker {  
    volatile boolean shutdownRequested;  
  
    public void shutdown() { shutdownRequested = true; }  
    public void doWork() {  
        while (!shutdownRequested) {  
            // do stuff  
        }  
    }  
}
```

- A thread executes in loop *doWork()*, another thread ends the work with *shutdown()*
- *volatile* ensures that the two threads have the same view on the data, and it is simpler than the use of *synchronized*

Exercise – The Theatre

- Service to book theatre tickets
- Assumptions: a single show, a single type of ticket
- It must be developed as a concurrent server
- Issue: you mustn't sell more than the available tickets
- You have to create the classes necessary for the multi-thread communication, and a class "Reservations" with a method without parameters that check if there are free seats:
 - If there are, it returns the number of the reserved seat
 - If there are not, it returns zero
- Check if the synchronization problems are solved by using Thread.sleep()

References

- Code Examples:

<https://ewserver.di.unimi.it/gitlab/luca.arrotta/lab1-examples>

- Exercises Setup:

https://ewserver.di.unimi.it/gitlab/riccardopresotto/setup_test_sdp

Contact

- Contact the tutors via email for any clarification or meeting:

tutorsdp@di.unimi.it