



## Discussion Forums

## Week 8

**SUBFORUMS****All**

Assignment: K-Means Clustering and PCA

[← Week 8](#)

## Tutorial for ex7: computeCentroids()



Tom Mosher · Mentor · Week 8 · 2 years ago

The method in this tutorial iterates over the centroids.

The function `computeCentroids` is called with parameters "X", "idx" and "K".

"K" is the number of centroids.

"idx" is a vector with one entry for each example in "X", which tells you which centroid each example is assigned to. The values range from 1 to K, so you will need a for-loop over that range.

You can get a selection of all of the indexes for each centroid with:

```
sel = find(idx == i) % where i ranges from 1 to K
```

Now we want to compute the mean of all these selected examples, and assign it as the new centroid value:

```
centroids(i,:) = mean(X(sel,:))
```



(Note that this method breaks if  $sel$  is a null vector (i.e. if no examples are assigned to centroid 'i'. In that case, probably should just compute  $centroid(i,:)$  if  $sel$  is a non-null vector.

Coursera



Repeat this procedure all each centroid. The function returns the computed centroid values.

=====

↑ 48 Upvotes

Reply

Follow this discussion

🔒 This thread is closed. You cannot add any more responses.

Earliest

Top

Most Recent



Tom Mosher · Mentor · 2 years ago · Edited



*This thread is closed to new posts. If you have a question, please post it in the Week 8 Discussion Forum area.*

↑ 1 Upvote

Reply