Conformalized Heteroscedastic Variant Effect Prediction with Local Coverage Guarantees

Anonymous Authors
Submission under double-blind review

Abstract

How fine should the Mondrian partition of a conformal predictor be under heteroscedasticity and class imbalance? The bin count K governs whether prediction sets attain bin-local coverage — the per-region calibration that pointwise conditioning provably cannot deliver in finite samples [Barber et al., 2020]. For binary conformal classification *within the equi-bin Mondrian-K family*, we prove a tight finite-sample $O(n^{-1/2})$ rate on the worst-cell coverage gap, $G(K^\star) \leq 2\sqrt{L_F R/(\pi_{\min} n)}$ at $K^\star = \lfloor \sqrt{L_F R \pi_{\min} n} \rfloor$, with a matching finite-sample lower bound on the same family that exposes an explicit $\pi_{\min}^{-1/2}$ constant (Theorem 3, 4); the rate is dimension-free because conditioning is on the 1-D summary $\hat{\sigma}(x)$. The result instantiates as **HCCP** (Heteroscedastic Class-Conditional Conformal Prediction), a post-hoc framework pairing a learned variance head $\hat{\sigma}$ with Mondrian-($y \times \hat{\sigma}$-bin) calibration. An explicit robustness corollary (T3′, via Barber et al. [2023]) certifies coverage under cell-level exchangeability violations identified by our per-chromosome KS audit on Mendelian. On TraitGym variant effect prediction [Benegas et al., 2025], HCCP is the only single-fold partition we evaluated — among normalized split, $\hat{\sigma}$-Mondrian, class-Mondrian, RLCP, weighted CP and SC-CP at matched $(\hat{p}, \hat{\sigma})$ — that simultaneously satisfies $\mathrm{cov}_{|Y=1} \geq 0.85$ and $\hat{\sigma}$-bin gap ≤ 0.20 on both Mendelian ($n = 3{,}380$) and Complex ($n = 11{,}400$), tightening the bin-local gap by $33\times$ on Complex and $2.3\times$ on Mendelian over the strongest single-axis Mondrian baseline (class-Mondrian), with cross-domain replication on ProteinGym [Notin et al., 2023]. A K_{eval} sensitivity sweep (App. C.1) shows HCCP's Complex advantage is robust across $K_{\mathrm{eval}} \in [2, 10]$ (3–$34\times$); on Mendelian weighted CP narrows HCCP's margin to $1.15\times$ at the recommended operating point and overtakes HCCP at high K_{eval} where the per-cell minority count drops below ~ 70. The GBM aggregator on TraitGym features reaches AUPRC 0.900 on Mendelian, a $+14.8$ pp improvement over the published LogReg baseline.

1 Introduction

Clinical variant interpretation needs more than a score. Classifying a human genomic variant as pathogenic or benign drives consequential clinical decisions, from cascade testing of relatives to reproductive choices. The ACMG/AMP consensus guidelines [Richards et al., 2015] structure this decision as a weighted aggregation of evidence categories rather than as a point estimate. Modern machine-learned variant effect predictors (VEPs) collapse that structure into a single probability [Kircher et al., 2014, Linder et al., 2025, Benegas et al., 2023, 2025], which clinicians then threshold downstream. This presents the user with a number that lacks an explicit notion of confidence: the same $\hat{p}(x) = 0.6$ may reflect a well-covered near-decision variant for which labels are genuinely

Preprint. Under review.



Figure 1: HCCP at a glance. **(a)** A heteroscedastic aggregator produces a point estimate $\hat{p}(x)$ and a learned variance $\hat{\sigma}(x)$; the nonconformity score $s(x, y) = |y - \hat{p}(x)|/\hat{\sigma}(x)$ scales the decision radius by local uncertainty. **(b)** Mondrian calibration partitions the labeled data by $(y \times \hat{\sigma}\text{-bin})$; per-cell quantile thresholds $\hat{q}_{k,b}$ restore both class-conditional (T2) and bin-conditional (T3) coverage, while remaining compatible with Barber's [Barber et al., 2020] pointwise impossibility. **(c)** Three-axis OOD stress tests — chromosome-LOO, trait-LOO, cross-dataset — verify that the $\hat{\sigma}$-bin coverage gap reaches the finite-sample floor 0.002–0.004 under trait-LOO and stays ≤ 0.077 across chromosome-LOO and the C→M cross-dataset direction on TraitGym; the M→C cross-dataset direction is reported as an honest limitation.

ambiguous, or an out-of-distribution prediction for which the model is silently extrapolating. What is missing is a prediction *set* with finite-sample coverage guarantees that remain informative when the data-generating regime shifts across chromosomes, traits, or disease architectures.

Existing uncertainty quantification for VEP is either absent or marginal-only. The TraitGym benchmark [Benegas et al., 2025], the current standard for evaluating VEP aggregators on 3,380 Mendelian and 11,400 complex-trait variants, reports only point AUPRC and provides no calibration of its LogReg aggregator. DEGU [Zhou et al., 2026] introduces a heteroscedastic variance head for MPRA regression via deep ensemble distillation and explicitly motivates conformal prediction as future work, but the published method does not formalise a coverage guarantee or transfer to variant classification. Conformal prediction itself is mature: split CP [Vovk et al., 2005], Mondrian CP [Vovk et al., 2003], CQR for regression [Romano et al., 2019], jackknife+ [Barber et al., 2021], and CP beyond exchangeability [Barber et al., 2023] cover a wide design space, and Barber et al. [Barber et al., 2020] rule out pointwise conditional coverage in finite samples. What is *not* in prior art is a composition that (i) consumes a learned $\hat{\sigma}(x)$ the way CQR consumes a quantile regressor, (ii) stratifies calibration by both label and $\hat{\sigma}$-bin to regain as much conditionality as finite samples allow, and (iii) carries local coverage guarantees across the distribution shifts that define real VEP deployment. The gap is especially load-bearing for VEP: the minority-class (pathogenic) positive rate is $\approx 10\%$, $\hat{p}(x)$ is sharply heteroscedastic across the $\hat{\sigma}$-bins we identify, and chrom-LOO + trait-LOO + cross-dataset shift are intrinsic to any clinical rollout.

From clinical gap to a sharper technical question. The three requirements above translate into a precise question: which Mondrian partition simultaneously delivers (i) class-conditional coverage under extreme imbalance ($\pi_{\min} \approx 0.10$ on TraitGym) and (ii) bin-local coverage under heteroscedasticity? Off-the-shelf single-axis answers fail individually: $\hat{\sigma}$-Mondrian (Boström and Johansson [2020]; `crepes` [Boström, 2022]) attains local coverage but *collapses to* $\mathrm{cov}_{|Y=1} = 0.66$ *on TraitGym Complex*; class-Mondrian (Sadinle et al. [2019]; equivalent to Vovk et al. [2003]) attains class coverage but leaves a bin-local gap $33\times$ wider than the joint partition on Complex and $2.3\times$ wider on Mendelian under cross-method-fair K_{eval} scoring. Within the equi-bin Mondrian-K family, we prove the joint $(y \times \hat{\sigma}\text{-bin})$ Mondrian attains both with worst-cell coverage gap $G(K^\star) \leq 2\sqrt{L_F R/(\pi_{\min} n)}$ (Theorem 3) and a matching $\Omega(\sqrt{L_F R/(\pi_{\min} n)})$ finite-sample lower bound (Theorem 4). Crucially, $\pi_{\min}$ enters the rate *explicitly* — a finite-sample dependence that prior class-conditional CP and prior imbalanced CP analyses (Ding et al. [2023], Xie et al. [2025], Shi

et al. [2024]) do not provide. HCCP is the post-hoc framework that instantiates this answer in the VEP setting.

Contributions. Figure 1 summarizes the pipeline. Our contributions are:

1. **Joint partition is uniquely necessary (empirical Pareto).** Across the off-the-shelf CP variants we evaluated on TraitGym (split CP, $\hat{\sigma}$-Mondrian, class-Mondrian, RLCP [Hore and Barber, 2025], weighted CP [Tibshirani et al., 2019], SC-CP [van der Laan, 2024]; Tab. 4, 5), no single-axis variant simultaneously satisfies $\mathrm{cov}_{|Y=1} \geq 0.85$ and $\hat{\sigma}$-bin gap ≤ 0.20 on both datasets at $\pi_{\min} = 0.10$. HCCP's joint $(y \times \hat{\sigma}\text{-bin})$ Mondrian is the unique frontier point at this corner under cross-method-fair K_{eval} scoring, tightening the bin-local gap by $33\times$ on Complex and $2.3\times$ on Mendelian over the strongest of these baselines at matched $(\hat{p}, \hat{\sigma})$ — the empirical observation that motivates the rest of the paper.
2. **Tight finite-sample rate within the equi-bin Mondrian-K class, with $\pi_{\min}$ explicit in the constant.** For Mondrian conformal classification stratified by a learned L_F-Lipschitz variance head $\hat{\sigma}$ within the equi-bin Mondrian-K family, Theorem 3 proves the worst-cell coverage gap satisfies $G(K^\star) \leq 2\sqrt{L_F R/(\pi_{\min} n)}$ at $K^\star = \lfloor \sqrt{L_F R \pi_{\min} n} \rfloor$. Theorem 4 establishes a matching $\Omega(\sqrt{L_F R/(\pi_{\min} n)})$ lower bound under an explicitly constructed worst-case family, so the $O(n^{-1/2})$ rate is unimprovable within this class without strengthening assumptions; the minority-class prevalence $\pi_{\min}$ enters the constant as an explicit $\pi_{\min}^{-1/2}$ factor. To our knowledge this is the first finite-sample bound for class-conditional + heteroscedastic-local CP in which the minority-class probability appears in the rate; the constant is dimension-free under a 1-D Lipschitz assumption on $\hat{\sigma}$. Concurrent imbalanced-CP work [Xie et al., 2025, Ding et al., 2023, Shi et al., 2024] provides marginal or class-cond rates without the $\pi_{\min}$-local product (§5.3, App. A.11).
3. **HCCP — a post-hoc framework with an exchangeability-robust counterpart.** A gradient-boosted aggregator $\hat{p}$ over pre-trained genomic features, a reliability head $\hat{\sigma}$ trained under Gaussian NLL on chrom-LOO out-of-fold residuals, and Mondrian conformal calibration stratified by $(y \times \hat{\sigma}\text{-bin})$. The nonconformity score $s(x, y) = |y - \hat{p}(x)|/\hat{\sigma}(x)$ is the binary-classification analog of CQR [Romano et al., 2019]; the partition extends Mondrian-by-y [Sadinle et al., 2019, Vovk et al., 2003] with a heteroscedastic second taxon level. HCCP simultaneously admits marginal (T1), class-conditional (T2), and bin-conditional (T3) coverage with finite-sample rate $1/(n_{k,b} + 1)$ from a single calibration fold; an explicit robustness layer T3′, via Barber et al. [2023] Theorem 2 at the cell level, makes coverage operational under verifiably violated cell-level exchangeability and is the binding guarantee on Mendelian (per-chromosome KS rejection 46%, App. B.4). HCCP is compatible with Barber et al. [2020]'s pointwise impossibility throughout (§4, §5.1).
4. **Empirical validation on TraitGym and ProteinGym.** On TraitGym Mendelian ($n =$ 3,380) and Complex ($n =$ 11,400), HCCP under proper nested chrom-LOO K-selection is the unique single-fold partition simultaneously satisfying minority-class and bin-local coverage at $\pi_{\min} = 0.10$ across both datasets and across an imbalance sweep $\pi_{\min} \in \{0.05, 0.10, 0.20, 0.30, 0.50\}$ (Tab. 4, 6); off-the-shelf $\hat{\sigma}$-Mondrian's $\mathrm{cov}_{|Y=1}$ degrades monotonically as $\pi_{\min} \to 0$ while HCCP holds at target — the $\pi_{\min}$-explicit rate of T5 manifests empirically. The same machinery transfers to ProteinGym [Notin et al., 2023] cross-domain ($\approx$ 357k mutants, 50 held-out assays, App. E). The GBM aggregator on TraitGym features attains AUPRC 0.900 on Mendelian, a $+14.8$ pp improvement over the published LogReg baseline [Benegas et al., 2025].

The result is a post-hoc framework with a matching-rate theoretical guarantee and a drop-in implementation that consumes any probabilistic VEP and returns prediction sets with three layers of coverage (marginal, class-conditional, and $\hat{\sigma}$-bin-local), all of which degrade gracefully under the distribution shifts that clinical deployment unavoidably induces.

2 Related work

Conformal prediction and conditional coverage. Split conformal prediction [Vovk et al., 2005, Lei et al., 2018] provides distribution-free marginal coverage, and Mondrian conformal [Vovk et al.,

2003] extends this to group-conditional coverage via partitioned calibration; we refer the reader to Angelopoulos and Bates [2022] for a recent introduction. Barber et al. [2020] showed that pointwise conditional coverage $P(Y \in \mathcal{C}_\alpha(X) \mid X = x)$ is impossible in finite samples without structural assumptions, motivating coarsened conditioning.

Normalized nonconformity scores with a learned $\hat{\sigma}$ originate with Papadopoulos et al. [2008], who used kNN-residuals or a separate regressor to scale the absolute residual; Lei et al. [2018] §5 supplies a formal analysis of the locally-weighted score $|y - \hat{\mu}(x)|/\hat{\sigma}(x)$ for regression. Boström and Johansson [2020] systematized Mondrian conformal regression with normalized scores, and the `crepes` package [Boström, 2022] ships an industrial implementation that accepts a difficulty estimator and a Mondrian categorizer as plug-ins. Our score Eq. (3) extends this lineage in three respects: (i) it is a binary-classification adaptation of the normalized form (CQR [Romano et al., 2019] is the regression analog; RAPS [Angelopoulos et al., 2021] is a classification-side adaptive score that does not exploit a learned $\hat{\sigma}$); (ii) the same $\hat{\sigma}$ is embedded inside the Mondrian partition ($y \times \hat{\sigma}$-bin), not only inside the score; (iii) we provide finite-sample analysis of the bin count K under extreme class imbalance ($\pi_{\min} \approx 0.10$), neither addressed in prior normalized-Mondrian work. Tibshirani et al. [2019] established weighted CP under covariate shift, which we invoke to interpret the asymmetric C→M vs M→C transfer in §6; Gibbs and Candès [2021] cover online distribution shift, complementary to our batch chrom-shift bound T4. Barber et al. [2023] generalized CP beyond exchangeability via weighted residual swaps; we use their Theorem 2 for robust forms T1′–T3′ and T4.

Three recent lines of work target conditional coverage more directly. **RLCP** [Hore and Barber, 2025] uses random localization with kernel weights to achieve feature-space local coverage at rate $O(n^{-2/(d+2)})$; this degrades in high dimensions ($d > 100$), making it impractical for our genomic feature space ($d \approx 7{,}700$). De Wolf et al. [2025] analyze the conditional validity of heteroscedastic Mondrian conformal for regression, establishing when normalized and Mondrian CP adapt correctly to the noise level; our T3–T5 complement their analysis by deriving the optimal Mondrian granularity (bin count K) for classification with a *learned* variance head. **Self-Calibrating CP** [van der Laan, 2024] provides prediction-conditional validity by binning along the calibrated point prediction $\hat{\mu}$ via Venn–Abers / isotonic calibration, achieving a faster $O(n^{-2/3})$ rate that exploits the monotone structure of isotonic regression [Deng et al., 2021] without a Lipschitz score assumption. Their construction is on the orthogonal $\hat{\mu}$-axis and, as the authors note, does not adapt to mean-independent heteroscedasticity; our T5 conditions on the $\hat{\sigma}$-axis under 4 and admits class-imbalance constants ($\pi_{\min}$) that SC-CP, restricted to regression, does not encode. Toccaceli [2026] (concurrent) identifies the optimal bin count under covariate-sorted contiguous binning as an open problem in conformal regression; Theorem 3 resolves a special case of this open problem for ($y \times \hat{\sigma}$-bin) Mondrian under class imbalance.

Class-conditional and imbalanced conformal classification. **Class-conditional CP.** Sadinle et al. [2019] introduced label-conditional CP (the LAC score with separate per-class quantiles), which is the canonical fix for marginal CP's class-imbalance pathology and is functionally equivalent to Mondrian-by-y [Vovk et al., 2003]; Shi et al. [2024] augment the label rank score for tighter class-wise coverage in many-class settings. Ding et al. [2023] cluster classes adaptively to retain class-conditional coverage when per-class calibration sizes are small. **Imbalanced binary CP.** Xie et al. [2025] (concurrent) study open-set + imbalanced classification with reweighting, providing a $O(n^{-1/2})$ marginal-coverage bound; their analysis does not condition on a heteroscedastic axis and does not let $\pi_{\min}$ enter a local coverage rate. The empirical observation driving this paper is that none of these methods address the heteroscedastic axis: as our H2H ablation shows (Tab. 4), *single-axis* Mondrian predictors face a fundamental tradeoff in the imbalanced regime — class-Mondrian preserves $\mathrm{cov}_{|Y=1}$ but loses $\hat{\sigma}$-bin local coverage (gap 0.32–0.45), while $\hat{\sigma}$-Mondrian preserves local coverage but loses $\mathrm{cov}_{|Y=1}$ down to 0.66 at $\pi_{\min} = 0.10$. HCCP's joint ($y \times \hat{\sigma}$-bin) Mondrian is, to our knowledge, the first construction simultaneously satisfying both objectives in this regime, with T5 quantifying the price as $O(\sqrt{L_F R/(\pi_{\min} n)})$ — an explicit dependence on $\pi_{\min}$ that prior class-conditional CP and prior imbalanced CP do not provide.

Multi-objective coverage and selective classification. Recent work on conformal risk control [Angelopoulos and Bates, 2022] and *Pareto testing* [Laufer-Goldshtein et al., 2023] extends CP to multiple risks; these target a Pareto frontier in the (*risk, set-size*) space rather than a frontier across

distinct *coverage* objectives (marginal vs. class-conditional vs. local). Our analysis is orthogonal: T5 characterises the unique joint partition under which marginal, class-conditional, and $\hat{\sigma}$-bin coverage are all attained simultaneously. We are also *not* a selective-classification framework in the sense of El-Yaniv and Wiener [2010], Geifman and El-Yaniv [2017]: HCCP outputs a calibrated prediction set rather than a single label with a learned reject option, and our coverage guarantees apply to every variant rather than to a confident subset.

Heteroscedastic uncertainty quantification. Gaussian NLL training for learned variance originates with Nix and Weigend [1994]. Deep ensembles [Lakshminarayanan et al., 2017] capture epistemic uncertainty via inter-model disagreement. DEGU [Zhou et al., 2026] pioneered the application of learned heteroscedastic variance heads to genomic UQ, distilling a deep-ensemble teacher into a Gaussian-uncertainty student for MPRA regression. We build directly on this lineage by extending heteroscedastic $\hat{\sigma}$ to (a) variant classification, (b) conformal prediction sets that consume $\hat{\sigma}$ inside the nonconformity score, and (c) finite-sample local coverage with adaptive partition granularity (T5). Our DEGU-lite ablation (§6) maps out where each $\hat{\sigma}$ source is more informative: ensemble disagreement is comparable to supervised residual regression on Mendelian (monogenic, where epistemic and aleatoric uncertainty are similar in magnitude); supervised $\hat{\sigma}$ captures the aleatoric component that dominates Complex polygenic traits ($4.3\times$ smaller worst-cell gap).

Variant effect prediction and benchmarks. TraitGym [Benegas et al., 2025] standardizes VEP evaluation on Mendelian and complex trait variants, with a chrom-LOO protocol. Input features include CADD [Kircher et al., 2014], Borzoi [Linder et al., 2025], and GPN-MSA [Benegas et al., 2023]. AlphaGenome [Avsec et al., 2026] is the most recent foundation model for genomics, though it has not been evaluated on TraitGym to date; ProteinGym [Notin et al., 2023] is a related large-scale variant fitness benchmark in the protein domain (217 DMS assays, 2.4M mutants), which we use as a cross-domain stress test for HCCP's coverage machinery (App. E). Conformal prediction has been explored in genomic medicine for drug response [Papangelou et al., 2025] and polygenic risk scores [Wang et al., 2025], but not for binary variant pathogenicity classification. To our knowledge, HCCP is the first framework to provide class-conditional and bin-local coverage guarantees for VEP.

3 Problem formulation

3.1 Setup

Let $X \in \mathcal{X} \subseteq \mathbb{R}^d$ denote a variant feature vector, $Y \in \{0, 1\}$ its pathogenic label, and $C \in \mathcal{C} = \{1, \ldots, 22, X\}$ its chromosome. We observe $\mathcal{D} = \{(X_i, Y_i, C_i)\}_{i=1}^n$. We adopt TraitGym's [Benegas et al., 2025] chrom-LOO evaluation: for each test chromosome $c^\star \in \mathcal{C}$, set $\mathcal{D}^{(-c^\star)} = \{i : C_i \neq c^\star\}$ for train + calibration and $\mathcal{D}^{(c^\star)} = \{i : C_i = c^\star\}$ for test. The benchmark's primary metric is AUPRC weighted by test-chromosome size.

Exchangeability. We anchor our analysis on a triple of structured exchangeability assumptions, of increasing strength:

Assumption 1 (A1 Chrom-group exchangeability)**.** *Conditional on $C = c$, $\{(X_i, Y_i) : C_i = c\}$ are exchangeable with chrom-specific law P_c. Different chromosomes are mutually independent.*

Assumption 2 (A1' Chrom-wise i.i.d.)**.** *Conditional on $C = c$, $\{(X_i, Y_i) : C_i = c\}$ are i.i.d. P_c. Strict strengthening of 1.*

Assumption 3 (A2 Score stationarity across chromosomes)**.** *The score law is chrom-invariant at some granularity: A2-marginal, A2-class (conditional on $Y = k$), or A2-cell (conditional on $Y = k$ and $\hat{\sigma}$-bin membership $b(X) = b$). Hierarchy: A2-cell $\Rightarrow$ A2-class $\Rightarrow$ A2-marginal.*

1 is load-bearing (empirical chrom-LOO protocol). 2 and 3 enable finite-sample *exact* coverage; under 1 alone we obtain *robust* coverage with a chromosome total-variation gap (§5). Empirically, the within-cell KS audit (App. B, Table 9) finds approximate stationarity on Complex (10.4% rejection across 125 tests, near the 5% null) and pronounced cell-level violations on Mendelian (46.2% rejection across 52 tests, max KS 0.434); T3′ is the operational certificate on Mendelian (§5.2), T3 exact suffices on Complex.



Figure 2: **A-SL audit.** Each subfigure shows (a) per-pair Lipschitz ratio histogram with median, p95, p99, max, and the LCLS least-squares slope $\hat{L}_F$ overlay; (b) raw KS vs σ-gap scatter, LCLS slope (green), and noise-adjusted p95 upper envelope $L_F^{(95\%)}$ (purple). On Mendelian (left, $n = 3380$) the upper envelope is wider because KS sampling noise dominates small bins; on Complex (right, $n = 11400$) noise contracts, exposing a tighter envelope $L_F^{(95\%)} = 8.1$. In both cases the noise-adjusted distribution has finite, bounded support, supporting 4.

Assumption 4 (A-SL Score-Lipschitz regularity)**.** *The conditional score CDF varies smoothly with the $\hat{\sigma}$ value: for each class $k \in \{0, 1\}$,*

$$\sup_{s\in\mathbb{R}} \big|F_{k,\sigma_1}(s) - F_{k,\sigma_2}(s)\big| \;\le\; L_F \cdot |\sigma_1 - \sigma_2|, \qquad \forall\, \sigma_1, \sigma_2 \in [\hat{\sigma}_{\min}, \hat{\sigma}_{\max}],$$

where $F_{k,\sigma}(s) := P(S \le s \mid Y = k,\, \hat{\sigma}(X) = \sigma)$ and L_F is the score-Lipschitz constant.

4 controls how the score distribution shifts across $\hat{\sigma}$-bins. Since $s(x, k) = |k - \hat{p}(x)|/(\hat{\sigma}(x) + \epsilon)$, a change δ in $\hat{\sigma}$ rescales the score by $O(\delta/\hat{\sigma}^2)$, so 4 holds when $\hat{p}$ and $\hat{\sigma}$ are bounded. This assumption is used only by T5 (§5.3) to derive the optimal bin count $K^\star$; T3 is valid for any fixed K without 4.

Empirical audit of 4. We probe 4 by computing per-pair Lipschitz ratios $\rho_{k,a,b} = \mathrm{KS}(\hat{F}_{k,a}, \hat{F}_{k,b})/|\bar{\sigma}_a - \bar{\sigma}_b|$ across all $(k, a < b)$ within-class $\hat{\sigma}$-bin pairs (Fig. 2, $K = 30$ bins, ≥ 20 variants per bin). The naive maximum saturates at the KS sample-noise floor on small bins. After subtracting the per-pair noise floor $c_{0.05}\sqrt{(n_a + n_b)/(n_a n_b)}$, the noise-adjusted upper envelope is finite without fat-tail breakdown: $L_F^{(95\%)} = 13.8$ (Mendelian, $n_{\text{pairs}} = 325$) and $L_F^{(95\%)} = 8.1$ (Complex, $n_{\text{pairs}} = 870$). The LCLS least-squares estimator $\hat{L}_F \approx$ 3–4.5 (App. A, Table 18) measures the *typical* local slope and underestimates the upper envelope by ∼3–5×, as expected for a least-squares slope vs. a sup-Lipschitz constant. Plugging $L_F^{(95\%)}$ into T5.1 leaves $K^\star = O(\sqrt{n})$ well above the empirical $\hat{K}_{\text{CV}} \in \{2, 3\}$, so the finite-sample variance term remains the binding constraint regardless of which envelope is used.

3.2 Base aggregator and heteroscedastic head

Aggregator $\hat{p}$. A probabilistic classifier $\hat{p} : \mathcal{X} \to [0, 1]$ fit on $\mathcal{D}^{(-c^\star)}$. In experiments we use *HistGradientBoostingClassifier* (depth 2, 100 iters, class-balanced), which is both an ablation variant of TraitGym's LogReg baseline and the current SOTA aggregator on Mendelian (§6).

Heteroscedastic reliability head $\hat{\sigma}$. A second regressor $\hat{\sigma} : \mathcal{X} \to \mathbb{R}_+$ predicting the expected chrom-LOO residual magnitude:

$$\hat{\sigma}(x) \;\approx\; \sqrt{\mathbb{E}\big[(Y - \hat{p}^{(-C)}(X))^2 \,\big|\, X = x\big]}. \tag{1}$$

We train $\hat{\sigma}$ on residual targets $r_i = |Y_i - \hat{p}^{(-C_i)}(X_i)|$ with a Gaussian negative log-likelihood objective:

$$\mathcal{L}_{\text{GLL}}(\hat{\sigma}) = \sum_{i\in\mathcal{D}^{(-c^\star)}} \left[\frac{r_i^2}{2\hat{\sigma}(X_i)^2} + \log \hat{\sigma}(X_i)\right] + \lambda\|\theta\|^2, \tag{2}$$

matching DEGU's heteroscedastic baseline [Zhou et al., 2026] so that the $\hat{\sigma}$ head is apples-to-apples with prior art. We use the same GBM backbone for $\hat{\sigma}$ and $\hat{p}$.

3.3 Nonconformity score and Mondrian prediction set

The *feature-dependent* nonconformity score is

$$s(x, y) \;:=\; \frac{|y - \hat{p}(x)|}{\hat{\sigma}(x) + \epsilon}, \qquad \epsilon = 10^{-6}. \tag{3}$$

This is a binary-classification analog of CQR [Romano et al., 2019]: large $\hat{\sigma}(x)$ yields a more permissive threshold, shrinking the effective radius in high-confidence regions.

Mondrian-($y \times \hat{\sigma}$-bin) calibration. Fix $K \in \mathbb{N}$ and define K $\hat{\sigma}$-bins by the calibration-fold quantile edges $e_0 < \cdots < e_K$ with $B_b = (e_{b-1}, e_b]$. Let $b(x)$ be the bin index of x. For each cell (k, b) collect $\mathcal{I}_{kb}^{(-c^\star)} = \{i \in \mathcal{D}^{(-c^\star)} : Y_i = k,\ \hat{\sigma}(X_i) \in B_b\}$ of size n_{kb}, compute the per-cell threshold

$$\hat{q}_{k,b} \;=\; \mathrm{Quantile}\left(\{s(X_i, k) : i \in \mathcal{I}_{kb}^{(-c^\star)}\},\ \frac{\lceil (n_{kb}+1)(1-\alpha) \rceil}{n_{kb}}\right), \tag{4}$$

and predict

$$\mathcal{C}_\alpha(x) \;=\; \big\{k \in \{0,1\} : s(x,k) \le \hat{q}_{k,b(x)}\big\}. \tag{5}$$

Equivalently, $k \in \mathcal{C}_\alpha(x)$ iff $|k - \hat{p}(x)| \le \hat{q}_{k,b(x)} \cdot \hat{\sigma}(x)$, so the decision radius scales with local heteroscedasticity.

Comparison to prior scores. Split conformal [Vovk et al., 2005] uses $s = |y - \hat{p}(x)|$, independent of x. CQR [Romano et al., 2019] uses quantile regression, regression-only. DEGU [Zhou et al., 2026] learns $\hat{\sigma}$ but does not fold it into the score. Our score (3) combines DEGU's $\hat{\sigma}$ machinery with the Mondrian partition of Vovk et al. [2003] stratified by $(y, b(x))$, the unique product partition over $\{y, b(x)\}$ that admits both class-conditional (T2) and bin-conditional (T3) coverage simultaneously (§4, §5).

Coverage targets. Given $\alpha \in (0, 1)$, we require:

(i) *Marginal coverage* $P(Y \in \mathcal{C}_\alpha(X)) \ge 1 - \alpha$ (T1);

(ii) *Class-conditional coverage* $P(Y \in \mathcal{C}_\alpha(X) \mid Y = k) \ge 1 - \alpha$ for each k (T2);

(iii) *$\hat{\sigma}$-bin local coverage* $P(Y \in \mathcal{C}_\alpha(X) \mid Y = k, b(X) = b) \approx 1 - \alpha$ for each (k, b) (T3);

(iv) *Chrom-shift robustness*: the (i)–(iii) gaps degrade gracefully under total-variation drift between $P_{c^\star}$ and the calibration mixture (T4).

Pointwise conditional coverage $P(Y \in \mathcal{C}_\alpha(X) \mid X = x) \ge 1 - \alpha$ is ruled out in finite samples [Barber et al., 2020]; our (iii) is the coarsest practically useful strengthening.

4 Method: HCCP

4.1 Pipeline overview

HCCP is a three-stage post-hoc framework on top of any probabilistic classifier: (1) aggregator $\hat{p}$, (2) heteroscedastic head $\hat{\sigma}$, (3) Mondrian-($y \times \hat{\sigma}$-bin) conformal calibration. Each stage is decoupled, so HCCP accepts any $(\hat{p}, \hat{\sigma})$ pair as a drop-in; we instantiate with gradient boosting for reproducibility and CPU tractability on TraitGym scale ($n \le 11{,}400$).

1. **Aggregator $\hat{p}$.** Trained on $\mathcal{D}^{(-c^\star)}$ with chrom-LOO out-of-fold (OOF) predictions retained for the $\hat{\sigma}$ fit. We use HistGradientBoostingClassifier (depth 2, 100 iters, class-balanced); §6 shows this strictly dominates TraitGym's LogReg aggregator on Mendelian ($+14.8$ pp AUPRC).
2. **Heteroscedastic head $\hat{\sigma}$.** Trained on OOF residual targets $r_i = |Y_i - \hat{p}^{(-C_i)}(X_i)|$ with the Gaussian NLL objective of Eq. (2). Same GBM backbone. Using OOF residuals (rather than in-sample) avoids an optimistic bias; §6 ablates in-sample alternatives.
3. **Mondrian calibration.** Partition $\mathcal{D}^{(-c^\star)}$ into $2K$ cells via $(Y_i, \mathrm{bin}_K(\hat{\sigma}(X_i)))$. Per-cell thresholds $\hat{q}_{k,b}$ of Eq. (4). Prediction set of Eq. (5).

Algorithm 1 states the full pipeline.

Algorithm 1 HCCP — Heteroscedastic Class-Conditional Conformal Prediction

Require: Data $\mathcal{D}$, test chrom $c^\star$, miscoverage α, bin count K

$\mathcal{D}_{\text{tr}} \leftarrow \{i : C_i \neq c^\star\}, \mathcal{D}_{\text{te}} \leftarrow \{i : C_i = c^\star\}$
Fit $\hat{p}$ on $\mathcal{D}_{\text{tr}}$; compute chrom-LOO OOF predictions $\{\hat{p}^{(-C_i)}(X_i)\}_{i \in \mathcal{D}_{\text{tr}}}$
Fit $\hat{\sigma}$ on targets $\{|Y_i - \hat{p}^{(-C_i)}(X_i)|\}_{i \in \mathcal{D}_{\text{tr}}}$ under Gaussian NLL (Eq. 2)
Compute $\hat{\sigma}$-bin edges $e_0 < \cdots < e_K$ from $\{\hat{\sigma}(X_i)\}_{i \in \mathcal{D}_{\text{tr}}}$ quantiles
Compute calibration scores $s_i = |Y_i - \hat{p}(X_i)|/(\hat{\sigma}(X_i) + \epsilon)$ for $i \in \mathcal{D}_{\text{tr}}$
Partition $\mathcal{D}_{\text{tr}}$ by $(Y_i, \text{bin}_K(\hat{\sigma}(X_i)))$; compute $\hat{q}_{k,b}$ via Eq. (4)
for each cell (k, b) with $n_{k,b} < \lceil 1/\alpha \rceil$ **do** ▷ small-cell fallback
    $\hat{q}_{k,b} \leftarrow \hat{q}_k$ ▷ T2 pooled class-conditional threshold
end for
for each test point $x \in \mathcal{D}_{\text{te}}$ **do**
    $b \leftarrow \text{bin}_K(\hat{\sigma}(x))$
    $\mathcal{C}_\alpha(x) \leftarrow \{k \in \{0, 1\} : |k - \hat{p}(x)| \leq \hat{q}_{k,b} \cdot \hat{\sigma}(x)\}$
end for
return $\{(x, \mathcal{C}_\alpha(x)) : x \in \mathcal{D}_{\text{te}}\}$

Worked example (toy). To make the cell-fallback logic concrete, consider a calibration fold of $n_{\text{tr}} = 20$ variants with $K = 2$ $\hat{\sigma}$-bins, $\alpha = 0.10$, and a positive rate of 20% ($n_+ = 4$). The bin edge is the median of $\hat{\sigma}$ over the calibration fold; let four positives split as $(n_{1,0}, n_{1,1}) = (1, 3)$ and sixteen negatives as $(n_{0,0}, n_{0,1}) = (9, 7)$. The (k, b) cell-counts are therefore $(9, 7, 1, 3)$. With $\lceil 1/\alpha \rceil = 10$, only the negative-low-$\hat{\sigma}$ cell $(0, 0)$ has $n_{0,0} = 9$, narrowly below the threshold; all other cells are below as well, so all four cells trigger the pooled class-conditional fallback (small-cell fallback step of Algorithm 1). For positives we set $\hat{q}_{1,b} = \hat{q}_1$ where $\hat{q}_1$ is the $\lceil (n_+ + 1)(1 - \alpha) \rceil / n_+ = 0.99$ quantile of the four positive scores (effectively the maximum). For negatives we set $\hat{q}_{0,b} = \hat{q}_0$ as the analogous quantile over the sixteen negative scores. A test point with $\hat{\sigma}$ in bin b produces $\mathcal{C}_\alpha(x) = \{k : |k - \hat{p}(x)|/(\hat{\sigma}(x) + \epsilon) \leq \hat{q}_{k,b(x)}\}$. In this toy regime the predictor effectively behaves like T2 class-conditional CP because cells are too small for T3; HCCP's local-coverage advantage emerges only once K and n are large enough that $n_{k,b} \geq \lceil 1/\alpha \rceil$. On TraitGym Mendelian ($n_+ = 338$) at $K = 5$, the smallest cell has $n_{k,b} \geq 13$ and HCCP delivers full T3 bin-conditional coverage on most cells (App. C.4).

4.2 Why Mondrian on ($y \times \hat{\sigma}$-bin)?

Pure class-conditional calibration (Mondrian on y alone) [Vovk et al., 2003] fixes the imbalance pathology of split conformal — without stratifying by y, the minority class (positives, ≈10% on TraitGym) is systematically under-covered — but leaves within-class local coverage unaddressed. Our ablation experiments confirm this: class-conditional + homoscedastic calibration reached $\text{cov}_{|Y=1} = 0.896$ on Complex but the hardest $\hat{\sigma}$-decile had coverage 0.454. The $\hat{\sigma}$-bin stratification folds heteroscedastic information into the partition itself, restoring near-uniform coverage across $\hat{\sigma}$-bins (§6).

Stratifying by $\hat{\sigma}$-bin alone, without y, re-introduces the minority-class pathology because the $\hat{\sigma}$-distribution is dominated by negatives. The product partition ($y \times \hat{\sigma}$-bin) is the smallest that simultaneously corrects both modes, at the cost of requiring $n_{k,b} \geq \lceil 1/\alpha \rceil$ per cell; this is comfortably satisfied on TraitGym at $K = 5$ (App. B sample-size audit). Formally, among Mondrian partitions over the joint axes $\{y, b(x)\}$, the product partition $(y \times b)$ is the unique refinement that admits both T2 (which requires conditioning on y) and T3 (which requires conditioning on b); the two strict coarsenings (project to y-only or to b-only) each violate one of the two coverage targets, as the preceding paragraphs establish. This justifies the "smallest modification of split CP" phrasing used throughout.

4.3 Bin-edge design and adaptive K selection

We use equiprobable $\hat{\sigma}$-bins from calibration-fold quantiles, so that $n_{k,b}$ is roughly balanced across b for each fixed k. Theorem 3 (§5.3) formalizes the bias–variance tradeoff: larger K reduces the stationarity bias $L_F R/K$ but inflates the finite-sample variance $K/(\pi_{\min} n)$, with oracle $K^\star =$

$O(\sqrt{n})$. In practice we select $\hat{K}(c_{\text{outer}})$ per outer fold via *proper nested chrom-LOO cross-validation* with K_{eval}-fair scoring (§5.3, App. C.4). The modal $\hat{K}(c_{\text{outer}})$ across outer folds is $K = 5$ on Complex and $K = 5$–8 on Mendelian; HCCP's worst-cell $\hat{\sigma}$-bin gap reported on the cross-method-fair K_{eval} axis (Mendelian $K_{\text{eval}} = 3$, Complex $K_{\text{eval}} = 5$) is $33\times$ (Complex) and $2.3\times$ (Mendelian) tighter than the strongest single-axis Mondrian baseline (§6.3, Table 4); a K_{eval} sensitivity sweep (Tab. 13) shows the Complex advantage is robust across $K_{\text{eval}} \in [2, 10]$.

4.4 Score comparison

Table 1 places our score among common baselines.

Table 1: Nonconformity scores. Our $s(x, y) = |y - \hat{p}(x)|/\hat{\sigma}(x)$ is the unique combination of DEGU-style $\hat{\sigma}$ [Zhou et al., 2026] and a classification-compatible score; paired with Mondrian-($y \times \hat{\sigma}$-bin), it yields bin-conditional coverage (T3).

Score	Uses $\hat{\sigma}(x)$?	Task type
Split conformal [Vovk et al., 2005]	No	Any
CQR [Romano et al., 2019]	Via $q_\alpha, q_{1-\alpha}$	Regression only
DEGU + split CP [Zhou et al., 2026]	Reports $\hat{\sigma}$, not in score	Regression (MPRA)
HCCP (ours), Eq. (3)	**In score + partition**	**Binary classification**

The score is a binary analog of CQR: the CQR numerator $\max(\hat{q}_{\alpha/2} - y,\ y - \hat{q}_{1-\alpha/2})$ becomes $|y - \hat{p}(x)|$ (with $y \in \{0, 1\}$), and the implicit interval half-width $(\hat{q}_{1-\alpha/2} - \hat{q}_{\alpha/2})/2$ becomes our learned $\hat{\sigma}(x)$. The Mondrian partition then extends class-conditional Mondrian of Vovk et al. [2003] with a data-dependent second taxon level.

4.5 Implementation details

- **Chrom-LOO OOF** for $\hat{p}$ uses the 22+X chrom fold rotation natively (not k-fold); this is exact for the residual target in Eq. (2).
- $\epsilon = 10^{-6}$ in Eq. (3) prevents division issues when $\hat{\sigma} \to 0$; sensitivity analysis in App. C shows results invariant for $\epsilon \in [10^{-8}, 10^{-4}]$.
- **Bin-edge perturbation** when recomputed from the full dataset (not just $\mathcal{D}^{(-c^\star)}$) causes a coverage shift $\leq K/(n+1) \approx 10^{-3}$ in our regime (App. A, T3 Remark §2.1).
- **Small cells** ($n_{k,b} < 5$): we fall back to the pooled class-conditional threshold $\hat{q}_k$ of T2. This fallback never triggers on TraitGym at $K \leq 10$.

5 Theory

This section states HCCP's four main-text theorems: **Theorem 1** (T3, exact bin-conditional coverage), **Theorem 2** (T3′, the Barber-2023 robustness corollary at the cell level, which provides the uniform finite-sample certificate when our per-chromosome KS audit detects cell-level exchangeability violations on Mendelian), and the principal new contributions **Theorems 3–4** (T5.1 oracle bin count within the equi-bin Mondrian-K family + T5.2 a matching finite-sample lower bound on the same class). Auxiliary lemmas (T1/T2 corollaries at coarser partitions; T1′/T2′/T4 robust counterparts via Barber et al. [2023] Theorem 2; T3-loc feature-ball extension; T3.b $\hat{\sigma}$-perturbation robustness) are stated and proved in App. A.

Unless otherwise noted, all statements take the calibration fold $\mathcal{D}^{(-c^\star)}$ and the test point $(X, Y) \sim P_{c^\star}$ as in §3.1, and $\mathcal{C}_\alpha$ is the Mondrian prediction set of Eq. (5). We use the A1/A1′/A2 hierarchy of 1–3; two further assumptions used only by appendix lemmas (**A3-loc**, **B1**) are stated explicitly in App. A.

5.1 Theorem 1: Bin-conditional coverage

Theorem 1 (T3 bin-conditional coverage, exact)**.** *Under 2 and A2-cell (A2 at the (k, b)-cell level), for each cell with $n_{k,b} \geq \lceil 1/\alpha \rceil$ and continuous F_{kb},*

$$1 - \alpha \;\leq\; P\big(Y \in \mathcal{C}_\alpha(X) \mid Y = k,\, b(X) = b\big) \;\leq\; 1 - \alpha + \frac{1}{n_{k,b} + 1}.$$

Proof sketch. The standard split-CP rank-uniformity argument carried inside a single Mondrian cell: under A1′ + A2-cell, the calibration scores restricted to cell (k, b) are i.i.d. F_{kb}, the test score is independent and F_{kb}-distributed, and exchangeability of the augmented sequence yields the two-sided rate $1/(n_{k,b} + 1)$ via Lemma 2 (full proof in App. A.6).

Positioning against Barber et al. [2020].

> **We do not claim pointwise conditional coverage** $P(Y \in \mathcal{C}_\alpha(X) \mid X = x) \geq 1$
> Barber et al. [2020] rule out in finite samples absent structural assumptions.
> guarantees coverage conditional on the partition event $b(X) = b$ and label $Y = k$
> are the *coarsest practically useful* strengthening of standard class-conditional
> carries finite-sample bounds: any refinement (e.g., $\hat{\sigma}$-quantile or feature-ball c
> must either invoke an additional regularity assumption (as T3-loc does via A3-lo
> a slower $O(n^{-2/(d+2)})$ rate (as RLCP does). HCCP deliberately stops at the $(y$
> partition where T3 applies.

Auxiliary lemmas in App. A. Theorem 1 specialises to standard split-CP at coarser partitions: marginalising b recovers *class-conditional* coverage (Lem. 6), and further marginalising y recovers *marginal* coverage (Lem. 5). When A2 fails but 1 holds, T1, T2, and T3 degrade gracefully into robust forms T1′/T2′/T3′ via the underlying weighted-swap bound of Barber et al. [2023] Theorem 2 with uniform calibration weights (Lem. 10); the cell-level instance is Lem. 7. Two further extensions are appendix-only: *feature-ball coverage* T3-loc, which translates partition-level T3 to coverage on ℓ_2-balls under L-Lipschitz $\hat{\sigma}$ + A3-loc (Lem. 8), and *$\hat{\sigma}$-plug-in robustness* T3.b, which establishes graceful degradation when the variance head is misspecified by relative error η (Lem. 9).

T3 vs T3′ on TraitGym. T3′ degrades T3 by exactly the cell-level chrom-TV $\bar{\delta}_{\mathrm{TV}}^{(k,b)}$ that our per-chromosome KS audit (App. B.4) bounds empirically. On Complex the audit is close to the 5% null (10.4% rejection at $p < 0.05$, max KS 0.315), so T3 exact is adequate. On Mendelian the audit rejects 46% of cell-chrom pairs, driven by the highest-$\hat{\sigma}$ positive-class cell where pathogenic variants concentrate on a few chromosomes (chr9, chr7, chr3); $d_{\mathrm{TV}} \leq \mathrm{KS}/\sqrt{2}$ then gives $\bar{\delta}_{\mathrm{TV}}^{(k,b)} \leq 0.31$ on the worst cell, consistent with the observed per-chromosome coverage gap ≤ 0.073 (Table 14). **This rejection rate is approximately K-invariant**: at $K_{\mathrm{eval}} \in \{2, 3, 5, 8, 10\}$ the cell-by-chrom KS audit rejects 40–46% of pairs (App. B.4), confirming that the violation is dataset-intrinsic chrom-TV rather than a binning artefact and that T3′ is the binding operational guarantee on Mendelian regardless of partition granularity. T3 exact remains valid on Complex.

5.2 Theorem 2: Robust bin-conditional coverage under exchangeability violation (T3′)

T3 requires A2-cell (within-cell exchangeability between calibration and test scores). Our per-chromosome KS audit (App. B.4) verifies that A2-cell holds approximately on Complex (10.4% rejection, near the 5% null) but fails on 46% of (k, b)-cell-by-chromosome pairs on Mendelian. T3′ is the operational guarantee in this regime.

Theorem 2 (T3′ bin-conditional coverage, robust)**.** *Let $\bar{\delta}_{\mathrm{TV}}^{(k,b)}$ denote the average total-variation distance between the calibration-fold and test-fold conditional score distributions in cell (k, b). Under 2 (without A2-cell), for each cell with $n_{k,b} \geq \lceil 1/\alpha \rceil$,*

$$P\big(Y \in \mathcal{C}_\alpha(X) \mid Y = k,\, b(X) = b\big) \;\geq\; (1 - \alpha) - \bar{\delta}_{\mathrm{TV}}^{(k,b)}.$$

Proof sketch. A direct application of Barber et al. [2023] Theorem 2 (uniform calibration weights) at the cell level: the swap-TV bound on coverage degradation specialises to $\bar{\delta}_{\mathrm{TV}}^{(k,b)}$ on the (k, b) cell. Full proof in App. A.7.

T3′ is the operative *certificate* on Mendelian rather than a tight prediction: the empirical $\bar{\delta}_{\mathrm{TV}}^{(k,b)} \leq 0.31$ on the worst cell yields a coverage lower bound of 0.59, which is loose by construction (the bound is uniform over all distributions satisfying 2 alone), while the observed per-chromosome coverage gap remains ≤ 0.073 throughout (Table 14). The operational interpretation: T3′ supplies the only uniform finite-sample lower bound on coverage in the regime where T3's exactness assumption (A2-cell) is empirically rejected, and that lower bound — though loose — is non-vacuous and certifies that no distribution-shift pathology can push coverage below 0.59 on Mendelian. We do not claim T3′ predicts the empirical gap; it bounds the worst case.

5.3 Theorems 3–4: Optimal bin count and matching lower bound within the equi-bin Mondrian-K class

This is the principal theoretical contribution. Theorem 1 holds for any fixed K but says nothing about *which* K to choose. We now derive the optimal K by formalising the bias–variance tradeoff that governs bin-conditional coverage and prove a matching finite-sample lower bound *within the equi-bin Mondrian-K family* to establish that the $O(n^{-1/2})$ rate is tight on this class, dimension-free, and depends explicitly on the minority-class prevalence $\pi_{\min}$ through the $\pi_{\min}^{-1/2}$ constant. The lower bound is not a distribution-free minimax bound over arbitrary CP procedures (other axes of conditioning, e.g. self-calibrating CP [van der Laan, 2024], achieve different rates on different metrics; we discuss this below); it certifies that $O(n^{-1/2})$ is unimprovable for the specific equi-bin Mondrian-K partition that HCCP uses.

Two sources of coverage gap. Under 4, the worst-cell coverage gap decomposes as

$$G(K) \;:=\; \max_{k,b}\big|\mathrm{cov}_{k,b} - (1-\alpha)\big| \;\leq\; \underbrace{\frac{L_F \cdot R}{K}}_{\text{stationarity bias}} \;+\; \underbrace{\frac{K}{\pi_{\min} \cdot n}}_{\text{finite-sample variance}}, \tag{6}$$

where $R = \hat{\sigma}_{\max} - \hat{\sigma}_{\min}$ is the $\hat{\sigma}$ range and $\pi_{\min} = \min(\pi, 1-\pi)$ the minority-class prevalence. The bias term captures within-bin heterogeneity (wider bins violate A2-cell more); the variance term is $1/(n_{k,b}+1) \approx K/(\pi_{\min} n)$ for the smallest Mondrian cell.

Theorem 3 (T5.1 Oracle bin count)**.** *Under 2 and 4 with equiprobable $\hat{\sigma}$-bins,*

$$K^\star \;=\; \lfloor \sqrt{L_F \cdot R \cdot \pi_{\min} \cdot n} \rfloor, \qquad G(K^\star) \;\leq\; \frac{2\sqrt{L_F \cdot R}}{\sqrt{\pi_{\min} \cdot n}}.$$

Theorem 4 (T5.2 Matching lower bound within the equi-bin Mondrian-K class)**.** *Restrict attention to conformal predictors using equiprobable $\hat{\sigma}$-bin Mondrian partitions on the calibration fold (the class HCCP belongs to). There exists a distribution satisfying 2 and 4 such that, for any choice of K within this class, $\min_K G(K) = \Omega\big(\sqrt{L_F R/(\pi_{\min} n)}\big)$. Hence the $O(n^{-1/2})$ rate of T5.1 is tight on this class, and the $\pi_{\min}^{-1/2}$ constant is not improvable without strengthening assumptions or moving outside the class.*

Proof sketch. For T5.1, set $g'(K) = -L_F R/K^2 + 1/(\pi_{\min} n) = 0$ to obtain $K^\star = \sqrt{L_F R \pi_{\min} n}$; substitution gives $g(K^\star) = 2\sqrt{L_F R/(\pi_{\min} n)}$, with the floor introducing $O(1/(\pi_{\min} n))$ slack dominated by the leading term. For T5.2, construct a linear-shift family $F_{k,\sigma}(s) = \Phi(s - L_F \sigma)$; both the bias and variance lower bounds are tight on this family. Full proofs in App. A.11.

Dimension-free rate — what it does and does not say. The $O(n^{-1/2})$ rate of Theorem 3 is *dimension-free* in the sense that the constant does not depend on the feature dimension d; it does depend on $L_F \cdot R$, the Lipschitz constant of the conditional score CDF with respect to the 1-D summary $\hat{\sigma}(x)$, and on the minority-class prevalence $\pi_{\min}$. This is a different guarantee from RLCP's [Hore and Barber, 2025] feature-space local coverage rate $O(n^{-2/(d+2)})$: RLCP targets $P(Y \in \mathcal{C}_\alpha(X) \mid X \approx x)$, our T3/T5 target $P(Y \in \mathcal{C}_\alpha(X) \mid \hat{\sigma}(X) \in B_b)$. We do not claim the two rates are comparable on their native targets; we claim that the $\hat{\sigma}$-bin conditioning is the coarsest practically useful conditioning under which a dimension-free rate exists, and T5 quantifies the exact constant $L_F \cdot R$ it costs. At $d = 7{,}731$ (our feature dimension), RLCP's rate is intractable on any realistic calibration set size, so the two methods occupy different operating points rather than competing on the same metric; T3-loc (Lem. 8) provides the feature-ball bridge at the cost of the additional A3-loc assumption.



Figure 3: Empirical validation of Theorem 3 (T5.1) on TraitGym. Each panel sweeps $K \in \{2, 3, 5, 8, 10, 15, 20, 30\}$ and overlays the bias term $L_F R/K$ (green shaded) and variance term $K/(\pi_{\min} n)$ (red shaded) of Eq. 6, plus the T5 bound $G(K) \leq L_F R/K + K/(\pi_{\min} n)$ (grey curve). Blue dots: empirical mean-cell gap. Red squares: empirical worst-cell gap. The CV-selected $\hat{K}_{\mathrm{CV}}$ (dashed vertical line) coincides with the empirical minimum on both datasets ($\hat{K}_{\mathrm{CV}} = 3$ on Mendelian, $\hat{K}_{\mathrm{CV}} = 2$ on Complex), and the empirical curves track the T5 bound across the bias-dominated and variance-dominated regimes.

Comparison to prior CP minimax / impossibility results. T5.2 sits inside an existing landscape of CP lower bounds, none of which directly subsume it. Barber et al. [2020] prove that distribution-free pointwise conditional coverage $P(Y \in \mathcal{C}_\alpha(X) \mid X = x) \geq 1 - \alpha$ is unattainable in finite samples and characterise which conditional-coverage targets are attainable; this is an *impossibility* result, not a rate, and motivates partition-based conditioning of the type T3 / T5 instantiate. Classical CP minimax analyses [Vovk et al., 2005] establish $n^{-1/2}$ as the unimprovable rate for marginal coverage. Barber et al. [2023] provides robust counterparts under exchangeability violations via a swap-TV bound but does not separate the imbalance constant. T5.2's contribution is orthogonal to these: it places an explicit $\pi_{\min}^{-1/2}$ in the constant of the worst-cell bin-conditional gap within the equi-bin Mondrian-K family, certifying that the imbalance dependence cannot be hidden in implicit constants. This is the load-bearing claim for imbalanced VEP at $\pi_{\min} \approx 0.10$.

Comparison to SC-CP's $O(n^{-2/3})$ rate. van der Laan [2024] achieve a faster $O(n^{-2/3})$ rate (their Thm. 4.2) on the $\hat{\mu}$-axis via the monotone structure of isotonic regression, inheriting the segment-count concentration of Deng et al. [2021] *without* requiring 4. Our $O(n^{-1/2})$ rate trades a slower asymptotic rate for three properties SC-CP does not provide: (i) conditioning on $\hat{\sigma}$ rather than $\hat{\mu}$, which adapts to mean-independent heteroscedasticity (SC-CP §5 explicitly notes its $\hat{\mu}$-axis binning cannot adapt unless heteroscedasticity is mean-driven); (ii) explicit dependence on minority-class prevalence $\pi_{\min}$, which makes T5 directly applicable to severely imbalanced classification (TraitGym $\pi_{\min} \approx 0.10$) where SC-CP's regression formulation does not encode the class-conditional sample-size constraint; (iii) a matching minimax lower bound (Thm. 4) under 4, certifying that the $O(n^{-1/2})$ rate is unimprovable in the $(y \times \hat{\sigma}\text{-bin})$ regime without strengthening assumptions. The two results are therefore complementary rather than competing: SC-CP is the recommended choice when heteroscedasticity is mean-driven; T5 is the recommended choice when $\hat{\sigma}$ is supplied as an independent learned summary, as in DEGU-style [Zhou et al., 2026] VEP pipelines.

Practical $\hat{K}$ selection: nested chrom-LOO with K_{eval}-fair scoring. We select $\hat{K}$ per outer fold via *proper nested chrom-LOO cross-validation*, ensuring $\hat{K}(c_{\mathrm{outer}})$ is a deterministic function of the outer calibration set alone (CP exchangeability-preserving). For each outer fold c_{outer}, we run inner chrom-LOO on the remaining chromosomes and pick $\hat{K}(c_{\mathrm{outer}}) = \mathrm{argmin}_K \, \overline{G}_{\mathrm{inner}}(K)$ where the inner-fold worst-cell gap is measured on a fixed-K_{eval} sigma-bin partition (NOT on each candidate K itself, which would artificially favour smaller K via fewer cells). K_{eval} is set per dataset to keep ≥ 100 minority-class samples per cell, which we found empirically separates the regime where heteroscedastic stratification is informative from the regime where per-cell binomial noise dominates: $K_{\mathrm{eval}} = 3$ on Mendelian ($n = 3{,}380$, $n_{1,b} \approx 113$ per cell) and $K_{\mathrm{eval}} = 5$ on Complex ($n = 11{,}400$, $n_{1,b} \approx 228$). A sensitivity sweep across $K_{\mathrm{eval}} \in \{2, 3, 5, 8, 10\}$ (App. C.1, Table 13) shows HCCP

dominates contemporary single-axis CP baselines (RLCP, weighted CP, SC-CP) by 25–34× on Complex across the full sweep, and by $1.15\times$ on Mendelian at the recommended $K_{\text{eval}} = 3$; at higher K_{eval} on Mendelian, the per-cell positive count drops below ~ 70 and the heteroscedastic head can no longer be reliably calibrated, at which regime simpler weighted-CP-style methods become competitive. On TraitGym, the modal $\hat{K}(c_{\text{outer}})$ across outer folds is $K = 5$ on Complex and $K = 5$–8 on Mendelian (App. C.4); these are above the legacy $\hat{K}_{\text{CV}} \in \{2, 3\}$ that an earlier draft reported under a non-nested protocol where K-selection used the same chrom-LOO worst-cell gap that the manuscript subsequently reported, an invalid double-use of the test fold that we have rectified.

Asymptotic vs. finite-sample regimes. A reader may notice the gap between asymptotic $K^\star$ and the modal nested-CV-selected $\hat{K}$. Plugging the LCLS estimate of L_F [Huang et al., 2024] into Theorem 3 gives $K^\star = 22$ (Mendelian, $\hat{L}_F = 2.97 \in [2.89, 3.45]$) and $K^\star = 50$ (Complex, $\hat{L}_F = 4.51 \in [4.47, 4.69]$); see App. C.4, Table 18 for the bootstrap CI. These are above the modal nested-CV $\hat{K} \in \{5, 8\}$ reported above, but the legacy max-of-ratios estimator overstates $K^\star$ by an order of magnitude (88 Mendelian, 110 Complex), so the apparent contradiction is largely an artefact of the estimator. The remaining gap is genuine: T5.1 characterises the *asymptotic* optimum where Eq. 6 is binding, while in the finite-sample regime ($n \leq 11{,}400$) the per-cell sample-size floor $n_{k,b} \geq \lceil 1/\alpha \rceil$ becomes binding before the variance term reaches the bias term. The empirical K-sweep extended to $K = 200$ (App. C.4) exposes a third *fallback-dominated* regime not modelled by Eq. 6, in which the predictor reverts to T2 pooled class-conditional thresholds and the worst-cell gap saturates. We therefore recommend nested chrom-LOO $\hat{K}(c_{\text{outer}})$ as the practical selector at the sample sizes typical of human-variant benchmarks; the gap to the LCLS-derived $K^\star$ closes as $n \to \infty$.

5.4 Summary of guarantees

Table 2 consolidates the three hero theorems and points to the appendix lemmas that handle robust counterparts and extensions.

Table 2: HCCP coverage guarantees at a glance. $n_{k,b}$: cell calibration count. Four numbered hero theorems in main text. Auxiliary lemmas (T1/T2 corollaries; T1′/T2′/T4 robust counterparts via Barber et al. [2023] Theorem 2; T3-loc/T3.b extensions) live in App. A.

Result	Assumptions	Bound type	Guarantee
Theorem 1 (T3)	A1′ + A2-cell	exact two-sided	$\text{cov}_{k,b} \in [1-\alpha,\ 1-\alpha+1/(n_{k,b}+1)$
Theorem 2 (T3′)	A1′ only	robust lower bound	$\text{cov}_{k,b} \geq (1-\alpha) - \bar{\delta}_{\text{TV}}^{(k,b)}$
Theorem 3 (T5.1)	A1′ + 4	oracle rate (within equi-bin Mondrian-K)	$G(K^\star) \leq 2\sqrt{L_F R/(\pi_{\min} n)},\ K^\star = O$
Theorem 4 (T5.2)	(within equi-bin Mondrian-K)	matching lower bound	$\min_K G(K) = \Omega(\sqrt{L_F R/(\pi_{\min} n)})$
App. A (auxiliaries)	A1 / A1′	robust / extensions	T1, T2, T1′, T2′, T3-loc, T3.b, T4

Validation map. §6 validates each hero theorem: **T3** on trait-LOO (the bin-local gap reaches the finite-sample floor 0.002–0.004, matching the $1/(n_{k,b}+1)$ rate) and on chrom-LOO with the SOTA feature set (gap ≤ 0.077); **T5** via the K-sweep, nested-CV $\hat{K}(c_{\text{outer}})$ selection, and the head-to-head against contemporary single-axis CP baselines on the cross-method-fair K_{eval} axis (33× Complex, 2.3× Mendelian tighter worst-cell gap, §6.3). T3′ absorbs cell-level chrom-TV deviations on Mendelian via the Barber 2023 swap-TV bound; T4 marginal-coverage proxy diagnoses the cross-dataset M→C boundary case in §6.7.

6 Experiments

6.1 Setup

Datasets. TraitGym Mendelian matched_9 ($n = 3380$, 113 OMIM) and Complex matched_9 ($n = 11{,}400$, 29 traits). Chrom-LOO protocol (test chroms $\{17, 18, 19, 20, 21, 22, X\}$).

Table 3: Main results on TraitGym chrom-LOO. AUPRC is weighted by test-chrom size (TraitGym convention). $\hat{\sigma}$-bin gap is the max-over-bins absolute coverage deviation from target 0.90. HCCP uses the CADD+GPN-MSA+Borzoi feature set (SOTA); DEGU-lite results from our reimpl (App. B). HCCP row subscripts are $\pm$ one std from $B = 200$ chromosome-level bootstrap resamples; the reported $\hat{\sigma}$-bin gap is the bootstrap-mean of the per-resample max-over-bins deviation. Non-HCCP rows and the corresponding all-chrom point estimates in Table 7 are computed without resampling and are generally larger when a few chromosomes drive the maximum (e.g., Mendelian CADD+GPN-MSA+Borzoi: bootstrap-mean 0.020 ± 0.012 here vs all-chrom point 0.077 in Table 7). HCCP rows use $K = 5$ for direct comparability with prior split-CP and class-conditional baselines that share this default; the cross-validated $\hat{K}_{\mathrm{CV}}$ selected via proper nested chrom-LOO (App. C.4) is reported separately in Tables 4 and 5 with K_{eval}-fair scoring (§5.3).

Dataset	Aggregator	Calibration	AUPRC ↑	Marg. cov.	Cov $\lvert Y{=}1$	**$\hat{\sigma}$-bin gap** ↓	Singleton frac
Mendelian	LogReg [Benegas et al., 2025]	Split CP	0.752	0.900	0.89	0.54	91%
	GBM (ours)	Split CP	**0.900**	0.900	0.73	0.46	96%
	GBM	Class-cond. (Day 10)	**0.900**	0.900	0.90	0.46	92%
	GBM	DEGU-lite + split	0.901	0.900	0.88	0.43	85%
	GBM	**HCCP (ours)**	**0.900**	$0.899_{\pm 0.006}$	$0.894_{\pm 0.015}$	$\mathbf{0.020}_{\pm 0.012}$	$0.776_{\pm 0.040}$
Complex	LogReg	Split CP	0.332	0.900	0.88	0.43	23%
	GBM	Split CP	0.353	0.900	0.54	0.53	55%
	GBM	Class-cond. (Day 10)	0.353	0.900	0.90	0.51	31%
	GBM	DEGU-lite + split	0.353	0.900	0.86	0.43	20%
	GBM	**HCCP (ours)**	0.353	$0.901_{\pm 0.001}$	$0.904_{\pm 0.004}$	$\mathbf{0.004}_{\pm 0.002}$	$0.228_{\pm 0.019}$

Features. CADD [Kircher et al., 2014], Borzoi_L2_L2 [Linder et al., 2025], GPN-MSA_absLLR [Benegas et al., 2023]. Four feature sets: CADD, Borzoi, CADD+Borzoi, CADD+GPN-MSA+Borzoi.

Metrics. AUPRC weighted by test-chrom size (TraitGym leaderboard primary); marginal coverage; class-conditional coverage; *$\hat{\sigma}$-bin coverage gap*, the max-over-bins absolute deviation of per-bin coverage from target $1 - \alpha$. All results are at $\alpha = 0.10$, seed 42, $K = 5$ unless noted.

Uncertainty quantification of the metrics themselves. `HistGradientBoostingClassifier` at `max_depth=2` with `early_stopping=False` is *deterministic* given fixed data. Under our configuration (default `subsample=1.0`, `max_features=None`, `max_bins=255`), `random_state` has no active injection point, and the headline AUPRC and coverage are identical across seeds $\{42, 7, 2024\}$. We ruled out the alternative hypothesis of data leakage via three orthogonal sanity checks (App. B.5): (i) training with 50% random label corruption collapses AUPRC from 0.90 / 0.35 to 0.147 / 0.126, near the positive-class base rate; (ii) forcibly introducing row-level stochasticity via 80% subsampling produces strictly positive seed variance (std 0.0006 on Mendelian, 0.0027 on Complex); (iii) the chrom-LOO split has zero train-test row overlap. We therefore report 95% confidence intervals from chromosome-level bootstrap ($B = 200$ resamples with replacement of calibration chromosomes) in addition to the point estimates. The bootstrap captures *calibration-set variability*, which is the deployment-relevant source of uncertainty.

6.2 Main results

Table 3 summarizes HCCP against the TraitGym LogReg aggregator with split conformal, our GBM aggregator with class-conditional (Day 10) conformal, our full HCCP, and our DEGU reimplementation (DEGU-lite, deep ensemble distillation to a Gaussian-uncertainty student). HCCP achieves the *lowest* $\hat{\sigma}$-bin coverage gap across both datasets while matching or exceeding SOTA AUPRC.

Key reading. (i) The GBM aggregator alone reaches SOTA Mendelian AUPRC 0.900, a $+14.8$ pp improvement over the published LogReg [Benegas et al., 2025]. (ii) Class-conditional calibration (Day 10) fixes the minority-class pathology of split CP (Cov $\lvert Y{=}1$ $0.54 \to 0.90$ on Complex) but leaves the *local* gap untouched. (iii) The Mondrian-$(y \times \hat{\sigma}\text{-bin})$ partition of HCCP reduces the $\hat{\sigma}$-bin gap by a further 5–25$\times$ over these legacy split-CP and class-conditional baselines, to within one standard error of the finite-sample $1/(n_{k,b} + 1)$ floor; against contemporary normalized-Mondrian

Table 4: Head-to-head against off-the-shelf normalized + Mondrian CP, sharing the same $(\hat{p}, \hat{\sigma})$. Partition K for B2 / B4 selected per outer fold via proper nested chrom-LOO with K_{eval}-fair scoring; reporting metric is the $(y, \hat{\sigma}\text{-bin})$-conditional worst-cell coverage gap on a fixed K_{eval} partition (Mendelian $K_{\text{eval}} = 3$, Complex $K_{\text{eval}} = 5$, set per dataset to ensure ≥ 30 minority-class samples per cell, §5.3). Single-seed point estimates. **No single-axis CP simultaneously satisfies** $\text{cov}_{|Y=1} \geq 0.85$ **and** $\hat{\sigma}$**-bin gap** ≤ 0.20 **on either dataset.** HCCP is the unique frontier point on both.

Dataset	Method	Marg. cov.	Cov$\|Y{=}1$	$\hat{\sigma}$**-bin gap** $\downarrow$	Per-chrom gap
Mendelian ($\pi_+ = 0.10$)	B1 vanilla split CP	0.899	0.956	0.374	0.170
	B2 $\hat{\sigma}$-Mondrian [Boström and Johansson, 2020]	0.903	0.840	0.374	0.129
	B3 class-Mondrian [Sadinle et al., 2019]	0.898	0.894	0.374	0.161
	B4 HCCP (ours)	0.902	**0.876**	**0.163**	0.158
Complex ($\pi_+ = 0.10$)	B1 vanilla split CP	0.900	0.616	0.802	0.049
	B2 $\hat{\sigma}$-Mondrian [Boström and Johansson, 2020]	0.899	0.656	0.802	0.047
	B3 class-Mondrian [Sadinle et al., 2019]	0.900	0.902	0.802	0.053
	B4 HCCP (ours)	0.900	**0.905**	**0.024**	0.047

and self-calibrating CP variants under matched K_{eval} scoring (Tab. 4, 5) the ratio is $33\times$ on Complex and $2.3\times$ on Mendelian. (iv) DEGU-lite [Zhou et al., 2026] learns $\hat{\sigma}$ but applies split CP in the Tab. 3 headline, and the $\hat{\sigma}$-bin gap therefore remains near the class-conditional level. App. C.5 reports a separate matched comparison where DEGU-lite's $\hat{\sigma}$ is paired with HCCP's Mondrian-$(y \times \hat{\sigma}\text{-bin})$ partition (Tab. 19), isolating the $\hat{\sigma}$-mechanism from the partition — the conformal partition, not the $\hat{\sigma}$ head in isolation, is the load-bearing component.

6.3 Joint frontier: head-to-head with off-the-shelf normalized + Mondrian CP

The three preceding rows of Tab. 3 (split-CP, class-conditional, DEGU-lite + split) characterise HCCP's improvement over historical TraitGym pipelines. To address whether HCCP also improves on *contemporary* normalized-Mondrian CP, we run all four reasonable single-axis variants on top of the same $(\hat{p}, \hat{\sigma})$ pair, using the `crepes` [Boström, 2022] reference implementation:

B1 vanilla normalized split CP (no Mondrian);

B2 $\hat{\sigma}$-Mondrian [Boström and Johansson, 2020]: bins along $\hat{\sigma}$ only;

B3 class-Mondrian [Sadinle et al., 2019]: bins along y only;

B4 HCCP (ours): joint $(y \times \hat{\sigma}\text{-bin})$ Mondrian.

The four predictors share their $\hat{p}$ and $\hat{\sigma}$; they differ only in the partitioning of the calibration fold. Tab. 4 reports the resulting coverages on TraitGym CADD+GPN-MSA+Borzoi at $K = \hat{K}_{\text{CV}}$.

Reading. Under the cross-method-fair $(y, \hat{\sigma}\text{-bin})$-conditional reporting metric at fixed K_{eval}, B1 (split CP) over-covers the minority class on Mendelian ($\text{cov}_{|Y=1} = 0.96$) and under-covers on Complex ($\text{cov}_{|Y=1} = 0.62$); B2 ($\hat{\sigma}$-Mondrian) under-covers the minority class on both ($0.84/0.66$); B3 (class-Mondrian) recovers minority coverage but leaves the bin-local gap untouched ($0.37/0.80$). HCCP is the unique point simultaneously satisfying $\text{cov}_{|Y=1} \geq 0.85$ *and* $\hat{\sigma}$-bin gap ≤ 0.20 on both datasets, tightening the bin-local gap by $33\times$ over B3 on Complex and $2.3\times$ on Mendelian. The improvement is on the joint (class, $\hat{\sigma}$-bin) frontier — the operationally relevant target for clinical VEP.

Comparison against contemporary local CP methods. We additionally benchmark HCCP against three contemporary CP methods that target conditional coverage along axes complementary to ours: **RLCP** [Hore and Barber, 2025] (kernel-weighted localization, feature-space local), **weighted CP** [Tibshirani et al., 2019] (covariate-shift adaptation via likelihood-ratio weights estimated by a logistic discriminator between source and target chromosomes), and **Self-Calibrating CP** [van der Laan, 2024] (binning along the calibrated point prediction $\hat{\mu} = \hat{p}$, equivalent to a Venn–Abers refinement at first-order). Each is paired with the same $(\hat{p}, \hat{\sigma})$ as Tab. 4 for a like-for-like comparison; RLCP is run

Table 5: HCCP vs. contemporary local-CP methods on TraitGym CADD+GPN-MSA+Borzoi, sharing the same $(\hat{p}, \hat{\sigma})$. Partition K for HCCP / SC-CP selected per outer fold via proper nested chrom-LOO; reporting metric $(y, \hat{\sigma}\text{-bin})$-conditional worst-cell gap at fixed K_{eval} (Complex $K_{\text{eval}} = 5$, Mendelian $K_{\text{eval}} = 3$). **HCCP is the unique method satisfying both** $\text{cov}_{|Y=1} \geq 0.85$ **and** $\hat{\sigma}$**-bin gap** ≤ 0.20 **on both datasets.** RLCP / SC-CP collapse minority coverage on Complex; weighted CP over-covers the minority on Mendelian (singleton fraction 0.50 vs. HCCP 0.83). Numbers from `T_tools/cp_baselines_h2h.py` with `-K-mode nested-cv`.

Dataset	Method	Marg. cov.	Cov|Y=1	$\hat{\sigma}$-bin gap ↓	Singleton	Conditioning
Complex ($K_{\text{eval}} = 5$)	**HCCP (ours)**	0.900	**0.905**	**0.024**	0.224	$(y, \hat{\sigma}\text{-bin})$
	RLCP [Hore and Barber, 2025]	0.952	0.545	0.802	0.762	$(p, \hat{\sigma})$ kernel
	weighted CP [Tibshirani et al., 2019]	0.901	0.613	0.802	0.785	chrom-shift weights
	SC-CP [van der Laan, 2024]	0.900	0.627	0.802	0.710	$\hat{p}$-bin
Mendelian ($K_{\text{eval}} = 3$)	**HCCP (ours)**	0.902	**0.876**	**0.163**	0.827	$(y, \hat{\sigma}\text{-bin})$
	RLCP [Hore and Barber, 2025]	0.939	0.876	0.321	0.890	$(p, \hat{\sigma})$ kernel
	weighted CP [Tibshirani et al., 2019]	0.902	0.982	0.188	0.499	chrom-shift weights
	SC-CP [van der Laan, 2024]	0.900	0.846	0.374	0.777	$\hat{p}$-bin

Table 6: Imbalance sweep: $\text{cov}_{|Y=1}$ as a function of positive-class prevalence π_+, Complex CADD+GPN-MSA+Borzoi. Partition K for B2 / B4 selected per outer fold via nested chrom-LOO at $K_{\text{eval}} = 5$. B1 and B2 collapse as $\pi_+ \to 0$; B3 and B4 are insensitive. The right-most column reports HCCP's $\hat{\sigma}$-bin gap, which stays ≤ 0.07 across the sweep.

π_+	0.05	0.10	0.20	0.30	0.50	B4 $\hat{\sigma}$-gap
n	10800	11400	5700	3800	2280	—
B1 (split)	0.587	0.616	0.664	0.725	0.810	—
B2 ($\hat{\sigma}$-Mond)	0.650	0.656	0.718	0.800	0.878	—
B3 (class-Mond)	0.904	0.902	0.902	0.902	0.902	—
B4 (HCCP)	**0.898**	**0.905**	**0.894**	**0.902**	**0.896**	0.036 / 0.024 / 0.067 / 0.057 / 0.041

in the $(\hat{p}, \hat{\sigma})$ 2-D space (favouring it; the original feature space $d \approx 7{,}731$ would put RLCP's rate $O(n^{-2/(d+2)})$ in the intractable regime).

Imbalance sweep validates T5's $\pi_{\min}$ dependence. Tab. 6 subsamples Complex to $\pi_+ \in \{0.05, 0.10, 0.20, 0.30, 0.50\}$ (positives kept whole; negatives subsampled or vice versa) and re-runs the four variants under proper nested chrom-LOO K-selection. B1 (split CP) and B2 ($\hat{\sigma}$-Mondrian) minority-coverage *degrades monotonically* as $\pi_+ \to 0$ ($0.587 \to 0.810$ for B1; $0.650 \to 0.878$ for B2), while B3 and B4 hold at the target across the full sweep — the empirical realisation of the $\pi_{\min}^{-1/2}$ factor in T5's bound $G(K^\star) \leq 2\sqrt{L_F R/(\pi_{\min} n)}$. Fig. 4 visualises the same data as a joint frontier scatter. Mendelian replicates the same qualitative pattern at $\pi_+ \in \{0.10, 0.20, 0.30\}$ (the sample-size-stable regime: $n_+ \geq 86$ per cell): B2's $\text{cov}_{|Y=1}$ ranges 0.840–0.873 while HCCP holds at 0.876–0.893; B1 over-covers the minority on Mendelian ($\text{cov}_{|Y=1} \approx 0.95$) but at the cost of $\hat{\sigma}$-bin gap ≥ 0.37 throughout. At the extreme imbalance points ($\pi_+ = 0.05$, $n_+ \approx 17$ per cell) and the dropped-negatives extreme ($\pi_+ = 0.50$, $n = 676$), all four methods are dominated by the per-cell sample-size floor $n_{k,b} \geq \lceil 1/\alpha \rceil$ and the metric saturates; we read these endpoints as binomial-noise-limited rather than as method comparisons.

6.4 Three-axis OOD coverage

We stress-test HCCP along three orthogonal distributional axes: cross-chromosome (chrom-LOO), cross-trait (trait-LOO), and cross-dataset (Mendelian ↔ Complex). Figure 6 summarizes, Table 7 gives the numbers.

Three observations.

1. **HCCP holds across the three axes with degraded margin in chrom-LOO Mendelian.** Trait-LOO reaches the 0.002–0.004 floor on both datasets; chrom-LOO Complex stays



Figure 4: **Complex.** (a) Joint frontier: $\mathrm{cov}_{|Y=1}$ versus $\hat{\sigma}$-bin gap, points colored by method, sized by π_+ (Tab. 6). Lower-right is best. HCCP cluster occupies the high-coverage, low-gap corner alone. (b) $\mathrm{cov}_{|Y=1}$ versus π_+. Single-axis predictors B1 and B2 collapse as $\pi_+ \to 0$; HCCP and class-Mondrian (B3) hold at target. T5's $\pi_{\min}^{-1/2}$ dependence is visible in the divergence of the coloured curves.



Figure 5: **Mendelian** companion to Fig. 4. (a) Joint frontier: HCCP (B4, red) is again the unique point at $\mathrm{cov}_{|Y=1} \approx 0.90$ *and* low $\hat{\sigma}$-bin gap; B3 (class-Mondrian) holds class coverage but with higher gap; B2 ($\hat{\sigma}$-Mondrian) under-covers the minority class; B1 (vanilla split) over-covers the minority but at large gap. (b) Imbalance scaling: same qualitative pattern as Complex — HCCP and B3 hold $\mathrm{cov}_{|Y=1} \approx 0.90$ across $\pi_+ \in [0.05, 0.50]$, B2 collapses to ~ 0.79 at $\pi_+ = 0.05$. The two datasets together establish the joint $(y \times \hat{\sigma}\text{-bin})$ Mondrian as the unique single-fold partition simultaneously satisfying class and bin-local coverage under imbalance.

≤ 0.023 across feature sets; chrom-LOO Mendelian is 0.198 on CADD+Borzoi and tightens to 0.077 with the SOTA feature set CADD+GPN-MSA+Borzoi (still > 0.04, the binding regime). C→M cross-dataset direction is in-bound (gap ≤ 0.036). The reverse M→C direction is reported separately in §6.7 as a diagnostic case study of joint base-predictor + assumption failure, not as a deployment scenario.

2. **Trait-LOO reaches the finite-sample floor on aggregate.** Gaps of 0.002–0.004 match the $1/(n_{k,b} + 1)$ bound of T3; per-OMIM coverage std is ≤ 0.052, within binomial noise at $n = 30$ OMIMs. The OMIM-cluster aggregation (Table 16) exposes one exception: the Skeletal/connective cluster on Mendelian shows $\mathrm{cov}_{|Y=1} = 0.745$ at cluster size $n_{\mathrm{tot}} = 470$, the worst-cell exception we report honestly. This cluster carries low-AUPRC pathogenic variants whose $\hat{\sigma}$ scale is mis-estimated; we treat it as the boundary case for trait-LOO and discuss in §7 (assumption discussion).



Figure 6: HCCP $\hat{\sigma}$-bin gap across three OOD axes (log scale). Trait-LOO reaches the finite-sample $1/(n_{k,b}+1)$ floor on both datasets (≤ 0.004); chrom-LOO Complex stays ≤ 0.023; chrom-LOO Mendelian is 0.077 on the SOTA feature set; cross-dataset is shown for the C→M direction only (in-bound at 0.036). The reverse M→C direction is reported separately in §6.7 as a diagnostic case study, not summarised here.

Table 7: Three-axis OOD evaluation of HCCP. Trait-LOO rotates the held-out trait/OMIM (30 Mendelian OMIMs, 28 Complex traits with ≥ 10 positives). Cross-dataset trains on one dataset and tests on the other. All numbers at $\alpha = 0.10$, $K = 5$ (chosen for direct comparability with the baselines in Table 3); per-outer-fold nested-CV $\hat{K}(c_{\text{outer}})$ with K_{eval}-fair scoring is reported in Tables 4 and 5 (App. C.4). Trait-LOO already reaches the finite-sample $1/(n_{k,b}+1)$ floor at $K = 5$.

Axis	Dataset	Feature set	AUPRC ↑	Marg. cov.	$\hat{\sigma}$**-bin gap** ↓	Per-partition cov. std
Chrom-LOO	Mendelian	CADD+Borzoi	0.889	0.901	0.198	0.03 (22 chroms)
	Mendelian	CADD+GPN-MSA+Borzoi	0.900	0.900	**0.077**	0.03
	Complex	CADD+Borzoi	0.350	0.902	**0.020**	0.05
	Complex	CADD+GPN-MSA+Borzoi	0.353	0.900	0.023	0.04
Trait-LOO	Mendelian	CADD+Borzoi	0.902	0.902	**0.004**	0.049 (30 OMIMs)
	Mendelian	CADD+GPN-MSA+Borzoi	0.902	0.902	**0.004**	0.052
	Complex (top-28)	CADD+Borzoi	0.273	0.902	**0.002**	0.020
	Complex (top-28)	CADD+GPN-MSA+Borzoi	0.278	0.902	**0.003**	0.017
Cross-dataset (C → M)	C → M	CADD+Borzoi	**0.665**	**0.901**	**0.035**	—
	C → M	CADD+GPN-MSA+Borzoi	0.651	0.896	0.036	—

3. **Cross-dataset C→M transfer is in-bound.** Complex → Mendelian retains AUPRC $= 0.665$ and $\hat{\sigma}$-bin gap 0.035, indicating that calibration on the broader polygenic feature space transfers to monogenic targets without coverage collapse.

6.5 Cross-domain validation: ProteinGym

To test whether HCCP's coverage machinery generalises beyond human variant pathogenicity, we evaluate on **ProteinGym** [Notin et al., 2023], a protein variant fitness benchmark with 217 deep mutational scanning assays. We use the `DMS_score_bin` discretisation ($\approx 57\%$ high-fitness positives) as the binary target and engineer a 67-dimensional protein-agnostic feature set (one-hot WT/mutant amino acids, BLOSUM62 score, physicochemical deltas, local composition; App. E.1). For each held-out assay we train $\hat{p}$ on all mutants from the remaining ≥ 166 assays, fit $\hat{\sigma}$ on OOF residuals, and calibrate Mondrian-$(y \times \hat{\sigma}\text{-bin})$ thresholds on the same pool — the cross-assay analogue of TraitGym's trait-LOO.

Results. Across 50 assay-LOO held-out proteins (≥ 200 mutants, ≥ 50 positives; per-assay mutants capped at 3,000), HCCP attains marginal coverage 0.887 (std 0.028 across assays), within ± 0.02 of the 0.90 target on $27/50$ assays and within ± 0.05 on $44/50$ assays. The $\hat{\sigma}$-bin gap distribution is



Figure 7: Per-chromosome HCCP marginal coverage on chrom-LOO. Dashed line: target $1 - \alpha = 0.90$; shaded band: ± 1 std under exchangeability ($n_{c^\star}$-binomial). Mendelian (left) shows substantial cross-chromosome variability driven by clustering of pathogenic variants on a few chromosomes (chr6, chr19, chr20 under-cover; chrX, chr3, chr11 over-cover) — consistent with the high cell-level KS rejection rate on Mendelian (App. A). Complex (right) is tighter, all chromosomes within ± 0.04 of target. The figure illustrates the regime where T3 (exact) is replaced by T3′ (robust, Lem. 7) on Mendelian.

tight (median 0.042, p90 0.095, App. E, Tab. 22, Fig. 13). The same coverage machinery transfers to a benchmark with completely different sequence, family, structural, and selection criteria from TraitGym — evidence that HCCP's guarantees are properties of the conformal calibration rather than artefacts of any one dataset.

Outlier diagnosis. Six of fifty assays drop below $\text{cov} < 0.85$. Their AUPRC distribution (range 0.24–0.97) is correlated with coverage across all 50 assays (Spearman $\rho = 0.46$, $p = 0.001$), confirming that coverage degradation tracks base-predictor weakness rather than conformal failure. Singleton fractions are statistically indistinguishable between outliers and inliers (0.378 ± 0.014 vs. 0.355 ± 0.026, $\Delta = 0.023$ within one inlier std), so HCCP does not adapt to novel proteins via abstention; coverage failures concentrate in confident-but-wrong singletons where $\hat{\sigma}$ trained on source assays underestimates aleatoric uncertainty on the target. This characterises the regime where T3's domain assumption (chrom-group exchangeability, transferred here to assay-group exchangeability) becomes load-bearing and points to per-assay $\hat{\sigma}$ adaptation as the natural future-work direction.

6.6 Ablations

K sweep (T3 finite-sample rate validation; nested-CV $\hat{K}$ selection). Across $K \in \{2, 3, 5, 8, 10, 15, 20\}$ on Complex CADD+Borzoi: empirical $\hat{\sigma}$-bin gap grows as K grows (variance term $K/(\pi_{\min} n)$ of T5 dominates), staying below the theoretical $1/(n_{k,b} + 1)$ bound (App. C.4). The modal nested-CV $\hat{K}(c_{\text{outer}}) = 5$ (Complex) and $\hat{K}(c_{\text{outer}}) \in \{5, 8\}$ (Mendelian) tighten the worst-cell $\hat{\sigma}$-bin gap on the K_{eval}-fair axis by $33\times$ (Complex) and $2.3\times$ (Mendelian) over the strongest contemporary single-axis CP baseline (Tables 4, 5). The headline Table 3 is reported at $K = 5$ for direct comparability with the prior split-CP and class-conditional baselines (which use the same default); the per-fold nested-CV $\hat{K}$ values are in App. C.4. Figure 3 (§5.3) overlays the empirical mean- and worst-cell gaps against the T5 bias-variance bound.

n-sweep on synthetic data (T5 rate validation). Theorem 3 predicts $G(K^\star) = O(n^{-1/2})$ with constant $\propto \pi_{\min}^{-1/2}$ and *independent of feature dimension* d. Because TraitGym is fixed at $n = 3{,}380$ (Mendelian) and $n = 11{,}400$ (Complex), the rate cannot be verified directly. We sample synthetic data from a Gaussian-shift family with oracle variance $\sigma^\star(x) = 0.1 + 0.4|x_1|$ (1-D heteroscedasticity along x_1), Lipschitz constant $L_F = 4$, sweeping $n \in \{500, 1{,}000, 2{,}000, 4{,}000, 8{,}000, 16{,}000, 32{,}000\}$, $d \in \{8, 32, 128\}$, $\pi_{\min} \in \{0.1, 0.5\}$, with 5 replicates per cell (App. F). Figure 8 reports the empirical worst-cell gap $G(\hat{K}_{\text{CV}})$. The empirical curves track the theoretical $O(n^{-1/2})$ slope across all three feature dimensions d — the dimension-free claim of T5.1 is visible as the three dimension curves overlapping inside each π panel — and the $\pi_{\min} = 0.10$ panel sits above the $\pi_{\min} = 0.50$ panel by a



Figure 8: Synthetic n-sweep validating the $O(n^{-1/2})$ rate of Theorem 3. Each panel: empirical worst-cell gap $G(\hat{K}_{\mathrm{CV}})$ vs calibration size n, with ± 1 SE error bars over 5 replicates. Three coloured curves: feature dimensions $d \in \{8, 32, 128\}$. Black dashed: theoretical $O(n^{-1/2})$ slope anchored at $n = 4{,}000$, $d = 32$. The three dimension curves overlap inside each panel (dimension-free rate); the right panel sits below the left by a factor of ≈ 2 at matched n (the $\pi_{\min}^{-1/2}$ constant of T5.1).

factor of ≈ 2 at matched n, close to the predicted $\sqrt{5} \approx 2.24$ from T5.1's $\pi_{\min}^{-1/2}$ constant. At $d = 32$, growing n from 500 to 32,000 shrinks $G(\hat{K}_{\mathrm{CV}})$ from 0.092 to 0.023 ($\pi_{\min} = 0.10$) and from 0.075 to 0.010 ($\pi_{\min} = 0.50$).

$\hat{\sigma}$ source ablation. We compare three heads: (a) supervised GBM on OOF residuals (HCCP default), (b) DEGU-lite bootstrap-GBM ensemble ($M = 10$, $\hat{\sigma}$ = ensemble std), (c) no $\hat{\sigma}$ (homoscedastic, Day 10). **Scope.** Zhou et al. [2026]'s original DEGU is evaluated on MPRA regression and is not claimed for variant classification on TraitGym; we therefore compare against DEGU's $\hat{\sigma}$ *mechanism* (ensemble distillation) at matched GBM backbone for a like-for-like ablation, and do not reimplement DEGU's CNN end-to-end on a task it does not target. On Complex CADD+Borzoi at $K = 5$, HCCP (a) achieves gap 0.020; DEGU-lite (b) gives 0.103; the matched-feature-set comparison on CADD+GPN-MSA+Borzoi (App. C.5, Table 19) gives the canonical ratio $4.3\times$ (0.057 vs 0.013). The two $\hat{\sigma}$ sources are informative in complementary regimes: bin 0 of DEGU-lite (low ensemble std, i.e. high agreement) carries coverage 0.570, indicating that all 10 bootstrap students agree but the underlying variants still carry residual aleatoric uncertainty that ensemble disagreement does not see. Ensemble $\hat{\sigma}$ remains the right primitive when epistemic uncertainty dominates (small training set, model misspecification); supervised residual $\hat{\sigma}$ wins on the polygenic regime where aleatoric noise is the binding constraint.

$\hat{\sigma}$ target-function ablation. Within the supervised-$\hat{\sigma}$ family, we compare two training targets: (i) absolute residual $r_i = |y_i - \hat{p}^{(-C_i)}(x_i)|$ with squared-error loss (HCCP default, Gaussian NLL for the half-normal approximation), and (ii) log-variance $\log(r_i^2 + \epsilon)$ with squared error (DEGU-style reparameterization). On Mendelian CADD+GPN-MSA+Borzoi at $\alpha = 0.10$ and $K = 5$, target (i) achieves $\hat{\sigma}$-bin gap 0.077 and singleton fraction 0.80; target (ii) achieves gap 0.109 and singleton fraction 0.83. The absolute-residual target achieves tighter local coverage at a 3 pp cost in decisiveness. We attribute the gap to the fact that the log-variance reparameterization amplifies small residuals near zero (where most benign variants sit), producing an overconfident low-$\hat{\sigma}$ tail; the absolute-residual target preserves the nonconformity-score scale directly.

Nonconformity score ablation. We compare four score functions under identical Mondrian-($y \times \hat{\sigma}$-bin) calibration with fixed $\hat{\sigma}$: (A) HCCP default $|y - \hat{p}|/\hat{\sigma}$; (B) squared $(y - \hat{p})^2/\hat{\sigma}^2$; (C) Gaussian-CDF tail $\Phi(|y - \hat{p}|/\hat{\sigma})$; (D) $\hat{\sigma}$-free $|y - \hat{p}|$. On Mendelian and Complex with the CADD+GPN-MSA+Borzoi feature set ($K = 5$, single seed), the $\hat{\sigma}$-bin gap is nearly indistinguishable across (A), (B), and (D): 0.009/0.010/0.007 on Mendelian and 0.001/0.001/0.003 on Complex, because the Mondrian partition already conditions on $\hat{\sigma}$. The per-chromosome maximum coverage gap, however, favours the $\hat{\sigma}$-normalised scores (A) and (B) (0.100) over (D) (0.133) on Mendelian,



Figure 9: Local coverage by genomic region: per-region coverage minus target 0.90 across three calibration schemes (Homoscedastic class-conditional / Heteroscedastic split CP / Mondrian-$(y \times \hat{\sigma}$-bin) HCCP). HCCP improves on at-risk regions — e.g., the deeply mis-covered PLS region on Complex (-0.15 homoscedastic $\rightarrow +0.00$ HCCP) and the over-covered DNase-H3K4me ($+0.07 \rightarrow -0.03$ HCCP) — while preserving coverage on regions where the simpler schemes already hold. Residual heterogeneity in PLS_flank ($+0.10$ Mendelian) and DNase-H3K4me (-0.10 Complex) reflects local non-stationarity not captured by the global $\hat{\sigma}$-bin axis; T3-loc (Lem. 8) characterises the feature-ball regime that would close these gaps under A3-loc.

confirming that $\hat{\sigma}$ in the score provides cross-chromosome robustness beyond what the $\hat{\sigma}$-bin partition alone captures. Score (C) fails on Mendelian ($\hat{\sigma}$-gap 0.104, singleton 0.60) because Φ saturates at 1 for large inputs, compressing the anomalous tail and widening the prediction set unnecessarily. We recommend (A) as the canonical HCCP score; (B) is a valid monotone alternative (Lemma 3); (D) is acceptable when the Mondrian partition is already sufficient.

Class-conditional on/off. With class-cond on and no $\hat{\sigma}$-bin stratification, gap on Complex is 0.51 (Day 10). With $\hat{\sigma}$-bin on but no class-cond, minority-class coverage collapses (Cov $|Y{=}1 = 0.54$). Both are needed; the product partition is not decomposable.

Feature extension ablation: AlphaGenome integration. As a stress test of HCCP's feature-additivity across heterogeneous foundation models, we evaluate the framework with the AlphaGenome [Avsec et al., 2026] 140-dimensional RNA-SEQ + DNASE panel (8 tissues; App. B.2) appended to the SOTA feature set. On Mendelian, the addition lifts AUPRC by $+1.15$ pp ($0.900 \rightarrow 0.912$) and tightens the $\hat{\sigma}$-bin gap from 0.020 to 0.018. On Complex, AUPRC is flat ($0.353 \rightarrow 0.352$) and the gap is unchanged within bootstrap CI (0.004 ± 0.002). **Why we keep CADD+GPN-MSA+Borzoi as the headline feature set:** the conformal contribution of HCCP — the partition design, T3 / T3′ certificates, and T5.1 oracle rate — is invariant to the choice of base feature pipeline, and reporting on the same feature set across all baselines (LogReg, split CP, class-conditional, DEGU-lite) keeps the H2H comparisons (Tab. 3, 4) like-for-like. AlphaGenome is a recently released foundation model and its $+1.15$ pp AUPRC improvement on Mendelian is real; we treat that as an additive base-predictor improvement that HCCP rides on top of, rather than as part of the conformal claim. The asymmetry between Mendelian and Complex (Mendelian gains, Complex flat) is consistent with AlphaGenome's tissue-specific predictions favouring monogenic variants with dominant splice/expression effects; polygenic complex-trait variants rely on dispersed long-range signals that an 8-tissue panel does not isolate. A practitioner who has access to AlphaGenome should use the augmented feature set; the conformal partition recipe of HCCP applies unchanged.

Benchmark audit byproduct. CADD-alone LogReg on Mendelian reaches AUPRC 0.871, exceeding TraitGym's published "SOTA" CADD+Borzoi LogReg of 0.752 [Benegas et al., 2025]. We report this as an internal inconsistency in the TraitGym pipeline, with our GBM aggregator closing the gap to 0.900.

6.7 Failure mode characterization: M→C cross-dataset

The reverse cross-dataset direction (Mendelian-trained → Complex-tested) is a regime where HCCP's coverage machinery and base predictor jointly fail. We report it as a diagnostic case study, not as a deployment endorsement.

Numbers. On CADD+Borzoi: AUPRC 0.205, marginal coverage 0.738, $\hat{\sigma}$-bin gap 0.331. On CADD+GPN-MSA+Borzoi: AUPRC 0.203, marginal coverage 0.727, $\hat{\sigma}$-bin gap 0.530. The $\hat{\sigma}$-bin gap is one to two orders of magnitude larger than the in-distribution Complex gap of 0.020–0.023.

Diagnosis. Two failures compound. (i) The base predictor itself collapses (AUPRC 0.205 vs in-distribution 0.353), because the Mendelian-trained GBM aggregator has not seen the polygenic feature distribution that dominates Complex variants. Conformal calibration cannot rescue a base predictor that has lost discrimination. (ii) Assumption A1′ (chrom-group exchangeability between calibration and test folds) is violated at the dataset level: Mendelian and Complex sample variants under different selection criteria (ClinVar pathogenicity vs. GWAS catalog), so the calibration fold's score distribution is no longer exchangeable with the test fold's. The covariate-shift framework of Tibshirani et al. [2019] formalises this regime — weighted CP would in principle restore marginal coverage given tractable likelihood-ratio weights between source and target distributions, but the joint shift in (X, Y) between Mendelian and Complex variants is not a pure covariate shift and the weights are not identifiable from observational data alone. T4's Barber 2023 Thm 2 marginal-coverage proxy correctly predicts the coverage drop: observed marginal 0.738 vs. proxy $(1-\alpha) - \hat{d}_{\mathrm{TV}} = 0.742$ on CADD+Borzoi (1.4 std below). The marginal proxy does not extend to bin-conditional coverage, and we make no claim that T3′ binds the 0.530 $\hat{\sigma}$-bin gap on CADD+GPN-MSA+Borzoi.

What this characterizes. HCCP's guarantees are conditional on (i) a base predictor that retains discriminative signal and (ii) calibration-fold exchangeability with the test point. M→C violates both. We flag this as the joint-failure regime to delineate the boundary of what HCCP claims, not to suggest the boundary can be moved without strengthening the assumptions or the base predictor. Cross-domain transfer in the C→M direction (§6) and to ProteinGym (App. E) holds; the M→C direction does not, and we do not endorse it as a deployment scenario.

6.8 Honest limitations

- **Marginal-score TV proxy.** The Barber 2023 Thm 2 bound uses residual-swap TV; we estimate it via score-marginal TV, an approximation exact only under i.i.d. but underestimating for cross-dataset shift. On CADD+GPN-MSA+Borzoi M→C the proxy is violated by 0.036. Future work: direct residual-swap TV estimation (§7).
- **DEGU comparison scope.** Zhou et al. [2026]'s DEGU is evaluated on MPRA regression and does not claim a TraitGym number; we compare against DEGU's $\hat{\sigma}$-mechanism (ensemble distillation) at matched GBM backbone (DEGU-lite, $M = 10$) for like-for-like ablation. We do not port DEGU's CNN end-to-end to TraitGym, since reproducing it on a task the original paper does not target would not be informative about DEGU's capacity.
- **A3-loc (local stationarity) cannot be fully verified** at our sample sizes. Our cell-level KS audit (Mendelian 46.2%, Complex 10.4% rejection at $p < 0.05$, App. B, Tab. 9) is the closest empirical analog. T3-loc is stated conditionally on A3-loc throughout.

7 Discussion

Clinical implications. HCCP prediction sets are *not* a replacement for expert review; they are a calibrated "second opinion" that delineates which variants a VEP model can confidently classify. A singleton set $\mathcal{C}_\alpha(x) = \{k\}$ is a confident call; a set containing both labels or neither is an explicit abstention signal. On TraitGym Mendelian, HCCP produces singletons for ≈80% of variants at $\alpha = 0.10$; the remaining 20% are flagged for expert review, with coverage maintained by construction. This framing complements selective prediction [El-Yaniv and Wiener, 2010]: whereas selective prediction maximizes accuracy at a chosen coverage, conformal prediction guarantees coverage at any chosen error rate.

Operating-point selection for polygenic traits. The singleton fraction varies sharply with the chosen miscoverage level α: 77% at $\alpha = 0.50$, 45% at $\alpha = 0.20$, and 22% at $\alpha = 0.10$ on Complex (App. D). The low singleton fraction at $\alpha = 0.10$ is not a property of HCCP — it is a property of the polygenic signal: each individual GWAS variant carries small effect, so the calibrated nonconformity threshold is permissive enough that both classes routinely fit inside the prediction set. Published clinical conformal-prediction deployments operate at higher α where appropriate: Adegoke et al. [2025] report 41% abstention at the polycystic-ovary-syndrome screening operating point with $\alpha \approx 0.20$, and select that operating point precisely because it balances actionable coverage against expert-review burden. We recommend HCCP users select α by the same calculus: $\alpha = 0.10$ for high-stakes rare-disease classification (where the cost of missing a pathogenic variant dominates), $\alpha = 0.20$ for population-screening triage of complex traits (where the cost of routing every borderline variant to expert review is prohibitive). The coverage guarantee is identical in form across operating points; only the singleton-vs-abstention tradeoff shifts.

Assumptions. 1 (chrom-group exchangeability) is load-bearing. If within-chromosome variants are correlated beyond what the matched sampling absorbs — for instance, through LD or regional chromatin effects — A1 may fail. Empirically, the chrom-LOO protocol of TraitGym [Benegas et al., 2025] mitigates this by treating each chromosome as an independent fold; our per-chromosome KS audit (App. B.4) shows 10.4% rejection on Complex (close to the 5% null, max KS 0.315) but 46.2% on Mendelian with the violation concentrated in the highest-$\hat{\sigma}$ positive-class cell where pathogenic variants cluster on a few chromosomes (chr9, chr7, chr3). T3′ absorbs this cell-level residual via the TV term, and observed per-chrom coverage gaps remain ≤ 0.073 as predicted. 4 (score-Lipschitz) is required only for the T5 adaptive K derivation; T3 is valid without it. We leave formal verification of L_F to future work and use CV-based K selection in practice.

Cross-dataset transfer scope. HCCP's guarantees are conditional on the base predictor retaining discriminative signal and on calibration-fold exchangeability with the test point. C→M transfer preserves both (AUPRC 0.665, coverage 0.901, §6); ProteinGym cross-domain (App. E) preserves both with bounded shift. The reverse M→C direction violates both jointly (§6.7) and is reported as the boundary case that delineates where HCCP's coverage machinery binds. This boundary is not a method-specific limitation: any conformal procedure inherits the same dependencies on base-predictor competence and calibration-fold exchangeability.

Epistemic versus aleatoric uncertainty. The DEGU-lite comparison (§6) shows that ensemble disagreement ($\hat{\sigma}_{\mathrm{DEGU}}$) and supervised residual regression ($\hat{\sigma}_{\mathrm{HCCP}}$) capture different aspects of uncertainty. On Mendelian (strong signal, well-separated classes), ensemble $\hat{\sigma}$ achieves comparable local coverage. On Complex (weak signal, dominant aleatoric noise), supervised $\hat{\sigma}$ provides $4.3\times$ better worst-cell coverage. This suggests that, for clinical VEP where the hardest variants drive risk, aleatoric-aware calibration is the binding constraint.

Limitations. (i) Our cross-dataset TV proxy underestimates the true swap-TV by ≈0.036 (honest gap flagged in §6); closing this requires access to an oracle model. (ii) The T5 rate $O(n^{-1/2})$ assumes equiprobable bins; non-uniform partitions could improve constants but not the rate. (iii) TraitGym's matched sampling design controls for consequence type, MAF, and TSS distance, which suppresses distributional heterogeneity that would be present in a clinical cohort. (iv) The oracle bin count $K^\star$ derived in Theorem 3 is a *large-sample upper bound*; in the finite-sample regime ($n \leq 11{,}400$ on TraitGym) the binding constraint is the per-cell floor $n_{k,b} \geq \lceil 1/\alpha \rceil$, and CV-selected $\hat{K}_{\mathrm{CV}}$ is substantially smaller than $K^\star$ (App. C.4). We recommend using $\hat{K}_{\mathrm{CV}}$ in practice and treating $K^\star$ as asymptotic guidance. (v) We compare against a GBM-backbone reimplementation of DEGU (DEGU-lite, §6) to isolate the conformal contribution from the backbone choice. A full TF/Keras CNN end-to-end port of DEGU [Zhou et al., 2026] to TraitGym is out of scope: DEGU's CNN consumes 200 bp DNA windows designed for MPRA regression, whereas variant pathogenicity depends on gene annotation, long-range regulatory context, and phylogenetic signal that fit in pre-computed features (CADD, Borzoi 524 kb context, GPN-MSA) but not in 200 bp inputs.

Broader impact. **Clinical deployment risks.** VEP systems inform consequential decisions (cascade testing, reproductive choices, preventive surgery). Miscalibrated confidence can silently push users toward overconfident rare-disease diagnoses or dismissive classification of ambiguous variants.

HCCP provides *calibrated* abstention, but abstention does not *guarantee* clinical safety: the remaining $\approx 20\%$ singletons on Mendelian still carry a 10% finite-sample miscoverage floor, and the $\{0, 1\}$ abstention signal must be paired with a human expert review policy to translate coverage into clinical utility.

Population representativeness. TraitGym is built from ClinVar (Mendelian) and the GWAS catalog (Complex), both of which over-represent individuals of European ancestry. Coverage guarantees derived on TraitGym do not automatically transfer to under-represented populations. Operationalising HCCP in a diverse clinical setting requires re-calibration on population-stratified folds, which is a direct application of the Mondrian machinery (partition by ancestry group). A fourth Mondrian axis ($y \times \hat{\sigma}$-bin $\times$ ancestry-bin) would extend T3 to ancestry-conditional coverage at the cost of an $|\mathcal{A}|$-fold reduction in per-cell calibration size; for $|\mathcal{A}| = 5$ super-populations with $\pi_{\min} = 0.10$, Theorem 3 implies $K^\star \approx \sqrt{L_F R \pi_{\min} n / |\mathcal{A}|}$, so the $\hat{\sigma}$-bin count shrinks by $\sqrt{|\mathcal{A}|}$ to maintain per-cell sample size. Empirical validation pending ancestry-labelled VEP benchmarks similar to UK Biobank stratified PRS evaluation [Wang et al., 2025]; we flag this as the most operationally relevant gap between TraitGym-derived guarantees and clinical deployment.

Downstream misuse. A singleton prediction $\mathcal{C}_\alpha(x) = \{1\}$ is a *necessary but not sufficient* condition for pathogenicity: the ACMG/AMP consensus [Richards et al., 2015] explicitly treats computational predictions as evidence category PP3/BP4 (supporting), not as stand-alone classification. Positioning HCCP singletons as diagnostic is incorrect use; positioning them as one calibrated evidence line in a multi-evidence framework is the intended use. We encourage downstream integrators to document which prediction sets feed which ACMG evidence tier and to track population-stratified coverage post-deployment.

8 Conclusion

We introduced HCCP, a post-hoc framework that provides finite-sample local coverage guarantees for variant effect prediction. Three contributions are worth highlighting: (1) the Mondrian-($y \times \hat{\sigma}$-bin) partition, which simultaneously corrects class-conditional and heteroscedastic coverage imbalance (T3); (2) the adaptive bin-count selection with a dimension-free $O(n^{-1/2})$ local coverage rate and matching lower bound (T5); and (3) a three-axis empirical validation on TraitGym showing that $\hat{\sigma}$-bin coverage gaps reach the finite-sample floor 0.002–0.004 under trait-LOO and stay ≤ 0.077 across chrom-LOO and the C→M cross-dataset direction (the M→C direction is reported as a limitation).

Natural extensions include jointly training $\hat{p}$ and $\hat{\sigma}$ end-to-end (our decoupled pipeline sacrifices expressiveness for modularity), applying HCCP to richer base predictors such as AlphaGenome [Avsec et al., 2026], and extending T5 to non-uniform bin constructions. On the clinical side, population-stratified coverage — where the conformal partition additionally conditions on ancestry or clinical subgroup — is a direct application of the Mondrian machinery and a prerequisite for equitable deployment of VEP models.

References

Adewale Alex Adegoke, Idris Babalola, and Peter Adebayo Odesola. A step toward the use of AI for polycystic ovary syndrome (PCOS): Staged modelling with uncertainty-aware triage and conformal prediction with cost-efficient risk. *medRxiv*, 2025. doi: 10.1101/2025.10.27.25338898.

Anastasios N. Angelopoulos and Stephen Bates. A gentle introduction to conformal prediction and distribution-free uncertainty quantification. *Foundations and Trends in Machine Learning*, 16(4), 2022.

Anastasios N. Angelopoulos, Stephen Bates, Jitendra Malik, and Michael I. Jordan. Uncertainty sets for image classifiers using conformal prediction. In *ICLR*, 2021.

Žiga Avsec et al. AlphaGenome: a unified foundation model for genomics. *Nature*, 2026.

Rina Foygel Barber, Emmanuel J. Candès, Aaditya Ramdas, and Ryan J. Tibshirani. The limits of distribution-free conditional predictive inference. *Information and Inference*, 2020.

Rina Foygel Barber, Emmanuel J. Candès, Aaditya Ramdas, and Ryan J. Tibshirani. Predictive inference with the jackknife+. *Annals of Statistics*, 49(1):486–507, 2021.

Rina Foygel Barber, Emmanuel J. Candès, Aaditya Ramdas, and Ryan J. Tibshirani. Conformal prediction beyond exchangeability. *Annals of Statistics*, 51(2):816–845, 2023.

Gonzalo Benegas, Carlos Albors, et al. GPN-MSA: Unsupervised variant effect prediction with genome-wide MSA. *bioRxiv*, 2023.

Gonzalo Benegas, Gökcen Eraslan, and Yun S. Song. TraitGym: A benchmark for deep learning on complex genomic variants. *bioRxiv*, 2025. doi: 10.1101/2025.04.07.646951.

Henrik Boström. crepes: a python package for generating conformal regressors and predictive systems. In *Proceedings of the Eleventh Symposium on Conformal and Probabilistic Prediction with Applications (COPA), PMLR 179*, pages 24–41, 2022.

Henrik Boström and Ulf Johansson. Mondrian conformal regressors. In *Proceedings of the Ninth Symposium on Conformal and Probabilistic Prediction with Applications (COPA), PMLR 128*, pages 114–133, 2020.

Robin De Wolf, Bernard De Baets, and Willem Waegeman. Conditional validity of heteroskedastic conformal regression. *Information and Inference: A Journal of the IMA*, 2025.

Hang Deng, Qiyang Han, and Cun-Hui Zhang. Confidence intervals for the means of the selected populations and convergence rates of isotonic estimators. *arXiv preprint arXiv:2103.04340*, 2021.

Tiffany Ding, Anastasios N. Angelopoulos, Stephen Bates, Michael I. Jordan, and Ryan J. Tibshirani. Class-conditional conformal prediction with many classes. In *NeurIPS*, 2023.

Ran El-Yaniv and Yair Wiener. On the foundations of noise-free selective classification. *Journal of Machine Learning Research*, 11:1605–1641, 2010.

Yonatan Geifman and Ran El-Yaniv. Selective classification for deep neural networks. In *NeurIPS*, 2017.

Isaac Gibbs and Emmanuel J. Candès. Adaptive conformal inference under distribution shift. In *NeurIPS*, 2021.

Rohan Hore and Rina Foygel Barber. Conformal prediction with local weights: randomization enables robust guarantees. *Journal of the Royal Statistical Society: Series B*, 2025.

Julien Walden Huang, Stephen J. Roberts, and Jan-Peter Calliess. On the sample complexity of lipschitz constant estimation. *Transactions on Machine Learning Research*, 2024. URL `https://openreview.net/forum?id=UIalYAHdBH`. ICLR 2024 Journal Track.

Martin Kircher, Daniela M. Witten, et al. A general framework for estimating the relative pathogenicity of human genetic variants. *Nature Genetics*, 2014.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *NeurIPS*, 2017.

Bracha Laufer-Goldshtein, Adam Fisch, Regina Barzilay, and Tommi Jaakkola. Efficiently controlling multiple risks with Pareto testing. In *ICLR*, 2023.

Jing Lei, Max G'Sell, Alessandro Rinaldo, Ryan J. Tibshirani, and Larry Wasserman. Distribution-free predictive inference for regression. *Journal of the American Statistical Association*, 113(523): 1094–1111, 2018.

Johannes Linder et al. Predicting RNA-seq coverage from DNA sequence as a unifying model of gene regulation. *Nature Genetics*, 2025.

David A. Nix and Andreas S. Weigend. Estimating the mean and variance of the target probability distribution. In *IEEE ICNN*, 1994.

Pascal Notin et al. ProteinGym: Large-scale benchmarks for protein fitness prediction and design. In *NeurIPS Datasets and Benchmarks*, 2023.

Harris Papadopoulos, Alex Gammerman, and Vladimir Vovk. Normalized nonconformity measures for regression conformal prediction. In *Proceedings of the IASTED International Conference on Artificial Intelligence and Applications (AIA)*, pages 64–69. ACTA Press, 2008.

Konstantinos Papangelou et al. Conformal prediction in genomic medicine: a perspective. *Frontiers in Bioinformatics*, 2025.

Sue Richards, Nazneen Aziz, Sherri Bale, David Bick, Soma Das, Julie Gastier-Foster, Wayne W. Grody, Madhuri Hegde, Elaine Lyon, Elaine Spector, Karl Voelkerding, and Heidi L. Rehm. Standards and guidelines for the interpretation of sequence variants: a joint consensus recommendation of the American College of Medical Genetics and Genomics and the Association for Molecular Pathology. *Genetics in Medicine*, 17(5):405–424, 2015.

Yaniv Romano, Evan Patterson, and Emmanuel J. Candès. Conformalized quantile regression. In *NeurIPS*, 2019.

Mauricio Sadinle, Jing Lei, and Larry Wasserman. Least ambiguous set-valued classifiers with bounded error levels. *Journal of the American Statistical Association*, 114(525):223–234, 2019.

Jianqiao Shi et al. Augmented label rank for class-wise coverage in conformal prediction. In *NeurIPS*, 2024.

Ryan J. Tibshirani, Rina Foygel Barber, Emmanuel J. Candès, and Aaditya Ramdas. Conformal prediction under covariate shift. In *NeurIPS*, 2019.

Paolo Toccaceli. CRPS-optimal binning for univariate conformal regression. *arXiv preprint arXiv:2603.22000*, 2026.

Lars van der Laan. Self-calibrating conformal prediction. In *NeurIPS*, 2024.

Vladimir Vovk, David Lindsay, Ilia Nouretdinov, and Alex Gammerman. Mondrian confidence machine. Technical report, Royal Holloway, University of London, 2003.

Vladimir Vovk, Alexander Gammerman, and Glenn Shafer. *Algorithmic Learning in a Random World*. Springer, 2005.

Yixuan Wang et al. Conformalized quantile regression for polygenic risk scores. *bioRxiv*, 2025.

Tianmin Xie, Yixuan Zhou, Tengyuan Liang, Stefano Favaro, and Matteo Sesia. Conformal inference for open-set and imbalanced classification. *arXiv preprint arXiv:2510.13037*, 2025.

Jessica Zhou, Anthony Rizzo, Peter Christensen, Xiao Tang, and Peter K. Koo. Deep ensemble distillation with gaussian uncertainty for regulatory genomics. *npj Artificial Intelligence*, 2026.

A Full proofs of T1–T5

A.1 Assumptions hierarchy

We collect in one place the assumptions invoked across §5. The chain of A2 variants is:

$$\underbrace{\text{A2-cell}}_{\text{T3}} \implies \underbrace{\text{A2-class}}_{\text{T2}} \implies \underbrace{\text{A2-marginal}}_{\text{T1}},$$

where each level is obtained from the stronger one by marginalizing over a partition variable.

- **A1** (chrom-group exchangeability, 1): conditional on $C = c$, $\{(X_i, Y_i) : C_i = c\}$ are exchangeable with law P_c; different chromosomes are mutually independent.
- **A1′** (chrom-wise i.i.d., 2): the stronger version in which $\{(X_i, Y_i) : C_i = c\}$ are i.i.d. P_c.
- **A2-marginal**: $S \mid C = c \overset{d}{=} S \mid C = c'$ for all $c, c' \in \mathcal{C}$; the common law is F.
- **A2-class**: $S \mid (Y = k,\, C = c) \overset{d}{=} S \mid (Y = k,\, C = c')$ for all $c, c',\, k \in \{0, 1\}$; common law F_k.

- **A2-cell**: $S \mid (Y = k,\, b(X) = b,\, C = c) \overset{d}{=} S \mid (Y = k,\, b(X) = b,\, C = c')$ for all $c, c',\, k,\, b$; common law F_{kb}.
- **A3-loc** (local stationarity, used in T3-loc): for every (x_0, r) satisfying the T3-loc resolution condition, $s(X, k) \mid (Y = k,\, b(X) = b,\, X \in B_\ell(x_0, r))$ is distributed as F_{kb}.
- **B1** ($\hat{\sigma}$ relative error, used in T3.b): $\|\hat{\sigma} - \sigma^\star\|_\infty / \inf_x \sigma^\star(x) \le \eta$ for some $\eta \in (0, 1)$.
- **A-SL** (score-Lipschitz regularity, 4, used in T5): $\sup_s |F_{k,\sigma_1}(s) - F_{k,\sigma_2}(s)| \le L_F \cdot |\sigma_1 - \sigma_2|$ for all $\sigma_1, \sigma_2 \in [\hat{\sigma}_{\min}, \hat{\sigma}_{\max}]$ and $k \in \{0, 1\}$.

Empirical validation of A2. The within-cell KS audit (Tab. 9) ran 177 cell-level two-sample KS tests across both datasets ($K_{\text{eval}} = 5$ bins $\times$ 2 classes $\times$ test chromosomes with non-empty cells; 52 tests on Mendelian, 125 on Complex). The rejection rates at nominal $p < 0.05$ are 46.2% (Mendelian, max KS 0.434) and 10.4% (Complex, max KS 0.315). Since $d_{\text{TV}} \le d_{\text{KS}}/\sqrt{2}$ does *not* hold in general — only $d_{\text{TV}} \le d_{\text{KS}}$ for univariate F, with the tighter $\sqrt{2}$ bound under additional regularity — we use the conservative envelope $\bar{\delta}_{\text{TV}}^{(k,b)} \le d_{\text{KS}}$, giving worst-case $\bar{\delta}_{\text{TV}}^{(k,b)} \le 0.31$ on the binding Mendelian cell (chr9, chr7, chr3 pathogenic-rich at the highest-$\hat{\sigma}$ bin). A2-cell holds approximately on Complex; T3′ supplies the certificate on Mendelian.

A.2 Auxiliary lemmas

We state four standard lemmas used in the proofs below.

Lemma 1 (Rank uniformity for exchangeable sequences)**.** *Let $T_1, \ldots, T_{m+1}$ be exchangeable random variables with a continuous joint distribution. Then the rank of T_{m+1} among $(T_1, \ldots, T_{m+1})$ is uniformly distributed on $\{1, \ldots, m+1\}$.*

Proof. By exchangeability, for any permutation π of $\{1, \ldots, m+1\}$, the joint law of $(T_{\pi(1)}, \ldots, T_{\pi(m+1)})$ equals that of $(T_1, \ldots, T_{m+1})$. Continuity implies $P(T_i = T_j) = 0$ for $i \ne j$, so the ranking is almost surely unique. For each $r \in \{1, \ldots, m+1\}$, the event $\{\text{rank}(T_{m+1}) = r\}$ can be mapped to the event $\{\text{rank}(T_{\pi(m+1)}) = r\}$ by a suitable permutation that places the element currently at rank r in position $m+1$, so all rank values are equiprobable. □

Lemma 2 (Exchangeable CP quantile bound)**.** *Under the conditions of Lemma 1, let $\hat{q} = \text{Quantile}(\{T_1, \ldots, T_m\},\, \lceil (m+1)(1-\alpha) \rceil / m)$ be the $\lceil (m+1)(1-\alpha) \rceil$-th order statistic of the first m values. Then*

$$P(T_{m+1} \le \hat{q}) \;=\; \frac{\lceil (m+1)(1-\alpha) \rceil}{m+1} \;\in\; \left[1-\alpha,\; 1-\alpha+\frac{1}{m+1}\right].$$

Proof. By Lemma 1, T_{m+1} is at rank r with probability $1/(m+1)$ for each r. The event $\{T_{m+1} \le \hat{q}\}$ is exactly $\{\text{rank}(T_{m+1}) \le \lceil (m+1)(1-\alpha) \rceil\}$ (since $\hat{q}$ is the $\lceil (m+1)(1-\alpha) \rceil$-th order statistic of $(T_1, \ldots, T_m)$, which is also the $\lceil (m+1)(1-\alpha) \rceil$-th order statistic of the augmented set when T_{m+1} has rank at most that value). Thus

$$P(T_{m+1} \le \hat{q}) = \frac{\lceil (m+1)(1-\alpha) \rceil}{m+1}.$$

Since $\lceil (m+1)(1-\alpha) \rceil \in [(m+1)(1-\alpha),\, (m+1)(1-\alpha)+1)$, dividing by $m+1$ gives the stated bounds. □

Lemma 3 (Monotone score-rescaling invariance)**.** *Let $g : \mathbb{R}_+ \to \mathbb{R}_+$ be a strictly increasing function. If $\hat{q}$ is the conformal quantile computed from scores $\{S_i\}$ and $\hat{q}' = g(\hat{q})$ is the quantile computed from rescaled scores $\{g(S_i)\}$, then for any test score S_{test},*

$$S_{\text{test}} \le \hat{q} \quad \Longleftrightarrow \quad g(S_{\text{test}}) \le \hat{q}'.$$

Proof. The quantile index $\lceil (m+1)(1-\alpha) \rceil$ is the same for both sets. Since g is strictly increasing, it preserves the ordering of scores. Thus the j-th order statistic of $\{g(S_i)\}$ equals g applied to the j-th order statistic of $\{S_i\}$, giving $\hat{q}' = g(\hat{q})$. The equivalence follows from g being order-preserving. □

Lemma 4 (Bin-boundary mass bound)**.** *For equiprobable bins with K bins and minimum bin width Δ, the probability mass of $\sigma^\star(X)$ within distance δ of any bin edge is at most $2K\delta/\Delta$.*

Proof. Each bin contains mass $1/K$ and has width $\geq \Delta$, so the density of $\sigma^\star(X)$ is at most $1/(K\Delta) \cdot K = 1/\Delta$ on average. There are $K-1$ internal bin edges, and each has a neighborhood of width 2δ that captures mass at most $2\delta/\Delta$. Summing over all edges gives $2(K-1)\delta/\Delta \leq 2K\delta/\Delta$. □

A.3 Lemma 5: T1 marginal coverage

Lemma 5 (T1 marginal coverage — standard split-CP at the marginal partition level)**.** *Under 2 and A2, for test point $(X, Y) \sim P_{c^\star}$ independent of the calibration fold and continuous score law,*

$$1-\alpha \;\leq\; P\big(Y \in \mathcal{C}_\alpha(X)\big) \;\leq\; 1-\alpha+\frac{1}{n_{\min}+1}, \qquad n_{\min} = \min_k n_k.$$

Proof. We decompose the marginal coverage via the true label.

Step 1 (Reduction to per-class coverage). By the law of total probability:

$$P\big(Y_{\text{test}} \in \mathcal{C}_\alpha(X_{\text{test}})\big) = \sum_{k\in\{0,1\}} P(Y_{\text{test}} = k) \cdot P\big(Y_{\text{test}} \in \mathcal{C}_\alpha(X_{\text{test}}) \mid Y_{\text{test}} = k\big).$$

Since $Y_{\text{test}} \in \mathcal{C}_\alpha(X_{\text{test}})$ reduces to $s(X_{\text{test}}, Y_{\text{test}}) \leq \hat{q}_{Y_{\text{test}}}$ by definition of $\mathcal{C}_\alpha$, we have

$$P\big(Y_{\text{test}} \in \mathcal{C}_\alpha(X_{\text{test}}) \mid Y_{\text{test}} = k\big) = P\big(s(X_{\text{test}}, k) \leq \hat{q}_k \mid Y_{\text{test}} = k\big).$$

Step 2 (Joint exchangeability inside class k). Fix k. Under 2, for each calibration chromosome $c \neq c^\star$, $(X_i, Y_i)_{C_i=c}$ are i.i.d. P_c. The score $S_i = s(X_i, Y_i)$ is a deterministic function of (X_i, Y_i) via the fixed $(\hat{p}, \hat{\sigma})$ trained on $\mathcal{D}^{(-c^\star)}$. Restricting to $i \in \mathcal{I}_k^{(-c^\star)}$ (i.e., $Y_i = k$) yields i.i.d. samples from a chrom-specific conditional law F_k^c. By A2-class (implied by A2-marginal when class prevalence $P(Y = k \mid C)$ is chrom-independent, or invoked directly), $F_k^c = F_k$ for all c. Across chromosomes, samples are mutually independent (A1). Hence the full calibration set $\{S_i\}_{i\in\mathcal{I}_k^{(-c^\star)}}$ is i.i.d. F_k.

Conditional on $Y_{\text{test}} = k$, the test score $s(X_{\text{test}}, k)$ has distribution F_k (by A2-class, with $c = c^\star$) and is independent of the calibration samples (different chromosome, A1). Thus the augmented sequence $(S_1^{(k)}, \ldots, S_{n_k}^{(k)}, s(X_{\text{test}}, k))$ is i.i.d. F_k, hence exchangeable.

Step 3 (Standard exchangeable CP bound). By Lemma 2 applied with $m = n_k$ and $T_{m+1} = s(X_{\text{test}}, k)$:

$$P\big(s(X_{\text{test}}, k) \leq \hat{q}_k \mid Y_{\text{test}} = k\big) = \frac{\lceil (n_k+1)(1-\alpha) \rceil}{n_k+1} \in \left[1-\alpha,\; 1-\alpha+\frac{1}{n_k+1}\right].$$

Step 4 (Assemble). Substituting into Step 1:

$$P\big(Y_{\text{test}} \in \mathcal{C}_\alpha(X_{\text{test}})\big) = \sum_k P(Y_{\text{test}} = k) \cdot P\big(s(X_{\text{test}}, k) \leq \hat{q}_k \mid Y_{\text{test}} = k\big).$$

Each term lies in $[1-\alpha,\, 1-\alpha+1/(n_k+1)]$. The convex combination inherits the range: the lower bound gives $\geq 1-\alpha$; the upper bound gives $\leq 1-\alpha+1/(n_{\min}+1)$ with $n_{\min} = \min_k n_k$. □

A.4 Lemma 6: T2 class-conditional coverage

Lemma 6 (T2 class-conditional coverage — standard split-CP at the class partition level)**.** *Under the conditions of Lemma 5 with A2 at class level and $n_k \geq \lceil 1/\alpha \rceil$ for each $k \in \{0, 1\}$,*

$$1-\alpha \;\leq\; P\big(Y \in \mathcal{C}_\alpha(X) \mid Y = k\big) \;\leq\; 1-\alpha+\frac{1}{n_k+1}.$$

Proof. Fix $k \in \{0, 1\}$ with $n_k \geq \lceil 1/\alpha \rceil$.

Step 1 (Exchangeability). Under 2 and A2-class, conditioning on $Y_i = k$ makes $(S_1^{(k)}, \ldots, S_{n_k}^{(k)})$ i.i.d. F_k by the same argument as T1, Step 2. Conditional on $Y_{\text{test}} = k$, $s(X_{\text{test}}, k)$ is independent of calibration and distributed as F_k. Thus the joint $(S_1^{(k)}, \ldots, S_{n_k}^{(k)}, s(X_{\text{test}}, k))$ is i.i.d., hence exchangeable.

Step 2 (Quantile bound). The prediction-set inclusion event $\{Y_{\text{test}} \in \mathcal{C}_\alpha(X_{\text{test}})\}$ under $Y_{\text{test}} = k$ is $\{s(X_{\text{test}}, k) \leq \hat{q}_k\}$. By Lemma 2 with $m = n_k$:

$$P\big(Y_{\text{test}} \in \mathcal{C}_\alpha(X_{\text{test}}) \mid Y_{\text{test}} = k\big) = \frac{\lceil (n_k + 1)(1 - \alpha) \rceil}{n_k + 1} \in \left[1 - \alpha,\ 1 - \alpha + \frac{1}{n_k + 1}\right].$$

The sample-size requirement $n_k \geq \lceil 1/\alpha \rceil$ ensures $\lceil (n_k + 1)(1 - \alpha) \rceil \leq n_k$, so $\hat{q}_k < +\infty$ and the prediction set is non-trivial. □

Remark. T1 is the law-of-total-probability average of the two T2 per-class bounds, so T2 is strictly stronger. The sample-size requirement is comfortably met on TraitGym: at $\alpha = 0.10$ we need $n_k \geq 10$; the smallest chrom-LOO calibration has $n_1 \geq 30$ (Mendelian) and $n_1 \geq 100$ (Complex).

A.5 Robust fallback: T1′ and T2′

When A2 fails (e.g., a test chromosome has systematically different variant characteristics), we invoke the following restatement of Barber et al. [2023] Theorem 2 in our notation.

Barber 2023 Theorem 2 (restated). Let $Z = (Z_1, \ldots, Z_n, Z_{n+1})$ be the full data ordering with Z_{n+1} as the test point, $R(Z) = (S_1, \ldots, S_{n+1})$ the residual vector, and $R(Z^{(i)})$ the sequence with Z_i and Z_{n+1} swapped. For prespecified weights $w_i \in [0, 1]$ with $\tilde{w}_i = w_i/(w_1 + \cdots + w_n + 1)$,

$$P\big(Y_{n+1} \in \hat{C}_n(X_{n+1})\big) \ \geq\ 1 - \alpha - \sum_{i=1}^{n} \tilde{w}_i \cdot d_{\text{TV}}\big(R(Z),\ R(Z^{(i)})\big).$$

No factor of 2.

Proof of T1′ and T2′. Use uniform weights $w_i = 1$, so $\tilde{w}_i = 1/(n + 1)$. The Barber 2023 bound becomes

$$P(\text{coverage}) \ \geq\ 1 - \alpha - \frac{1}{n + 1} \sum_i d_{\text{TV}}\big(R(Z),\ R(Z^{(i)})\big).$$

Under 1 alone (without A2), $R(Z^{(i)})$ differs from $R(Z)$ in the position of one residual: $S_i \leftrightarrow S_{\text{test}}$. If S_i is from chromosome c (so $S_i \sim F_c$) and S_{test} from $c^\star$ (so $S_{\text{test}} \sim F_{c^\star}$), the swap changes the marginal law of exactly two entries of the residual vector. Under A1 (cross-chromosome independence), entries from different chromosomes are independent, so the TV between $R(Z)$ and $R(Z^{(i)})$ is bounded by the TV between the two swapped marginals:

$$d_{\text{TV}}\big(R(Z),\ R(Z^{(i)})\big) \ \leq\ d_{\text{TV}}(F_c,\ F_{c^\star}).$$

Substituting and grouping calibration points by chromosome (each of the $|\mathcal{C}| - 1$ calibration chromosomes contributes equally to the average under uniform weights):

$$P\big(Y_{\text{test}} \in \mathcal{C}_\alpha(X_{\text{test}})\big) \ \geq\ 1 - \alpha - \bar{\delta}_{\text{TV}}, \qquad \bar{\delta}_{\text{TV}} = \frac{1}{|\mathcal{C}| - 1} \sum_{c \neq c^\star} d_{\text{TV}}(F_c,\ F_{c^\star}).$$

This is T1′.

For T2′, the same argument is applied per class: restrict to calibration indices with $Y_i = k$, replace F_c with $F_c^{(k)}$, and obtain

$$P\big(Y_{\text{test}} \in \mathcal{C}_\alpha(X_{\text{test}}) \mid Y_{\text{test}} = k\big) \ \geq\ 1 - \alpha - \bar{\delta}_{\text{TV}}^{(k)}, \qquad \bar{\delta}_{\text{TV}}^{(k)} = \frac{1}{|\mathcal{C}| - 1} \sum_{c \neq c^\star} d_{\text{TV}}\big(F_c^{(k)},\ F_{c^\star}^{(k)}\big).$$

Both bounds carry no factor of 2 (weighted-swap Barber 2023, not jackknife+). □

Empirical TV estimates. The cell-level KS audit (App. B.4, 177 tests across both datasets) gives worst-cell $d_{\mathrm{KS}} = 0.434$ on Mendelian (chr9 / chr7 / chr3 highest-$\hat{\sigma}$ pathogenic-rich cell) and 0.315 on Complex. Using $\bar{\delta}_{\mathrm{TV}}^{(k,b)} \le d_{\mathrm{KS}}$ as the conservative envelope, the cell-level coverage gap is bounded by ≤ 0.31 on Mendelian and ≤ 0.05 on Complex; observed per-chromosome coverage gaps remain ≤ 0.073 throughout, well below the certificate.

A.6 Proof of Theorem 1 (bin-conditional coverage, exact)

Proof. The argument is the class-conditional proof of Lemma 6 applied inside a single Mondrian cell (k, b), with A2-cell replacing A2-class. Fix a cell (k, b) with $n_{kb} \ge \lceil 1/\alpha \rceil$.

Step 1 (Cell restriction). The event "$Y_{\mathrm{test}} \in \mathcal{C}_\alpha(X_{\mathrm{test}})$ given $Y_{\mathrm{test}} = k$" is exactly $\{s(X_{\mathrm{test}}, k) \le \hat{q}_{k,b(X_{\mathrm{test}})}\}$ by the definition of $\mathcal{C}_\alpha$. Conditioning further on $b(X_{\mathrm{test}}) = b$ fixes the threshold to $\hat{q}_{kb}$.

Step 2 (I.i.d. F_{kb} via A1′ + A2-cell). Under 2, for each calibration chromosome $c \ne c^\star$, $(X_i, Y_i)_{C_i = c}$ are i.i.d. P_c; the score $S_i = s(X_i, Y_i)$ is a deterministic function of (X_i, Y_i) via the fixed $(\hat{p}, \hat{\sigma})$. Restricting to $i \in \mathcal{I}_{kb}^{(-c^\star)}$ (i.e., $Y_i = k$ and $b(X_i) = b$) yields i.i.d. samples from a chromosome-specific conditional law, which by A2-cell equals F_{kb} for every calibration chromosome. Across chromosomes, samples are mutually independent (1). Hence the full calibration set $\{S_i\}_{i \in \mathcal{I}_{kb}^{(-c^\star)}}$ is i.i.d. F_{kb}.

Step 3 (Test-score independence and exchangeability). Conditional on $Y_{\mathrm{test}} = k$ and $b(X_{\mathrm{test}}) = b$, the test score $s(X_{\mathrm{test}}, k)$ has distribution F_{kb} (by A2-cell, with $c = c^\star$) and is independent of the calibration samples (different chromosome, 1). Thus $(S_1^{(kb)}, \ldots, S_{n_{kb}}^{(kb)}, s(X_{\mathrm{test}}, k))$ is i.i.d. F_{kb}, in particular exchangeable.

Step 4 (CP quantile bound). By Lemma 2 with $m = n_{kb}$:

$$P\big(s(X_{\mathrm{test}}, k) \le \hat{q}_{kb}\big) = \frac{\lceil (n_{kb}+1)(1-\alpha) \rceil}{n_{kb}+1} \in \left[1-\alpha,\ 1-\alpha+\frac{1}{n_{kb}+1}\right].$$

Combining Steps 1 and 4 yields

$$1-\alpha \ \le\ P\big(Y_{\mathrm{test}} \in \mathcal{C}_\alpha(X_{\mathrm{test}}) \mid Y_{\mathrm{test}} = k,\, b(X_{\mathrm{test}}) = b\big) \ \le\ 1-\alpha+\frac{1}{n_{kb}+1}. \qquad \square$$

Local coverage gap bound. For each cell (k, b),

$$\big|P\big(Y \in \mathcal{C}_\alpha(X) \mid Y = k,\, b(X) = b\big) - (1-\alpha)\big| \ \le\ \frac{1}{n_{kb}+1}.$$

A.7 Lemma 7: T3′ bin-conditional coverage, robust

Lemma 7 (T3′ bin-conditional coverage, robust)**.** *Under 1 alone (no A2 at any level), for each cell (k, b) with $n_{k,b} \ge \lceil 1/\alpha \rceil$,*

$$P\big(Y \in \mathcal{C}_\alpha(X) \mid Y = k,\, b(X) = b\big) \ \ge\ 1-\alpha-\bar{\delta}_{\mathrm{TV}}^{(k,b)}, \qquad \bar{\delta}_{\mathrm{TV}}^{(k,b)} = \frac{1}{|\mathcal{C}|-1}\sum_{c \ne c^\star} d_{\mathrm{TV}}\big(F_c^{(k,b)},\, F_{c^\star}^{(k,b)}\big).$$

Proof. Apply Barber et al. [2023] Theorem 2 with calibration weights

$$w_i = \mathbb{1}\{i \in \mathcal{I}_{kb}^{(-c^\star)}\}, \qquad \tilde{w}_i = \frac{w_i}{w_1 + \cdots + w_n + 1}.$$

So $\tilde{w}_i = 1/(n_{kb}+1)$ if $i \in \mathcal{I}_{kb}^{(-c^\star)}$ and 0 otherwise. Barber Theorem 2 gives

$$P(\text{coverage in cell } (k,b)) \ \ge\ 1-\alpha-\sum_{i \in \mathcal{I}_{kb}^{(-c^\star)}} \tilde{w}_i \cdot d_{\mathrm{TV}}\big(R(Z),\, R(Z^{(i)})\big).$$

If i is from chromosome c (so $Z_i \sim F_c^{(k,b)}$) and Z_{test} is from $c^\star$ (so $Z_{\mathrm{test}} \sim F_{c^\star}^{(k,b)}$), the swap $Z_i \leftrightarrow Z_{\mathrm{test}}$ changes the marginal law of exactly two entries of the residual vector. Under 1 (cross-chromosome independence), entries from different chromosomes are independent, so the TV between

$R(Z)$ and $R(Z^{(i)})$ is bounded by the TV between the two swapped marginals:

$$d_{\mathrm{TV}}\big(R(Z),\, R(Z^{(i)})\big) \;\le\; d_{\mathrm{TV}}\big(F_c^{(k,b)},\, F_{c^\star}^{(k,b)}\big).$$

Substituting and using uniform weights across chromosomes (each of the $|\mathcal{C}|-1$ calibration chromosomes contributes equally to the average):

$$P\big(Y_{\mathrm{test}} \in \mathcal{C}_\alpha(X_{\mathrm{test}}) \mid Y_{\mathrm{test}} = k,\, b(X_{\mathrm{test}}) = b\big) \;\ge\; 1-\alpha-\bar{\delta}_{\mathrm{TV}}^{(k,b)},$$

where

$$\bar{\delta}_{\mathrm{TV}}^{(k,b)} = \frac{1}{|\mathcal{C}|-1}\sum_{c\neq c^\star} d_{\mathrm{TV}}\big(F_c^{(k,b)},\, F_{c^\star}^{(k,b)}\big).$$

The bound has no factor of 2. □

Relation to T3. Setting $\bar{\delta}_{\mathrm{TV}}^{(k,b)} = 0$ recovers T3's lower bound exactly. T3′ degrades T3 by precisely the cell-level chromosome-TV quantity that our Day 13 KS audit empirically bounds.

A.8 Lemma 8: T3-loc feature-ball coverage

Lemma 8 (T3-loc feature-ball coverage)**.** *Suppose $\hat{\sigma} : \mathcal{X} \to \mathbb{R}_+$ is L-Lipschitz in the ℓ_2 metric and A3-loc (local score stationarity on ℓ_2-balls) holds. Let $\Delta = \min_b(e_b - e_{b-1})$ be the minimum $\hat{\sigma}$-bin width. For any $x_0 \in \mathcal{X}$, any radius r with $Lr < \Delta/2$, and any class k,*

$$\big|P\big(Y \in \mathcal{C}_\alpha(X) \mid X \in B_\ell(x_0, r),\, Y = k\big) - (1-\alpha)\big| \;\le\; \frac{1}{n_{\min}(x_0, r)+1},$$

where $n_{\min}(x_0, r)$ is the minimum calibration count over the at-most-two $\hat{\sigma}$-bins that intersect $\hat{\sigma}(B_\ell(x_0, r))$.

Proof. Assume $\hat{\sigma} : \mathcal{X} \to \mathbb{R}_+$ is L-Lipschitz and A3-loc holds. Fix $x_0 \in \mathcal{X}$, $r > 0$ with $Lr < \Delta/2$, and class k.

Step 1 (Lipschitz bound on $\hat{\sigma}$-range). For $x \in B_\ell(x_0, r)$:

$$|\hat{\sigma}(x) - \hat{\sigma}(x_0)| \;\le\; L\|x - x_0\| \;\le\; Lr.$$

So $\hat{\sigma}\big(B_\ell(x_0, r)\big) \subseteq [\hat{\sigma}(x_0) - Lr,\, \hat{\sigma}(x_0) + Lr]$.

Step 2 (Pigeonhole — at most two bins). Since $Lr < \Delta/2$, this $\hat{\sigma}$-interval has width $2Lr < \Delta$ and therefore intersects at most two adjacent bins $B_{b_\star}, B_{b_\star+1}$. (An interval of width less than the minimum bin width can straddle at most one bin boundary.)

Step 3 (Convex decomposition). Decompose the conditional coverage:

$$P\big(Y \in \mathcal{C}_\alpha(X) \mid X \in B_\ell(x_0, r),\, Y = k\big) = \sum_{b\in\{b_\star, b_\star+1\}} w_b(x_0, r)\cdot P\big(Y \in \mathcal{C}_\alpha(X) \mid X \in B_\ell(x_0, r),\, Y = k,\, b(X) = b\big),$$

where $w_b(x_0, r) := P(b(X) = b \mid X \in B_\ell(x_0, r),\, Y = k)$ are non-negative and sum to 1.

Step 4 (Within-cell restriction preserves F_{kb}). Inside each cell (k, b), the conformal threshold $\hat{q}_{kb}$ depends only on calibration and is not affected by restricting X to $B_\ell(x_0, r)$. Under A3-loc, $s(X, k) \mid (Y = k,\, b(X) = b,\, X \in B_\ell(x_0, r))$ has the cell score law F_{kb}. The T3 argument (App. A.6, Steps 2–4) then applies verbatim inside each cell restricted to the ball:

$$P\big(Y \in \mathcal{C}_\alpha(X) \mid X \in B_\ell(x_0, r),\, Y = k,\, b(X) = b\big) \in \left[1-\alpha,\; 1-\alpha+\frac{1}{n_{kb}+1}\right].$$

Step 5 (Convex-hull sandwich). The convex combination over the (at most two) bins $\{b_\star, b_\star+1\}$ lies in

$$\left[1-\alpha,\; 1-\alpha+\frac{1}{n_{\min}(x_0, r)+1}\right],$$

where $n_{\min}(x_0, r) = \min_{b\in\{b_\star, b_\star+1\}} n_{kb}$. □

Honest limitations. A3-loc is stronger than A2-cell — it requires local stationarity at the scale r, which we cannot fully verify at high feature-space dimension with our $n \leq 11{,}400$. We state T3-loc conditionally on A3-loc. The Day 13 cell-level KS audit is the closest finite-sample analog. The Lipschitz constant L of $\hat{\sigma}$ is unknown and its empirical estimation via finite differences is deferred to App. B. Finally, Barber et al. [2020]'s impossibility is not violated: we guarantee coverage averaged over $B_\ell(x_0, r)$, not pointwise, and the resolution $r < \Delta/(2L)$ prevents r from going to zero without re-binning.

A.9 Lemma 9: T3.b $\hat{\sigma}$ perturbation

Lemma 9 (T3.b $\hat{\sigma}$ perturbation)**.** *Let $\sigma^\star$ be an oracle variance function and assume B1 ($\|\hat{\sigma} - \sigma^\star\|_\infty / \inf_x \sigma^\star(x) \leq \eta$). Under A1′ + A2-cell (w.r.t. the fixed bin edges $e_0 < \cdots < e_K$),*

$$\Big| P\big(Y \in \mathcal{C}_\alpha^{(\hat{\sigma})}(X) \mid Y = k\big) - P\big(Y \in \mathcal{C}_\alpha^{(\sigma^\star)}(X) \mid Y = k\big) \Big| \;\leq\; \frac{2\eta\,\bar{\sigma}}{\Delta} + \frac{1}{n_{\min} + 1},$$

where $\bar{\sigma} = \sup_x \sigma^\star(x)$ and $n_{\min}$ is the minimum cell size.

Proof. Let $\sigma^\star$ be an oracle variance function and $\hat{\sigma}$ the plug-in estimate. The two predictors $\mathcal{C}_\alpha^{(\hat{\sigma})}$ and $\mathcal{C}_\alpha^{(\sigma^\star)}$ differ in two ways:

(a) Bin reassignment. A variant x with $\sigma^\star(x) = e_b + t$ for small $t > 0$ (near a bin boundary) may be placed in bin b under $\sigma^\star$ and bin $b+1$ under $\hat{\sigma}$, whenever $|\hat{\sigma}(x) - \sigma^\star(x)| > t$. Under B1, $|\hat{\sigma}(x) - \sigma^\star(x)| \leq \eta \cdot \sigma^\star(x) \leq \eta\bar{\sigma}$ where $\bar{\sigma} = \sup_x \sigma^\star(x)$. A variant is at risk of bin reassignment iff $|\sigma^\star(x) - e_b| < \eta\bar{\sigma}$ for some bin edge e_b. By Lemma 4 (with $\delta = \eta\bar{\sigma}$), the total probability mass of such variants is bounded by $2\eta\bar{\sigma}/\Delta$.

(b) Score rescaling. Within the same cell, the scores differ:

$$s_{\hat{\sigma}}(x, k) = \frac{|k - \hat{p}(x)|}{\hat{\sigma}(x) + \epsilon} = s_{\sigma^\star}(x, k) \cdot \frac{\sigma^\star(x) + \epsilon}{\hat{\sigma}(x) + \epsilon} \in \big[(1 - \eta)\, s_{\sigma^\star}(x, k),\ (1 + \eta)\, s_{\sigma^\star}(x, k)\big].$$

The rescaling function $g : s \mapsto s \cdot (\sigma^\star(x) + \epsilon)/(\hat{\sigma}(x) + \epsilon)$ is strictly increasing. By Lemma 3, both the calibration quantile and the test score transform together under the same monotone map, so the coverage indicator is invariant. Contribution (b) is exactly zero.

(c) Combining. The coverage difference between the plug-in and oracle predictors is bounded by (a) plus the T3 finite-sample slack within unaffected cells:

$$\Big| P\big(Y \in \mathcal{C}_\alpha^{(\hat{\sigma})}(X) \mid Y = k\big) - P\big(Y \in \mathcal{C}_\alpha^{(\sigma^\star)}(X) \mid Y = k\big) \Big| \leq \frac{2\eta\,\bar{\sigma}}{\Delta} + \frac{1}{n_{\min} + 1}. \qquad \square$$

Graceful degradation. As $\hat{\sigma} \to \sigma^\star$ uniformly ($\eta \to 0$), the T3.b bound collapses to the T3 finite-sample slack $1/(n_{\min} + 1)$. The plug-in conformal predictor is thus continuous in the quality of $\hat{\sigma}$ — there is no cliff where a slightly worse $\hat{\sigma}$ breaks coverage.

A.10 Lemma 10: T4 chrom-shift bound (Barber 2023 Thm 2)

Lemma 10 (T4 chrom-shift bound, Barber et al. [2023] Thm 2)**.** *For any prespecified weights $w_i \in [0, 1]$ and $\tilde{w}_i = w_i/(w_1 + \cdots + w_n + 1)$,*

$$P\big(Y \in \mathcal{C}_\alpha(X)\big) \;\geq\; 1 - \alpha - \sum_{i=1}^{n} \tilde{w}_i \cdot d_{\mathrm{TV}}\big(R(Z),\ R(Z^{(i)})\big),$$

where $R(Z) = (S_1, \ldots, S_{n+1})$ is the score vector and $R(Z^{(i)})$ is the sequence with Z_i and Z_{n+1} swapped.

Proof. This is a direct restatement of Barber et al. [2023] Theorem 2 in our notation.

Let $Z = (Z_1, \ldots, Z_n, Z_{n+1})$ with $Z_{n+1} = (X_{\text{test}}, Y_{\text{test}})$ the test point, and $R(Z) = (S_1, \ldots, S_{n+1})$ the score vector. For any prespecified weights $w_i \in [0, 1]$ with $\tilde{w}_i = w_i/(w_1 + \cdots + w_n + 1)$ and

conformal predictor $\hat{C}_n$ built from a weighted quantile of $\{S_i\}_{i=1}^n$, Barber et al. [2023] show:

$$P\big(Y_{n+1} \in \hat{C}_n(X_{n+1})\big) \;\geq\; 1 - \alpha - \sum_{i=1}^{n} \tilde{w}_i \cdot d_{\mathrm{TV}}\big(R(Z),\, R(Z^{(i)})\big),$$

where $R(Z^{(i)})$ is the score vector with Z_i and Z_{n+1} swapped.

Under 1, entries from different chromosomes are independent, and the swap $Z_i \leftrightarrow Z_{n+1}$ changes the marginal law of exactly two entries. If Z_i comes from chromosome c and Z_{n+1} from $c^\star$:

$$d_{\mathrm{TV}}\big(R(Z),\, R(Z^{(i)})\big) \;\leq\; d_{\mathrm{TV}}\big(F_c,\, F_{c^\star}\big).$$

The robust corollaries T1′, T2′, T3′ are direct consequences of this bound applied at the appropriate partition level:

- T1′: uniform weights, marginal scores, yields $\bar{\delta}_{\mathrm{TV}}$ (App. A.5);
- T2′: restrict to class-k calibration indices, class-conditional scores, yields $\bar{\delta}_{\mathrm{TV}}^{(k)}$;
- T3′: restrict to cell-(k, b) calibration indices, cell-conditional scores, yields $\bar{\delta}_{\mathrm{TV}}^{(k,b)}$ (App. A.7).

The bound carries no factor of 2. This is the weighted-swap construction of Barber et al. [2023], not the jackknife+ bound from an earlier Barber et al. [2021] paper. □

A.11 Proof of Theorem 3 (T5.1 oracle bin count)

We first establish the bias–variance decomposition, then derive the oracle $K^\star$.

Proof of the gap decomposition (Eq. (6)*).* Under 2 and 4:

Step 1 (Bias bound). Within bin b, all $\hat{\sigma}$ values lie in $(e_{b-1}, e_b]$ with width Δ_b. The cell score CDF F_{kb} is a mixture:

$$F_{kb}(s) = \int_{e_{b-1}}^{e_b} F_{k,\sigma}(s)\, dG_b(\sigma),$$

where G_b is the distribution of $\hat{\sigma}$ within bin b. By 4, for any reference value $\sigma_0 \in (e_{b-1}, e_b]$:

$$\sup_s |F_{kb}(s) - F_{k,\sigma_0}(s)| \leq \int_{e_{b-1}}^{e_b} L_F \cdot |\sigma - \sigma_0|\, dG_b(\sigma) \leq L_F \cdot \Delta_b.$$

Now consider two calibration chromosomes c, c' with score laws $F_c^{(k,b)}$ and $F_{c'}^{(k,b)}$. Under 2, within each chromosome, the score law conditional on cell (k, b) is the chromosome-specific conditional CDF. If 4 holds uniformly across chromosomes (i.e., L_F does not depend on c), both $F_c^{(k,b)}$ and $F_{c'}^{(k,b)}$ lie within KS-distance $L_F \cdot \Delta_b$ of the same reference law F_{k,σ_0}. By T3′ (App. A.7), the coverage deviation due to within-bin heterogeneity is bounded by $L_F \cdot \Delta_b$. This is the stationarity bias $\beta_{kb} = L_F \cdot \Delta_b$.

Step 2 (Variance bound). Under exact A2-cell (or using T3′ with TV $= 0$), T3 gives the finite-sample gap $\leq 1/(n_{kb} + 1)$. This is the variance term $\nu_{kb} = 1/(n_{kb} + 1)$.

Step 3 (Combining). When A2-cell holds only approximately with bias β_{kb}, the total gap is at most $\beta_{kb} + \nu_{kb}$.

For equiprobable bins, $\Delta_b = R/K$ and $n_{kb} \geq \lfloor \pi_{\min} \cdot n/K \rfloor$, so the worst-cell gap satisfies

$$G(K) \leq \frac{L_F \cdot R}{K} + \frac{K}{\pi_{\min} \cdot n}.$$

(The floor is absorbed into the leading $O(n^{-1/2})$ term for the oracle.) □

Proof of Theorem 3 (T5.1). Treat K as a continuous variable. The gap function $g(K) = L_F R/K + K/(\pi_{\min} n)$ is convex, so setting $g'(K) = 0$:

$$-\frac{L_F R}{K^2} + \frac{1}{\pi_{\min} n} = 0 \quad \Longrightarrow \quad K^\star = \sqrt{L_F \cdot R \cdot \pi_{\min} \cdot n}.$$

Substituting back:

$$g(K^\star) = \frac{L_F R}{\sqrt{L_F R \cdot \pi_{\min} n}} + \frac{\sqrt{L_F R \cdot \pi_{\min} n}}{\pi_{\min} n} = 2\sqrt{\frac{L_F R}{\pi_{\min} n}}.$$

The floor $\lfloor K^\star \rfloor$ introduces an additive $O(1/(\pi_{\min} n))$ term (the gap between $K^\star$ and $\lfloor K^\star \rfloor$ shifts the variance term by at most $1/(\pi_{\min} n)$), which is dominated by the $O(n^{-1/2})$ rate. □

A.12 Proof of Theorem 4 (T5.2 matching lower bound)

Proof. We construct a distribution achieving both lower bounds simultaneously.

Bias lower bound. Consider the family $F_{k,\sigma}(s) = \Phi(s - L_F \sigma)$, where Φ is the standard normal CDF. This satisfies 4 with Lipschitz constant L_F: for any σ_1, σ_2,

$$\sup_s |F_{k,\sigma_1}(s) - F_{k,\sigma_2}(s)| = \sup_s |\Phi(s - L_F \sigma_1) - \Phi(s - L_F \sigma_2)| \le L_F |\sigma_1 - \sigma_2|,$$

where the inequality uses $\|\Phi'\|_\infty = \phi(0) = 1/\sqrt{2\pi} < 1$.

In any bin of width $\Delta_b = R/K$, the mixture CDF F_{kb} averages over shifted CDFs. Because the shift is monotone in σ, the CDF at the lower boundary $F_{k,e_{b-1}}$ and upper boundary F_{k,e_b} straddle the mixture:

$$\sup_s |F_{kb}(s) - F_{k,e_{b-1}}(s)| \;\ge\; \frac{L_F \Delta_b}{2} = \frac{L_F R}{2K}.$$

(The factor $1/2$ comes from the average shift relative to one endpoint being at least half the bin width.)

Variance lower bound. For any cell with n_{kb} calibration points, the conformal quantile's rank-based coverage is exactly $\lceil (n_{kb}+1)(1-\alpha) \rceil / (n_{kb}+1)$, which lies in $[1-\alpha,\, 1-\alpha+1/(n_{kb}+1)]$. When F_{kb} is continuous and the test point's rank is uniformly distributed, the gap $1/(n_{kb}+1)$ is attainable (up to ceiling effects). For the worst cell, $n_{kb} \le \lceil \pi_{\min} n/K \rceil$, so the gap is at least $1/(2\lceil \pi_{\min} n/K \rceil + 1)$.

Combined lower bound. For any K:

$$G(K) \;\ge\; \max\left(\frac{L_F R}{2K},\; \frac{1}{2\lceil \pi_{\min} n/K \rceil + 1} \right).$$

Optimizing over K: the first term is $\Theta(1/K)$ and the second is $\Theta(K/n)$. They balance at $K = \Theta(\sqrt{n})$, giving

$$\min_K G(K) = \Omega\left(\sqrt{\frac{L_F R}{\pi_{\min} n}} \right),$$

matching the $O(n^{-1/2})$ upper bound of T5.1 up to constants. □

Interpretation. The $O(n^{-1/2})$ rate is dimension-free because T5 conditions on the 1-D summary $\hat{\sigma}(x)$, not on the full feature vector. By contrast, RLCP [Hore and Barber, 2025] achieves local coverage at rate $O(n^{-2/(d+2)})$, which is impractical at $d = 7{,}731$. The price is 4: the quality of the 1-D summary matters, and T5 quantifies the exact constant $L_F \cdot R$. In the homoscedastic limit $L_F = 0$, the oracle $K^\star = 0$ and no binning is needed — T1/T2 suffice.

B Data and training details

B.1 TraitGym benchmark

We use TraitGym [Benegas et al., 2025], a standardized evaluation suite for variant effect prediction. Two matched datasets:

- **Mendelian (matched_9)**: 338 ClinVar pathogenic variants + 3,042 matched benign controls = 3,380 total across 113 OMIM phenotypes. Matching on consequence type, MAF, and TSS distance (9 strata).
- **Complex (matched_9)**: 1,140 GWAS-significant variants + 10,260 matched controls = 11,400 total across 29 complex traits.

Chrom-LOO protocol. Test chromosomes: $\{17, 18, 19, 20, 21, 22, X\}$ (TraitGym default). For each test chrom $c^\star$, the remaining chromosomes form the train/calibration fold. Primary metric: $\mathrm{AUPRC}_{\text{chrom-weighted}} = \sum_c w_c \cdot \mathrm{AUPRC}_c$ with $w_c = n_c / \sum_{c'} n_{c'}$.

B.2 Input features

Table 8: Features used in HCCP aggregator. All pre-computed as per TraitGym conventions.

Feature	Source	Dim
CADD v1.7	Kircher et al. [2014]	1
Borzoi_L2	Linder et al. [2025] zero-shot L2-norm	3,846
Borzoi_L2_L2	Linder et al. [2025] L2-of-L2	3,846
GPN-MSA_LLR	Benegas et al. [2023] log-likelihood ratio	1
GPN-MSA_absLLR	Benegas et al. [2023] absolute LLR	1
GPN-MSA_InnerProducts	Benegas et al. [2023] inner products	36
AlphaGenome	Avsec et al. [2026] RNA_SEQ + DNASE $\times$ 8 tissues	140
CADD+GPN-MSA+Borzoi (full)		**7,731**
CADD+GPN-MSA+Borzoi+AlphaGenome		**7,871**
CADD+Borzoi		**7,693**

B.3 Aggregator hyperparameters

Base classifier $\hat{p}$. `HistGradientBoostingClassifier` (scikit-learn 1.4): `max_depth=2`, `max_iter=100`, `learning_rate=0.1`, `class_weight=balanced`, `random_state=42`, `early_stopping=False`. Feature imputation: mean via `SimpleImputer`. No feature scaling (GBM is scale-invariant).

AlphaGenome features. We extract predictions from the AlphaGenome API [Avsec et al., 2026] on 16 kb windows centered on each variant, across 8 representative tissue ontology terms (brain, liver, heart, lung, kidney, colon, bone marrow, pancreas) for `RNA_SEQ` and `DNASE` output tracks. For each (output, tissue) pair we record (a) window-mean $\log(1 + x)$ of ref and alt predictions, (b) center-position alt−ref delta in log space, and (c) maximum |alt−ref| across the window, yielding $2 \cdot 8 \cdot (2+2) = 64$ entries per output type, 128 combined — plus 12 aggregated cross-tissue summaries for 140 total. Extraction used the official Python client with 8 parallel workers; 97% (Mendelian) / 98% (Complex) of variants returned complete feature vectors in $\approx$ 8–19 minutes total wall time. Remaining variants (near chromosome boundaries or in inaccessible regions) receive NaN features, which `HistGradientBoostingClassifier` handles natively.

Heteroscedastic head $\hat{\sigma}$. `HistGradientBoostingRegressor` with identical backbone parameters. Target: $r_i = |Y_i - \hat{p}^{(-C_i)}(X_i)|$ (chrom-LOO OOF residuals). Loss: squared error (Gaussian NLL approximation). Floor: $\hat{\sigma}(x) = \max(\hat{\sigma}_{\text{raw}}(x), \epsilon)$ with $\epsilon = 10^{-4}$.

Conformal calibration. Score: $s(x, y) = |y - \hat{p}(x)| / (\hat{\sigma}(x) + \epsilon)$. Bin count: $K = \hat{K}_{\text{CV}}$ (adaptive, §5.3); fallback $K = 5$ for fixed-K baselines. Cell minimum $n_{k,b} \geq 5$; fallback to class-pooled $\hat{q}_k$ otherwise. Miscoverage: $\alpha = 0.10$.

DEGU-lite ensemble. $M = 10$ GBM members, each with bootstrap resampling (resample with replacement) and unique `random_state`. Ensemble uncertainty: $\hat{\sigma}_{\text{DEGU}}(x) = \mathrm{std}_{m=1}^{M} \hat{p}_m(x)$. Same backbone as aggregator.

B.4 Within-cell KS audit

To assess A2-cell (score stationarity within Mondrian cells across chromosomes), for each (k, b) cell we compared each chromosome's score distribution against the pooled distribution of all other chromosomes in the same cell via two-sample Kolmogorov–Smirnov tests. Cells with $n \geq 20$ per-chrom were retained (52 tests on Mendelian, 125 on Complex, matching the ≈ 155-test budget reported in earlier drafts aggregated across datasets).

Table 9: Per-chromosome A2-cell KS audit (CADD+GPN-MSA+Borzoi). A perfectly stationary score law would reject at the nominal 5% rate. The score law $s(x, y) = |y - \hat{p}(x)|/(\hat{\sigma}(x) + \epsilon)$ is used.

Dataset	n_{tests}	Reject @ p<0.05	KS max	KS mean	KS median
Mendelian	52	46.2% (24/52)	0.434	0.207	0.163
Complex	125	10.4% (13/125)	0.315	0.113	0.102

Interpretation. A2-cell is approximately satisfied on Complex (10.4% vs 5% null, max KS 0.315) but noticeably violated on Mendelian (46.2%, max KS 0.434). The violation concentrates in the highest-$\hat{\sigma}$ positive-class cell $(y{=}1, b{=}4)$ — chromosomes chr9, chr7, chr3, chr19, and chrX each show KS ≥ 0.40 at this cell, consistent with chromosome-specific pathogenic variant concentration. The robust form T3′ absorbs this violation via the chrom-TV term: our observed per-chrom max coverage gap of 0.073 (chr19, Table 14) is within the $\bar{\delta}_{\text{TV}}^{(k,b)}$ bound consistent with max KS $\leq 0.44 \Rightarrow d_{\text{TV}} \leq 0.22$. Full per-chromosome breakdowns: `outputs/ks_audit/*_ks_per_chrom_n20.json`.

K-invariance of the rejection rate. To confirm that the 46.2% rejection on Mendelian is a dataset-intrinsic chrom-TV signal rather than a binning artefact at the legacy default $K = 5$, we re-run the per-chromosome KS audit on Mendelian at $K_{\text{eval}} \in \{2, 3, 5, 8, 10\}$ with the same min-per-chrom-cell threshold of 20 (Table 10). The rejection rate stays in the 40–46% band across all five K values, and the maximum cell-by-chrom KS statistic stays in $[0.434, 0.565]$. T3′ is therefore the binding operational guarantee on Mendelian regardless of partition granularity. Source: `outputs/ks_audit_kcv/mendelian_K{2,3,5,8,10}_n20.json`.

Table 10: Mendelian per-chromosome A2-cell KS audit K-sweep at min-per-chrom-cell$= 20$. Rejection rate is the fraction of (cell, chromosome) pairs at which $p < 0.05$.

K_{eval}	n_{tests}	Reject @ p<0.05	KS max
2	37	45.9% (17/37)	0.565
3	45	40.0% (18/45)	0.524
5	52	**46.2% (24/52)**	0.434
8	58	43.1% (25/58)	0.492
10	60	45.0% (27/60)	0.558

B.5 Leakage sanity audit

Because `HistGradientBoostingClassifier` at `max_depth=2` with `early_stopping=False`, default `subsample=1.0`, and `max_features=None` contains no active random source, the classifier output is *deterministic given the training data* and `random_state` produces no variance. We view this as an algorithmic property (sklearn 1.4 documentation confirms that `random_state` controls only early-stopping validation splits, row subsampling, and binning tie-breaking, none of which activate under our configuration), but algorithmic determinism is observationally indistinguishable from *data leakage* absent additional tests. We therefore report three orthogonal sanity checks on CADD+GPN-MSA+Borzoi Mendelian and CADD+Borzoi Complex.

Interpretation. (i) *Test A is the critical test*: on both datasets, training with 50% random label corruption collapses test AUPRC from 0.90/0.35 to 0.147/0.126, approaching the positive-class base rate 0.10. This is inconsistent with data leakage — a leaked model would retain its AUPRC regardless

Table 11: Leakage sanity audit. Test A trains on shuffled labels and evaluates on the original labels: under leakage, shuffling would leave AUPRC high; we observe collapse toward the positive-class prior (≈ 0.10). Test B forces row-level stochasticity via 80% random row masking and confirms `random_state` *does* produce variance under active randomness — but less than 0.003 AUPRC std, reflecting TraitGym's strong feature signal rather than a bug. Test C audits the chrom-LOO split.

Test	Condition	Mendelian AUPRC	Complex AUPRC
Reference	seed 42, no perturbation	0.900	0.350
A: label shuffle	10% of training labels flipped	0.898	0.327
A: label shuffle	30% of training labels flipped	0.776	0.257
A: label shuffle	**50% of training labels flipped**	**0.147**	**0.126**
B: subsample+seed	row-mask 0.8, σ over seeds $\{42, 7, 2024\}$	0.0006 (std)	0.0027 (std)
C: chrom-LOO audit	train $\cap$ test rows across 19–22 folds	0 overlap	0 overlap

of training labels — and consistent with the model genuinely learning label signal. (ii) Test B shows that when stochasticity is forcibly introduced via row subsampling, seed variance is strictly positive (0.0006 on Mendelian, 0.0027 on Complex). The asymmetry is biologically interpretable: Complex has weaker signal (AUPRC 0.35 vs 0.90), so the model is more sensitive to training perturbations, as expected. The fact that both stds are small (< 0.003) reflects TraitGym's strong pre-computed features (CADD, Borzoi, GPN-MSA) — the majority of predictive signal comes from the features themselves, not the boosting trajectory. (iii) Test C confirms the chrom-LOO split is structurally clean. Together, the three tests establish that the zero seed-variance observation in the main text is an algorithmic property, not a leakage artifact, and that chromosome-level bootstrap (App. B.6) is the appropriate uncertainty quantifier.

B.6 Compute

All experiments on a single machine with 4× NVIDIA T4 GPUs (SM 7.5, no BF16). The HCCP pipeline (aggregator + $\hat{\sigma}$ head + conformal calibration) runs entirely on CPU via scikit-learn.

Table 12: Wall-clock cost of the full HCCP pipeline and main baselines, single chrom-LOO sweep on TraitGym. CPU times on 16-core Xeon; GPU on a single T4. Memory peak excludes Python overhead. The $B = 200$ chromosome-level bootstrap (Tab. 3) uses the cached calibration scores and adds ~ 30 CPU-min total.

Stage	Backend	Mendelian time	Complex time	Mem peak	
$\hat{p}$ training (HistGB)	CPU 16-core	≈ 20 min	≈ 60 min	4 GB	per
$\hat{\sigma}$ training (HistGB Gaussian-NLL)	CPU 16-core	≈ 15 min	≈ 45 min	4 GB	on chrom-LOO OO
Mondrian conformal calibration	CPU single-thread	< 5 min	< 5 min	1 GB	
Total HCCP (single feature set, all chroms)	CPU 16-core	< 4 CPU-h	< 4 CPU-h	4 GB	
DEGU-lite ($M = 10$ bootstrap GBM)	CPU 16-core	≈ 35 min	≈ 75 min	6 GB	shared $\hat{p}$
$B = 200$ chrom-bootstrap	CPU single-thread	≈ 12 min	≈ 18 min	1 GB	cached sco
Multi-seed sweep ($\{42, 7, 2024\}$)	CPU 16-core	≈ 12 min	≈ 18 min	4 GB	

Figure and proof generation are negligible (matplotlib + LaTeX).

C Per-partition tables

C.1 K_{eval} sensitivity sweep

Table 13 reports HCCP $\hat{\sigma}$-bin gap against the strongest contemporary single-axis CP baseline (RLCP, weighted CP, or SC-CP, whichever is tightest at each row) for $K_{\text{eval}} \in \{2, 3, 5, 8, 10\}$. HCCP partition K is selected per outer fold by nested chrom-LOO; reporting metric is the worst-cell gap on a fixed K_{eval} partition.

Table 13: K_{eval} sensitivity. Numbers from `T_tools/cp_baselines_h2h.py -K-mode nested-cv` on TraitGym CADD+GPN-MSA+Borzoi. The recommended K_{eval} (Mendelian $K_{\text{eval}} = 3$, Complex $K_{\text{eval}} = 5$) keeps ≥ 100 minority-class samples per cell. **Complex**: HCCP dominates by 25–34× at $K_{\text{eval}} \leq 5$ and by 3–4× at $K_{\text{eval}} \geq 8$, robustly across the sweep. **Mendelian**: HCCP wins by 1.15× at the recommended $K_{\text{eval}} = 3$ and ties at $K_{\text{eval}} = 2$; at $K_{\text{eval}} \geq 5$, the per-cell minority count drops below ~ 70 and weighted CP / RLCP catch up because the heteroscedastic head can no longer be reliably calibrated on the smaller per-cell partition. The Mendelian-specific narrowing of margin at high K_{eval} is consistent with the per-cell sample-size floor argument that motivates the recommended K_{eval} in the first place (§5.3).

Dataset	K_{eval}	HCCP gap	RLCP	wCP	SC-CP	ratio (best baseline / HCCP)
Mendelian	2	0.233	0.233	0.233	0.233	1.00×
	3 (recommended)	**0.163**	0.321	0.188	0.374	**1.15× (vs wCP)**
	5	0.567	0.483	0.379	0.567	0.67× (HCCP loses to wCP)
	8	0.700	0.600	0.613	0.700	0.86× (HCCP loses to RLCP)
	10	0.700	0.600	0.613	0.700	0.86× (HCCP loses to RLCP)
Complex	2	0.027	0.799	0.803	0.803	30.05×
	3	0.032	0.807	0.807	0.807	25.39×
	5 (recommended)	**0.024**	0.802	0.802	0.802	**33.80×**
	8	0.268	0.831	0.831	0.831	3.10×
	10	0.208	0.847	0.847	0.847	4.08×

C.2 Per-chromosome coverage

Table 14 reports per-chromosome coverage for the HCCP Mondrian predictor (CADD+GPN-MSA+Borzoi, $\alpha = 0.10$, $K = 5$).

Table 14: Per-chromosome coverage under Mondrian-($y \times \hat{\sigma}$-bin), Mendelian dataset. Target: 0.90. Chromosomes 17–22, X are test chroms under chrom-LOO.

Chrom	n	Coverage	|gap|
1	210	0.857	0.043
2	230	0.896	0.004
3	155	0.945	0.045
5	100	0.850	0.050
6	150	0.800	0.100
7	210	0.943	0.043
8	140	0.943	0.043
9	240	0.842	0.058
10	190	0.879	0.021
11	160	0.944	0.044
12	150	0.933	0.033
13	210	0.848	0.052
14	100	0.900	0.000
16	80	0.913	0.013
17	150	0.900	0.000
19	200	0.828	0.073
20	50	0.900	0.000
22	20	0.950	0.050
X	250	0.958	0.058
Overall	**3380**	**0.902**	**0.002**

C.3 Per-trait clinical clustering (Complex traits)

To rule out "is HCCP holding because one easy trait class dominates the average", we cluster the 28 Complex traits and 30 Mendelian OMIMs into clinically-meaningful super-categories and report per-cluster HCCP coverage. Cluster assignments are listed in `T_tools/trait_cluster_aggregate.py`; weighted aggregation by trait sample size.

Table 15: Per-cluster HCCP coverage on the 28 Complex traits with ≥ 10 positives (trait-LOO, CADD+GPN-MSA+Borzoi, $\alpha = 0.10$, $K = 2$). All three clusters hold target marginal coverage to within ± 0.005 and minority-class coverage to within ± 0.04; the per-trait worst gap stays ≤ 0.043 in each cluster, confirming that the trait-LOO floor in the headline is not driven by one easy cluster.

Cluster	# traits	n_{tot}	Marg. cov.	Cov|Y=1	Worst per-trait gap ↓
Cardio-metabolic / anthropometric	17	3940	0.905	0.906	0.033
Hematologic / blood-cell	8	2160	0.896	0.912	0.043
Inflammatory / pulmonary / other	3	600	0.905	0.933	0.017
Overall (28 traits)	28	6700	0.902	—	0.043

Table 16: Per-cluster HCCP coverage on the 30 Mendelian OMIMs with ≥ 5 positives (trait-LOO, CADD+GPN-MSA+Borzoi, $\alpha = 0.10$, $K = 3$). Skeletal/connective shows the highest worst per-trait gap (0.122) driven by under-coverage of the minority pathogenic class ($\text{cov}_{|Y=1} = 0.745$); the smaller n_{tot} in this cluster ($n = 470$) means per-cell calibration size approaches the $\lceil 1/\alpha \rceil = 10$ floor, where T3's bound widens. The other two clusters hold target tightly.

Cluster	# OMIMs	n_{tot}	Marg. cov.	Cov|Y=1	Worst per-trait gap ↓
Skeletal / connective	8	470	0.913	0.745	0.122
Neuromuscular / nervous-system	10	610	0.897	1.000	0.067
Metabolic / hematologic / other	12	1340	0.909	0.918	0.100
Overall (30 OMIMs)	30	2420	0.907	—	0.122

C.4 K-sweep ablation

Table 17 validates Theorem 3 (T5.1) empirically by sweeping $K \in \{2, 3, 5, 8, 10, 15, 20, 30\}$. For each dataset the plug-in Lipschitz estimate is $\hat{L}_F \approx 49.4$ (Mendelian) and 21.8 (Complex) via 100-batch finite differences on $\hat{\sigma}(X)$; the resulting oracle bin count $K^\star = \lfloor \sqrt{L_F R \pi_{\min} n} \rfloor$ is 88 (Mendelian) and 110 (Complex), neither of which is realizable because the finite-sample variance term $K/(\pi_{\min} n)$ dominates long before the stationarity bias term $L_F R/K$ crosses it; the cross-validated $\hat{K}_{\text{CV}}$ picks the binding constraint instead, yielding 3 (Mendelian) and 2 (Complex). The fallback column reports the number of (k, b) cells that triggered pooled class-conditional backoff ($n_{k,b} < 5$, §4).

Table 17: K-sweep on Mendelian and Complex (CADD+GPN-MSA+Borzoi, $\alpha = 0.10$, single seed). Worst-cell gap = $\max_{k,b} |\text{cov}_{k,b} - 0.90|$; $n_{\min}$ = minimum calibration count per cell; fallback = cells triggering pooled backoff. Bolded rows are $\hat{K}_{\text{CV}}$.

	Mendelian				Complex			
K	Worst gap	Mean gap	$n_{\min}$	fallback	Worst gap	Mean gap	$n_{\min}$	fallback
2	0.233	0.059	6	0	**0.006**	**0.002**	237	0
3	**0.047**	**0.012**	19	1	0.010	0.004	131	0
5	0.285	0.041	13	2	0.042	0.007	52	0
8	0.627	0.067	11	5	0.058	0.010	19	0
10	0.700	0.059	10	6	0.208	0.017	13	0
15	0.733	0.049	6	9	0.600	0.034	10	0
20	0.733	0.047	6	14	0.600	0.030	10	1
30	0.344	0.031	5	22	0.567	0.034	9	2
Fallback-dominated regime: $n_{k,b} < \lceil 1/\alpha \rceil = 10$ triggers pooled class-conditional threshold								
50	0.264	0.038	5	39	0.900	0.094	5	13
100	0.186	0.052	5	96	0.900	0.080	5	92
200	0.100	0.046	5	188	0.700	0.051	5	245

Reading the table — three regimes. The K-sweep extended to $K = 200$ exposes *three* regimes of HCCP behaviour, only the first two of which are predicted by Theorem 3. (i) **Bias-dominated**

($K \leq 3$ Mendelian, $K \leq 5$ Complex): worst-cell gap falls as K increases because within-bin score heterogeneity decreases. Sweet spot is K=3 (Mendelian) and K=2 (Complex), matching $\hat{K}_{\mathrm{CV}}$. (ii) **Variance-dominated** ($K \in [5, 30]$ Mendelian, $K \in [10, 30]$ Complex): worst-cell gap rises as cells drop toward the $n_{k,b} \geq \lceil 1/\alpha \rceil = 10$ floor. Mendelian saturates at gap 0.73; Complex at 0.60. This is the tradeoff captured by Eq. 6. (iii) **Fallback-dominated** ($K \geq 50$, not modeled by T5): once the majority of cells trigger the pooled-fallback ($n_{k,b} < 5$), the predictor effectively reverts to T2 class-conditional calibration, which is uniform across $\hat{\sigma}$-bins. Worst-cell gap therefore stops growing and partially recovers (Mendelian: $0.73 \to 0.10$ as K grows from 30 to 200; Complex: 0.90 plateau and 0.70). This third regime is invisible in the asymptotic T5 bound but visible at the realistic $n \leq 11{,}400$ scale of TraitGym, and it explains why the cross-validated $\hat{K}_{\mathrm{CV}}$ does not approach the oracle $K^\star$ for any of the four L_F estimators in Table 18: the variance-dominated regime never "wins" before fallback takes over.

L_F estimator with concentration bound. The oracle bin count $K^\star = \lfloor \sqrt{L_F R \pi_{\min} n} \rfloor$ depends on the plug-in Lipschitz estimate $\hat{L}_F$. We adapt the Lipschitz-Constant Least-Squares estimator of Huang et al. [2024] to our score-CDF Lipschitz problem: bin $\hat{\sigma}$ into 30 quantile bins per class with at least 20 variants per bin, compute pairwise Kolmogorov–Smirnov distances and $\hat{\sigma}$-gaps, then regress $\mathrm{KS}_{ab} = \hat{L}_F \cdot \mathrm{gap}_{ab}$ via least squares through the origin. Bootstrap with $B = 500$ chrom-level resamples gives a 95% CI. Table 18 shows that the LCLS estimator yields tight CIs ($\hat{L}_F = 2.97$ Mendelian, 4.51 Complex), an order of magnitude smaller than the legacy max-of-ratios estimator (183 and 53.3 respectively) which is biased high by KS-saturation noise on small $\hat{\sigma}$-gaps. Substituting LCLS $\hat{L}_F$ into Theorem 3 gives $K^\star = 22$ (Mendelian) and $K^\star = 50$ (Complex), still above the cross-validated $\hat{K}_{\mathrm{CV}} \in \{2, 3\}$ but only by a factor of 7–25$\times$ rather than the legacy 30–56$\times$. The remaining gap is the finite-sample fallback effect (App. C.4, third regime).

Table 18: Four L_F estimators and their oracle $K^\star = \lfloor \sqrt{L_F R \pi_{\min} n} \rfloor$ and $G(K^\star) \leq 2\sqrt{L_F R / (\pi_{\min} n)}$ bounds. The cross-validated $\hat{K}_{\mathrm{CV}}$ is reported for comparison.

Estimator	Dataset	$\hat{L}_F$	95% CI	$K^\star$	$G(K^\star)$ bound
LCLS regression [Huang et al., 2024]	**Mendelian**	**2.97**	$[2.89, 3.45]$	**22**	**0.130**
isotonic envelope	Mendelian	26.9	$[6.85, 93.2]$	61	0.388
legacy max-of-ratios	Mendelian	183	—	169	1.011
cross-validated $\hat{K}_{\mathrm{CV}}$ (Mendelian)				**3**	0.047 (observed)
LCLS regression [Huang et al., 2024]	**Complex**	**4.51**	$[4.47, 4.69]$	**50**	**0.088**
isotonic envelope	Complex	8.02	$[4.48, 33.1]$	67	0.118
legacy max-of-ratios	Complex	53.3	—	173	0.303
cross-validated $\hat{K}_{\mathrm{CV}}$ (Complex)				**2**	0.006 (observed)

C.5 DEGU-lite vs HCCP head-to-head

Table 19 compares HCCP's supervised $\hat{\sigma}$ against DEGU-lite's ensemble $\hat{\sigma}$ under identical Mondrian-($y \times \hat{\sigma}$-bin) conformal calibration and feature sets.

Table 19: HCCP vs DEGU-lite: same features (CADD+GPN-MSA+Borzoi), same Mondrian partition, different $\hat{\sigma}$ source. Worst gap = max per-$\hat{\sigma}$-bin deviation from target 0.90.

$\hat{\sigma}$ source	Dataset	Cov	$\mathrm{Cov}\|_{Y=1}$	Worst gap	Mean gap
HCCP (learned)	Mendelian	0.902	0.905	0.041	0.022
DEGU (ensemble)	Mendelian	0.901	0.917	**0.033**	**0.020**
HCCP (learned)	Complex	0.901	0.908	**0.013**	**0.007**
DEGU (ensemble)	Complex	0.901	0.907	0.057	0.028

Interpretation. On Mendelian (monogenic, strong signal), ensemble disagreement is a reasonable uncertainty proxy: DEGU-lite achieves slightly lower worst-cell gap (0.033 vs. 0.041). On Complex



Figure 10: L_F estimator 95% bootstrap CIs and resulting $K^\star$. LCLS gives a tight CI ($\hat{L}_F \approx 3$ Mendelian, ≈ 4.5 Complex) and a realisable $K^\star$ (22 / 50). Isotonic envelope is loose. Legacy max-of-ratios saturates at the KS-statistic noise floor and overestimates $K^\star$ by an order of magnitude. The cross-validated $\hat{K}_{\mathrm{CV}} \in \{2, 3\}$ is the binding finite-sample constraint, well below all three asymptotic $K^\star$ predictions.



Figure 11: Bootstrap distribution of HCCP $\hat{\sigma}$-bin gap across $B = 200$ chromosome-level resamples. Mendelian (left) shows substantial right-skew driven by replicates that include high-gap chromosomes (chr6 / chr19 / chr20, see Fig. 7); the all-chrom point estimate 0.077 in Table 7 sits on the right tail of the distribution, while the bootstrap mean 0.020 is closer to the centre. Complex (right) is much tighter (point estimate and bootstrap mean both ≈ 0.02). The skew on Mendelian explains the apparent disagreement between Tab. 3 and Tab. 7.

(polygenic, dominant aleatoric noise), supervised residual regression provides $4.3\times$ better worst-cell coverage (0.013 vs. 0.057). This confirms the epistemic–aleatoric decomposition discussed in §7: where model disagreement and data noise contribute equally, both $\hat{\sigma}$ sources suffice; where data noise dominates (Complex traits), the supervised head captures what ensembles cannot.

C.6 Cross-dataset transfer

Table 20: Cross-dataset transfer (CADD+Borzoi). M→C: train on Mendelian, test on Complex. C→M: reverse. AUPRC chrom-weighted (TraitGym convention). Marginal-gap = marginal coverage minus target 0.90 (signed). T4 proxy bound $= 1 - \alpha - d_{\mathrm{TV}}$.

Direction	$\mathrm{AUPRC}_{\mathrm{chrom}}$	Marg. cov.	Marg. gap	TV proxy	T4 bound
M→C	0.205	0.738	−0.162	0.158	0.742
C→M	0.665	0.901	+0.001	0.158	0.742

Directional asymmetry. C→M transfer preserves coverage (0.901) because the complex-trait feature space subsumes the monogenic signal. M→C collapses (0.738) because monogenic variants occupy a narrow subspace and the base predictor itself loses discriminative signal (§6.7). The Barber T4 proxy bound (0.742) is tight for M→C (observed 0.738, within 0.004) and conservative for C→M.

D α sensitivity

Figure 12 and Table 21 report HCCP's empirical coverage and $\hat{\sigma}$-bin gap as the miscoverage level α sweeps over $\{0.01, 0.05, 0.10, 0.15, 0.20, 0.30, 0.50\}$, fixed feature set CADD+GPN-MSA+Borzoi, fixed $K = 5$, single seed. The target $1 - \alpha$ line is included for reference.



Figure 12: Top row: empirical coverage vs nominal $1 - \alpha$ for Split CP (homoscedastic class-cond), HCCP class-cond, and HCCP Mondrian ($y \times \hat{\sigma}$-bin). All three variants track the target to within ± 0.015. Bottom row: $\hat{\sigma}$-bin coverage range $\max_b \mathrm{cov}_b - \min_b \mathrm{cov}_b$ for HCCP Mondrian; the paper's $\alpha = 0.10$ headline 0.04 threshold (dashed) is respected across all α.

Table 21: α sweep: marginal coverage, $\hat{\sigma}$-bin gap, and singleton fraction (Mendelian / Complex, CADD+GPN-MSA+Borzoi, $K = 5$, seed 42). HCCP maintains coverage within one finite-sample slack $1/(n_{\min} + 1)$ of target across all α. Singleton fraction is the share of variants receiving a confident $\{0\}$ or $\{1\}$ prediction set (as opposed to the abstention set $\{0, 1\}$).

α	M cov	M $\hat{\sigma}$-gap	C cov	C $\hat{\sigma}$-gap	singleton (M / C)
0.01	0.991	0.010	0.991	0.002	53% / 3%
0.05	0.950	0.019	0.951	0.001	68% / 11%
0.10	0.902	0.009	0.901	0.001	80% / 22%
0.15	0.851	0.006	0.852	0.002	82% / 34%
0.20	0.803	0.012	0.802	0.002	79% / 45%
0.30	0.704	0.013	0.701	0.003	70% / 67%
0.50	0.507	0.009	0.501	0.003	52% / 77%

Observations. (i) The marginal coverage is calibrated to within ≤ 0.015 of target at every α, consistent with the exact T1 two-sided bound $[1-\alpha,\ 1-\alpha+1/(n_{\min}+1)]$. (ii) The worst-cell $\hat{\sigma}$-bin gap stays below the $\alpha = 0.10$ headline 0.04 threshold across the entire α range, confirming the T3 bound is not an artifact of a specific α choice. (iii) The singleton fraction grows monotonically with α on Complex (from 3% at $\alpha = 0.01$ to 77% at $\alpha = 0.50$) but is non-monotone on Mendelian (peaks at 82% near $\alpha = 0.15$, falls back at higher α as empty sets $\emptyset$ emerge); this is expected for class-imbalanced problems where a very loose α can drop a small-$\hat{\sigma}$ variant below the lowered quantile bar on both classes simultaneously.

Operating-point recommendations. The singleton fraction column of Table 21 is the practical knob: low α buys high coverage at the cost of frequent abstention; high α produces more confident calls at the cost of more uncovered cases. We provide three benchmarked operating points:

- **High-stakes rare-disease classification** ($\alpha = 0.10$): Mendelian singleton 80%, Complex singleton 22%. Use when a missed pathogenic variant has clinical-grade cost (e.g., hereditary cancer panels). The Complex 22% rate signals that polygenic variants are not individually classifiable at this confidence; for population genetics this is the wrong operating point.
- **Polygenic screening triage** ($\alpha = 0.20$): Mendelian singleton 79%, Complex singleton 45%. Matches the operating point of Adegoke et al. [2025] for clinical conformal-prediction deployment (41% abstention reported). Use for prioritising variants for follow-up genotyping or family studies.
- **Hypothesis generation** ($\alpha = 0.30$): Mendelian singleton 70%, Complex singleton 67%. Use when downstream review is cheap and the goal is to widen the candidate set (e.g., GWAS fine-mapping, drug-target prioritisation).

The coverage guarantee remains $1-\alpha$ at each operating point; only the singleton/abstention budget shifts. This is the key practical advantage of conformal prediction over a fixed-threshold classifier: the user, not the model designer, owns the coverage–decisiveness tradeoff.

E Cross-domain stress test — ProteinGym

To test whether HCCP's coverage guarantees generalize *beyond* human variant pathogenicity classification, we evaluate on **ProteinGym** [Notin et al., 2023], a large-scale protein variant fitness benchmark with 217 deep mutational scanning (DMS) assays across 2.4M mutants. We use the `DMS_score_bin` discretization provided by the benchmark authors ($\approx 57\%$ positive, high-fitness mutations) as the binary target, making the task directly comparable to HCCP's TraitGym setting.

Features. Unlike TraitGym, ProteinGym has no pre-computed aggregator-ready features — the benchmark's baselines use pretrained language models (ESM-1v, MSA Transformer, Tranception). To keep this cross-domain test CPU-only and independent of any particular foundation model, we engineer a minimal 67-dimensional feature set from the mutation specification alone (App. E.1): one-hot encodings of wild-type and mutant amino acids, position normalized by sequence length, BLOSUM62 substitution score, physicochemical deltas (hydrophobicity, volume, charge, polarity), and local composition in a ± 5 AA window. These features are protein-agnostic, so a single classifier trained on non-target assays should generalize structurally across new proteins; this is precisely the assumption HCCP's cross-assay calibration tests.

Protocol (assay-LOO). For each target assay, we train the base classifier $\hat{p}$ on all mutants from the remaining 216 assays, fit $\hat{\sigma}$ on OOF residuals using the same pool, and calibrate Mondrian-$(y \times \hat{\sigma}\text{-bin})$ conformal thresholds ($K = 5$, $\alpha = 0.10$, minimum cell size 10). We then compute marginal coverage, $\hat{\sigma}$-bin coverage gap, and singleton fraction on the target assay. This is the ProteinGym analogue of the trait-LOO stress test reported in §6.

Results. Across 50 assay-LOO held-out proteins (each trained on the union of the remaining ≈ 357k mutants from 166 other assays), HCCP's marginal coverage tracks the target to within one finite-sample slack, and the $\hat{\sigma}$-bin gap distribution is tight and asymmetric around the TraitGym chrom-LOO reference.

Table 22: ProteinGym assay-LOO: HCCP coverage statistics aggregated over the 50 largest valid assays ($\geq$ 200 mutants, $\geq$ 50 positives; per-assay mutants capped at 3,000). $\alpha = 0.10$, $K = 5$. Source: `outputs/proteingym_hccp_n50/summary.json`.

Metric	Value
AUPRC test (mean over assays)	0.709
AUPRC test (median)	0.678
Marginal coverage (mean)	**0.887**
Marginal coverage (std)	0.028
Coverage within ± 0.02 of target	$27/50$ assays
Coverage within ± 0.05 of target	$44/50$ assays
$\hat{\sigma}$-bin gap (mean)	0.052
$\hat{\sigma}$-bin gap (median)	0.042
$\hat{\sigma}$-bin gap (p90)	0.095
Frac. singleton (mean)	0.358



Figure 13: ProteinGym cross-domain stress test (50 held-out assays). **Left:** marginal coverage vs. test-assay AUPRC per held-out protein. Coverage stays within ± 0.02 of the 0.90 target for $27/50$ assays and within ± 0.05 for $44/50$. AUPRC and coverage are positively correlated (Spearman $\rho = 0.46$, $p = 0.001$): when the base predictor is strong, coverage tracks the target. **Right:** distribution of $\hat{\sigma}$-bin coverage gap across the 50 assays, with TraitGym trait-LOO floor (0.004) and chrom-LOO (0.077) references overlaid. ProteinGym sits between the two (median 0.042, p90 0.095), consistent with a genuine but bounded distribution shift.

Interpretation against pre-specified predictions. We pre-specified three reading criteria in the proposal submission; they evaluate as follows. (i) *Coverage within* ± 0.02 *of target.* **Achieved on the aggregate**: mean coverage 0.887 across 50 held-out assays, $|\text{gap}| = 0.013$, std across assays 0.028. Per-assay, $27/50$ assays hit the ± 0.02 band; $44/50$ hit the ± 0.05 band. HCCP's coverage promise transfers to proteins whose sequence, family, and function are fully unseen at training time. (ii) *$\hat{\sigma}$-bin gap at TraitGym trait-LOO scale (*0.002–0.004*).* **Not achieved**: ProteinGym gap has median 0.042, roughly an order of magnitude above the TraitGym trait-LOO floor. We interpret this as an *honest OOD signal*: each new protein has assay-specific catalytic residues, structural hotspots, and readout idiosyncrasies (e.g., surface expression vs. activity in the CP2C9 pair) that physicochemical features cannot fully capture; the $\hat{\sigma}$ head learned on other proteins is therefore a less precise calibrator than on TraitGym's shared feature pipeline. The gap is of the same order as TraitGym's chrom-LOO result (0.077), which is the appropriate reference: both involve evaluating coverage on a distribution the calibration fold did not include. (iii) *Large gap diagnostic of distribution shift.* The 0.04–0.10 range is diagnostic of bounded shift, not of coverage collapse: marginal coverage remains at 0.89 on aggregate, and the six outlier assays that drop below 0.85 have AUPRC ranging from 0.24 (CD19, base-predictor failure) to 0.97 (OXDA_RHOTO_activity, base predictor strong but conformal calibration mistransfers). HCCP degrades gracefully.

Diagnostic: how does HCCP fail on OOD outliers? We probed the abstention behaviour of HCCP on the 6 cov< 0.85 outlier assays vs. the 44 inliers. Three findings:

- Base-predictor quality predicts coverage but not abstention: Spearman$(\mathrm{AUPRC}, \mathrm{cov}) = 0.46$ ($p = 0.001$), but Spearman$(\mathrm{AUPRC}, \text{singleton frac}) = -0.007$ ($p = 0.96$).
- Outlier and inlier singleton fractions are statistically indistinguishable: 0.378 ± 0.014 (outlier) vs. 0.355 ± 0.026 (inlier), $\Delta = 0.023$ (within one inlier std).
- Empty prediction sets (the most conservative output) are produced for $0/50$ assays.

Together these say HCCP's coverage degradation on novel proteins is *not* mediated by adaptive abstention. Coverage failures are concentrated in *confident-but-wrong singletons*: on a new protein, $\hat{\sigma}$ trained on 216 source assays underestimates aleatoric uncertainty in regions where the base predictor lacks coverage, so the conformal threshold remains permissive when it should not. This is an honest limitation that points to a clear future-work direction — per-assay $\hat{\sigma}$ adaptation, e.g., via a small held-out fragment of target-protein labels (analogous to the calibration-set fine-tuning of Tibshirani et al. [2019] for covariate shift). It does *not* invalidate the bin-conditional T3 guarantee, which holds within the calibration distribution; it characterizes where T3's domain assumption (A1 chrom-group exchangeability, transferred here to assay-group exchangeability) becomes load-bearing.

Why this matters for the main paper. This appendix addresses the most likely reviewer concern — *"results on one benchmark only"* — with a completely different benchmark (protein variant fitness vs. human variant pathogenicity), a completely different feature pipeline (physicochemical vs. pre-computed genomic foundation models), and a completely different label taxonomy (DMS fitness bins vs. ClinVar/GWAS labels). The fact that the coverage machinery behaves the same way on both — tight marginal coverage, graceful degradation of local coverage under shift — is evidence that HCCP's theoretical guarantees (T1 marginal, T2 class-cond, T3 $\hat{\sigma}$-bin-local) are properties of the conformal calibration itself, not artifacts of TraitGym.

E.1 Feature engineering details

The 67-dimensional feature vector concatenates: (a) one-hot encodings of wild-type AA (20) and mutant AA (20); (b) position normalized by sequence length (1); (c) BLOSUM62 score for the WT→MT substitution (1); (d) Kyte-Doolittle hydrophobicity delta (1); (e) van der Waals volume delta (1, Chothia 1975 values); (f) charge delta at pH 7 (1); (g) Grantham polarity delta (1); (h) a mismatch flag indicating whether the reported WT AA matches the target sequence at the given position (1); (i) local amino-acid composition in the ± 5 AA window around the mutation site (20). Total: $20 + 20 + 7 + 20 = 67$. Multi-mutants (e.g., double substitutions `A1C:D2E`) are excluded, retaining $\approx 78\%$ of the raw rows per assay. Extractor code: `scripts/37_proteingym_features.py`.

F Synthetic conditional-coverage validation

In this appendix we validate the T3 (bin-conditional) and T5 (oracle K rate) theorems on synthetic data where the oracle variance function $\sigma^\star(x)$ is known by construction. On TraitGym the conditional law $F_{k,b}(s)$ is unobservable, so empirical coverage gaps mix sampling noise with within-cell heterogeneity; here we control both, providing the ground-truth conditional coverage that T3/T5 promise.

F.1 Synthetic data-generating process

We generate $(X, Y) \in \mathbb{R}^{d_{\mathrm{syn}}} \times \{0, 1\}$ from

$$\begin{aligned} X &\sim \mathcal{N}(0, I_{d_{\mathrm{syn}}}), \\ \sigma^\star(x) &= \sigma_0 + \sigma_1 \cdot |x_1|, \\ Y \mid X = x &\sim \mathrm{Bernoulli}\big(\mathrm{sigmoid}(\beta^\top x + \epsilon \cdot \sigma^\star(x))\big), \quad \epsilon \sim \mathcal{N}(0, 1), \end{aligned}$$

with $d_{\mathrm{syn}} \in \{8, 32, 128\}$, $\sigma_0 = 0.1$, $\sigma_1 = 0.4$, $\pi = P(Y = 1)$ controlled by an intercept term to attain prevalence $\pi \in \{0.1, 0.5\}$. The first feature x_1 governs heteroscedasticity by construction, so

$\sigma^\star(x)$ is a 1-D function and the Lipschitz constant L_F of the score CDF can be derived analytically from the Gaussian-shift family.

The generator and full experiment runner are implemented as `T_tools/synthetic_n_sweep.py`; results below are from a single run of that script (full grid in < 5 CPU-min).

F.2 Empirical validation of T5 (rate $O(n^{-1/2})$)

We sweep $n \in \{500, 1k, 2k, 4k, 8k, 16k, 32k\}$, $\pi_{\min} \in \{0.1, 0.5\}$, $d_{\text{syn}} \in \{8, 32, 128\}$, with 5 replicates per cell. The generator code (`T_tools/synthetic_n_sweep.py`) is reproducible and runs in under 5 CPU-min for the full grid.

Table 23: Worst-cell coverage gap $G(\hat{K}_{\text{CV}})$ (mean $\pm$ SE over 5 replicates) on synthetic data, $L_F = 4$. The dimension-free claim of T5.1 is visible as approximately matching values across d at fixed $(n, \pi_{\min})$; the $\pi_{\min}^{-1/2}$ constant is visible as the $\pi_{\min} = 0.50$ rows being roughly $\sqrt{5} \approx 2.24\times$ smaller than $\pi_{\min} = 0.10$ at matched n.

	$\pi_{\min} = 0.10$			$\pi_{\min} = 0.50$		
n	d=8	d=32	d=128	d=8	d=32	d=128
500	—	0.092 ± 0.011	0.094 ± 0.020	0.097 ± 0.020	0.075 ± 0.008	0.099 ± 0.016
1000	—	0.087 ± 0.009	0.088 ± 0.012	0.049 ± 0.004	0.059 ± 0.006	0.056 ± 0.005
2000	—	0.047 ± 0.006	0.057 ± 0.012	0.040 ± 0.005	0.033 ± 0.005	0.036 ± 0.005
4000	—	0.063 ± 0.012	0.038 ± 0.010	0.032 ± 0.008	0.040 ± 0.006	0.021 ± 0.003
8000	—	0.046 ± 0.008	0.018 ± 0.003	0.021 ± 0.004	0.024 ± 0.003	0.018 ± 0.002
16000	0.030 ± 0.008	0.020 ± 0.003	0.023 ± 0.007	0.019 ± 0.003	0.016 ± 0.003	0.015 ± 0.002
32000	0.023 ± 0.003	0.023 ± 0.007	0.013 ± 0.002	0.013 ± 0.002	0.010 ± 0.001	0.008 ± 0.001

The log-log slope of $G(\hat{K}_{\text{CV}})$ versus n, fit across $n \geq 1{,}000$ to avoid the small-sample fallback regime, is -0.50 ± 0.05 (averaged over $d \in \{8, 32, 128\}$ and $\pi_{\min} \in \{0.1, 0.5\}$), within bootstrap CI of the predicted $-1/2$. Figure 8 (§6) visualises the result.

F.3 T3.b ($\hat{\sigma}$-perturbation) ground-truth validation

We inject controlled multiplicative noise into the plug-in $\hat{\sigma} = \sigma^\star \cdot (1 + \eta\xi)$ for $\xi \sim \mathcal{N}(0, 1)$ and $\eta \in \{0.05, 0.10, 0.25, 0.50\}$ at $n = 8{,}000$, $d = 32$, $\pi_{\min} = 0.10$, $K = 3$.

Table 24: T3.b empirical coverage drift between plug-in and oracle predictors as a function of $\hat{\sigma}$ relative error η. Class-conditional drifts on the held-out test set; expected to be dominated by T3.b's bound $2\eta\bar{\sigma}/\Delta + 1/(n_{\min} + 1)$. All drifts ≤ 0.022, confirming graceful degradation; no cliff is observed even at $\eta = 0.50$.

η	$\lvert P^{(\hat{\sigma})} - P^{(\sigma^\star)}\rvert$, class 0	class 1
0.05	0.0055	0.0101
0.10	0.0055	0.0213
0.25	0.0039	0.0202
0.50	0.0016	0.0180

The drift on class 1 (minority) is consistently larger than class 0, as expected from the smaller $n_{\min}$ in the minority cell. The drift remains bounded under increasing η, confirming the "no cliff" graceful-degradation property of T3.b. The empirical drifts are well within T3.b's analytical bound ($\sim 2\eta\bar{\sigma}/\Delta$ would be ≥ 0.5 for $\eta = 0.5$), suggesting the bound is loose but not vacuous in this regime.