

QTrak API Contact Import Guide

Introduction

QTrak's Contact Import API allows you to upload contact information to QTrak using a CSV file. Requests are authenticated using an API key and submitted as `multipart/form-data`. This guide explains the required request parameters, supported responses, and provides example requests in multiple scripting languages.

Prerequisites

- A valid **QTrak API key** (provided by QTrak).
- A valid **Organization ID** (provided by QTrak).
- A **CSV file** containing the contact data to import.
 - Note: The CSV file must meet the Contact Import CSV formatting requirements before it can be processed successfully. You can download a template [here](#).
- The **Contact Settings** in QTrak are configured to match the CSV column headers. Instructions for this can be found [here](#).
- A tool capable of sending **HTTP POST multipart/form-data** requests (such as PowerShell, Bash, Python, Postman, or another HTTP client).
 - *Note: QTrak uses Postman to generate our API keys.*

Environment Endpoints

The appropriate API key and Organization ID will be provided in this file according to the initial desired endpoint. If switching from one environment to another (eg. from Staging to Production), updated information will be provided.

Method: POST

Environment	Endpoint
Production	<code>https://api.qtrak.net/prod-sec/external/contact/import</code>
Staging	<code>https://api.qtrak.net/dev-sec/external/contact/import</code>

Request Headers

Header	Required	Description	Value
x-api-key	Yes	API Authentication Key	<YOUR_API_KEY>

Content Type: `multipart/form-data`

Form Data

Parameter	Required	Description	Value
organizationID	Yes	Organization identifier	<YOUR_ORGANIZATION_ID>
csvFile	Yes	CSV file to upload	<CSV_FILE>
email	No	Email address for import notifications	<YOUR_EMAIL>

Responses

Success Response

200 OK

Returned when the CSV file is successfully received and accepted for processing.

```
JSON
{
  "success": true,
  "response": {
    "data": {
      "Message": "Contact Import File Received Successfully.",
      "UploadedFileSize": "857 Bytes"
    }
  }
}
```

```
}  
}  
}
```

Error Response

422 Unprocessable Entity

Missing Organization ID

```
JSON  
{  
  "success": false,  
  "response": "Organization ID is required."  
}
```

Invalid Organization ID

```
JSON  
{  
  "success": false,  
  "response": "Invalid Organization ID."  
}
```

403 Forbidden

Returned when the supplied API key is invalid.

```
JSON  
{  
  "success": false,  
  "response": "Invalid API key."  
}
```

Script Examples

The following examples demonstrate how to upload a contact CSV using the Contact Import API.

PowerShell

```
Shell
# Set the API endpoint URL and CSV file path
$endpointUrl = "https://api.qtrak.net/prod-sec/external/contact/import"
$csvPath = "C:\TestFolder\contacts.csv"
$APIKEY = "YOUR_API_KEY"
$ORGID = "YOUR_ORGANIZATION_ID"
$email = "test@example.com"

# Check if the CSV file exists
if (-not (Test-Path $csvPath -PathType Leaf)) {
    Write-Error "CSV file does not exist at path '$csvPath'."
    Exit 1
}

# Send the CSV file to the Contact Import API
$result = curl.exe -X POST $endpointUrl `
    -H "x-api-key:$APIKEY" `
    -F "organizationID=$ORGID" `
    -F "email=$email" `
    -F "csvFile=@$csvPath"

# Display the API response
$result
```

Bash

```
Shell
#!/bin/bash

if [ ! -f "$1" ]; then
    echo "Error: Provide input CSV file and retry."
    exit 1
fi
```

```
ORGID="YOUR_ORGANIZATION_ID"
URL="https://api.qtrak.net/prod-sec/external/contact/import"
API_KEY="YOUR_API_KEY"
EMAIL="test@example.com"

curl --location --request POST "$URL" \
  --header "x-api-key:$API_KEY" \
  --form "organizationID=$ORGID" \
  --form "email=$EMAIL" \
  --form "csvFile=@$1"
```

Python

```
Python
import sys
import requests
from pathlib import Path

if len(sys.argv) < 2:
    print("Missing input - pass the CSV file path as a command line argument.")
    sys.exit(1)

csv_path = Path(sys.argv[1])

if not csv_path.is_file():
    print(f"CSV file does not exist: {csv_path}")
    sys.exit(1)

ORGID = "YOUR_ORGANIZATION_ID"
URL = "https://api.qtrak.net/prod-sec/external/contact/import"
API_KEY = "YOUR_API_KEY"

headers = {
    "x-api-key": API_KEY
}

payload = {
    "organizationID": ORGID,
    "email": "test@example.com"
}

with open(csv_path, "rb") as csv_file:
    files = {
```

```
        "csvFile": (csv_path.name, csv_file, "text/csv")
    }

    response = requests.post(
        URL,
        headers=headers,
        data=payload,
        files=files
    )

    print(response.status_code)
    print(response.text)
```