

# Evaluation of methods for inference of ancestral recombination graphs

Débora Y. C Brandt\*, Xinzhu Wei\* and Rasmus Nielsen\*,<sup>3</sup>

\*Department of Integrative Biology and Department of Statistics, University of California Berkeley, Berkeley, CA 94720, USA

**ABSTRACT** The ancestral recombination graph (ARG) is a model that describes the genealogy of samples of DNA sequences, keeping full information of inferred coalescence, mutation, and recombination events. Recent methods have made impressive progress towards scalably estimating whole-genome genealogies. In addition to inferring the ARG, some of these methods can also provide ARGs sampled from a defined posterior distribution. Obtaining good samples of ARGs is crucial for quantifying statistical uncertainty and for the downstream processing of ARGs to estimate parameters such as effective population size, mutation rate and age of variants. Here, we use simulations to benchmark three ARG inference programs: ARGweaver, Relate and tsdate. We use neutral coalescent simulations to 1) compare the true coalescence times to the inferred times at each locus; 2) compare the distribution of coalescence times across all loci to the expected exponential distribution; 3) evaluate whether the sampled coalescence times have the properties expected of a valid posterior distribution. We found that Relate and ARGweaver estimate coalescence times at each locus that are closer to the true values than tsdate. However, all methods have biases towards overestimating small coalescence times and underestimating large ones. Bias in these methods is unsurprising since they are all Bayesian, and thus are not designed to yield unbiased estimates. Finally, ARGweaver provides a distribution of samples that is closer to the correct posterior distribution than Relate, but this accuracy comes at a substantial computational cost. We conclude that the best choice of method will depend on the number of input sequences and on the specifics of the downstream analyses.

**KEYWORDS** Ancestral recombination graph; ARGweaver; Relate; tsdate; simulation; calibration

[OBS: subtitles here are just for our reference, I don't plan to keep them all in the final version – Debora]

The ancestral recombination graph (ARG) is a model that represents the evolutionary history of a sample of DNA sequences as a set of coalescence, recombination and mu-

tation events (Griffiths and Marjoram 1997). At each given site, the genealogy can be described by the coalescent model (Kingman 1982), but because recombination breaks loci apart, the local genealogies can differ between sites. Hudson (1983) first proposed a model to combine recombination and coalescence to fully describe the genealogy of a set of samples.

doi: 10.1534/genetics.XXX.XXXXXX  
 Manuscript compiled: Tuesday 10<sup>th</sup> August, 2021  
<sup>3</sup>University of California, Berkeley Department of Integrative Biology  
 3040 Valley Life Sciences Building #3140 Berkeley, CA 94720-3140.  
 rasmus\_nielsen@berkeley.edu

## Motivation - quantify ARG uncertainty

The ARG can also be defined as a data structure. In this context, it is a lossless representation of a sample of DNA sequences. As such, the ARG fully represents all the information in a sample of DNA sequences and therefore it is necessarily more informative than any summary statistics traditionally used to learn about evolutionary processes (e.g.  $F_{ST}$ ,  $\pi$ , Tajima's D, or haplotype based ones such as EHH, etc). In other words, all traditional summary statistics can be calculated from the ARG.

One difficulty, however, is that it is impossible to know the true ARG underlying a sample, since many ARGs can be compatible with a given sample of DNA sequences. Thus, if one is interested in modelling evolutionary processes using ARGs, it is desirable to quantify the uncertainty around the inferred ARG by getting samples of ARGs according to their posterior probability, given some data. Another way to see this from a Bayesian perspective is that the true ARG underlying a sample of DNA sequences is only one instance of a random variable that was sampled from a distribution that depends on evolutionary parameters of interest (e.g. effective population size, selection, mutation and recombination rates).

Inferring full ARGs, and quantifying inference uncertainty by getting samples from their posterior distribution is a challenging problem theoretically and computationally. It requires navigating a high dimensional distribution of ARGs, which are themselves a complicated data structure. For this reason, inferring ARGs and sampling from their posterior distribution seemed like a nearly impossible endeavour some years ago, but important theoretical and methodological developments now allow us to do so. Today, many methods to estimate the ARG from a sample of DNA sequences are available. However, thus far only ARGweaver (Rasmussen *et al.* 2014) and Relate (Speidel *et al.* 2019) are able to output samples of ARGs proportionally to their posterior probability, thus accounting for inference uncertainty.

Accurate sampling from the posterior dis-

tribution is especially relevant for downstream methods that rely on importance sampling to infer evolutionary parameters from ARGs. In essence, these methods weight parameter inference under each sampled ARG by the ARG probability, and therefore require that the samples of ARGs accurately reflect their probability distribution. This type of methods can be used to infer population size history (Speidel *et al.* 2019), selection (Stern *et al.* 2019), migration, mutation and recombination rates.

Here, we first summarize the most important milestones for the development of methods for ARG inference and introduce their theoretical foundations relevant for interpreting our results. Next, we use simulations to evaluate ARG inference in three programs: ARGweaver (Rasmussen *et al.* 2014), Relate (Speidel *et al.* 2019) and tsdate (Wohns *et al.* 2021). tsdate is a more recent method that does not allow ARG sampling, but is a promising framework for it. We evaluate these programs by comparing the coalescence times between simulated and inferred ARGs.

## Milestones for the development of ARG inference methods

**SMC and SMC' models** Within the coalescent framework, the most straightforward way to include recombination is to consider it as a process of splitting lineages as one moves backwards in time (Hudson 1983; Griffiths and Marjoram 1997). One key insight for the development of methods based on the ARG was the idea that the coalescent process with recombination can also be simulated as a process that happens along a sequence (Wiuf and Hein 1999), as opposed to the formulation as a process that occurs backwards in time. In that formulation, the ARG is constructed as a sequence of local coalescent trees along a genome, separated by recombination events. At each recombination breakpoint, a new tree is formed from the immediately preceding tree. To form the next tree, first one of the branches in the current tree is detached. Next, a branch from any of the previous trees in the sequence

1 is randomly chosen. Finally, the detached  
2 branch coalesces to it.

3 To allow for more computational effi-  
4 ciency in simulating this process, it has been  
5 approximated as a Markovian process (*i.e.* a  
6 process where the next state only depends  
7 on the current state). In this approximation,  
8 when a lineage is detached from a tree at a re-  
9 combination event, it can only coalesce back  
10 to one of the other lineages present at the  
11 current tree (McVean and Cardin 2005). This  
12 model is called the Sequentially Markovian  
13 Coalescent (SMC). The SMC model has later  
14 been improved to better approximate the  
15 full coalescent with recombination. In this  
16 improved version, known as SMC', when  
17 a recombination happens, the detached lin-  
18 eage can coalesce to any branch in the cur-  
19 rent tree, including the one it was detached  
20 from. This means that some recombination  
21 events in this model do not generate a dif-  
22 ferent local coalescent tree. This apparently  
23 slight modification has been shown to sig-  
24 nificantly improve the model in terms of ap-  
25 proximation of the full coalescent (Marjoram  
26 and Wall 2006; Wilton *et al.* 2015).

27 **Li and Stephens copy model** Another  
28 model that approximated the coalescent  
29 with recombination making it more compu-  
30 tationally tractable is the Li and Stephens  
31 haplotype copying model (Li and Stephens  
32 2003). In this model, the genealogy is gen-  
33 erated by a copying process in which each  
34 new haplotype is formed by copying chunks  
35 of other haplotypes present in the sample.  
36 Errors in the copy are introduced accord-  
37 ing to the mutation rate, and changes on  
38 which haplotype to copy from are made ac-  
39 cording to the recombination rate. Similar  
40 to the SMC and SMC' models, the Li and  
41 Stephens model is not only more compu-  
42 tationally tractable for simulating data and  
43 performing MCMC, but also reproduces rel-  
44 evant properties of the full model and de-  
45 pends on the same parameters such as re-  
46 combination and mutation rates.

## Methods I'm comparing

Altogether, the formulation of the coales-  
cent with recombination as a spatial pro-  
cess along a sequence (Wiuf and Hein 1999),  
as well its simplification as a Markovian  
process in SMC (McVean and Cardin 2005)  
and SMC' (Marjoram and Wall 2006) and  
as a copying process in the Li and Stephens  
model (Li and Stephens 2003) paved the way  
to methods that are able to estimate ARGs  
for large sample sizes. Notably, ARGweaver  
(Rasmussen *et al.* 2014) is based on the SMC  
model, and Relate (Speidel *et al.* 2019) and  
tsdate (Kelleher *et al.* 2019; Wohns *et al.* 2021)  
are based on the Li and Stephens model.

## ARGweaver and time discretization + weaving

In ARGweaver, two crucial nov-  
elties further make the problem of ARG  
sampling tractable. First, discretization of  
time (such that all recombination and coa-  
lescence events are only allowed to happen  
at a discrete set of timepoints) decreases the  
size of the state space ARGs, which is oth-  
erwise infinite. Second, ARGweaver uses  
the lineage threading approach, which is a  
clever way to navigate the large state space  
of ARGs. With these key implementations,  
ARGweaver uses MCMC under the SMC or  
SMC' model to generate samples of ARGs  
from the posterior distribution.

## Relate and Li and Stephens 2003 model

Relate tackles the problem of ARG inference  
differently, dividing it in 2 steps. First, the  
Li and Stephens (Li and Stephens 2003) hap-  
lotype copying model is used to infer local  
tree topologies. Next, it uses MCMC under  
a coalescent prior to infer coalescence times  
on those local trees. Relate is able to output  
samples of coalescence times from the poste-  
rior distribution using this MCMC approach,  
but it does not generate different samples of  
ARG topologies.

## tsinfer, tsdate and the tree sequence framework

Tsdate (Wohns *et al.* 2021) is a  
method that dates tree sequences inferred by  
tsinfer (Kelleher *et al.* 2019). Like Relate, tsin-  
fer is also based on the copying process from

Li and Stephens (Li and Stephens 2003). Another key innovation of tsinfer is using the highly efficient tree sequence data structure to store sequence data and compute statistics from them. tsinfer performs inference in two steps. First, it recreates ancestral haplotypes based on allele sharing between samples. Next, it uses an HMM to infer the closest matches between ancestral haplotypes and the sampled haplotypes, using an ancestral copying process based on the Li and Stephens model (Li and Stephens 2003). This step results in the tree topology. Next, the local tree topologies inferred by tsinfer can be dated by tsdate. tsdate uses a conditional coalescent prior, where the traditional coalescent is conditioned on the number of descendants of each node on a local tree. Like ARGweaver, tsdate also uses a discretization of time to make computations more efficient.

### What we are doing here

Here, we used simulations to benchmark ARG inference in ARGweaver (Rasmussen et al. 2014), Relate (Speidel et al. 2019) and tsdate (Wohns et al. 2021). We focus mainly on ARGweaver and Relate because they inform about uncertainty in inference by allowing the user to output multiple samples from the posterior distribution. Sampling from the posterior is not currently implemented in tsdate, but we include it in this evaluation because it is a promising framework for very fast ARG inference and will likely include an option to output samples from the posterior distribution of ARGs soon.

We ran coalescent simulations on msprime (Kelleher et al. 2016) and we compared the true (simulated) ARGs to the ARGs sampled by ARGweaver and Relate and inferred by tsinfer/tsdate. We compared the ARGs based on their pairwise coalescence times, using three different types of evaluation. First, we evaluate the true pairwise coalescence time at each site to the inferred time. Second, we compared the overall distribution of pairwise coalescence times across all sites and all MCMC samples to the expected distribution. Since data was simulated under the coalescent with

recombination, and Bayesian inference was done using close approximations of the coalescent with recombination to compute the likelihood, the expected posterior distribution of coalescent times is the same as the prior, *i.e.* exponential with rate 1. Third, we used simulation based calibration (SBC) (Cook et al. 2006; Talts et al. 2020) to evaluate if the posterior distributions sampled by ARGweaver and Relate are well calibrated.

## Methods

### Simulations with msprime

We simulated tree sequences and SNP data with msprime version 0.7.4 (Kelleher et al. 2016). Unless otherwise noted, simulations were done under the standard neutral coalescent (Hudson model in msprime) and using the following parameters: 4 diploid samples (*i.e.* 8 haplotypes), effective population size of 10,000 diploids ( $2N = 20,000$ ), mutation rate and recombination rate of  $2 * 10^{-8}$  per base pair per generation and a total sequence length of 100Mb.

We varied these standard simulation scenarios in several ways: using SMC and SMC' models, different numbers of samples (4, 16, 32 and 80 haplotypes) and 10 times increased mutation to recombination ratio (both by increasing mutation rate to  $2 * 10^{-7}$ , and by decreasing recombination rate to  $2 * 10^{-9}$ ).

We ran msprime simulations using the python Application Programming Interface (API), and stored data in VCF and tree sequence format.

Next, we describe how we ran ARGweaver, Relate and tsinfer/tsdate under the simulated parameters described above. In ARGweaver and Relate, we ran 1000 MCMC iterations after burn-in and output every 10th sample, for a total of 100 MCMC samples from the posterior.

### ARGweaver

VCF files from msprime were converted to ARGweaver sites format using a custom python script. We ran ARGweaver's *arg-*



sample program to sample ARGs. This was done in parallel on twenty 5Mb segments, using the `-region` option. We used the same values used in the msprime simulations (`-mutrate` and `-recombrate 2e-8` and `-popsize 10000`) and except where otherwise noted, we ran ARGweaver using the SMC' model (`-smcprime` option). We ran ARGweaver for 1200 or 2200 iterations (`-iters`) depending on how long it took to converge. Assessment of convergence is described below. We extracted 100 MCMC samples from every 10th iteration among the last 1000 iterations (default `-sample-step 10`).

We extracted all pairwise coalescence times with the program *arg-summarize* using options `-tmrca` and `-subset`, and we used bedops (version 2.4.35 (Neph et al. 2012)) to match the times sampled by ARGweaver to the simulated ones at each sequence segment. Finally, we used a custom Python script to calculate the ranks of simulated pairwise coalescence times on ARGweaver MCMC samples per site.

### Time discretization

In ARGweaver, time is discretized such that recombination and coalescence events are only allowed to happen at a user-defined number of time points,  $K$  (default value is 20) (Rasmussen et al. 2014). These time points  $s_j$  (for  $0 \leq j \leq K-1$ ) are given by the function

$$s_j = g(j) = \frac{1}{\delta} \left\{ \exp \left[ \frac{j}{K-1} \log(1 + \delta s_{K-1}) \right] - 1 \right\} \quad (1)$$

where  $\delta$  is a parameter determining the degree of clustering of points in recent times. Small values of  $\delta$  leads to a distribution of points that is closer to uniform between 0 and  $s_{K-1}$ , and higher values increase the density of points at recent times (default value is 0.01) (Hubisz and Siepel 2020). Equation 1 determines that  $s_0$  is always 0, and  $s_{K-1}$  (or  $s_{max}$ ) is user defined in ARGweaver, with the parameter `-maxtime` (default value is 200,000).

Rounding of continuous times into these  $K$  time points is given by defining break-

points between them, such that the breakpoint between times  $s_j$  and  $s_{j+1}$  is  $s_{j+\frac{1}{2}} = g(j + \frac{1}{2})$ . All continuous values between  $s_{j-\frac{1}{2}}$  and  $s_{j+\frac{1}{2}}$  are assigned the value  $s_j$ . We note that for the first and last intervals, the values assigned ( $s_0$  and  $s_{K-1}$ ) don't correspond to a midpoint in the time interval, but rather to its minimum ( $s_0 = 0$ ) or maximum ( $s_{K-1} = s_{max}$ )

Here, we use the same time discretization bins defined by ARGweaver breakpoints ( $s_{j+\frac{1}{2}}$ ) as described above. However, we change the value assigned to times in these bins: instead of using  $s_j$ , we define  $t_j$  so that half of the probability mass on time bin  $j$  is to the left of  $t_j$ , and half is to the right of it. This step is relevant for the simulation-based calibration (see below), where we take the rank of true (simulated) coalescence times relative to the values sampled by ARGweaver. With  $s_j$ , any coalescence times in the first or last time interval from ARGweaver would not be represented by a midpoint as they are in the other intervals. We correct for that by using  $t_j$ , so that all time intervals are comparable.

Relate does not use time discretization, and tsdate uses a different discretization. Here, we apply the ARGweaver time discretization scheme to compare results among these methods.

### Relate

VCF files generated with msprime were converted to Relate haps and sample files using *RelateFileFormats -mode CovertFromVcf* and Relate's *PrepareInputFiles* script. We ran Relate mode All with the same mutation rate (`-m 2e-8`) and effective population size (`-N 20000`) used in the msprime simulations, as well as a recombination map with constant recombination rate along the genome, with the same rate used in msprime (`2e-8`).

We used Relate's *SampleBranchLengths* program to get 1000 MCMC samples of coalescence times for the local trees inferred in the previous step, with anc/mut output format (`-format a`). Similarly to ARGweaver, we also performed this step in 20 sequence

segments of 5Mb, and we thinned the results to keep only every 10th MCMC sample. Finally, we concatenated *anc* and *mut* files from all chunks and used a custom c++ script to obtain all pairwise coalescence times for the local trees and branch lengths inferred in the previous step, and to calculate the ranks of true pairwise coalescence times relative to the 100 MCMC samples.

### tsinfer and tsdate

VCF files generated by msprime were provided as input to the python API using *cyvcf2.VCF* and converted to *tsinfer samples* input object using the *add\_diploid\_sites* function described in the *tsinfer* tutorial (<https://tsinfer.readthedocs.io/en/latest/tutorial.html#reading-a-vcf>). Genealogies were inferred with *tsinfer* (version 0.2.0 (Kelleher et al. 2019)) with default settings and dated with *tsdate* (version 0.1.3 (Wohns et al. 2021)) using the same parameter values as in the simulations ( $N_e=10000$ ,  $\text{mutation\_rate}=2e-8$ ), with a prior grid with 20 timepoints.

Pairwise coalescence times were extracted from the tree sequences using functions *get\_interval()* and *tmrca()* from *tskit* (version 0.3.4 (Kelleher et al. 2018)), and coalescence times at each site were matched to the simulated ones using *bedops* (Neph et al. 2012).

### Convergence of MCMC chains

**ARGweaver** In ARGweaver, we monitored convergence by plotting likelihood per iteration and autocorrelation between consecutive samples. We chose a burn in period of 200 iterations for most scenarios, which was enough for the convergence of most ARGweaver runs, based on the visual inspection of autocorrelation and traces plots. Traces of the output statistics and autocorrelation plots from both programs are provided in Supplemental Materials .

**Relate** Relate does not output MCMC traces. Therefore, we evaluated convergence based on the repeatability of our results when running Relate multiple times for the same data, as well as running one longer chain (10 times

as long, with 10 thousand iterations). Since results didn't change between 1000 or 10,000 iterations, and neither among five repeated runs with 1000 iterations, we chose to use 1000 MCMC iterations, and, similarly to ARGweaver, we thinned down samples, taking every tenth.

### Point estimates of pairwise coalescence times

We estimated pairwise coalescence times from the MCMC samples from Relate and ARGweaver by taking the mean value of 100 samples at each site. Since *tsdate* does not have an option to output multiple samples of node times, we use its single estimate of pairwise coalescence times directly.

Mean squared error of point estimates was calculated per bin of size 0.1 of the simulated coalescence times (in units of  $2N$  generations). In each bin, we calculated the mean of the point estimates at all sites, and the mean squared error was calculated relative to that mean.

### Simulation-based calibration

To go one step further than comparing MCMC point estimates to the true simulated values, we have used a method proposed by Cook et al. (2006) and Talts et al. (2020) to assess if Bayesian methods are sampling well from the true posterior distribution. Cook et al. (2006) proposed testing this using simulations. The essential idea is that when you simulate data according to parameters sampled from the prior, and use the same data sampling distribution in the MCMC inference, then the posterior distribution should recover the prior distribution. In other words, under this condition, the posterior distribution is well calibrated by construction. Therefore, we can evaluate MCMC software by checking if their posterior distributions are well calibrated.

More specifically, Cook et al. (2006) and Talts et al. (2020) proposed that we i) generate samples of parameter values  $\theta$  (in our case, coalescence times), from their prior distribution  $P(\theta)$  (in our case, the prior comes from the full coalescent with recombination

could explain here that Relate already converges in the topology inference part and burnin is not needed to sample branch lengths?

include argw convergence in supp

include convergence diagnostic stats analyses (CODA)

process) and ii) generate data  $y$  (sequences) from the data sampling distribution  $P(y|\theta)$ , which in our case comes from adding mutations according to a certain rate on the genealogies from the coalescent with recombination. Here, all these steps were done by the simulation program msprime. Next, the simulated data and parameters are provided to the MCMC sampler (ARGweaver and Relate) for inference of the posterior distribution using the same data generating model. In our case, ARGweaver and Relate use approximations of the model (coalescent with recombination) used in the data simulations: the SMC' and the Li and Stephens models, respectively. The final step for simulation based calibration is calculating the rank of each simulated parameter value on the values sampled from the posterior by MCMC. In our case, we took 100 MCMC samples from ARGweaver and Relate thus our ranks take values from 0 to 100. Cook *et al.* (2006) and Talts *et al.* (2020) showed that if the MCMC methods are sampling from a well calibrated posterior as expected, these ranks will follow a uniform distribution.

Deviations from the uniform distribution of ranks show how the posterior is biased. For example, an excess of low and high ranks indicate that the inferred posterior distribution is underdispersed relative to the true posterior.

## Results

### **Comparison of simulated to estimated coalescence time per site**

We compared coalescence times estimated by ARGweaver, Relate and tsdate to the true values known from msprime simulations. In all three methods, estimates of coalescence time per site are biased and have low precision (Fig. 1A, 2A, 3A and S2).

Small values of coalescence times are generally overestimated, while large values tend to be underestimated (Fig S2). In ARGweaver, the first issue (overestimation of small coalescence times) seems to be more prevalent (Fig. 1A, mean square error (MSE)=0.397). In Relate, there are more sites

where coalescence times are underestimated (Fig. 2A, MSE=0.845). In tsdate, point estimates are apparently bounded to a narrow range (Fig. 3A, MSE=0.812).

For ARGweaver and Relate, these point estimates of coalescence times are the means of the samples from the posterior. As Bayesian estimates, they are not designed to be unbiased. The concept of bias itself is based on the idea that there is a true parameter value. In a Bayesian point of view, there is no one true parameter value, but a prior distribution. Therefore, it's important to keep in mind that a Bayesian estimator given by the mean of the posterior distribution has been "weighted" by the prior distribution.

In a Bayesian context, a given ARG ( $G_0$ ) can be seen as one instance of a random variable, and one could be interested in the parameters ( $\theta$ ) of the distribution from which that ARG was drawn ( $P(G|\theta)$ ). For example, one could be interested in effective population size, which is a parameter that affects the distribution of coalescence times in ARGs. In that scenario, bias in certain estimates would not be necessarily problematic if the correct distribution of coalescence times was recovered. To sum up, a Bayesian method that generates biased estimates of some parameter values may still accurately infer the posterior distribution. In the next sections, we evaluate the distribution of coalescence times from ARGweaver, Relate and tsdate.

### **Posterior distribution of coalescence times**

We simulated data under the standard coalescent model, therefore the distribution of pairwise coalescence times (in units of  $2N$  generations, where  $N$  is the diploid effective population size) follows an exponential distribution with rate parameter 1 (Fig. S3).

We compared the expected exponential distribution of coalescence times to the observed distribution of coalescence times across all sites inferred by ARGweaver, Relate and tsdate (Fig. 1D, 2D and 3D). For ARGweaver and Relate, we output 100

needs better wording

1 MCMC samples from the posterior distribution, and and plot the distribution of pairwise coalescence times across all sites and MCMC samples.

2 To facilitate visual comparison of the distributions between methods, we discretized Relate and tsdate coalescence times into the same bins as ARGweaver (Fig. 2D and 3D, see distributions without discretization in Fig. S4 and see Methods for a description of ARGweaver time discretization). Because time discretization breakpoints are regularly spaced in a log scale, we use a log scale on the x axis for better visualization.

3 Distributions of coalescence times from ARGweaver (Fig. 1D) and Relate (Fig. 2D) show an excess at low values, when compared to the expected exponential distribution. However, that bias is more pronounced in Relate than ARGweaver. In tsdate, the distribution is truncated at ??? and there is an excess of coalescence times around the mean (Fig. 3D). We note that the plots from ARGweaver and Relate are not directly comparable to those of tsdate, since there are 100 coalescence time samples at each site from the former two programs, but only one from tsdate.

### 4 **Simulation based calibration**

5 In this section, we use simulation-based calibration to evaluate whether ARGweaver and Relate are generating samples from a valid posterior distribution of ARGs (see Methods). To that end, we simulated coalescence times at multiple sites following the standard coalescent prior distribution, and we generated 100 MCMC samples from the posterior distribution using both ARGweaver and Relate. Finally, we analyse the distribution of the ranks of the simulated coalescence times relative to the 100 sampled values, at each site.

6 In the previous section, we showed that the posterior distributions of ARGweaver and Relate are similar to the theoretically expected exponential. However, in that analysis we have not evaluated the distribution of MCMC samples relative to each simulated value. The results of simulation based cali-

7 bration are informative about that, and can reveal if the posterior distribution is well calibrated around each simulated value.

8 The distribution of ranks from ARGweaver (Fig. 1G) is closer to uniform than that of Relate (Fig. 2G). Both show an excess of low and high ranks, but this excess is more pronounced in Relate. The excess of low and high ranks indicates that the sampled posterior distribution is underdispersed (Talts *et al.* 2020).

### 9 **Increased mutation to recombination ratio**

10 When inferring an ARG from sequence data, what provides information for inference is the set of mutations that cause variable sites in the sequence data. The lower the recombination rate, the longer will be the span of local trees, and more mutations will be available to provide information about each local tree. More generally, an increased mutation to recombination ratio is expected to increase the amount of information available to infer the ARG. In our standard simulations presented so far, the mutation to recombination ratio is one ( $\mu = \rho = 2 * 10^{-8}$ ), which is similar to what is observed in humans .

11 Here, we increased the simulated mutation to recombination ratio to 10, both by decreasing the recombination rate ( $\rho$ ) ten fold and also by increasing the mutation rate ( $\mu$ ) ten fold. We expected that these scenarios would improve inference of ARGs. However, for Relate the coalescence times distribution (Fig. 2E,F) showed larger skew towards lower values with increased  $\mu/\rho = 10$  than with  $\mu/\rho = 1$  (Fig 2D). The simulation based calibration remained qualitatively similar (Fig. 2G-I).

12 The results from ARGweaver with  $\mu/\rho = 10$  were more surprising, with the simulation based calibration showing a more pronounced underdispersion of the posterior distribution (Fig. 1H,I). The overall distribution of coalescence times, however, showed little change (Fig. 1E,F), and point estimates improved with increased mutation to recombination ratio (Fig. 1B,C).

13 In tsdate, both the point estimates and

REF



posterior distribution improved with increasing mutation to recombination ratio (Fig. 3), particularly with increased mutation rate, as expected.

### Number of samples

Next, we evaluate ARG inference with simulations with larger sample sizes. Our standard sample size used so far was 8 haplotypes, and here we change it to 4, 16, 32 and 80.

With a smaller sample size ( $n=4$  haplotypes), the coalescence time distribution from Relate showed an excess around the mean value (coalescence time of 1) (Fig 5F). With increasing sample sizes, it was skewed towards lower values (Fig 5G-J). Calibration of the posterior distribution remains similar with increasing sample sizes (Fig. 5K-O).

For ARGweaver, increasing sample sizes had the effect of slightly increasing the underdispersion of the posterior distribution (Fig. 4F-J,K-O). This could be caused by an MCMC mixing problem, causing the ARGweaver MCMC to not converge well with an increasing number of samples, due to an increasing number of states to explore by the algorithm.

Both the point estimates and posterior distribution of tsdate improved with increasing sample sizes (Fig. 6). This is expected from inference using the Li and Stephens copy algorithm (Li and Stephens 2003), which tends to .

### Run time

#### Standard simulations

- ARGweaver: 640.8 total hours for all chunks (34.5h per 5Mb chunk)
- Relate: 17 total hours
- tsinfer+tsdate: 4.9min (not comparable because it is not doing MCMC sampling)

### Discussion


ARG inference is both an interesting theoretical problem per se and also a useful tool

for downstream inference of particular aspects of evolutionary history, such as natural selection or population size changes. It is a hard computational problem, which requires implementing approximations of the full coalescent with recombination model. We have compared methods that use different approaches to this problem, and evaluated their accuracy using simulated data and comparisons of three aspects: 1) individual point estimates of each pairwise coalescence time; 2) the overall distribution of coalescence times across all sites; 3) the sampling of ARGs from the posterior distribution.


We found that there is a strong speed-accuracy trade-off in ARG inference. ARGweaver is performing best in our three tests: point estimates, the overall distribution of coalescence times, and the quality of sampling from the posterior. Importantly, it is also the only method that we compared that resamples both topologies and node times. This probably leads to a better exploration of ARG space and the reason why it provides better samples from the posterior. On the other hand, it also contributes to making ARGweaver much slower than the other methods and not scalable for genomewide inference of 100 or more samples, taking X days for  $n=32$  and  $l=100\text{Mb}$ .

Despite not performing as well as ARGweaver in our evaluation criteria, Relate and tsdate can be good enough for comparisons of average trees among different regions in the genome. Additionally, we showed that their inference is better with more samples, particularly in tsdate (Fig. 5,6). Because these programs are fast enough even for thousands of samples, this is an ideal scenario to use those programs.


Increasing the mutation to recombination ratio in simulations improved point estimates from ARGweaver, but did not improve posterior calibration (Fig. 1). This lack of improvement of the posterior sampling is not explained by lack of convergence (Fig. S5-S10).



**Figure 1** ARGweaver increased mutation to recombination rate. Left column (A,D,G):  $\mu = \rho = 2 * 10^{-8}$ ; middle column (B,E,H):  $\mu/\rho = 10$  decreasing recombination rate ( $\rho = 2 * 10^{-9}$ ); right column (C,F,I):  $\mu/\rho = 10$  increasing mutation rate ( $\mu = 2 * 10^{-7}$ ). (A-C) point estimates (mean of 100 MCMC iterations). Note that axes are in log scale. Mean squared error: A) 0.397 B) 0.120 C) 0.117. See Fig. S1 for this data plotted in linear axes. Diagonal line shows  $x=y$ , points show the mean inferred coalescence time across all sites within the same true coalescence time bin. (D-F) Distribution of coalescence times inferred by ARGweaver, combining all sites and MCMC samples. (G-I) Counts of ranks from simulation-based calibration. Horizontal line shows expected uniform distribution.




**Figure 2** Relate increased mutation to recombination rate. Left column:  $\mu = \rho = 2 * 10^{-8}$ ; middle column:  $\mu/\rho = 10$  decreasing recombination rate ( $\rho = 2 * 10^{-9}$ ); right column:  $\mu/\rho = 10$  increasing mutation rate ( $\mu = 2 * 10^{-7}$ ). (A-C) point estimates (mean of 100 MCMC iterations). Mean squared error calculated per simulated bin: A) 0.845, B) 0.629, C) 0.600. (D-F) Distribution of coalescence times inferred by Relate. Plots D shows the same data as in Figure S4A, using different binning. (G-I) Counts of ranks from simulation-based calibration. Horizontal line shows expected uniform distribution.




**Figure 3** tsdate increased mutation to recombination rate. Left column:  $\mu = \rho = 2 * 10^{-8}$ ; middle column:  $\mu/\rho = 10$  decreasing recombination rate ( $\rho = 2 * 10^{-9}$ ); right column:  $\mu/\rho = 10$  increasing mutation rate ( $\mu = 2 * 10^{-7}$ ). (A-C) point estimates (mean of 100 MCMC iterations). Mean squared error: A)0.812 B) 0.679 C) 1.399 (D-F) Distribution of coalescence times inferred by tsdate. Plots D shows the same data as in Figure S4B, using different binning.






**Figure 4** ARGweaver (A-E) Point estimates. Mean squared error: A) 0.419 B) 0.384 C) 0.382. (F-J) Distribution of coalescence times, (K-O) Simulation-based calibration. Note that the y axis is centralized on different values but always has the same length. (A,D,G) nsamples = 4 haplotypes (B,E,H) nsamples = 16 haplotypes (C,F,I) nsamples=32 haplotypes



**Figure 5** Relate (A-D) Point estimates. Mean squared error: A) 0.676, B) 0.844, C) . (E-H) Distribution of coalescence times, (I-L) Simulation-based calibration. (A,E,I) nsamples = 4 haplotypes (B,F,J) nsamples = 16 haplotypes (C,G,K) nsamples = 32 haplotypes (D,H,L) 80 haplotypes



**Figure 6** tsdate (A-D) Point estimates. Mean squared error: A) 0.877, B) 1.608, C) 1.606, D) 0.845. (E-H) Distribution of coalescence times. (A,E) nsamples = 4 haplotypes (B,F) nsamples = 16 haplotypes (C,G) 32 haplotypes (D,H) 80 haplotypes

## Other points for discussion

**Underestimation of coalescence times** In ARGweaver the excess of underestimated coalescence times (high ranks) could be explained by an effect of the MCMC sampler being stuck with short branches. Once one coalescence time is underestimated, all its subtrees' coalescence times will also tend to be underestimated. In short branches such as those, recombination will be less likely to occur, thus it will be relatively more difficult to sample a tree that changes a branch that was underestimated than to change a branch that was overestimated.

**Relate** only samples new local trees when there is enough discrepancy with the current local tree. Therefore, short branches, which have fewer mutations, will be sampled less frequently and this may cause biases in estimation. Similarly for old coalescence times, recombinations happening when there are few lineages left will have a lower chance of changing tree topology and will not be well sampled. (Deng et al. 2021)

## Other features of methods that we didn't explore

ARGweaver can take into account local variation in coverage, mapping quality, sequencing errors, and incorporate gt probabilities. Our simulations assume known genotypes, and no error.

We also assume the data is phased correctly.

Differences in mutation hotspots can be informed to ARGweaver and Relate. We're not using any of that.

In our standard simulations we use mutation rate equal to recombination rate, which is believed to be approximately true for humans. In reality, the average recombination rate is not distributed equally along the genome in humans and other mammals, but is concentrated in recombination hotspots. Therefore, it is possible that inference would be easier with real data, where local trees probably span longer sequences separated by recombination hotspots.

## In supplement but not yet mentioned

- point estimate plots in linear scale
- Relate sample order effect


- SMC vs. SMC' modes in ARGweaver

## Literature Cited


- Cook, S. R., A. Gelman, and D. B. Rubin, 2006 Validation of software for Bayesian models using posterior quantiles. *Journal of Computational and Graphical Statistics* **15**: 675–692.
- Deng, Y., Y. S. Song, and R. Nielsen, 2021 The distribution of waiting distances in ancestral recombination graphs. *Theoretical Population Biology* .
- Griffiths, R. C. and P. Marjoram, 1997 An Ancestral Recombination Graph. In *Progress in Population Genetics and Human Evolution, IMA Volumes in Mathematics and its Applications, vol. 87*, edited by P. Donnelly and S. Tavaré, pp. 257–270, Springer.
- Hubisz, M. and A. Siepel, 2020 Inference of Ancestral Recombination Graphs Using ARGweaver. In *Statistical Population Genomics*, edited by Julien Y. Dutheil, volume 2090, chapter 10, pp. 231–266.
- Hudson, R. R., 1983 Properties of a neutral allele model with intragenic recombination. *Theoretical Population Biology* **23**: 183–201.
- Kelleher, J., A. M. Etheridge, and G. McVean, 2016 Efficient Coalescent Simulation and Genealogical Analysis for Large Sample Sizes. *PLoS Computational Biology* **12**: 1–22.
- Kelleher, J., K. R. Thornton, J. Ashander, and P. L. Ralph, 2018 Efficient pedigree recording for fast population genetics simulation. *PLOS Computational Biology* **14**: 1–21.
- Kelleher, J., Y. Wong, A. W. Wohns, C. Fadil, P. K. Albers, *et al.*, 2019 Inferring whole-genome histories in large population datasets. *Nature Genetics* **51**: 1330–1338.
- Kingman, J. F. C., 1982 On the Genealogy of Large Populations. Technical report.
- Li, N. and M. Stephens, 2003 Modelling Linkage Disequilibrium using Single Nucleotide Polymorphism Data **2233**: 2213–2233.
- Marjoram, P. and J. D. Wall, 2006 Fast "coalescent" simulation. *BMC Genetics* **7**: 16.
- McVean, G. A. T. and N. J. Cardin, 2005 Approximating the coalescent with recombination. *Philosophical transactions of the Royal Society of London. Series B, Biological sciences* **360**: 1387–93.
- Neph, S., M. S. Kuehn, A. P. Reynolds, E. Haugen, R. E. Thurman, *et al.*, 2012 BEDOPS: high-performance genomic feature operations. *Bioinformatics* **28**: 1919–1920.
- Rasmussen, M. D., M. J. Hubisz, I. Gronau, and A. Siepel, 2014 Genome-Wide Inference of Ancestral Recombination Graphs. *PLoS Genetics* **10**.
- Speidel, L., M. Forest, S. Shi, and S. R. Myers, 2019 A method for genome-wide genealogy estimation for thousands of samples. *Nature Genetics* **51**: 1321–1329.
- Stern, A. J., P. R. Wilton, and R. Nielsen, 2019 *An approximate full-likelihood method for inferring selection and allele frequency trajectories from DNA sequence data*, volume 15.
- Talts, S., M. Betancourt, D. Simpson, A. Vehtari, and A. Gelman, 2020 Validating Bayesian Inference Algorithms with Simulation-Based Calibration. *arXiv* pp. 1–19.
- Wilton, P. R., S. Carmi, and A. Hobolth, 2015 The SMC' is a highly accurate approximation to the ancestral recombination graph. *Genetics* **200**: 343–355.
- Wiuf, C. and J. Hein, 1999 Recombination as a point process along sequences. *Theoretical Population Biology* **55**: 248–259.
- Wohns, A. W., Y. Wong, B. Jeffery, A. Akbari, S. Mallick, *et al.*, 2021 A unified genealogy of modern and ancient genomes. *bioRxiv* .




## Figures



**Figure S1** True pairwise coalescence time from msprime simulations compared to inferred coalescence time from (A) ARGweaver (B) Relate (C) tsdate. Note that axes are in linear scale. See Fig. ?? for this data plotted in logarithmic axes. Standard simulations with  $\mu=\text{rec}$  and 8 haploid samples. Diagonal line shows  $x=y$ , points show the mean inferred coalescence time across all sites within the same true coalescence time bin.




(a)




(b)

**Figure S2** Mean (a) and mean squared error (b) of estimates by ARGweaver, Relate and tsdate in each bin of size 0.1 of simulated coalescence times. These results are for standard simulations with  $n=8$  samples, mutation and recombination rates of  $2 \times 10^{-8}$ .



**Figure S3** Histogram of the distribution of coalescence times in msprime simulations. Red line show expected exponential distribution with rate 1.



(a) tsdate pmf

**Figure S4** Posterior distributions of pairwise coalescence times in Relate and tsdate without ARGweaver time discretization. (A) Relate with  $n$  equal size bins (B) tsdate with  $n$  equal size bins



Evaluating MCMC Convergence

ARGweaver

MCMC traces were obtained from ARGweaver .stats output file and plotted in R (Fig. S5, S6, S7). Autocorrelation plots were generated with the R function *acf*. Gelman-Rubin convergence statistics were generated with R package *coda* for 5 chains starting at different random ARGs for the first 5Mb of simulated sequence (Table S1, Fig. S8, S9, S10).


We verified that ARGweaver converged in all three simulation scenarios.

Table S1 Gelman-Rubin convergence diagnostic statistics


	Standard		Lower recombination		Higher mutation	
ARGweaver stats	Point est.	Upper C.I.	Point est.	Upper C.I.	Point est.	Upper C.I.
prior	1.06	1.15	1.01	1.03	1.00	1.01
prior2	1.06	1.17	1.01	1.03	1.00	1.01
likelihood	1.02	1.05	1.04	1.11	1.01	1.02
joint	1.06	1.16	1.01	1.02	1.01	1.02
recombs	1.04	1.1	1.01	1.03	1.00	1.01
noncompats	1.02	1.04	1.01	1.03	1.01	1.04
arglen	1.06	1.16	1.08	1.21	1.05	1.12
Multivariate psrf	1.15		1.1		1.05	

Relate


Relate does not output traces files like ARGweaver, so we evaluated convergence by running it 5 times and verifying that the posterior distributions of all runs were similar. We also ran Relate for 10x as many iterations, and we verified that the posterior distribution of coalescence times didn't change much.




**Figure S5** Convergence of likelihood across iterations of ARGweaver MCMC for data simulated under standard conditions. We used a burn in of 200 iterations (indicated by vertical line), and ran them for 1200 iterations in total, sampling every 10th iteration.



**Figure S6** Convergence of likelihood across iterations of ARGweaver MCMC for data simulated with ten times lower recombination rate ( $2 \times 10^{-9}$ ) than standard conditions. We used a burn in of 200 iterations (indicated by vertical line), and ran them for 1200 iterations in total, sampling every 10th iteration.



**Figure S7** Convergence of likelihood across iterations of ARGweaver MCMC for data simulated with ten times higher mutation rate ( $2 \times 10^{-7}$ ) than standard conditions. These chains took longer to converge, and we used a burn in of 1200 iterations (indicated by vertical line), and ran them for 2200 iterations in total, sampling every 10th iteration.




**Figure S8** Gelman-Rubin convergence diagnostic for data simulated under standard conditions.

### Relate sample order effect

There seems to be an effect of sample order, where coalescence times between the first samples (e.g. pairs 0-1, 0-2, 1-2 in Fig S12 and Fig ??) show a more dramatic underestimation. This sample order effect showed up in independent simulations.







**Figure S9** Gelman-Rubin convergence diagnostic for data simulated with ten times lower recombination rate ( $2 \times 10^{-9}$ ) than standard conditions.

## 1 SMC and SMC' modes in ARGweaver


2 In previous ARGweaver results, I simulated under standard Hudson coalescent, and did inference in ARGweaver under SMC' (Figs S13A, S14A). Inference looks better when simulating under SMCprime and inferring under SMCprime (Figs S13C, S14C). It is unexpected that  
 3  
 4  
 5  
 6  
 7  
 8  
 9  
 10  
 11  
 12  
 13  
 14  
 15  
 16  
 17  
 18  
 19  
 20  
 21  
 22  
 23  
 24  
 25  
 26  
 27  
 28  
 29  
 30  
 31  
 32  
 33  
 34  
 35  
 36  
 37  
 38  
 39  
 40  
 41  
 42  
 43  
 44  
 45  
 46  
 47  
 48  
 49  
 50  
 51  
 52  
 53  
 54  
 55  
 56  
 57  
 58  
 59  
 60  
 61  
 62  
 63  
 64  
 65  
 66  
 67  
 68  
 69  
 70  
 71  
 72  
 73  
 74  
 75  
 76  
 77  
 78  
 79  
 80  
 81  
 82  
 83  
 84  
 85  
 86  
 87  
 88  
 89  
 90  
 91  
 92  
 93  
 94  
 95  
 96  
 97  
 98  
 99  
 100  
 101  
 102  
 103  
 104  
 105  
 106  
 107  
 108  
 109  
 110  
 111  
 112  
 113  
 114  
 115  
 116  
 117  
 118  
 119  
 120  
 121  
 122  
 123  
 124  
 125  
 126  
 127  
 128  
 129  
 130  
 131  
 132  
 133  
 134  
 135  
 136  
 137  
 138  
 139  
 140  
 141  
 142  
 143  
 144  
 145  
 146  
 147  
 148  
 149  
 150  
 151  
 152  
 153  
 154  
 155  
 156  
 157  
 158  
 159  
 160  
 161  
 162  
 163  
 164  
 165  
 166  
 167  
 168  
 169  
 170  
 171  
 172  
 173  
 174  
 175  
 176  
 177  
 178  
 179  
 180  
 181  
 182  
 183  
 184  
 185  
 186  
 187  
 188  
 189  
 190  
 191  
 192  
 193  
 194  
 195  
 196  
 197  
 198  
 199  
 200  
 201  
 202  
 203  
 204  
 205  
 206  
 207  
 208  
 209  
 210  
 211  
 212  
 213  
 214  
 215  
 216  
 217  
 218  
 219  
 220  
 221  
 222  
 223  
 224  
 225  
 226  
 227  
 228  
 229  
 230  
 231  
 232  
 233  
 234  
 235  
 236  
 237  
 238  
 239  
 240  
 241  
 242  
 243  
 244  
 245  
 246  
 247  
 248  
 249  
 250  
 251  
 252  
 253  
 254  
 255  
 256  
 257  
 258  
 259  
 260  
 261  
 262  
 263  
 264  
 265  
 266  
 267  
 268  
 269  
 270  
 271  
 272  
 273  
 274  
 275  
 276  
 277  
 278  
 279  
 280  
 281  
 282  
 283  
 284  
 285  
 286  
 287  
 288  
 289  
 290  
 291  
 292  
 293  
 294  
 295  
 296  
 297  
 298  
 299  
 300  
 301  
 302  
 303  
 304  
 305  
 306  
 307  
 308  
 309  
 310  
 311  
 312  
 313  
 314  
 315  
 316  
 317  
 318  
 319  
 320  
 321  
 322  
 323  
 324  
 325  
 326  
 327  
 328  
 329  
 330  
 331  
 332  
 333  
 334  
 335  
 336  
 337  
 338  
 339  
 340  
 341  
 342  
 343  
 344  
 345  
 346  
 347  
 348  
 349  
 350  
 351  
 352  
 353  
 354  
 355  
 356  
 357  
 358  
 359  
 360  
 361  
 362  
 363  
 364  
 365  
 366  
 367  
 368  
 369  
 370  
 371  
 372  
 373  
 374  
 375  
 376  
 377  
 378  
 379  
 380  
 381  
 382  
 383  
 384  
 385  
 386  
 387  
 388  
 389  
 390  
 391  
 392  
 393  
 394  
 395  
 396  
 397  
 398  
 399  
 400  
 401  
 402  
 403  
 404  
 405  
 406  
 407  
 408  
 409  
 410  
 411  
 412  
 413  
 414  
 415  
 416  
 417  
 418  
 419  
 420  
 421  
 422  
 423  
 424  
 425  
 426  
 427  
 428  
 429  
 430  
 431  
 432  
 433  
 434  
 435  
 436  
 437  
 438  
 439  
 440  
 441  
 442  
 443  
 444  
 445  
 446  
 447  
 448  
 449  
 450  
 451  
 452  
 453  
 454  
 455  
 456  
 457  
 458  
 459  
 460  
 461  
 462  
 463  
 464  
 465  
 466  
 467  
 468  
 469  
 470  
 471  
 472  
 473  
 474  
 475  
 476  
 477  
 478  
 479  
 480  
 481  
 482  
 483  
 484  
 485  
 486  
 487  
 488  
 489  
 490  
 491  
 492  
 493  
 494  
 495  
 496  
 497  
 498  
 499  
 500  
 501  
 502  
 503  
 504  
 505  
 506  
 507  
 508  
 509  
 510  
 511  
 512  
 513  
 514  
 515  
 516  
 517  
 518  
 519  
 520  
 521  
 522  
 523  
 524  
 525  
 526  
 527  
 528  
 529  
 530  
 531  
 532  
 533  
 534  
 535  
 536  
 537  
 538  
 539  
 540  
 541  
 542  
 543  
 544  
 545  
 546  
 547  
 548  
 549  
 550  
 551  
 552  
 553  
 554  
 555  
 556  
 557  
 558  
 559  
 560  
 561  
 562  
 563  
 564  
 565  
 566  
 567  
 568  
 569  
 570  
 571  
 572  
 573  
 574  
 575  
 576  
 577  
 578  
 579  
 580  
 581  
 582  
 583  
 584  
 585  
 586  
 587  
 588  
 589  
 590  
 591  
 592  
 593  
 594  
 595  
 596  
 597  
 598  
 599  
 600  
 601  
 602  
 603  
 604  
 605  
 606  
 607  
 608  
 609  
 610  
 611  
 612  
 613  
 614  
 615  
 616  
 617  
 618  
 619  
 620  
 621  
 622  
 623  
 624  
 625  
 626  
 627  
 628  
 629  
 630  
 631  
 632  
 633  
 634  
 635  
 636  
 637  
 638  
 639  
 640  
 641  
 642  
 643  
 644  
 645  
 646  
 647  
 648  
 649  
 650  
 651  
 652  
 653  
 654  
 655  
 656  
 657  
 658  
 659  
 660  
 661  
 662  
 663  
 664  
 665  
 666  
 667  
 668  
 669  
 670  
 671  
 672  
 673  
 674  
 675  
 676  
 677  
 678  
 679  
 680  
 681  
 682  
 683  
 684  
 685  
 686  
 687  
 688  
 689  
 690  
 691  
 692  
 693  
 694  
 695  
 696  
 697  
 698  
 699  
 700  
 701  
 702  
 703  
 704  
 705  
 706  
 707  
 708  
 709  
 710  
 711  
 712  
 713  
 714  
 715  
 716  
 717  
 718  
 719  
 720  
 721  
 722  
 723  
 724  
 725  
 726  
 727  
 728  
 729  
 730  
 731  
 732  
 733  
 734  
 735  
 736  
 737  
 738  
 739  
 740  
 741  
 742  
 743  
 744  
 745  
 746  
 747  
 748  
 749  
 750  
 751  
 752  
 753  
 754  
 755  
 756  
 757  
 758  
 759  
 760  
 761  
 762  
 763  
 764  
 765  
 766  
 767  
 768  
 769  
 770  
 771  
 772  
 773  
 774  
 775  
 776  
 777  
 778  
 779  
 780  
 781  
 782  
 783  
 784  
 785  
 786  
 787  
 788  
 789  
 790  
 791  
 792  
 793  
 794  
 795  
 796  
 797  
 798  
 799  
 800  
 801  
 802  
 803  
 804  
 805  
 806  
 807  
 808  
 809  
 810  
 811  
 812  
 813  
 814  
 815  
 816  
 817  
 818  
 819  
 820  
 821  
 822  
 823  
 824  
 825  
 826  
 827  
 828  
 829  
 830  
 831  
 832  
 833  
 834  
 835  
 836  
 837  
 838  
 839  
 840  
 841  
 842  
 843  
 844  
 845  
 846  
 847  
 848  
 849  
 850  
 851  
 852  
 853  
 854  
 855  
 856  
 857  
 858  
 859  
 860  
 861  
 862  
 863  
 864  
 865  
 866  
 867  
 868  
 869  
 870  
 871  
 872  
 873  
 874  
 875  
 876  
 877  
 878  
 879  
 880  
 881  
 882  
 883  
 884  
 885  
 886  
 887  
 888  
 889  
 890  
 891  
 892  
 893  
 894  
 895  
 896  
 897  
 898  
 899  
 900  
 901  
 902  
 903  
 904  
 905  
 906  
 907  
 908  
 909  
 910  
 911  
 912  
 913  
 914  
 915  
 916  
 917  
 918  
 919  
 920  
 921  
 922  
 923  
 924  
 925  
 926  
 927  
 928  
 929  
 930  
 931  
 932  
 933  
 934  
 935  
 936  
 937  
 938  
 939  
 940  
 941  
 942  
 943  
 944  
 945  
 946  
 947  
 948  
 949  
 950  
 951  
 952  
 953  
 954  
 955  
 956  
 957  
 958  
 959  
 960  
 961  
 962  
 963  
 964  
 965  
 966  
 967  
 968  
 969  
 970  
 971  
 972  
 973  
 974  
 975  
 976  
 977  
 978  
 979  
 980  
 981  
 982  
 983  
 984  
 985  
 986  
 987  
 988  
 989  
 990  
 991  
 992  
 993  
 994  
 995  
 996  
 997  
 998  
 999  
 1000




**Figure S10** Gelman-Rubin convergence diagnostic for data simulated with ten times higher mutation rate ( $2 \times 10^{-7}$ ) than standard conditions.




**Figure S11** Convergence of the likelihood two ARGweaver runs for 1 chunk of 5Mb. In blue, 1000 iterations; in red, 10,000 iterations




**Figure S12** Relate sample order effect. Boxplots show quartiles and dots show means. "Simulated" is the distribution of coal times from the ARGs simulated with msprime. "Relate" is the distribution of coalescence times from Relate output (mean of 1000 MCMC samples for each site).



**(a)** Simulate Hudson, ARGweaver SMC




**(b)** Simulate SMC, ARGweaver SMC




**(c)** Simulate SMCprime, ARGweaver SMCprime


**Figure S13** Distribution of coal times



**(a)** Simulate Hudson, ARGweaver SMCprime



**(b)** Simulate SMC, ARGweaver SMC



**(c)** Simulate SMCprime, ARGweaver SMCprime

**Figure S14** Ranks