Rideshare

User

- created_at *datetime (6,0)*∗
- drivers_license_number *string (100)*
- email *string*∗ *U*
- first_name *string*∗
- id *integer (8) PK*
- last_name *string*∗
- password_digest *string*
- trips_count *integer*
- type *string*∗
- updated_at *datetime (6,0)*∗

Location

- address *string*∗ *U*
- city *string*
- created_at *datetime (6,0)*∗
- id *integer (8) PK*
- position *point*∗
- state *string (2)*∗
- updated_at *datetime (6,0)*∗

TripRequest

- created_at *datetime (6,0)*∗
- end_location_id *integer*∗ *FK*
- id *integer (8) PK*
- rider_id *integer*∗ *FK*
- start_location_id *integer*∗ *FK*
- updated_at *datetime (6,0)*∗

Vehicle

- created_at *datetime (6,0)*∗
- id *integer (8) PK*
- name *string*∗ *U*
- status *enum*∗
- updated_at *datetime (6,0)*∗

Trip

- completed_at *datetime*
- created_at *datetime (6,0)*∗
- driver_id *integer*∗ *FK*
- id *integer (8) PK*
- rating *integer*
- trip_request_id *integer (8)*∗ *FK*
- updated_at *datetime (6,0)*∗

VehicleReservation

- canceled *boolean*∗
- created_at *datetime (6,0)*∗
- ends_at *timestamptz*∗
- id *integer (8) PK*
- starts_at *timestamptz*∗
- trip_request_id *integer*∗ *FK*
- updated_at *datetime (6,0)*∗
- vehicle_id *integer*∗ *FK*

TripPosition

- created_at *datetime (6,0)*∗
- id *integer (8) PK*
- position *point*∗
- trip_id *integer (8)*∗ *FK*
- updated_at *datetime (6,0)*∗