

```

# User Model - Complete Reference & Usage Guide

**File:** `app/Models/User.php`

This model is the central authentication and RBAC entry point. It links to `person` and `employee` via natural keys.

---

### 1. Core Relations

| Method | Returns | Usage Example | Description |
|-----|-----|-----|-----|
| `person()` | `BelongsTo` | `$user->person` or `$user->person()` | Linked person record |
| `employee()` | `BelongsTo` | `$user->employee` or `$user->employee()` | Linked employee record (null if not assigned) |

---

### 2. Primary Organisation Codes (Single Value)

| Method | Returns | Usage Example | Description |
|-----|-----|-----|-----|
| `primaryBranchCode()` | `?string` | `$user->primaryBranchCode()` | Primary branch code |
| `primaryLocationCode()` | `?string` | `$user->primaryLocationCode()` | Primary location code |
| `primaryDepartmentCode()` | `?string` | `$user->primaryDepartmentCode()` | Primary department code |
| `primaryDivisionCode()` | `?string` | `$user->primaryDivisionCode()` | Primary division code |

**Accessor shortcuts (magic properties):**
```php
$user->primary_branch_code
$user->primary_location_code
$user->primary_department_code
$user->primary_division_code

```

3. All Assigned Collections (Primary + Additional)

Method	Returns	Usage Example	Description
<code>branches()</code>	<code>BelongsToMany</code>	<code>\$user-&gt;branches()-&gt;pluck('branch_code')</code>	All branches
<code>locations()</code>	<code>BelongsToMany</code>	<code>\$user-&gt;locations()-&gt;pluck('code')</code>	All locations
<code>departments()</code>	<code>BelongsToMany</code>	<code>\$user-&gt;departments()-&gt;pluck('code')</code>	All departments
<code>divisions()</code>	<code>BelongsToMany</code>	<code>\$user-&gt;divisions()-&gt;pluck('code')</code>	All divisions

Accessor shortcuts:

```

$user->all_branches // Collection of branch_codes
$user->all_locations // Collection of location codes
$user->all_departments // Collection of dept codes
$user->all_divisions // Collection of division codes

```

4. Post & Role Assignments

Method	Returns	Usage Example	Description
<code>posts()</code>	<code>HasMany</code>	<code>\$user-&gt;posts()</code>	All currently assigned posts
<code>primaryPost()</code>	<code>?string</code>	<code>\$user-&gt;primaryPost()</code>	Primary <code>post_code</code> (string)
<code>post()</code>	<code>?Post</code>	<code>\$user-&gt;post()</code>	First active Post model

5. Data Scopes (RBAC Scoping)

Method	Returns	Usage Example	Description
<code>dataScopes()</code>	<code>HasMany</code>	<code>\$user-&gt;dataScopes()</code>	Raw scopes
<code>getActiveScopes()</code>	<code>array</code>	<code>\$user-&gt;getActiveScopes()</code>	Grouped active scopes
<code>hasScope(\$type, \$value)</code>	<code>bool</code>	<code>\$user-&gt;hasScope('branch', 'BKN')</code>	Check access (true if wildcard or match)

#### Common usage:

```
// Check if user can access a specific branch
if ($user->hasScope('branch', 'BKN')) { ... }

// Get all accessible branches
$branches = $user->getActiveScopes()['branch'] ?? [];
```

## 6. Accessors (Magic Properties)

Accessor	Returns	Usage Example	Description
display_name	string	<code>\$user-&gt;display_name</code>	Person display name or username
primary_email	?string	<code>\$user-&gt;primary_email</code>	Primary email from person
primary_mobile	?string	<code>\$user-&gt;primary_mobile</code>	Primary mobile from person
official_email	?string	<code>\$user-&gt;official_email</code>	Official email from employee
official_mobile	?string	<code>\$user-&gt;official_mobile</code>	Official mobile from employee

## 7. Helper Methods

Method	Returns	Usage Example	Description
<code>isSuperAdmin()</code>	bool	<code>if (\$user-&gt;isSuperAdmin())</code>	Has super admin role
<code>isEmployee()</code>	bool	<code>if (\$user-&gt;isEmployee())</code>	Is Emp type with employee_code

## 8. Query Scopes

Scope	Usage Example	Description
<code>active()</code>	<code>User::active()-&gt;get()</code>	Active + not deleted
<code>employees()</code>	<code>User::employees()-&gt;get()</code>	Only Emp users
<code>search(\$term)</code>	<code>User::search('ashraf')-&gt;get()</code>	Search by username / person name

## Quick Reference Examples

```
$user = Auth::user();

// Basic info
echo $user->display_name;
echo $user->primary_email;

// Organisation
echo $user->primaryBranchCode();
$allBranches = $user->branches()->pluck('name');

// Posts
$primaryPost = $user->primaryPost();
$allPosts = $user->posts();

// Scopes
if ($user->hasScope('branch', 'BKN')) {
 // can access Bikaner data
}

// Full active scopes
$scopes = $user->getActiveScopes();
```

All methods are chainable where appropriate and respect soft deletes.

You can now safely use `$user->primary_branch`, `$user->post()`, `$user->hasScope(...)`, etc. in your controllers, policies, and views.