#### CSCI 4061: Unix Basics

Chris Kauffman

Last Updated: Mon Jan 25 03:18:57 PM CST 2021

# Logistics

#### Reading: Stevens and Rago

- ► Ch 1: Unix Overview
- ► Ch 2: Unix Standards (skim)
- ► Ch 7: Processes (Up Next)

#### Goals Today

- Finish C review
- Unix Basics
- Process Sys Calls

#### Assignments

- ► HW01/Lab01 up
- ▶ Due Mon 2/1
- Project 1 is coming

#### Lab01 Today

- Comments?
- Discord work alright?

# Wrap up C Programming Exercises

- ► Finish Reviewing C programs from last time
- Answer any pressing questions
- Reminder: C programming links on Canvas Homepage

#### Access to Unix Machines

Several options described in a class tutorial getting access to Unix

https://www.cs.umn.edu/~kauffman/tutorials/unix-environment

- CSE Labs
  - Via SSH
  - Via http://vole.cse.umn.edu
- ► Windows: Maybe Windows Subsystem for Linux (WSL)
- ▶ Mac OS X: No native environment, use a Virtual Machine
- Any: Install VirtualBox to host a Unix you like
- Install Native Linux or BSD: "Now you're playing with power!"

#### Unix Standards: POSIX

POSIX defines what you an plausibly expect on unix-like systems like Linux/BSD. Includes

- C libraries for system calls, standard libraries
- Basic layout of file system and naming conventions
- Some Devices such as /dev/null
- Presence of a shell and certain utilities like cat, grep, ...

#### Distinction: C Standard vs Unix Library

- ► Lots of systems have a C compiler which has the C standard library: printf(), fopen(), pow() etc.
- Unix systems have additional, separate libraries for Unix-specific stuff like read(), fork(), kill()
- Some branches of Unix have their own special, special versions of these like Linux clone()

#### Brief Tour of Unix Utilities

- ► Will discuss briefly tools that are useful for interacting with Unix in a "command shell"
- ► Shell / Terminal / Command Line / Non-graphical login, etc.
- Most of the discussion is widely applicable to any Unix system
- ▶ A few parts are specific to the **Bash** shell specifically (alternatives exist but Bash is default on many systems)


# Command Line: Basic File System Navigation

> pwd
/home/kauffman
> ls

Command	Effect
pwd	print the current directory
cd folder	change directory / folder
ls	list files in directory
cd ~	change to home directory

```
1103-F2017 aurs
                     Downloads
                               Hello.class Hello.java~
                                                         PathClassLoader.txt
                    Dropbox
                                                          public_html
4061-F2017 Desktop
                               Hello.java
                                            misc
> cd 4061-F2017
> 1s
                                          schedule.html~
                                                           schedule.org~ textbook
     lectures Makefile~
                           projects
exams
labs
      Makefile misc
                            schedule html
                                          schedule.org
                                                           svllabus
> pwd
/home/kauffman/4061-F2017
> cd lectures
> pwd
/home/kauffman/4061-F2017/lectures
> 1s
00-course-mechanics.org
                         00-course-mechanics.tex
                                                   01-introduction.org
                                                                         01-introduction.tex
00-course-mechanics.org~
                         01-introduction-code
                                                   01-introduction.org~
                                                                         02-unix-basic.c
00-course-mechanics.pdf
                                                   01-introduction.pdf
                         01-introduction-code.zip
                                                                         02-unix-basics.org
> cd ~
> pwd
/home/kauffman
> 1s
1103-F2017
                               Hello.class Hello.java~
            aurs
                     Downloads
                                                         PathClassLoader.txt
4061-F2017 Desktop
                    Dropbox
                               Hello.java
                                            misc
                                                          public_html
```

# Typical Unix Directory Structure



- rooted at /, reachable via 'cd /'
- user directories such as /home/kauffman/

#### Determining File Types

# Command Effect file something.ext try to determine the type of given file

```
> file xxx
xxx: UTF-8 Unicode text, with very long lines
> file test txt
test txt: ASCII text
> file www
www: directory
> file 4061-F2017
4061-F2017: symbolic link to /home/kauffman/Dropbox/teaching/4061-F2017
> file 4061-F2017/
4061-F2017/: directory
> cd 4061-F2017/lectures/
> file 01-introduction-code.zip
01-introduction-code.zip: Zip archive data, at least v1.0 to extract
> file 02-unix-basics-code/no_interruptions.c
02-unix-basics-code/no interruptions.c: C source. ASCII text
> file 02-unix-basics-code/no_interruptions.o
02-unix-basics-code/no interruptions.o: ELF 64-bit LSB relocatable, x86-64, version 1 (SYSV),
not stripped
> file 02-unix-basics-code/a.out
02-unix-basics-code/a.out: ELF 64-bit LSB shared object, x86-64, version 1 (SYSV).
dynamically linked, interpreter /lib64/ld-linux-x86-64.so.2, for GNU/Linux 2.6.32,
BuildID[sha1]=ffb87934737b0e48b891d27573ae8a2e5687c46a, not stripped
>
```

# Searching and Manipulating Text

Command	Effect
cat file.txt	show contents of file in terminal
less file.txt	"page" text file, press "q" to quit
grep 'expression' file.txt	show lines matching expression in file
<pre>grep 'expression' *.txt</pre>	search every .txt file for lines
find .	show all files recursively from current directory
findname '*.c'	find all C source files recursively

These are very handy, worth knowing about, but won't be covered in detail during our course. Try the relevant session in Tool Time Lectures if curious.

# **Editing Files**

- ► There are fancy text editors like Atom (free, GUI, on lab machines)
- ▶ Then there are the old-school terminal editors like these:

Command	Effect
vi	modal editing, terse, powerful, ALWAYS present
emacs	modes for editing, extensible, mostly available, $\heartsuit$
nano	simple, podunky, usually available

- Learn some vi or emacs: long-term worthwhile investment
- Comes in real handy when you need to edit but there is no graphical login

# File Permissions / Modes

- Unix enforces file security via modes: permissions as to who can read / write / execute each file
- ► See permissions/modes with 1s -1
- Look for series of 9 permissions

```
> ls -1
total 140K
-rwx--x--- 2 kauffman faculty
                          8.6K Oct 2 17:39 a.out
-rw-r--r-- 1 kauffman devel
                           1.1K Sep 28 13:52 files.txt
                          1.5K Sep 26 10:58 gettysburg.txt
-rw-rw---- 1 kauffman faculty
                          8.6K Oct 2 17:39 my_exec
-rwx--x--- 2 kauffman faculty
----- 1 kauffman kauffman 128 Oct 2 17:39 unreadable.txt
-rw-rw-r-x 1 root root
                           1.2K Sep 26 12:21 scripty.sh
U G O
                               МТ
                          S
S R T W
                          I O I
E O H N
                           7. D M
R. U.E. E
                          E.
```

#### PERMISSIONS

Every file has permissions set from somewhere on creation

# Changing File Permissions

Command	Effect
ls -1	long listing of files, shows permissions
chmod u+x file.abc	make file executable by user
chmod o-rwx file.abc	remove permissions from other users
chmod 777 file.abc	everyone can do anything to file

```
> 1s
a.out no_interruptions.c no_interruptions.c~ no_interruptions.o
> 1s -1
total 40K
-rwxrwx--- 1 kauffman kauffman 8.5K Sep 7 09:55 a.out
-rw-r--r-- 1 kauffman kauffman 955 Sep 7 09:55 no_interruptions.c
-rw-r--r- 1 kauffman kauffman 883 Sep 7 09:54 no interruptions.c~
-rw-rw--- 1 kauffman kauffman 2.4K Sep 7 11:59 no interruptions.o
> chmod u-x a.out
> 1s -1
total 40K
-rw-rwx--- 1 kauffman kauffman 8.5K Sep 7 09:55 a.out
-rw-r--r- 1 kauffman kauffman 955 Sep 7 09:55 no interruptions.c
-rw-r--r- 1 kauffman kauffman 883 Sep 7 09:54 no interruptions.c~
-rw-rw--- 1 kauffman kauffman 2.4K Sep 7 11:59 no interruptions.o
> ./a.out
bash: ./a.out: Permission denied
> chmod u+x a out
> ./a.out
Ma-na na-na!
```

### Manual Pages

Command	Effect
man 1s	Bring up the manual page for command 1s
	'space' scrolls down, 'q' quits

```
> man ls | cat
                                                                   LS(1)
LS(1)
                           User Commands
NAME
       1s - list directory contents
SYNOPSIS
       ls [OPTION]... [FILE]...
DESCRIPTION
       List information about the FILEs (the current directory by
       default). Sort entries alphabetically if none of -cftuvSUX nor
       --sort is specified.
       Mandatory arguments to long options are mandatory for short
       options too.
       -a, --all
              do not ignore entries starting with .
       -A, --almost-all
              do not list implied . and ..
```

# Program Search PATH

Command	Effect
echo \$PATH	show where shell looks for programs
PATH=\$PATH:/home/kauffman/bin	also look in my bin directory
PATH=\$PATH:.	also look in current directory
PATH=.	ONLY look in the current directory

#### > echo \$PATH

/usr/local/sbin:/usr/local/bin:/usr/bin:/usr/lib/jvm/default/bin: /usr/bin/site\_perl:/usr/bin/vendor\_perl:/usr/bin/core\_perl:/home/kauffman/bin:/home/kauffman/Dropbox/bin:/home/kauffman/code/bin:/home/kauffman/code/utils:.

Search directories are separated by colons in Unix Note: PATH is a notable **Environment Variable.** We'll discuss these soon and how they relate to processes.

# **Exercise**: Compilation

- 1. What command is typically used to compile C programs?
- 2. What is the default name of a compiled program on Unix and how can it be changed?
- 3. What function does a *runnable* C file need to have to make a program?
- 4. Must *every* C file have that special function? Can you compile C files without that special function?

Write down your answers as a team for screen sharing

# **Answers**: Compilation

- 1. What command is typically used to compile C programs?
  - > gcc myprog.c
- 2. What is the default name of a compiled program on Unix and how can it be changed?
  - > ./a.out
  - > gcc -o mprog mprog.c
  - > ./myprog
- 3. What function does a *runnable* C file need to have to make a program?
  - ▶ main() must be present in at least one C file to make program
- 4. Must *every* C file have that special function? Can you compile C files without that special function?

- > gcc -o prog funcs1.o funcs2.o # link object files
- # Either funcs1.c or funcs2.c had main(), not both
- > ./prog

#### make and Makefiles

- Example of a build system
- Very old system, many newer ones but a good starting point
- ▶ Discussed in HW01 which is due soon
  - Get some experience creating a Makefile
  - ▶ Will be a required element for Projects

#### How make and Makefile Works

#### Build up dependencies recursively

- A tree-like structure (actually a DAG)
- Run commands for the lowest level
- Then go up a level
- ► Then up another . . .
- Can recurse to subdirectories to use other Makefiles as well
- Makefile describes dependencies between source/program files and commands to generate/compile

#### Makefile Format

```
target1 : dependecy1 dependency2 do command 1 then do command 2
```

target2 : target1 dependency3
 do command X
 then do command Y

# Showing and Murdering Running Processes

Command	Effect
ps	show running processes associated with terminal
ps a	show ALL running processes
ps u	show all processes for me
kill 1234	send process 1234 the TERM signal
kill -9 1234	send process 1234 the KILL signal
pkill a.out	send process named a.out the TERM signal
pkill -9 a.out	send process named a.out the KILL signal

S1+

Sep06

Sl+ Sep06

0:00 cinnamon-session --session cinnamon

0:00 /usr/lib/cinnamon-settings-daemon/csd-or

```
> ps
 PID TTY
                  TIME CMD
8050 pts/1 00:00:00 bash
8061 pts/1
           00:00:00 ssh
11033 pts/1
             00:00:00 ps
> ps u
USER
          PID %CPU %MEM
                          VSZ
                                RSS TTY
                                            STAT START
                                                        TIME COMMAND
kauffman 724 0.0 0.0 201092 5520 tty2
                                            Ssl+ Sep06 0:00 /usr/lib/gdm/gdm-x-session --run-script
        726 0.1 0.5 691872 94388 tty2
                                                 Sep06
                                                        2:08 /usr/lib/xorg-server/Xorg vt2 -displayfd
kauffman
                                            R1+
```

737 0.0 0.3 603020 49496 ttv2

784 0.0 0.1 565264 23008 tty2

kauffman ...

kauffman

# Exercise: Summarize the most important Unix Commands

- 1. Discuss what the most important Unix command line concepts and commands are for beginners
- 2. Explain these in your own words, how to use them, and why they are important
- 3. How do these commands interact with the operating system? What role does the OS play in the command?

Write down your answers as a team for screen sharing