Architecture and Parallel Computers

Chris Kauffman

Last Updated:
Wed Sep 8 09:15:59 AM CDT 2021

Logistics

Reading: Grama Ch 2

- **Focus on 2.3-5**, material pertaining to distributed memory
- We will return to shared memory arch later in the course
- Cache Coherence, PRAM models, False Sharing, Memory Bus are all shared memory topics
- Sections 2.1 and 2.2 optional, deeper architectures
- Sections 2.6 and 2.7 encouraged, deeper on networks

Assignment 1

- Will post on Thursday
- 8-day turn around
- Mostly written assignment
- Pair-work is allowed

SISD, SIMD, MIMD, SPAM, and other 4-letter words

- Traditional CPU, Single Instruction Single Data (SISD)
  ```
  ADD r1, r2      # add int in r2 to r1
  ```
- Most computers now have cpu instructions to add multiple
  ```
  PHADD mm1, mm2  # add two ints in mm2 to ints in mm1
  ```
- Smart compilers will select **vector instructions** when appropriate
- Explicit hardware parallelism is good for multimedia stuff (graphics, games, images, sound, videos)
- Flynn's taxonomy discusses several variants

SISD	SIMD	SPMD
MISD	MIMD	MPMD

- Some parallel programs exist as Multiple Program Mulitple Data (MPMD) like client server models (`client.c` and `server.c` are separate programs)
- Our focus and the most common type of parallel program: **Single Program Multiple Data (SPMD)**: *Write one program which processes different hunks of data in parallel*

Recall: Distributed vs Shared Memory

Distributed Memory



Source: Kaminsky/Parallel Java

- Far more scalable/cost effective
- Sharing information requires explicit send/receive commands between processors
- Communication requires more care/more expensive

Shared Memory



Source: Kaminsky/Parallel Java

- Convenience: no explicit send/receive, write shared memory address
- Requires coordination to prevent corrupting memory
- Communication cost is low but requires discipline

Modeling Distributed Memory Parallel Computers

- Will spend a some time discussing networks used in parallel computing
- These have consequences for algorithms, but unless you're building your own machine (for like $1M) you're stuck with what you get
  - Example: We will use CSE Labs machines with MPI installed to do Distributed programming : lacks a high-powered, dense network interconnect
  - Example: If you have a chance to work on the #2 Super Computer in the World, Summit, it is reported to have a Fat Tree Network Architecture can be exploited in its MPI communications

Static Networks for Distributed Machines

- String up a bunch of **Processing Elements (PEs)**
- Which PE is connected to which other?
- This can affect the cost of communication

Full Communication Costs

When sending a message of size m words of memory

- t_s: Startup time, incurred once
- t_h: Per-hop time, overhead incurred for each link between source and destination
- t_w: Per-word transfer time between two nodes, takes $t_w \times M$ time for each link between source and destination
- L: number of links to traverse
- M: number of words being sent
- Typical model for communication time w/ packet routing

$$t_{comm} = t_s + Lt_h + t_w M$$

Grid and Torus



Figure 2.16 Two and three dimensional meshes: (a) 2-D mesh with no wraparound; (b) 2-D mesh with wraparound link (2-D torus); and (c) a 3-D mesh with no wraparound.

Source: Grama, Sec 2.4.3

- Common arrangement of links between PEs
- Each PE node connected to neighbors
- When wrapping around, grid becomes a torus
- For a 2D torus with p nodes, how many links are required?
- *Hint: surprisingly simple, think of each processor "owning" down and right links*
- How many links in a 3D torus?

Fat Trees



Figure 2.19 A fat tree network of 16 processing nodes.

Often used as network switches are commodities while still providing good speeds

HyperCube

- N-dimension hypercube: connect two $(N-1)$ dimension hypercubes, link corresponding nodes
- How many nodes and links in an N-dimension hypercube?
- *Hint: Nodes are easy, links are tricky, try your textbook...*



Exercise: Compare Networks: Parallel Stencil

- P processors
- $\log_2(P)$ dimension Hypercube: $(P \log_2(P)/2)$ links
- 2D-torus: $2P$ links
- **Discuss** advantages/disadvantages of torus vs hypercube arrangement for this application
- Outline an algorithm, estimate cost-effectiveness of code+hardware

Image "blurring"

- A large image is distributed across the P processors
- Each proc holds a 2D hunk of the image
- To blur the entire image, must assign RGB values which are average of "neighborhood"

Stencil



Answers Compare Networks: Parallel Stencil

- Obviously PEs must communicate with other PEs that have neighboring hunks
- Maps VERY easily onto a 2D Torus (or Grid)
  - PEs locally blur
  - Exchange pixels with 4 neighbors
  - Compute blur for edge
- Trickier for the Hypercube
  -

Compare Networks: Parallel Sum

- p processors
- \$$\log_2$(p)\$-dimension Hypercube: $(p\log_2(p)/2)$ links
- 2D-torus: $2p$ links
- **Discuss** advantages/disadvantages of torus vs hypercube arrangement for this application
- Outline an algorithm, estimate cost-effectiveness

Sum Array of Numbers

- Each proc holds a hunk of the data array
- Want a single processor to eventually contain sum o
- **State your algorithm**: Try to minimize communication at each step, exploit as much parallelism as possible

Networks



Figure 2.16 Two and three dimensional meshes: (a) 2-D mesh with no wraparound; (b) 2-D mesh with wraparound link (2-D torus); and (c) a 3-D mesh with no wraparound.



Some details on Parallel Sum

- We will talk more about parallel sum later
- Parallel sum is an example of a **reduction**
- For those curious, have a look at Lecture notes by Susan Hayes

Characteristics of Various Networks

Table 2.1. A summary of the characteristics of various static network topologies connecting p nodes.

Network	Diameter	Bisection Width	Arc Connectivity	Cost (No. of links)
Completely-connected	1	$p^2/4$	$p - 1$	$p(p - 1)/2$
Star	2	1	1	$p - 1$
Complete binary tree	$2 \log((p + 1)/2)$	1	1	$p - 1$
Linear array	$p - 1$	1	1	$p - 1$
2-D mesh, no wraparound	$2(\sqrt{p} - 1)$	$\sqrt{p}$	2	$2(p - \sqrt{p})$
2-D wraparound mesh	$2\lfloor\sqrt{p}/2\rfloor$	$2\sqrt{p}$	4	2p
Hypercube	$\log p$	$p/2$	$\log p$	$(p \log p)/2$
Wraparound k-ary d-cube	$d\lfloor k/2\rfloor$	$2k^{d-1}$	$2d$	dp

Several metrics described in textbook

- *Diameter*: how many hops away any two procs can be
- *Bisection width*: number of links to break to partition network
- *Arc Connectivity*: number of paths between two nodes
- *Cost*: can correspond to number of links

Dynamic Networks



- In a static network, connections are fixed
- Dynamic networks use switches: send data into network with destination, may alter a connection to point in a different direction
- Akin to the internet: packet switching network
- Textbook mixes concepts somewhat: Network for
    - Distributed PEs to communicate
    - PEs to share memory

CrossBar and Omega Network





Tree

- Frequently used: Fat tree
- Fairly cost effective: Why?
- What drawbacks might it have?



Routing: Store/Forward Packet, Switching, Cut-Through

- When sending messages, intermediate nodes must decide what to do with a message: **Routing protocol/scheme**

Store and Forward

- Accumulate the whole message (all M words), store it until it can be forwarded to next hop
- Easy to build but requires large-ish internal buffers and generally has bad performance

Standard Packet Switching

- Break message into chunks (packets)
- Use packet header to carry error-correction info, routing info
- Optimized for the unreliable internet (go around overloaded/dead nodes)
- Better but incurs overhead to solve problems that aren't present in most parallel machines

Cut-through Routing/Switching

Routing: Cut-through Routing

- Similar to packet switching: break message into chunks
- Send a *tracer* from source to destination to determine route
- Send message in *flits* (packets) along single route
- Include minimal overhead in packet for error correction, re-routing, etc.
- Cost to communicate message size M between two PEs L hops away

$$t_{comm} = t_s + Lt_h + t_w M$$

The Simplified Model Communication Model

When analyzing performance of programs, consider the following

- t_s: Startup time, incurred once
- t_h: Per-hop time, overhead incurred for each link between source and destination
- t_w: Per-word transfer time between two nodes, takes $t_w \times M$ time for each link between source and destination
- L: number of links to traverse
- M: number of words being sent

Simplified model advocated by Grama et. al

$$t_{comm} = t_s + t_w M$$

- Easy to understand/use
- Relatively easy to apply to programs
- Ignores a pretty big component: why?
- Why would the text adopt this podunk model?

Our Approach

Analyzing Communication Patterns

Will incorporate number of hops L between PEs in the network

$$t_{comm} = t_s + Lt_h + t_w M$$

Try to derive good source/destination pairs and message routes

Analyzing Programs

Will ignore network topology, congestion, number of hops

$$t_{comm} = t_s + t_w M$$

Somewhat unrealistic but makes analysis much simpler