CSCI 4061: Signals and Signal Handlers

Chris Kauffman

Last Updated: Mon Mar 8 03:54:07 PM CST 2021

Signals Overview

- Signals are an old system of communication to convey a limited amount of info to a process
- "Delivered" by the OS to a running process to inform of it of an event
- Process responds in one of several ways according to its Disposition
- Default disposition for most signals is to die
- Process can ignore most signals or handle them with a designated functions but some cannot be caught in this way
- Signals are asynchronous, could delivered to a process at any time which makes them a pain in the @\$\$

Sending Signals: kill Utility and kill() Syscall

Have seen that the kill utility sends signals on the command line

```
> kill 1234
                   # attempt to end a program "nicely"
> kill -TERM 1234 # same as above
> kill -15 1234  # same as above
> kill -9 1234  # forcefully kill a program
> kill -KILL 1234  # same as above
Corresponds to invocations of the kill() system call
> man 2 kill
NAMF.
   kill - send signal to a process
SYNOPSTS
   #include <sys/types.h>
   #include <signal.h>
    int kill(pid_t pid, int sig);
DESCRIPTION
   The kill() system call can be used to send any signal to any
    process group or process.
```

EXAMPLE { ...

kill(1234, SIGKILL);

Process Signal Disposition

Cont.

stopped.

```
> man 7 signal
Signal dispositions
    Each signal has a current disposition, which determines how the
   process behaves when it is delivered the signal.
   The entries in the "Action" column of the tables below specify the
   default disposition for each signal, as follows:
   Term
           Default action is to terminate the process.
           Default action is to ignore the signal.
    Ign
   Core
           Default action is to terminate the process and dump core (see
           core(5)).
    Stop
          Default action is to stop the process.
```

Default action is to continue the process if it is currently

Can adjust signal disposition with various system calls and establish **signal handlers** for the process.

Standard Types of Signals

> man 7 signal Standard Signals

	x86	Default		
Signal	Value	Action	Comment	
SIGHUP	1	Term	01	
SIGINT		Term	Interrupt from keyboard	
SIGQUIT	3	Core	Quit from keyboard	
SIGILL	4	Core	Illegal Instruction	
SIGTRAP	5	Core	Trace/breakpoint trap	
SIGABRT	6	Core	Abort signal from abort(3)	
SIGBUS	7	Core	Bus error (bad memory access)	
SIGFPE	8	Core	Floating-point exception (CK: actually integer divide by 0)	
SIGKILL	9	Term	Kill signal	
SIGUSR1	10	Term	User-defined signal 1	
SIGSEGV	11	Core	Invalid memory reference	
SIGUSR2	12	Term	User-defined signal 2	
SIGPIPE	13	Term	Broken pipe: write to pipe with no readers; see pipe(7)	
SIGALRM	14	Term	Timer signal from alarm(2)	
SIGTERM	15	Term	Termination signal	
SIGSTKFLT	16	Term	Stack fault on coprocessor (unused)	
SIGCHLD	17	Ign	Child stopped or terminated	
SIGCONT	18	Cont	Continue if stopped	
SIGSTOP	19	Stop	Stop process	
SIGTSTP	20	Stop	Stop typed at terminal	
SIGUNUSED	31	Core	Synonymous with SIGSYS	

Note: Different CPU architectures may have different values for some signals and support other signals not listed

(Ex: MIPS CPUs use SIGCONT=25 with a synonym for SIGCHLD=19)

Basic Signal Handlers via signal()

Pressing Ctrl-c in a terminal sends SIGINT to a running program which normally Terminates the program. The below template establishes a **signal handler** for SIGINT.

```
#include <signal.h>
void handle_SIGINT(int sig_num) {
    ...
}
int main () {
    // Set handling functions for programs
    signal(SIGINT, handle_SIGINT);
    ...
}
```

- ▶ When SIGINT arrives at program, control jumps to function handle_SIGINT() with argument sig_num == SIGINT
- ► When handle_SIGINT() completes, control returns to wherever the program left off

Examine: no_interruptions_signal.c

Historical Notes 1 / 2

- Signals were an early concept but were initially "unreliable": might get lost and so were not as useful as their modern incarnation
- ► Historically, required to reset signal handlers after they were called. First line of handler was always

```
signal(this_signal, this_hanlder);
though this was still buggy.
void handle_SIGINT(int sig_num) {
    signal(SIGINT, handle_SIGINT); // Reset handler, unnecessary nowadays
    printf("\nNo SIGINT-erruptions allowed.\n");
    fflush(stdout);
}
int main () {
    signal(SIGINT, handle_SIGINT); // Set handler the first time
    ...
```

- Old sources describe the need to reset handles while running
- ▶ What moment(s) in the program is no signal handler set?
- Not needed on most modern Unix systems

Historical Notes 2 / 2

► Historically, some system calls could be interrupted by signals. Robbins & Robbins go on and on about this.

On FreeBSD 8.0, Linux 3.2.0, and Mac OS X 10.6.8, when signal handlers are installed with the signal function, interrupted system calls will be restarted. The default on Solaris 10, however, is to return an error (EINTR) instead when system calls are interrupted by signal handlers installed with the signal function.

- Stevens and Rago, 10.5
- Interrupted system calls meant EVERY system call had to appear in some sort of a try loop:

Modern sigaction() function does not have the problems of the old signal() function

Portability Notes on signal()

> man 2 signal

The behavior of signal() varies across UNIX versions, and has also varied historically across different versions of Linux.

AVOID ITS USE: use sigaction(2) instead.

PORTABILITY

The semantics when using signal() to establish a signal handler vary across systems (and POSIX.1 explicitly permits this variation); *do not use it for this purpose.*

- signal() part of the C standard but is old with different behaviors across different systems
- ► POSIX defined **new functions** which were designed to break from its tradition and fix problems associated with it

Portable Signal Handlers via sigaction()

- ► The sigaction() function is more portable than signal() to register signal handlers.
- Makes use of struct sigaction which specifies properties of signal handler registrations, most importantly the field sa_handler

```
int main(){
    struct sigaction my_sa = {};
    my_sa.sa_handler = handle_signals;
    sigemptyset(&my_sa.sa_mask);
    my_sa.sa_flags = SA_RESTART;
    sigaction(SIGTERM, &my_sa, NULL);
    sigaction(SIGINT, &my_sa, NULL);
}

// SAMPLE HANDLER SETUP USING sigaction()
// portable signal handling setup with sigaction()
// don't block any other signals during handling
// restart system calls on signals if possible
sigaction(SIGINT, &my_sa, NULL);
// register SIGIERM with given action
...;
}
```

See no_interruptions_sigaction.c

Ignoring Signals, Restoring Defaults

- ► Setting the signal handler to SIG_IGN will cause signals to be silently ignored.
- Setting the signal handler to SIG_DFL will restore default disposition.

Demo no_interruptions_ignore.c

Sleeping, Pausing, and Stopping

Sleeping/Pausing: wait for a signal

- sleep(5) suspends process execution until a signal is delivered or for 5 seconds elapses
- pause() suspends process execution until a signal is delivered;
- sleep(0) is equivalent to pause()

Note sleep behavior of various no_interruptions programs

Signals that Affect Execution

- SIGSTOP will causes process to stop, will not resume until...
- SIGCONT causes a stopped process to resume, otherwise ignored by default
- All signals are delivered while a process is stopped BUT it is not resumed until receiving SIGCONT

Examine: start_stop.c with circle_of_life.c

You want the Signal? You Can't Handle the Signal!

- SIGKILL and SIGSTOP cannot have dispositions changed from default
 - SIGKILL always terminates a process
 - SIGSTOP always stops a process execution
- In that sense they are a little different than the other signals but use the same OS delivery mechanism and kill() semantics
- ► Calls to sigaction() or signal() for these two will fail
- See cant_handle_kill.c

Exercise: What Can you do with signals?

- Now have basics of signals and handlers in play
- Natural question: what are they good for?
- Identify some uses for signals that we have seen so far:
 - Standard uses for signals that have been demonstrated
 - How to use signals in this way
- Propose some uses for signals and handlers that are new and different from our examples so far

Answers: What Can you do with signals?

- ► Kill progams via kill(pid, SIGKILL) or kill -9 pid
- Signals used in Shell for job control
 - Ctrl-Z suspends, uses to kill(pid, SIGSTOP)
 - ▶ fg / bg resumes, uses kill(pid, SIGCONT)
- ► Catch SIGTERM / SIGINT and shut down gracefully:
 - ► Save files, close network connections, write to Databases etc.
 - Many programs do not want to suddenly die when in a sensitive state
 - Examples in Lab this week, used in P2 / P3
- Perform limited, dynamic responses to signals though this is tricky and there are usually better methods than signals that we will discuss

Other Parts of struct sigaction

The struct sigaction argument to the sigaction() function allows several options for handlers to be specified.

Туре	Field	Purpose
<pre>void(*) (int)</pre>	sa_handler	Pointer to a signal-catching function
		or one of the macros SIG_IGN or SIG_DFL.
sigset_t	sa_mask	Additional set of signals to be blocked
		during execution of signal-catching function.
int	sa_flags	Special flags to affect behavior of signal.
		Typically SA_RESTART is used to restart
		system calls automatically
<pre>void(*) (int,</pre>	sa_sigaction	More complex handler used when sa_flags has
siginfo_t *,		SA_SIGINFO set; passes additional info to
void *)		handler like PID of signaling process.

Standard setup for sigaction() call is

Dangers in Signal Handlers

- General advice: do as little as possible in a signal handler
- Make use of only reentrant functions
 - ... reentrant if it can be interrupted in the middle of its execution, and then be safely called again ("re-entered") before its previous invocations complete execution.
 - Wikipedia: Reentrancy
- Notably NOT reentrant
 printf() family, malloc(), free()
- Reentrant functions pertinent to thread-based programming as well (discussed later)

Leading Example: crypt_not_reentrant.c

- Makes use of library call to crypt() which is used to generate encrypted versions of passwords
- crypt() called in both...
 - main() during a while() loop
 - in a signal handler for alarms
- crypt() is non-reentrant: why?
- Observe what happens during runs of program¹

Note: alarm(secs)

- Request to OS to send SIGALRM to program later on
- Alerts program that a certain amount of time has passed

 $^{^1}$ Similar example is in <code>getpwnam_not_reentrant.c</code>

Exercise: Non-Reentrant Function Example

- Program calls non-reentrant function f() in two locations
 - main()
 - ► handle_signal() (!)
- With no signals, expect to see 7 printed
- ▶ If signaled should see 19,7 printed in either order
- ➤ Show a control flow involving signals that prints 19 twice
- ▶ Why is f() not reentrant?

```
1 int z;
2 int f(int x, int y){
     int tmp = x + y;
     z = tmp * 2 + 1;
     return z:
8 void handle_signal(int sig){
     int t = f(4.5):
10
     printf("%d\n",t);
11
     return:
12 }
13
14 int main(){
15
     signal(SIGINT, handle_signal);
     int v = f(1.2):
16
     printf("%d\n".v);
17
18 }
```

Answer: Non-Reentrant Function Example

- Program below calls non-reentrant function f() in both main() and handle_signal()
- ► With no interrupts, would expect to see 7 printed, with interrupts see 19 and 7
- ► Right hand shows one possible flow through the code which produces 19 then 19 again

```
1 int z;
                                      EXECUTION STARTS IN main()
 2 int f(int x, int y){
                                      15: signal(SIGINT, handle_signal);
 3 int tmp = x + y;
                                      16: int v = f(1,2); // main(), Expect: (1+2)*2+1 = 7
 4 z = tmp * 2 + 1;
                                       3: tmp = x + y; // f(1,2): tmp = 1+2 = 3
                                       4: z = tmp*2 + 1; // z is 7
    return z:
 6 }
                                      SIGINT delivered, run handler
                                          9: int t = f(4,5); // handle signal(2)
 8 void handle_signal(int sig){
                                          3: tmp = x + y; // f(4,5): tmp = 4+5 = 9
    int t = f(4,5);
                                          4: z = tmp*2 + 1; // z is now 19
                                          5: return z; // back to handle_signal()
    printf("%d\n",t);
10
                                          9: int t = f(4,5); // finished, t is 19
11
    return:
12 }
                                         10: printf("%d\n",t); // PRINT 19
13
                                         11: return; // back to normal control
                                    5: return z;  // back to main(), but z is 19
16: int v = f(1,2);  // v is actually 19
14 int main(){
    signal(SIGINT, handle_signal);
15
                                      17: printf("%d\n",v); // PRINT 19
16
    int v = f(1,2);
17
    printf("%d\n",v);
                                                             // 7 Expected
18 }
```

Signal Sets

- A set of signals, likely implemented as a bit vector
- Functions allow addition, removal, clearing of set and tests for membership

```
#include <signal.h>
int sigemptyset(sigset_t *set);
// empty out the set
int sigfillset(sigset_t *set);
// fill the entire set with all signals
int sigaddset(sigset_t *set, int signo);
// add given signal to the set
int sigdelset(sigset_t *set, int signo);
// remove given signal to the set
// All of the above return 0 on succes, -1 on error
int sigismember(const sigset_t *set, int signo);
// return 1 if signal is a member of set, 0 if not
```

Examine sigsets_demo.c

Blocking (Disabling) Signals

- ▶ Processes can **block** signals, disable receiving them
- Signal is still there, just awaiting delivery
- Blocking is different from Ignoring a signal
 - Ignored signals are received and discarded
 - Blocked signals will be delivered after unblocking
- Can protect Critical Sections of code with by blocking if signals would screw it up

Process Signal Mask

Example: block all signals that can be blocked

Examine no_interruptions_block.c

Exercise: Protect Non-Reentrant Call

Examine the code for crypt_not_recentrant.c and modify it to use signal blocking to protect the **critical region** associated with calls to crypt().

- Create a mask for all signals
- ▶ Block all signals prior to function call
- Unblock after returning
- Use code like below

Note: Be *very careful* where you unblock signal handling in main() to avoid errors: protect the **Critical Section**

Code for crypt_not_reentrant.c on next slide

Exercise: Protect Non-Reentrant Call

```
// crypt_not_reentrant.c
                                                    18
2
                                                        int main(void) {
                                                    19
    #define PASSWORD "password123"
                                                           struct sigaction mv sa = {
                                                    20
    #define SALT
                                                    21
                                                             .sa_handler = alarm_handler,
                      "00"
    char reference[128]:
   void alarm handler(int signo) {
                                                     23
                                                           sigaction(SIGALRM, &mv sa, NULL):
      printf("in signal handler\n");
                                                    24
                                                           alarm(1);
      char *crypted = crypt(PASSWORD,SALT);
                                                    25
8
      if( strncmp(reference, crypted, 128) != 0 ){ 26
                                                           printf("Repeatedly crypting '%s'\n".PASSWORD):
10
        printf("MISMATCH: %s\n",crypted);
                                                     27
        exit(1);
                                                    28
11
                                                           char *refcrypted = crypt(PASSWORD,SALT);
12
                                                    29
                                                           strncpv(reference.refcrypted.128):
13
      printf("HANDLER ENCRYPTED: %s\n",crypted);
                                                     30
                                                           printf("REFERENCE ENCRYPTED: %s\n",reference);
                                                    31
14
      printf("leaving signal handler\n");
      alarm(1);
                                                    32
15
                                                           int successes = 0;
16
                                                    33
                                                           while(1){
17
                                                    34
                                                             char *crypted = crypt(PASSWORD, SALT);
                                                    35
                                                             if( strncmp(reference, crypted, 128) != 0 ){
                                                    36
                                                               printf("MISMATCH: %s\n",crvpted):
                                                     37
                                                               exit(1):
                                                    38
                                                             7
                                                     39
                                                             successes++:
                                                    40
                                                             if(successes % 10000 == 0){
                                                               printf("%d successes so far\n", successes);
                                                    41
                                                    42
                                                    43
                                                    44
                                                           return 0;
                                                    45 F
```

Answers: Protect Non-Reentrant Call

```
// crypt protected.c
                                                        // BLOCK DURING CRITICAL REGION
   // SAME AS BEFORE
                                                        int main(void) {
    #define PASSWORD "password123"
                                                    20
                                                          struct sigaction my_sa = {
    #define SALT
                                                            .sa handler = alarm handler,
                                                    21
  char reference[128]:
                                                    22
   void alarm handler(int signo) {
                                                    23
                                                          sigaction(SIGALRM, &my_sa, NULL);
7
      printf("in signal handler\n");
                                                    24
                                                          alarm(1);
8
      char *crypted = crypt(PASSWORD,SALT);
                                                    25
      if( strncmp(reference, crypted, 128) != 0 ){ 26
                                                          printf("Repeatedly crypting '%s'\n",PASSWORD);
        printf("MISMATCH: %s\n",crypted);
                                                    27
10
11
        exit(1):
                                                    28
                                                          char *refcrypted = crypt(PASSWORD.SALT):
12
                                                    29
                                                          strncpy(reference, refcrypted, 128);
13
      printf("HANDLER ENCRYPTED: %s\n",crypted);
                                                    30
                                                          printf("REFERENCE ENCRYPTED: %s\n",reference);
14
      printf("leaving signal handler\n"):
                                                    31
15
      alarm(1):
                                                    32
                                                          int successes = 0:
16 }
                                                    33
                                                          while(1){
17
                                                    34
                                                            sigset_t block_all, defaults;
                                                                                                               //
                                                                                                               //
                                                    35
                                                            sigfillset( &block all ):
                                                    36
                                                            sigprocmask(SIG_SETMASK, &block_all, &defaults); //
                                                    37
                                                            char *crypted = crypt(PASSWORD, SALT);
                                                    38
                                                            if( strncmp(reference, crypted, 128) != 0 ){
                                                    39
                                                              printf("MISMATCH: %s\n",crypted);
                                                    40
                                                              exit(1);
                                                    41
                                                    42
                                                            sigprocmask(SIG SETMASK, &defaults, NULL):
                                                                                                               //
                                                            successes++:
                                                    43
                                                    44
                                                            if(successes % 10000 == 0){
                                                    45
                                                              printf("%d successes so far\n".successes):
                                                    46
                                                            7
                                                    47
                                                    48
                                                          return 0:
                                                    49 }
```

Hardware Analogs to Signals

- Unix Signals are a software mechanism: happens via OS mechanisms in code
- Similar hardware mechanisms exist and deserve mention as some are related to software signals

Example 1: Division by 0

- Processor ALU performs division
- ▶ Div by 0 generates an exceptional condition which transfers control to a hardware exception handler
- ► Typical CPU response is to jump to OS code
- OS sends a software signal to running program as SIGFPE

See div0.c and explain the output...

Example 2: Alarms

Hardware timer expires \rightarrow hardware signal \rightarrow software signal

Hardware Exceptions, Interrupts, Traps

Hardware features **electrical signals** that can cause control jumps. Definitions vary somewhat but two general types are common.

Trap

- Generated by specific assembly instructions
- ▶ Div by 0 is a trap due to use of idivX instruction
- Jumps to handler indicated by CPU table
- Generated and handled synchronously

Interrupt

- Generated by hardware devices like a disk drive often to indicate completion of operation
- Jumps CPU to interrupt handler so OS can react, move process waiting for file load from blocked to unblocked
- Major parts of OS kernel handle hardware via asynchronous interrupts

Just to Muddy the Waters further...

- Modern system calls are made via sysenter (32-bit) and syscall (64-bit), BUT...
- ▶ In old-school 32-bit x86 assembly, making a system call was done via the *interrupt instruction* int 0x80 # trigger interrupt 128, handled by OS kernel
- Referred to as "trapping to the OS"
- ▶ Is this a...
 - 1. Trap?
 - 2. Interrupt?
 - 3. Another example of computer jargon that makes you want to change majors?

Signal Take-Home

- Signals provide a simple way for programs to perform limited communications
- Can send signals via kill utility and system call kill()
- Programs respond to signals in a default manner ("signal disposition") that can be changed and customized via handlers
- Can sleep() or pause() a program until a signal is received
- Can block signals if needed
- ► First example of **asynchronous** events in programs which introduces dangers associated with non-reentrant functions
- Signals not good for general purpose communication but are useful to convey simple events like "wake up already"