CSCI 2021: x86-64 Assembly Extras and Wrap

Chris Kauffman

Last Updated:
Fri Mar 12 10:05:05 AM CST 2021

Logistics

Reading Bryant/O'Hallaron

Read in Full

- Ch 3.7 Procedure Calls

Skim the following

- Ch 3.8-3.9: Arrays, Structs
- Ch 3.10: Pointers/Security
- Ch 3.11: Floating Point

Goals

- ⊟ Asm Procedure Calls
- ☐ Assembly vs C
- ☐ Data in Assembly
- ☐ Security Risks
- ☐ Floating Point Instr/Regs

Date	Event
Fri 3/12	Asm Extras
Mon 3/15	Asm Wrap-up
Wed 3/17	**P3 Due**
	Practice Exam 2
	Lab/HW 9: Review
Fri 3/19	Exam 2

Project 3

- Problem 1: Battery Assembly Functions (50%)
- Problem 2: Binary Bomb via debugger (50%)

Exercise: All Models are Wrong...

- Rule #1: The Doctor Lies
- Below is our original model for memory layout of C programs
- Describe what is **incorrect** based on x86-64 assembly
- Will all variables have a position in the stack?
- What else is on the stack / control flow info?
- What registers are likely used?

```
 9: int main(...){
10:   int x = 19;
11:   int y = 31;
12:   swap(&x, &y);
13:   printf("%d %d\n",x,y);
14:   return 0;
15: }

18: void swap(int *a,int *b){
19:   int tmp = *a;
20:   *a = *b;
21:   *b = tmp;
22:   return;
23: }
```

STACK: Caller main(), prior to swap()

FRAME	ADDR	NAME	VALUE
main()	#2048	x	19
line:12	#2044	y	31

STACK: Callee swap() takes control

FRAME	ADDR	NAME	VALUE
main()	#2048	x	19
line:12	#2044	y	31
swap()	#2036	a	#2048
line:19	#2028	b	#2044
	#2024	tmp	?

Answers: All Models are Wrong, Some are Useful

```
    9: int main(...){
   10:   int x = 19;
   11:   int y = 31;
+-<12:   swap(&x, &y);
|  13:   printf("%d %d\n",x,y);
|  14:   return 0;
V  15: }
|
|  18: void swap(int *a,int *b){
+->19:   int tmp = *a;
   20:   *a = *b;
   21:   *b = tmp;
   22:   return;
   23: }
```

```
STACK: Callee swap() takes control
| FRAME   | ADDR  | NAME | VALUE |
|---------+-------+------+-------|
| main()  | #2048 | x    |    19 |
|         | #2044 | y    |    31 |
|---------+-------+------+-------|
| swap()  | #2036 | rip  |Line 13|
|---------+-------+------+-------|
REGS as swap() starts
| REG | VALUE | NOTE          |
|-----+-------+---------------|
| rdi | #2048 | for *a        |
| rsi | #2044 | for *b        |
| rax |     ? | for tmp       |
| rip |   L19 | line in swap  |
```

- `main()` must have stack space for locals passed by address
- `swap()` needs no stack space for arguments: in registers
- Return address is next value of `rip` register in `main()`
- Mostly don't need to think at this level of detail but **can be useful in some situations**

Data In Assembly

Arrays

Usually: base + index × size

```
arr[i] = 12;
movl $12,(%rdi,%rsi,4)

int x = arr[j];
movl (%rdi,%rcx,4),%r8d
```

- Array starting address often held in a register
- Index often in a register
- Compiler inserts appropriate size (1,2,4,8)

Structs

Usually base+offset

```
typedef struct {
  int i; short s;
  char c[2];
} foo_t;
foo_t *f = ...;

short sh = f->s;
movw 4(%rdi),%si

f->c[i] = 'X';
movb $88, 6(%rdi,%rax)
```

Packed Structures as Procedure Arguments

- Passing pointers to structs is 'normal': registers contain addresses to main memory
- Passing actual structs may result in *packed structs* where several fields are in a single register
- Assembly must *unpack* these through **shifts and masking**

```
 1  // packed_struct_main.c
 2  typedef struct {
 3    short first;
 4    short second;
 5  } twoshort_t;
 6
 7  short sub_struct(twoshort_t ti);
 8
 9  int main(){
10    twoshort_t ts = {.first=10,
11                     .second=-2};
12    int sum = sub_struct(ts);
13    printf("%d - %d = %d\n",
14           ts.first, ts.second, sum);
15    return 0;
16  }
```

```
 1  ### packed_struct.s
 2  .text
 3  .globl  sub_struct
 4  sub_struct:
 5    ## first arg is twoshort_t ts
 6    ## %rdi has 2 packed shorts in it
 7    ## bits  0-15 are ts.first
 8    ## bits 16-32 are ts.second
 9    ## upper bits could be anything
10
11    movl %edi,%eax      # eax = ts;
12    andl $0xFFFF,%eax   # eax = ts.first;
13    sarl $16,%edi       # edi = edi >> 16;
14    andl $0xFFFF,%edi   # edi = ts.second;
15    subw %di,%ax        # ax = ax - di
16    ret                 # answer in ax
```

Example: `coins_t` in HW06 / Lab07

```
// Type for collections of coins
typedef struct {  // coint_t has the following memory layout
  char quarters;  //
  char dimes;     // |          | Pointer | Packed | Packed |
  char nickels;   // |          |  Memory | Struct | Struct |
  char pennies;   // | Field    |  Offset | Arg#   | Bits   |
} coins_t;        // |----------+---------+--------+--------|
                  // | quarters |      +0 | #1     | 0-7    |
                  // | dimes    |      +1 | #1     | 8-15   |
                  // | nickels  |      +2 | #1     | 16-23  |
                  // | pennies  |      +3 | #1     | 24-31  |
```

```
## | #2048 | c->quarters | 2 |
## | #2049 | c->dimes    | 1 |
## | #2050 | c->nickels  | - |
## | #2051 | c->pennies  | - |

set_coins:
### int set_coins(int cents, coins_t *coins)
### %edi = int cents
### %rsi = coints_t *coins
  ...
  # rsi: #2048
  # al: 0  %dl: 3
  movb    %al,2(%rsi)     # coins->nickels = al;
  movb    %dl,3(%rsi)     # coins->pennies = dl;

## | #2048 | c->quarters | 2 |
## | #2049 | c->dimes    | 1 |
## | #2050 | c->nickels  | 0 |
## | #2051 | c->pennies  | 3 |
```

```
total_coins:
### args are
### %rdi packed coin_t struct with struct fields
### {0-7: quarters, 8-15: dimes,
###  16-23-: nickels, 24-31: pennies}
  ...

### rdi: 0x00 00 00 00 03 00 01 02
###                       p  n  d  q
  movq    %rdi,%rdx         # extract dimes
### rdx: 0x00 00 00 00 03 00 01 02
###                       p  n  d  q
  sarq    $8,%rdx           # shift dimes to low bits
### rdx: 0x00 00 00 00 00 03 00 01
###                          p  n  d
  andq    $0xFF,%rdx        # rdx = dimes
### rdx: 0x00 00 00 00 00 00 00 01
###                          p  n  d
```

General Cautions on Structs

Struct Layout by Compilers

- Compiler honors order of source code fields in struct
- BUT compiler may add padding between/after fields for alignment
- Compiler determines total struct size

Struct Layout Algorimths

- Baked into compiler
- **May change from compiler to compiler**
- May change through history of compiler

Structs in Mem/Regs

- Stack structs spread across several registers
- Don't need a struct on the stack at all in some cases (just like don't need local variables on stack)
- Struct arguments packed into 1+ registers

Stay Insulated

- Programming in C insulates you from all of this
- Feel the **warmth** of gcc's abstraction blanket

Security Risks in C

Buffer Overflow Attacks

- No default bounds checking in C: Performance favored over safety
- Allows classic security flaws:

```
char buf[1024];
printf("Enter you name:");
fscanf(file,"%s",buf); // BAD
// or
gets(buf);                    // BAD
// my name is 1500 chars
// long, what happens?
```

- For data larger than `buf`, begin overwriting other parts of the stack
  - Clobber return addresses
  - Insert executable code and run it

Counter-measures

- **Stack protection** is default in `gcc` in the modern era
- Inserts "canary" values on the stack near return address
- Prior to function return, checks that canaries are unchanged
- **Stack / Text Section Start randomized** by kernel, return address and function addresses difficult to predict ahead of time
- Kernel may also vary virtual memory address as well
- Disabling protections is risky

Sample Buffer Overflow Code

```
#include <stdio.h>            // compiled with gcc will likely result
void never(){                 // only in 'stack smashing'
  printf("This should never happen\n");
  return;
}
int main(){
  union {long addr; char str[9];} never_info;
  never_info.addr = (long) never;
  never_info.str[8] = '\0';

  printf("Address of never: %0p\n",never_info.addr);
  printf("Address as string: %s\n",never_info.str);

  printf("Enter a string: ");
  char buf[4];
  fscanf(stdin,"%s",buf);
  // By entering the correct length of string followed by the ASCII
  // representation of the address of never(), one might be able to
  // get that function to run (on windows...)

  printf("You entered: %s\n",buf);
  return 0;
}
```

Accessing Global Variables in Assembly

Global data can be set up in assembly in `.data` sections with labels and assembler directives like `.int` and `.short`

```
.data
an_int:                 # single int
        .int 17
some_shorts:            # array of shorts
        .short 10       # some_shorts[0]
        .short 12       # some_shorts[1]
        .short 14       # some_shorts[2]
```

Modern Access to Globals

```
movl an_int(%rip),  %eax
leaq some_shorts(%rip), %rdi
```

- Uses `%rip` relative addressing
- Default in `gcc` as it plays nice with OS security features
- May discuss again later during Linking/ELF coverage

Traditional Access to Globals

```
movl an_int,  %eax          # ERROR
leaq (some_shorts), %rdi    # ERROR
```

- Not accepted by `gcc` by default
- Yields compile/link errors

```
/usr/bin/ld: /tmp/ccocSiw5.o:
  relocation R_X86_64_32S against `.data'
  can not be used when making a PIE object;
  recompile with -fPIE
```

Floating Point Operations

- The original Intel Chips 8086 **didn't have floating point ops**
- Had to buy a co-processor, Intel 8087, to add FP ops
- Modern CPUs ALL have FP ops but they feel separate from the integer ops: FP Unit versus AL Unit

FP "Media" Registers

256-bits	128-bits	Use
`%ymm0`	`%xmm0`	FP Arg 1/ Ret
`%ymm1`	`%xmm1`	FP Arg 2
...	...	...
`%ymm7`	`%xmm7`	FP Arg 8
`%ymm8`	`%xmm8`	Caller Save
...	...	...
`%ymm15`	`%xmm15`	Caller Save

- Can be used as "scalars" - single values but...
- `xmmI` is 128 bits big holding
  - 2 64-bit FP values OR
  - 4 32-bit FP values
- `ymmI` doubles this

Instructions

- Usually 3 operands:

  `C = B op A`

- Ex: Subtraction `vsubsd`, with `d` for 64-bit `double`

```
# xmm0 = xmm2 - xmm4
vsubsd %xmm2,%xmm4,%xmm0
```

- 3-operands common in modern assembly
- Can operate on single values or "vectors" of packed values

Floating Point and ALU Conversions

- Recall that bit layout of Integers and Floating Point numbers are quite different (**how?**)
- Leads to a series of assembly instructions to interconvert between types

```
# int eax = ...;
# double xmm0 = (double) eax;
vcvtsi2sd       %eax,%xmm0,%xmm0

# double xmm1 = ...
# long rcx = (int) xmm1;
vcvttsd2siq     %xmm1,%rcx
```

- These are non-trivial conversions: 5-cycle latency (delay) before completion, can have a performance impact on code which does conversions