

Assignment-3

Sanyam Kaul: CS23MTECH14011

Mayuresh Rajesh Dindorkar: CS23MTECH14007

Shrenik Ganguli: CS23MTECH14014

Sreyash Mohanty: CS23MTECH14015

Assumption

- Rank of A is n
- Initial feasible point is given

Instructions to execute code: -

- Kindly re-start the kernel every-time before running the code

```
In [25]: # =====
# Sanyam Kaul: CS23MTECH14011
# Mayuresh Rajesh Dindorkar: CS23MTECH14007
# Shrenik Ganguli: CS23MTECH14014
# Sreyash Mohanty: CS23MTECH14015
#
#
#
# Assumption
# 1. Polytope is non-degenerate.
# 2. Rank of A is n
# =====

import csv
import numpy as np
from numpy import linalg as la

class LO_Assignment_3():

    def __init__(self, A, B, C, z, m, n ):
        self.m = m
        self.n = n
        self.A = A
        self.B = B
        self.C = C
        self.eps = 1e-8
        self.X = z.reshape((n,1))

        self.check_dimensions(self.A, self.B, self.C, self.X, self.n, self.m)

    #validating input dimensions
    def check_dimensions(self, A, B, C, X, n, m):
        try:
            assert(A.shape == (m, n))
            assert(B.shape == (m, 1))
            assert(C.shape == (n, 1))
```

```

        assert(X.shape == (n, 1))
    except AssertionError:
        self._return_error()
    return

self.B = self.get_non_degenerate() # Making LP non degenerate
print(self.B)
if self.B is not None:
    print("Non-feasible problem\n") if self.n != np.linalg.matrix_rank(self

#checking non_degeneracy
def get_non_degenerate(self) -> np.ndarray:
    itr = 0
    while True:
        i = self.m - self.n
        B_ = self.B
        if (itr < 1000):
            # Perturbing B by adding noise

            B_[i] = self.B[i] + np.random.uniform(1e-6, 1e-5, size=(i,1))
            itr += 1

        else:
            # Checking for a Larger range
            B_[i] = self.B[i] + np.random.uniform(0.1, 10, size=(i,1))

        Z = np.dot(self.A, self.X) - B_
        inds = np.where(np.abs(Z) < self.eps)[0]
        if len(inds) == self.n: # Converted to non degenerate
            break
        print(itr)
    return B_

#checking feasibility of point
def check_point_feasibility(self, A, X, B):
    return np.all(np.dot(A, X) <= B)

#checking if any constraint is tight
def check_any_constraint_tight(self, A, X, B):
    return True if np.any(B - np.dot(A, X) < pow(10, -4)) else False

#method to approach polytope boundary
def approach_polytope_boundary(self, A, X, B, C):

    dir_vec = C
    alpha = 0.01
    while not self.check_any_constraint_tight(A, X, B):
        if not self.check_point_feasibility(A, (X + alpha * dir_vec), B):
            alpha /= 10
        else:
            print('\nApproaching boundry: -\n')
            cost = np.dot(X.T, C)
            print(f"X: {X.ravel()}\t Cost: {cost.ravel()}")
            X = X + alpha * dir_vec
            print(f"New point- {X} \t Cost: {cost}")

    return X

def obtain_initial_vertex(self, A, B):
    rank = la.matrix_rank(A)
    initial_vertex = np.dot(la.pinv(A[:rank]), B[:rank])
    return initial_vertex

def calculate_alpha_value(self, A, X, B, C):
    get_independent_rows = lambda A, X, B: (B - np.dot(A, X) < self.eps).T[0]

```

```

lin_ind = A[get_independent_rows(A, X, B)]
alpha = np.dot(la.pinv(lin_ind.T), C)
return alpha

def calculate_beta(self, A, X, B, is_min_ratio_positive, min_ratio):
    beta = np.min(((B - np.dot(A, X)).T[0] / min_ratio + 1e-12)[is_min_ratio_pos
    return beta

#checking vertex optimality
def find_optimal_vertex(self, A, X, B, C):
    if np.all(self.calculate_alpha_value(A, X, B, C) >= 0):
        calculated_cost = np.dot(X.T, C).ravel()
        print(f'X: {X.ravel()}\t cost: {calculated_cost}')
        return X
    get_independent_rows = lambda A, X, B: (B - np.dot(A, X) < pow(10, -4)).T[0]
    tight_rows_matrix = get_independent_rows(A, X, B)
    direction_matrix = -la.pinv(A[tight_rows_matrix])
    cost_list = []
    for i in range(0, direction_matrix.shape[1], 1):
        direction_vector = direction_matrix[:, i].reshape(-1, 1)
        min_ratio = (np.dot(A, direction_vector)).T
        is_min_ratio_positive = min_ratio > 0
        if np.any(is_min_ratio_positive):
            beta = self.calculate_beta(A, X, B, is_min_ratio_positive, min_ratio)
            z_prime = X + direction_vector * beta
            calculated_cost = np.dot(z_prime.T, C)
            cost_list.append((calculated_cost, i, z_prime))
            print(f'Z_prime: {z_prime.ravel()}\t cost: {calculated_cost}')
        else:
            print("This is unbounded case\n")
            return []

    _, index, z_prime = max(cost_list)
    return self.find_optimal_vertex(A, z_prime, B, C)

#method to run simplex algorithm
def execute_simplex_algo(self):
    temp_A, temp_B, temp_C = self.A, self.B, self.C
    if self.X.shape != self.C.shape:
        temp_A = np.append(np.append(self.A, np.zeros((1, self.n))), axis = 0),
        temp_A[-1][-1] = -1
        temp_B = np.append(self.B, [abs(min(self.B))], axis = 0)
        temp_C = np.zeros((self.n + 1, 1))
        temp_C[-1] = 1

    self.X = self.approach_polytope_boundary(temp_A, self.X, temp_B, temp_C)
    print('Reached polytope boundary, now approaching vertex: -\n')
    self.X = self.obtain_initial_vertex(temp_A, temp_B)
    opt_vertex = self.find_optimal_vertex(temp_A, self.X, temp_B, temp_C)
    if len(opt_vertex) == 0:
        print('Polytope is unbounded- optimal value does not exist\n')
    else:
        print(f'Optimal vertex: {self.X.T[0]}\n')

#method to read csv file
def read_linear_programming_input(file_path):
    with open(file_path, 'r') as file:
        reader = csv.reader(file)
        data = list(reader)

# Extracting data
z = np.array([float(x) for x in data[0][:-1]])
c = np.array([float(x) for x in data[1][:-1]])
b = np.array([float(x) for x in [row[-1] for row in data[2:]]])

```

```

A = np.array([[float(x) for x in row[:-1]] for row in data[2:]])
return z, c, b, A

# main method
def main():
    #input test case file here
    file_path = 'Assignment3.csv'
    z, C, B, A = read_linear_programming_input(file_path)

    print(f'Initial feasible point z: {z}\t Cost Vector C: {C}\n')
    print(f'Constraint Vector B: {B}\n')
    print(f'Co-efficient Matrix A:\n {A}')

    m = A.shape[0]
    n = A.shape[1]
    B = B.reshape((m,1))
    C = C.reshape((n,1))

    LO_Assignment_3(A, B, C, z, m, n)

if __name__=="__main__":
    main()

```

Initial feasible point z: [0. 0.] Cost Vector C: [1. 2.]

Constraint Vector B: [1. 4. 0. 0.]

Co-efficient Matrix A:

```

[[ 1. -3.]
 [-1.  2.]
 [-1.  0.]
 [ 0. -1.]]
[[1.00000418]
 [4.00000283]
 [0.         ]
 [0.         ]]

```

Reached polytope boundary, now approaching vertex: -

```

Z_prime: [-14.00001685 -5.00000701]      cost: [[-24.00003087]]
Z_prime: [-3.40000449e+01 -5.77315973e-14]      cost: [[-34.00004489]]
This is unbounded case

```

Polytope is unbounded- optimal value does not exit

In []: