1. You can cd to “/var/log” and see there are some log files.



2. When you cat out the file, you’ll see a lot of data will shown on your screen. Let’s search for the log that we log in today.

```
[root@localhost audit]# ausearch -m LOGIN --start today
```

3. Now, we’re going to see if someone touches the sshd file and see using the “auditctl” command.

```
[root@localhost audit]# auditctl -w /etc/ssh/sshd_config -p rwxa -k sshd_tag
```

4. Now, let’s make some logs on sshd file and see if it’ll make some logs. The command you need to run and the result is shown below.

```
[root@localhost audit]# ausearch -f /etc/ssh/sshd_config _
```



5. You can get your log summary by using the command “aureport”.

```
[root@localhost audit]# aureport

Summary Report
======================
Range of time in logs: 12/31/1969 19:00:00.000 - 04/11/2024 11:48:42.254
Selected time for report: 12/31/1969 19:00:00 - 04/11/2024 11:48:42.254
Number of changes in configuration: 1896
Number of changes to accounts, groups, or roles: 22
Number of logins: 119
Number of failed logins: 9
Number of authentications: 309
Number of failed authentications: 11
Number of users: 3
Number of terminals: 8
Number of host names: 3
Number of executables: 18
Number of commands: 12
Number of files: 3
Number of AVC's: 0
Number of MAC events: 125
mber of failed syscalls: 2
mber of anomaly events: 0
mber of responses to anomaly events: 0
Number of crypto events: 1495
Number of integrity events: 0
Number of virt events: 0
Number of keys: 1
Number of process IDs: 708
Number of events: 6761

[root@localhost audit]#
```

6. You can also use -f option to filter only for files.

```
[root@localhost audit]# aureport -f

File Report
===============================================
# date time file syscall success exe auid event
===============================================
1. 04/11/2024 11:47:27 /etc/ssh/sshd_config 2 yes /usr/bin/cat 0 2043
2. 04/11/2024 11:47:42 /etc/ssh/sshd_config 2 yes /usr/bin/vi 0 2044
3. 04/11/2024 11:47:42 /etc/ssh/sshd_config 89 no /usr/bin/vi 0 2045
4. 04/11/2024 11:48:42 /etc/ssh/sshd_config 191 no /usr/bin/vi 0 2046
5. 04/11/2024 11:48:42 /etc/ssh/ 82 yes /usr/bin/vi 0 2047
6. 04/11/2024 11:48:42 /etc/ssh/ 2 yes /usr/bin/vi 0 2048
7. 04/11/2024 11:48:42 /etc/ssh/sshd_config 191 yes /usr/bin/vi 0 2049
8. 04/11/2024 11:48:42 /etc/ssh/sshd_config 188 yes /usr/bin/vi 0 2050
9. 04/11/2024 11:48:42 /etc/ssh/sshd_config 90 yes /usr/bin/vi 0 2051
10. 04/11/2024 11:48:42 /etc/ssh/sshd_config 188 yes /usr/bin/vi 0 2052
[root@localhost audit]# _
```

7. You can also put –summary to make it more organized. You can also use -x option to filter the execution.

```
[root@localhost audit]# aureport -f --summary

File Summary Report
===========================
total  file
===========================
10  /etc/ssh/sshd_config
3  /etc/ssh/
1  /etc/ssh/sshd_config~
[root@localhost audit]# aureport -x --summary

Executable Summary Report
================================
total  file
================================
2844  /usr/sbin/sshd
1333  /usr/sbin/xtables-multi
1248  /usr/lib/systemd/systemd
285  /usr/sbin/ebtables-restore
248  /usr/bin/python2.7
  2  /usr/bin/kmod
  3  /usr/bin/login
     /usr/lib/systemd/systemd-update-utmp
42  /usr/sbin/crond
41  /usr/bin/sudo
12  /usr/sbin/groupadd
9  /usr/bin/vi
8  /usr/sbin/useradd
5  /usr/sbin/load_policy
3  /usr/sbin/sshd;5dd19d3c (deleted)
3  /usr/sbin/sshd;65a698a9 (deleted)
2  /usr/sbin/pam_tally2
1  /usr/bin/cat
[root@localhost audit]# _
```

8. This “auditctl” command will only watch this time but, it will not automatically run when you restart the server. There is a directory in the etc folder which controls the “auditctl” commands. You will see the options that automatically run which are stored in the rule.d folder.

```
[root@localhost audit]# cat audit.rules
## This file is automatically generated from /etc/audit/rules.d
-D
-b 8192
-f 1

[root@localhost audit]#
```

9. Let’s edit the file using vi.

```
[root@localhost rules.d]# vi /etc/audit/rules.d/audit.rules
```

```
## First rule - delete all
-D

## Increase the buffers to survive stress events.
## Make this bigger for busy systems
-b 8192

## Set failure mode to syslog
-f 1

-w /etc/ssh/sshd_config -p rwxa -k sshd_tag_
```