


DECA

Section	Title	Page
01.0	Design Introduction	
1.01	Cover Page	1
1.02	Block Diagram	2
02.0	MAX 10 10M50DAF484	
02.01	MAX 10 BANK1 & BANK2	3
02.02	MAX 10 BANK3 & BANK4	4
02.03	MAX 10 BANK5 & BANK6	5
02.04	MAX 10 BANK7 & BANK8	6
02.05	MAX 10 Clocks & Configuration	7
02.06	MAX10 Power & GND	8
02.07	MAX10 Decoupling	9
03.0	Clock	
03.01	Clock	10
04.0	JTAG	
04.01	USB Blaster II	11
05.0	Expansion Port	
05.01	Expansion Headers - BBB Headers	12
06.0	Memory	
06.01	DDR3 SDRAM & QSPI Flash	13
06.02	SD Card	14

09.02

Section	Title	Page
07.0	Video & Audio	
07.01	MIPI Interface	15
07.02	HDMI TX	16
07.03	Audio CODEC	17
08.0	Ethernet	
08.01	Ethernet	18
09.0	USB PHY	
09.01	USB PHY	19
10.0	Analog Interface	
10.01	SMA Connectors & Differential Amplifier	20
11.0	Sensors	
11.01	Accelerometer	21
11.02	Gesture, Humidity, Temperature Sensors	22
12.0	User Interface	
12.01	LED & BUTTON & SWITCH	23
13.0	System Power	
13.01	1.2V & 1.5V & 1.8V & 5V	24
13.02	2.5V & 2.8V & 3.3V	25




CAD Notes:
1. Put all the 1pF caps close to each MAX10 analog pin.
2. Route the analog input signal adjacent to the REFGND.

MIPI Interface



MIPI Control Interface




MIPI I2C Interface







Audio LINE-IN to MAX10 ADC




Ethernet




Header Analog Input



QSPI Flash




Header GPIO




Temperature Sensor



Humidity and Temperature Sensor




Gesture Sensor



Power Monitor



CapSense Buttons




Micro SD Card




U1B

MAX 10 BOTTOM BANKS




10M50DAF484C6GES


Micro SD Card




Audio CODEC Interface







Audio Control Interface










SWITCH






KEY




terasic			Copyright (c) 2014 by Terasic Technologies Inc. Taiwan. All rights reserved. No part of this schematic design may be reproduced, duplicated, or used without the prior written permission of Terasic.		
Title					
DECA					
Size	Document Number				Rev
B	MAX 10 Bank 5 & 6				C
Date:	Thursday, May 21, 2015		Sheet	5	of 25









VCC1P2_VCC




VCC1P2_VCCD




VCC2P5_VCCA




VCC1P5_DDR3




VCC1P2




VCC1P8





VCC2P5






VCC3P3







		Copyright (c) 2014 by Terasic Technologies Inc. Taiwan. All rights reserved. No part of this schematic design may be reproduced, duplicated, or used without the prior written permission of Terasic.			
Title					
DECA					
Size	Document Number		Rev		
B	MAX10 Decoupling		C		
Date:	Wednesday, March 11, 2015	Sheet	9 of 25		



















MIPI Interface






MIPI Control Interface









Default :
I2C Address 0x30/31




D
C
B
A







Notes:
Amplifier output voltage $V_o = (6.25 + V_{in})/5$




Notes:
Amplifier output voltage $V_o = (6.25 + V_{in})/5$






Copyright (c) 2014 by Terasic Technologies Inc. Taiwan. All rights reserved. No part of this schematic design may be reproduced, duplicated, or used without the prior written permission of Terasic.		
Title		
DECA		
Size	Document Number	Rev
B	SMA Connectors & Difference Amplifier	C
Date:	Friday, May 15, 2015	Sheet 20 of 25



Proximity/Ambient Light Sensor





Power up Sequence:
 5V -->3.3V--->1.5V--->1.8V
 --->2.5V--->1.2V--->2.8V

