

Evaluating distribution choices

MONTE CARLO SIMULATIONS IN PYTHON



Izzy Weber

Curriculum Manager, DataCamp

Choosing variable probability distributions

1. Gain an intuitive understanding of data and available probability distributions
2. Use Maximum Likelihood Estimation (MLE) to compare candidate distributions
3. Use Kolmogorov-Smirnov test to evaluate *goodness of fit* of probability distributions
 - Quantifies distance between the empirical distribution of the data and the theoretical candidate probability distribution
 - Use `scipy.stats.kstest()` to calculate

Evaluating choice of distribution: age

```
results = []
list_of_dists = ["laplace", "norm", "expon"]
for i in list_of_dists:
    dist = getattr(st, i)
    param = dist.fit(dia["age"])
    result = st.kstest(dia["age"], i, args=param)
    print(result)
```

Results for Laplace, normal, and exponential distributions in that order:

```
KstestResult(statistic=0.09511179937112832, pvalue=0.0006239579389182981)
KstestResult(statistic=0.0615913626181368, pvalue=0.06703225234359811)
KstestResult(statistic=0.2536037941921312, pvalue=1.5202547969084796e-25)
```

Evaluating choice of distribution: age

Results for Laplace, normal, and exponential distributions in that order:

```
KstestResult(statistic=0.09511179937112832, pvalue=0.0006239579389182981)  
KstestResult(statistic=0.0615913626181368, pvalue=0.06703225234359811)  
KstestResult(statistic=0.2536037941921312, pvalue=1.5202547969084796e-25)
```

Evaluating choice of distribution: tc blood serum

```
results = []  
list_of_dists = ["laplace", "norm", "expon"]  
for i in list_of_dists:  
    dist = getattr(st, i)  
    param = dist.fit(dia["tc"])  
    result = st.kstest(dia["tc"], i, args=param)  
    print(result)
```

Results for Laplace, normal, and exponential distributions in that order:

```
KstestResult(statistic=0.06435779928393615, pvalue=0.04915329841106708)  
KstestResult(statistic=0.051165295747227724, pvalue=0.19085587687385897)  
KstestResult(statistic=0.3318461436889846, pvalue=7.018486943525e-44)
```

Let's practice!

MONTE CARLO SIMULATIONS IN PYTHON

Visualizing simulation results

MONTE CARLO SIMULATIONS IN PYTHON



Izzy Weber

Curriculum Manager, DataCamp

Answering questions using Monte Carlo simulations

What are the differences in the predicted y values for people who are in the fourth quartile of each predictor compared to the first quartile?

Starting with the simulated results

```
df_summary.head()
```

	age	bmi	bp	tc	ldl	hdl	tch	ltg	glu	predicted_y
0	54.491842	32.512362	82.131464	203.075420	114.043050	44.820017	5.137683	5.254633	100.815909	209.297688
1	66.380490	29.380708	98.810054	136.474760	68.457982	51.691298	3.455412	4.572478	96.117969	177.081339
2	59.003285	27.015225	92.195168	242.796424	126.541644	86.050629	2.423928	4.640063	87.485747	123.192425
3	34.803821	20.961365	86.852597	168.762268	110.113823	53.158621	3.925988	4.080205	79.187999	84.284908
4	56.732615	32.682115	118.384860	226.152964	136.838283	46.467736	4.376397	5.374001	104.184429	244.900141

Answering our question

```
dic_diffs = {}
for var in ["age", "bmi", "bp", "tc", "ldl", "hdl", "tch", "ltg", "glu"]:
    var_q25 = np.quantile(df_summary[var], 0.25)
    var_q75 = np.quantile(df_summary[var], 0.75)
    q75_outcome = np.mean(df_summary[(df_summary[var] > var_q75)]["predicted_y"])
    q25_outcome = np.mean(df_summary[(df_summary[var] < var_q25)]["predicted_y"])
    y_diff = q75_outcome - q25_outcome
    dic_diffs[var] = [y_diff]
df_diffs = pd.DataFrame.from_dict(dic_diffs)
df_diffs.head()
```

	age	bmi	bp	tc	ldl	hdl	tch	ltg	glu
0	36.721	114.462	87.101	42.625	35.413	-77.653	82.835	105.611	74.744

Simulating 1,000 times


```
df_diffs.head()
```

	age	bmi	bp	tc	ldl	hdl	tch	ltg	glu
0	30.045	108.973	81.107	36.728	31.060	-75.885	79.829	101.231	67.215
1	36.860	112.486	86.164	39.596	33.970	-71.609	77.367	100.964	72.301
2	30.387	110.651	79.972	44.655	39.583	-74.377	82.354	103.808	71.804
3	35.047	113.609	83.241	34.706	23.764	-75.798	83.070	102.119	75.230
4	31.050	109.022	81.727	41.590	31.136	-73.955	80.866	101.668	74.225

- This DataFrame has 1,000 rows: one row for each set of mean difference from each of the 1,000 simulations


Pairplot

```
sns.pairplot(df_diffs)
```




Pairplot

```
sns.pairplot(df_diffs)
```



Clustermap

```
sns.clustermap(df_diffs.corr())
```



Converting to long format


- DataFrames in long format often contain two columns: the variable name and the other the corresponding value

```
df_diffs_long=df_diffs.melt(value_name="y_diff",  
                             value_vars=["age", "bmi", "bp", "tc", "ldl", "hdl",  
                                           "tch", "ltg", "glu"])  
  
df_diffs_long.head()
```

	variable	y_diff
0	age	30.045
1	age	36.860
2	age	30.387
3	age	35.047
4	age	31.050

Boxplot

```
sns.boxplot(x="variable", y="y_diff", data=df_diffs_long)
```



Let's practice!

MONTE CARLO SIMULATIONS IN PYTHON

Sensitivity analysis

MONTE CARLO SIMULATIONS IN PYTHON



Izzy Weber

Curriculum Manager, DataCamp

Sensitivity analysis

- Helps us understand the impact of the range of inputs
- Illustrates the patterns or trends when summarized in tables or plots

If we increase or decrease the values for `bmi` and `hdl` using a Monte Carlo simulation, how will the predicted y values (disease progression) change?

Defining the parameters

```
cov_dia = dia[["age", "bmi", "bp", "tc", "ldl", "hdl", "tch", "ltg", "glu"]].cov()  
mean_dia = dia[["age", "bmi", "bp", "tc", "ldl", "hdl", "tch", "ltg", "glu"]].mean()
```

Defining the simulation function

```
def simulate_bmi_hdl(cov_dia, mean_list):
    list_ys = []
    for i in range(50):
        simulation_results = st.multivariate_normal.rvs(mean=mean_list,
                                                         size=500, cov=cov_dia)

        df_results = pd.DataFrame(simulation_results,
                                   columns=["age", "bmi", "bp", "tc", "ldl", "hdl", "tch", "ltg", "glu"])

        predicted_y = regr_model.predict(df_results)
        df_y = pd.DataFrame(predicted_y, columns=["predicted_y"])
        df_summary = pd.concat([df_results, df_y], axis=1)
        y = np.mean(df_summary["predicted_y"])
        list_ys.append(y)
    return(np.mean(list_ys))
```

Perform simulations with a range of input parameters

```
hdl = []
bmi = []
simu_y = []
for mean_hdl_inc in np.arange(-20, 50, 30):
    for mean_bmi_inc in np.arange(-7, 11, 3):
        mean_list = mean_dia + np.array([0, mean_bmi_inc, 0, 0, 0, mean_hdl_inc, 0, 0, 0])
        hdl.append(mean_hdl_inc)
        bmi.append(mean_bmi_inc)
        mean_y = simulate_bmi_hdl(cov_dia, mean_list)
        simu_y.append(mean_y)
df_sa = pd.concat([pd.Series(hdl), pd.Series(bmi), pd.Series(simu_y)], axis=1)
df_sa.columns = ["hdl_inc", "bmi_inc", "y"]
```


Styled DataFrames of sensitivity analysis results

```
df_sa.sort_values(by=['hdl_inc', 'bmi_inc']).pivot(index='hdl_inc',  
                                                  columns='bmi_inc',  
                                                  values='y').style.background_gradient(  
    cmap=sns.light_palette("red", as_cmap=True))
```


bmi_inc	-7	-4	-1	2	5	8
hdl_inc						
-20	128.313347	146.788965	165.237888	183.925198	202.439964	220.860332
10	99.150789	117.993128	136.040590	154.108108	173.100882	191.778971
40	70.351470	89.323106	106.627512	125.809040	144.166632	162.095737

Hexbin plot for sensitivity analysis results

```
df_sa.plot.hexbin(x='hdl_inc', y='bmi_inc', C='y',  
                  reduce_C_function=np.mean,  
                  gridsize=10, cmap="viridis",  
                  sharex=False)
```



Hexbin plot for dense parameter space




Let's practice!

MONTE CARLO SIMULATIONS IN PYTHON

Congratulations!

MONTE CARLO SIMULATIONS IN PYTHON



Izzy Weber
Curriculum Manager, DataCamp

What we've covered

- What Monte Carlo simulations are and why they are useful
- Sampling from probability distributions as the basis for Monte Carlo simulations
- The steps of performing Monte Carlo simulations
- How to further evaluate and interpret simulation results

Tips on further learning

1. **Continue learning about statistics**
 - DataCamp skill track: Statistics Fundamentals with Python
2. **Expand on your data visualization skills**
 - Introduction to Data Visualization with Seaborn
 - Intermediate Data Visualization with Seaborn

Thank you!

MONTE CARLO SIMULATIONS IN PYTHON