

# ODATA INTERVIEW QUESTIONS AND ANSWER MADE EASY

By Pankaj Kumar  
ABAP | OOPS ABAP | ABAP ON  
HANA | ODATA | ALE IDOC Trainer  
Email – [pankajkumaram@gmail.com](mailto:pankajkumaram@gmail.com)  
--Training is my Passion  
Website: [www.saptechmadeeasy.com](http://www.saptechmadeeasy.com)



## **Morning ABAP Ritual – Get Mastery in ABAP related Technology**

### **Why ABAP Ritual?**

- ❖ **Self growth**
- ❖ **No Ignorance – Never ignore your potential**
- ❖ **Self esteem and Self confidence**
- ❖ **Be Competent in the Market Place**
- ❖ **Get Mastery In Interview Questions and Answer**
- ❖ **Have Strong Fundamentals**
- ❖ **Be more productive and Effective in Daily Project work**
- ❖ **Help and Contribution**
- ❖ **Health**

## Affirmation

- ❖ Easy and Frequently Asked question – Never Ignore.
- ❖ Niche Question – Have regular practice
- ❖ Facebook/WhatsApp/Instagram/or Any Social Media – Use Intelligently
- ❖ Declutter the Digital Space – Turn off the unnecessary notification( **unroll.me** )
- ❖ **Soft Skill(80%)** is more important the **Technical Skill(20%)**
- ❖ **Helping** and **Contributing** to society is the key for success
- ❖ Health( Physical and Mental Health) – **Never ignore**
  - ❖ Physical Health – Yoga, Walking, Gym, Marathon, Game etc.
  - ❖ Mental Health – Pranayama, Meditation, Spiritual Practices, Association with the right people

**1**

ABAP in Detail

OOPS ABAP in Detail

ABAP ON HANA in Detail

GOOGLE CHROME  
LIST OF ALL PURCHASE  
ORDER



S  
A  
P  
G  
A  
T  
E  
W  
A  
Y



APPLICATION  
SERVER



DATABASE

## OData Interview Questions And Answer


Protocol -> set of rules

Web Services?

->One which provides the service on the web / to the web

What is web service?

How web services generated by protocol



Web services

SOAP PROTOCOL

Xml( WSDL )  
http/ftp/smtp

ENVELOP  
MORE SECURITY  
SLOWER  
HEAVY WEIGHT  
**STATEFUL SESSION**  
SIMPLE OBJECT ACCESS PROTOCOL

REST PROTOCOL

No WSDL( XML/JSON)/ EDMX  
http/https

POSTCARD  
LESS SECURITY  
FASTER  
LIGHTWEIGHT  
**STATELESS SESSION**  
REPRESENTATIONAL STATE TRANSFER

1995

ENVELOPE- ADDRESS

PAGE

## **What is Protocol?**

**Protocol is set of Rules**

## **What is web services?**

**One which serves the web.**

**OR**

**A service made for the Web**

**ODATA** stands for Open Data Protocol.

- It is open standard to send the data back and forth between two system via REST using HTTP
- It follows the REST standard
- ODATA Contains the Service document which is a collection of entity Sets.
- Each Entity set is used to perform the CRUD operation.
- An Entity set is used to create with the help of Entity Type
- Entity type is template( Blueprint ) of any entity set.




## Q. What is the SOAP ?

SOAP full form is Simple Object Access Protocol. It is a state full protocol with below characteristics -

- Like Envelope
- Inbuilt high security feature
- Heavy
- No Good Performance
- HTTP/SMTP/FTP etc.
- XML(WSDL) Based protocol
- State full

# An Illustration how SOAP works



# An Wikipedia Example of SOAP

## Example message (encapsulated in HTTP) [\[ edit \]](#)

The message below requests a stock price for AT&T (stock ticker symbol "T").

```
POST /InStock HTTP/1.1
Host: www.example.org
Content-Type: application/soap+xml; charset=utf-8
Content-Length: 299
SOAPAction: "http://www.w3.org/2003/05/soap-envelope"

<?xml version="1.0"?>
<soap:Envelope xmlns:soap="http://www.w3.org/2003/05/soap-envelope" xmlns:m="http://www.example.org">
  <soap:Header>
  </soap:Header>
  <soap:Body>
    <m:GetStockPrice>
      <m:StockName>T</m:StockName>
    </m:GetStockPrice>
  </soap:Body>
</soap:Envelope>
```

SOAP-ENV: Envelope

SOAP-ENV: Header

SOAP-ENV: Body

# What is REST?

- It is stateless protocol with below characteristics -
  - Like Post Card
  - No that much secured comparatively. Workaround is required
  - Light weight
  - Super Performance
  - Only HTTP
  - Architecture Based Protocol
  - Usage cookies to give the better user experience

## What is Stateless communication?

- The communication which doesn't store the user information in session permanently.
- When every time communication is established new session is loaded irrespective of previous session

## An Illustration of REST

Resource URI  
GET <https://www.amazon.co.uk/electronics/tv/modelno/SCX-100>

Service Consumer

REST Request

REST Response

Service Provider

XML Response

```
<...>
  <modelno>SCX-100</modelno>
  <name>Samsung Xenia</name>
  <Price>GBP 250</price>
  <category>OLED Flat</category>
  ....
  ....
<...>
```

# Soap VS REST

## SOAP

- Like Envelope
- Inbuilt high security feature
- Heavy
- No Good Performance
- HTTP/SMTP/FTP etc.
- State full

## REST


- Like Post Card
- No that much secured comparatively. Workaround is required
- Light weight
- Super Performance
- Only HTTP
- Stateless

# Example 1 – SOAP vs ODATA




# Example 2: SOAP Vs OData

REST



Post Card

SOAP



Envelop




# Technical Comparison



# Where does industry stands?

SAP UI technologies like  
Webdynpro, Portal, BSP  
Backend support for classical  
Suite, Java based Apps



SAP Latest UI Technology UI5  
and Fiori Usage REST based  
OData Services, Backend  
supported by SAP Gateway

Last 4 Slides:

Credit: Anubhav Sir – Videos

Link: - [https://www.youtube.com/watch?v=v\\_xPIRumdbE&t=34s](https://www.youtube.com/watch?v=v_xPIRumdbE&t=34s)

2

9<sup>th</sup> Feb

Why SAP needed OData?

Ans. Smooth, Fast and Great user Experience

What is the T-code to create an OData project?

VVI

Ans. SEGW

# What is Entity

Google Translation in Hindi

The screenshot shows the Google Translate interface. At the top, the word 'entity' is entered in the English input field, and its Hindi translation 'इकाई' (ikaee) is shown in the output field. Below this, under the heading 'Translations of entity', three Hindi words are listed with their corresponding English meanings: 'अस्तित्व' (existence, being, entity), 'सत्ता' (power, authority, entity, government), and 'सत्व' (entity, substance, nature, heart, core, keynote).

English Word	Hindi Word	Meaning
entity	इकाई	ikaee
Translations of <b>entity</b>		
noun		
	अस्तित्व	existence, being, entity
	सत्ता	power, authority, entity, government
	सत्व	entity, substance, nature, heart, core, keynote

- One which has real existence is known as Entity.
- Let us say Ram is described by the Characteristics ( Id, Name, Age ).
- These set of sequential characteristics( i.e. Tuple) is nothing but Entity because it is having real time existence.

## Entity

It is real time existing object

Employee – Entity Type

Id, Name, Age, Salary

Ram( 1, Ram, 20, 20000) - Entity 1

Mohan( 2, Mohan, 30, 30000) – Entity 2

Rohan( 3, Rohan, 40, 40000) – Entity 3

Q. What is the difference between Entity, Entity type and Entity set in OData?

### Entity

- It is something which has real existence.
- A tuple ( Name, Id, Age ) is having the real time existence. Hence it is called Entity
- Work Area

### Entity Type

- It is collection of entity having common attribute. As in Student table each row is an entity and have common attributes. So **STUDENT** is an entity type which contains entities having attributes id, name and Age
- It is like “Types”

### Entity Set

- It is a set of entities of same entity type. so a set of one or more entities of Student Entity type is an Entity Set.
- It is like “Internal Table”



Are you confused between Entity type and Entity set difference?

Let us make it very simple in layman term –

Entity Type: It is blue print / Structure for Entity set. Entity type must have key defined.

Entity Set: It is similar to Internal table of type “ENTITY TYPE”

In ODATA protocol the resources are exposed in which format?

Ans.

What is the other name of O Data ?

O Data is also known as ODBC of the Web


ODBC -> Open Database connectivity

What are the Gateway Deployment in order to generate the OData we have?

1. Hub Deployment

And

2. Embedded Deployment



If your system is on NW7.3 or Before what are the components need to be installed in order to enable the SAP Gateway?

Ans. -> There are three components –

1. GW\_CORE
2. IW\_FND
3. IW\_BEP

Q. If you are on NW7.4 onwards release which component need to be installed in order to enable the GW

Ans. SAP\_GWFND.

Q. How you will identify in your system if it is Hub Deployment or Embedded Deployment?

1. Go to SEGW.
2. Maintenance Service – if some artifact is there then that is Embedded otherwise it is HUB.

Session 3

10<sup>TH</sup> Feb

What is the t-Code to Register the Service?

VVI

Ans. /IWFND/MAINT\_SERVICE

What is the T-Code to Test the service?

Ans. /IWFND/GW\_CLIENT

What is the T-Code to Troubleshoot any error occurred?

Ans. /IWFND/ERROR\_LOG



Q. What are the classes generated when we create and activate a project?

Ans.

DPC

DPC\_EXT


MPC

MPC\_EXT

## Q. What is the Architecture of SAP OData?

### 4 Major Parts of SAP Odata-

- **OData Model**
  - Used to represent the data from different sources into single format
- **OData Service**
  - Odata Model is exposed using **Odata Services** using **Odata Protocol** and **Odata Libraries**
- **OData Protocol**
  - **Best on REST Principle**
- **OData Client Libraries**
  - Used by Browser of Client application to access the data using O Data Protocol



Session 4


**11-Feb**

## Q. What are the different way of generating O Data Service?


Ans.

1. **ABAP Code based Implementation** -> Write the Code in typically in DPC Extension Class
2. **Mapping Editor** -> In SEGW gateway builder, you can map an ABAP CDS Views as a data source to the entity type properties. SADL Framework will generate the O data Service to retrieve the data from CDS.

Using Service Generation



**3. Data References** -> Using the **Referenced Data Source** - In SEGW gateway builder, you can reference an ABAP CDS Views as a data source. **Each entity type in OData service model corresponds to 1 ABAP CDS view.**



#### 4. Using Annotation

**@Odata.publish: true**

Q. What is SADL?

Ans.

SADL – Service Adaptation Description Language

- This is a framework which generates the O Data service from the CDS

Below approaches uses SADL framework to generate service -

- @ODATA.PUBLISH: TRUE
- Mapping editor
- Data References

Q. What are the different methods for each entity set?



CURD

C-> CREATE

U-> UPDATE

R-> READ

D-> DELETE

CRUD

- **Create** – Includes the business logic to create data in the back-end system.
- **Delete** – to delete the data from the back-end system.
- **GetEntity(Read)** – to read the single record details from back-end system.
- **GetEntitySet(Query)** – to read the list of data from the back-end system
- **Update** - to update the data into back-end system.

Q. On top of which artifact you perform the CURD/CRUD operation?

1. Entity - NOT
2. Entity Type – Not
3. Entity Set - Yes



## Q. What is Function Import?

VVI

**Ans.**

- **Function Imports** are the actions like **release of a sales order/purchase order** executed in the back-end system.
- Function Imports can be used when ever the given requirement does not fit into the CRUD-Q operations.
- They are defined at service level and you can have N number of function imports functions.

Function import is a service operation in the Open Data Protocol (OData) that allows users to perform custom operations that are not supported by the standard CRUD (Create, Retrieve, Update, and Delete) operations.

FI\_PORELEASE  
ET\_eMPLOYEEseT

Q. In Odata, when you create and activate the project what are the classes generated?

There are 4 Classes generated –

1. **MPC** –
2. **MPC\_EXT** -> **Annotations**
3. **DPC**
4. **DPC\_EXT** -> **Write the logic to fetch the data**

**Note:** One Service and one Model also gets Created

Q. If you want to implement fetching logic for **header and item** which method need to be opted to write

VVI

Ans. **Get\_Expanded\_EntitySet**

VVI

Q. If you want to implement record creation logic for **header and item**, which method to be opted.

Ans. **Create\_Deep\_EntitySet**

## What are the HTTP methods

1. GET -> Read
2. POST -> Create New Record
3. PUT -> Update
4. **PATCH -> Modify**
5. DELETE -> Delete
6. **MERGE -> Modify**
7. HEAD ->

Patch -> This is the Actual HTTP Method. We are supposed to use the PATCH (SAP NetWeaver Gateway 2.0 SP05)

Merge -> it is given by Microsoft. Hence it is not global Standard. So the preferred approach should be PATCH.

Q. What is the Difference between **PUT**( Complete Update) and ( **PATCH/Merge** => Partial Update)

EmpId(Key)	EmpName	Age
1	Pankaj	35
2	Ram	40 → 58
3	Jitendra	35
4	Adi	28 → 39
5	Jayant	30

need to be whole record , if we need to update a one field or many

PUT=> Complete Replacement

Patch => partial Update

Only field which needs to be updated are required

There is difference in terms of how we use?

**PUT** -> From the front end we are supposed to pass all the fields content. In if some value is not supplied then, it will take the initial value.

**PATCH** -> In patch from the frontend , all the fields are not required. We can send only specific field which need to be updated.

Session 5

**12<sup>th</sup> Feb**

Q. What is the T-Code for Cache Clean Up?

Ans. /n/IWFND/CACHE\_CLEANUP

Q. What are the different way of cleaning the Cache?

Ans.

1. Globally for all the services in case we have central hub scenario—

/n/IWFND/CACHE\_CLEANUP -> Gateway ✓

/n/IWBEP/CACHE\_CLEANUP-> BACKEND

or IN case of Embedded Scenario-

/n/IWBEP/CACHE\_CLEANUP-> BACKEND

2. Specific to Service

/iwfnd/gw\_client-> More-> Metadata-> Clean up

3. Using Class method -

/iwfnd/cl\_sutil\_moni=>cleanup\_metadata\_cache ✓


Q. In case of Embedded Scenario, What is the T-Code to Clear the cache?

Ans. /n/IWBEP/CACHE\_CLEANUP

Method Signature:

```
/iwfnd/cl_sutil_moni=
>cleanup_metadata_c
ache(
  EXPORTING
    iv_mode      = 'A'
    iv_multi_origin = abap_true
    iv_namespace  = '/SAP/'
    iv_service_name = 'Your Service Name'
    iv_service_version = '0001'
  IMPORTING
    ev_error_text = lv_error_text
).
```

In this method, we make use of the TCodes /n/iwfnd/maint\_service and /n/iwfnd/gw\_client to clear our metadata cache. Follow the below steps:



To clear the metadata cache using the above process, for the Embedded implementation, it is enough to clear only on **the back end system**, but in Hub implementation, it is mandatory to clear the cache on both systems to properly clear the metadata cache.

**Q. When we have to clean the Cache?**

**Or**

**Q. When we need to clean up the Cache?**

**Ans.**

Whenever we do any changes at service level and those changes are not reflecting then we are supposed to do both type of Cache Cleanup.

When we add / delete / modify any property in the entity set or an annotation in the CDS or any BOPF functionality such as Creatable, Updatable or Delectable, then we need to clear the metadata cache for our changes to be visible in the Metadata.xml file of the OData service, which can then be consumed in any UI5 application.



Session 6

13-Feb-2020

Q. How to do file / Image handling in Odata?

VVI

Ans. Using **Stream Method**.

What are the different stream methods to create/Update/Read the image/file/pdf?

VVI

Ans.

- `/IWBEP/IF_MGW_APPL_SRV_RUNTIME~CREATE_STREAM.`
- `/IWBEP/IF_MGW_APPL_SRV_RUNTIME~GET_STREAM.`
- `/IWBEP/IF_MGW_APPL_SRV_RUNTIME~UPDATE_STREAM`

## What is Concurrency Control?

Ans. When at same time more than one people are going to perform some changes from UI side then need to implement the concurrency control in order to have the consistent data and not to have the data loss.

## How to handle concurrency?

In Odata we generally use the concept of Optimistic Concurrency control.  
Because O Data usage the HTTP method.  
HTTP method generally use the Optimistic Concurrency control.

This is handled using the E-Tag=> Entity Tag

UI5

PO	QUANT	MATERIAL
1234	300	SWEET SUGAR

Ram

ABCD123

SAP GATEWAY

EKPO

1234	400	SWEET SUGAR



ABCD123SUGAR

UI5

PO	QUANT	MATERIAL
1234	400	SWEET SUGAR

ABCD123SUGAR

E-TAG  
Entity Tag

Session 7

14-Feb-2020

What is the function module to generate the Hash Value for Etag?

Ans. FM is - **'CALCULATE\_HASH\_FOR\_RAW'**

Q. How to Troubleshoot if your break-point is not triggering which was already triggering sometimes back?

This is the steps we followed and started working

1. **Check if you have put the external break point**
2. Clean up the cache using the t-Code **/n/IWFND/CACHE\_CLEANUP** and **/n/IWBEP/CACHE\_CLEANUP**
3. **Srdebugger – Use this transaction in order to activate the remote debugger**
4. **Log out the session**
5. **Put the break point**
6. **Run the gateway client and check**

Q. What is the T-Code to take the Trace in Odata?

Ans. /n/IWFND/TRACES

Q. Suppose you want to delete the Odata Service. Is it possible to delete directly.

**Ans. No.**

Q. What error it gives?

**Ans. It will give the error – ICF Node will be deleted first**

**Note: when you will try to delete the ICF node it gives the error - “*Object directory entry cannot be deleted, the object is locked*”.**

Q. How to correct the “object is locked error”?

Ans. By deleting the System Alias

## Delete Service

Filter Add Service Delete Service Service Details Load Me

### Service Catalog

Type	Technical Service Name	V...	Service Description	External Ser
BEP	YPK_CDS_SO_SRV	1	ODATA FROM CDS VIEW	YPK_CDS_S
BEP	YPK_ODATA_CDS_CDS	1		YPK_ODAT.
BEP	Z_PK_SALES_ODATA_SRV	1	Sales Details	Z_PI
BEP	ZC_MATERIALPK_CDS	1		ZC_I
BEP	ZPK_C_FL_MEAL_CDS	1		ZPK
BEP	ZPK_CUSSTOMER_ORDER_DETAILS_SRV	1	Customer Order details	ZPK
BEP	ZPK_LTA_SRV	1	LTA	ZPK
BEP	ZPK_MEAL_APP_SRV	1	MEAL APP	ZPK

ICF Node

Call Browser

SAP Gateway Client

### ICF Nodes

Status	ICF Node	Session Time-out Soft State	Description
○○○	ODATA	00:00:00	Standard Mode

Turning Green To gray (White)

ICF Node

Call Browser

SAP Gateway Client

### ICF Nodes

Status	ICF Node	Session Time-out Soft State	Description
○○○	ODATA	00:00:00	Standard Mode

ICF Node

Call Browser

SAP Gateway Client

Activate

Deactivate

Delete

Configure (SICF)

Session Time-out Soft State

Description

00:00:00


Standard Mode



Q. What are the steps need to be performed in order to delete the service?

1. Delete the Alias
2. Delete the ICF Node
3. Delete the Service

Q. What is System Alias



Jitendra -> Jitu

Again Tried Deleting but different error

## Activate and Maintain Services

Service Catalog

Type	Technical Service Name	V...	Service Description	External Service Name
BEP	YPK_CDS_SO_SRV	1	ODATA FROM CDS VIEW	YPK_CDS_SO_SRV
BEP	YPK_ODATA_CDS_CDS	1		YPK_ODATA_CDS_CDS
BI				Z_PK_SALES_ODATA_SRV
BI				ZC_MATERIALPK_CDS
BI				ZPK_C_FL_MEAL_CDS
BI				ZPK_CUSSTOMER_ORDER_DE
BI				ZPK_LTA_SRV
BI				ZPK_MEAL_APP_SRV

Information

Service cannot be deleted, delete Destination Assignment(s) first

Session 8

**15<sup>th</sup> Feb**

## Navigation & Association

## EKKO – ET\_PO\_HEADER

PO	TOTAL PRICE	ADDRESS
1	200	
2	300	
3	400	

ET\_PO\_ITEM\_DESC

Po No.	Item	Material Desc
1	10	Big Laptop
1	20	Big Mouse, Black
1	30	CPU, i7 processor

1..N

## EKPO – ET\_PO\_ITEM

Po No.	Item	material
1	10	Laptop
1	20	Mouse
1	30	CPU

2	10	CHAIR
2	20	TABLE
2	30	ROUND TABLE

3	10	PRINTER
3	20	INK

Q. What is Navigation?

Ans. In case one Entity set is associated with multiple entity set, then in order to determine from which entity set, data need to be fetched is determined by navigation properties.

Q. What is Association?

Ans. It is a relationship between two entity with cardinality.

Q. What is the difference between cardinality 'M' and 'N' of dependent entity in **OData Association**?

Ans.      M => 0..n  
             N => 1..n

Q. What is Association and Navigation in OData

## SAP Gateway Service Builder

The screenshot displays the SAP Gateway Service Builder interface. On the left, a tree view shows the project structure for 'ZABAPRITUAL', including 'Data Model', 'Entity Types', 'Associations', and 'Entity Sets'. The 'Navigation Properties' folder under 'Et\_POHeader' is highlighted, and the 'HeadToItemNav' property is selected. Two arrows point from this selection to the 'Navigation Properties' and 'Associations' tables on the right. The 'Navigation Properties' table lists the navigation property 'HeadToItemNav' with its relationship name 'HeadToItemAss' and ABAP field name 'HEADTOITEMNAV'. The 'Associations' table lists the association 'HeadToItemAss' with principal entity 'Et\_POHeader' (cardinality 1) and dependent entity 'Et\_POItem' (cardinality N).

**Navigation Properties**

Name	Relationship Name	ABAP Field Name	Label
HeadToItemNav	HeadToItemAss	HEADTOITEMNAV	

**Associations**

Name	Ex.	Principal Entity	Principal Entity Cardinality	Dependent Entity	Dependent Entity Cardinality	Label
HeadToItemAss		Et_POHeader	1	Et_POItem	N	

## What are different frequently used **URI Notations?**

This is to get all the data from PO\_HEADER

`/sap/opu/odata/SAP/ZABAPRITUAL_SRV/Et_POHeaderSet`

Note: Name of the field should be used same as there in the properties

This is to get the specific header information

`/sap/opu/odata/SAP/ZABAPRITUAL_SRV/Et_POHeaderSet('4400000000')/`

This is how to fetch a single field

`/sap/opu/odata/SAP/ZABAPRITUAL_SRV/Et_POHeaderSet('4400000000')/Statu?$format=json`

Note: Name of the field should be used same as there in the properties

\*\*\*\*\*

Get number of entries - `/sap/opu/odata/SAP/ZABAPRITUAL_SRV/Et_POHeaderSet('4500000001')/$count`

\*\*\*\*\*

Extract only some fields of the Entity Type (\$select=Field1,Field2,Field3)

`/sap/opu/odata/SAP/ZABAPRITUAL_SRV/Et_POHeaderSet('4500000001')?$select=Ernam,Bukrs`

\*\*\*\*\*



Session 9

16 Feb 2021

**Get all the PO Items( ET\_POITEMSET\_GET\_ENTITYSET method should be implemented)**

**/sap/opu/odata/SAP/ZABAPRITUAL\_SRV/Et\_POItemSet**

\*\*\*\*\*

**Get the specific PO ITEM( ET\_POITEMSET\_GET\_ENTITY method should be implemented )**

**/sap/opu/odata/SAP/ZABAPRITUAL\_SRV/Et\_POItemSet(Ebeln='4500000002',Ebelp='00010')**

\*\*\*\*\*

**Get few fields:**

**/sap/opu/odata/SAP/ZABAPRITUAL\_SRV/Et\_POItemSet?\$select=Ebeln,Ebelp,Werks**

\*\*\*\*\*

**in json format**

**/sap/opu/odata/SAP/ZABAPRITUAL\_SRV/Et\_POItemSet?\$select=Ebeln,Ebelp,Werks&\$format=json**

\*\*\*\*\*

**get the count**

**/sap/opu/odata/SAP/ZABAPRITUAL\_SRV/Et\_POItemSet/\$count**

\*\*\*\*\*

**Access a specific field**

**/sap/opu/odata/SAP/ZABAPRITUAL\_SRV/Et\_POItemSet(Ebeln='4500000000',Ebelp='00010')/Menge**

\*\*\*\*\*

**Multiple Values**

**/sap/opu/odata/SAP/ZABAPRITUAL\_SRV/Et\_POHeaderSet('5815000026')/HeadToItemNav?\$format=json**

**/sap/opu/odata/SAP/ZABAPRITUAL\_SRV/Et\_POHeaderSet('5815000026')/?\$expand=HeadToItemNav&\$format=json**

**Q: What is the difference between the below two URIs?**

1. `/sap/opu/odata/SAP/ZABAPRITUAL_SRV/Et_POHeaderSet('5815000026')/HeadToItemNav`
2. `/sap/opu/odata/SAP/ZABAPRITUAL_SRV/Et_POHeaderSet('5815000026')/?$expand=HeadToItemNav`

Session 10

**17<sup>TH</sup> Feb**

**/sap/opu/odata/SAP/ZABAPRITUAL\_SRV/ => Resource Root**  
**Et\_POItemSet(Ebeln='4500000002',Ebelp='00010') => Resource**  
**?**

**/sap/opu/odata/SAP/ZABAPRITUAL\_SRV/ => Resource Root**

**Et\_POItemSet => Resource Name**

**? \$select=Ebeln,Ebelp,Werks => Query String**

## What are the different Query Option?

DPC_EXT Method	OData Query (URI)	DPC_EXT Method Key Parameter(s)
_GET_ENTITYSET	<ENTITYSET Path> = /sap/opu/odata/sap/<SERVICE NAME>/<ENTITYSET Name>	<b>Export:</b> ET_ENTITYSET
_GET_ENTITYSET	<ENTITYSET Path>?\$format=json	
_GET_ENTITYSET	<ENTITYSET Path>?\$filter=<Entity Property1> eq <value> and <Entity Property2> eq <value> <ENTITYSET Path>?\$filter= Ebeln eq '4000000' and Bukrs = 'IN50'	<b>Import:</b> IT_FILTER_SELECT_OPTIONS and IV_FILTER_STRING <b>Export:</b> ET_ENTITYSET
_GET_ENTITYSET	<ENTITYSET Path>?\$orderby=<Entity Property1>,<Entity Property2> /sap/opu/odata/sap/<SERVICE NAME>/<ENTITYSET Name>?\$orderby= <b>Ebeln,Bukrs OR</b> <ENTITYSET Path>?\$orderby=<Entity Property1> desc,<Entity Property2> desc	<b>Import:</b> IT_ORDER <b>Export:</b> ET_ENTITYSET

_GET_ENTITYSET	<ENTITYSET Path>?\$search=<value>	<b>Import:</b> IV_SEARCH_STRING <b>Export:</b> ET_ENTITYSET
_GET_ENTITYSET	<ENTITYSET Path>?\$stop=<value> Or <ENTITYSET Path>?\$stop=1000&\$skip=10	<b>Import:</b> IS_PAGING-TOP <b>Export:</b> ET_ENTITYSET
_GET_ENTITY	<ENTITYSET Path>(<Entity Property>='value') <b>OR</b> <ENTITYSET Path>('value')	<b>Import:</b> IT_KEY_TAB <b>Export:</b> ER_ENTITY
_GET_ENTITY	In case if we had association and navigation between 2 entities	<b>Import:</b> IT_NAVIGATION_PATH <b>Export:</b> ER_ENTITY
_EXPANDED_ENTITY	ReosouceRoot/<ENTITYSET Name1>(<'value'>)/<ENTITYSET Name2> <b>OR</b> ResourceRoot/<ENTITYSET Name1>(<'value'>) ?\$expand=<ENTITYSET Name2>	<b>Import:</b> IV_ENTITY_NAMEIV_ENTITY_S ET_NAMEIT_NAVIGATION_PAT HIT_KEY_TAB <b>Export:</b> ER_ENTITYSET

## What are the different status codes and their Meaning?

Status Code	Text	Cause
200	OK	The request is successfully executed by GET method
201	OK	The request is successfully executed by POST method
203	OK	The request is successfully executed by UPDATE method
204	OK	The request is successfully executed by DELETE method
400	Bad Request	The request could not be parsed successfully because of a syntactically or semantically incorrect URI.
401	Unauthorized	Authentication is required and has not been provided.
403	Forbidden	User does not have privileges to access the entity
404	Record Not Found	The record does not exist for the given query.
405	Method Not Allowed	A request cannot be used for this record.
406	Not Acceptable	Self-explanatory
500	Internal Server Error	Internal Error
501	Not Implemented	Not Implemented
502	Bad Gateway	Gateway issue
503	Service Unavailable	Self-explanatory



Entity Name, Entity Type and Entity Sets are case sensitive or not?

Ans. - Yes

What is the difference between Bad request and Bad Gateway?

Ans.

Bad Request(400) – Incorrect URI

Bad Gateway(502) – SAP NW Issue

**Session 11**



18t – Feb

## Q. What is Batch Call Processing?

VVI


If you want to perform the multiple operations on a single or multiple entity together then we go for Batch Call Processing.

It helps to improve the performance and to maintain the data integrity and consistency while processing. It gets processed normally in parallel





Q. What HTTP method need to be called in order to call the Batch Processing?

Ans. POST



Q. Where we can define the number of parallel queries for Batch Call processing?

Ans.



In case if you want to disable the activation of parallel batch request, how to do?

Program Edit Goto System Help

/o/IWBEP/REG\_SERVICE


### Maintain Service

Delete Service

Technical Service Name /CPD/SC\_PROJ\_ENGMT\_CREATE\_UPD\_SRV

Service Version 1

Display Change Create



Program Edit Goto System Help

Configuration

### Display Service

Cleanup Cache Configuration

Service Information

Technical Service Name	/CPD/SC_PROJ_ENGMT_CREATE_UPD_SRV
Service Version	1
Description	External Service for Engagement Project
External Service Name	SC_PROJ_ENGMT_CREATE_UPD_SRV
Namespace	/CPD/



### Change Configuration

Service Information

Technical Service Name	/CPD/SC_PROJ_ENGMT_CREATE_UPD_SRV
Service Version	1

Service Settings

☐ Deactivate Soft-State based Query Result Cache

☒ Deactivate Parallelization of Batch Requests

Protocol HTTP HTTPS Test Group ZRM\_TESTCASE Test

HTTP Request

Header Name	Value
Content-Type	multipart/mixed;boundary=batch_00567
X-CSRF-Token	uEzjmAE-ZKr-ZKXHeZ22Bg==

**FOR BATCH START CONTENT TYPE HEADER**

```
1 --batch_00567
2 Content-Type: application/http
3 Content-Transfer-Encoding: binary
4
5 GET ZEMPLOYEE_DETAILSet(EmpId='0000000001') HTTP/1.1
6
7
8 --batch_00567
9 Content-Type: application/http
10 Content-Transfer-Encoding: binary
11
12 GET ZEMPLOYEE_DETAILSet(EmpId='0000000002') HTTP/1.1
13
14
15 --batch_00567
16 Content-Type: multipart/mixed; boundary=changeset
17
18 --changeset
19 Content-Type: application/http
20 Content-Transfer-Encoding: binary
```

**FOR CHANGESET CONTENT TYPE HEADER**

Source:

<https://blogs.sap.com/2018/05/06/batch-request-in-sap-gateway/>

```
15 --batch 00567
16 Content-Type: multipart/mixed; boundary=changeset
17
18 --changeset
19 Content-Type: application/http
20 Content-Transfer-Encoding: binary
21
22 DELETE ZEMPLOYEE_DETAILSet(EmpId='0000000002') HTTP/1.1
23
24
25 --changeset
26 Content-Type: application/http
27 Content-Transfer-Encoding: binary
28
29 PUT ZEMPLOYEE_DETAILSet(EmpId='0000000001') HTTP/1.1
30 Content-Type: application/json
31
32 {
33     "EmpId" : "0000000001",
34     "Name" : "DONALD",
35     "Dept" : "DS ABAP",
36     "Designation" : "ASE",
37     "Skillset" : "ABAP",
38     "Experience" : "000002"
39 }
40
41 --changeset
42
43 --batch_00567--
```

FOR CHANGESET  
CONTENT TYPE  
HEADER



Q. Can we use multiple **one or more Update/delete/insert** operation within a “Changeset”?

Yes

Q. Can we use “**Commit work**” statement within any one UPDATE/CREATE/DELETE entity method.

No

Q. What will happen if you use Commit work?

Go into dump

Q. What prefix need to be used in HTTP header in order to segregate the multiple batch request separately?

Ans. By defining the **Boundry Value** for Batch request

Q. How to segregate the multiple action within a change set?

Ans. By defining **the boundary value** for Change set

**Session 12**

**19<sup>TH</sup> Feb**

What is the correct Full form of **CSRF** ?


1. Cross site reference Forgery

**2. Cross site Request Forgery**

3. Cross significance random Forgery

4. Cross site rare Forgery

## Explain XCSRF Token with example ?




or example, a typical GET request for a \$100 bank transfer might look like:

```
GET http://netbank.com/transfer.do?acct=PersonB&amount=$100 HTTP/1.1
```

A hacker can modify this script so it results in a \$100 transfer to their own account. Now the malicious request might look like:

```
GET http://netbank.com/transfer.do?acct=AttackerA&amount=$100 HTTP/1.1
```



## What is CSRF Definition ?

Cross site request forgery (CSRF), also known as **XSRF**, **Sea Surf** or **Session Riding**, is an **attack** that **tricks a web browser** into executing an **unwanted action** in an application to which a user is logged in.


## Some Good Reference:-

<https://www.youtube.com/watch?v=m0EHIfTgGUU> => Animation 3 Minutes

<https://www.youtube.com/watch?v=Y8-duChsYqI> => 20 Minutes, Anubhav Sir Video

## OData and CSRF Token

- CSRF token is applicable on HTTP protocol only
- REST, SOAP supports the HTTP protocol so CSRF token can be used for REST and SOAP to validate the session for a specific user



Q. Do we have to take care while performing the post call from Gateway/Fiori/UI5 Application?

No. It will be taken care by the ui5 Framework/Odata Gateway



## When CSRF Token is required?

1. It is required when you are going to call the Odata Service from third Party Application – PostMan, Java Application, Any .Net Application
2. From UI5/Fiori also it can be required if you are not going to make the Odata Call. Rather you are making a REST based call using AJAX.

## How to achieve this one?

Ans. First make the Get call and the get the token.  
Once you get the token, pass this token during post call and then only you will be able to perform

**What is the T-Code to set the parameter to enable or disable the CSRF Token Request?**

Ans. T-Code is **SICF** Parameter Name: ~CHECK\_CSRF\_TOKEN . Here value =1 => Enable  
and 0 => Disable

**Q. If you are going to make that parameter(~CHECK\_CSRF\_TOKEN ) disable then do you not have to do anything while posting from the third party application or using the AJAX Call?**


Ans. No We have to pass the below parameter. We have to do something.

X-SCRF-TOKEN = 'X'.

## **Session 13**

20<sup>th</sup> Feb '21

Q. What is the performance improvement techniques in Odata?



## How to do -

1. Use the \$expand in query string – It will reduce the roundtrip time

2. Use the Data provider expand Method in stead of default implementation -

```
GET_EXPANDED_ENTITY  
GET_EXPANDED_ENTITYSET
```

3. **\$Batch** Call – grouping the multiple operation together in one Odata call

4. **Deep Insert**

5. Delta Query – Instead of getting all get the difference

6. \$select

7. \$filter

8. \$top and \$skip


9. Avoid the coding at NW Gateway Layer. Do Maximum coding at Application Server

10. Whenever possible prefer for the Embedded scenario.  
In the embedded also prefer to Co-Deployment option.

**Note:-** There are two option to select in embedded scenario –

1. Routing Based
2. Co- Deployment

Sap suggests to use Co-Deployment whenever possible because 2<sup>nd</sup> option ( Co-deployment ) is 15% is faster than 1<sup>st</sup> one( Routing Based)



Total = 100ms, GWHUB = 50ms , GWRFCOH = 10ms, Gwbe = 20ms  
Gwapp = 5ms,

Gwnongw = format conversion =  
In case of json and xml = 0,  
But in case of XLSX format = 30ms

Gwappssum = The complete time taken by the application in case of  
Batch parallelization.

Gwbewait = The time for which GWBE has to wait to become free  
the work process

$Fw = nw \text{ gateway time} + rfc + as = 2 + 5 + 10 = 17ms$

$Gwtotal = fw + \text{Service Implementation( Logic Execution )}$

**Gwapplogic => 70ms**

## Different Parameters and their meaning ~

Parameter	Description
<u>gwhub</u>	Time spent at Gateway framework on the Hub system
gwrftcoh	Time spent on then network (between hub and backend)
gwbe	Time spent at Gateway framework in the backend
gwapp	Time consumed by implementation of the Gateway service itself
gwnongw	Time consumed by components other than SAP Gateway (e.g. RAL, Excel-format)
gwappsum	Only in case of batch parallelization: the sum of service implementations in the multiple operations (inside the batch)
gwbewait	Only in case of batch parallelization: the Gateway FWK has to wait for e.g. work process or operation to finish
fw	The sum of SAP Gateway framework. With other words: $fw = gwhub + gwbe + gwrftcoh$
gwtotal	The sum of SAP Gateway FWK and service implementation: $gwtotal = fw + gwapp$

Detail Carlos Roggan Blog Reference: [Click Here](#)

Anubhav Video : <https://youtu.be/vYbd0IUd9Go>

Thanks to Carlos Roggan(great blog) and Anubhav(for video)

Blog full link:- <https://blogs.sap.com/2016/01/28/understanding-sap-performance-statistics-for-sap-netweaver-gateway-ser>



What is the t-Code to have the performance Trace in GW?

Ans. **/IWFND/TRACES**

XS oDATA

In case of any Query or Feedback, Please feel free to reach out to [pankajkumaram@gmail.com](mailto:pankajkumaram@gmail.com)  
Or My WhatsApp: +918700435272

I provide Live training as well as Video courses on different Subjects in super simple and easy way.

Some of my Popular courses:

ABAP MADE EASY( Available on My LMS Only )

OOPS ABAP MADE EASY( Available on My LMS Only )

ABAP ON HANA MADE EASY( Available on My LMS Only )

ABAP ENHANCEMENT MADE EASY ( Available on My LMS Only )

ALE IDOC MADE EASY(Available on Udemy + My LMS )

ADOBE Form MADE EASY( Available on Udemy + My LMS )

CDS Made Easy( Available On Udemy + My LMS )

ABAP ON HANA Interview Questions and Answer Made Easy ( MY LMS + UDEMY )

Adobe form Made Easy Interview Questions and Answer Made Easy( MY LMS + UDEMY )

ODATA Interview Question's and Answer Made Easy( MY LMS + UDEMY )

OOPS ABAP Interview Question's and Answer Made Easy ( MY LMS + UDEMY)

SAP ADOBE Forms Interview Question's and Answer Made Easy ( MY LMS + UDEMY )

Can visit my website [www.saptechmadeeasy.com](http://www.saptechmadeeasy.com) for more detail about different courses