

CloudStorage Pro API Documentation v2.1

Overview : The CloudStorage Pro API allows developers to integrate cloud storage functionality into their applications. RESTful API with JSON responses.

Authentication All API requests require authentication using API keys.

Getting Your API Key:

1. Log into your account
2. Navigate to Settings > Developers
3. Click "Generate New API Key"
4. Copy and store securely (shown only once)

Authentication Header:

Authorization: Bearer YOUR_API_KEY

Base URL:

<https://api.cloudstorage.pro/v2>

Rate Limits

- Basic: 1,000 requests/hour
- Pro: 10,000 requests/hour
- Enterprise: 100,000 requests/hour

Core Endpoints

1. Upload File

POST /files/upload

Content-Type: multipart/form-data

Parameters:

- file (required): Binary file data
- folder_id (optional): Destination folder ID
- overwrite (optional): true/false

Response:

```
{
  "file_id": "f_abc123",
  "name": "document.pdf",
  "size": 1048576,
  "created_at": "2024-01-15T10:30:00Z"
}
```

2. Download File

GET /files/{file_id}/download

Response: Binary file data

3. List Files

GET /files

Parameters:

- folder_id (optional): Filter by folder
- limit (optional): Results per page (default: 100)
- offset (optional): Pagination offset

Response:

```
{
  "files": [...],
  "total": 1250,
  "limit": 100,
  "offset": 0
}
```

4. Delete File

DELETE /files/{file_id}

Response:

```
{
  "success": true,
  "message": "File deleted successfully"
}
```

5. Create Folder

POST /folders

Body:

```
{
  "name": "Project Files",
  "parent_id": null
}
```

Response:

```
{
  "folder_id": "fd_xyz789",
  "name": "Project Files"
}
```

```
}
```

Error Codes

- 400: Bad Request - Invalid parameters
- 401: Unauthorized - Invalid API key
- 403: Forbidden - Insufficient permissions
- 404: Not Found - Resource doesn't exist
- 429: Too Many Requests - Rate limit exceeded
- 500: Internal Server Error

Error Response Format:

json

```
{
  "error": {
    "code": "INVALID_PARAMETER",
    "message": "File size exceeds limit",
    "field": "file"
  }
}
```

Webhooks Configure webhooks to receive real-time notifications.

Events:

- file.uploaded
- file.deleted
- folder.created
- user.added

Setup: Settings > Developers > Webhooks > Add Endpoint

Payload Example:

json

```
{
  "event": "file.uploaded",
  "timestamp": "2024-01-15T10:30:00Z",
  "data": {
    "file_id": "f_abc123",
    "user_id": "u_def456"
  }
}
```

Best Practices

1. Store API keys securely (never in code)

2. Implement exponential backoff for retries
3. Use pagination for large datasets
4. Cache responses when appropriate
5. Monitor rate limit headers

SDK Libraries

- Python: `pip install cloudstorage-sdk`
- JavaScript: `npm install @cloudstorage/sdk`
- Java: Maven dependency available
- Ruby: `gem install cloudstorage`