CT216 Introduction to Communication Systems Lecture 4: Source Coding

Yash M. Vasavada

Professor, DA-IICT, Gandhinagar

4th March 2024



Communication System Model and a Preview



- Communication System Model and a Preview
- Source Coding
 - Huffman Coding
 - Lempel-Ziv Coding




- Communication System Model and a Preview
- 2 Source Coding
 - Huffman Coding
 - Lempel-Ziv Coding
- The Binomial RV and a Proof



- Communication System Model and a Preview
- Source Coding
 - Huffman Coding
 - Lempel-Ziv Coding
- The Binomial RV and a Proof
- 4 Summary




The Model of a Communication System



• A preview of next several lectures: study (i) the source coding, (ii) the channel coding and (iii) the modulation blocks



The Model of a Communication System



- A preview of next several lectures: study (i) the source coding, (ii) the channel coding and (iii) the modulation blocks
 - ▶ The basic theoretical framework underlying all these blocks has already been developed!



How can the bits take fractional values?

 We have seen that the concepts of information is obtained in terms of fraction of bits. Both the entropy and the amount of information transfer take the values which are fractional bits. However, how can the bits be in fractional units?



How can the bits take fractional values?

- We have seen that the concepts of information is obtained in terms of fraction of bits. Both the entropy and the amount of information transfer take the values which are fractional bits. However, how can the bits be in fractional units?
- Shannon's answer: one bit at a time cannot be in fraction. However, the best way to think about the information generation and its transfer is to consider a large sequence of bits



Entropy H(X) of the Source and Its Compressibility Source Coding Problem

- For example, suppose that an informative source X has the entropy H(X) = 0.5 bits.
- Thus, only half of the bits generated by source actually contain the information. The remaining half are non-informative (i.e., redundant).
- Therefore, if the above source generates 10 million bits, this sequence can be shortened to 5 million bits without losing any information



Entropy H(X) of the Source and Its Compressibility Source Coding Problem

- For example, suppose that an informative source X has the entropy H(X) = 0.5 bits.
- Thus, only half of the bits generated by source actually contain the information. The remaining half are non-informative (i.e., redundant).
- Therefore, if the above source generates 10 million bits, this sequence can be shortened to 5 million bits without losing any information
 - ▶ This has vast implication in today's world where a lot of data is continuously generated and stored. If the data can be compressed before the storage or transmission over a communication channel, it is clear that that would provide a tremendous benefit



Entropy H(X) of the Source and Its Compressibility Source Coding Problem

- For example, suppose that an informative source X has the entropy H(X) = 0.5 bits.
- Thus, only half of the bits generated by source actually contain the information. The remaining half are non-informative (i.e., redundant).
- Therefore, if the above source generates 10 million bits, this sequence can be shortened to 5 million bits without losing any information
 - ▶ This has vast implication in today's world where a lot of data is continuously generated and stored. If the data can be compressed before the storage or transmission over a communication channel, it is clear that that would provide a tremendous benefit
 - ▶ We will study the problem of data compression, also called the source coding problem

 Suppose the communication channel has an information transfer rate I(X; Y) = 0.33 bits. In this case, only one-third of the bits transmitted by the sender can be successfully received.



- Suppose the communication channel has an information transfer rate I(X; Y) = 0.33 bits. In this case, only one-third of the bits transmitted by the sender can be successfully received.
- Thus, if the source has 10 million bits to be transferred over a communication channel, it has to actually transmit 30 million bits, where the extra 20 million bits ensure that the communication channel does not corrupt the main informative content of 10 million bits



- Suppose the communication channel has an information transfer rate I(X; Y) = 0.33 bits. In this case, only one-third of the bits transmitted by the sender can be successfully received.
- Thus, if the source has 10 million bits to be transferred over a communication channel, it has to actually transmit 30 million bits, where the extra 20 million bits ensure that the communication channel does not corrupt the main informative content of 10 million bits
 - ▶ This is called the channel coding problem. We have already studied a basic scheme...



- Suppose the communication channel has an information transfer rate I(X; Y) = 0.33 bits. In this case, only one-third of the bits transmitted by the sender can be successfully received.
- Thus, if the source has 10 million bits to be transferred over a communication channel, it has to actually transmit 30 million bits, where the extra 20 million bits ensure that the communication channel does not corrupt the main informative content of 10 million bits
 - ▶ This is called the channel coding problem. We have already studied a basic scheme...
 - ▷ ..., i.e., the repetition coding. Would "Repeat-by-Three" scheme solve this problem?



- Suppose the communication channel has an information transfer rate I(X; Y) = 0.33 bits. In this case, only one-third of the bits transmitted by the sender can be successfully received.
- Thus, if the source has 10 million bits to be transferred over a communication channel, it has to actually transmit 30 million bits, where the extra 20 million bits ensure that the communication channel does not corrupt the main informative content of 10 million bits
 - ▶ This is called the channel coding problem. We have already studied a basic scheme...
 - ▷ ..., i.e., the repetition coding. Would "Repeat-by-Three" scheme solve this problem?
 - Shannon showed that the repetition coding is too simple and does not work well for the real-world channels. Schemes that are smarter and more complex are needed to solve the channel coding problem

 $\mathsf{Mod}/\mathsf{Demod}\ \mathsf{Problem}$

 The bits which convey the information are not suitable for transmission over long distances — electromagnetic waves are needed for this purpose



Need of Modulation for Transmission over a Communication Channel

Mod/Demod Problem

- The bits which convey the information are not suitable for transmission over long distances — electromagnetic waves are needed for this purpose
- The communication transmitter converts the informative bits to the electromagnetic waves which are emitted by an antenna.



Need of Modulation for Transmission over a Communication Channel Mod/Demod Problem

- The bits which convey the information are not suitable for transmission over long distances — electromagnetic waves are needed for this purpose
- The communication transmitter converts the informative bits to the electromagnetic waves which are emitted by an antenna.
 - ▶ This is called the modulation, since the bits are used to "modulate" one or multiple characteristics of the EM wave — e.g., the amplitude, the phase, or the frequency.



Need of Modulation for Transmission over a Communication Channel Mod/Demod Problem

- The bits which convey the information are not suitable for transmission over long distances — electromagnetic waves are needed for this purpose
- The communication transmitter converts the informative bits to the electromagnetic waves which are emitted by an antenna.
 - This is called the modulation, since the bits are used to "modulate" one or multiple characteristics of the EM wave e.g., the amplitude, the phase, or the frequency.
 - ▶ The received modulated wave has to be converted back to the bits. This is called the demodulation.



Mod/Demod Problem

- The bits which convey the information are not suitable for transmission over long distances — electromagnetic waves are needed for this purpose
- The communication transmitter converts the informative bits to the electromagnetic waves which are emitted by an antenna.
 - ▶ This is called the modulation, since the bits are used to "modulate" one or multiple characteristics of the EM wave — e.g., the amplitude, the phase, or the frequency.
 - ▶ The received modulated wave has to be converted back to the bits. This is called the demodulation.
- We have studied a basic modulation and demodulation scheme the BPSK (Binary Phase Shift Keying). We will expand upon [1] further

Also known as Data Compression

- Many digital data streams contain a lot of redundant information. For example, a digital image file may contain more zeros than ones: 0,0,0,0,1,0,0,1,0,0,1,1
- We wish to squeeze out the redundant information to minimize the amount of data needed to be stored or transmitted
- Definition of Data Compression Problem:
 - What are the good algorithms that achieve the maximal data compression?
 - What is the maximum data compression that can be achieved if we want to recover the exact bit sequence after decompression?
- Importance of Data Compression Problem:
 - Cannot be overstated given so much data is getting uploaded/downloaded and stored in today's world of YouTube, Facebook, etc.



Discrete Memoryless Source (DMS)

• A Discrete Memoryless Source (DMS) generates discrete symbols (instead of continuous-valued output) which are independent of each other, i.e., the source is discrete and it does not have memory



Discrete Memoryless Source (DMS)

- A Discrete Memoryless Source (DMS) generates discrete symbols (instead of continuous-valued output) which are independent of each other, i.e., the source is discrete and it does not have memory
 - → Consider two discrete informative sources: (i) a playwriter composing a drama using her laptop keyboard, (ii) a monkey punching the keys of a typewriter placed in front of it. Which of the two sources is memoryless?



Discrete Memoryless Source (DMS)

- A Discrete Memoryless Source (DMS) generates discrete symbols (instead of continuous-valued output) which are independent of each other, i.e., the source is discrete and it does not have memory
 - → Consider two discrete informative sources: (i) a playwriter composing a drama using her laptop keyboard, (ii) a monkey punching the keys of a typewriter placed in front of it. Which of the two sources is memoryless?
 - → Source (ii)
- We will mostly assume that the source is DMS



Discrete Memoryless Source (DMS)

 A Discrete Memoryless Source (DMS) generates discrete symbols (instead of continuous-valued output) which are independent of each other, i.e., the source is discrete and it does not have memory

000000000000000000000

Source Coding

- → Consider two discrete informative sources: (i) a playwriter composing a drama using her laptop keyboard, (ii) a monkey punching the keys of a typewriter placed in front of it. Which of the two sources is memoryless?
- → Source (ii)
- We will mostly assume that the source is DMS
 - → With more complicated notations, the theory for DMS can be extended to the more realistic informative sources which exhibit a memory



for DMS

- A source code is a rule which maps symbols from the source alphabet to sequence of bits
- Fixed length source code maps source symbols into codewords of the same length:
 - \rightarrow Example: $x_1 \Rightarrow 00, x_2 \Rightarrow 01, x_2 \Rightarrow 10, x_4 \Rightarrow 11$
- Variable length source code maps source symbols into codewords of different lengths:
 - \rightarrow Example: $x_1 \Rightarrow 1, x_2 \Rightarrow 01, x_2 \Rightarrow 101, x_4 \Rightarrow 11$
- Variable length source code is uniquely decodeable if no codeword is a prefix of another codeword:
 - \rightarrow Uniquely decodeable: $x_1 \Rightarrow 000, x_2 \Rightarrow 0010, x_3 \Rightarrow 01, x_4 \Rightarrow 10, x_5 \Rightarrow 1100, x_6 \Rightarrow 1101, x_7 \Rightarrow 111$
 - \rightarrow Counter-example: $x_1 \Rightarrow 1, x_2 \Rightarrow 00, x_2 \Rightarrow 01, x_4 \Rightarrow 10$. If we get 001001, should we decode it as $x_2, x_1, x_2 x_1$ or as x_2, x_4, x_3 ?

We will work only with the prefix-free codes.

for DMS: Variable Length Codes

• Why to consider variable-length codes, when the fixed length codes don't have the ambiguity problem outlined earlier?



for DMS: Variable Length Codes

 Why to consider variable-length codes, when the fixed length codes don't have the ambiguity problem outlined earlier?

0000000000000000000000

Source Coding

→ When different symbols have vastly varying probabilities (e.g., the letter "e" versus the letter "q" in English), using equal-length codewords is inefficient. Why?



for DMS: Variable Length Codes

- Why to consider variable-length codes, when the fixed length codes don't have the ambiguity problem outlined earlier?
 - → When different symbols have vastly varying probabilities (e.g., the letter "e" versus the letter "q" in English), using equal-length codewords is inefficient. Why?
 - \rightarrow We have seen that the information generated in number of bits upon the occurrence of the k^{th} symbol, i.e., $I_k = -\log_2(p_k)$, is much smaller for "e" versus "q".



for DMS: Variable Length Codes

- Why to consider variable-length codes, when the fixed length codes don't have the ambiguity problem outlined earlier?
 - → When different symbols have vastly varying probabilities (e.g., the letter "e" versus the letter "q" in English), using equal-length codewords is inefficient. Why?
 - \rightarrow We have seen that the information generated in number of bits upon the occurrence of the k^{th} symbol, i.e., $I_k = -\log_2(p_k)$, is much smaller for "e" versus "q".
 - ightarrow We will see that the highest amount of data compression can be achieved if the codeword length equals the information I_k in bits
- How to represent the variable/fixed length codewords?



for DMS: Variable Length Codes

 Why to consider variable-length codes, when the fixed length codes don't have the ambiguity problem outlined earlier?


0000000000000000000000

Source Coding

- → When different symbols have vastly varying probabilities (e.g., the letter "e" versus the letter "q" in English), using equal-length codewords is inefficient. Why?
- \rightarrow We have seen that the information generated in number of bits upon the occurrence of the k^{th} symbol, i.e., $I_k = -\log_2(p_k)$, is much smaller for "e" versus "q".
- → We will see that the highest amount of data compression can be achieved if the codeword length equals the information I_k in bits
- How to represent the variable/fixed length codewords?
 - → For binary codewords, a binary tree is a useful representation




for DMS: An Example Prefix-Free Code on a Binary Tree



An assigned codeword is never part of a subtree of another assigned codeword

for DMS: An Example of Non-Prefix-Free Code on a Binary Tree



• Codeword X_4 belongs to the subtree of X_3 , hence violates the prefix-free requirement




Observations from the Binary Tree

- Let n_ℓ be the number of bits in the codeword which represents a source symbol x_ℓ and let n_{\max} be the length of the longest codeword.
- The subtree under x_{ℓ} bits has $A_{\ell} = 2^{n_{\text{max}} n_{\ell}}$ leaf nodes.



Observations from the Binary Tree

- Let n_ℓ be the number of bits in the codeword which represents a source symbol x_ℓ and let n_{\max} be the length of the longest codeword.
- The subtree under x_{ℓ} bits has $A_{\ell} = 2^{n_{\text{max}} n_{\ell}}$ leaf nodes.





• For prefix free code, where individual codewords have lengths $1 \le n_{\ell} \le n_{\text{max}}$,

$$\sum_{\ell=1}^{L} 2^{-n_\ell} \le 1$$



• For prefix free code, where individual codewords have lengths $1 \le n_{\ell} \le n_{\text{max}}$,

$$\sum_{\ell=1}^{L} 2^{-n_\ell} \le 1$$

Proof:



• For prefix free code, where individual codewords have lengths $1 < n_{\ell} < n_{\text{max}}$.

$$\sum_{\ell=1}^L 2^{-n_\ell} \le 1$$


- Proof:
 - The subtree under an assigned codeword of length n_ℓ bits has $A_\ell = 2^{n_{\max} n_\ell}$ leaf nodes.
 - Since the code is prefix-free, the subtrees for different codewords are disjoint.
 - The total number of leaf nodes equals $2^{n_{\text{max}}}$. Therefore,



 For prefix free code, where individual codewords have lengths $1 < n_{\ell} < n_{\max}$

$$\sum_{\ell=1}^L 2^{-n_\ell} \le 1$$

- Proof:
 - The subtree under an assigned codeword of length n_{ℓ} bits has $A_{\ell} = 2^{n_{\text{max}} - n_{\ell}}$ leaf nodes.
 - Since the code is prefix-free, the subtrees for different codewords are disjoint.
 - The total number of leaf nodes equals $2^{n_{\text{max}}}$. Therefore,



An Interesting Observation

Suppose for some code, the Kraft's Inequality turns into an equality,

i.e.,
$$\sum_{\ell=1}^{L} 2^{-n_{\ell}} = 1$$
.



An Interesting Observation

Suppose for some code, the Kraft's Inequality turns into an equality,

i.e.,
$$\sum_{\ell=1}^{L} 2^{-n_{\ell}} = 1$$
.

• In this case, we can possibly consider the left side of the equality as forming...



An Interesting Observation

Suppose for some code, the Kraft's Inequality turns into an equality,

i.e.,
$$\sum_{\ell=1}^{L} 2^{-n_{\ell}} = 1$$
.

- In this case, we can possibly consider the left side of the equality as forming...
- ... a probability mass function (note that it is for the probability mass function that this equality is satisfied)



An Interesting Observation

Suppose for some code, the Kraft's Inequality turns into an equality,

i.e.,
$$\sum_{\ell=1}^{L} 2^{-n_{\ell}} = 1$$
.

- In this case, we can possibly consider the left side of the equality as forming...
- ... a probability mass function (note that it is for the probability mass function that this equality is satisfied)
- Thus, if 2^{-n_ℓ} is equated to (pseudo-) probability \hat{p}_ℓ of ℓ^{th} symbol, we obtain

$$\hat{p}_{\ell} = 2^{-n_{\ell}} \Rightarrow n_{\ell} = -\log_2(\hat{p}_{\ell})$$

However, the right side is the information content of a symbol with the probability \hat{p}_{ℓ} !



An Interesting Observation

Suppose for some code, the Kraft's Inequality turns into an equality,

i.e.,
$$\sum_{\ell=1}^{L} 2^{-n_{\ell}} = 1$$
.

- In this case, we can possibly consider the left side of the equality as forming...
- ... a probability mass function (note that it is for the probability mass function that this equality is satisfied)
- Thus, if 2^{-n_ℓ} is equated to (pseudo-) probability \hat{p}_ℓ of ℓ^{th} symbol, we obtain

$$\hat{p}_{\ell} = 2^{-n_{\ell}} \Rightarrow n_{\ell} = -\log_2(\hat{p}_{\ell})$$

However, the right side is the information content of a symbol with the probability $\hat{p}_{\ell}!$

• Thus, when the Kraft's Inequality turns into the equality, the codeword lengths $\{n_\ell\}$ equal the Shannon's definition of the information generated by the symbols having the pseudo-probabilities $\{\hat{p}_\ell\}$



for DMS

• Rate *R* of a source code is the expected number of bits (mean value) required to represent a source symbol



for DMS

• Rate *R* of a source code is the expected number of bits (mean value) required to represent a source symbol

$$\rightarrow$$
 Therefore, $R = \sum_{k=1}^{L} p_k n_k$ bits



for DMS

- Rate *R* of a source code is the expected number of bits (mean value) required to represent a source symbol
 - ightarrow Therefore, $R = \sum_{k=1}^{L} p_k n_k$ bits
 - \rightarrow For fixed length codes, $R \ge \lceil \log_2 L \rceil$



for DMS

- Rate R of a source code is the expected number of bits (mean value) required to represent a source symbol
 - ightarrow Therefore, $R = \sum_{k=1}^{L} p_k n_k$ bits
 - \rightarrow For fixed length codes, $R \ge \lceil \log_2 L \rceil$
- Goal of Source Encoding: find a uniquely decodeable code that minimizes R



for DMS

- Rate *R* of a source code is the expected number of bits (mean value) required to represent a source symbol
 - \rightarrow Therefore, $R = \sum_{k=1}^{L} p_k n_k$ bits
 - \rightarrow For fixed length codes, $R \ge \lceil \log_2 L \rceil$
- Goal of Source Encoding: find a uniquely decodeable code that minimizes R
- **Strategy:** assign short codewords (small n_k) to the most likely symbols (large p_k)



- A fundamental theorem of the Information Theory [Shannon 1948 paper]:
 - \rightarrow For a uniquely decodeable source code that provides lossless compression (i.e., perfect reconstruction of the source symbols at the source decoder), $R \ge H(X)$.
 - \triangleright Rate can be made arbitrarily close to, but not less than, H(X)



- A fundamental theorem of the Information Theory [Shannon 1948 paper]:
 - → For a uniquely decodeable source code that provides lossless compression (i.e., perfect reconstruction of the source symbols at the source decoder), R > H(X).
 - \triangleright Rate can be made arbitrarily close to, but not less than, H(X)
 - → This is the Source Coding (or Data Compression) Theorem



- A fundamental theorem of the Information Theory [Shannon 1948 paper]:
 - → For a uniquely decodeable source code that provides lossless compression (i.e., perfect reconstruction of the source symbols at the source decoder), R > H(X).
 - \triangleright Rate can be made arbitrarily close to, but not less than, H(X)
 - → This is the Source Coding (or Data Compression) Theorem
- How to prove this theorem?



Practical Source Coding Algorithms

- There are two widely used source coding methods which make R
 approach the lower bound of H(X) promised by data compression
 theorem:
 - Huffman Coding: requires the knowledge of probabilities of DMS
 - 2 Lempel-Ziv Coding: operates in a *blind* manner (i.e., without requiring the knowledge of the DMS' PMF)



Practical Source Coding Algorithms

- There are two widely used source coding methods which make R approach the lower bound of H(X) promised by data compression theorem:
 - 4 Huffman Coding: requires the knowledge of probabilities of DMS
 - 2 Lempel-Ziv Coding: operates in a *blind* manner (i.e., without requiring the knowledge of the DMS' PMF)
- Several other algorithms: Shannon-Fano coding, Shannon-Fano-Elias coding, Arithmetic coding, etc. we will not study these schemes



Huffman Coding Algorithm

Huffman coding is based upon the idea of allocating short codewords to highly probable symbols. The algorithm for Huffman coding belongs to a class of algorithms based upon the Greedy Approach.

- List all symbols in descending order of probability
- @ Group the two lowest probability symbols into a new combined symbol
- Repeat steps 1 and 2 until only a single combined symbol remains
- Assign a 1 to each upper branch and 0 to each lower branch of the resulting binary tree
- Odeword for each symbol is the sequence of bits from the root of the tree to that symbol




Source Coding Theorem

Huffman Coding Algorithm: An Example




Symbol	Probability
x_1	0.45
x_2	0.2
x_3	0.13
x_4	0.1
<i>x</i> ₅	0.07
<i>x</i> ₆	0.05





Symbol	Probability
x_1	0.45
x_2	0.2
x_3	0.13
*	0.12
x_4	0.1







Source Coding Theorem

Huffman Coding Algorithm: An Example




Symbol	Probability
x_1	0.45
*	0.22
x_2	0.2
x_3	0.13





0.22







Source Coding Theorem

Communication System Model and a Preview

Huffman Coding Algorithm: An Example








Source Coding Theorem

Huffman Coding Algorithm: An Example



Symbol	Probability	Codeword
x_1	0.45	0
x_2	0.2	111
x_3	0.13	110
x_4	0.1	100
x_5	0.07	1011
x_6	0.05	1010





Source Coding Theorem

Communication System Model and a Preview

Huffman Coding Algorithm: Numerical Analysis

Symbol	Probability p_k	Codeword	Length L_k	$p_k L_k$	$-log_2p_k$	$-p_k log_2 p_k$
x_1	0.45	0	1	0.45	1.15	0.518
x_2	0.2	111	3	0.6	2.32	0.464
x_3	0.13	110	3	0.39	2.94	0.382
x_4	0.1	100	3	0.3	3.32	0.332
x_5	0.07	1011	4	0.28	3.83	0.268
x_6	0.05	1010	4	0.2	4.32	0.216
				2.2		2.18



Huffman Coding Algorithm: Summary

illian Coding Algorithm. Summary

- How do we get even closer to Entropy?
 - $\,\,\,\,\,\,\,\,\,\,\,\,\,$ Use Huffman Algorithm on pairs of symbols, or
 - $\,\rightarrow\,$ Even better, on triplets of symbols, or quadruplets or,
 - ightarrow In general, *m*-tuple of symbols.
- A limitation of Huffman Algorithm is that it requires the source symbol probabilities to be known. These are not known exactly but they can be estimated from a sufficiently large sample of source output. Mismatch between the estimated and exact symbol probabilities contributes to a degraded performance of Huffman's Algorithm.
- Another limitation of Huffman Code is that the symbol probabilities are assumed to be fixed. If these probabilities change with time Huffman Code may provide suboptimal data compression.

Lempel-Ziv Coding

Encoding Algorithm

- In Lempel-Ziv coding, the source sequence is sequentially parsed into strings that have not appeared so far.
 - ightarrow Continually parse the symbol sequence and insert a comma on detecting the shortest sequence that has not been seen earlier
- Example sequence: 1011010100010...
- Sequential parsing method in Lempel-Ziv encoding:
 - \rightarrow **1**,011010100010...
 - \rightarrow 1,0,11010100010...
 - \rightarrow 1,0,11,010100010...
 - \rightarrow 1,0,11,01,0100010...
 - \rightarrow 1,0,11,01,010,0010...
 - \rightarrow 1,0,11,01,010,00,10...
 - \rightarrow 1,0,11,01,010,00,10,...



Lempel-Ziv Coding

Lempel-Ziv Coding

Encoding Algorithm

- Prefix of each "phrase" (phrase is the symbol string between two commas), i.e., the string consisting of all but the last symbol of each phrase, must have occurred earlier.
- Encode this phrase by giving the location of the prefix and the value of the last bit.
- Let C(n) be the number of phrases in the parsing of the input sequence with n symbols.
- Thus, $\log C(n)$ bits are needed to describe the location of the prefix to the phrase and one bit to describe the last bit.
- In the above example, the code sequence is:
 (000, 1), (000, 0), (001, 1), (010, 1), (100, 0), (010, 0), (001, 0)
 - → First number of each pair gives the index of the prefix and the number gives the last bit of the phrase.



- Suppose I perform an experiment N times, where each outcome is a Binary RV (Bernouilli RV), with probability of 1 equal to p and 0 equal to 1-p
- Questions:
 - ▶ What are all the possible outcomes?
 - ▶ What is the *sum* of *N* binary outcomes?
- Let us look at the cases N = 2,3 and 4.



Experie	ment ID	Binomial RV	
1	2	Υ	
0	0	0	
0	1	1	
1	0	1	
1	1	2	



Experiement ID			Binomial RV
1	2	3	Υ
0	0	0	0
0	0	1	1
0	1	0	1
0	1	1	2
1	0	0	1
1	0	1	2
1	1	0	2
1	1	1	3



Experiement ID				Binomial RV
1	2	3	4	Υ
0	0	0	0	0
0	0	0	1	1
0	0	1	0	1
0	0	1	1	2
0	1	0	0	1
0	1	0	1	2
0	1	1	0	2
0	1	1	1	3
1	0	0	0	1
1	0	0	1	2
1	0	1	0	2
1	0	1	1	3
1	1	0	0	2
1	1	0	1	3
1	1	1	0	3
1	1	1	1	4



- lacktriangle Outcomes of N experiments form a binary "string" of length N bits
- When these N bits are added up, we get a variable Y, which is the Binomial RV
- Value of Y can be any integer between 0 (all-zeros binary string) to N (all-ones string)
- There is a total of 2^N possible strings (these form a set of all possible outcomes)
- **3** A total of $\binom{N}{y}$ strings have y ones and N-y zeros. When any of these strings occur, the variable Y will take a value y.
- Due to independence between N experiments, probability of occurrence of any one of $\binom{N}{v}$ string is the same, and it is given as $p^{y}(1-p)^{N-y}$.
- Therefore, the total probability that Y = y is given as $\binom{N}{y} p^y (1-p)^{N-y}$.



Another Problem

You are told:



Another Problem

- You are told:
 - ▶ At a bicycle company, 70% of the newly made cycles pass the quality inspection and 30% fail.



- You are told:
 - ▶ At a bicycle company, 70% of the newly made cycles pass the quality inspection and 30% fail.
- Question:



- You are told:
 - ▶ At a bicycle company, 70% of the newly made cycles pass the quality inspection and 30% fail.
- Question:
 - ▶ What are the chances that 3 of 10 cycles that you're inspecting will fail?



- You are told:
 - ▷ At a bicycle company, 70% of the newly made cycles pass the quality inspection and 30% fail.
- Question:
 - ▶ What are the chances that 3 of 10 cycles that you're inspecting will fail?
- Answer:
 - N = 10, p = 0.1, y = 3.



- You are told:
 - ▷ At a bicycle company, 70% of the newly made cycles pass the quality inspection and 30% fail.
- Question:
 - ▶ What are the chances that 3 of 10 cycles that you're inspecting will fail?
- Answer:
 - \triangleright N = 10, p = 0.1, y = 3.

$$(N=10)_{v=3} = 120$$



- You are told:
 - ▷ At a bicycle company, 70% of the newly made cycles pass the quality inspection and 30% fail.
- Question:
 - ▶ What are the chances that 3 of 10 cycles that you're inspecting will fail?
- Answer:

$$\triangleright$$
 $N = 10$, $p = 0.1$, $y = 3$.

$$(N=10) = 120$$

$$p^{y}(1-p)^{N-y}=0.3^{3}0.7^{7}=0.0022235661$$



- You are told:
 - ▷ At a bicycle company, 70% of the newly made cycles pass the quality inspection and 30% fail.
- Question:
 - ▶ What are the chances that 3 of 10 cycles that you're inspecting will fail?
- Answer:

$$\triangleright$$
 $N = 10$, $p = 0.1$, $y = 3$.

$$(N=10) = 120$$

$$p^{y}(1-p)^{N-y}=0.3^{3}0.7^{7}=0.0022235661$$

$$\triangleright \binom{N=10}{y=3} p^{y'} (1-p)^{N-y} = 120 \times 0.0022235661 = 0.2668$$



Another Problem

- You are told:
 - At a bicycle company, 70% of the newly made cycles pass the quality inspection and 30% fail.
- Question:
 - ▶ What are the chances that 3 of 10 cycles that you're inspecting will fail?
- Answer:

$$\triangleright$$
 $N = 10$, $p = 0.1$, $y = 3$.

$$\triangleright \binom{N=10}{N-3} = 120$$

$$p^{y}(1-p)^{N-y}=0.3^{3}0.7^{7}=0.0022235661$$

Therefore, the chances that 30% of N=10 cycles you're inspecting will fail are $\approx 27\%$.



Another Problem

- You are told:
 - At a bicycle company, 70% of the newly made cycles pass the quality inspection and 30% fail.
- Question:
 - ▶ What are the chances that 3 of 10 cycles that you're inspecting will fail?
- Answer:

$$\triangleright$$
 $N = 10$, $p = 0.1$, $y = 3$.

$$\triangleright \binom{N=10}{N-3} = 120$$

$$p^{y}(1-p)^{N-y} = 0.3^{3}0.7^{7} = 0.0022235661$$

Therefore, the chances that 30% of N=10 cycles you're inspecting will fail are $\approx 27\%$.

 What are the chances that 2 cycles will fail, or 5 will fail, or all 10 will fail?



Another Problem

- You are told:
 - ▷ At a bicycle company, 70% of the newly made cycles pass the quality inspection and 30% fail.
- Question:
 - ▶ What are the chances that 3 of 10 cycles that you're inspecting will fail?
- Answer:

$$\triangleright$$
 $N = 10$, $p = 0.1$, $y = 3$.

$$ho \ \binom{N=10}{v=3} = 120$$

$$p^{y}(1-p)^{N-y} = 0.3^{3}0.7^{7} = 0.0022235661$$


$$\triangleright \binom{N=10}{y=3} p^{y} (1-p)^{N-y} = 120 \times 0.0022235661 = 0.2668$$

Therefore, the chances that 30% of N=10 cycles you're inspecting will fail are $\approx 27\%$.

- What are the chances that 2 cycles will fail, or 5 will fail, or all 10 will fail?
 - ▶ Binomial PMF gives the answers to all such questions.




Yash M. Vasavada (DA-IICT)






- Although the failure rate is 30%, there is a good amount of chance that only one out of 10 cycles fails (10% failure rate) or even that none fail (0% failure rate)
- ullet This happens because ${\it N}=10$ is not large enough as the number of independent experiments
 - ▶ Let us see what happens as we increase N
















An Observation

- As $N \to \infty$, we will indeed (as expected) see with a very high probability that $0.3 \times N$ cycles failing
- Alternatively, the chances that the number of cycles failing is different from $0.3 \times N$ will diminish and become near zero



An Observation

- As $N \to \infty$, we will indeed (as expected) see with a very high probability that $0.3 \times N$ cycles failing
- Alternatively, the chances that the number of cycles failing is different from $0.3 \times N$ will diminish and become near zero
 - ▷ In general, when the individual Bernouilli variable has a probability of one of q, there will be Nq failed cycles (ones) and N(1-q) good cycles (zeros) as N becomes sufficiently large



An Observation

- As $N \to \infty$, we will indeed (as expected) see with a very high probability that $0.3 \times N$ cycles failing
- \bullet Alternatively, the chances that the number of cycles failing is different from 0.3 \times N will diminish and become near zero
 - ▷ In general, when the individual Bernouilli variable has a probability of one of q, there will be Nq failed cycles (ones) and N(1-q) good cycles (zeros) as N becomes sufficiently large
 - ho Another justification: the relative-frequency definition of the probability $q=\lim_{N\to\infty}N_1/N$. However, this implies that the number of ones $N_1\to q\ N$ as $N\to\infty$. This is observed in the asymptotic form of the Binomial PDF in the prior slide



When is the Fixed-Length Coding Optimal?

• If the source DMS has 4 symbols, each with the probability 1/4, a fixed-length coding which assigns two bits to each source symbol is optimal

$$\triangleright X_1 = 00, X_2 = 01, X_3 = 10, X_4 = 11$$

• If the source DMS has 8 symbols, each occurring with the probability 1/8, a fixed-length coding which assigns three bits to each source symbol is optimal

$$X_1 = 000, X_2 = 001, X_3 = 010, X_4 = 011, X_5 = 100, X_6 = 101, X_7 = 110, X_8 = 111$$



- A Bernouilli(q) source has two symbols, 1 and 0, that occur with unequal probabilities, q and 1 q, respectively
- However, if we generate a sequence of N symbols out of this source, what can we say about its composition as $N \to \infty$?



- A Bernouilli(q) source has two symbols, 1 and 0, that occur with unequal probabilities, q and 1 q, respectively
- However, if we generate a sequence of N symbols out of this source, what can we say about its composition as $N \to \infty$?
 - Any sequence with sufficiently large N will have Nq ones and N(1-q) zeros



- A Bernouilli(q) source has two symbols, 1 and 0, that occur with unequal probabilities, q and 1 q, respectively
- However, if we generate a sequence of N symbols out of this source, what can we say about its composition as $N \to \infty$?
 - ightharpoonup Any sequence with sufficiently large N will have N q ones and N (1-q) zeros
 - This is what we have concluded earlier based on the asymptotic form of the Binomial PDF.



• Since each sequence i with sufficiently long length N has the same number of ones and zeros, i.e., Nq and N(1-q), they all have the same probability given as



• Since each sequence i with sufficiently long length N has the same number of ones and zeros, i.e., Nq and N(1-q), they all have the same probability given as

$$p_i = q^{N q} (1 - q)^{N(1 - q)}$$



• Since each sequence i with sufficiently long length N has the same number of ones and zeros, i.e., Nq and N(1-q), they all have the same probability given as

$$p_i = q^{N q} (1 - q)^{N(1-q)}$$

A mathematical trick:



 Since each sequence i with sufficiently long length N has the same number of ones and zeros, i.e., Nq and N(1-q), they all have the same probability given as

$$p_i = q^{N q} (1 - q)^{N(1 - q)}$$

A mathematical trick:

Communication System Model and a Preview

$$p_i = q^{Nq} (1 - q)^{N(1-q)}$$

$$= 2^{\log_2(q^{Nq} (1-q)^{N(1-q)})}$$

$$= 2^{N(q \log_2 q + (1-q) \log_2(1-q))}$$

$$= 2^{-NH_b(q)}.$$

where $H_b(q) = -(q \log_2 q + (1-q) \log_2 (1-q))$ is the Binary Entropy function of variable q.



- generated by $\mathsf{Bernouilli}(q) \mathsf{DMS}$
 - With large N, the Bernouilli(q) DMS becomes a source which
 generates all the sequences with the same probability p_i
 The total number of such sequences K has to be such that Kn
 - The total number of such sequences K has to be such that $Kp_i=1$. Why?



Source Coding

- With large N, the Bernouilli(q) DMS becomes a source which generates all the sequences with the same probability p_i
- The total number of such sequences K has to be such that $Kp_i = 1$. Why?
 - □ Generation of these binary sequences are mutually exclusive (atomic) events



- With large N, the Bernouilli(q) DMS becomes a source which generates all the sequences with the same probability p_i
- The total number of such sequences K has to be such that $Kp_i = 1$. Why?
 - □ Generation of these binary sequences are mutually exclusive (atomic) events
 - Union of these atomic events is the universal set whose probability is 1 — since the DMS generates only one of these sequences as $N \to \infty$



Communication System Model and a Preview


- With large N, the Bernouilli(q) DMS becomes a source which generates all the sequences with the same probability p_i
- ullet The total number of such sequences K has to be such that $Kp_i=1$. Why?
 - Generation of these binary sequences are mutually exclusive (atomic) events
 - ightharpoonup Union of these atomic events is the universal set whose probability is 1 since the DMS generates only one of these sequences as $N o \infty$
 - \triangleright Therefore, from Axiom 3 of the Probability Theory, $Kp_i = 1$



- With large N, the Bernouilli(q) DMS becomes a source which generates all the sequences with the same probability p_i
- The total number of such sequences K has to be such that $Kp_i=1$. Why?
 - Generation of these binary sequences are mutually exclusive (atomic) events
 - ightharpoonup Union of these atomic events is the universal set whose probability is 1 since the DMS generates only one of these sequences as $N o \infty$
 - ightharpoonup Therefore, from Axiom 3 of the Probability Theory, $\mathit{Kp}_i = 1$
- Therefore $K = 1/p_i = 2^{NH_b(q)}$. These sequences members of what is called the typical set, therefore, need $NH_b(q)$ bits for their representation, i.e., the maximum average rate per source symbol is $H_b(q)$ bits
- This completes the proof of the source coding theorem. The average number of bits per source symbol cannot be less than $H_h(q)$.

A Visual Summary


• When the DMS alphabet size is $L = 2^n$, and its PMF is uniform, the probability of each letter is $p = 1/L = 2^{-n}$, and each letter is encoded using a fixed-length code of length $-\log_2(p) = n$ bits. Shown here when n = 7 bits.





A Visual Summary

 Suppose L = 128, however, only M = 16 symbols actually occur realistically (these form the typical set). Remaining 112 symbols have vanishing probability of occurrence. In this case of non-uniform PMF, one needs n = 4 bits instead of 7 bits (using less than 4 bits will not be enough, more than 4 is wasteful)



 An arbitrary DMS with non-uniform probabilities can be converted to a case in which most of its output sequences have vanishing probability



Summary

• The importance of source coding in digital communication systems cannot be overemphasized

Source Coding

- We have studied the basic mathematical framework and several algorithms of source coding — a detailed study of the source coding requires at least an entire semester-long course
- Although the important concepts are covered, a lot of details are not examined (for example, the information source is rarely memoryless; a significant data compression is possible if the algorithm can model the dependence between successive source symbols)



What Next?

- The source coding is often combined with the quantization of the analog source. Advanced algorithms to represent the analog source output in an efficient manner are currently being developed/proposed
- These algorithms leverage the machine learning techniques. An
 efficient source encoder is an intelligent machine that can model and
 predict the output of the information source, such as audio, video, etc.
- These algorithms often are based on linear prediction/regression, dynamic programming and hidden Markov models, deep neural networks and related techniques. These algorithms often also utilize the Fourier transformation, discrete cosine transformation, wavelet transformation, etc.
- The research and development in this field is currently on-going;
 Apple SIRI, Amazon ALEXA, Google Assistant, etc. are intelliged machines that are capable of data compression since they closed model the information source.