

# Multi-Agent Communication

## Proof of Work — Two Use Cases

### Overview

This document demonstrates two working use cases of agent-to-agent communication built on Claude Code sub-agents. Each use case shows one agent handing off work to another agent to complete a task end-to-end.

**Use Case 1 — Coder & Reviewer:** A coder agent writes a Python script, then a reviewer agent reviews it. Runs without any hooks.

**Use Case 2 — News Gatherer & Emailer:** A news-gatherer agent collects the latest news, and an emailer agent sends it via Gmail. Wired together using a SubagentStop hook and the Gmail MCP connector.

## Use Case 1 — Coder & Reviewer (without hooks)

The goal here is simple: the user asks for a Python script. The main Claude Code instance dispatches the request to the coder-agent, which writes the code, and then automatically hands it off to the reviewer-agent for review. No hooks are used, the delegation is driven purely by the sub-agent descriptions.

### Step 1: Agent definitions in the .claude/agents folder

Both sub-agents are defined as Markdown files inside the project's .claude/agents directory. Listing the folder confirms both files exist.

```
terminal
PS D:\1subagent> mkdir .claude\agents

Directory: D:\1subagent\.claude

Mode                LastWriteTime         Length Name
----                -
d-----         22-07-2026    21:33             agents

PS D:\1subagent> ls

Directory: D:\1subagent

Mode                LastWriteTime         Length Name
----                -
d-----         22-07-2026    21:33             .claude

PS D:\1subagent> mkdir .claude\memory

Directory: D:\1subagent\.claude

Mode                LastWriteTime         Length Name
----                -
d-----         22-07-2026    21:33             memory
```

Note: Here you need to provide the specific tools that the agent will have access to and also the memory state file so that the other agent can use that.

### Step 2: The coder agent

The coder agent handles Python coding tasks. It is also marked to be used proactively when a coding request comes in.

```

PS D:\1subagent> '@'
>> ---
>> name: coder
>> description: Writes code based on the user's request. Use PROACTIVELY for any implementation task - new features, bug fixes, patches.
>> tools: Read, Write, Edit, Glob, Grep, Bash
>> model: sonnet
>> ---
>>
>> You are the implementation agent.
>>
>> 1. Before starting, read .claude/memory/state.md and .claude/memory/learnings.md
>>    if they exist. They contain past review feedback and known pitfalls.
>>    Do NOT repeat past mistakes.
>> 2. Understand the user's request fully before writing code.
>> 3. Read existing files first - match the project's style, imports, patterns.
>> 4. Implement the change with minimal diff. Do not refactor unrelated code.
>> 5. Self-check: missing imports? obvious syntax errors?
>> 6. End every response with:
>>
>> ## PATCH SUMMARY
>> - Files changed: <list>
>> - What changed: <1-2 lines>
>> - How to test: <build/test command>
>>
>> 7. Append a record to memory using Bash:
>>    echo "## Coders round - task: <one line>, files: <list>" >> .claude/memory/state.md
>>
>> Do NOT run tests yourself - that is the reviewer's job.
>> Do NOT claim the code works, only that it is written.
>> '@ | Out-File -FilePath .claude\agents\coder.md -Encoding utf8

```

### Step 3: The reviewer agent

The reviewer agent is configured with a PROACTIVELY-triggered description so Claude picks it up automatically after code is written.

```

PS D:\1subagent> '@'
>> ---
>> name: reviewer
>> description: Reviews and verifies code written by the coder agent. Compiles, runs tests, checks for regressions. Use after any code change.
>> tools: Read, Glob, Grep, Bash
>> model: sonnet
>> ---
>>
>> You are the validation agent. You NEVER edit or fix source code. You only verify and report.
>>
>> 4. Tests: run the test suite (npm test / pytest / gradlew.bat test).
>>    All previously passing tests must still pass.
>> 5. Regression check: grep for callers of any changed function/class
>>    signature; verify nothing broke.
>> 6. If no test suite exists, write a temporary test script in the temp
>>    folder, run it, then delete it.
>>
>> Output EXACTLY:
>>
>> ## VERDICT: PASS | FAIL
>>
>> ## BUILD
>> <command + result>
>>
>> ## TESTS
>> <command + counts>
>>
>> ## ISSUES
>> - [high|medium|low] <file:line> - <issue>
>> (empty if none)
>>
>> ## REQUIRED FIXES
>> <numbered list, or "None">
>>
>> FAIL if: build breaks, any previously-passing test fails, or any
>> high-severity issue exists. Be specific with file:line references.
>>
>> After the verdict, append to memory using Bash ONLY (never the Write tool
>> on source files):
>> echo "## Review round - VERDICT: <PASS/FAIL>, issues: <short list>" >> .claude/memory/state.md
>>

```

#### Step 4: Send a coding request to Claude Code

Start Claude Code in the project directory and give it a simple coding task — write a Python script that multiplies two numbers. But before that we will check if the agents exists or not

```
what are the agents available in this project

Ran 4 commands, read 2 files ›

Confirmed — these are project-local agents. Let me read their definitions.

Read 2 files ›

This project (D:\1subagent) defines two custom agents in .claude/agents/:

1. coder — implementation agent. Writes/edits code with minimal diffs, matches existing project style, reads .claude/memory/state.md and learnings.md first to avoid repeating past mistakes, and logs a patch summary + memory entry after each round. Doesn't run tests itself. Tools: Read, Write, Edit, Glob, Grep, Bash.

2. reviewer — validation agent. Never edits code, only verifies: builds the project, runs the test suite, checks for regressions in callers of changed functions, and outputs a strict PASS/FAIL verdict with issues and required fixes. Logs results to memory too. Tools: Read, Glob, Grep, Bash.

Use the coder agent to create calc.py with a function divide(a, b) that returns
/ b. Also create test_calc.py using pytest with these test cases:
- divide(10, 2) == 5
- divide(9, 3) == 3
- divide(5, 0) should return the string "Error: division by zero"

Run the coder, then let the reviewer validate.
```

The above prompt is used and you can see here we have explicitly mentioned here the agent names , thats an way we can specify the agents or we can use @agent\_name also.

#### Step 5: Both agents run in sequence

Claude Code invokes the coder-agent using the Task tool, which produces multiplication.py. As soon as the coder finishes, the reviewer-agent is automatically invoked to review the generated file. This is agent-to-agent communication in its simplest form — no hooks, just proactive sub-agent descriptions.

In the directory D:\subagent, create two files:

1. `calc.py` — a function `divide(a, b)` that returns `a / b`, except when `b == 0`, in which case it returns the string `"Error: division by zero"` (not raise an exception).
2. `test_calc.py` — pytest tests importing `divide` from `calc`, with these exact cases:
  - `divide(10, 2) == 5`
  - `divide(9, 3) == 3`
  - `divide(5, 0) == "Error: division by zero"`

Keep it minimal — no extra features, no extra test cases beyond what's listed. Do not run the tests yourself; that will be handled separately by a reviewer.

Ran 2 commands, created 2 files +17 -0 ▾

Ran a command ▸

Created `calc.py` +4 -0 ▸

Created `test_calc.py` +13 -0 ▸

Ran a command ▸

### Allow Claude to run?

echo "## Review round - VERDICT: PASS, issues: no..."

Claude requested permissions to edit D:\1subagent\claude\memory\state.md which is a sensitive file.

```
echo "## Review round - VERDICT: PASS, issues: none" >>
"D:\1subagent\claude\memory\state.md"
```

The above screenshot shows that the reviewer has reviewed and tested and this going to save it to memory state.

Done. Both files are created and verified:



- `calc.py` — `divide(a, b)` returns `a / b`, or `"Error: division by zero"` when `b == 0`.
- `test_calc.py` — 3 `pytest` cases covering all the specified scenarios.

Reviewer ran `pytest test_calc.py -v`: **3 passed, 0 failed**. No issues found.

The final message.

## Use Case 2 — News Gatherer & Emailer (with hooks + Gmail)

This use case is more advanced. The news-gatherer agent fetches the latest news, and the emailer agent sends that news via Gmail. The two agents are connected using a `SubagentStop` hook — as soon as the news-gatherer finishes, the hook triggers the emailer agent automatically. The emailer uses the Gmail MCP connector to actually send the email.



what are the agents available in this project

just now

Ran a command, read 4 files >

This project defines 4 custom agents in `.claude/agents`:

- **coder** — implementation agent. Reads past review feedback from memory before starting, writes minimal-diff code matching existing style, does not run tests itself, logs a patch summary and appends to `.claude/memory/state.md`.
- **reviewer** — validation-only agent (never edits code). Builds the project, runs tests, checks for regressions, and outputs a strict PASS/FAIL verdict with issues and required fixes.
- **news-gatherer** — pulls today's top 10 AI news stories, verifies each against a trusted-source allowlist (Reuters, AP, Ars Technica, etc.), writes verified stories to `.claude/memory/news_draft.md`.
- **emailer** — takes the verified news draft and composes an email (to kaushikkalita654@gmail.com) with the top stories, saved to `.claude/memory/email_ready.md`.

These look like a pipeline: `news-gatherer` → `emailer` for a news-roundup workflow, and `coder` → `reviewer` for a code change/review loop.

## Part A — Agent definitions

### Step 1: The news-gatherer agent

Configured to fetch the latest news headlines using web search / fetch tools.

```
D: > 1subagent > .claude > agents > news-gatherer.md
1  |--
2  name: news-gatherer
3  description: Gathers today top 10 AI news stories from trusted sources, verifies each, writes them to memory. Use for an AI news roundup.
4  tools: WebSearch, WebFetch, Write
5  model: sonnet
6  ---
7
8  You gather AI news. Steps:
9
10 1. Web search for today AI news. Put the current date in your queries.
11 2. Collect the top 10 distinct stories.
12 3. Verify EACH against a TRUSTED source. Trusted = reuters.com, apnews.com,
13    arstechnica.com, theverge.com, techcrunch.com, wired.com, bloomberg.com,
14    or official company blogs (openai.com, anthropic.com, deepmind.google, etc).
15    Discard anything only on unknown blogs, content farms, or social rumors.
16 4. For each kept story record: headline, 1-2 sentence summary in YOUR OWN words
17    (never copy article text), source name, source URL, VERIFIED: yes/no.
18 5. Write only VERIFIED: yes stories to .claude/memory/news_draft.md as a
19    numbered list. If fewer than 10 verify, keep what is real - do not pad.
20
```

### Step 2: The emailer agent

Configured to send emails through Gmail using the Gmail MCP tools.

Also you need to set the correct mscptool in tools, so i checked what are the available mcp

List the exact names of all Gmail tools you currently have access to

Based on the deferred tools available in this session, the Gmail tools all share the prefix `mcp__263dc852-3a5a-452f-b856-5d30ad89916f__`. Here are the exact names:

1. `mcp__263dc852-3a5a-452f-b856-5d30ad89916f__apply_sensitive_message_label`
2. `mcp__263dc852-3a5a-452f-b856-5d30ad89916f__apply_sensitive_thread_label`
3. `mcp__263dc852-3a5a-452f-b856-5d30ad89916f__create_draft`
4. `mcp__263dc852-3a5a-452f-b856-5d30ad89916f__create_label`
5. `mcp__263dc852-3a5a-452f-b856-5d30ad89916f__get_message`
6. `mcp__263dc852-3a5a-452f-b856-5d30ad89916f__get_thread`
7. `mcp__263dc852-3a5a-452f-b856-5d30ad89916f__label_message`
8. `mcp__263dc852-3a5a-452f-b856-5d30ad89916f__label_thread`
9. `mcp__263dc852-3a5a-452f-b856-5d30ad89916f__list_drafts`
10. `mcp__263dc852-3a5a-452f-b856-5d30ad89916f__list_labels`
11. `mcp__263dc852-3a5a-452f-b856-5d30ad89916f__search_threads`
12. `mcp__263dc852-3a5a-452f-b856-5d30ad89916f__unlabel_message`
13. `mcp__263dc852-3a5a-452f-b856-5d30ad89916f__unlabel_thread`

```
---
name: emailer
description: Reads the verified AI news list and creates a Gmail draft to the user. Use after news-gatherer.
tools: Read, mcp__263dc852-3a5a-452f-b856-5d30ad89916f__create_draft
model: sonnet
---
```

You create the AI news email as a Gmail draft. Steps:

1. Read `.claude/memory/news_draft.md`
2. Keep ONLY stories marked VERIFIED: yes. Drop everything else.
3. If zero verified stories remain, do NOT create a draft - report that instead.
4. If fewer than 10 remain, note that at the top of the body.
5. Create a Gmail draft using the `create_draft` tool:  
To: `kaushikkalita654@gmail.com`  
Subject: Top AI News - `<today date>`  
Body: numbered list, each story with headline, 1-2 line summary in your own words, and the source link.
6. After creating the draft, tell the user the draft is ready in Gmail and how many stories it contains. They open Gmail and click Send.

Do NOT invent stories. Only use verified content from `news_draft.md`.

### Step 3: Both agent files in the project

A combined view of both agent definitions and their system prompts.

## Part B — Wiring the agents with a SubagentStop hook

To make the emailer agent run automatically as soon as the news-gatherer finishes, we register a SubagentStop hook using the `/hooks` command in Claude Code.

### Step 4: Open the hooks configuration

Run the `/hooks` slash command to open the hook configuration menu.

We need to set the hook under `.claude/settings.json`


```
{
```



```
"hooks": {  
  "SubagentStop": [  
    {  
      "matcher": "news-gatherer",  
      "hooks": [  
        {  
          "type": "prompt",  
          "prompt": "The news-gatherer subagent finished. Check if  
.claude/memory/news_draft.md was written and contains at least one VERIFIED:  
yes story. If yes invoke the emailer agent to create a Gmail draft to  
kaushikkalita654@gmail.com. "  
        }  
      ]  
    }  
  ]  
}
```

### Step 5: Next step is to ask the query

So here you can see I have mentioned about the news-gatter agent but not the emailer so the hook will help the emailer agent to call



### Step 6: gathered info now draft of email

Fetching <https://huggingface.co/blog/security-incide...> ▾

Searched web AI news July 22 2026 ▸

Searched web artificial intelligence news today Ju... ▸

Searched web Google Gemini 3.6 Flash Gemini 4 p... ▸

Searched web Microsoft Mistral AI partnership ex... ▸

Searched web OpenAI news July 22 2026 ▸

Searched web Anthropic news July 2026 ▸

Fetches <https://www.bloomberg.com/news/newsli...> ▸


Fetches <https://news.microsoft.com/source/2026...> ▸

Searched web Nvidia AI chip news July 22 2026 ▸

Searched web China AI chip restrictions export J... ▸

Searched web OpenAI models hacked Hugging Fa... ▸

Searched web Sam Altman brief officials next gen... ▸



Thus we can see the top AI news is now saved as draft in mail and you can send it.

## Summary

Both use cases demonstrate working agent-to-agent communication in Claude Code, but through different mechanisms:

**Use Case 1 (Coder + Reviewer):** Relies purely on proactive sub-agent descriptions. The main agent decides on its own to invoke the reviewer after the coder finishes. Simple, no extra infrastructure needed.

**Use Case 2 (News Gatherer + Emailer):** Uses a SubagentStop hook to deterministically chain the two agents, plus the Gmail MCP connector to give the emailer real send-email capability. More setup, but the flow is guaranteed and can integrate with external services.

Together they show two valid patterns for multi-agent workflows: description-driven delegation for lightweight flows, and hook-driven delegation for reliable, external-service-connected flows.