

Day38 - March 14th 2024

1. Started my day at 6 am
2. Cooked food for lunch and packed it in box
3. Headed to library at 8:20am
4. Started solving leetcode questions to improve my logical building skills
5. Learning spark theory from manish kumar

Spark Theory Day2

File Edit View Insert Format Tools Extensions Help

100% Normal text Arial 11 B I U

Associated SQL Query: 7  
Job Group: 4707406643918011608\_6962245675942610428\_4851d5693cc34324856764e05d3  
Completed Stages: 1

Event Timeline  
DAG Visualization

Stage 7

Scan test

WholeStageCodegen

10. Here our first action is read and it is our first job...so it scanning the data and generated a java byte code

11. And our next action is inferSchema...which read our data and gives the schema of our

DeserializeToObject

mapPartitions

mapPartitions

7 of 8

11°C Cloudy


Search

ENG US

10:51 PM 3/14/2024

6. Spark theory day 2 docs :  
[https://docs.google.com/document/d/1thpe8lYbgXfvzfml5s2YG9nZj9\\_HnF9Ck4N2qrHTw2k/edit?usp=sharing](https://docs.google.com/document/d/1thpe8lYbgXfvzfml5s2YG9nZj9_HnF9Ck4N2qrHTw2k/edit?usp=sharing)

## 7. Ended my day by solving a complex SQL from Ankit'YT



SQLQuery1.sql - KAUSHI\SQLEXPRESS:master (KAUSHI\jamka (67)) - Microsoft SQL Server Management Studio

Object Explorer: KAUSHI\SQLEXPRESS (16.0 RTM) - KAUSHI\jamka (67) - master

Query: SQLQuery1.sql - K:\KAUSHI\jamka (67)\\*


```
create table drivers(id varchar(10), start_time time, end_time time, start_loc varchar(10), end_loc varchar(10));
insert into drivers values('dri_1', '09:00', '09:30', 'a', 'b');
insert into drivers values('dri_1', '10:30', '11:00', 'b', 'c');
insert into drivers values('dri_1', '11:00', '11:30', 'c', 'd');
insert into drivers values('dri_1', '12:00', '12:30', 'd', 'e');
insert into drivers values('dri_1', '12:30', '13:00', 'e', 'f');
insert into drivers values('dri_2', '12:15', '12:30', 'f', 'g');
insert into drivers values('dri_2', '13:30', '14:30', 'g', 'h');
```

--Q : Write a query to print total rides and profit rides of each driver  
-- profit ride is when end location of current ride is same as start loc of next ride  
select \* from drivers;

Results: 7 rows

id	start_time	end_time	start_loc	end_loc
dri_1	09:00:00.0000000	09:30:00.0000000	a	b
dri_1	09:30:00.0000000	10:30:00.0000000	b	c
dri_1	11:00:00.0000000	11:30:00.0000000	d	e
dri_1	12:00:00.0000000	12:30:00.0000000	f	g
dri_1	13:30:00.0000000	14:30:00.0000000	c	h
dri_2	12:15:00.0000000	12:30:00.0000000	f	g
dri_2	13:30:00.0000000	14:30:00.0000000	e	h

Query executed successfully.



SQLQuery1.sql - KAUSHI\SQLEXPRESS:master (KAUSHI\jamka (67)) - Microsoft SQL Server Management Studio

Object Explorer: KAUSHI\SQLEXPRESS (16.0 RTM) - KAUSHI\jamka (67) - master

Query: SQLQuery1.sql - K:\KAUSHI\jamka (67)\\*

```
create table drivers(id varchar(10), start_time time, end_time time, start_loc varchar(10), end_loc varchar(10));
insert into drivers values('dri_1', '09:00', '09:30', 'a', 'b');
insert into drivers values('dri_1', '10:30', '11:00', 'b', 'c');
insert into drivers values('dri_1', '11:00', '11:30', 'c', 'd');
insert into drivers values('dri_1', '12:00', '12:30', 'd', 'e');
insert into drivers values('dri_1', '12:30', '13:00', 'e', 'f');
insert into drivers values('dri_2', '12:15', '12:30', 'f', 'g');
insert into drivers values('dri_2', '13:30', '14:30', 'g', 'h');
```

--Q : Write a query to print total rides and profit rides of each driver  
-- profit ride is when end location of current ride is same as start loc of next ride  
select \* from drivers;

with cte as (
select \*, lag(end\_loc, 1) over(partition by id order by end\_time) as prev\_end\_loc
from drivers)
select \* from cte
select id, count(start\_loc) as total\_rides, sum(case when start\_loc = prev\_end\_loc then 1 else 0 end) as profit\_rides
from cte
group by id

/\* Explanation:
Step1 : From the given data we have retrieved prev\_end\_loc using lag(end\_loc, 1) and framed it in a CTE
Step2 : Now from the cte we select count(start\_loc) to get count of total rides
Step3 : When start\_loc = prev\_end\_loc then it is profit ride
Step4 : Next we count the total rides and sum(start\_loc = prev\_end\_loc) to get profit\_rides grouped by id

Results: 2 rows

id	total_rides	profit_rides
dri_1	5	1
dri_2	2	0

Query executed successfully.