

The problem: How do agents use state values in their instructions?

Introduction: Where you are now

Part recap: You learned

- 1 Session state is a dictionary accessible via `session.state`
- 2 `output_key` automatically saves agent responses to state
- 3 You can access state from outside the agent using `session.state.get("key")`

You can now

```
Python
from google.adk.agents import LlmAgent

# Agent that saves its response
agent = LlmAgent(
    instruction="Extract the user's name",
    output_key="user_name"
)

# After running:
session.state["user_name"] contains
the extracted name
```

The next step

Learn how to use those saved values inside agent instructions, making your agents dynamic and context-aware.



The problem:

How do agents use state values in their instructions?

You know how to save data to state, but how do you tell the agent to use that data?

```
Python
from google.adk.agents import LlmAgent

# Imagine state already has user information
# session.state["user_name"] = "Alex"
# session.state["user_language"] = "Spanish"

# How do you tell the agent to USE these values?
agent = LlmAgent(
    instruction="Respond to the user" # ❌ Too generic!
    # How do we say: "Respond to Alex in Spanish"?
)
```

The challenge

You want instructions to adapt based on state values. You want the agent to automatically use “Alex” and “Spanish” without hard-coding them.

What you need

A way to inject `state["user_name"]` and `state["user_language"]` into the instruction automatically.

