

Dr.AMBEDKAR INSTITUTE OF TECHNOLOGY

Approved by AICTE, New Delhi, Affiliated to VTU, Recognized by Govt. of Karnataka
Accredited by NBA

DEPARTMENT OF INFORMATION SCIENCE AND ENGINEERING

FULL STACK WEB DEVELOPMENT(22ISU601)

Module-1: MVC based Web Designing

Full stack web development

Full-stack development refers to development of both the front-end (client-side) and back-end (server-side) components of a web application.

Back-end Development:

Backend Development refers to the server-side development of the web application. It is the part of the application where the server and database reside and the logics is build to perform operations.

- **Model Layer:** Define data models using Django's Object-Relational Mapping (ORM) system. Models represent the structure of the application's data and interact with the database.
- **View Layer:** Implement views, which are Python functions or classes responsible for processing incoming HTTP requests, interacting with the database through models, and returning HTTP responses.
- **Controller (Business Logic):** Django's views act as controllers in the MVC pattern, handling the business logic of the application by processing requests, validating input, and generating responses.
- **URL Routing:** Define URL patterns in the URLconf (URL configuration) to map incoming URLs to views. Django's URL routing mechanism allows for clean and flexible URL patterns.
- **Middleware:** Implement middleware components to process requests and responses at various stages of the Django request/response cycle. Middleware can perform tasks such as authentication, session management, and error handling.

Front-end Development:

Front-end Development is the development or creation of a user interface using some markup languages and other tools. It is basically the development of the user side where only user interaction will be counted.

- **Templates:** Create HTML templates using Django's template engine, which allows for the dynamic generation of HTML content based on data provided by views.
- **Static Files Handling:** Serve static files (e.g., CSS, JavaScript, images) using Django's built-in static files handling capabilities. Static files are typically stored in the project's static directory.
- **Integration with Front-end Frameworks:** Optionally integrate Django with front-end frameworks like React.js, Vue.js, or Angular for building rich, interactive user interfaces. Django can serve as a RESTful API backend while the front-end framework handles the UI rendering and user interactions.

Database Interaction:

Django supports multiple databases including PostgreSQL, MySQL, SQLite, and Oracle. Developers can define database models using Django's ORM and perform database operations such as querying, inserting, updating, and deleting records.

1. What Is a Web Framework?

A web framework often referred to as a web application framework is a pre-built set of libraries, software tools, and best practices that support the overall software development of web apps. It handles multiple routine tasks and provides a structured way to organize code, making development more maintainable and efficient.

Django is a prominent member of a new generation of *Web frameworks*.

For example, here's a simple CGI script, written in Python, that displays the ten most recently published books from a database:

```
#!/usr/bin/python import
```

```
MySQLdb
```

```
print "Content-Type: text/html"
print
print "<html><head><title>Books</title></head>"
print "<body>"
print "<h1>Books</h1>"
print "<ul>"
```

```
connection = MySQLdb.connect(user='me', passwd='letmein', db='my_db')
cursor = connection.cursor()
cursor.execute("SELECT name FROM books ORDER BY pub_date DESC LIMIT
10") for row in cursor.fetchall():
```

```
print "<li>%s</li>" % row[0]
```


```
print "</ul>"
print "</body></html>"
connection.close()
```

In this code First, it prints a “Content-Type” line, followed by a blank line, as required by CGI. It prints some introductory HTML, connects to a database, and executes a query that retrieves the latest ten books. Looping over those books, it generates an HTML unordered list. Finally, it prints the closing HTML and closes the database connection.

The passage discusses the limitations of writing web applications from scratch using basic CGI scripts in Python. It highlights the issues that arise as the application grows more complex, such as code duplication, productivity reduction due to boilerplate code, environment-specific configurations, and the need for separation of concerns between logic and presentation. These challenges are addressed by using web frameworks like Django, which provide a structured programming environment, handle common tasks, and promote clean, maintainable code.

2. The MVC Design Pattern

The MVC design pattern is a software architecture pattern that separates an application into three main components: Model, View, and Controller, making it easier to manage and maintain the codebase. It also allows for the reusability of components and promotes a more modular approach to software development.



The Model-View-Controller (MVC) design pattern is a software architectural pattern commonly used for developing user interfaces. It divides an application into three interconnected components to separate internal representations of information from the ways that information is presented and accepted by the user.

1. **Model:** This represents the application's data and business logic. It is responsible for managing the application's data, responding to queries about the state of the application, and responding to instructions to change the state of the application.
2. **View:** This represents the application's presentation layer. It is responsible for displaying the data provided by the model in a particular format, and for accepting user input and passing it on to the controller.
3. **Controller:** This acts as an intermediary between the model and the view. It listens to user input and invokes the corresponding actions on the model, potentially updating the view as a result. It also handles any input validation and other application logic.

The key benefits of using the MVC pattern include:

- **Separation of Concerns:** Each component focuses on a specific aspect of the application, which makes the codebase easier to understand, maintain, and test.
- **Modularity:** Because each component is separate, it's easier to make changes to one part of the application without affecting the others.
- **Reusability:** Components can be reused in different parts of the application or even in different projects.

Example that demonstrates the difference between the previous approach and that undertaken using a Web framework. Here's how you might write the previous CGI code using Django:

```
# models.py
from django.db import models

class Book(models.Model):
    name = models.CharField(max_length=50)
    pub_date = models.DateField()

# views.py (the business logic)
from django.shortcuts import render
from .models import Book

def latest_books(request):
    book_list = Book.objects.order_by('-pub_date')[:10]
    return render(request, 'latest_books.html', {'book_list': book_list})
```

10. **Internationalization:** Django supports internationalization, making it easy to create applications that can handle multiple languages.
11. **Extensibility:** Django's architecture is highly extensible, allowing developers to plug in third-party or custom modules as needed.

5. Mapping URLs to Views

URL conf in Django serves as a mapping between URL patterns and the corresponding view functions. When you create a new Django project using `django-admin.py startproject`, a file named `urls.py` is automatically generated. This file defines the `urlpatterns` variable, which determines how URLs are routed to view functions.

Key points regarding URLconf:

1. **Basic Structure:** The `urlpatterns` variable is defined within `urls.py`, typically imported from `django.conf.urls.defaults`. It's a list of tuples where each tuple contains a regular expression pattern and the corresponding view function.
2. **Defining URL Patterns:** URL patterns are defined using regular expressions. For example, `(r'^time/$', current_datetime)` maps the URL `/time/` to the `current_datetime` view function. The `r` before the string denotes a raw string in Python, which is useful for regular expressions.
3. **View Functions:** View functions are referenced directly in the URLconf without calling them. This is possible because functions are first-class objects in Python, meaning they can be passed around as variables.
4. **Caret (^) and Dollar Sign (\$):** These symbols are used in regular expressions to denote the start and end of the string, respectively. They ensure that the URL pattern matches the entire URL and not just a portion of it.
5. **Appending Slash:** Django automatically appends a slash to URLs. If a URL pattern expects a trailing slash but is accessed without it, Django redirects the request to the version with the slash. This behavior can be controlled using the `APPEND_SLASH` setting.
6. **Testing Changes:** To test changes made to the URLconf, start the Django development server using `python manage.py runserver`. The server automatically reloads when Python code changes, so there's no need to restart it between modifications.

URLconf is a fundamental part of Django development, allowing developers to define how URLs are mapped to views in their applications. Understanding its structure and functionality is essential for building Django-powered web applications efficiently.

Regular expressions (or *regexes*) are a compact way of specifying patterns in text. While Django URLconfs allow arbitrary regexes for powerful URL-matching capability, you'll probably use only a few regex patterns in practice. Here's a small selection of common patterns:

Symbol	Matches
<u>.</u> (<u>dot</u>)	Any character
<u>\d</u>	<u>Any</u> digit
[A-Z]	Any character, A-Z (uppercase)
[a-z]	<u>Any</u> character, a-z (lowercase)
[A-Za-z]	Any character, a-z (case insensitive)
+	One or more of the previous character (e.g., <u>\d+</u> matches one or more digit)
[^/]+	All characters until a forward slash (excluding the slash itself)
?	Zero or more of the previous character (e.g., <u>\d*</u> matches zero or more digits)
{1,3}	Between one and three (inclusive) of the previous expression

5.1 How Django Processes a Request

Process that happens when you run the Django development server and make requests to web pages:

1. Starting the Server:

- The command `python manage.py runserver` is used to start the Django development server.
- This command imports the `settings.py` file from the same directory, which contains various configuration settings for the Django instance.

2. Settings and URL Configuration:

- One critical setting in `settings.py` is `ROOT_URLCONF`, which tells Django which Python module to use as the URLconf for the website.
- When you use `django-admin.py startproject`, it generates `settings.py` and `urls.py`. The autogenerated `settings.py` file has a `ROOT_URLCONF` that points to the autogenerated `urls.py`.

3. Handling a Request:

- When a request is made, for example to `/time/`, Django loads the URLconf specified by the `ROOT_URLCONF` setting.
- Django then processes the urlpatterns in the URLconf in order. It compares the requested URL with each pattern one by one until it finds a match.
-
- Once a matching pattern is found, Django calls the associated view function, passing an `HttpRequest` object as the first parameter.

4. View Functions and Responses:

- The view function handles the request and is responsible for returning an `HttpResponse` object, which contains the response data for the client.

Key Points

- **Configuration:** `settings.py` and `urls.py` are automatically created when you start a new Django project. `ROOT_URLCONF` in `settings.py` specifies the module to use for URL configuration.
- **URL Matching:** Django processes URL patterns sequentially and uses regular expressions to match the requested URL to a view function.

- **View Handling:** When a URL pattern matches, the corresponding view function is called with an HttpRequest object, and it must return an HttpResponse object.

5.2 How Django Processes a Request

When an HTTP request is received by a Django application, a series of steps involving handlers and middleware takes place before a response is sent back to the client. Here's a summary of this process:

1. Request Handling:

- A server-specific handler constructs an HttpRequest object when a request is received.
- This HttpRequest object is then passed through a series of middleware components.

2. Middleware Processing:

- **Request Middleware:** Middleware in this category can modify the HttpRequest object or provide special handling for certain types of requests. If any request middleware returns an HttpResponse, the process skips the view function.
- **View Middleware:** Similar to request middleware, but it operates just before the view is called. It can also short-circuit the process by returning an HttpResponse.

3. View Execution:

- If no middleware has returned a response, the appropriate view function is called based on the URL routing. The view processes the request and generates an HttpResponse.

4. Exception Handling:

- If the view function raises an exception, control is transferred to the exception middleware.
- **Exception Middleware:** This middleware tries to handle exceptions. If it does not return an HttpResponse, the exception is reraised.
- Django's default views provide user-friendly 404 (not found) and 500 (server error) responses if no custom exception handling is provided.

5. Response Middleware:

- After the view (or exception middleware) generates an HttpResponse, response middleware is applied.
- **Response Middleware:** This is used for any postprocessing of the HttpResponse before it is sent back to the client. It can also be used for cleanup tasks specific to the request.

Key Points

- **HttpRequest Construction:** The initial request object is created by the server-specific handler.
- **Middleware Types:**
 - **Request Middleware:** Enhances or processes the request before it reaches the view.
 - **View Middleware:** Acts just before the view is called, can halt processing by returning a response.
 - **Exception Middleware:** Handles exceptions raised by the view, can provide custom responses.
 - **Response Middleware:** Final processing before the response is sent to the client.
- **Exception Handling:** Ensures that even when errors occur, Django can provide appropriate error messages or fallback responses.

Process Flow

1. **Incoming Request -> Request Middleware -> View Middleware -> View Execution -> Exception Middleware (if needed) -> Response Middleware -> Outgoing Response**

This structured flow ensures that requests are processed efficiently and that various aspects of the request and response can be managed and modified by middleware at appropriate stages.




Figure 3-1. *The complete flow of a Django request and response*

6. URLconfs and Loose Coupling

Django's use of URLconfs is a clear demonstration of the loose coupling principle.

By separating URL definitions from view implementations, Django promotes a flexible and maintainable codebase.

This separation allows developers to make changes in one area (like URLs) without unintended consequences in another (like view logic), leading to more robust and adaptable web applications.

Loose coupling is a software development principle that emphasizes the independence of components. In a loosely coupled system, changes in one component have minimal impact on others, promoting flexibility and maintainability.

URLconfs as an Example of Loose Coupling

In Django, URLconfs exemplify loose coupling. Here's how:

1. **Separate URL Definitions and View Functions:**

- **URL Definitions:** URLs are defined in the `urls.py` file.
- **View Functions:** View functions reside in separate Python modules (e.g., `views.py`).

2. **Independent Modification:**

- **Changing URLs:** You can modify the URL pattern in `urls.py` without altering the view function.
- **Changing View Logic:** You can change the logic in a view function without needing to update the URL configuration.

3. **Multiple URLs for a Single View:**

- You can map multiple URLs to the same view function by adding multiple patterns in `urls.py`.

Benefits of Loose Coupling

1. **Flexibility:** Easily change URLs without impacting view logic and vice versa.
2. **Maintainability:** Simplify updates and refactoring by isolating changes to specific parts of the code.
3. **Reusability:** Reuse view functions across different URLs without duplication.

7. 404 Errors

Django's handling of undefined URLs by displaying a "Page not found" message adheres to its principle of clear and informative error reporting. You can further enhance user experience by creating custom 404 error pages tailored to your application's design. This demonstrates Django's flexibility and commitment to a clean, user-friendly web development framework.




Figure 3-2. Django's 404 page

Django's approach to handling undefined URLs showcases its commitment to clear and informative error reporting. When a request is made to a URL not defined in the URLconf, Django responds with a "Page not found" (404) message. This ensures users are promptly informed when they navigate to a non-existent page, maintaining a user-friendly experience.

Key Points

1. Default 404 Error Handling:

- When a URL is requested that is not mapped in the URLconf, Django displays a default "Page not found" message.
- This behavior ensures that users receive clear feedback when they attempt to access undefined routes.

2. Testing Undefined URLs:

- By running the Django development server and visiting URLs such as `http://127.0.0.1:8000/hello/`, `http://127.0.0.1:8000/does-not-exist/`, or `http://127.0.0.1:8000/`, you can see the default 404 page in action.

3. Customizing the 404 Error Page:

- **Creating a Custom Template:** You can create a custom 404 error page by adding a `404.html` template in your templates directory.
- **Configuring Django:** Ensure that the templates directory is correctly configured in `settings.py`, and set `DEBUG = False` to see the custom error page in a production-like environment.

8. Wildcard URL patterns

Django URLconf to handle dynamic URL patterns using wildcards and implemented a view function that takes parameters extracted from the URL. This functionality allows us to create more flexible and interactive web applications.

1. Defining Dynamic URL Patterns:

- We used regular expressions in our URLconf to capture dynamic parts of the URL. Specifically, we used `\d{1,2}` to match one or two-digit numbers.
- Example of URL patterns:

```
urlpatterns = patterns('',
    (r'^time/$', current_datetime),
    (r'^time/plus/(\d{1,2})/$', hours_ahead),
)
```

2. Capturing URL Data:

- By placing parentheses around parts of the regular expression in the URL pattern, we capture that part of the URL and pass it as a parameter to the view function.
- For instance, `(r'^time/plus/(\d{1,2})/$', hours_ahead)` captures the number in the URL `/time/plus/3/` and passes it to the `hours_ahead` view function.

3. Implementing the View Function:

- The `hours_ahead` view function takes the `offset` parameter, converts it to an integer, and calculates the future time.
- Example view function:

```
from django.http import HttpResponseRedirect
import datetime

def hours_ahead(request, offset):
    offset = int(offset)
    dt = datetime.datetime.now() + datetime.timedelta(hours=offset)
```

```

        html = "<html><body>In %s hour(s), it will be %s.</body></html>"
    % (offset, dt)
    return HttpResponse(html)

```

4. Handling Invalid URLs:

- If a URL does not match any pattern in the URLconf, Django returns a "Page not found" (404) error.
- For example, accessing `/time/plus/100/` should return a 404 error since our URL pattern restricts the offset to one or two digits.

5. Testing the URL Patterns and Views:

- By running the Django development server and visiting various URLs, we can verify that the application behaves as expected.
- URLs like `/time/plus/3/`, `/time/plus/24/` should work, while `/time/plus/100/` should return a 404 error.

6. Complete `views.py` Example:

- The `views.py` file should now contain both the `current_datetime` and `hours_ahead` view functions:

```

from django.http import HttpResponse
import datetime

def current_datetime(request):
    now = datetime.datetime.now()
    html = "<html><body>It is now %s.</body></html>" % now
    return HttpResponse(html)

def hours_ahead(request, offset):
    offset = int(offset)
    dt = datetime.datetime.now() + datetime.timedelta(hours=offset)
    html = "<html><body>In %s hour(s), it will be %s.</body></html>"
    % (offset, dt)
    return HttpResponse(html)

```

Using dynamic URL patterns and capturing URL data in Django allows developers to create more interactive and flexible web applications. By handling different URLs with appropriate view functions and ensuring proper error handling, Django maintains its principles of loose coupling and user-friendly error reporting.

9. Django's Pretty Error Pages

Understanding and utilizing Django's detailed error pages is essential for efficient debugging. The error pages provide comprehensive information, making it easier to identify and resolve issues in your code. However, it's

crucial to ensure these detailed error pages are not exposed in production environments due to the sensitive information they contain.

We intentionally introduced an error into our Django application to explore Django's detailed error pages. Understanding how to interpret these error pages is crucial for debugging and improving your development workflow.

Key Points

1. Deliberately Introducing an Error:

- We commented out a crucial line in the `hours_ahead` view to cause a `TypeError`:

```
def hours_ahead(request, offset):  
    # offset = int(offset)  
    dt = datetime.datetime.now() + datetime.timedelta(hours=offset)  
    html = "<html><body>In %s hour(s), it will be %s.</body></html>"  
    % (offset, dt)  
    return HttpResponse(html)
```

- Visiting `/time/plus/3/` would result in a "unsupported type for timedelta hours component: str" error.

2. Understanding Django's Error Page:

- **Exception Information:** The error page displays the type of exception, a message, the file, and the line number where the exception occurred.
- **Python Traceback:** A detailed traceback similar to Python's standard traceback but more interactive. It includes:
 - File name, function/method name, line number, and source code for each frame in the stack.
 - Ability to click on lines of source code to see surrounding lines for context.
 - "Local vars" link to view local variables and their values at the point where the exception was raised.
- **Copy-and-Paste View:** An option to switch to a view of the traceback that is easier to copy and paste for sharing with others.
- **Request Information:** Details about the incoming request, including GET and POST data, cookies, and meta-information such as CGI headers.

- **Settings Information:** Lists all Django settings for the current installation.

3. Using the Debug Page for Debugging:

- Temporarily inserting an `assert False` statement in your view can trigger the error page, allowing you to inspect local variables and program state without using print statements.
- Example:

```
def hours_ahead(request, offset):
    assert False # Triggers the debug page
    offset = int(offset)
    dt = datetime.datetime.now() + datetime.timedelta(hours=offset)
    html = "<html><body>In %s hour(s), it will be %s.</body></html>"
    % (offset, dt)
    return HttpResponse(html)
```

4. Security Considerations:

- The debug page contains sensitive information about your code and configuration.
- It is only displayed when your Django project is in debug mode to prevent exposure in a production environment.
- Every new Django project starts in debug mode automatically. We'll learn how to deactivate debug mode later.

5. Restoring Functionality:

- After exploring the error page, uncomment the line to fix the view function:

```
def hours_ahead(request, offset):
    offset = int(offset)
    dt = datetime.datetime.now() + datetime.timedelta(hours=offset)
    html = "<html><body>In %s hour(s), it will be %s.</body></html>"
    % (offset, dt)
    return HttpResponse(html)
```


Dr.AMBEDKAR INSTITUTE OF TECHNOLOGY

Approved by AICTE, New Delhi, Affiliated to VTU, Recognized by Govt. of Karnataka
Accredited by NBA

DEPARTMENT OF INFORMATION SCIENCE AND ENGINEERING

FULL STACK WEB DEVELOPMENT(22ISU601)

Module-2: Django Templates and Models

1. Template System Basics

Django templates are used to separate the presentation of a document from its data, primarily for generating HTML but capable of producing any text-based format. Templates include placeholders and basic logic (template tags) to control document display.

Example Template

An example template for an HTML page thanking a customer for an order:

```
<html>
<head>
    <title>Ordering notice</title>
</head>
<body>
    <p>Dear {{ person_name }},</p>
    <p>Thanks for placing an order from {{ company }}. It's scheduled to ship on {{ ship_d
    <p>Here are the items you've ordered:</p>
    <ul>
        {% for item in item_list %}
        <li>{{ item }}</li>
        {% endfor %}
    </ul>
    {% if ordered_warranty %}
    <p>Your warranty information will be included in the packaging.</p>
    {% endif %}
    <p>Sincerely,<br />{{ company }}</p>
</body>
</html>
```

Key Components

1. Variables

- Denoted by double curly braces `{{ }}`.
- Example: `{{ person_name }}` inserts the value of `person_name`.

2. Template Tags

- Enclosed in `{% %}` and perform actions or control logic.
- **For Tag:** `{% for item in item_list %}` loops over each item in `item_list`.
- **If Tag:** `{% if ordered_warranty %}` includes content conditionally based on the value of `ordered_warranty`.
- Supports additional logic like `{% else %}`.

3. Filters

- Modify the display of variables, denoted by a pipe character `|`.
- Example: `{{ ship_date|date:"F j, Y" }}` uses the `date` filter to format `ship_date`.

2. Using Django Template System

Here's a summary of how to use the template system in Python with Django:

1. Create a Template Object:

- **From a string:** You can create a `Template` object by providing the raw template code as a string.
- **From a file:** Django also allows you to create `Template` objects by specifying the path to a template file on the filesystem.

2. Render the Template:

- **Render with context:** Call the `render()` method of the `Template` object, passing a dictionary of variables (context). This will return a fully rendered template as a string, where all the variables and block tags are evaluated based on the provided context.

2.1 Creating Template Objects

Steps to Create and Use a Django Template

1. Start the Django Shell:

- Open your terminal and navigate to your Django project directory.
- Start the interactive interpreter by typing: `python manage.py shell`

2. Create a Template Object:

- Import the `Template` class from the `django.template` module.
- Instantiate a `Template` object with raw template code.

3. Handle Template Syntax Error Exceptions:

- If there are any syntax errors in your template code, Django will raise a `TemplateSyntaxError`.

Example:

Step 1: Start the Django Shell

```
python manage.py shell
```

Step 2: Create a Template Object

```
>>> from django.template import Template
>>> t = Template("My name is {{ name }}.")
>>> print(t)
<django.template.Template object at 0xb7d5f24c>
```

Step 3: Handle TemplateSyntaxError Exceptions

If you try to create a template with invalid syntax, you'll encounter a `TemplateSyntaxError`:

```
>>> t = Template('{% notatag %} ')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
django.template.TemplateSyntaxError: Invalid block tag: 'notatag'
```

2.2 Rendering a Template

Steps for compiling and rendering a Django template using the `Template` and `Context` classes from the `django.template` module.

Steps:

1. Import Required Classes:

- Import the `Template` and `Context` classes from the `django.template` module.

```
>>> from django.template import Template, Context
```

2. Define the Raw Template:

- Create a string that contains your raw template code.

```
>>> raw_template = """<p>Dear {{ person_name }},</p>
... <p>Thanks for ordering {{ product }} from {{ company }}. It's scheduled
... to ship on {{ ship_date|date:"F j, Y" }}.</p>
... {% if ordered_warranty %}
... <p>Your warranty information will be included in the packaging.</p>
... {% endif %}
... <p>Sincerely,<br />{{ company }}</p>"""
```

3. Create a Template Object:

- Instantiate the `Template` class with the raw template string.

```
>>> t = Template(raw_template)
```

4. Create a Context Object:

- Use the `Context` class to create a context with a dictionary mapping variable names to their values.

```
>>> import datetime
>>> c = Context({
...     'person_name': 'John Smith',
...     'product': 'Super Lawn Mower',
...     'company': 'Outdoor Equipment',
...     'ship_date': datetime.date(2009, 4, 2),
...     'ordered_warranty': True
... })
```

5. Render the Template:

- Call the `render()` method on the `Template` object, passing in the `Context` object to get the fully rendered template.

```
>>> rendered_template = t.render(c)
```

6. Print the Rendered Template:

- Use the `print` function to display the rendered template with proper line breaks.

```
>>> print(rendered_template)
```

Example Output:

```
<p>Dear John Smith,</p>

<p>Thanks for ordering Super Lawn Mower from Outdoor Equipment. It's scheduled
to ship on April 2, 2009.</p>

<p>Your warranty information will be included in the packaging.</p>

<p>Sincerely,<br />Outdoor Equipment</p>
```

3.Basic Template Tags and Filters

In Django's templating system, template tags and filters are fundamental constructs used to generate dynamic content in HTML templates.

1. **Template Tags:** These are enclosed within `{% %}` and are used to control the flow of the template or to perform some logic. Here are some common template tags:
 - `if, else, endif`: Conditional statements.
 - `for, empty, endfor`: Looping constructs.
 - `block, endblock, extends`: Used for template inheritance.
 - `include`: Includes the content of another template.
 - `csrf_token`: Renders a CSRF token for form submissions.
 - `url`: Generates URLs for named routes.

Example:

```
{% if user.is_authenticated %}
    Welcome, {{ user.username }}!
{% else %}
    Please log in.
{% endif %}
```

2. **Filters:** Template filters in Django are tools that alter the value of variables before displaying them.

They are applied using a pipe (|) and can be chained together for multiple transformations. Some filters also accept arguments.

Key Concepts:

1. **Basic Filter Usage:**

- Syntax: {{ variable|filter }}
- Example: {{ name|lower }} converts the name variable to lowercase.

2. **Chaining Filters:**

- Multiple filters can be applied in sequence.
- Example: {{ my_text|escape|linebreaks }} first escapes HTML characters and then converts line breaks to <p> tags.

3. **Filters with Arguments:**

- Some filters accept arguments, provided in double quotes.
- Example: {{ bio|truncatewords:"30" }} displays the first 30 words of the bio variable.

Common Filters:

1. **addslashes:**

- Adds a backslash before any backslash, single quote, or double quote.
- Useful for including text in a JavaScript string.
- Example: {{ text|addslashes }}

2. **date:**

- Formats a date or datetime object according to a specified format string.
- Example: {{ pub_date|date:"F j, Y" }} displays the date in "Month day, Year" format.
- Format strings are detailed in Django's documentation and Appendix F.

3. **escape:**

- Escapes ampersands, quotes, and angle brackets, making text safe for XML or XHTML.
- Conversions:
 - & to &
 - < to <

- `>` to `>`;
 - `"` to `"`;
 - `'` to `'`;
 - Example: `{{ user_input|escape }}`
4. **length:**
- Returns the length of a value (string, list, or any object with a `len()` method).
 - Example: `{{ items|length }}`

5. Template Loading

- **Settings File Configuration:** In your Django project's settings file (`settings.py`), you specify the location of your templates using the `TEMPLATE_DIRS` setting. This setting tells Django where to look for template files.
- **Template Directory Structure:** Django expects templates to be stored in a specific directory structure within each app in your project. By default, templates are stored in a directory named `templates` within each app.
- **Using `get_template()`:** To load a template within your views, you can use `django.template.loader.get_template()`. This function takes the name of the template as an argument and returns a compiled `Template` object.
- **Using `render_to_response()`:** Django provides a shortcut, `render_to_response()`, which simplifies the process of loading a template, creating a context, and returning an `HttpResponse` object with the rendered template. This function is often used instead of manually loading templates and creating context objects.
- **Using `locals()`:** You can use the built-in Python function `locals()` to automatically create a context dictionary containing all local variables defined in your view function. This can be useful for passing variables to templates without explicitly defining them in the context.
- **Subdirectories in `get_template()`:** You can organize your templates into subdirectories within the `templates` directory. When using `get_template()`, you specify the template name including the subdirectory path.
- **The `include` Template Tag:** Django provides the `{% include %}` template tag, which allows you to include the contents of another template within your template. This can be useful for reusing common components across multiple templates.

6. Template Inheritance

In Django, to reduce duplication and redundancy across a website, you can use template inheritance. **Server-Side Includes vs. Template Inheritance:** While server-side includes involve embedding one web page inside another using directives, Django's preferred approach is template inheritance. Template inheritance allows you to build a base template containing common parts of your site and define "blocks" that child templates can override.

1. **Base Template:** Start by creating a base template that contains the common structure of your site. This template acts as a skeleton and defines blocks that child templates can fill in. Blocks are defined using the `{% block %}` tag.
2. **Child Templates:** Child templates extend the base template using the `{% extends %}` tag. They override, add to, or leave alone the contents of blocks defined in the base template.
3. **Benefits:** Template inheritance reduces redundancy by allowing each template to contain only the code unique to that template. If you need to make a sitewide design change, you can update the base template, and all child templates will reflect the change.
4. **Tips for Working with Template Inheritance:**
 - `{% extends %}` must be the first template tag in a child template.
 - Use more `{% block %}` tags in base templates for better flexibility.
 - Avoid duplicating code in multiple templates; move it to blocks in parent templates.
 - Use `{{ block.super }}` to access the content of a block from the parent template.
 - Avoid defining multiple `{% block %}` tags with the same name in the same template.
 - The template name passed to `{% extends %}` is loaded using the same method as `get_template()`.
 - You can pass a variable as the argument to `{% extends %}` for dynamic template inheritance.

By following these principles, you can create a more maintainable and DRY (Don't Repeat Yourself) codebase for your Django project.

7. The MVT Development Pattern

In Django's design philosophy, loose coupling and strict separation between application components are encouraged to facilitate easier maintenance and changes. This is achieved by following the Model-View-Controller (MVC) pattern, although in Django's case, it's more accurately described as the Model-Template-View (MTV) pattern.

Here's a summary of how Django's components map to the MVC/MTV pattern:

1. **Model (M):**

- Handles the data access layer.
- Managed by Django's database layer.
- Defines data structure, relationships, access methods, and validation.

2. **Template (T):**

- Represents the presentation layer.
- Determines how data should be displayed on a webpage or document.
- Contains presentation-related decisions.

3. **View (V):**

- Contains the business logic layer.
- Acts as a bridge between models and templates.
- Accesses the model to retrieve data and defers to appropriate templates to present the data.

In Django, the "controller" aspect is handled by the framework itself, following the URLconf and calling the appropriate Python function based on user input. Django views are often mistakenly interpreted as controllers, but they actually fulfill the role of the "view" in the MTV pattern, presenting data to the user.

While Django's interpretation of MVC/MTV may differ from other frameworks like Ruby on Rails, the key is to understand the underlying concepts and how Django's components fulfill their roles in separating concerns and promoting maintainability.

Overall, Django's adherence to the MVC/MTV pattern contributes to its flexibility, scalability, and ease of development for web applications.

8. Configuring the Database

Configuring the database in Django involves specifying settings in the `settings.py` file. Here's a summary of the configuration settings and how to test the configuration:

1. **DATABASE_ENGINE:** Specifies the database engine to use. Must be set to one of the supported values like `'postgresql'`, `'mysql'`, `'sqlite3'`, or `'oracle'`. Corresponding database adapters must be installed.
2. **DATABASE_NAME:** Specifies the name of the database. For SQLite, it's the full filesystem path to the database file. For other databases, it's the name of the database.
3. **DATABASE_USER:** Specifies the username to use when connecting to the database. For SQLite, leave this blank.
4. **DATABASE_PASSWORD:** Specifies the password to use when connecting to the database. Leave blank for SQLite or if there's no password.
5. **DATABASE_HOST:** Specifies the host of the database server. For SQLite or if the database is on localhost, leave this blank.
6. **DATABASE_PORT:** Specifies the port to use when connecting to the database. Leave blank for SQLite or to use the default port for other databases.

To test the database configuration:

- Run `python manage.py shell` from the project directory.
- Import `connection` from `django.db`.
- Create a cursor using `connection.cursor()`.

If there are no errors, the database is configured properly. Otherwise, check for common error messages like missing settings, undefined environment variables, missing database adapter, non-existent database or user, or connection issues.

By following these steps, you can ensure that Django is properly configured to connect to your database, allowing you to interact with it within your Django project.