

19:

1. Create Custom Object

Object Name:

- Product_Inventory__c

Fields:

Field Label	API Name	Data Type
Product Name	Name	Text
Serial No	Serial_No__c	Number
Manufacture Date	Manufacture_Date__c	Date
Expiry Date	Expiry_Date__c	Date

2. Apex Controller

Create Apex Class: ProductInventoryController

```
public class ProductInventoryController {

    public Product_Inventory__c product {get; set;}
    public List<Product_Inventory__c> productList {get; set;}

    // Constructor
    public ProductInventoryController() {

        product = new Product_Inventory__c();

        productList = [
            SELECT Id,
                Name,
                Serial_No__c,
                Manufacture_Date__c,
                Expiry_Date__c
            FROM Product_Inventory__c
        ];
    }

    // Add Product
    public PageReference saveProduct() {

        insert product;

        product = new Product_Inventory__c();
```

```

productList = [
    SELECT Id,
        Name,
        Serial_No__c,
        Manufacture_Date__c,
        Expiry_Date__c
    FROM Product_Inventory__c
];

return null;
}

// Delete Product
public void deleteProduct() {

    String productId =
        ApexPages.currentPage().getParameters().get('pid');

    Product_Inventory__c p =
        [SELECT Id
        FROM Product_Inventory__c
        WHERE Id = :productId];

    delete p;

    productList = [
        SELECT Id,
            Name,
            Serial_No__c,
            Manufacture_Date__c,
            Expiry_Date__c
        FROM Product_Inventory__c
    ];
}
}

```

3. Visualforce Page

Create Visualforce Page:
ProductInventoryPage

<apex:page controller="ProductInventoryController">

<apex:form >

<h1>Product Inventory Management</h1>

```
<apex:pageBlock title="Add Product">

    <apex:pageBlockSection columns="1">

        <apex:inputField value="{!product.Name}"/>

        <apex:inputField value="{!product.Serial_No__c}"/>

        <apex:inputField value="{!product.Manufacture_Date__c}"/>

        <apex:inputField value="{!product.Expiry_Date__c}"/>

    </apex:pageBlockSection>

    <apex:commandButton value="Save"
        action="{!saveProduct}"/>

</apex:pageBlock>

<br/>

<apex:pageBlock title="Product List">

    <apex:pageBlockTable value="{!productList}"
        var="p">

        <apex:column value="{!p.Name}"
            headerValue="Product Name"/>

        <apex:column value="{!p.Serial_No__c}"
            headerValue="Serial No"/>

        <apex:column value="{!p.Manufacture_Date__c}"
            headerValue="Manufacture Date"/>

        <apex:column value="{!p.Expiry_Date__c}"
            headerValue="Expiry Date"/>

        <apex:column headerValue="Action">

            <apex:commandLink value="Delete"
                action="{!deleteProduct}">

                <apex:param name="pid"
                    value="{!p.Id}"/>

            </apex:commandLink>

        </apex:column>

    </apex:pageBlockTable>

</apex:pageBlock>
```

</apex:column>

</apex:pageBlockTable>

</apex:pageBlock>

</apex:form>

</apex:page>

Viva Questions

- What is Visualforce?
- What is Apex Controller?
- Difference between Standard and Custom Controller?
- What is PageReference?
- What is <apex:form>?
- What is <apex:pageBlockTable>?
- Why use return null?
- What is SOQL?